District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.
For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action:  Below grade tank registration  Permit of a pit or proposed alternative method  Closure of a pit, below-grade tank, or proposed alternative method  Modification to an existing permit/or registration  Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
5-20738 Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinal
1. Operator: RP America Production Company OCRID #1 778
Operator: BP America Production Company OGRID#: 778  Address:200 Energy Court, Farmington, NM 87401 OIL CONS. DIV DIST. 3
Facility or well name:Pritchard 5
API Number:3004520738 OCD Permit Number:
U/L or Qtr/Qtr B Section 34 Township 31N Range 9W County: San Juan
Center of Proposed Design: Latitude36.858556
Surface Owner: ☑ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no
☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: Lx Wx D
3.
■ Below-grade tank: Subsection 1 of 19.15.17.11 NMAC        Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
Secondary containment with leak detection   Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Single walled/single bottomed, side walls not visible
Liner type: Thicknessmil

Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

5.  Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school	, hospital,
institution or church)  Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	•
8.	
<u>Variances and Exceptions</u> :  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	
Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	•
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC	
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. ( <b>Does not apply to below grade tanks</b> )  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks)	Yes No
- FEMA map	
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured	
from the ordinary high-water mark).	Yes No
- Topographic map; Visual inspection (certification) of the proposed site	
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	Yes No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.  Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9	cuments are
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II.  Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	cuments are
□ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC □ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC   Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC   Climatological Factors Assessment   Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC   Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC   Quality Control/Quality Assurance Construction and Installation Plan   Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC   Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan   Emergency Response Plan   Oil Field Waste Stream Characterization   Monitoring and Inspection Plan   Erosion Control Plan   Erosion Control Plan   Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC   Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit
☐ Alternative  Proposed Closure Method: ☐ Waste Excavation and Removal ☐ Waste Removal (Closed-loop systems only) ☐ On-site Closure Method (Only for temporary pits and closed-loop systems) ☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached.  □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS, Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	D V D N
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
<ul> <li>Within an unstable area.</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	
Within a 100-year floodplain.	☐ Yes ☐ No
- FEMA map	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	II NMAC 15.17.11 NMAC
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature:  OCD Permit Number:	20H
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date:5/29/2014	
20.  Closure Method:  Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo ☐ If different from approved plan, please explain.	op systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please into mark in the box, that the documents are attached.  Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude 36.858556 Longitude -107.76466 NAD:	

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure repbelief. I also certify that the closure complies with all applicable closure requirements.	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Jeff Peace	Date:July 18, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

### BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

### BELOW-GRADE TANK CLOSURE PLAN

# Pritchard 5 API No. 3004520738 Unit Letter B, Section 34, T31N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

### General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
  - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
  - Notice is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and BTEX, TPH and chloride were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.

    Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District 1
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011
Submit 1 Copy to appropriate District Office in

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	catio	n and Co	orrective A	ction	·			
	•					OPERA'	ГOR		] Initia	al Report	$\boxtimes$	Final Repor
Name of Co	mpany: B	P				Contact: Jeff Peace						
Address: 20	0 Energy	Court, Farmi	ngton, N	M 87401		Telephone 1	No.: 505-326 <b>-</b> 94	179				
Facility Nar	ne: Pritcha	ard 5				Facility Typ	e: Natural gas v	well				
Surface Owner: Federal Mineral Owne						Federal			API No	. 30045207	738	
LOCATION O							LEASE					
Unit Letter	Section	Township	Range	Feet from the		/South Line	Feet from the	East/Wes	et Line	County: S	an Juar	<u> </u>
B	34	31N	9W	1,190	North		1,650	East	St Line	County. 5	an sua	1
		Lati	tude36	5.858556		Longitud	le107.76466_				-	
				NAT	'URE	OF REL	EASE					
Type of Rele	ase: none						Release: N/A	V	olume R	Recovered: N	N/A	
Source of Re	lease: belov	v grade tank –	95 bbl				lour of Occurrenc	e: D	ate and	Hour of Dis	covery	: N/A
Was Immedia	nte Notice C	Given?				N/A If YES, To	Whom?			·· -		
			Yes [	No 🖾 Not Re	equired							
By Whom?						Date and I						
Was a Water	course Reac		Yes 🗵	] No		If YES, Volume Impacting the Watercourse.						
If a Watercou	rse was Im	pacted, Descri	ibe Fully.*	k		1						
				n Taken.* Sampli and chlorides belo					removal t	o ensure no	soil in	ipacts from
				ten.* BGT was re active well area.	moved	and the area u	nderneath the BG	T was sam	ipled. Th	ne excavated	d area v	vas
regulations al public health should their o	l operators or the envir perations h ment. In a	are required to conment. The ave failed to a ddition, NMO	o report ar acceptance adequately ICD accep	is true and comp ad/or file certain r se of a C-141 repo investigate and r stance of a C-141	elease n ort by th emediat	notifications and le NMOCD m te contaminati	nd perform correct arked as "Final R on that pose a thr	ctive action eport" does eat to grou	s for rele s not reli nd water	eases which eve the oper s, surface wa	may er ator of ter, hu	ndanger Fliability man health
Signature:	off P.	eace					OIL CON	SERVA <sup>*</sup>	TION	DIVISIC	<u>N</u>	
Printed Name	Jeff Peace					Approved by	Environmental S	pecialist:				
Title: Area E	vironment	al Advisor				Approval Da	te:	Exp	piration I	Date:	<u></u>	
E-mail Addre	ss: peace.je	ffrey@bp.cor	n			Conditions of	f Approval:		Attached			

Phone: 505-326-9479

Date: July 18, 2014 Pho
\* Attach Additional Sheets If Necessary

CLIENT: BP	L	NGINEERING, INC. BLOOMFIELD, NM 87413		7 ( 1 n	520738
	(50	05) 632-1199		TANK ID (if applicble):	<u> </u>
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OTHER:		PAGE #: <b>1</b>	of <u>1</u>
SITE INFORMATION		HARD # 5		DATE STARTED:	05/20/14
	31N RNG: 9W PM		<u>IM</u>	DATE FINISHED:	
1/4-1/4/FOOTAGE: 1,190'N / 1,6		TYPE: FEDERAL / STATE / FEE / INDI.		ENVIRONMENTAL	IOD
		ONTRACTOR: MBF - B. SCHUMAN			JCB
REFERENCE POINT	: WELL HEAD (W.H.) GPS	S COORD.: 36.85883 X 107.7			
,	GPS COORD.: 36				34', S22E
2)				RING FROM W.H.:	
3)		DIST		RING FROM W.H.:	
SAMPLING DATA:		OR LAB USED: HALL	- ANCE/BEAR	KING PROM W.n	OVM READING
		D/14 SAMPLETIME: 1603 LABANALYSIS: 4	10 1/0	015D/9021D/200 0	(ppm)
		SAMPLETIME: LAB ANALYSIS:			(01) 0.0
		SAMPLETIME: LAB ANALYSIS:			
		SAMPLE TIME: LAB ANALYSIS: _			
		SILT / SILTY CLAY / CLAY / GRAVEL / OTHER			
	ATE BROWN	PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLA	ASTIC / CC	OHESIVE / MEDIUM PLASTIC	/ HIGHLY PLASTIC
COHESION (ALL OTHERS): NON COHESIVE (SLIGHTL)		,			RD
CONSISTENCY (NON COHESIVE SOILS): LO		HC ODOR DETECTED: YES NO EXPLANATION		<del></del>	
SAMPLE TYPE: GRAB (COMPOSITE) #	OF PTS	ANY AREAS DISPLAYING WETNESS: YES NO	EXPLAN	IATION -	
DISCOLORATION/STAINING OBSERVED: YES	<del></del>				
SITE OBSERVATION  APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: [ OTHER:	D AND/OR OCCURRED : YES NO EXP	Lanation:			
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA	ft. X NA ft. EXCAVATION	ON EST	IMATION (Cubic Yards)	: NA
	EAREST WATER SOURCE: >1,000			D TPH CLOSURE STD:	
SITE SKETCH	BGT Located: off on si	te PLOT PLAN circle: attached	OWO	CALIB. READ. = <b>52.1</b>	ppm   RE =0.52
OFFICIAL			. I	CALIB. GAS = 100	ppm RF =0.52
SEPARATOR>	\	/ WASH CHANNEL	TIME:	<b>5:40</b>	05/20/14
$\sqrt{\begin{pmatrix} x \\ x \\ x \end{pmatrix}}$	4		<u>'</u>	MISCELL. N	IOTES
BERM	PBGTL T.B. ~ 6'		w	o: <b>N15445</b> 9	970
	B.G.			O#:	
,				K: USE <b>ZEVH01</b>	
				J#: <b>Z2-0060</b> ermit date(s): <b>06</b>	3/14/10
,				CD Appr. date(s): 03	
			Tan ID	k OVM = Organic Vap ppm = parts per mil	or Meter Ilion
	то \		A	BGT Sidewalls Visible:	
	W.H. 🔪	X - S.P.[		BGT Sidewalls Visible:	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION; T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW-SINGL	OW-GRADE TANK LOCATION; SPD = SAMPLE	3ELOW; T.H. = TEST HOLE; ~ = APPROX.; W.H. = WELL HEA POINT DESIGNATION; R.W. = RETAINING WALL; NA - NOT TTOM; DB - DOUBLE BOTTOM.	D;   <u>M</u>	BGT Sidewalls Visible: agnetic declination:	
NOTES:		ONSITE: 05/20/14			

### **Analytical Report**

### Lab Order 1405977

Date Reported: 5/29/2014

# Hall Environmental Analysis Laboratory, Inc.

**CLIENT:** Blagg Engineering

Project:

Lab ID:

Pritchard 5 1405977-001 Matrix: SOIL Client Sample ID: 95 BGT 5-pt @ 6'

Collection Date: 5/20/2014 4:03:00 PM

Received Date: 5/22/2014 10:00:00 AM

RL Qual Units **Analyses** Result DF Date Analyzed Batch

	resure	ne ço	ini emis	υ,	Date Many Zea	Daten
EPA METHOD 8015D: DIESEL RANG	GE ORGANICS				Analyst	:: BCN
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	5/23/2014 6:57:05 PM	13321
Surr: DNOP	79.7	57.9-140	%REC	1	5/23/2014 6:57:05 PM	13321
EPA METHOD 8015D: GASOLINE R	ANGE				Analyst	:: NSB
Gasoline Range Organics (GRO)	ND	4.6	mg/Kg	1	5/23/2014 10:37:40 PM	13319
Surr: BFB	84.6	. 80-120	%REC	1	5/23/2014 10:37:40 PM	13319
EPA METHOD 8021B: VOLATILES					Analyst	: NSB
Benzene	ND	0.046	mg/Kg	1	5/23/2014 10:37:40 PM	13319
Toluene	ND	0.046	mg/Kg	1	5/23/2014 10:37:40 PM	13319
Ethylbenzene	ND	0.046	mg/Kg	1	5/23/2014 10:37:40 PM	13319
Xylenes, Total	ND	0.093	mg/Kg	1	5/23/2014 10:37:40 PM	13319
Surr: 4-Bromofluorobenzene	99.0	80-120	%REC	·1	5/23/2014 10:37:40 PM	13319
EPA METHOD 300.0: ANIONS					Analyst	JRR
Chloride	ND	30	mg/Kg	20	5/23/2014 5:44:57 PM	13335
EPA METHOD 418.1: TPH					Analyst	JME
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	5/27/2014 12:00:00 PM	13322

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- 0 RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits
- В Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit

Page 1 of 6

- Sample pH greater than 2.
- Reporting Detection Limit

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1405977 29-May-14

Client:

Blagg Engineering

Project:

Pritchard 5

Sample ID MB-13335

SampType: MBLK

TestCode: EPA Method 300.0: Anions

LowLimit

Client ID: PBS

Batch ID: 13335

RunNo: 18847

Prep Date: 5/23/2014 Analysis Date: 5/23/2014

SeqNo: 544228

%REC

Units: mg/Kg

HighLimit

%RPD **RPDLimit** Qual

Analyte Chloride

Result **PQL** ND 1.5

Sample ID LCS-13335

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID:

LCSS

5/23/2014

RunNo: 18847

Units: mg/Kg

Prep Date: Analyte

Batch ID: 13335 Analysis Date: 5/23/2014

SeqNo: 544229

SPK value SPK Ref Val %REC LowLimit

**RPDLimit** 

Result PQL

15.00

SPK value SPK Ref Val

HighLimit

%RPD

Qual

Chloride

1.5

90

110

14 95.2

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range Е

Analyte detected below quantitation limits

0 RSD is greater than RSDlimit

RPD outside accepted recovery limits R

Spike Recovery outside accepted recovery limits

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Reporting Detection Limit

Sample pH greater than 2.

RL

Page 2 of 6

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1405977

29-May-14

Client:

Blagg Engineering

Project:

Pritchard 5

Sample ID MB-13322	SampType: MBLK			TestCode: EPA Method 418.1: TPH						
Client ID: PBS	Batch II	D: <b>133</b>	322	F	RunNo: 1	8817				
Prep Date: 5/22/2014	Analysis Date	e: <b>5/2</b>	23/2014	8	SeqNo: <b>5</b> 4	43363	Units: mg/k	(g		
Analyte	Result F	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Petroleum Hydrocarbons, TR	ND	20								
Sample ID LCS-13322	SampType	e: LC:	s	Tes	tCode: <b>EF</b>	PA Method	418.1: TPH			
Sample ID LCS-13322 Client ID: LCSS	SampType Batch ID				tCode: <b>Ef</b> RunNo: <b>1</b>		418.1: TPH			
1		⊃: <b>133</b>		F		8817	<b>418.1: TPH</b> Units: <b>mg/</b> F	(g		
Client ID: LCSS	Batch ID Analysis Date	⊃: <b>133</b> e: <b>5/2</b>	322 23/2014	F	RunNo: 18	8817		<b>(g</b> %RPD	RPDLimit	Qual

Sample ID LCSD-13322	SampType: LCSD TestCode: EPA Method 4				418.1: TPH				
Client ID: LCSS02	Batch ID:	13322	F	RunNo: 1	8817				
Prep Date: 5/22/2014	Analysis Date:	5/23/2014	5	SeqNo: 5	43365	Units: mg/K	g	-	
Analyte	Result PC	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Petroleum Hydrocarbons, TR	110	20 100.0	0	110	80	120	12.4	20	-

### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 3 of 6

# Hall Environmental Analysis Laboratory, Inc.

WO#: 1405977

29-May-14

Client:

Blagg Engineering

Project:

Pritchard 5

Sample ID MB-13321	SampT	ype: <b>M</b> E	BLK	TestCode: EPA Method 8015D: Diesel Range Organics											
Client ID: PBS	Batch	n ID: 13	321	F	RunNo: 1	8820									
Prep Date: 5/22/2014	Analysis D	ate: <b>5</b> /	23/2014	SeqNo: <b>543460</b> L			Units: mg/Kg								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Diesel Range Organics (DRO) Surr: DNOP	ND 9.5	10	10.00		95.1	57.9	140								
Sample ID LCS-13321	SampT	ype: LC	s	Tes	tCode: El	PA Method	8015D: Dies	el Range (	Organics						
Client ID: LCSS	Batch	n ID: 13	321	F	RunNo: 1	8820									
Prep Date: 5/22/2014	Analysis D	ate: <b>5/</b>	23/2014	SeqNo: <b>543509</b>		Units: mg/k	(g								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Diesel Range Organics (DRO)	47	10	50.00	0	93.6	60.8	145								
Surr: DNOP	4.7		5,000		94.3	57.9	140								

### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Ē Value above quantitation range
- Analyte detected below quantitation limits
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- Not Detected at the Reporting Limit ND

Page 4 of 6

Sample pH greater than 2.

Reporting Detection Limit

# Hall Environmental Analysis Laboratory, Inc.

WO#: 1405977

29-May-14

Client:

Blagg Engineering

Project:

Pritchard 5

Sample ID MB-13319	Samp	Гуре: МЕ	BLK	TestCode: EPA Method 8015D: Gasoline Range										
Client ID: PBS	Batc	h ID: 13	319	F	RunNo: 1	8829								
rep Date: 5/22/2014 Analysis Date: 5/23/2014			\$	SeqNo: 5	43975	Units: mg/Kg								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Gasoline Range Organics (GRO)	ND	5.0												
Surr: BFB	810		1000		81.3	80	120							

Sample ID LCS-13319	Samp	Гуре: <b>LC</b>	S	Tes	oline Rang	je				
Client ID: LCSS	319	F								
Prep Date: 5/22/2014	Analysis Date: 5/23/2014			SeqNo: <b>543976</b>			Units: mg/h			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	20	5.0	25.00	0	80.0	71.7	134			
Surr: BFB	890		1000		88.7	80	120			

### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 5 of 6

# Hall Environmental Analysis Laboratory, Inc.

1.0

1.000

WO#: **1405977** 

29-May-14

Client:

Blagg Engineering

Project:

Pritchard 5

Sample ID MB-13319	Samn	Type: ME	RI K	Tes		·····				
•	•	•					8021B: Volat	illes		
Client ID: PBS	Batcl	h ID: 13	319	F	RunNo: 1	8829				
Prep Date: 5/22/2014	2/2014 Analysis Date: 5/23/2014 SeqNo: 544018		44018	Units: mg/K	(g					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Quạl
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Kylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.95		1.000		94.8	80	120			
Sample ID LCS-13319	Samp1	Type: <b>LC</b>	s	Tes	tiles					
Client ID: LCSS	Batcl	h ID: <b>13</b>	319	F	RunNo: 1	8829				
Prep Date: 5/22/2014	Analysis D	Date: <b>5</b> /	23/2014	9	SeqNo: 5	44019	Units: mg/K	ζg		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.050	1.000	0	109	80	120			
Toluene	1.0	0.050	1.000	0	99.5	80	120		•	
		0.050	4 000	^	00.4	00	400			
Ethylbenzene	0.99	0.050	1.000	0	99.1	80	120			

102

80

120

### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range

Surr: 4-Bromoffuorobenzene

- J Analyte detected below quantitation limits
- O RSD is greater than RSDImit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 6



riau Environmeniai Anaiysis Laboraiory 4901 Hawkins NE Albuquerque, NM 87105

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

# Sample Log-In Check List

Client Name: BLAGG Work Order Nu	mber: 1405977		RcptNo:	1
Received by/date: 05 02/1/5				
Logged By: Lindsay Mangin 5/22/2014 10:00:0	00 AM	July Hayo		•
Completed By: Lindsay Mangin 5/22/2014 1:13:20	D PM	Janey Hleggo		
Reviewed By: CS oskuly				
Chain of Custody				
1. Custody seals intact on sample bottles?	Yes 🗌	No 🗌	Not Present	
2. Is Chain of Custody complete?	Yes 🗹	No 🗌	Not Present	•
3. How was the sample delivered?	Client			
<u>Log In</u>				
4. Was an attempt made to cool the samples?	Yes 🗹	No 🗌	NA 🗆 .	
5. Were all samples received at a temperature of >0° C to 6.0°C	Yes 🗹	No 🗌	NA 🗆	
6. Sample(s) in proper container(s)?	Yes 🗸	No 🗌		
7. Sufficient sample volume for indicated test(s)?	Yes 🗹	No 🗌		
8. Are samples (except VOA and ONG) properly preserved?	Yes 🗹	No 🗌	•	•
9. Was preservative added to bottles?	Yes 🗌	No 🗹	NA 🗀	
10.VOA vials have zero headspace?	Yes 🗌	No 🗆	No VOA Vials 🗹	
11. Were any sample containers received broken?	Yes	No 🗹	# of	
			# of preserved bottles checked	•
12.Does paperwork match bottle labels? (Note discrepancies on chain of custody)	Yes 🗹	No 📙	for pH:	>12 unless noted)
13. Are matrices correctly identified on Chain of Custody?	Yes 🗹	No 🗆	Adjusted?	
14. Is it clear what analyses were requested?	Yes 🗹	No 🗆		
15. Were all holding times able to be met?	Yes 🗹	No 🗆	Checked by:	
(If no, notify customer for authorization.)			-	
Special Handling (if applicable)	•			
16. Was client notified of all discrepancies with this order?	Yes 🗌	No 🗌	NA 🗹	•
Person Notified: Da	ite:			
By Whom: Via	a: 🗌 eMail 🔲 P	hone  Fax	☐ In Person	
Regarding:	1Acrosi de la Francisca de la Constantina del Constantina de la Co			
Client Instructions:		W. Sain - C. Siin	e et la companya de l	
17. Additional remarks:				
18. Cooler Information  Cooler No Temp °C Condition Seal Intact Seal No. 1.1 Good Not Present	Seal Date	Signed By:		

Client:	Blagg Engi	neering, In	c.	Standard				] ]				IVI IS I							
	BP America			Project Name:								www	/.halle	enviro	nmer	ital.co	om		
Mailing Add	Mailing Address: P.O. Box 87			Pritchard 5				www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109											
			eld, NM 87413	Project #:	***************************************			7			505-345-3975			Fax 505-345-4107					
Phone #:		(505)320	0-1183	1				26						is Re					
email or Fax	c#:			Project Mana	iger:														T
QA/QC Pack	-		☐ Level 4 (Full Validation		Jeff Blagg					6									
			•	Sampler:	Jeff Blagg		······································	-		(GRO / DRO)				-					
☐ Other	pe)				✓ Yes	□ No		8		õ								Ì	Z
(,,	F*/			Sample Temperature:						9					1	1 1			٤ ا
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL	No:	BTEX (8021)		TPH 8015B	TPH 418.1							Chloride	Air Bubbles (Y or N)
05/20/2014	16:03	Soil	95 BGT 5-pt @ 6'	1x 4oz	cool	-6	$\overline{\alpha}$	x	$\dashv$	×	х							x	1
		1						1-1						+	_	<del>                                     </del>	$\dashv$	-	+
<del></del>						<b> </b>		╁╼╅				-	-		+-	-	-	-	
· · · · · · · · · · · · · · · · · · ·								╁╌┼					$\dashv$	+	+		-+	+	<del></del>
		_					<del></del>	-				-			╅—				
	<del>                                     </del>			<u> </u>				1-1			_	-	-		┷	-			
	<u> </u>		<u> </u>					1 1			_		_				_		
						<u> </u>						$\Box$							
						20° 24.								_L					
				- C									•						
Date:	Time:	Relinquished by:		Received by:	`	Date 5	Time	Rem							_				
21/2014	820	2-11 Bley		Winter Waller 52/2014 820			Payl						Ples	250 00	nv re	eulte	-to:	ļ	
Date:	Time:	Relinquished by:		Received by: Date Time				BP Contact: Jeff Peace Please copy results to peace.jeffrey@bp.com											
If ne	<u> </u>	s submitted to H	Hall Environmental may be subcontract	ed to other accredite	<del></del>	119/1-1	1600 of this possit	bility. An	y sub-	contra	acted d	ata wi	l be cle	arly nota	ated on	the anal	ytical n	aport.	



**IBP America Production Company** :200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

April 7, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

### VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a bellow grade tank

Well Name: PRITCHARD 005

API#: 3004520738

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about May 15, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the bellow grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper Surface Land Negotiator

9D Va Riz

**BP America Production Company** 

### **BP America Production Company**

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

April 10, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

PRITCHARD 005 API 30-045-20738 (G) Section 34 – T31N – R09W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



