District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

7

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.
For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

1220 S. St. Francis Dr., Santa Fe, NM 8/505	Santa Fe, NM 87505	to the appropriate NMOCD District Office.
Proposed Alternative	., Below-Grade Tank, or Method Permit or Closure	Plan Application
Closure of a pit, b Modification to a	n existing permittor registration	tive method or non-permitted pit, below-grade tank,
Instructions: Please submit one application	on (Form C-144) per individual pit, belov	v-grade tank or alternative request
Please be advised that approval of this request does not relieve the environment. Nor does approval relieve the operator of its respons	operator of liability should operations result ibility to comply with any other applicable g	in pollution of surface water, ground water or the governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company	OGRID #:	OIL CONS. DIV DIST. 3
Facility or well name:Barrett LS 4		
API Number:3004510598		
U/L or Qtr/QtrA Section20 Towns	ship31N Range9W	County:San Juan
Center of Proposed Design: Latitude36.887555	Longitude107.79895_	NAD: □1927 ⊠ 1983
Surface Owner: ☐ Federal ☐ State ☐ Private ☐ Tribal Tru	st or Indian Allotment	
2.		
☐ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: ☐ Drilling ☐ Workover		
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Mu	· ulti-Well Fluid Management I	ow Chloride Drilling Fluid □ ves □ no
Lined Unlined Liner type: Thicknessmi		
☐ String-Reinforced		
Liner Seams:	Volume:bt	ol Dimensions: Lx Wx D
3.		
Below-grade tank: Subsection I of 19.15.17.11 NMAC	Tank A	
Volume:95.0bbl Type of fluid: _	Produced water	
Tank Construction material:Steel		
☐ Secondary containment with leak detection ☐ Visible si	idewalls, liner, 6-inch lift and automatic o	verflow shut-off
$\ \ \square$ Visible sidewalls and liner $\ \square$ Visible sidewalls only $\ \boxtimes$	Other _Single walled/single botto	omed; side walls not visible
Liner type: Thicknessmil		
4. Alternative Method:		

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	•
6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
s. Variances and Exceptions:	
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Uariance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acce,	ptable source
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	
General siting	·
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.	☐ Yes ☐ No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes☐ No☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.	Yes No
NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)	Yes No
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below grade tanks)	
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain. (Does not apply to below grade tanks)	☐ Yes ☐ No
- FEMA map	
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).	☐ Yes ☐ No
- Topographic map; Visual inspection (certification) of the proposed site	
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;	☐ Yes ☐ No
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No					
application Visual inspection (certification) of the proposed site; Aerial photo; Satellite image						
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No					
Temporary Pit Non-low chloride drilling fluid						
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No					
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No					
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Permanent Pit or Multi-Well Fluid Management Pit						
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image						
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site						
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No					
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9	ruments are					
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC					
Previously Approved Design (attach copy of design) API Number: or Permit Number:						
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	uments are					
 □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC 	15.17.9 NMAC					
☐ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC						
Previously Approved Design (attach copy of design) API Number: or Permit Number:						

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	
Within a 100-year floodplain FEMA map	Yes ☐ NoYes ☐ No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17.	
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address:Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: OCD Permit Number:	JON 4
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 6/11/2014	
Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-loc If different from approved plan, please explain.	op systems only)
21. <u>Closure Report Attachment Checklist</u> : Instructions: Each of the following items must be attached to the closure report. Please incommark in the box, that the documents are attached.	dicate, by a check

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this belief. I also certify that the closure complies with all applicable closure	closure report is true, accurate and complete to the best of my knowledge and requirements and conditions specified in the approved closure plan.
Name (Print):Jeff_Peace	Title: Area Environmental Advisor
Signature: Jaff Peace	Date:August 4, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Barrett LS 4 API No. 3004510598 Unit Letter A, Section 20, T31N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B.	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141** is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notifi	catio	n and Co	orrective A	ction		·		
		•				OPERA'	ГOR		☐ Initia	al Report	Final Rep	
Name of Co	ompany: B	3P				Contact: Jeff Peace						
Address: 20	00 Energy	Court, Farm	ington, N	M 87401		Telephone 1	No.: 505-326-94	179				
Facility Na	me: Barret	t LS 4				Facility Typ	oe: Natural gas v	well				
Surface Ow	ner: Feder	ral		Mineral (Owner:	Federal			API No	. 300451059	8	
				LOCA	ATIO	N OF RE	LEASE					
Unit Letter A	Section 20	Township 31N	Range 9W	Feet from the 1,190	North North	/South Line	Feet from the 1,190	East/V East	Vest Line	County: San	Juan	
		Lati	tude36	5.887555		Longitud	le107.79895_					
				NAT	TURE	OF REL						
Type of Rele							Release: N/A			Recovered: N/A		
Source of Re	Source of Release: below grade tank – 95 bbl						lour of Occurrence	ce:	Date and	Hour of Disco	very: N/A	
Was Immedi	Was Immediate Notice Given?					N/A If YES, To	Whom?	t				
			Yes [] No 🛛 Not R	equired							
By Whom?						Date and I-						
Was a Water	Was a Watercourse Reached? ☐ Yes ☒ No						olume Impacting t	the Wate	rcourse.			
If a Waterco	ırse was Im	pacted, Descr	ibe Fully.	*								
							the BGT was do		g removal	to ensure no so	il impacts from	
tile BOT, 30	ii alialysis i	esuited iii 1 F	n, bica	and emorides ber	ow stanc	iaius. Aliaiys	is results are allac	ched.				
Describe Are	a Affected	and Cleanup A	Action Tak	cen.* BGT was re	moved a	and the area u	nderneath the BG	T was sa	ampled. Ti	he area under t	he BGT was	
				active well area.					•			
							knowledge and u					
							nd perform correct arked as "Final R					
should their	perations h	nave failed to a	idequately	investigate and r	emediat	e contaminati	on that pose a thr	eat to gr	ound water	, surface water	, human health	
		ıddition, NMC ws and/or regu		otance of a C-141	report d	oes not reliev	e the operator of	responsi	bility for co	ompliance with	any other	
rederal, state,	or local la	ws and/or regu	nations.				OIL CON	SERV	ATION	DIVISION		
Signature:	leff i	Peace					OIL COIN	<u>DLICY</u>	111011	DIVIDIOI	_	
Printed Name	e: Jeff Peac	e				Approved by Environmental Specialist:						
Title: Area E						Approval Dat	·e·	F	Expiration 1	Date:		
								1 1	мришон .	Dato.		
E-mail Addre	ess: peace.je	effrey@bp.coi	n			Conditions of	Approval:			Attached []	
Date: Augus	t 4, 2014		Phone:	505-326-9479								

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, BLO	NEERING, INC. OMFIELD, NM 87 332-1199	413	API #:	4510598 A
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELE			PAGE #:	
SITE INFORMATION	I: SITE NAME: BARRETT I 31N RNG: 9W PM: N		NM	DATE STARTED:	06/04/14
1/4 -1/4/FOOTAGE: 1,190'N / 1,19	00'E NE/NE LEASE TYPE:	FEDERAL STATE / FEE /	INDIAN	DATE FINISHED: ENVIRONMENTAL SPECIALIST(S):	NJV
REFERENCE POINT		RD.: 36.88747 X 1	07.79860	GL ELE	.v.: 6,276'
2)	GPS COORD:: 36.8879 GPS COORD:: GPS COORD		DISTANCE/BEAL	RING FROM W.H.: RING FROM W.H.: RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAB			04 ED (9034 D /30)	OVM READING (ppm)
2) SAMPLEID:	SAMPLE DATE:	SAMPLE TIME: LAB ANAL	 Ysis:		0.0 (CI) NA
	COHESIVE COHESIVE HIGHLY COHESIVE DENS DOSE / FIRM DENSE / VERY DENSE HC OF PTS. DESTRICT OF PTS. DENSE HC OF PTS. DENSE HC OF PTS. ANY	ON:	SOFT/FIRM/ NATION- S/NO EXPLAN	STIFF / VERY STIFF / I	
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <100' N				TIMATION (Cubic Yar	400
SITE SKETCH PBGTL T.B. ~ 5' B.G. PF	BGT Located : off on site SEPARATOR COMPRESSO COD. UNK STEEL CONTAINMENT RING	PLOT PLAN circle: at	N TIME	MISCELL. /O: N154396 O #: K: ZEVH01 J #: Z2-006Q ermit date(s): CD Appr. date(s): OVM = Organic	Ppm RF = 1.00 A PPM RF = 1.00
APPLICABLE OR NOT AVAILABLE; SW - SINGL	OW-GRADE TANK LOCATION; SPD = SAMPLE POINT DE E WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; DE	ESIGNATION; R.W. = RETAINING WALL; N. B - DOUBLE BOTTOM.		lagnetic declination	
NOTES: GOOGLE EARTH IMAGE	KY DATE: 11/1//2013.	ONSITE: 06/04/14			· · · · · · · · · · · · · · · · · · ·

Analytical Report

Lab Order 1406323

Date Reported: 6/11/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC - TB @ 4' (95)

Project: Barrett LS #4

Collection Date: 6/4/2014 11:10:00 AM

Lab ID: 1406323-001

Received Date: 6/6/2014 10:09:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	E ORGANICS				, Analyst	BCN
Diesel Range Organics (DRO)	ND	9.8	mg/Kg	1	6/10/2014 3:17:39 AM	13570
Surr: DNOP	. 124	57.9-140	%REC	1	6/10/2014 3:17:39 AM	13570
EPA METHOD 8015D: GASOLINE RA	NGE				Analyst	NSB
Gasoline Range Organics (GRO)	ND	4.9	mg/Kg	1	6/9/2014 11:02:08 PM	13564
Surr: BFB	91.2	80-120	%REC	1	6/9/2014 11:02:08 PM	13564
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.049	mg/Kg	1	6/9/2014 11:02:08 PM	13564
Toluene	ND	0.049	mg/Kg	1	6/9/2014 11:02:08 PM	13564
Ethylbenzene	ND	0.049	mg/Kg	1	6/9/2014 11:02:08 PM	13564
Xylenes, Total	ND	0.098	mg/Kg	1	6/9/2014 11:02:08 PM	13564
Surr: 4-Bromofluorobenzene	103	80-120	%REC	1	6/9/2014 11:02:08 PM	13564
EPA METHOD 300.0: ANIONS					Analyst	JRR
Chloride	ND	30	mg/Kg	20	6/9/2014 11:59:13 AM	13585
EPA METHOD 418.1: TPH					Analyst	JME
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	6/11/2014 12:00:00 PM	13571

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 6

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1406323

11-Jun-14

Client:

Blagg Engineering

Project:

Barrett LS #4

Sample ID MB-13585

Prep Date:

6/9/2014

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

Sample ID LCS-13585

LCSS

6/9/2014

PBS

Batch ID: 13585 Analysis Date: 6/9/2014

1.5

RunNo: 19158

SeqNo: 553664

Units: mg/Kg

Analyte

Result PQL

ND

SPK value SPK Ref Val

%REC LowLimit

HighLimit

%RPD **RPDLimit**

Qual

Chloride

SampType: LCS Batch ID: 13585

TestCode: EPA Method 300.0: Anions

RunNo: 19158

LowLimit

Units: mg/Kg

SPK value SPK Ref Val

SeqNo: 553665 %REC

HighLimit

RPDLimit

Qual

Analyte Chloride

Client ID:

Prep Date:

Result 14

15.00

93.6

%RPD

1.5

Analysis Date: 6/9/2014

PQL

90

110

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range E
- Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RLReporting Detection Limit

Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1406323

11-Jun-14

Client:

Blagg Engineering

Project:

Barrett LS #4

Sample ID

MB-13571 SampType: MBLK

TestCode: EPA Method 418.1; TPH

Client ID:

PBS

Batch ID: 13571

RunNo: 19175

Analysis Date: 6/11/2014

SeqNo: 554453

Units: mg/Kg

Prep Date:

HighLimit

Analyte

6/6/2014

PQL Result

SPK value SPK Ref Val %REC LowLimit

%RPD **RPDLimit**

Qual

Petroleum Hydrocarbons, TR

ND

92

Result

96

SampType: LCS

TestCode: EPA Method 418.1: TPH

SeqNo: 554454

91.5

Sample ID LCS-13571

Client ID:

LCSS

Batch ID: 13571

RunNo: 19175

Units: mg/Kg

Analyte

Prep Date:

6/6/2014

Analysis Date: 6/11/2014 Result **PQL**

SPK value SPK Ref Val %REC

LowLimit

HighLimit %RPD

Qual

Qual

Petroleum Hydrocarbons, TR

120

RPDLimit

Sample ID LCSD-13571

SampType: LCSD Batch ID: 13571

20

100.0

TestCode: EPA Method 418.1: TPH

RunNo: 19175

Units: mg/Kg

Analyte

Prep Date: 6/6/2014

Client ID: LCSS02

Analysis Date: 6/11/2014 PQL

20

SPK value SPK Ref Val

%REC

LowLimit

HighLimit

%RPD

RPDLimit

Petroleum Hydrocarbons, TR

100.0

95.7

SeqNo: 554455

80

4.44

20

Value exceeds Maximum Contaminant Level.

Value above quantitation range Analyte detected below quantitation limits

RSD is greater than RSDlimit

Analyte detected in the associated Method Blank

Not Detected at the Reporting Limit

Sample pH greater than 2.

Reporting Detection Limit RL

Qualifiers:

0

RPD outside accepted recovery limits

S Spike Recovery outside accepted recovery limits

Н Holding times for preparation or analysis exceeded

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1406323

11-Jun-14

Client:

Blagg Engineering

Project:

Barrett LS #4

Sample ID MB-13570	SampType: MBLK	TostCodo: EDA Method	2015D: Diagol Bango O	raaniaa				
•		TestCode: EPA Method 8015D: Diesel Range Organics						
Client ID: PBS	Batch ID: 13570	RunNo: 19120						
Prep Date: 6/6/2014	Analysis Date: 6/9/2014	SeqNo: 553331	Units: mg/Kg					
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual				
Diesel Range Organics (DRO)	ND 10							
Surr: DNOP	8.1 10.00	81.4 57.9	140					
Sample ID LCS-13570	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range O	rganics				
Client ID: LCSS	Batch ID: 13570	RunNo: 19120						
Prep Date: 6/6/2014	Analysis Date: 6/9/2014	SeqNo: 553332	Units: mg/Kg	g/Kg				
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual				
Diesel Range Organics (DRO)	55 10 50.00	0 109 60.8	145					
Surr: DNOP	5.2 . 5.000	104 57.9	140					
Sample ID MB-13578	SampType: MBLK	TestCode: EPA Method	8015D: Diesel Range O	rganics				
Client ID: PBS	Batch ID: 13578	RunNo: 19152						
Prep Date: 6/9/2014	Analysis Date: 6/10/2014	SeqNo: 553568	Units: %REC					
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual				
Surr: DNOP	12 10.00	116 57.9	140					
Sample ID LCS-13578	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range O	3015D: Diesel Range Organics				
Olimat ID. 1000	Databilly 40570	Dumbles 40450	Duralles 40450					

Client ID:	LCSS	Batch	ID: 1	3578	R	tunNo: 1	9152				
Prep Date:	6/9/2014	Analysis Da	ate: 6	6/10/2014	S	SeqNo: 5	53571	Units: %RE	С		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimít	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP		4.8		5.000		95.5	57.9	140			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDImit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

23

930

WO#:

1406323

11-Jun-14

Client:

Blagg Engineering

Gasoline Range Organics (GRO)

Surr: BFB

Project: Barrett	LS #4						
Sample ID MB-13564	SampType: MBLK	TestCode: EPA Method 8015D: Gasoline Range					
Client ID: PBS	Batch ID: 13564	RunNo: 19108					
Prep Date: 6/6/2014	Analysis Date: 6/7/2014	SeqNo: 552282	Units: mg/Kg				
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual			
Gasoline Range Organics (GRO)	ND 5.0						
Surr: BFB	880 1000	87.8 80	120				
Sample ID LCS-13564	SampType: LCS	rpe: LCS TestCode: EPA Method 8015D: Gasoline Range					
Client ID: LCSS	Batch ID: 13564	RunNo: 19108					
Prep Date: 6/6/2014	Analysis Date: 6/7/2014	SeqNo: 552283	Units: mg/Kg				
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual			

90.8

93.0

71.7

80

134

120

25.00

1000

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range Е
- Analyte detected below quantitation limits J
- 0 RSD is greater than RSDlimit
- RPD outside accepted recovery limits R
- S Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2.
- RLReporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1406323 11-Jun-14

Client:

Blagg Engineering

Project:

Barrett LS #4

Sample ID LCS-13564	SampType: LCS			TestCode: EPA Method 8021B: Volatiles						
Client ID: LCSS	Batch ID: 13564			RunNo: 19108						
Prep Date: 6/6/2014	Analysis [Date: 6 /	7/2014	SeqNo: 552328			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.050	1.000	0	107	80	120			
Toluene ·	0.99	0.050	1.000	0	98.7	80	120			
Ethylbenzene	0.97	0.050	1.000	0	96.9	80	120			
Xylenes, Total	2.9	0.10	3.000	0	95.7	80	120			
Surr: 4-Bromofluorobenzene	1.2		1.000		116	80	120			
Sample ID MB-13564	Samp	Гуре: МЕ	BLK	.K TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS	Batc	h ID: 13	564	F	RunNo: 1	9108				

Sample ID WB-13364	Samprype: WBLK		resicode: EPA Wethod 8021B: Volatiles								
Client ID: PBS	Batch ID: 13564			RunNo: 19108							
Prep Date: 6/6/2014	Analysis D	is Date: 6/7/2014		SeqNo: 552329 Units: mg/			Units: mg/K	Кg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	ND	0.050									
Toluene	ND	0.050									
Ethylbenzene	ND	0.050					4				
Xylenes, Total	ND	0.10								*	
Surr: 4-Bromofluorobenzene	1.1		1.000		107	80	120				

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG Work Order Number	er: 1406323		RcptNo: 1			
Received by/date: CS O(0/0/14						
Logged By: Michelle Garcia 6/6/2014 10:09:00 AN	VI	Міни Ср	un)			
Completed By: Michelle Garcia 6/6/2014 12:17:37 PM	νI	Mitiell Ga Mitiell Ga	ua)			
Reviewed By: (14		. ,				
Chain of Custody						
1. Custody seals intact on sample bottles?	Yes 🗌	No 🗌	Not Present ☑			
2. Is Chain of Custody complete?	Yes 🗹	No 🗌	Not Present			
3. How was the sample delivered?	Courier					
<u>Log In</u>						
4. Was an attempt made to cool the samples?	Yes 🗹	No 🗌	NA 🗆			
5. Were all samples received at a temperature of >0° C to 6.0°C	Yes 🗹	No 🗆	na \square			
6. Sample(s) in proper container(s)?	Yes 🗹	No 🗌	•			
7. Sufficient sample volume for indicated test(s)?	Yes 🗹	No 🗌				
8. Are samples (except VOA and ONG) properly preserved?	Yes 🔽	No 🗌				
9. Was preservative added to bottles?	Yes 🗌	No 🗹	NA \square			
10.VOA vials have zero headspace?	Yes 🗌	No 🗆	No VOA Vials 🗹			
11. Were any sample containers received broken?	Yes	No 🗹	# of preserved			
40.5	🗖		bottles checked			
12.Does paperwork match bottle labels? (Note discrepancies on chain of custody)	Yes 🗹	∴ No □	for pH: (<2 or >12 unless noted)			
13. Are matrices correctly identified on Chain of Custody?	Yes 🗹	No 🗆	Adjusted?			
14. Is it clear what analyses were requested?	Yes 🗹	No 🗆				
15. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes 🗹	No 🗌	Checked by:			
Special Handling (if applicable)						
16. Was client notified of all discrepancies with this order?	Yes 🗌	No 🗆	NA 🗹			
Person Notified: Date:						
By Whom: Via:	eMail F	Phone 🔲 Fax	☐ In Person			
Regarding:						
Client Instructions:						
17. Additional remarks:						
18. Cooler Information Cooler No Temp C Condition Seal Intact Seal No 1 1 1.7 Good Not Present	Seal Date	Signed By				

LIL HALL ENVIRONMENTAL						
ANALYSIS LABORATORY						
www.hallenvironmental.com						
4901 Hawkins NE - Albuquerque, NM 87109						
Tel. 505-345-3975 Fax 505-345-4107						
Añalysis Request						
#B5-(8021B) PH (Gas only) (DRO / which C 18.1) 04.1) 270SIMS) / 8082 PCB's / 8082 PCB's / 8082 PCB's						
18.1) 14.1) 14.1) 17.05.PM 18.1) 18.1) 18.1) 19.0 / wate						
THMB5 TPH (G O / DRC 103,NO S00.0 / W S00.0 / W S00.0 / W						
oor E						
BTEX + MTBE + TPH (Gas only) BTEX + MTBE + TPH (Gas only) TPH 8015B (GRO / DRO / MRC) TPH 8015B (GRO / DRO / MRC) TPH (Method 418.1) EDB (Method 504.1) PAH (8310 or 8270SIMS) RCRA 8 Metals Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄) 8081 Pesticides / 8082 PCB's 8260B (VOA) Chloride (soil - 300.0 / water - 300.1) Grab sample 5 pt. composite sample						
i literatura						
BILL DIRECTLY TO BP: Jeff Peace, 200 Energy Court, Farmington, NM 87401						
Time Work Order: N15439605 Paykey: ZEVH01BGT2						
一門ないということが						



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

May 5, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: BARRETT LS 004

API#: 3004510598

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about May 29, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

9DULKE

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

May 7, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

BARRETT LS 004 API 30-045-10598 (G) Section 20 – T31N – R09W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



