District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe. NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application
Proposed Alternative Method Permit or Closure Plan Application Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Atlantic B LS 16AUG 0 5 2014
API Number:3004524203OCD Permit Number:
U/L or Qtr/Qtr B Section 4 Township 30N Range 10W County: San Juan
Center of Proposed Design: Latitude36.845636 Longitude107.884912 NAD: □1927 ⋈ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2. Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary:
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:45.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☑ Visible sidewalls only ☐ Other _Single walled/double bottomed
Liner type: Thickness mil
4. Alternative Method:

Form C-144

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Ý	
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
☐ Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school	, hospital,
institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC	
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	•
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. ☐ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
2.100 p. 100 consideration of approval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable acceptable in the application.	eptable source
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	•
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	☐ Yes☐ No☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.	Yes No
NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	│
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☐ No
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)	
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	Yes No
Society; Topographic map	
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).	Yes No
- Topographic map; Visual inspection (certification) of the proposed site	
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;	☐ Yes ☐ No
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole,	Yes No
or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Ýes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1	
and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	uments are
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
<u>Proposed Closure</u> : 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	Fluid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sout provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from		
	the municipality	Yes No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Div	vision	Yes No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Reso Society; Topographic map	ources; USGS; NM Geological	Yes No
Within a 100-year floodplain FEMA map		Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.1 Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate require Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13	5.17.10 NMAC 19.15.17.13 NMAC ments of Subsection K of 19.15.17.1 the appropriate requirements of 19.1 5.17.13 NMAC AC case on-site closure standards canno NMAC NMAC	11 NMAC 5.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to	o the best of my knowledge and belie	of.
Signature: Date:	·	·
e-mail address:		
e-mail address: Telephone:		
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Representative Signature: OCD Permit Nu	Approval Date: 9/11/2	M4
OCD Approval: Permit Application (including closure plat) Closure Rian (only) OCD Representative Signature: Title: OCD Permit Nu 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing an The closure report is required to be submitted to the division within 60 days of the completion of the section of the form until an approved closure plan has been obtained and the closure activities have	Approval Date: 9/11/2 mber: y closure activities and submitting to the closure activities. Please do not de	the closure report.
OCD Approval: Permit Application (including closure plat) Closure Rian (only) OCD Representative Signature: Title: OCD Permit Nu 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing an The closure report is required to be submitted to the division within 60 days of the completion of the section of the form until an approved closure plan has been obtained and the closure activities have	Approval Date: 9/1/2 mber:	the closure report. complete this

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirem	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Off Posco	Date:August 4, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Atlantic B LS 16 API No. 3004524203 Unit Letter B, Section 4, T30N, R10W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- i. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	45 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

* Attach Additional Sheets If Necessary

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	ation	n and Co	rrective A	ction				
				. <u>.</u>		OPERA			Initia	al Report	\boxtimes	Final Report
Name of Co	_		NI	N 67401		Contact: Jef		170				
Facility Nar		Court, Farm	ington, N	M 8/401			lo.: 505-326-94 e: Natural gas v					
							C. Hatarar gas v	7011				
Surface Ow	ner: Fedei	ral		Mineral C	wner:	Federal_			API No	. 30045242	203	
				LOCA		N OF REI	LEASE					
Unit Letter B	Section 4	Township 30N	Range 10W	Feet from the 860	North North	South Line	Feet from the 1,680	East/We East	est Line	County: Sa	an Juan	
		Latit	ude36	.845636		_ Longitud	e107.884912					
		<u>-</u>		NAT	URE	OF RELI	EASE					
Type of Rele		u anada tanla	45 hh1				Release: N/A			Recovered: N		NI/A
Source of Re	lease: belo	w grade tank -	- 45 00!			N/A	our of Occurrenc	ce:	Date and	Hour of Dis	covery:	N/A
Was Immedia	ate Notice (Yes [] No ⊠ Not R€	quired	If YES, To	Whom?	,				
By Whom?						Date and I-						
Was a Water	course Rea	ched?	Yes 🗵	No	•	If YES, Vo	lume Impacting t	the Water	course.			
Describe Cau	se of Probl		dial Actio	n Taken.* Samplin and chlorides belo					removal (to ensure no	soil im	pacts from
				en.* BGT was reactive well area.	noved a	and the area u	nderneath the BG	T was sar	npled. Th	ne area unde	r the B	GT was
regulations al public health should their of or the environ	I operators or the envious hoperations homent. In a	are required tronment. The nave failed to	o report and acceptance acceptanc	is true and completed in the control of the certain received of a C-141 reposition of the certain received investigate and received in the certain of a C-141 received in the certain of a C-14	elease norther the the the the the the the the the the	otifications ar e NMOCD m e contaminati	nd perform correctarked as "Final Room that pose a three	ctive action eport" doc eat to grou	ns for rele es not reli und water	eases which eve the oper s, surface wa	may en ator of ter, hur	danger liability nan health
							OIL CON	SERVA	TION	DIVISIO	N	
Signature:	off	Peace	<u></u>									
Printed Name	e: Jeff Peac	e				Approved by	Environmental S	pecialist:				
Title: Area E	nvironmen	tal Advisor				Approval Dat	e:	Ex	cpiration I	Date:		
E-mail Addre	ess: peace.j	effrey@bp.co	m			Conditions of	`Approval:			Attached		
Date: Augus	t 4, 2014		Phone:	505-326-9479								

CLIENT: BP	P.O. BOX 87, B	NGINEERING, INC. BLOOMFIELD, NM 874 05) 632-1199	413	API #:
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OTHER:		PAGE#: 1 of 1
1/4-1/4/FOOTAGE: 860'N / 1,680 '	30N RNG: 10W PM E NW/NE LEASE		INDIAN	DATE STARTED: 06/13/14 DATE FINISHED: ENVIRONMENTAL SPECIALIST(S): JCB
1) 45 BGT (SW/DB) 2) 3)	GPS COORD.: GPS COORD.: GPS COORD.:	36.84561 X 1 3.845636 X 107.884912	07.88487 DISTANCE/BEAI DISTANCE/BEAI	RING FROM W.H.: 20', N65W RING FROM W.H.:
SAMPLING DATA: 1) SAMPLE ID: 45 BGT 5 pt. @ 2) SAMPLE ID: 3) SAMPLE ID: 4) SAMPLE ID:	CHAIN OF CUSTODY RECORD(S) # 0 SAMPLE DATE: SAMPLE DATE: SAMPLE DATE:	OR LAB USED: HALL 3/14 SAMPLETIME: 0836 LAB ANAL SAMPLETIME: LAB ANAL LAB ANAL	ysis: 418.1/8 ysis:	015B/8021B/300.0 (CI) 0.0
SOIL DESCRIPTION SOIL COLOR: DARK YE COHESION (ALL OTHERS): NON COHESIVE) SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY SLIGHTLY MOIST MOIST / W SAMPLE TYPE: GRAB COMPOSITE # DISCOLORATION/STAINING OBSERVED: YES N	CLLOWSH ORANGE COHESIVE / COHESIVE / HIGHLY COHESIVE OSE FIRM / DENSE / VERY DENSE T / SATURATED / SUPER SATURATED OF PTS. EXPLANATION -	PLASTICITY (CLAYS): NON PLASTIC / SLIGH DENSITY (COHESIVE CLAYS & SILTS): HC ODOR DETECTED: YES NO EXPLAN ANY AREAS DISPLAYING WETNESS: YES	TLY PLASTIC / CO SOFT / FIRM / : ATION -	
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER: PVC LINER (VISIBLE) UNDER E	D AND/OR OCCURRED : YES NO EXPL YES NO EXPLANATION -	Anation:		
SITE SKETCH	NA ft. X NA EAREST WATER SOURCE: >1,000' BGT Located: off on sit PBGTL T.B. ~ 6' B.G. X X X X X X X X X X X X X X X X X X X	NEAREST SURFACE WATER: <20 TE PLOT PLAN circle: att BERM WOODEN R.W.	O' NMOC Cached OWN OWN TIME: W PC PI PA OC Tan ID A	#: Z2-006Q0 ermit date(s): 06/02/10 CD Appr. date(s): 04/23/14 k
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGLE NOTES:	OW-GRADE TANK LOCATION; SPD = SAMPLE F	POINT DESIGNATION; R.W. = RETAINING WALL; NA	LL HEAD;	BGT Sidewalls Visible: Y / N agnetic declination: 10° E

Analytical Report

Lab Order 1406667

Date Reported: 6/18/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering **Project:** Atlantic B LS 16

Client Sample ID: 45 BGT 5-pt @ 6'

Collection Date: 6/13/2014 8:36:00 AM

Lab ID: 1406667-001

Matrix: MEOH (SOIL) Received Date: 6/14/2014 10:00:00 AM

Analyses	Result	RL Qı	nal Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RAN	GE ORGANICS				Analyst	BCN
Diesel Range Organics (DRO)	22	9.9	mg/Kg	1	6/15/2014 11:58:42 PM	13706
Surr: DNOP	101	57.9-140	%REC	1	6/15/2014 11:58:42 PM	13706
EPA METHOD 300.0: ANIONS					Analyst	SRM
Chloride	ND	30	mg/Kg	20	6/16/2014 9:56:30 AM	13714
EPA METHOD 8260B: VOLATILES S	SHORT LIST				Analyst	cadg
Benzene	ND	0.046	mg/Kg	1	6/16/2014 11:16:47 AM	R19305
Toluene	ND	0.046	mg/Kg	. 1	6/16/2014 11:16:47 AM	R19305
Ethylbenzene	ND	0.046	mg/Kg	1	6/16/2014 11:16:47 AM	R19305
Xylenes, Total	ND	0.091	mg/Kg	1	6/16/2014 11:16:47 AM	R19305
Surr: 1,2-Dichloroethane-d4	97.6	70-130	%REC	1	6/16/2014 11:16:47 AM	R19305
Surr: 4-Bromofluorobenzene	90.9	70-130	%REC	1 、	6/16/2014 11:16:47 AM	R19305
Surr: Dibromofluoromethane	114	70-130	%REC	1	6/16/2014 11:16:47 AM	R19305
Surr: Toluene-d8	91.0	70-130	%REC	1	6/16/2014 11:16:47 AM	R19305
EPA METHOD 8015D MOD: GASOLI	NE RANGE				Analyst:	cadg
Gasoline Range Organics (GRO)	ND	4.6	mg/Kg	1	6/16/2014 11:16:47 AM	R19305
Surr: BFB	110	61.2-137	%REC	1	6/16/2014 11:16:47 AM	R19305
EPA METHOD 418.1: TPH					Analyst:	BCN
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	6/17/2014	13718

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 5

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1406667

18-Jun-14

Client:

Blagg Engineering

Project:

Atlantic B LS 16

Sample ID MB-13718

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID: PBS

Prep Date:

6/16/2014

Batch ID: 13718 Analysis Date: 6/17/2014

PQL

20

RunNo: 19311 SeqNo: 558300

%REC

LowLimit

Units: mg/Kg

%RPD **RPDLimit**

Qual

Analyte Petroleum Hydrocarbons, TR

Sample ID LCS-13718

Result

ND

SampType: LCS

TestCode: EPA Method 418.1: TPH

Client ID: LCSS Batch ID: 13718

20

RunNo: 19311

LowLimit

Units: mg/Kg

Prep Date: 6/16/2014 Analyte

Analysis Date: 6/17/2014

SeqNo: 558301 %REC

HighLimit

HighLimit

Petroleum Hydrocarbons, TR

87

Batch ID: 13718

86.6

120 80

RPDLimit Qual

Sample ID LCSD-13718 LCSS02

SampType: LCSD

TestCode: EPA Method 418.1: TPH

RunNo: 19311

SeqNo: 558302

Units: mg/Kg

Prep Date:

Client ID:

6/16/2014

Analysis Date: 6/17/2014

88

SPK value SPK Ref Val %REC

HighLimit

%RPD

%RPD

RPDLimit

Qual

Analyte

Result

100.0

100.0

87.9

80

120

Petroleum Hydrocarbons, TR

20

SPK value SPK Ref Val

SPK value SPK Ref Val

1.56

20

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- Analyte detected below quantitation limits RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits Spike Recovery outside accepted recovery limits S
- Analyte detected in the associated Method Blank
- Н
- P Sample pH greater than 2.
- Reporting Detection Limit

Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Page 2 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1406667 18-Jun-14

Client:

Blagg Engineering

Project:

Atlantic B LS 16

Sample ID MB-13706

SampType: MBLK

TestCode: EPA Method 8015D: Diesel Range Organics

Client ID:

PBS

Batch ID: 13706

PQL

RunNo: 19265

Prep Date: 6/15/2014 Analysis Date: 6/15/2014

SeqNo: 556848

%REC

Units: mg/Kg

SPK value SPK Ref Val

HighLimit %RPD

RPDLimit Qual

Diesel Range Organics (DRO)

ND

Result

10.00

82.0

57.9

LowLimit

Surr: DNOP

Analyte

10 8.2

SampType: LCS

TestCode: EPA Method 8015D: Diesel Range Organics

140

Sample ID LCS-13706 Client ID: LCSS

Batch ID: 13706

RunNo: 19265

SeqNo: 556850

LowLimit

Units: mg/Kg

%RPD

Qual

Analyte Diesel Range Organics (DRO) Surr: DNOP

6/15/2014

Analysis Date: 6/15/2014 Result PQL

SPK value SPK Ref Val

50.00

99.0 74.1

%REC

60.8

HighLimit 145 **RPDLimit**

Prep Date:

49 10 3.7

5.000

57.9

140

Qualifiers:

R

- Value exceeds Maximum Contaminant Level.
- Е Value above quantitation range
- Analyte detected below quantitation limits RSD is greater than RSDlimit 0

RPD outside accepted recovery limits

- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- Not Detected at the Reporting Limit P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 3 of 5

Hall Environmental Analysis Laboratory, Inc.

WO#:

1406667

18-Jun-14

Client:

Blagg Engineering

Project: Atlantic B LS 16

									•	
Sample ID 5ml-rb	SampT	Гуре: М І	BLK	Tes	tCode: E	PA Method	8260B: Vola	tiles Shor	t List	
Client ID: PBS	Batch	h ID: R1	19272	F	RunNo: 1	9272				
Prep Date:	Analysis E	Date: 6	/15/2014		SeqNo: 5	57042	Units: %RE	C		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 1,2-Dichloroethane-d4	0.50		0.5000		100	70	130			, ,
Surr: 4-Bromofluorobenzene	0.51		0.5000		103	70	130			
Surr: Dibromofluoromethane	0.55		0.5000		111	70	130			
Surr: Toluene-d8	0.49		0.5000		98.9	70	130			
Sample ID 100ng Ics	SampT	ype: LC	s	Tes	tCode: El	PA Method	8260B: Vola	tiles Short	t List	
Client ID: LCSS	Batch	n ID: R1	9272	F	RunNo: 1	9272				
Prep Date:	Analysis D)ate: 6/	15/2014	9	SeqNo: 5	57043	Units: %RE	:C		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 1,2-Dichloroethane-d4	0.50		0.5000		99.0	70	130			
Surr: 4-Bromofluorobenzene	0.50		0.5000		99.8	70	130			
Surr: Dibromofluoromethane	0.50		0.5000		99.5	70	130		,	
Surr: Toluene-d8	0.49		0.5000		98.9	70	130			
Sample ID 5ml-rb	SampT	ype: ME	BLK	Tes	tCode: El	PA Method	8260B: Vola	tiles Short	List	
Client ID: PBS	Batch	1D: R1	9305	RunNo: 19305						
Prep Date:	Analysis D	ate: 6/	16/2014	5	SeqNo: 5	58034	Units: mg/h	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 1,2-Dichloroethane-d4	0.49		0.5000		97.1	70	130			
Surr: 4-Bromofluorobenzene	0.50	•	0.5000		101	70	130			
Surr: Dibromofluoromethane	0.54		0.5000		108	70	130			
Surr: Toluene-d8	0.51		0.5000		101	70	130			
Sample ID 100ng Ics	SampT	ype: LC	S	Tes	tCode: El	PA Method	8260B: Vola	tiles Short	List	
Client ID: LCSS	Batch	1D: R1	9305	F	RunNo: 19	9305				
Prep Date:	Analysis D	ate: 6/	16/2014	S	SeqNo: 5	58035	Units: mg/k	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.050	1.000	0	107	70	130			
Toluene	1.0	0.050	1.000	. 0	104	60.1	120			
Surr: 1,2-Dichloroethane-d4	0.50		0.5000		99.2	70	130			

Qualifiers:

* Value exceeds Maximum Contaminant Level.

0.49

0.51

0.49

0.5000

0.5000

0.5000

- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit

Surr: 4-Bromofluorobenzene

Surr: Dibromofluoromethane

Surr: Toluene-d8

- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank

70

70

70

130

130

130

- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

98.6

102

97.4

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 5

Hall Environmental Analysis Laboratory, Inc.

Result

26

480

PQL

5.0

WO#:

1406667 18-Jun-14

Client:

Blagg Engineering

Analyte

Surr: BFB

Gasoline Range Organics (GRO)

atio D I C 16

Project: Atlantic	c B LS 16			
Sample ID 2.5ug gro lcs	SampType: LCS		8015D Mod: Gasoline Range	
Client ID: LCSS	Batch ID: R19272	RunNo: 19272		
Prep Date:	Analysis Date: 6/15/2014	SeqNo: 557016	Units: %REC	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit	Qual
Surr: BFB	480 500.0	96.9 61.2	137	
Sample ID 5ml-rb	SampType: MBLK	TestCode: EPA Method	8015D Mod: Gasoline Range	
Client ID: PBS	Batch ID: R19305	RunNo: 19305		
Prep Date:	Analysis Date: 6/16/2014	SeqNo: 558041	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit	Qual
Gasoline Range Organics (GRO)	ND 5.0			
Surr: BFB	470 500.0	94.3 61.2	137	
Sample ID 2.5ug gro lcs	SampType: LCS	TestCode: EPA Method	8015D Mod: Gasoline Range	
Client ID: LCSS	Batch ID: R19305	RunNo: 19305		
Prep Date:	Analysis Date: 6/16/2014	SeqNo: 558042	Units: mg/Kg	

0

SPK value SPK Ref Val

25.00

500.0

LowLimit

80

61.2

%REC

106

95.6

120

137

%RPD

RPDLimit


Qual

HighLimit

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- Analyte detected below quantitation limits
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2.
- Reporting Detection Limit

Page 5 of 5



4901 Hawkins NE Albuquerque, NM 87105 TEL: 505-345-3975 FAX: 505-345-4107

Sample Log-In Check List

Website: www.hallenvironmental.com

Client Name: BLAGG Work Orde	er Number: 1406667	7	RcptNo: 1									
Received by/date:	[] [4											
Logged By: Ashley Gallegos 6/14/2014 1	/ 0:00;00 AM	A										
Completed By: Ashley Gallegos 6/14/2014 10	0:21:56 AM .	A		ļ.								
Reviewed By:	4114	2 – 0										
Chain of Custody												
1. Custody seals intact on sample bottles?	Yes 🗌] No 🗆	Not Present 🗹									
2. Is Chain of Custody complete?	Yes 🗹	No 🗆	Not Present									
3. How was the sample delivered?	Courier		÷									
Log In												
4. Was an attempt made to cool the samples?	Yes 🖳	Ø No □	na 🗆									
5. Were all samples received at a temperature of >0° C to 6	3.0°C Yes ✓	No 🗆	na 🗆									
6. Sample(s) in proper container(s)?	Yes 🗹	No 🗆										
7. Sufficient sample volume for indicated test(s)?	Yes 🗹	No 🗌										
8, Are samples (except VOA and ONG) properly preserved?	Yes 🗸	No 🗌										
9, Was preservative added to bottles?	Yes 🗆	No 🗹	NA \square									
10.VOA vials have zero headspace?	Yes 🗆	No 🗆	No VOA Viais ⊻									
11. Were any sample containers received broken?	Yes 🗀	No ✓										
		-	# of preserved bottles checked									
12.Does paperwork match bottle labels? (Note discrepancies on chain of custody)	Yes 🗹	No 🗆	for pH: (<2 or	>12 unless noted)								
13. Are matrices correctly identified on Chain of Custody?	Yes 🔽	No □	Adjusted?	- 12 amood notedy								
14. Is it clear what analyses were requested?	Yes 🗹											
15. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes 🗸	No 🗌	Checked by:									
(i. vo, ioniy carana, io addisa attorny												
Special Handling (if applicable)												
16. Was client notified of all discrepancies with this order?	Yes 🗌	No 🗆.	NA 🗹									
Person Notified:	Date:											
By Whom:	Via: 🗌 eMail	Phone Fax	In Person	1								
Regarding:												
Client Instructions:												
17. Additional remarks:												
18. Cooler Information												
Cooler No Temp °C Condition Seal Intact Se	al No Seal Date	Signed By										
1 1.9 Good Yes			J									

Client:	Blagg Engir	agg Engineering, Inc.			☐ Standard ★ Rush					ANALYSIS LABORATORY											
BP America			Project Name:													-					
Mailing Address: P.O. Box 87		Atlantic B LS 16			www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109																
Bloomfield, NM 87413			Project #:				Tel. 505-345-3975 Fax 505-345-4107														
Phone #: (505)320-1183																3 2 4	57				
email or Fax#:		Project Manager:																			
QA/QC Packa	age:				Jeff Blagg											, 1					
Standard Level 4 (Full Validation))				1		<u> </u>		1 1				1 1							
□ Other				Sampler:	Jeff Blagg			1	2	2			1								
□ EDD (Typ	oe)			On Ice: XVYes □ No					2						, ,						
		Sample Temperature () ()				9	2			ļ			.		1						
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type		No.	BTEX (8021)	Cad / Cad/ as No nat	TPH 418.1							Chloride				
06/13/2014	8:36	Soil	45 BGT 5-pt @ 6'	1x 4oz	cool		001	x	, ,								x	十			
	,								_	+-				_	+-	7		\dagger			
										+-	一		_		+	\Box	_	+			
	<u> </u>									+-	 				+-	 		+			
		-								-	┼	-						+			
	ļ	 							_	+	 		_		-		+	+			
				ļ			···			-	ļ				+			4			
											<u> </u>				4-4			4			
											<u> </u>							1			
											<u> </u>							\bot			
							·														
			·																		
Date: 0/13/2014	Time: 1400	Relinquist	H Blogg	Received by: Date Time Remarks: Bill BP Paykey: ZEVH01BGT2 BP Contact: Jeff Peace Plea						ase o	opy re	esults	s to:								
Date:	Time: 2030	Relinquish	otte Walls	Received by:	DA	lli SS	06/14	peac	e.jeffr	ey@t	p.co	m			. •						
if nec	cessary, samples	submitted to I	Hall Environmental may be subcontracted	ed to other accredite	d laboratories. This	serves as notice	of this possibi	ility. An	y sub-col	ntracted	data w	vill be d	learly no	tated on	the ana	lytical r	eport.				

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

June 3, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: ATLANTIC-B LS-016

API#: 3004524203

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about June 18, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

9 Ducke

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

June 3, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

ATLANTIC B LS 016 API 30-045-24203 (G) Section 04– T30N – R10W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 45 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



