District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.
For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method Type of action: Below grade tank registration Closure of a pit, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Elliott Gas Com S 1E
API Number: 3004524364 OCD Permit Number:
U/L or Qtr/QtrF Section33 Township30N Range9W County:San Juan
Center of Proposed Design: Latitude36.77040 Longitude107.78890 NAD: ☐1927 ☑ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2. DIL COMS. DIV.
Pit: Subsection F, G or J of 19.15.17.11 NMAC DIST. 3
Temporary: Drilling Workover
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. Tools A. Tools A. Tools A. Tools A.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other _Single walled/double bottomed
Liner type: Thicknessmil
4. Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
☐ Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6. Notting: Subsection F of 10.15.17.11 NIMAC (Applies 4.5 property)	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
8. Variances and Exceptions:	
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC	
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
, , , , , , , , , , , , , , , , , , , ,	
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)	☐ Yes ☐ No
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured	Yes No
from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ 162 ☐ 140
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	MAC cuments are
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	cuments are
 Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC 	
A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.	15.17.9 NMAC
and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	/

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.	documents are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit
☐ Alternative Proposed Closure Method: ☐ Waste Excavation and Removal ☐ Waste Removal (Closed-loop systems only) ☐ On-site Closure Method (Only for temporary pits and closed-loop systems) ☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method	
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be	attached to the
closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC	
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
- Written committation of verification from the municipality, written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	
Within a 100-year floodplain. - FEMA map	☐ Yes ☐ No☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including qlosure plan) X Glospire Plan (only) OCD Conditions (see attachment)	
OCD Representative Signature: Approval Date: 4	10014
Approvar Date. The sentative signature.	201 1
Title: OCD Permit Number:	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not a section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:7/1/2013	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	complete this

22. Operator Closure Certification:	•
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirem	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Jeff Rosee	Date:September 4, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Elliott Gas Com S 1E
API No. 3004524364
Unit Letter F, Section 33, T30N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was sent due to misunderstanding of BGT closure notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was sent due to misunderstanding of BGT closure notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and will be reclaimed with the rest of the site since the well has been plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the will be reclaimed as part of final reclamation since the well has been plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT will be reclaimed as part of final reclamation since the well has been plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT will be reclaimed as part of final reclamation since the well has been plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation since the well has been plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141
Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	atio	n and Co	rrective A	ction			
						OPERA	ГOR	Initia	al Report	\boxtimes	Final Report
Name of Co						Contact: Jef					
		Court, Farmi		M 87401	_	Telephone No.: 505-326-9479					
Facility Nat	ne: Elliott	Gas Com 11	<u> </u>			Facility Type: Natural gas well					
Surface Ow	Surface Owner: Private Mineral C							API No	. 30045243	64	
				LOCA	TIO	N OF REI	LEASE				
Unit Letter	Section	Township	Range	Feet from the		/South Line	Feet from the	East/West Line	County: Sa	ın Juan	1
F	33	30N	9W	1,830	North	ì	1,640	West	•		
		Lati	tude3	6.77040		Longitude	e107.78890_				
				NAT	URE	OF RELI	EASE				
Type of Rele							Release: N/A		lecovered: N		
		v grade tank –	95 bbl				our of Occurrenc	e: Date and	Hour of Disc	covery	
Was Immedia	ate Notice (Yes	No 🛭 Not Re	quired	If YES, To	Whom?				
By Whom?						Date and H					
Was a Watercourse Reached? ☐ Yes ☑ No						If YES, Vo	lume Impacting t	he Watercourse.			
If a Watercou	irse was Im	pacted, Descr	ibe Fully.*								
		•	•								
the BGT. So	il analysis ı	resulted in TPI	H, BTEX a	and chloride belov	w stand	lards. Analysis	s results are attach				
				en.* BGT was res with the rest of th				T was sampled. Thand abandoned.	ne excavated	area v	/as
regulations al public health should their of or the environ	I operators or the envious longerations In a ment. In a	are required to ronment. The lave failed to a	o report an acceptance adequately OCD accep	d/or file certain re e of a C-141 repo investigate and re	elease r rt by th emedia	notifications ar ne NMOCD ma te contaminati	nd perform correct arked as "Final Re on that pose a thre	nderstand that purs tive actions for rele eport" does not reli eat to ground water responsibility for co	eases which eve the oper , surface wa	may en ator of ter, hu	ndanger Tliability man health
G:	1.00	Page					OIL CONS	SERVATION	DIVISIO	N	
Signature: Printed Name	: Jeff Peac	e .				Approved by	Environmental Sp	pecialist:			
Title: Area E						Approval Dat	e:	Expiration I	Date:		
E-mail Addre	ess: peace.je	effrey@bp.cor	n			Conditions of	Approval:		Attached		
Date: Septen	nber 4, 201	4	Phon	e: 505-326-9479							

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, BLO	INEERING, INC. OMFIELD, NM 874 632-1199	13	API #: 30(TANK ID (if applicble):	
FIELD REPORT:	(circle one): BGT CONFIRMATION / REL	EASE INVESTIGATION / OTHER:		PAGE#:	1 of 1
QUAD/UNIT: F SEC: 33 TWP:		M CNTY: SJ ST:		DATE STARTED: DATE FINISHED:	06/20/13
LEASE#: -	D'W SE/NW LEASE TYPE: PROD. FORMATION: DK CONTE	CROSSFIRE RACTOR: MBF - T. PETERS	ON		NJV
2)	GPS COORD.: 36.77 GPS COORD.: GPS COORD.:		DISTANCE/BE, DISTANCE/BE, DISTANCE/BE,	ARING FROM W.H.: ARING FROM W.H.: _ ARING FROM W.H.:	EV.: <u>5,775'</u> 102', S39E
SAMPLING DATA: 1) SAMPLE ID:5PC-TB @ 5' (95)	CHAIN OF CUSTODY RECORD(S) # OR LAE SAMPLE DATE: 06/20/13	BUSED: HALL			OVM READING (ppm) NA
2) SAMPLE ID: 3) SAMPLE ID: 4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANALYSI	S:		
SOIL DESCRIPTION SOIL COLOR: MODE COHESION (ALL OTHERS): NON COHESIVE / SLIGHTL' CONSISTENCY (NON COHESIVE SOILS): LO MOISTURE: DRY SLIGHTLY MOIST MOIST / W SAMPLE TYPE: GRAB COMPOSITE # DISCOLORATION/STAINING OBSERVED	FRATE BROWN COHESIVE / COHESIVE / HIGHLY COHESIVE COSE FIRM DENSE / VERY DENSE ET / SATURATED / SUPER SATURATED OF PTS	D / SILT / SILTY CLAY / CLAY / GF PLASTICITY (CLAYS): NON PLASTIC / SLIGI DENSITY (COHESIVE CLAYS & S HC ODOR DETECTED: YES	HTLYPLASTIC/(ILTS): SOFT	COHESIVE/MEDIUM PLAST	Y STIFF / HARD
ANY AREAS DISPLAYING WETNESS: YES NO APPARENT EVIDENCE OF A RELEASE CADDITIONAL COMMENTS: GAS WELL IS SOIL IMPACT DIMENSION ESTIMATION:	BSERVED AND/OR OCCURRED: YES RECENTLY PLUGGED AND ABANDON	ED (P&A).		IMATION (Cubic Ya	ards): NA
DEPTH TO GROUNDWATER: >100' N SITE SKETCH P & A MARKER		PLOT PLAN circle: attack	ched OVM	CALIB. READ. =	D:
BERM BERM	(XXX)	PBGTL T.B. ~ 5' B.G. X - S.P.	P. P. P. O. Tar		COSJS 73-E 06/14/10 05/10/13 ic Vapor Meter per million sible: Y / N
	ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW; OW-GRADE TANK LOCATION; SPD = SAMPLE POINT C E WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; C	DESIGNATION; R.W. = RETAINING WALL; NA - I	NOT <u>N</u>	lagnetic declina	

Analytical Report

Lab Order 1306967

Date Reported: 7/1/2013

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 5' (95)

Project: Elliott GC S #1E

Collection Date: 6/20/2013 8:50:00 AM

Lab ID: 1306967-001

Matrix: SOIL

Received Date: 6/22/2013 11:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGE	ORGANICS				Analys	: JME
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	6/26/2013 2:59:06 AM	8058
Surr: DNOP	100	63-147	%REC	1	6/26/2013 2:59:06 AM	8058
EPA METHOD 8015D: GASOLINE RAN	GE				Analyst	: NSB
Gasoline Range Organics (GRO)	ND	4.6	mg/Kg	1	6/25/2013 7:21:58 PM	8070
Surr: BFB	90.2	80-120	%REC	1	6/25/2013 7:21:58 PM	8070
EPA METHOD 8021B: VOLATILES					Analyst	: NSB
Benzene	ND	0.046	mg/Kg	1	6/25/2013 7:21:58 PM	8070
Toluene	ND	0.046	mg/Kg	1	6/25/2013 7:21:58 PM	8070
Ethylbenzene	ND	0.046	mg/Kg	1	6/25/2013 7:21:58 PM	8070
Xylenes, Total	ND	0.093	mg/Kg	1	6/25/2013 7:21:58 PM	8070
Surr: 4-Bromofluorobenzene	104	80-120	%REC	1	6/25/2013 7:21:58 PM	8070
EPA METHOD 300.0: ANIONS					Analyst	: JRR
Chloride	ND	1.5	mg/Kg	1	6/25/2013 1:31:19 PM	8092
EPA METHOD 418.1: TPH					Analyst	: jmb
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	6/28/2013	8126

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDImit
- R RPD outside accepted recovery limits

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
 - Page 1 of 6
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1306967

01-Jul-13

Client:

Blagg Engineering

Project:

Elliott GC S #1E

Sample ID MB-8092

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID: PBS

Batch ID: 8092

RunNo: 11560

Prep Date: 6/25/2013

Analysis Date: 6/25/2013

SeqNo: 327531

Units: mg/Kg

Result

SPK value SPK Ref Val %REC LowLimit

HighLimit

RPDLimit

Qual

Analyte Chloride

PQL ND

Sample ID LCS-8092

SampType: LCS

RunNo: 11560

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

6/25/2013

Batch ID: 8092

SeqNo: 327532

Units: mg/Kg

%RPD

Prep Date: Analyte

Analysis Date: 6/25/2013

Result

14

%REC LowLimit

HighLimit

%RPD **RPDLimit**

Chloride

PQL 1.5

15.00

SPK value SPK Ref Val

92.8

Qual

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits

RSD is greater than RSDlimit 0

RPD outside accepted recovery limits R

Analyte detected in the associated Method Blank В

Holding times for preparation or analysis exceeded Н

ND Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

Reporting Detection Limit

Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1306967 01-Jul-13

Client:

Analyte

Blagg Engineering

Project:

Elliott GC S #1E

Sample ID MB-8126

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID:

PBS

Batch ID: 8126

PQL

20

RunNo: 11642

%REC LowLimit

Analysis Date: 6/28/2013

Result

ND

SeqNo: 330336

Units: mg/Kg

HighLimit

RPDLimit %RPD

Qual

Petroleum Hydrocarbons, TR

Prep Date: 6/26/2013

Batch ID: 8126

TestCode: EPA Method 418.1: TPH

Sample ID LCS-8126 Client ID: LCSS

SampType: LCS

RunNo: 11642

Prep Date:

6/26/2013

Analysis Date: 6/28/2013

SeqNo: 330337

101

Units: mg/Kg

Analyte Petroleum Hydrocarbons, TR Result PQL 100

97

SPK value SPK Ref Val

100.0

SPK value SPK Ref Val

%REC LowLimit

HighLimit

RPDLimit %RPD

Qual

SampType: LCSD

TestCode: EPA Method 418.1: TPH

120

Sample ID LCSD-8126

Batch ID: 8126

RunNo: , 11642

%REC

Units: mg/Kg

Analyte

Client ID:

Prep Date: 6/26/2013

LCSS02

Analysis Date: 6/28/2013

20

SeqNo: 330338

HighLimit %RPD 120

RPDLimit

Qual

Petroleum Hydrocarbons, TR

PQL SPK value SPK Ref Val 20

100.0

97.1

80

4.06

20

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits

RSD is greater than RSDIimit 0 RPD outside accepted recovery limits В

Holding times for preparation or analysis exceeded Н

ND Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

Reporting Detection Limit RL

Analyte detected in the associated Method Blank

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: **1306967**

01-Jul-13

Client:

Blagg Engineering

Project:	Elliott GO	C S #1E			•						
Sample ID	MB-8095	SampTy	/pe: M	BLK	Tes	tCode: E	PA Method	8015D: Dies	el Range (Organics	
Client ID:	PBS	Batch	ID: 80	95	F	RunNo: 1	1523				
Prep Date:	6/25/2013	Analysis Da	ate: 6	/25/2013	. 8	SeqNo: 3	26782	Units: %RE	C		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP		8.5		10.00		85.3	63	147			
Sample ID	LCS-8095	. SampTy	/pe: LC	cs	Tes	tCode: E	PA Method	8015D: Dies	el Range (Organics	
Client ID:	LCSS	Batch	ID: 80	95	F	RunNo: 1	1523				
Prep Date:	6/25/2013	Analysis Da	ate: 6	/25/2013	5	SeqNo: 3	26783	Units: %RE	C		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP		4.4		5.000		88.3	63	147			
Sample ID	MB-8058	SampTy	/pe: M I	BLK	Tes	tCode: E	PA Method	8015D: Dies	el Range (Organics	
Sample ID Client ID:		SampTy Batch				tCode: E l RunNo: 1		8015D: Dies	el Range (Organics	
	PBS	-	ID: 80	58	F		1523	8015D: Dies Units: mg/r	J	Organics	
Client ID:	PBS	Batch	ID: 80)58 /25/2013	F	RunNo: 1 SeqNo: 3	1523		J	Organics RPDLimit	Qual
Client ID: Prep Date: Analyte Diesel Range O	PBS 6/21/2013	Batch Analysis Da Result ND	ID: 80 ate: 6	958 /25/2013 SPK value	Fi S	RunNo: 1 SeqNo: 3 %REC	1523 27121 LowLimit	Units: mg/F HighLimit	(g	J	Qual
Client ID: Prep Date: Analyte	PBS 6/21/2013	Batch Analysis Da Result	ID: 80 ate: 6 . PQL	958 /25/2013 SPK value	Fi S	RunNo: 1 SeqNo: 3	1523 27121	Units: mg/h	(g	J	Qual
Client ID: Prep Date: Analyte Diesel Range O	PBS 6/21/2013 rganics (DRO)	Batch Analysis Da Result ND	ID: 80 ate: 6 PQL 10	958 /25/2013 SPK value 10.00	F S SPK Ref Val	RunNo: 1 SeqNo: 3 %REC 89.0	1523 27121 LowLimit 63	Units: mg/F HighLimit	(g %RPD	RPDLimit	Qual
Client ID: Prep Date: Analyte Diesel Range O Surr: DNOP	PBS 6/21/2013 rganics (DRO)	Batch Analysis Da Result ND 8.9	PQL 10	258 /25/2013 SPK value 10.00	SPK Ref Val	RunNo: 1 SeqNo: 3 %REC 89.0	1523 27121 LowLimit 63 PA Method	Units: mg/F HighLimit 147	(g %RPD	RPDLimit	Qual
Client ID: Prep Date: Analyte Diesel Range O. Surr: DNOP	PBS 6/21/2013 rganics (DRO) LCS-8058 LCSS	Batch Analysis Da Result ND 8.9 SampTy	ID: 80 PQL 10 rpe: LC	158 /25/2013 SPK value 10.00	SPK Ref Val Test	RunNo: 1 SeqNo: 3 %REC 89.0	1523 27121 LowLimit 63 PA Method 1523	Units: mg/F HighLimit 147	(g %RPD el Range (RPDLimit	Qual
Client ID: Prep Date: Analyte Diesel Range O Surr: DNOP Sample ID I Client ID:	PBS 6/21/2013 rganics (DRO) LCS-8058 LCSS	Batch Analysis Da Result ND 8.9 SampTy Batch	ID: 80 PQL 10 rpe: LC	25/2013 SPK value 10.00 CS 25/2013	SPK Ref Val Test	8unNo: 1 SeqNo: 3 %REC 89.0 CCode: El RunNo: 1 SeqNo: 3	1523 27121 LowLimit 63 PA Method 1523	Units: mg/F HighLimit 147 8015D: Diese	(g %RPD el Range (RPDLimit	Qual
Client ID: Prep Date: Analyte Diesel Range O Surr: DNOP Sample ID I Client ID: I Prep Date:	PBS 6/21/2013 rganics (DRO) LCS-8058 LCSS 6/21/2013	Batch Analysis Da Result ND 8.9 SampTy Batch Analysis Da	PQL 10 rpe: LC ID: 80 ate: 6.	25/2013 SPK value 10.00 CS 25/2013	SPK Ref Val Test	8unNo: 1 SeqNo: 3 %REC 89.0 CCode: El RunNo: 1 SeqNo: 3	1523 27121 LowLimit 63 PA Method 1523 27122	Units: mg/F HighLimit 147 8015D: Diese Units: mg/F	Kg %RPD el Range C	RPDLimit Organics	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

23

970

5.0

25.00

1000

WO#:

1306967

01-Jul-13

Client:

Blagg Engineering

Project:

Gasoline Range Organics (GRO)

Surr: BFB

Elliott GC S #1E

Sample ID MB-8070	SampType: MBLK	TestCode: EPA Method	8015D: Gasoline Rang	е
Client ID: PBS	Batch ID: 8070	RunNo: 11540		
Prep Date: 6/24/2013	Analysis Date: 6/25/2013	SeqNo: 327416	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Gasoline Range Organics (GRO)	ND 5.0			
Surr: BFB	910 1000	90.7 80	120	
Sample ID LCS-8070	SampType: LCS	TestCode: EPA Method	8015D: Gasoline Rang	e
Client ID: LCSS	Batch ID: 8070	RunNo: 11540		
Prep Date: 6/24/2013	Analysis Date: 6/25/2013	SeqNo: 327419	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual

0

91.5

96.8

62.6

80

136

120

Qualit	iers:
--------	-------

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1306967

01-Jul-13

Client: Project:

Blagg Engineering Elliott GC S #1E

Sample ID MB-8070 SampType: MBLK TestCode: EPA Method 8021B: Volatiles Client ID: PBS Batch ID: 8070 RunNo: 11540 Prep Date: 6/24/2013 Analysis Date: 6/25/2013 SeqNo: 327472 Units: mg/Kg Analyte Result **PQL** SPK value SPK Ref Val %REC LowLimit HighLimit %RPD **RPDLimit** Qual ND Benzene 0.050 Toluene ND 0.050 Ethylbenzene ND 0.050 Xylenes, Total ND 0.10 Surr: 4-Bromofluorobenzene 1.0 1.000 101 80 120

Sample ID LCS-8070 SampType: LCS TestCode: EPA Method 8021B: Volatiles										
Client ID: LCSS	F									
Prep Date: 6/24/2013	Analysis [Date: 6/	25/2013	SeqNo: 327473			Units: mg/h	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.97	0.050	1.000	0	97.0	80	120			
Toluene	0.95	0.050	1.000	. 0	94.6	80	120			
Ethylbenzene	0.96	0.050	1.000	0	96.4	80	120			
Xylenes, Total	2.9	0.10	3.000	0	97.9	80	120			
Surr: 4-Bromofluorobenzene	1 1		1 000		109	80	120			

Qualifiers:

* Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

O RSD is greater than RSDlimit

R RPD outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

P Sample pH greater than 2 for VOA and TOC only.

RL Reporting Detection Limit

Page 6 of 6



Han Environmeniai Analysis Lavoratory

4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: **BLAGG** Work Order Number: 1306967 RcptNo: 1 Received by/date: Logged By: Lindsay Mangin 6/22/2013 11:00:00 AM Completed By: Lindsay Mangin 6/24/2013 9:38:40 AM Reviewed By: plélzielin Chain of Custody Yes 🗌 1. Custody seals intact on sample bottles? No Not Present No 🗌 Yes 🗹 Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Courier Log In NA 🗌 4. Was an attempt made to cool the samples? Yes 🗸 No 🔲 5. Were all samples received at a temperature of >0° C to 6.0°C NA 🗆 Yes 🗸 No 🗌 6. Sample(s) in proper container(s)? Yes 🗸 No 7. Sufficient sample volume for Indicated test(s)? Yes V No □ ~ 8. Are samples (except VOA and ONG) properly preserved? Yes Yes No 🗹 NA 🔲 9. Was preservative added to bottles? 10.VOA vials have zero headspace? Yes 🗌 No 🗌 No VOA Vials No 🗹 11. Were any sample containers received broken? Yes # of preserved bottles checked Yes 🗹 No 🔲 for pH: 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? No 🗆 13. Are matrices correctly identified on Chain of Custody? ~ V No 🗌 14. Is it clear what analyses were requested? No 🗌 Checked by: \mathbf{Z} 15. Were all holding times able to be met? (If no, notify customer for authorization.) Special Handling (if applicable) Yes 🗌 16 Was client notified of all discrepancies with this order? No 🗆 NA 🗹 Person Notified: Date: By Whom: eMail Phone Fax In Person Via: Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Cooler No | Temp °C | Condition | Seal Intact | Seal No | Seal Date | Yes

Chain-of-Custody Record						HALL ENVIRONMENTAL															
Client:	ent: BLAGG ENGR. / BP AMERICA			Standard Project Name	Rush _													RA			
				ļ ´			-				ww	w.ha	allen	iviro	nme	ental	.con	n			
Mailing Address: P.O. BOX 87		ELLIOTT GC S # 1E				49	01 H	ławi	kins	NE -	Alk	ouqu	ierqi	ue, N	MI	37109	9				
BLOOMFIELD, NM 87413			Project #:				Tel. 505-345-3975 Fax 505-345-4107														
Phone #: (505) 632-1199								Analysis Request													
email or Fax#:			Project Manager:					nv					4				=				
QA/QC Package: Standard Level 4 (Full Validation)		NELSON VELEZ			MES (8021B)		1 4			15)		04,50	PCB's			er - 300.1}					
Accreditat	tion:			Sampler: NELSON VELEZ					_	ਜ਼	ਜ	SIR		02,1	087			wat			
□ NELAP □ Other		On lee: ∕≅ Yes □ No					d/c	418.	504.1)	8270SIMS)		S, S	8 / S		(A)	30.0		1	e sa		
□ EDD (1	Гуре)			Sample Temperature: 3.4					GRC	po od	bo	or 8	tals	Ž	ige	F	-\C). 		<u>e</u>	Sit
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEALING.	BTEX + NATE	BTEX + MTBE	TPH 8015B (GRO / DRO	TPH (Method 418.1)	EDB (Method	PAH (8310 or	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 / water		Grab sample	5 pt. composite sample
6/20/13	0850	SOIL	5PC-TB @ 5' (95)	4 oz 2	Cool	-001	٧		٧					-	-		-	V	7		V
																			\neg		
	 																		+	-	+
		<u> </u>		 															-		-
		 		 			-											\vdash	\dashv	-+	-
		 				<u> </u>												 	\dashv	-+	+
				<u> </u>														\dashv	\dashv	_	_
	<u> </u>							-			_							\vdash	\dashv	\dashv	+
				 												_		 	-	\dashv	
				<u> </u>				_										\vdash	-	-	
		ļ					_	-										\vdash	\dashv	_	_
		-					<u> </u>											$\vdash \downarrow$		_	_
			<u></u>	<u> </u>																	
Date: 6/21/13	Time: 1319	Relinguish	en of	Received by: Date Time Austra Welter 18/1/13/13/19				Remarks: BILL DIRECTLY TO BP: Jeff Peace, 200 Energy Court, Farmington, NM 87401													
Date:	Time: 1752	Relinquish	otre Walters	Received by: Date Time			Work Order: N1527/173 Paulou: 7EEIPKOSIS														



