District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, A District IV 1220 S. St. Francis Dr., Sa

# State of New Mexico **Energy Minerals and Natural Resources** Department

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and

	Dit Dalay Grada Tank or	
anta Fe, NM 87505	Santa Fe, NM 87505	Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
ZICC, INIVI 07410	1220 South St. Francis Dr.	For permanent pits submit to the Santa Fe
ztec, NM 87410	Oil Conservation Division	appropriate NMOCD District Office.
		multi-well fluid management pits, submit to the

Proposed Alternative Method Permit or Closure Plan Application  Type of action:   Below grade tank registration	
Proposed Alternative Method Permit or Closure Plan Application  Type of action:    Below grade tank registration	
Operator: BP America Production Company OGRID #:778 OIL CONS. DIV DIST. 3	
Address: _200 Energy Court, Farmington, NM 87401	
Facility or well name:Wilch A 3E	
API Number:3004525284OCD Permit Number:	
U/L or Qtr/QtrISection23 Township29NRange8WCounty:San Juan	
Center of Proposed Design: Latitude36.70837 Longitude107.64000 NAD: ☐1927 ☒ 1983	
Surface Owner:   Federal  State  Private  Tribal Trust or Indian Allotment	
☐ Pit:       Subsection F, G or J of 19.15.17.11 NMAC         Temporary:       ☐ Drilling       ☐ Workover         ☐ Permanent       ☐ Emergency       ☐ Cavitation       ☐ P&A       ☐ Multi-Well Fluid Management       Low Chloride Drilling Fluid       ☐ yes ☐ no         ☐ Lined       ☐ Unlined       Liner type:       Thicknessmil       ☐ LLDPE       ☐ HDPE       ☐ PVC       ☐ Other         ☐ String-Reinforced       Liner Seams:       ☐ Welded       ☐ Factory       ☐ Other       Volume:bbl       _ bbl       Dimensions:       Lx Wx D	
3.    Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A	
Volume:95.0bbl Type of fluid:Produced water	
Tank Construction material: Steel	
Secondary containment with leak detection  Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other Single walled/double bottomed	
Liner type: Thicknessmil	

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	1
☐ Signed in compliance with 19.15.16.8 NMAC	
8. <u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:  Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. ( <b>Does not apply to below grade tanks</b> )  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Wishing 200 G at Company and a state of the	
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
	163
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Natructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.5 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the dot attached.	cuments are
<ul> <li>□ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>□ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC</li> <li>□ A List of wells with approved application for permit to drill associated with the pit.</li> <li>□ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC</li> <li>□ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC</li> </ul>	.15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Previously Approved Design (attach copy of design) API Number: or Permit Number:	
or remember.	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached.  Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Climatological Factors Assessment  Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC  Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC  Quality Control/Quality Assurance Construction and Installation Plan  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan  Emergency Response Plan  Oil Field Waste Stream Characterization  Monitoring and Inspection Plan  Erosion Control Plan  Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	·
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative  Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be	
closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
<ul> <li>Within an unstable area.</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	
Within a 100-year floodplain FEMA map	☐ Yes ☐ No☐ Yes ☐ No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure pl by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann  Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17.  Operator Application Certification:  I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address:Telephone:	
OCD Approval: Permit Application (including glosure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature: Approval Date: 9/9/6  Title: OCD Permit Number:	2014
19.	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date:7/15/2014	
20.	
Siction Survers Method:  ☑ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo☐ If different from approved plan, please explain.	op systems only)
Closure Method:  ☑ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo	

Operator Closure Certification:	
	with this closure report is true, accurate and complete to the best of my knowledge and closure requirements and conditions specified in the approved closure plan.
benefit also certify that the closure compiles with an applicable	closure requirements and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Jeff Peace	Date:August 18, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

### BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

### BELOW-GRADE TANK CLOSURE PLAN

### Wilch A 3E API No. 3004525284 Unit Letter I, Section 23, T29N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

### **General Closure Plan**

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
  - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

### Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
_	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.** 

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.

    Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District 1 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

### State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	cation	n and Co	orrective A	etion	1 .			·
						OPERA?	ГOR		☐ Initia	al Report	$\boxtimes$	Final Repor
Name of Company: BP						Contact: Jef	f Peace					
Address: 200 Energy Court, Farmington, NM 87401						Telephone 1	No.: 505-326-94	179				
Facility Name: Wilch A 3E						Facility Typ	e: Natural gas'v	well				
Surface Owner: Federal Mineral Own						Federal			API No	. 3004525	284	
				LOCA	ATIO	N OF REI	LEASE					
Unit Letter I	Section 23	Township 29N	Range 8W	Feet from the 1,770		South Line	Feet from the 900	East/\ East	West Line	County: S	an Juan	
		Lati	tude36	5.70837		Longitude	107.764000_		<u> </u>			
				NAT	URE	OF RELI	EASE					
Type of Rele							Release: N/A			Recovered: 1		
Source of Re	lease: belov	v grade tank –	95 bbl				lour of Occurrenc	e:	Date and	Hour of Dis	covery:	N/A
Was Immedia	ate Notice (	liven?				N/A If YES, To	Whom?					
was minean	ate riotice (		Yes 🗀	No 🛛 Not Re	equired	11 125, 10	Whom:					
By Whom?						Date and H	lour					
Was a Water	course Read						lume Impacting t	he Wate	ercourse.			
ı			Yes 🛚	No								
		pacted, Descri										
the BGT. So	il analysis r	esulted in TPI	I, BTEX a	n Taken.* Samplin and chlorides belo	w stand	ards. Analys	is results are attac	ched.				
backfilled and	d compacte	d and is still w	ithin the ε	en.* BGT was reactive well area.								
regulations all public health should their contractions or the environ	I operators or the enviperations had not be a more of the contraction	are required to ronment. The lave failed to a	report an acceptance dequately CD accep	is true and comp id/or file certain re ee of a C-141 repo investigate and re tance of a C-141	elease no ort by the emediate	otifications ar e NMOCD ma e contaminati	nd perform correct arked as "Final R on that pose a thre	ctive acti eport" d eat to gr	ions for rele loes not reli ound water	eases which eve the ope surface wa	may en rator of iter, hur	danger Tiability nan health
		^					OIL CON	SERV	ATION	DIVISIO	<u>N</u>	
Signature: (	laft 1	ans.										
Printed Name	y or "		-			Approved by	Environmental S	pecialist	t:			
Title: Area E						Approval Dat	e:	]	Expiration l	Date:		
		effrey@bp.com	n			Conditions of	`Approval:			Attached		
Date: Augus	t 18, 2014		Phone	505-326-9479								

<sup>\*</sup> Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, B	NGINEERING, INC. LOOMFIELD, NM 874	113	TANK ID	045252	284
		05) 632-1199		(if applicble):	<u> </u>	
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OTHER:		PAGE #:	<b>1</b> of	1
SITE INFORMATION		A#3E		DATE STARTED:	07/10	)/14
	<b>29N</b> RNG: <b>8W</b> PM:	NM CNTY: SJ ST:	NM_	DATE FINISHED:		
1/4-1/4/FOOTAGE: 1,770'S / 900'		TYPE: FEDERAL STATE / FEE /		ENVIRONMENTAL		
		ONTRACTOR: MBF - T. GLYNN		SPECIALIST(S):	<u>NJ</u>	<u>V</u>
REFERENCE POINT	` '	S COORD.: 36.70868 X 1				
1) 95 BGT (SW/DB)	GPS COORD.: 3	6.70837 X 107.64000	DISTANCE/BEAF	RING FROM W.H.:	109.5', \$	S17W
2)				RING FROM W.H.:	•	
3)				RING FROM W.H.:		<del> </del>
			DISTANCE/BEAF	RING FROM W.H.:		OVM
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # 0					READING (ppm)
1) SAMPLE ID: <b>5 PC-TB @ 5'</b>					00.0 (CI)	NA
2) SAMPLE ID:						
3) SAMPLE ID:						
		SAMPLE TIME: LAB ANALY	-			
SOIL DESCRIPTION	SOIL TYPE: SAND / SILTY SAND /	SILT / SILTY CLAY / CLAY / GRAVEL / OTHE	R			
SOIL COLOR: DARK YELL		PLASTICITY (CLAYS): NON PLASTIC / SLIGHT				/ PLASTIC
COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC		DENSITY (COHESIVE CLAYS & SILTS): S HC ODOR DETECTED: YES NO EXPLANA				
MOISTURE: DRY SLIGHTLY MOIST MOIST / WI	ET / SATURATED / SUPER SATURATED					
SAMPLE TYPE: GRAB COMPOSITE #		ANY AREAS DISPLAYING WETNESS: YES	NO EXPLAN	ATION -		
DISCOLORATION/STAINING OBSERVED: YES N	<del></del>					
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE						
EQUIPMENT SET OVER RECLAIMED AREA:			SET ATOP B	GT POSITION.		
OTHER:						
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA	ft. X NA ft. EXCA	VATION EST	IMATION (Cubic Ya	ards) :	NA
DEPTH TO GROUNDWATER: >100' N	EAREST WATER SOURCE: >1,000	NEAREST SURFACE WATER: <b>&lt;20</b>	D' NMOC	D TPH CLOSURE ST	D: <u>100</u>	ppm
SITE SKETCH	BGT Located: off on sit	e PLOT PLAN circle: att	oched	CALIB. READ. = N	NA_ppm	RF =0.52
	1	ТО	<b>♦</b> ovm	CALIB. GAS =	<b>JA</b> ppm	
	PBGTL	N.H.	N TIME:	NA am/pm	DATE: N	IA
BERM	T.B. ~ 5' B.G.		'	MISCELL	NOTI	ES
			l w	o: <b>N1544</b> 5	976	
			P	O#:		
PROD.	X		<u>P</u> i			
TANK		SEPARATOR		#: <b>Z2-006</b>		
				ermit date(s):	06/14/1 03/27/1	
L			Tan		ic Vapor Meter	
	WOODEN TO EPHEMI R.W. WASH~		A A	1, 1, 2, 3, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4,		
	¥ VVASH ~	<sup>∞</sup> X - S		BGT Sidewalls Vis	sible: Y / N	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION	)N DEPRESSION; B.G. = BELOW GRADE; B = B	ELOW, T.H. = TEST HOLE; ~ = APPROX.; W.H. = WEI	L HEAD;	BGT Sidewalls Vis		
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELI APPLICABLE OR NOT AVAILABLE; SW - SINGLE		POINT DESIGNATION; R.W. = RETAINING WALL; NA TOM: DB - DOUBLE BOTTOM	· NOT   M	agnetic declinat	tion: 10°	<u>E</u>
NOTES: GOOGLE FARTH IMAGE		ONSITE: 07/14/14	!			

### **Analytical Report**

### Lab Order 1407509

Date Reported: 7/15/2014

## Hall Environmental Analysis Laboratory, Inc.

**CLIENT:** Blagg Engineering

Client Sample ID: 5PC-TB@5' (95)

**Project:** WILCH A #3E

**Collection Date:** 7/10/2014 3:03:00 PM

**Lab ID:** 1407509-001

Matrix: MEOH (SOIL) Received Date: 7/11/2014 7:55:00 AM

Analyses	Result	RL Qu	al Units	DF Date Analyzed Ba	itch
EPA METHOD 8015D: DIESEL RANGE	ORGANICS			Analyst: <b>B</b> C	ON.
Diesel Range Organics (DRO)	ND	10	mg/Kg	1 7/11/2014 11:11:11 AM 14	178
Surr: DNOP	82.0	57.9-140	%REC	1 7/11/2014 11:11:11 AM 14	178
EPA METHOD 8015D: GASOLINE RAN	GE			Analyst: <b>NS</b>	3B
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1 7/11/2014 10:23:43 AM R1	19836
Surr: BFB	90.3	80-120	%REC	1 7/11/2014 10:23:43 AM R1	19836
EPA METHOD 8021B: VOLATILES				Analyst: <b>NS</b>	SB
Benzene	ND	0.047	mg/Kg	1 7/11/2014 10:23:43 AM R1	19836
Toluene	ND	0.047	mg/Kg	1 7/11/2014 10:23:43 AM R1	19836
Ethylbenzene	ND	0.047	mg/Kg	1 7/11/2014 10:23:43 AM R1	19836
Xylenes, Total	ND	0.095	mg/Kg	1 7/11/2014 10:23:43 AM R1	19836
Surr: 4-Bromofluorobenzene	99.3	80-120	%REC	1 7/11/2014 10:23:43 AM R1	19836
EPA METHOD 300.0: ANIONS				Analyst: SR	۲M
Chloride	ND	30	mg/Kg	20 7/11/2014 9:03:46 AM 14	177
EPA METHOD 418.1: TPH				Analyst: BC	CN
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1 7/11/2014 4:00:00 PM 14	179

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDIimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 5

- P Sample pH greater than 2.
- RL Reporting Detection Limit

## Hall Environmental Analysis Laboratory, Inc.

110

20

WO#:

2.55

1407509

15-Jul-14

Client:

Petroleum Hydrocarbons, TR

Blagg Engineering

Project: WILCH	H A #3E			
Sample ID MB-14179	SampType: MBLK	TestCode: EPA Method	418.1: TPH	
Client ID: PBS	Batch ID: 14179	RunNo: 19833		•
Prep Date: 7/11/2014	Analysis Date: 7/11/2014	SeqNo: <b>576228</b>	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	ND 20			
Sample ID LCS-14179	SampType: LCS	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS	Batch ID: 14179	RunNo: 19833		
Prep Date: 7/11/2014	Analysis Date: 7/11/2014	SeqNo: 576229	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	100 20 100.0	0 103 80	120	
Sample ID LCSD-14179	SampType: LCSD	TestCode: EPA Method	418.1: TPH	
Client ID: LCS\$02	Batch ID: 14179	RunNo: 19833		
Prep Date: 7/11/2014	Analysis Date: 7/11/2014	SeqNo: <b>576230</b>	Units: mg/Kg	
Analyte	Result POI SPK value	SPK Ref Val. %REC. Lowlimit	HighLimit %RPD	RPDLimit Qual

### Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

O RSD is greater than RSDlimit

R RPD outside accepted recovery limits

S Spike Recovery outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

P Sample pH greater than 2.

RL Reporting Detection Limit

Page 2 of 5

## Hall Environmental Analysis Laboratory, Inc.

3.7

WO#:

1407509

15-Jul-14

Client: Project:

Surr: DNOP

Blagg Engineering

WILCH A #3E

Sample ID MB-14178	SampType	: MBLK	Tes	PA Method	1 8015D: Diesel Range Organics							
Client ID: PBS	Batch ID:	Batch ID: 14178 RunNo: 19825										
Prep Date: 7/11/2014	Analysis Date:	7/11/2014	SeqNo: <b>576053</b> Ur			Units: mg/k						
Analyte	Result P	Result PQL SPK value SPK Ref Val %REC LowLimit Hip				HighLimit	%RPD	RPDLimit	Qual			
Diesel Range Organics (DRO)	ND	10										
Surr: DNOP	7.7	10.00		76.7	57.9	140						
Sample ID LCS-14178	SampType	: LCS	Test	tCode: EF	PA Method	8015D: Dies	el Range (	Organics				
Client ID: LCSS	Batch ID:	14178	R	RunNo: <b>1</b> 9	9825							
Prep Date: 7/11/2014	Analysis Date:	7/11/2014	SeqNo: <b>576075</b>			Units: mg/K	(g					
Analyte	Result P	QL SPK value	SPK Ref Val %REC LowLimit H		HighLimit	%RPD	RPDLimit	Qual				
Diesel Range Organics (DRO)	48	10 50.00	0	96.0	68.6	130		-				

Sample ID 1407509-001AM	<b>S</b> Samp1	Type: MS	8	Tes	8015D: Diese	el Range (	Organics							
Client ID: 5PC-TB@5' (95)	Batcl	h ID: <b>14</b>	178	F	RunNo: 1	9825								
Prep Date: 7/11/2014	Analysis D	)ate: <b>7</b> /	11/2014	SeqNo: <b>576222</b>			Units: mg/Kg							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Diesel Range Organics (DRO)	47	9.8	49.16	0	95.9	40.1	152							
Surr: DNOP	3.7		4.916		74.5	57.9	140							

73.9

57.9

140

5.000

Sample ID 1407509-001AMS	D SampT	уре: <b>М</b>	SD	TestCode: EPA Method 8015D: Diesel Range Organics										
Client ID: 5PC-TB@5' (95)	Batch	ID: <b>14</b>	178	F	RunNo: 19825									
Prep Date: 7/11/2014	Analysis D	ate: 7/	11/2014	SeqNo: <b>576233</b>			Units: mg/Kg							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Diesel Range Organics (DRO)	47	10	50.00	0	94.7	40.1	152	0.391	32.1					
Surr: DNOP	3.8		5.000		75.1	57.9	140	0	0					

### Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits

RSD is greater than RSDlimit O

RPD outside accepted recovery limits R

Spike Recovery outside accepted recovery limits

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Η

ND Not Detected at the Reporting Limit

Sample pH gréater than 2.

Page 3 of 5

Reporting Detection Limit

### Hall Environmental Analysis Laboratory, Inc.

WO#:

1407509

15-Jul-14

Client: Project: Blagg Engineering WILCH A #3E

Sample ID MB-14171 MK

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID:

**PBS** 

Batch ID: R19836

PQL

5.0

RunNo: 19836

Prep Date:

Analyte

Analysis Date: 7/11/2014

SeqNo: 576988

%REC

Units: mg/Kg

Qual

Gasoline Range Organics (GRO)

Surr: BFB

ND 880

Result

1000

SPK value SPK Ref Val

88.0

120

HighLimit

**RPDLimit** 

%RPD

%RPD

Qual

Sample ID LCS-14171 MK

SampType: LCS

TestCode: EPA Method 8015D: Gasoline Range

Client ID: LCSS

Batch ID: R19836

RunNo: 19836

Prep Date:

Analysis Date: 7/11/2014

SeqNo: 577048

Units: mg/Kg

**RPDLimit** 

Analyte Gasoline Range Organics (GRO)

25

Result

SPK value SPK Ref Val PQL 5.0 25.00

%REC 101

0

71.7

HighLimit 134 120

Surr: BFB

980

1000

98.3

80

LowLimit

LowLimit

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Е Value above quantitation range
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2. Reporting Detection Limit RL

Page 4 of 5

## Hall Environmental Analysis Laboratory, Inc.

WO#:

1407509

15-Jul-14

Client:

Blagg Engineering

Project:

WILCH A #3E

Sample ID MB-14171 MK	Samp	SampType: MBLK TestCode: EPA Method						d 8021B: Volatiles										
Client ID: PBS	Batcl	Batch ID: <b>R19836</b> RunNo: <b>19836</b>																
Prep Date:	Analysis [	Date: <b>7</b> /	11/2014	SeqNo: <b>577078</b>			Units: mg/Kg											
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual								
Benzene	ND	0.050							,									
Toluene	ND	0.050																
Ethylbenzene	ND	0.050																
Xylenes, Total	ND	0.10																
Surr: 4-Bromofluorobenzene	0.95		1.000		95.1	80	120											
Sample ID LCS-14171 MK	SampType: LCS TestCode: EPA Method 8021B: Volatiles																	

Sample ID LCS-14171 MK	Samp <sup>-</sup>	Type: LC	s	Tes	PA Method	ethod 8021B: Volatiles									
Client ID: LCSS	Batc	h ID: <b>R1</b>	9836	F	RunNo: 1	9836									
Prep Date:	Analysis [	Date: <b>7</b> /	11/2014	SeqNo: <b>577079</b> l			Units: mg/k	(g							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Benzene	1.1	0.050	1.000	0	106	80	120			,					
Toluene	1.0	0.050	1.000	0	101	80	120								
Ethylbenzene	1.0	0.050	1.000	0	101	80	120								
Xylenes, Total	3.1	0.10	3.000	0 102 80		120									
Surr: 4-Bromofluorobenzene	1.1		1.000		105	80	120								

Sample ID 1407509-001AM	ISD Samp	Туре: М	SD	TestCode: EPA Method 8021B: Volatiles											
Client ID: 5PC-TB@5' (95)	) Batcl	h ID: <b>R1</b>	9836	F	RunNo: 1	9836									
Prep Date:	Analysis [	Analysis Date: 7/11/2014			SeqNo: <b>577082</b>			(g							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Benzene	0.98	0.047	0.9461	0	104	77.4	142	40.9	20	R					
Toluene	0.94	0.047	0.9461	0	99.1	77	132	40.9	20	R					
Ethylbenzene	0.94	0.047	0.9461	0	99.6	77.6	134	39.8	20	R					
Xylenes, Total	2.9	0.095	2.838	0 102 77.4			132	39.8	20	R					
Surr: 4-Bromofluorobenzene	1.0		0.9461		107	80	120	0	0						

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 5 of 5



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107

Website: www.hallenvironmental.com

# Sample Log-In Check List

Client Name: BLAGG	Work Order Number:	1407509		RcptN	lo: 1
Received by/date:	oghelich				
Logged By: Lindsay Mangin	7/11/2014 7:55:00 AM		James Hougo		
: Completed By: Lindsay Mangin	7/11/2014 7:57:09 AM		Junely Hope		
Reviewed By: AT 0//1/14			000		
Chain of Custody					
11 Custody seals intact on sample bottles?		Yes :	No	Not Present	•
2. Is Chain of Custody complete?		Yes 🗸	No l.i	Not Present	
3. How was the sample delivered?		Courier			
Log In					
4. Was an attempt made to cool the samples?		Yes 🗹	No :	NA	;
5. Were all samples received at a temperature	of >0° C to 6.0°C	Yes 🗸	No!	NA	
6. Sample(s) in proper container(s)?		Yes 🗸	No		
7. Sufficient sample volume for indicated test(s	)?	Yes 🗸	No 🗀		
8. Are samples (except VOA and ONG) proper	ly preserved?	Yes 🗸	No !		
9. Was preservative added to bottles?		Yes 🗔	No 🗸	NA .	
10.VOA vials have zero headspace?		Yes 🗀	No L	No VOA Vials	•
11. Were any sample containers received broke	en?	Yes	No 🗸	# of preserved	
		·	į	bottles checked	
12. Does paperwork match bottle labels? (Note discrepancies on chain of custody)		Yes 🗸	No ! .	for pH: (<	2 or >12 unless noted)
13. Are matrices correctly identified on Chain of	Custody?	Yes 🗸	No . i	Adjusted?	· · · · · · · · · · · · · · · · · ·
14. Is it clear what analyses were requested?	<b>,</b>	Yes 🗹			
15. Were all holding times able to be met?		Yes 🗸	No 🗓	Checked by	<b>y</b> :
(If no, notify customer for authorization.)			;		•
Special Handling (if applicable)					
16. Was client notified of all discrepancies with t	his order?	Yes	No	NA N	•
Person Notified:	Date:	in militari a di la di man	and the latest desired Address Mean In Property Control for the Add Add Add Add Add Add Add Add Add Ad		
By Whom:	Via: [	, i eMail	[ j Phone ⋅  Fax	: In Person	
Regarding:		alangaha an ing anganganga anganga			•
Client Instructions:					
17. Additional remarks:					
18. Cooler Information					
		Seal Date	Signed By		
1 2.7 Good Yes		······································			

V	Chair-or-custody Necord		_		FRIME	HALL ENVIRONMENTAL										ı				
Client:	BLAG	G ENGR.	. / BP AMERICA	Standard	Rush _	DUA					NA									
				Project Name						٧	vww.	halle	envir	onme	enta	l.con	n			
Mailing A	ddress:	P.O. BO	X 87	WIL	CH A #	13E		49	01 Ha	awki	ns NE	: - A	lbuc	uerq	ue, l	3 MV	3710	9		
		BLOOM	FIELD, NM 87413	Project #:				Τe	1. 50	5-34	5-397	75	Fax	505	-345	5-410	)7			
Phone #:		(505) 63	32-1199						-			Ān.	alysi	s Re	que	st.				
email or F				Project Manager:					nu	_			13	S	İ		0.1)			
QA/QC Pad  Standa			Level 4 (Full Validation)	NELSON VELEZ			(8021B)	only)	TANKO)		2	2	25,00	PCB's			er - 300.1)			
Accreditat	tion:			Sampler:	NELSON VI	ELEZ W	F	(Gas	$\sim 1$	ਜ	504.1)	<u> </u>	် ဝို	8087			/ wat			d E
□ NELAF	)	□ Other	·	Onlice	1/Yes	□ No :		뮵		418	중   5		.၂ ်	S		(A)	0.00			e sa
□ EDD (Type)		Samplexemp	erature: 2 1	4	t	+ 1	GRC	g	g   g	5   <u>T</u>	Ž	ide	12	-\C	1-3(		<u>u</u>	osit		
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL No:	BTEX +-NHTB	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO	TPH (Method 418.1)	EDB (Method 504.1)	RCRA & Motals	Anions (F.Cl. NO. NO. PO. SO.)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 / water		Grab sample	5 pt. composite sample
07/10/14	1503	SOLL	5PC-TBC5' (95)	402-1	CooL	-01	V		1	1	_	1				~	<u>/</u>	$\dashv$	-	<b>\</b>
						1 <del></del>	T		1	+		十	$\dagger$	<del> </del>				_	$\dashv$	+
				<u> </u>			╁┈		_		-	+	+				-	+	$\dashv$	$\dashv$
	<del> </del>						<del> </del>				+	+-	+					$\dashv$	+	$\dashv$
							╁			$\dashv$	-	+	╁	+-	-	-		$\dashv$	<del> </del> -	$\dashv$
							<del> </del>			$\dashv$		+	+-	+				$\dashv$	+	+
			-				1-		$\dashv$	$\dashv$	$\dashv$	+	+	-		<u> </u>		$\dashv$	十	$\dashv$
												1	+	1				$\top$	+	_
																				十
																		寸		$\top$
																				丁
Date:	Time:	Relinquish	led by:	Received by: Date Time				Remarks:												
01/10/14	1602	16	les of	Monst	whall	10/14/40			RECTL			<b>~</b>	. P	14						
Date:				Received by:  Date Time					Jeff Peace, 200 Energy Court, Farmington, NM 87401 Work Order: <u>NIS445976</u> Paykey: そだい代の18672									<u>ā</u>		
	17 1 10 11 MILLION CALL TOTAL AVE			subcontracted of other accredited laboratories. This serves as notice of				this possibility. Any sub-contracted data will be clearly notated on the analytical report.												



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

May 5, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

### VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: WILCH A 003E

API#: 3004525284

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about July 3, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

90 Vel/2

Surface Land Negotiator

**BP America Production Company** 

### **BP America Production Company**

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

### SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

May 7, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

WILCH A 003E API 30-045-25284 (G) Section 23 – T29N – R08W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



