District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #:
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Atlantic LS 17
API Number:3004523574OCD Permit Number:
U/L or Qtr/Qtr L Section 24 Township 31N Range 10W County: San Juan
Center of Proposed Design: Latitude36.881151Longitude107.839538NAD: ☐1927 ☒ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Drilling Workover Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Volume: 21.0 bbl Type of fluid: Produced water
Tank Construction material:Steel Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Single walled/double bottomed; side walls not visible
Liner type: Thickness mil
4. Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

5.	
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet	hospital,
Alternate. Please specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	otable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	,
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Temporary Pit Non-low chloride drilling fluid Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site Aerial photo; Satellite image Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Permanent Pit or Multi-Well Fluid Management Pit Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet of a wetland. Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application	No
watering purposes, or 300/feet of any other fresh water well or spring, in existence at the time of the initial application. Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Permanent Pit or Multi-Well Fluid Management Pit Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet for a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet form a permanent residence, schoo	No
Temporary Pit Non-low chloride drilling fluid Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet of a sentence of the state Engineer - IWATERS database search; Visual inspection (certification) of the proposed site Within 300 feet of a sentence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - IWATERS database search; Visual inspection (certification) of the proposed site Permanent Pit or Multi-Well Fluid Management Pit Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 500 feet of a permanent residence, school, hospital, institution, or church in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within 500 feet of a wetland.	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of a weltand. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Permanent Pit or Multi-Well Fluid Management Pit Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site, Aerial photo; Satellite image Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife W	No
or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Permanent Pit or Multi-Well Fluid Management Pit Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Ves Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19,15,17.9 NMAC Instructions: Each of the following items must be attached to t	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Permanent Pit or Multi-Well Fluid Management Pit Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within 500 feet of a wetl	
Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Permanent Pit or Multi-Well Fluid Management Pit Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within	No
watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Permanent Pit or Multi-Well Fluid Management Pit Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Yes Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application. Attachment Checklist: Subsection B of 19.15.17.9 NMAC Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application. Please indicate, by a check mark in the box, that the documents are attached.	No
Permanent Pit or Multi-Well Fluid Management Pit Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.	No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes 10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.	No
lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes 10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.	
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.	No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes □ Yes □ Yes □ Yes □ Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site □ Yes □ Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.	INU
initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.	No
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes 10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes 10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.	No
<u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 NMAC <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.</i>	No
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMA and 19.15.17.13 NMAC	.C
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are	
attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Compliance Departments of Paragraph appropriate requirements of 10.15.17.10 NMAC	A C
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	

Personated Bits Permit Augulation Cheeckins: Subsection B of 19.15.17.3 NMAC		
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fluid Management Pit Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) On-site Closure Method Maste Removal (Closed-loop systems only) On-site Closure Method Maste Excavation and Removal Closure Method On-site Trench Burial O	Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fluid Management Pit Alternative Alternative Waste Excavation and Removal Waste Excavation and Removal Closed-loop systems only)		
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation of Plan appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation of Plan appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation of Plan appropriate requirements	Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial	luid Management Pit
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Yes No Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Yes \ No Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	15.	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency.	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No No		
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site NA		
lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No		
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality □ Yes □ No Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site □ Yes □ No	lake (measured from the ordinary high-water mark).	Yes No
at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No		☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No	at the time of initial application.	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No		☐ Vec ☐ No
	Within 300 feet of a wetland.	
		Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality	
11	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map Within a 100-year floodplain.	☐ Yes ☐ No
- FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ef.
Name (Print): Title:	
Signature: Date:	
Signature: Date: e-mail address: Telephone:	
e-mail address:	the closure report.
e-mail address: Telephone:	the closure report.

22. Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirem	eport is true, accurate and complete to the best of my knowledge and ents and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Name (Print):Jeff Peace	Date:September 25, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Atlantic LS 17 Tank B BGT (21 bbl) API No. 3004523574 Unit Letter L, Section 24, T31N, R10W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT, Tank B	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141** is attached.
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and will be reclaimed with the rest of the site since the well has been plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT will be reclaimed with the rest of the site as part of final reclamation since the well has been plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT will be reclaimed with the rest of the site as part of final reclamation since the well has been plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT will be reclaimed with the rest of the site as part of final reclamation since the well has been plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation since the well has been plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following:
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.
 - Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notifi	catio	n and Co	orrective A	ction				
						OPERA	ГOR	[Initia	al Report		Final Report
Name of Co	_ 					Contact: Jef						
Address: 20 Facility Na		Court, Farmi	ington, N	M 87401			No.: 505-326-94					
Facility Na	me: Atlant	IC LS 17				Facility Typ	e: Natural gas v	well		 		
Surface Ow	ner: Priva	te		Mineral (Owner:	Private			API No	. 30045235	74	
				LOC	ATIO	N OF REI	LEASE					
Unit Letter L	Section 24	Township 31N	Range 10W	Feet from the 1,680		/South Line	Feet from the 965	East/W West	est Line	County: Sa	ın Juan	
		Latit	ude36	.881151		Longitud	e107.839538			·		
	·			NAT	ΓURE	OF REL						
Type of Rele		u anada tanlı	21 hh m	ands D			Release: N/A			Recovered: N		
Was Immedi		w grade tank – Given?	- 21 bbi, I	ank B		If YES, To	lour of Occurrence	ce:	Date and	Hour of Disc	covery:	
was mineur			Yes [] No 🛛 Not R	equired.		Whom:					
By Whom?						Date and I-						
Was a Water	course Read		Yes 🗵] No		If YES, Vo	olume Impacting t	the Water	course.			
If a Waterco	ırse was Im	pacted, Descr	ibe Fully.	*								
the BGT. So	il analysis r	resulted in TPI	н, втех	and chloride belo	w stand	lards. Analysi	the BGT was do s results are attacl	hed.				
							nderneath the BG as been plugged			he excavated	area wa	1S
			_									
regulations a public health should their or or the enviro	Il operators or the envi- operations homent. In a	are required to ronment. The nave failed to a	o report ar acceptand adequately OCD accep	nd/or file certain to be of a C-141 reportant investigate and i	release r ort by th remedia	notifications and ne NMOCD m te contaminati	knowledge and und perform correct arked as "Final R on that pose a three the operator of the correct arked as "Final R" on the correct arked as "Final R" on the correct arked	ctive actio eport" do eat to gro	ons for rele es not reli ound water	eases which in every the operations are the operations are the operations.	may end ator of l ter, hum	langer iability an health
	_						OIL CON	SERVA	ATION	DIVISIO	N	
Signature:	Iff 1	James				Approved by	Environmental S	nacialist:				
Printed Name	e: Jeff Peac	e				Approved by		pecialist.				
Title: Area E	nvironment	al Advisor				Approval Dat	e:	E	xpiration :	Date:		
E-mail Addr	ess: peace.jo	effrey@bp.cor	n			Conditions of	f Approval:			Attached		
Date: Septer Attach Addi		014 ets If Necess		one: 505-326-947	79	·						

CLIENT: BP		G ENGINE B7, BLOOM	,		API#: 30 (04523574
OLIENI.	1.0. DOX 0	•	,	107413	TANK ID (if applicble):	A& B
FIELD REPORT:	(circle one): BGT CONFIRM	IATION / RELEASE IN	/ESTIGATION / OT	THER:	PAGE #:	1 of 1
			,	N TO S	DATE STARTED:	07/29/13
					DATE FINISHED:	
	·		ELKHORN		ENVIRONMENTAL SPECIALIST(S):	JCB
				7 X 1 <u>07.83968</u>	GL ELE	,
· · · · · · · · · · · · · · · · · · ·					_	
3)	GPS COORD.: _	0010011017	1071000000		_	00,0101
4)	GPS COORD.: _			DISTANCE/BE	ARING FROM W.H.;	
SAMPLING DATA:	CHAIN OF CUSTODY RECOR	RD(S) # OR LAB USED:	HALL			OVM READING
l ' —						10:0(OI) 0:0
						0.0(CI) 0.0
· ·						

		SILTY SAND / SILT	SILTY CLAY / CL	LAY / GRAVEL / OT	HER	
		OHESIVE PLAS	ICITY (CLAYS): NON PLAS	STIC / SLIGHTLY PLASTIC / (COHESIVE / MEDIUM PLASTI	IC / HIGHLY PLASTIC
CONSISTENCY (NON COHESIVE SOILS): LC	OSE FIRM DENSE / VERY D	DENSE DEN	, ,			
		RATED HC (DOOR DETECTED); YES NO EXPL	ANATION	
		<u></u> -				
	BSERVED AND/OR OCCUR	RRED: YES INO E	XPLANATION :			
DEPTH TO GROUNDWATER: <50' N					•	
SITE SKETCH	\oplus	PLC	TPLAN circle	e: attached 0VM	CALIB. READ. = 100).1 ppm RF = 1.00
	P& A MARKER			1 1		
	MARKER			N TIME		
				1		
						747
				-		06 16
			/24\	_		06/02/10
		(x x x)	PBGTL	00	CD Appr. date(s):	06/28/11
		X	1.B. ~ 6' B.G.			er million
			•			
FIELD REPORT: (circle one): GST COMPRIATION: RELEASE INVESTIGATION / OTHER PAGE # 1 of 1 SITE INFORMATION: SITE MAKE ATLANTIC LS #17 QUADUNIT: L SEC 24 TWP: 31N RNs 10W PM NM CNTY SJ ST NM DIFFENSHED MINISTRUM: LEASE #PC FEBERAL/STATE [FEE INDIAN BECAUSTRY] LEASE # PROD. FORMATION: PC CONTROLOR: MIST C. DAVIS REFERENCE POINT: WELL HEAD (WH) (98 COORD: 36.88137 X 107.83968 G. ELEV. 6.448' 1) 36 BST (SWIDS): A GPS COORD: 36.881151 X 107.839538 GISTACLESS/RIGHT STATE WITH STATE OF THE STA						
				.H. = WELL HEAD; L	i i	
APPLICABLE OR NOT AVAILABLE; SW - SINGLE		NGLE BOTTOM; DB - DOUBL	E BOTTOM.		iagnetic decimat	IOI I. IU C
TRAVEL NOTES: CALLOUT:		ON	SITE: <u>07/2</u>	9/13		

Analytical Report

Lab Order 1307D69

Date Reported: 8/6/2013

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 21 BGT 5-pt @ 6'

Project: Atlantic LS 17

Collection Date: 7/29/2013 9:49:00 AM

Lab ID: 1307D69-001

Matrix: SOIL

Received Date: 7/30/2013 10:01:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGE	ORGANICS	-			Analysi	: JME
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	8/2/2013 5:11:50 AM	8651
Surr: DNOP	73.6	63-147	%REC	1	8/2/2013 5:11:50 AM	8651
EPA METHOD 8015D: GASOLINE RAN	IGE				Analyst	:: NSB
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	8/2/2013 12:17:58 AM	8655
Surr: BFB	87.3	80-120	%REC	1	8/2/2013 12:17:58 AM	8655
EPA METHOD 8021B: VOLATILES					Analyst	:: NSB
Benzene	ND	0.047	mg/Kg	1	8/2/2013 12:17:58 AM	8655
Toluene	ND	0.047	mg/Kg	1	8/2/2013 12:17:58 AM	8655
Ethylbenzene	ND	0.047	mg/Kg	1	8/2/2013 12:17:58 AM	8655
Xylenes, Total	ND	0.094	mg/Kg	1	8/2/2013 12:17:58 AM	8655
Surr: 4-Bromofluorobenzene	98.3	80-120	%REC	1	8/2/2013 12:17:58 AM	8655
EPA METHOD 300.0: ANIONS					Analyst	:: JRR
Chloride .	ND	1.5	mg/Kg	1	8/2/2013 11:08:18 AM	8696
EPA METHOD 418.1: TPH					Analyst	:: LRW
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	8/1/2013	8654

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
 - Page 1 of 7
 - P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1307D69

06-Aug-13

Client:

Blagg Engineering

Project:

Atlantic LS 17

Sample ID: MB-8696

Prep Date: 8/2/2013

Sample ID: LCS-8696

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 8696

RunNo: 12405

SeqNo: 353018

Units: mg/Kg

Analyte

Result

Analysis Date: 8/2/2013

SPK value SPK Ref Val %REC LowLimit

RPDLimit

Client ID:

PQL

1.5

HighLimit

%RPD

Qual

Chloride

ND

SampType: LCS Batch ID: 8696

RunNo: 12405

TestCode: EPA Method 300.0: Anions

LowLimit

Units: mg/Kg

Analyte

Prep Date: 8/2/2013

LCSS

Analysis Date: 8/2/2013

PQL

1.5

SPK value SPK Ref Val

%REC 96.0

SeqNo: 353019

HighLimit 110 %RPD

Qual

Chloride

Result 14

15.00

RPDLimit

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range Ε

Analyte detected below quantitation limits

RSD is greater than RSDlimit 0

RPD outside accepted recovery limits

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Н

ND Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

Reporting Detection Limit RL

Page 3 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#: 1307D69

06-Aug-13

Client:

Blagg Engineering

Project:

Analyte

Atlantic LS 17

Sample ID: MB-8654

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID:

PBS

Batch ID: 8654

RunNo: 12331

Prep Date: 7/31/2013

Analysis Date: 8/1/2013

PQL

SeqNo: 350879

SPK value SPK Ref Val %REC LowLimit

Units: mg/Kg

%RPD

RPDLimit

Qual

Petroleum Hydrocarbons, TR

ND 20

Result

Sample ID: LCS-8654

SampType: LCS

TestCode: EPA Method 418.1: TPH

80

%RPD

HighLimit

Prep Date: 7/31/2013

Client ID: LCSS

Batch ID: 8654

RunNo: 12331

SeqNo: 350880

Units: mg/Kg

Qual

Analyte Petroleum Hydrocarbons, TR

Analysis Date: 8/1/2013 PQL Result

99

Result

100

SPK value SPK Ref Val

100.0

%REC 99.4

LowLimit

HighLimit

120

RPDLimit

Sample ID: LCSD-8654

SampType: LCSD

20

TestCode: EPA Method 418.1: TPH RunNo: 12331

120

Client ID: Prep Date: 7/31/2013

LCSS02

Batch ID: 8654 Analysis Date: 8/1/2013

20

SeqNo: 350881

%REC

Units: mg/Kg HighLimit

RPDLimit Qual

Analyte Petroleum Hydrocarbons, TR

PQL

SPK value SPK Ref Val

100.0

101

0

LowLimit

80

%RPD

20

1.38

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range Е

Analyte detected below quantitation limits

RSD is greater than RSDImit 0 RPD outside accepted recovery limits Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

Reporting Detection Limit RL

Page 4 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#:

1307D69

06-Aug-13

Client:

Blagg Engineering

Project:

Project: Atlanti	ic LS 17	
Sample ID: MB-8598	SampType: MBLK TestCode: EPA Method 8015D: Diesel Range Organics	
Client ID: PBS	Batch ID: 8598 RunNo: 12312	
Prep Date: 7/29/2013	Analysis Date: 7/31/2013 SeqNo: 350434 Units: %REC	
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qu	ıal
Surr: DNOP	7.4 10.00 73.7 63 147	
Sample ID: LCS-8598	SampType: LCS TestCode: EPA Method 8015D: Diesel Range Organics	
Client ID: LCSS	Batch ID: 8598 RunNo: 12312	
Prep Date: 7/29/2013	Analysis Date: 7/31/2013 SeqNo: 350435 Units: %REC	
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qu	al
Surr: DNOP	3.5 5.000 70.2 63 147	
Sample ID: MB-8651	SampType: MBLK TestCode: EPA Method 8015D: Diesel Range Organics	
Client ID: PBS	Batch ID: 8651 RunNo: 12312	
Prep Date: 7/31/2013	Analysis Date: 8/2/2013 SeqNo: 351592 Units: mg/Kg	
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qua	al
Diesel Range Organics (DRO)	ND 10	
Surr: DNOP	7.2 10.00 71.8 63 147	
Sample ID: LCS-8651	SampType: LCS TestCode: EPA Method 8015D: Diesel Range Organics	
Client ID: LCSS	Batch ID: 8651 RunNo: 12312	
Prep Date: 7/31/2013	Analysis Date: 8/2/2013 SeqNo: 351593 Units: mg/Kg	
Analyte	Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qui	al
Diesel Range Organics (DRO)	37 10 50.00 0 73.4 77.1 128 S	
Surr: DNOP	3.0 5.000 59.9 63 147 S	
Sample ID: LCS-8651	SampType: LCS TestCode: EPA Method 8015D: Diesel Range Organics	
Client ID: LCSS	Batch ID: 8651 RunNo: 12371	
Prep Date: 7/31/2013	Analysis Date: 8/2/2013 SeqNo: 352158 Units: mg/Kg	
Analyte	Result PQL SPK value SPK Ref Val . %REC LowLimit HighLimit %RPD RPDLimit Qui	al
Diesel Range Organics (DRO)	46 10 50.00 0 92.5 77.1 128	

Qualifiers:

Surr: DNOP

* Value exceeds Maximum Contaminant Level.

4.1

5.000

- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

81.4

63

147

- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 5 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#:

1307D69

06-Aug-13

Client:

Blagg Engineering

Project:

Atlantic LS 17

Sample ID: MB-8655	Samp	Гуре: МЕ	BLK	Tes	tCode: El	PA Method	8015D: Gaso	line Rang	e	
Client ID: PBS	Batc	h ID: 86	55	F	RunNo: 1:	2346				
Prep Date: 7/31/2013	Analysis [Date: 8/	1/2013	8	SeqNo: 3	51757	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND	5.0								
Surr: BFB	880		1000		88.4	80	120			
Sample ID: LCS-8655	Samp	Гуре: LC	s	Tes	tCode: El	PA Method	8015D: Gaso	line Rang	e	
Client ID: LCSS	Batc	h ID: 86	55	F	RunNo: 1:	2346				
Prep Date: 7/31/2013	Analysis E	Date: 8/	1/2013	5	SeaNo: 3	51758	Units: ma/K	ā		

Client ID: LCSS	Batch ID: 8655			F	RunNo: 1	2346					
Prep Date: 7/31/2013	Analysis D	ate: 8/	1/2013	8	SeqNo: 3	51758	Units: mg/K	(g			
Analyte	Result PQL SPK value			SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Gasoline Range Organics (GRO)	27	5.0	25.00	0	107	62.6	136				
Surr: BFB	960		1000		96.2	80	120				

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 6 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#: 1307D69

06-Aug-13

Client:

Blagg Engineering

Project:

Atlantic LS 17

Sample ID: MB-8655	Samp1	Гуре: М Е	BLK	Tes	tCode: El								
Client ID: PBS	Batc	h ID: 86 :	55	F	RunNo: 1	2346							
Prep Date: 7/31/2013	Analysis Date: 8/1/2013			5	SeqNo: 3	51787	Units: mg/Kg						
Analyte	Result PQL SPK value			SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	ND 0.050												
oluene ND 0.050													
Ethylbenzene	ND 0.050												
Xylenes, Total	ND	0.10											
Surr: 4-Bromofluorobenzene	1.0		1.000		100	80	120						
Surr: 4-Bromofluorobenzene Sample ID: LCS-8655		Гуре: LC					120 8021B: Volat	tiles					
	Samp1	Гуре: LC h ID: 86 :	:S	Tes		PA Method		tiles					
Sample ID: LCS-8655	Samp1	h ID: 86 :	:S 55	Tes	tCode: EF	PA Method 2346							
Sample ID: LCS-8655 Client ID: LCSS	Samp1 Batc	h ID: 86 :	:S 55 1/2013	Tes	tCode: EF	PA Method 2346	8021B: Volat		RPDLimit	Qual			
Sample ID: LCS-8655 Client ID: LCSS Prep Date: 7/31/2013	Sampī Batci Analysis E	h ID: 86 : Date: 8/	:S 55 1/2013	Tes F	tCode: EFRunNo: 12	PA Method 2346 51798	8021B: Volat	(g	RPDLimit	Qual			
Sample ID: LCS-8655 Client ID: LCSS Prep Date: 7/31/2013 Analyte	Sampī Batci Analysis [Result	h ID: 86 : Date: 8/	:S 55 1/2013 SPK value	Tes F S SPK Ref Val	tCode: EF RunNo: 12 SeqNo: 38	PA Method 2346 51798 LowLimit	8021B: Volat Units: mg/K HighLimit	(g	RPDLimit	Qual			
Sample ID: LCS-8655 Client ID: LCSS Prep Date: 7/31/2013 Analyte Benzene	SampT Batcl Analysis D Result 1.0	h ID: 86 : Date: 8/ PQL 0.050	SFK value 1.000	Tes F S SPK Ref Val 0 0	tCode: ER RunNo: 12 SeqNo: 38 %REC 100	PA Method 2346 51798 LowLimit 80	8021B: Volate Units: mg/K HighLimit 120	(g	RPDLimit	Qual			
Sample ID: LCS-8655 Client ID: LCSS Prep Date: 7/31/2013 Analyte Benzene Toluene	SampT Batcl Analysis E Result 1.0 0.97	PQL 0.050 0.050	SPK value 1.000 1.000	Tes F S SPK Ref Val 0 0	tCode: EF RunNo: 1 2 SeqNo: 3 5 %REC 100 96.7	PA Method 2346 51798 LowLimit 80 80	8021B: Volate Units: mg/K HighLimit 120 120	(g	RPDLimit	Qual			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 7 of 7



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: **BLAGG** Work Order Number: 1307D69 RcptNo: 1 Received by/date: Logged By: **Lindsay Mangin** 7/30/2013 10:01:00 AM 7/30/2013 3₁19:34 PM Completed By: Lindsay Mangin 07/31/13 Reviewed By: Chain of Custody Not Present ✓ 1. Custody seals intact on sample bottles? Yes No Not Present 2. Is Chain of Custody complete? No : Yes 3. How was the sample delivered? Courier Log In NA : No 4. Was an attempt made to cool the samples? Yes . NA 5. Were all samples received at a temperature of >0° C to 6.0°C No No 6. Sample(s) in proper container(s)? No 7. Sufficient sample volume for indicated test(s)? No 8. Are samples (except VOA and ONG) properly preserved? Yes NA No A 9. Was preservative added to bottles? Yes No : No VOA Vials 🗸 10.VOA vials have zero headspace? Yes Yes No 11. Were any sample containers received broken? # of preserved bottles checked for pH: No 12. Does paperwork match bottle labels? Yes (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? No 13. Are matrices correctly identified on Chain of Custody? No 14. Is it clear what analyses were requested? Checked by: No 15. Were all holding times able to be met? Yes (If no, notify customer for authorization.) Special Handling (if applicable) 16. Was client notified of all discrepancies with this order? Yes No NA 🗸 Person Notified: Date: By Whom: Via: eMail Phone Fax In Person Regarding: Client Instructions: 17. Additional remarks: 18, Cooler Information Cooler No Temp °C Condition Seal Intact Seal No Seal Date Good Yes

Chain-of-Custody Record			Tum-Around Time:							L				MIX	/TE	20			NT	AI		
Client: BLAGG ENGINEERING INC.				Standard □ Rush																		
BP AMERICA Mailing Address: P.O. Box 97 BLOWFIELD NM 87413 Phone #: 505-632-1199			Project Name	Project Name: ATLANTIC LS 17				ANALYSIS LABORATORY www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109												•		
			ATLANTIC																			
			Project #:					Tel. 505-345-3975 Fax 505-345-4107														
													Analysis Request								· · ·	
email or Fax#:			Project Mana	ger:			=	ار کر	1					8	,			Ĭ				
QA/QC Package: Standard □ Level 4 (Full Validation)			J. 30	461			s (8021	(Gas o	DRO (MRG)			SIMS)		PO ₄ ,S	PCB's		:					
Accreditation □ NELAP □ Other			J. BLACE Sampler: J. BLACE On-Higher X Yes and 1980				+ (WIRE + HAB'S (8021)	'BE + TPH (Gas only)	ত্র	418.1)	od 504.1)			J ₃ ,NO ₂	3 / 8082		æ			į	or N)	
□ EDD (Type)			Sample Temperature: with Control				出			pd 4			stals	Ž,	ides	8	위	W			٤	
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type			BTEX +4td	BTEX + MTBE	TPH 8015B	TPH (Method	EDB (Method 504.1)	PAH's (8310 or	RCRA 8 Metals	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082 PCB'	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE			Air Bubbles (Y or N)
29/13	0949	Soil		402×1	cool	-00		X		X	×								×			\top
1(1115		95 BGT 5-PE@5		iu	-68		X		×	×							_	X	_	1	\dagger
	1		3-7-6-5-5					-											1		+	+
						-													\neg	+	+	+
															\vdash			\dashv	_	+	_	+
																\vdash		-	-	+	+	+
															\vdash	\vdash		\dashv	\dashv	+	+	+
															\vdash		-	\dashv	\dashv	+		+-
	 	 														\vdash		\dashv	-+	+	+	+
															\vdash	$\vdash \vdash$		\dashv	-	+	+	+
	 																			+	+	+
				 									<u> </u>					\dashv	\dashv	\dashv	+	+-
Date:	Time:	Time: Relinquished by:			Received by: Date. Time				Remarks: D PD													
29/2013 1150 Jeff Blogg		Mho. H. 1. Janle 723/2013 1150				SILL DI																
Date:	Time:	Religiquish	ed by:	Received by:	Received by: Date Time				Parker: ZFEIRKOSJS													
29/3	1750	Mi	otu Wales	07/30/13 100/					CONTACT! JETT PEACE													
	If necessary,	samples sub	mitted to Hall Environmental may be subo	contracted to other ac	credited laboratorie	s. This serves a	s notice of this	possil	bility.	Any st	ıb-coni	tracted	d data	will be	: cleart	y nota	ted on	the an	alytical	report.		



