

submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
Sundry Notices and Reports on Wells

RECEIVED

AUG 21 2014

Farmington Field Office  
Bureau of Land Management

1. **Type of Well**  
Gas

2. **Name of Operator**  
Max D. Webb

3. **Address & Phone No. of Operator**  
PO Box 190, Farmington, NM 87499

4. **Location of Well, Footage, Sec., T, R, M**  
1850' FSL & 790' FEL, Section 34, T-27-N, R-13-W,

5. **Lease Number**  
NM-33046

6. **If Indian, All. or Tribe Name**

7. **Unit Agreement Name**

8. **Well Name & Number Federal 34 #2**

9. **API Well No.**  
30-045-23014

10. **Field and Pool**  
WAW PC.

11. **County & State**  
San Juan County, NM

Approved as to plugging of the well bore. Liability under bond is retained until surface restoration is completed.

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

ACCEPTED FOR RECORD

SEP 15 2014

FARMINGTON FIELD OFFICE  
BY: J. L. SANCHEZ

13. Describe Proposed or Completed Operations

RCVD SEP 17 '14  
OIL CONS. DIV.  
DIST. 3

Plugging Work Details:

7/23/14 Rode cement equipment to location. Spot in and RU. Open up well; no pressures. Dig out plumb in bradenhead valve. RU 2-7/8" pumping tee on to 2-7/8" casing. RU pump to 7" bradenhead, pump 1-1/2 bbls. Pressure test bradenhead to 200 PSI, OK. RU pump to 2-7/8" casing, pump 10 bbls pressure up to 400 PSI. Pump down casing with 48 sxs (56.64 cf) Class B cement inside casing from 1380' to surface. SI well. SDFD. RD and MOL. ✓

7/24/14 Travel to location. RU cement equipment. Dig out wellhead. Fill out Hot Work Permit. Monitor well for LEL, no LEL. Cut off wellhead. Tag TOC in 2-7/8" casing at 1' and down 40' in 7" casing. Run poly pipe 40' down 7" casing. Spot plug #2 with 24 sxs (28.32 cf) Class B cement top off with 1" poly pipe down 40' in 7" casing and install P&A marker. RD and MOL. ✓

14. I hereby certify that the foregoing is true and correct.

Signed Max D. Webb Title Operator Date 7/30/14

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCDAV