District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application
Proposed Alternative Method Permit or Closure Plan Application Type of action: Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company Address:200 Energy Court, Farmington, NM 87401 Figure 277 AUG 18 2014
Address:200 Energy Court, Farmington, NM 87401AUG 7 8 2014
Facility or well name:Florance 77
API Number:3004511716 OCD Permit Number:
U/L or Qtr/QtrP Section12 Township29N Range9W County:San Juan
Center of Proposed Design: Latitude36.73445
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☑ Visible sidewalls only ☐ Other _Single walled/single bottomed
Liner type: Thicknessmil
4. Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school,	hospital
institution or church)	поѕриш,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
inspections (it netting of serecting is not physically reasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
<u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. ☐ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.3 and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	cuments are
 □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC □ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	_

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13;	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)	
On-site Closure Method (Only for temporary pits and closed-loop systems)	
☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method	
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be	
closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on site closure methods only): 19 15 17 10 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable south provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland.	
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☐ No
within incorporated municipal boundaries of within a defined municipal fresh water well field covered under a municipal ordinance	<u></u>

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the	e municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Divis	on	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources Society; Topographic map	ces; USGS; NM Geological	☐ Yes ☐ No
Within a 100-year floodplain FEMA map		Yes No
16.		
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items in by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15. Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15. Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in calcal Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 N Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 N Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 N	17.10 NMAC .15.17.13 NMAC ents of Subsection K of 19.15.17. e appropriate requirements of 19.1 17.13 NMAC se on-site closure standards cannot MAC MAC	II NMAC 15.17.11 NMAC
17. Operator Application Certification:		
I hereby certify that the information submitted with this application is true, accurate and complete to t	ne best of my knowledge and beli	ef.
Name (Fint).	,	
Signature: Date:		
e-mail address: Telephone:		
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Representative Signature:	Conditions (see attachment) Approval Date: 9/9/	2014
Title: OCD Permit Num	B.E. Land 2 OCD and	Surface Owner
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC	not tice	
Instructions: Operators are required to obtain an approved closure plan prior to implementing any The closure report is required to be submitted to the division within 60 days of the completion of the section of the form until an approved closure plan has been obtained and the closure activities have	closure activities. Please do not	
	вееп сотрієтеа.	
20. Closure Method:		op systems only)
20. Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method	Waste Removal (Closed-location the closure report. Please inc	

Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirem	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Jaff Pase	Date:August 15, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Florance 77 API No. 3004511716 Unit Letter P, Section 12, T29N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was sent. This BGT was removed as part of plug and abandon operations for this well and was not done by the BGT project group. Sufficient notice of the BGT removal by the plug and abandon group was not given to the BGT group in order to get the notice sent as required.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was sent. This BGT was removed as part of plug and abandon operations for this well and was not done by the BGT project group. Sufficient notice of the BGT removal by the plug and abandon group was not given to the BGT group in order to get the notice sent as required.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:

- a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
- b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
- c. Basin Disposal, Permit NM-01-0005 (Liquids)
- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and will be reclaimed with the rest of the site since the well was plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT will be reclaimed as part of final reclamation since the well has been plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT will be reclaimed as part of final reclamation since the well has been plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT will be reclaimed as part of final reclamation since the well has been plugged and abandoned.

- 13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.
 - BP will seed the area as part of final reclamation since the well has been plugged and abandoned.
- 14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.
 - BP will notify NMOCD when re-vegetation is successful.
- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.
 - Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141
Revised August 8, 2011
ubmit 1 Copy to appropriate District Office in

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rel	ease Notific	catio	on and Co	orrective A	ction	1				
						OPERA	ΓOR		☐ Initi	al Report	\boxtimes	Final Repo	
Name of Co			 			Contact: Jef							
		Court, Farmi	ington, N	M 87401		Telephone No.: 505-326-9479							
Facility Na	ne: Floran	ice //				Facility Type: Natural gas well							
Surface Ow	ner: Feder	al		Mineral (Owner:	: Federal		API No	. 30045117	716			
				LOCA	ATIO	N OF RE	LEASE						
Unit Letter	Section	Township	Range	Feet from the	1	h/South Line	Feet from the		Vest Line	County: Sa	an Jua	n	
P	12	29N	9W	790	Sout	h	990	East					
		Lati	itude3	6.73445		Longitud	e 107.72470_						
				NAT	URE	OF REL							
Type of Rele		-					Release: N/A			Recovered: N			
Source of Re	Source of Release: below grade tank – 95 bbl, Tank A						Iour of Occurrenc	e:	Date and	Hour of Dis	covery	:: N/A	
Was Immedi	ate Notice (•	N/A If YES, To	Whom?	1					
			Yes [] No 🛛 Not R	equired	1							
By Whom?						Date and I-				<u> </u>			
Was a Water	Was a Watercourse Reached? ☐ Yes ☑ No						If YES, Volume Impacting the Watercourse.						
If a Watercou	irse was Im	pacted, Descr	ibe Fully.	k		<u> </u>							
the BGT. So	il analysis r	esulted in TP	н, втех	and chlorides belo	ow stan	idards. Analys	the BGT was doi	ched.				•	
backfilled an	d compacte	d and will be i	reclaimed	with the rest of th	ne site s	since the well h	nderneath the BG nas been plugged	and abar	ndoned.				
regulations a public health should their c or the environ	I operators or the envi- perations h nment. In a	are required to ronment. The nave failed to a	o report ar acceptance adequately OCD accep	nd/or file certain rece of a C-141 reportant reports and received and	elease ort by tl emedia	notifications and the NMOCD mate contaminati	knowledge and und perform correctarked as "Final Roon that pose a three the operator of the correction of the operator of the correction o	tive acti eport" de eat to gr	ons for rele oes not rele ound water	eases which ieve the oper r, surface wa	may e ator o ter, hu	ndanger f liability ıman health	
	00	0			1		OIL CONS	<u>SERV</u>	ATION	DIVISIO	<u>N</u>		
Signature:	96	face											
Printed Name	g / V					Approved by	Environmental S	pecialist	:				
Title: Area E	nvironment	al Advisor				Approval Dat	e:	F	Expiration	Date:			
E-mail Addre	ess: peace.je	effrey@bp.cor	m			Conditions of	Approval:		Attached				
Date: Augus	t 15, 2014		Phone	: 505-326-9479									
* Attach Addi	tional She	ets If Necess		_									

CLIENT: BP	P.O. BOX 87, E	NGINEERING, INC. BLOOMFIELD, NM 87 05) 632-1199	413	API #: 3004511716 TANK ID (if applicble): A
FIELD REPORT:	(circle one): BGT CONFIRMATION	/ RELEASE INVESTIGATION / OTHER:		PAGE#: 1 of 1
SITE INFORMATION	I: SITE NAME: FLORA	NCE #77		DATE STARTED: 06/19/14
QUAD/UNIT: P SEC: 12 TWP:	29N RNG: 9W PM	: NM CNTY: SJ ST	: NM_	DATE FINISHED:
1/4-1/4/FOOTAGE: 790'S / 990'E	SE/SE LEASE	TYPE: FEDERAL STATE / FEE	/ INDIAN	ENVIRONMENTAL
LEASE #: SF080032	PROD. FORMATION: PC C	CROSSFIRE ONTRACTOR: MBF - T. PETEI	RSON	SPECIALIST(S): NJV
REFERENCE POINT	: WELL HEAD (W.H.) GP:	S COORD.: 36.73418 X	107.72508	GLELEV.: 6,419'
		6.73445 X 107.72470		
2)	GPS COORD.:		_ DISTANCE/BEA	RING FROM W.H.;
3)	GPS COORD.:		_ DISTANCE/BEA	RING FROM W.H.:
4)			_ DISTANCE/BEAI	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) #	OR LAB USED: HALL		OVM READING (ppm)
1) SAMPLE ID:	(95) SAMPLE DATE: 06/19	0/14 SAMPLE TIME: 1115 LAB ANA	iysis: 418.1/8	015B/8021B/300.0 (CI) NA
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANA	Lysis:	
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANA	LYSIS:	
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANA	LYSIS:	
SOIL DESCRIPTION SOIL COLOR: MODER COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY/SLIGHTLY MOIST MOIST/W SAMPLE TYPE: GRAB COMPOSITE # DISCOLORATION/STAINING OBSERVED: YES/M	ATE BROWN COHESIVE COHESIVE / HIGHLY COHESIVE DOSE / FIRM DENSE / VERY DENSE ET / SATURATED / SUPER SATURATED OF PTS. 5	PLASTICITY (CLAYS): NON PLASTIC / SLIGI	HTLY PLASTIC / CO SOFT / FIRM / NATION -	
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER: GAS WELL RECENTLY PLUGGE	DAND/OR OCCURRED: YES / NO EXP YES / NO EXPLANATION - ED AND ABANDONED (P & A). BO	LANATION: ST: BOTTOM 1/2 OF SIDEWALLS BU		·
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: >100' N				TMATION (Cubic Yards) : NA
DEPTH TO GROUNDWATER: >100' N	EAREST WATER SOURCE: >1,000			D TPH CLOSURE STD: 5,000 ppm
OTTE ORETOTT	PBGTL T.B. ~ 4' PBGTL X X X X X	METER RUN BERM	N TIME	CALIB. READ. = NA ppm RF = 0.52 CALIB. GAS = NA ppm DATE: NA MISCELL. NOTES /O: N15438273 O#:
P&A	B,G.	METER RUN	P.	ppm = parts per million
MARKER ⊕			S.P.D.	BGT Sidewalls Visible: Y / N
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELEAPPLICABLE OR NOT AVAILABLE; SW-SINGLE	OW-GRADE TANK LOCATION; SPD = SAMPLE E WALL; DW - DOUBLE WALL; SB - SINGLE BO	BELOW, T.H. = TEST HOLE; ~ = APPROX.; W.H. = V POINT DESIGNATION; R.W. = RETAINING WALL; N	ÆLL HEAD; LV	BGT Sidewalls Visible: Y / N lagnetic declination: 10° E

Analytical Report

Lab Order 1406954

Date Reported: 6/24/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC - TB @ 4' (95)

Project: Florance # 77

Collection Date: 6/19/2014 11:15:00 AM

Lab ID: 1406954-001

Matrix: MEOH (SOIL) Received Date: 6/20/2014 8:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGE C	RGANICS		·		Analyst	BCN
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	6/20/2014 10:11:14 AM	13803
Surr: DNOP	93.1	57.9-140	%REC	1	6/20/2014 10:11:14 AM	13803
EPA METHOD 8015D: GASOLINE RANG	Ε				Analyst	NSB
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	6/20/2014 9:55:05 AM	R19405
Surr: BFB	86.0	80-120	%REC	1	6/20/2014 9:55:05 AM	R19405
EPA METHOD 8021B: VOLATILES					Analyst	NSB
Benzene	ND	0.047	mg/Kg	1	6/20/2014 9:55:05 AM	R19405
Toluene	ND	0.047	mg/Kg	1	6/20/2014 9:55:05 AM	R19405
Ethylbenzene	ND	0.047	mg/Kg	1	6/20/2014 9:55:05 AM	R19405
Xylenes, Total	ND	0.093	mg/Kg	1	6/20/2014 9:55:05 AM	R19405
Surr: 4-Bromofluorobenzene	98.5	80-120	%REC	1	6/20/2014 9:55:05 AM	R19405
EPA METHOD 300.0: ANIONS					Analyst	JRR
Chloride	ND	30	mg/Kg	20	6/20/2014 11:23:22 AM	13810
EPA METHOD 418.1: TPH					Analyst	JME
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	6/20/2014 12:00:00 PM	13804

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 6

- $P \quad \ \mbox{Sample pH greater than 2}.$
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#: 1406954

24-Jun-14

Client:

Blagg Engineering

Project:

Florance #77

Sample ID MB-13810

Sample ID LCS-13810

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 13810

1.5

PQL

1.5

RunNo: 19436

Analysis Date: 6/20/2014

SeqNo: 562237

Units: mg/Kg

Analyte

6/20/2014

Prep Date:

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD **RPDLimit** Qual

Chloride

Result PQL ND

SampType: LCS

TestCode: EPA Method 300.0: Anions

RunNo: 19436

LowLimit

Client ID: Prep Date:

LCSS 6/20/2014 Batch ID: 13810

Analysis Date: 6/20/2014

SeqNo: 562238

Units: mg/Kg

%RPD **RPDLimit**

Qual

Analyte

15.00

SPK value SPK Ref Val %REC

HighLimit

Chloride

14

96.1

90

110

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits S
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2. Reporting Detection Limit

Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1406954

24-Jun-14

Qual

Qual

Client:

Blagg Engineering

Project:

Florance #77

Sample ID MB-13804

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID: PBS Batch ID: 13804

RunNo: 19397

Prep Date: 6/20/2014

Analysis Date: 6/20/2014

SeqNo: 561304

Units: mg/Kg HighLimit

Analyte

Analyte

Result PQL

Result

ND 20

Client ID: LCSS

SampType: LCS

TestCode: EPA Method 418.1: TPH

Prep Date: 6/20/2014

Petroleum Hydrocarbons, TR

Sample ID LCS-13804

Batch ID: 13804 Analysis Date: 6/20/2014 RunNo: 19397

%REC

SPK value SPK Ref Val %REC LowLimit

SeqNo: 561305

Units: mg/Kg

HighLimit %RPD **RPDLimit**

%RPD

Qual

Petroleum Hydrocarbons, TR Sample ID LCSD-13804

SampType: LCSD

PQL

20

20

TestCode: EPA Method 418.1: TPH

LowLimit

Batch ID: 13804

99

RunNo: 19397

Prep Date: 6/20/2014

LCSS02

Analysis Date: 6/20/2014

SeqNo: 561306

Units: mg/Kg HighLimit

%RPD

RPDLimit

RPDLimit

Analyte Petroleum Hydrocarbons, TR

Client ID:

Result

PQL

SPK value SPK Ref Val

SPK value SPK Ref Val

100.0

%REC 99.3

LowLimit

120

Qualifiers:

Value exceeds Maximum Contaminant Level.

Ε Value above quantitation range

Analyte detected below quantitation limits

RSD is greater than RSDlimit O

RPD outside accepted recovery limits R

Spike Recovery outside accepted recovery limits

Н

ND Not Detected at the Reporting Limit

Analyte detected in the associated Method Blank

Р Sample pH greater than 2.

Reporting Detection Limit

Holding times for preparation or analysis exceeded

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1406954

24-Jun-14

Client:

Blagg Engineering

Project:

Florance #77

Sample ID MB-13803	SampType: MBLK			Tes	TestCode: EPA Method 8015D: Diesel Range Organics					
Client ID: PBS	Batch ID: 13803 Analysis Date: 6/20/2014			F	RunNo: 1	9402				
Prep Date: 6/20/2014				SeqNo: 561328			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Surr: DNOP	8.3		10.00		83.4	57.9	140			
Sample ID LCS-13803	SampT	ype: LC	s	Tes	tCode: El	PA Method	8015D: Dies	el Range (Organics	
Client ID: LCSS	Batch	n ID: 13	803	F	RunNo: 1	9402				
Prep Date: 6/20/2014	Analysis D	ate: 6/	20/2014	5	SeqNo: 50	61594	Units: mg/K	(g	a 1,	
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	50	10	50.00	0	100	60.8	145			
Surr: DNOP	3.4		5.000		68.9	57.9	140			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1406954

24-Jun-14

Client:

Blagg Engineering

Project:

Florance #77

Sample ID MB-13793 MK	SampT	ype: Mi	3LK	Tes	TestCode: EPA Method 8015D: Gasoline Range					
Client ID: PBS	Batch ID: R19405			PBS Batch ID: R19405 RunNo: 19405						
Prep Date:	Analysis Date: 6/20/2014			SeqNo: 561885			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND	5.0								
Surr: BFB	960		1000		96.1	80	120			

Sample ID LCS-13793 MK	SampT	ype: LC	s	TestCode: EPA Method 8015D: Gasoline Range											
Client ID: LCSS	Batcl	n ID: R1	9405	F	RunNo: 1	9405									
Prep Date:	Analysis D	oate: 6/	20/2014	5	SeqNo: 5	61886	Units: mg/h								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Gasoline Range Organics (GRO)	22	5.0	25.00	0	89.1	71.7	134								
Surr: BFB	950		1000		95.2	80	120								

Qualifiers:

* Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

O RSD is greater than RSDlimit

R RPD outside accepted recovery limits

S Spike Recovery outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

P Sample pH greater than 2.

RL Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1406954

24-Jun-14

Client:

Blagg Engineering

Project:

Florance # 77

Sample ID MB-13793 MK	SampType: MBLK Batch ID: R19405			TestCode: EPA Method 8021B; Volatiles											
Client ID: PBS				F	lunNo: 1	9405	•	:							
Prep Date:	Analysis D)ate: 6/	20/2014	S	SeqNo: 5	61907	Units: mg/K	(g -							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Benzene	ND	0.050					· - · · · · · · · · · · · · · · · · · ·								
Toluene	ND	0.050													
Ethylbenzene	ND	0.050													
Xylenes, Total	ND	0.10													
Surr: 4-Bromofluorobenzene	1.1		1.000		114	80	120								

Sample ID LCS-13793 MK	Samo	Type: LC	:s	TestCode: EPA Method 8021B: Volatiles												
Client ID: LCSS	•	h ID: R1			RunNo: 1											
Prep Date:	Analysis I	Date: 6/	20/2014	5	SeqNo: 5	61908	Units: mg/k	(g								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual						
Benzene	0.96	0.050	1.000	0	95.6	80	120									
Toluene	0.93	0.050	1.000	0	92.8	80	120									
Ethylbenzene	0.93	0.050	1.000	0	92.5	80	120									
Xylenes, Total	2.9	0.10	3.000	0	97.8	80	120									
Surr: 4-Bromofluorobenzene	1.1		1.000		113	80	120									

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website; www.hallenvironmental.com

Sample Log-In Check List

RcptNo: 1 Client Name: **BLAGG** Work Order Number: 1406954 Received by/date: Logged By: 6/20/2014 8:00:00 AM **Lindsay Mangin** Completed By: 6/20/2014 8:04:36 AM Lindsay Mangin oc/zoli4 Reviewed By: Chain of Custody Nο Not Present 1 Custody seals intact on sample bottles? No Not Present 2. Is Chain of Custody complete? Yes V 3 How was the sample delivered? Courier Log In NA No 🗔 4. Was an attempt made to cool the samples? Yes 🗸 No 🗔 NA : 5. Were all samples received at a temperature of >0° C to 6.0°C No : Sample(s) in proper container(s)? No i 7. Sufficient sample volume for indicated test(s)? 8. Are samples (except VOA and ONG) properly preserved? No Yes NA 9. Was preservative added to bottles? Yes No 🗸 No VOA Vials V 10. VOA vials have zero headspace? Yes No 11. Were any sample containers received broken? Yes No V # of preserved bottles checked for pH: No 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? No 13. Are matrices correctly identified on Chain of Custody? 14. Is it clear what analyses were requested? No Checked by: 15. Were all holding times able to be met? Yes 🗸 No (If no, notify customer for authorization.) Special Handling (if applicable) Yes No 🗓 16. Was client notified of all discrepancies with this order? NA N Person Notified: Date: By Whom: eMail Phone In Person Via: Fax Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Cooler No Temp °C Condition Seal Intact | Seal No Seal Date 1.8 Good

, 	Date:	6/19/14							6/19/14	Date	□ EDD (Type)	□ NELAP	Accreditation:	QAVQC Package ✓ Standard	email or Fax#:	Phone #:		Mailing Address:
If necessa	Time:	155C							1115	Time	Гуре)	J	tion:	ckage: ard	ax#:			ddress:
Relinquished by: A and samples submitted	Relinquished by:							SOIL	Matrix		□ Other				(505) 632-1199	BLOOM	P.O. BOX 87	
submitted to Hall Environmental may be	the by:	la St							5PC-ТВ @ 4 1 (95)	Sample Request ID				Level 4 (Full Validation)		12-1199	BLOOMFIELD, NM 87413	X 87
subcontracted to othe	me: Relinquished by: Received	Received by:							4 oz 1	Container Type and #	Sample Temperature	On lice:	Sampler:		Project Manager.		Project #:	
r accredited laboratorie		facts							Cool	Preservative Type	oerature")M Yes	NELSON VELEZ	NELSON VELEZ	ger:		-	FLORANCE #77
This serves as not	Date Time	4							100-	HEAL NO		III No	ELEZ MY	ELEZ				# 77
of this p	3		1						٧	BTEX +-MTB		FIVE	- - 	021B)				l.—_
ossibi	Work Order: NS438273 Paykey: ZFEIS	Remarks: BILL DIRECTLY TO BP: leff Peace 700 Foeror								BTEX + MTB	E + 1	ГРН	(Gas	only)			<u></u>	49
īţ A)rder	S:							٨	TPH 8015B (GRO)/D	RO ,	'MRO	19		Tel. 505-345-3975	4901 Hawkins NE -
y sub	 احرا) T							4	TPH (Meth	od 4	118.	1)		-)5 -3	law.
contra	N(5438273	O BP								EDB (Meth	od!	504	.1)				1 5-3	ins I
acted	438	3								PAH (8310	or 8	3270	OSIN	15)			975	W.
data w	728	į	·							RCRA 8 Me	tals					\nal	_	
/ill be	W	יני B								Anions (F,C	I,N(۸,8С	102,	PO ₄ ,S	O ₄)	lysis	×E	ngu
early	Pay 18	;								8081 Pestid	ide	s / 8	3082	PCB	s	Rec	505	erq
notat	Paykey:	ś ≥			,					8260B (VO	A)					Request	Fax 505-345-4107	je,
ed on	. Z	<u>₹</u> ×								8270 (Semi	-VC	A)	_			3	-410	Σ
the an	ZFEIRKOSJS	7401						\Box	<u>ح</u>	Chloride (soi	I - 30	0.0	/ wat	er - 30	0.1)	,)7	Albuquerque, NM 87109
alytica	KOS															, d		9
nepo	S									Grab samp	le					4		
7	1								<	5 pt. compo	osit	e sa	mpl	e				

ANALYSIS LABORATORY

Client:

Chain-of-Custody Record BLAGG ENGR. / BP AMERICA

Standard Project Name:

Rush

SAME DAY

בימנות באומים באוום

www.hallenvironmental.com



