<u>District 1</u>
 1625 N. French Dr., Hobbs, NM 88240
 <u>District II</u>
 811 S. First St., Artesia, NM 88210
 <u>District III</u>
 1000 Rio Brazos Road, Aztec, NM 87410
 <u>District IV</u>
 1220 S. St. Francis Dr., Santa Fe, NM 87505

•

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application
Proposed Alternative Method Permit or Closure Plan Application WH3731 Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Derator: BP America Production CompanyOGRID #:778OIL CONS. DIV DIST. 3
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Eskeenalwood 1
API Number: 3004507137 OCD Permit Number:
U/L or Qtr/QtrJ Section25 Township28N Range9W County:San Juan
Center of Proposed Design: Latitude36.63028 Longitude107.73642 NAD: □1927 ⊠ 1983
Surface Owner: 🔲 Federal 🔲 State 🔲 Private 🖾 Tribal Trust or Indian Allotment
2. 2. 3. 4. 5. 5. 5. 7. 5. 5. 7. 7. 7. 7
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank B Volume: 21.0bbl Type of fluid:Produced water
Tank Construction material: Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
□ Visible sidewalls and liner □ Visible sidewalls only ⊠ Other _Single walled/Double bottomed, side walls not visible
Liner type: Thicknessmil HDPE PVC Other
 Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	, hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
 5. Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC 	
 <u>Variances and Exceptions</u>: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. <i>Please check a box if one or more of the following is requested, if not leave blank:</i> Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 	
^{9.} Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acce material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. -	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	🗌 Yes 🗌 No
Below Grade Tanks	
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole,	Yes 🗌 No

Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site -

1

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	□ Yes □ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
	Yes No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Permanent Pit or Multi-Well Fluid Management Pit	
 Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes 🗋 No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u>: Subsection B of 19.15.17.9 N <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.</i> Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC 	
 Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC 	NMAC
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC 	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit.	
 Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	.13.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

12.								
Permanent Pits Permit Application Checklist: Instructions: Each of the following items must	Subsection B of 19.15.17.9 NMAC be attached to the application. Please indicate, by a check mark in the box, that the	documents are						
 Siting Criteria Compliance Demonstrations Climatological Factors Assessment Certified Engineering Design Plans - based 	uirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC s - based upon the appropriate requirements of 19.15.17.10 NMAC upon the appropriate requirements of 19.15.17.11 NMAC							
Leak Detection Design - based upon the ap	sign - based upon the appropriate requirements of 19.15.17.11 NMAC propriate requirements of 19.15.17.11 NMAC							
Quality Control/Quality Assurance Constru	essment - based upon the appropriate requirements of 19.15.17.11 NMAC action and Installation Plan bon the appropriate requirements of 19.15.17.12 NMAC							
	n - based upon the appropriate requirements of 19.15.17.11 NMAC							
Emergency Response Plan Oil Field Waste Stream Characterization								
 Monitoring and Inspection Plan Erosion Control Plan 								
	requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC							
^{13.} <u>Proposed Closure</u> : 19.15.17.13 NMAC Instructions: Please complete the applicable box	ces, Boxes 14 through 18, in regards to the proposed closure plan.							
_	Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit						
Proposed Closure Method: Waste Excavation	and Removal (Closed-loop systems only)							
On-site Closure N	Aethod (Only for temporary pits and closed-loop systems) ice Burial On-site Trench Burial							
Alternative Closu	re Method							
closure plan. Please indicate, by a check mark in Protocols and Procedures - based upon the Confirmation Sampling Plan (if applicable) Disposal Facility Name and Permit Number Soil Backfill and Cover Design Specification Re-vegetation Plan - based upon the appropriate	Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be in the box, that the documents are attached. appropriate requirements of 19.15.17.13 NMAC - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC r (for liquids, drilling fluids and drill cuttings) ons - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC oriente requirements of Subsection H of 19.15.17.13 NMAC ropriate requirements of Subsection H of 19.15.17.13 NMAC							
15. Siting Criteria (regarding on-site closure metho	ods only): 19.15.17.10 NMAC							
Instructions: Each siting criteria requires a dem provided below. Requests regarding changes to a 19.15.17.10 NMAC for guidance.	nonstration of compliance in the closure plan. Recommendations of acceptable sou certain siting criteria require justifications and/or demonstrations of equivalency.	rce material are Please refer to						
Ground water is less than 25 feet below the bottom - NM Office of the State Engineer - iWATE	n of the buried waste. ERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA						
Ground water is between 25-50 feet below the bot - NM Office of the State Engineer - iWATE	tom of the buried waste ERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA						
Ground water is more than 100 feet below the bot - NM Office of the State Engineer - iWATE	tom of the buried waste. ERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA						
lake (measured from the ordinary high-water mark	Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site							
Within 300 feet from a permanent residence, scho - Visual inspection (certification) of the pro-	ol, hospital, institution, or church in existence at the time of initial application. posed site; Aerial photo; Satellite image	🗌 Yes 🗌 No						
at the time of initial application.	Tresh water well or spring used for domestic or stock watering purposes, in existence ERS database; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No						
Written confirmation or verification from the mun	icipality; Written approval obtained from the municipality	🗌 Yes 🗌 No						
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map;	Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No						
	in a defined municipal fresh water well field covered under a municipal ordinance							
Form C-144	Oil Conservation Division Page 4 c	of 6						

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No						
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes 🗌 No						
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological							
Society; Topographic map Within a 100-year floodplain. - FEMA map							
	Yes No						
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure partial of a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards canr Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	.11 NMAC 15.17.11 NMAC						
 17. Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and bel 	ief.						
Name (Print): Title:							
Signature: Date:							
e-mail address: Telephone:							
18. <u>OCD Approva</u> l: Permit Application (including closure plan) A Closure Plan (only) OCD Conditions (see attachment)							
OCD Representative Signature: Approval Date: Approval Date:	100H						
Title: Ompliance Octor 10 DED OCD Permit Number:							
V CLANTE TA ART TA ART TA ACT TO THE TO THE TANK							
* Closule Did not Comply with 19.13.17.13, E.I., no sustance owner A	obfication						
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not							
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Sever Closure activities and submitting Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting							
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	complete this						
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Image: Section of the form until an approved closure plan has been obtained and the closure activities have been completed. Image: Section of the form until an approved closure plan has been obtained and the closure activities have been completed. Image: Section of the form until an approved closure plan has been obtained and the closure activities have been completed. Image: Section of the form until an approved closure plan has been obtained and the closure activities have been completed. Image: Section of the following items activities have been completed. Image: Section of the following items must be attached to the closure report. Please in mark in the box, that the documents are attached. Image: Section of of Closure Notice (surface owner and division) Proof of Deed Notice (surface owner and division) Soi	complete this						

.

22.		
Operator	Closure	Certification:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print): _____Jeff Peace_

Title: Area Environmental Advisor_____

off Peace Signature:__

Date: __August 13, 2014_____

e-mail address: __peace.jeffrey@bp.com___

Telephone: ___(505) 326-9479_____

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Eskeenalwood 1 <u>API No. 3004507137</u> <u>Unit Letter J, Section 25, T28N, R9W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

<u>General Closure Plan</u>

- BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. No notice was sent. BP contacted the local FIMO office to request a list of landowners since this is Navajo Allotted land, but no response was received from FIMO.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number. Notice is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)
 - All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.
- 4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT, Tank B	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

> Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.
- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

State of New Mexico Energy Minerals and Natural Resources

> Oil Conservation Division 1220 South St. Francis Dr. Santa Fe. NM 87505

Form C-141 Revised August 8, 2011

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

1220 S. St. Fran	ncis Dr., Sant	a Fe, NM 8750	5	Sa	anta I	Fe, NM 875	505				
			Rele	ease Notifi	catio	on and Co	orrective A	ction			
						OPERA '	ΓOR	🗌 Ini	tial Report	\boxtimes	Final Repor
Name of Company: BP						Contact: Jef	ff Peace		· · · ·		*
					Telephone 1	No.: 505-326-94	79				
						be: Natural gas v					
Surface Ow	ner: Triha	1		Mineral (Jwner	· Federal		ΔΡΙΝ	lo. 3004507	137	
Surface of		· · · · · · · · · · · · · · · · · · ·							0. 500+507	157	
Unit Letter	Section	Township	Danaa	LOC:A		N OF RE	1	East/West Line	Country 6	I	
J	25	28N	Range 9W	1,650	Sout		Feet from the 1,650	East	County: S	an Juar	1
		Lat	itude3	6.63028		Longitud	e 107.73462				
				NAT	URE	E OF REL	EASE				
Type of Rele							Release: N/A		Recovered:		
		v grade tank –	- 21 bbl, Ta	ank B		N/A	Iour of Occurrenc	e: Date an	d Hour of Dis	scovery	: N/A
Was Immedi	ate Notice (Yes 🗌	No 🛛 Not R	equired	If YES, To	Whom?				
By Whom?	• • • •					Date and H	Iour				
Was a Water	course Read	ched?	Yes 🛛	No		If YES, Vo	olume Impacting t	he Watercourse.			
							the BGT was don is results are attac		l to ensure no	soil in	pacts from
				en.* BGT was re ctive well area.	moved	and the area u	nderneath the BG	T was sampled.	The excavate	d area v	was
regulations al public health should their c or the environ	I operators or the envir operations h nment. In a	are required to ronment. The ave failed to a	o report an acceptanc adequately OCD accep	d/or file certain r e of a C-141 repo investigate and r	elease ort by tl emedia	notifications an he NMOCD m ite contaminati	knowledge and u nd perform correc arked as "Final Ra on that pose a thra e the operator of t	tive actions for re eport" does not re eat to ground wat responsibility for	leases which lieve the ope er, surface wa compliance v	may er rator of ater, hur vith any	ndanger Tliability man health
Signature: Joff Peace					OIL CONSERVATION DIVISION						
					Approved by Environmental Specialist:						
Title: Area Environmental Advisor					Approval Dat	e:	Expiration	Expiration Date:			
E-mail Addre	ess: peace.je	effrey@bp.cor	n			Conditions of Approval: Attached					
Date: Augus	t 13, 2014		Phone:	505-326-9479							

* Attach Additional Sheets If Necessary

	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	API #: 3004507137 TANK ID (if applicble): B
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER:	PAGE #: <u>1</u> of <u>1</u>
QUAD/UNIT: J SEC: 25 TWP: 1/4 -1/4/FOOTAGE: 1,650'S / 1,65 LEASE #: 14-20-603-780	SITE NAME: ESKEENALWOOD # 1 28N RNG: 9W PM: NM CNTY: SJ ST: NM O'E NW/SE LEASE TYPE: FEDERAL / STATE / FEE INDIAN PROD. FORMATION: PC CONTRACTOR: MBF - S. GENTRY	DATE STARTED: 06/17/14 DATE FINISHED: ENVIRONMENTAL SPECIALIST(S): NJV
1) 21 BGT (SW/DB) 2) 3) 4)	GPS COORD.: DISTANCE/B	EARING FROM WH.:
2) SAMPLE ID:	CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL (21) SAMPLE DATE: 06/17/14 SAMPLE TIME: 1322 LAB ANALYSIS: 418.1 SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS:	/8015B/8021B/300.0 (CI) NA
SOIL COLOR: MODER COHESION (ALL OTHERS): NON COHESIVE) SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): CO MOISTURE: DRY (SLIGHTLY MOIST MOIST / WE SAMPLE TYPE: GRAB (COMPOSITE) # DISCOLORATION/STAINING OBSERVED: YES (N SITE OBSERVATION	COHESIVE / COHESIVE / HIGHLY COHESIVE DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM OSE / FIRM/ DENSE VERY DENSE OF PTS. 5 ANY AREAS DISPLAYING WETNESS: YES NO EXPLANATION - OF PTS. 5 NO EXPLANATION - O EXPLANATION - - - O EXPLANATION - - - O EXPLANATION - - - O ADJOR OCCURRED : YES NO EXPLANATION: - -	I / STIFF / VERY STIFF / HARD
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <a>	EAREST WATER SOURCE: >1,000' NEAREST SURFACE WATER: <1,000' NMC BGT Located : off fon site PLOT PLAN circle: attached 0V 	STIMATION (Cubic Yards) : NA DCD TPH CLOSURE STD: 100 ppm M CALIB. READ. = NA ppm M CALIB. GAS = NA ppm ME: NA am/pm DATE: NA MISCELL. NOTES
	W.H. BALE'S SALE'S	WO: N15483289 PO #: ZEVH01BGT2 PK: ZE-006Q0 Permit date(s): 06/10/10 OCD Appr. date(s): 05/29/14 ank OVM = Organic Vapor Meter ID ppm = parts per million A BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELC	W4GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING WALL; NA - NOT WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; DB - DOUBLE BOTTOM.	Magnetic declination: 10° E

Analytical Report
Lab Order 1406817
Date Reported: 6/20/2014

Hall Environmental Analysis Laboratory, Inc.

Project: ESKEENALWOOD # 1 Collection Date: 6/17/2014 1:22:00 F Lab ID: 1406817-001 Matrix: MEOH (SOIL) Received Date: 6/18/2014 7:40:00 A				
Project:ESKEENALWOOD # 1Collection Date: 6/17/2014 1:22:00 F	M			
	Л			
CLIENT: Blagg Engineering Client Sample ID: 5PC-TB @ 6' (21)	Client Sample ID: 5PC-TB @ 6' (21)			

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGE	ORGANICS				Analys	t: BCN
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	6/18/2014 1:06:05 PM	13755
Surr: DNOP	87.9	57.9-140	%REC	1	6/18/2014 1:06:05 PM	13755
EPA METHOD 8015D: GASOLINE RAI	NGE			t	Analys	t: NSB
Gasoline Range Organics (GRO)	ND	4.0	mg/Kg	1	6/18/2014 12:14:27 PN	R19352
Surr: BFB	89.8	80-120	%REC	1	6/18/2014 12:14:27 PN	I R19352
EPA METHOD 8021B: VOLATILES					Analys	t: NSB
Benzene	ND	0.040	mg/Kg	1	6/18/2014 12:14:27 PM	1 R19352
Toluene	ND	0.040	mg/Kg	.1	6/18/2014 12:14:27 PM	1 R19352
Ethylbenzene	ND	0.040	mg/Kg	1	6/18/2014 12:14:27 PM	1 R19352
Xylenes, Total	ND	0.080	mg/Kg	1	6/18/2014 12:14:27 PM	1 R19352
Surr: 4-Bromofluorobenzene	101	80-120	%REC	1	6/18/2014 12:14:27 PM	1 R19352
EPA METHOD 300.0: ANIONS					Analys	t: JRR
Chloride	ND	30	mg/Kg	20	6/18/2014 12:19:03 PM	1 13760
EPA METHOD 418.1: TPH					Analys	t: JME
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	6/18/2014 12:00:00 PM	1 13756

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Metho	od Blank
	Е	Value above quantitation range	Н	Holding times for preparation or analysis	s exceeded
	J	Analyte detected below quantitation limits	ND	Not Detected at the Reporting Limit	Page 1 of 6
	0	RSD is greater than RSDlimit	Р	Sample pH greater than 2.	rage roro
	R	RPD outside accepted recovery limits	RL	Reporting Detection Limit	
	S	Spike Recovery outside accepted recovery limits			

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

WO#: 1406817

20-Jun-14

Client:	Blagg E	Engine	ering	

Project: ESKEENALWOOD # 1

Sample ID MB-13760	SampType: MBLK	TestCode: EPA Method	TestCode: EPA Method 300.0: Anions				
Client ID: PBS	Batch ID: 13760	RunNo: 19385					
Prep Date: 6/18/2014	Analysis Date: 6/18/2014	SeqNo: 560712	Units: mg/Kg				
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual		
Chloride	ND 1.5						
Sample ID LCS-13760	SampType: LCS	TestCode: EPA Method	200 0: Anione				
	campilypo. Loo	restoute. EFAmethou	JUU.U. AMONS				
Client ID: LCSS	Batch ID: 13760	RunNo: 19385	500.0. Amons				
			Units: mg/Kg				
Client ID: LCSS	Batch ID: 13760 Analysis Date: 6/18/2014	RunNo: 19385		RPDLimit	Qual		

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 2 of 6

WO#: 1406817

20-Jun-14

Hall Environmental Analysis Laboratory, Inc.

Client:Blagg EngineeringProject:ESKEENALWOOD # 1

Sample ID MB-13756	SampType: MBLK	TestCode: EPA Method	418.1: TPH	
Client ID: PBS	Batch ID: 13756	RunNo: 19338		
Prep Date: 6/18/2014	Analysis Date: 6/18/2014	SeqNo: 559119	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	ND 20			
Sample ID LCS-13756	SampType: LCS	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS	Batch ID: 13756	RunNo: 19338		
Prep Date: 6/18/2014	Analysis Date: 6/18/2014	SeqNo: 559120	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	81 20 100.0	0 81.1 80	120	
Sample ID LCSD-13756	SampType: LCSD	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS02	Batch ID: 13756	RunNo: 19338		
Prep Date: 6/18/2014	Analysis Date: 6/18/2014	SeqNo: 559121	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	87 20 100.0	0 86.6 80	120 6.58	20

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 3 of 6

WO#: 1406817

20-Jun-14

	Engineering								
Sample ID MB-13755	755 SampType: MBLK			TestCode: EPA Method 8015D: Diesel Range Organics					
Client ID: PBS	Batch ID: 13	F	RunNo: 1	9341					
Prep Date: 6/18/2014	Analysis Date: 6/	18/2014	S	SeqNo: 5	59117	Units: mg/H	(g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND 10						-		
Surr: DNOP	8.4	10.00		84.0	57.9	140			
Sample ID LCS-13755	SampType: LC	:S	Tes	tCode: El	PA Method	8015D: Dies	el Range C	Drganics	
Client ID: LCSS	Batch ID: 13	755	F	RunNo: 1	9341				
Prep Date: 6/18/2014	Analysis Date: 6/	18/2014	S	SeqNo: 5	59118	Units: mg/k	(g		
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	49 10	50.00	0	98.5	60.8	145			
Surr: DNOP	4.3	5.000		85.2	57.9	140			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 6

[.]

Hall	Environmental	Analysis	Laborat	ory, Inc.
				,

1

WO#: 1406817

20-Jun-14

_

Client: Blagg Engineering

Sample ID MB-13743 MK	SampT	SampType: MBLK Batch ID: R19352			tCode: El	e				
Client ID: PBS	Batch				RunNo: 19352					
Prep Date:	Analysis Date: 6/18/2014			vsis Date: 6/18/2014 SeqNo: 559936 I			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO) Surr: BFB	ND 890	5.0	1000		89.0	80	120			
Sample ID LCS-13743 MK	SampT	ype: LC	s	TestCode: EPA Method 8015D: Gasoline Rang				e		
Client ID: LCSS	Batch ID: R19352			RunNo: 19352						
				SeqNo: 559937						
Prep Date:	Analysis D	ate: 6/	18/2014	S	SeqNo: 5	59937	Units: mg/K	(g		
Prep Date: Analyte	Analysis D Result	ate: 6/ PQL		SPK Ref Val	SeqNo: 5 %REC	59937 LowLimit	Units: mg/K HighLimit	(g %RPD	RPDLimit	Qual
·	,				•			-	RPDLimit	Qual

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 5 of 6

Hall Environmenta	l Ana	lysis	Lab	oratory, 1	Inc.
-------------------	-------	-------	-----	------------	------

WO#: 1406817

20-Jun-14

.....

Client:Blagg EngineeringProject:ESKEENALWOOD # 1

Sample ID MB-13743 MK	Samp	Туре: М	BLK	Tes	tCode: El	PA Method	8021B: Vola			
Client ID: PBS	Batch ID: R19352			F	RunNo: 19352					
Prep Date:	Analysis Date: 6/18/2014			S	SeqNo: 5	59977	Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.0		1.000		102	80	120			
Sample ID LCS-13743 MK	Samp	Type: LC	S	Tes	tCode: El	PA Method	8021B: Volat	tiles		
Client ID: LCSS	Batc	h ID: R1	9352	F	lunNo: 1	9352				
Prep Date:	Analysis [Date: 6/	18/2014	S	eqNo: 5	59979	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.96	0.050	1.000	0	96.1	80	120			
Toluene	0.94	0.050	1.000	0	93.5	80	120			
Ethylbenzene	0.94	0.050	1.000	0	94.4	80	120			
Xylenes, Total	3.0	0.10	3.000	0	98.7	80	120			
,										
Surr: 4-Bromofluorobenzene	1.2		1.000		115	80	120			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 6

HALL ENVIRONMENTAL ANALYSIS LABORATORY	Albu TEL: 505-345-3975	Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com			Sample Log-In Check List										
Client Name: BLAGG	Work Order Number:	14068	317			RcptNo: 1									
Received by/date:	OU (18/14)	••••••	<u>.</u>		liyon The second se										
Completed By: Lindsay Mangin Reviewed By:	6/18/2014 8:14:84 AM			Struky H											
<u>Chain of Custody</u>	р -	Yes		No		Not Present 🗸									
2. Is Chain of Custody complete?		Yes		No		Not Present									
3. How was the sample delivered?		<u>Cour</u>		,											
Log In															
4. Was an attempt made to cool the same	les?	Yes	2	No	1	NA									
5. Were all samples received at a tempera	ature of >0° C to 6.0°C	Yes	V	No		NA									
6. Sample(s) in proper container(s)?		Yes		No	[_]										
7. Sufficient sample volume for indicated t	est(s)?	Yes		No]										
8. Are samples (except VOA and ONG) pr	operly preserved?	Yes	×	No	••										
9. Was preservative added to bottles?		Yes	: ,	No	✔.	NA									
10.VOA vials have zero headspace?		Yes	.	No		No VOA Vials 🗸									
11. Were any sample containers received t	proken?	Yes		No		# of preserved bottles checked									
12.Does paperwork match bottle labels? (Note discrepancies on chain of custody	()	Yes		No		for pH:	>12 unless note	d)							
13. Are matrices correctly identified on Chai		Yes	V	No		Adjusted?		.'							
14. Is it clear what analyses were requested		Yes	V	No											
15. Were all holding times able to be met? (If no, notify customer for authorization.)		Yes		No		Checked by:		. .							

Special Handling (if applicable)

Person N	lotified:			Date				•
By Whor	n: j	and a second		Via:	eMail	🗋 Phone 📋 Fax] In Perso	'n
Regardir	ig:				niste veine bet kielen in endochsingering er inter inter	ana na katana ana katana ana ana ana ana ana ana ana ana an	n farmen and annual sector of the sector	
Client Ins	structions:					an Tanari at Indiana maninari ana na ana ang Barti at	*** *	<u> </u>
	ę.							
Iditional rem	• • • •	· · · · · ·						
iditional rem	• • • •	· ·· · ·				. .		
ooler inforn	narks: nation	• • • • •	•					·
	narks: nation	Condition	Seal Intact	Seal No	Seal Date	Signed By		

.

			/ BP AMERICA	Standard Project Name:	Rush_	DAY											RA'	ΓΟ
Mailing Address: P.O. BOX 87		ESKEENALWOOD # 1 Project #: Project Manager:				49()1 Ha	w wkin	ww.h s NF									
BLOOMFIELD, NM 87413 Phone #: (505) 632-1199								5-345				505-						
										Anal	-					يوني تو ^{ني} مر ماطح يد م		
email or Fax#:							a. 1/			Ĩ								
QA/QC Pac	kaoe:		· · · · · · · · · · · · · · · · · · ·						AY A				0 0	S'			300.1)	
Standard Level 4 (Full Validation)		NELSON VELEZ			МВ's (8021В)	- Nuo Nuo	(ONIN)		l îs		0	PCB'						
Accreditation:		Sampler:	NELSON VI	ELEZ 975	-8	Gas	~ 1	=	SIN	1	0 ₂ , P	8082			water			
						H	ē	81 18	2		3°N			F	20			
🗆 EDD (T	ype)				frature: 2 .			+	88	4 y 4 y	0 8	tals	N NO	ides	2	Ş	.30	l o
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEALNO HOG8V7	BTEX + MTBE	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO / DRO	TPH (Method 418.1) FDR (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chlaride (soil - 300.0	Grab sample
6/17/14	1322	SOIL	5PC - TB @ 6' (21)	4 oz 1	Cool	-001	V			V							V	+
				+					<u>+</u>		+							+
				 					╌╼┾╸		┽━							+
			 	}					-+	-+-	+					-+		+
									-+									+
											+							-
				ļ							<u> </u>							
			•															
									T									1
				1							T							1
				1			·				1							+
									-+	-+-	+							+
Date: ,	Time:	Relinquishe	ed, by:	Received by:	L	Date Time	Rem	harks	L			L						
17/14	1535	9/1	n Vf	Minten.	Walter	6/11/1 1535	BIL	L DIR	ECTL	Y TO E			_				_	
Date:	Time:	Relinquishe	ed by:	Received by:		Date Time				0 Ene <u>N1</u>			Farm				'401 <u>EVH01</u>	<u>.BGT2</u>

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

June 12, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

ESKEENALWOOD 001 API 30-045-07137 (G) Section 25- T28N - R09W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 21 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Posel

Jeff Peace BP Field Environmental Advisor

(505) 326-9479

