District 1 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-144 Revised June 6, 2013 For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
12212 Proposed Alter	Pit, Below-Grade Tank, or native Method Permit or Closure I	Plan Application
$\begin{array}{c} \square \text{ Permit} \\ \blacksquare \text{ Closure} \\ \square \text{ Modified} \end{array}$	grade tank registration of a pit or proposed alternative method of a pit, below-grade tank, or proposed alternatication to an existing permit/or registration plan only submitted for an existing permitted or	NICT 3
or proposed alternative metho	od	
Please be advised that approval of this request does not environment. Nor does approval relieve the operator of	e application (Form C-144) per individual pit, below relieve the operator of liability should operations result i f its responsibility to comply with any other applicable go	n pollution of surface water, ground water or the
1. Operator: BP America Production Company	y OGRID #:	778
	NM 87401	
API Number:3004525552	OCD Permit Number:	
U/L or Qtr/QtrO Section20_	Township28N Range8W	County:San Juan
Center of Proposed Design: Latitude36.64	157Longitude107.70262	NAD: □1927 ⊠ 1983
Surface Owner: 🛛 Federal 🔲 State 🗋 Private 🗍		
String-Reinforced Liner Seams: Welded Factory Other		
Tank Construction material: Steel Secondary containment with leak detection	of fluid:Produced water	verflow shut-off omed - side walls not visible
4.		

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

23

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify_

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen 🗌 Netting 🗌 Other_

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank	□ Yes □ No □ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗌 Yes 🗍 No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	🗌 Yes 🗌 No
Below Grade Tanks	
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No

and the second sec	
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗍 No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	
	Yes No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	Yes 🗋 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	Yes No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes 🗌 No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	Yes 🗍 No
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC 	<i>cuments are</i>) NMAC 15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

12. Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.	documents are
 Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment 	
 Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC 	
 Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Outline Control Outline Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC 	
 Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan 	
Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan	
 Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	
13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)	
 On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial 	
Alternative Closure Method	
 Colosure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	
is. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa ake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	🗌 Yes 🗌 No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
Within a 100-year floodplain. - FEMA map	Yes No
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure planet by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannet Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	11 NMAC 15.17.11 NMAC
 17. Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed. 	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including cosure plan) Image: Plan (only) OCD Conditions (see attachment) OCD Representative Signature:	2014
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 10/19/2012	
20. Closure Method: Waste Excavation and Removal On-Site Closure Method If different from approved plan, please explain.	op systems only)
21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please intermark in the box, that the documents are attached.	

and the second se	
22. Operator Closure Certification:	
I hereby certify that the information and attachments submitted with belief. I also certify that the closure complies with all applicable cl	h this closure report is true, accurate and complete to the best of my knowledge and osure requirements and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Jeff Pose	Date:September 25, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Bolack 3E BGT Tank A (21 bbl) <u>API No. 3004525552</u> Unit Letter O, Section 20, T28N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

4

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. **Notice is attached.**
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number. **Notice is attached.**
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	78

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

 If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.

7

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.


 $\dot{\sim}$

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.



State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr.

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa Ea N							
	Santa Fe, N			<u> </u>				
Release r	Notification a	nd Co	orrective A	ction				
	0]	PERA	FOR		Initia	l Report	\square	Final Repo
Name of Company: BP		ntact: Jef						
Address: 200 Energy Court, Farmington, NM 8740		· ·	No.: 505-326-94					
Facility Name: Bolack 3E	Fac	ility Typ	e: Natural gas v	vell				
Surface Owner: Federal N	1ineral Owner: Fed	eral		A	PI No.	. 3004525:	552	
	LOCATION C		FASE					
· · · · · · · · · · · · · · · · · · ·	om the North/Sou		Feet from the	East/West	Line	County: S	an Juan	
O 20 28N 8W 790	South		2,045	East				
Latitude36.64157	7 L	ongitud	e_107.70262_					
	NATURE OI	F RELI	EASE					
Type of Release: none			Release: N/A			ecovered: 1		
Source of Release: below grade tank – 21 bbl, Tank A			lour of Occurrenc	e: Dat	e and I	Hour of Dis	covery	
Was Immediate Notice Given?		f YES, To	Whom?					
By Whom?	D	ate and E	lour					
Was a Watercourse Reached?			lume Impacting t	he Watercou	rse.	3		
🗌 Yes 🖾 No								
the BGT. Soil analysis resulted in TPH, BTEX and chlo	ride below standards.	. Analysı	s results are attacl	ned.				
Describe Area Affected and Cleanup Action Taken.* BG backfilled and compacted and is still within the active we		the area u	nderneath the BG	T was sampl	ed. Th	ie area unde	r the B	GT was
I hereby certify that the information given above is true a regulations all operators are required to report and/or file public health or the environment. The acceptance of a C should their operations have failed to adequately investig or the environment. In addition, NMOCD acceptance of federal, state, or local laws and/or regulations.	certain release notifi- 141 report by the NM gate and remediate con-	cations ar MOCD m ntaminati	nd perform correct arked as "Final R on that pose a thre	tive actions f eport" does n eat to ground	or rele ot relie water,	ases which eve the oper , surface wa	may en ator of ter, hui	danger liability nan health
Signature: Aff Page			OIL CON	SERVAT	ION I	DIVISIC	<u>N</u>	
Printed Name: Jeff Peace	Арр	proved by	Environmental S	pecialist:				
Title: Area Environmental Advisor	Арр	oroval Dat	e:	Expir	ation I	Date:		
E-mail Address: peace.jeffrey@bp.com	Con	ditions of	Approval:			Attached		
Date: September 25, 2014 Phone: 505-	326-9479							

* Attach Additional Sheets If Necessary

٩.

		P.O. BOX 87,		LD, NI		3	API #: 30	04525	
		(505) 632-119	99			(if applicble): _	At	D
FIELD REPO	RT:	cle one): BGT CONFIRMATIC	N / RELEASE INVEST	GATION /	other:		PAGE #:	1 of	f 1
SITE INFORM	ATION:	SITE NAME: BOL	ACK # 3E				DATE STARTED:	09/2	8/12
QUAD/UNIT: 0 SEC: 2	20 TWP: 28	N RNG: 8W	р <u>м: NM с</u> мт	Y: SJ	ST:	NM	DATE FINISHED:		
<u>1/4 -1/4/FOOTAGE: 790'S</u> LEASE #: SF080		SW/SE LEAS	SE TYPE: FEDERA	LKHOF	RN		ENVIRONMENTAL SPECIALIST(S):		СВ
REFERENCE		WELL HEAD (W.H.) (72 X 107.			LEV.: 5.	,749'
1) 21 BBL BGT (SV		GPS COORD.:	36.64157 X 10				ARING FROM WH.:	105', 9	·
2)	•	GPS COORD.:	-36.64153 X 10	7.70212			ARING FROM W.H.:	182',	399E
3)		GPS COORD.:			Dis	TANCE/BE	ARING FROM W.H.:		
4)		GPS COORD.:			DIS	TANCE/BE	ARING FROM W.H.:		
SAMPLING DA		IN OF CUSTODY RECORD(S) # OR LAB USED:	HA					OVM READING
1) SAMPLE ID:21_BC	GT 5pt. @ 7'	SAMPLE DATE: 09/28	B/12 SAMPLE TIME:	1432	LAB ANALYSIS:	418.1	<u>, 8015, 8021, 3</u>	800.0(CI)	(ppm) 1.2
2) SAMPLE ID:	3GT @ 10'	SAMPLE DATE: 09/28	B/12 SAMPLE TIME:	1437	LAB ANALYSIS:		NA		0.0
3) Sample ID:45 BC	3 T 5pt. @ 5	SAMPLE DATE:09/20	SAMPLE TIME.	1420	LÃO ANALYSIS.	410.1	, 0015, 0021, 9	98.9(0l)	
4) SAMPLE ID:		SAMPLE DATE:	SAMPLE TIME:		LAB ANALYSIS:				
SOIL DESCRI	PTION:	SOIL TYPE: SAND / SI				/FL / OT	HËR		
ANY AREAS DISPLAYING WETNES APPARENT EVIDENCE OF A				ANATION :					
ADDITIONAL COMMENTS:									
SOIL IMPACT DIMENSION E		NA ft. X NA					IMATION (Cubic) D TPH CLOSURE S	·	NA ppm
SITE SKETCH			PLOT P	LAN cir	cle: attache	d 0vM	Calib. Read. = 5	2.9 ppm	n RF = 0.52
								00 ppm	1
		$\overset{WELL}{HEAD}\oplus$			N	TIME	: _ 2:25 ampm	DATE: 09/	28/12
						'Г	MISCELI	NOT	ES
(2 ⁻ PBG	GTL (X	à				<u>w</u>	0: N150 <u>61</u>	600	
T.B. B.(`.^,	<i>y</i>					0#: 430008	4562	
							K:		
							J #: ermit date(s):	06/14/1	10
							CD Appr. date(s):		
						Tan ID	k OVM = Orga	nic Vapor Met	er
						Α	BGT Sidewalls V	isible: Y /	<u> </u>
X -	S.P.D.					-9	BCT Sideualle V		
NOTES: BGT = BELOW-GRADE TANK; E									
						AD;	BGT Sidewalls V		
T.B. = TANK BOTTOM; PBGTL =	PREVIOUS BELOW-GRA	ESSION; B.G. = BELOW GRADE; E IDE TANK LOCATION; SPD = SAMF DW - DOUBLE WALL; SB - SINGLE	PLE POINT DESIGNATION; R.V	N = RETAINING		AD;	BGT Sidewalls V lagnetic declina		

•

Hall Environmental Analysi	s Labora	itory, Inc.			Order 1210355 e Reported: 10/19/2012
CLIENT: Blagg Engineering Project: Bolack 3E				ate: 9/28/20	012 2:32:00 PM
Lab ID: 1210355-002	Matrix: Result	·····	Received D	Date: 10/4/20 DF	D12 10:34:00 AM
EPA METHOD 8015B: DIESEL RANGE	ORGANICS				Analyst: JMP
Diesel Range Organics (DRO)	ND	9.7	mg/Kg	1	10/6/2012 6:48:28 PM
Surr: DNOP	106	77.6-140	%REC	1	10/6/2012 6:48:28 PM
EPA METHOD 8015B: GASOLINE RANG	GE	,			Analyst: NSB
Gasoline Range Organics (GRO)	ND	5.0	mg/Kg	1	10/7/2012 8:55:12 AM
Surr: BFB	104	84-116	%REC	1	10/7/2012 8:55:12 AM
EPA METHOD 8021B: VOLATILES					Analyst: NSB
Benzene	ND	0.050	mg/Kg	1	10/7/2012 8:55:12 AM
Toluene	ND	0.050	mg/Kg	1	10/7/2012 8:55:12 AM
Ethylbenzene	ND	0.050	mg/Kg	1	10/7/2012 8:55:12 AM
Xylenes, Total	ND	0.099	mg/Kg	1	10/7/2012 8:55:12 AM
Surr: 4-Bromofluorobenzene	108	80-120	%REC	1	10/7/2012 8:55:12 AM
EPA METHOD 300.0: ANIONS					Analyst: SRM
Chloride	78	30	mg/Kg	20	10/9/2012 1:57:29 PM
EPA METHOD 418.1: TPH					Analyst: JMP

19

mg/Kg

ND

Analytical Report

10/10/2012

1

,

14

Petroleum Hydrocarbons, TR

v

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Method Blank
	Е	Value above quantitation range	Н	Holding times for preparation or analysis exceeded
	J	Analyte detected below quantitation limits	ND	Not Detected at the Reporting Limit
	Р	Sample pH greater than 2	R	RPD outside accepted recovery limits
	RL	Reporting Detection Limit	S	Spike Recovery outside accepted recovery limits Page 2 of 7

Hall Environmental Analysis Laboratory, Inc.

Client: Blagg Engineering Bolack 3E **Project:**

Y

Sample ID	1210356-001AMS	SampTy	/pe: M \$	6	Tes	tCode: El	PA Method	300.0: Anions	;		
Client ID:	BatchQC	Batch	ID: 42	04	F	RunNo: 6	099				
Prep Date:	10/9/2012	Analysis Da	ate: 10	0/9/2012	. 9	SeqNo: 1	75795	Units: mg/K	J	•	
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Chloride		15	7.5	15.00	4.533	67.0	64.4	117			
Sample ID	1210356-001AMSE) SampTy	pe: MS	SD	Tes	tCode: El	PA Method	300.0: Anions	i		
Sample ID Client ID:	1210356-001AMSE BatchQC		vpe: MS			tCode: Éf		300.0: Anions	i		
•			ID: 42		F		099	300.0: Anions Units: mg/Kg			
Client ID:	BatchQC	Batch	ID: 42	04)/9/2012	F	RunNo: 6	099			RPDLimit	Qual

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- Analyte detected below quantitation limits J
- Sample pH greater than 2 Р

- В Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded

١

- ND Not Detected at the Reporting Limit
 - R RPD outside accepted recovery limits

-

Hall Environmental Analysis Laboratory, In	c.
--	----

Client:Blagg EngineeringProject:Bolack 3E

ъ.

.

Sample ID MB-4193	SampType: MBLK	TestCode: EPA Method	418.1: TPH	
Client ID: PBS	Batch ID: 4193	RunNo: 6110		
Prep Date: 10/9/2012	Analysis Date: 10/10/2012	SeqNo: 176066	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	ND 20			
Sample ID LCS-4193	SampType: LCS	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS	Batch ID: 4193	RunNo: 6110		
Prep Date: 10/9/2012	Analysis Date: 10/10/2012	SeqNo: 176067	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	100 20 100.0	0 101 80	120	
Sample ID LCSD-4193	SampType: LCSD	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS02	Batch ID: 4193	RunNo: 6110		
Prep Date: 10/9/2012	Analysis Date: 10/10/2012	SeqNo: 176068	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	100 20 100.0	0 104 80	120 2.67	20

Qualifiers:

* Value exceeds Maximum Contaminant Level.

- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits

1210355

WO#:

19-Oct-12

Client: Blagg E Project: Bolack	ngineering 3E									
Sample ID MB-4147	SampType: I	MBLK	Tes	tCode: EF	PA Method	8015B: Dies	el Range (Drganics		
Client ID: PBS	Batch ID: 4	147	F	RunNo: 60	027					
Prep Date: 10/5/2012	Analysis Date:	10/6/2012	S	SeqNo: 17	73596	Units: mg/H	٢g			
Analyte	Result PQI	. SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Diesel Range Organics (DRO)	ND 1	0								
Surr: DNOP	10	10.00		101	77.6	140				
Sample ID LCS-4147	SampType: I	_CS	Tes	tCode: EF	PA Method	8015B: Dies	el Range (Drganics		
Client ID: LCSS	Batch ID: 4	147	F	RunNo: 60	027					
Prep Date: 10/5/2012	Analysis Date:	10/6/2012	S	eqNo: 17	73598	Units: mg/H	(g			
Analyte	Result PQI	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Diesel Range Organics (DRO)	35 1	0 50.00	0	69.4	52.6	130				
Surr: DNOP	4.3	5.000		85.4	77.6	140				
Sample ID 1210279-012CM	S SampType: I	ИS	Tes	tCode: EF	PA Method	8015B: Dies	el Range (Drganics		
Client ID: BatchQC	Batch ID:	Batch ID: 4138 RunNo: 6027								

Prep Date: 10/5/2012 Analysis Date: 10/7/2012 SeqNo: 173631 Units: %REC Analyte Result PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual Surr: DNOP 4.1 5.128 79.6 77.6 140 Sample ID 1210344-001AMS SampType: MS TestCode: EPA Method 8015B: Diesel Range Organics Client ID: BatchQC Batch ID: 4147 RunNo: 6027 Prep Date: 10/5/2012 Analysis Date: 10/6/2012 SeqNo: 173632 Units: mg/Kg PQL SPK value SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Analyte Result Qual

SampType: MSD Batch ID: 4138 Iysis Date: 10/7/2012	RunN	le: EPA Method lo: 6027 lo: 173633	8015B: Diesel	U	Organics	
lysis Date: 10/7/2012	2 SeaN	0. 172622				
		10. 173033	Units: %REC			
sult PQL SPK va	value SPK Ref Val %F	REC LowLimit	HighLimit	%RPD	RPDLimit	Qual
4.0 5.	5.097	77.7 77.6	140	0	0	
	- <u> </u>	4.0 5.097	4.0 5.097 77.7 77.6	4.0 5.097 77.7 77.6 140	4.0 5.097 77.7 77.6 140 0	4.0 5.097 77.7 77.6 140 0 0

0

72.7

57.2

146

	les campi	,po		100			0010010100	or ridinge i	Bigainee	
Client ID: BatchQC	Batch	n ID: 41	47	F	RunNo: 6	027				
Prep Date: 10/5/2012	Analysis D	ate: 1	0/6/2012	5	SeqNo: 1	73634	Units: mg/F	٢g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	36	10	51.39	0	70.5	57.2	146	3.11	24.5	
Surr: DNOP	4.6		5.139		88.9	77.6	140	0	0	

Qualifiers:

- Value exceeds Maximum Contaminant Level. *
- Value above quantitation range Е
- Analyte detected below quantitation limits J
- Sample pH greater than 2 Р

Diesel Range Organics (DRO)

35

9.7

48.31

- Analyte detected in the associated Method Blank В
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits

1210355 19-Oct-12

Client: Project:	Blagg En Bolack 3	gineering E									
Sample ID	MB-4146	 SampT	ype: MI		 Tes	tCode: EF	PA Method	8015B: Gasc	line Rang		
Client ID:	PBS	Batch	ID: 41	46	F	RunNo: 60)45				
Prep Date:	10/5/2012	Analysis D	ate: 10	0/7/2012	5	SeqNo: 17	74157	Units: mg/H	ζg		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	- %RPD	RPDLimit	Qual
	e Organics (GRO)	ND	5.0								
Surr: BFB		1000		1000		102	84	116			
Sample ID	LCS-4146	SampT	ype: LC	s	Tes	tCode: EP	PA Method	8015B: Gasc	line Rang	e	
Client ID:	LCSS	Batch	ID: 41	46	F	RunNo: 60)45				
Prep Date:	10/5/2012	Analysis D	ate: 10	0/7/2012	5	SeqNo: 17	4158	Units: mg/K	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range	e Organics (GRO)	25	5.0	25.00	0	102	74	117			
Surr: BFB		1100		1000		108	84	116			
Sample ID	1210321-001AMS	SampT	pe: MS	3	Tes	tCode: EP	A Method	8015B: Gasc	line Rang	e	·
Client ID:	BatchQC	Batch	ID: 41	46	F	RunNo: 60)45				
Prep Date:	10/5/2012	Analysis Da	ate: 10)/6/2012	S	GeqNo: 17	4160	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range	e Organics (GRO)	27	4.9	24.63	1.166	104	70	130			
Surr: BFB		1100		985.2		107	84	116			
Sample ID	1210321-001AMS	D SampT	/pe: M S	SD	Tes	tCode: EP	A Method	8015B: Gaso	line Rang	e	
Client ID:	BatchQC	Batch	ID: 41	46	Ĥ	RunNo: 60	45				
Prep Date:	10/5/2012	Analysis Da	ate: 10	0/6/2012	S	SeqNo: 17	4161	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
	e Organics (GRO)	25	4.8	23.92	1.166	99.6	70	130	6.78	22.1	
Gasoline Range		1000		956.9		110	84	116	0	0	
Gasoline Range Surr: BFB											
	5ML RB	SampTy	/pe: ME	BLK	Tes	tCode: EP	A Method	8015B: Gaso	line Rang	e	
Surr: BFB	5ML RB PBS	SampTy	/pe: ME 1D: R6			tCode: EP RunNo: 60		8015B: Gaso	line Rang	e	

Hall Environmental Analysis Laboratory, Inc.

Surr: BFB	1000		1000		101	84	116			
Sample ID 2.5UG GRO LCS	Samp [*]	Гуре: LC	cs	Tes	tCode: El	PA Method	8015B: Gaso	line Rang	le	
Client ID: LCSS	Batc	h ID: R	6073	F	RunNo: 6	073				
Prep Date:	Analysis [Date: 1	0/8/2012	Ś	SeqNo: 1	75097	Units: %RE	C		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: BFB	1100		1000		106	84	116			

SPK value SPK Ref Val %REC

Qualifiers:

Analyte

* Value exceeds Maximum Contaminant Level.

Result

PQL

E Value above quantitation range

J Analyte detected below quantitation limits

P Sample pH greater than 2

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

LowLimit

HighLimit

%RPD

RPDLimit

Qual

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

1210355 19-Oct-12

2 ۰. •1

Hall En	vironment	al Anal	ysis I	Laborat	ory, Inc.					WO#:	1210355 19-Oct-12
Client: Project:	Blagg Er Bolack 3	igineering E									
Sample ID	MB-4146	Samp	Гуре: МІ	BLK	Tes	tCode: E	PA Method	8021B: Vola	tiles		
Client ID:	PBS	Batc	h ID: 41	46	F	RunNo: 6	045				
Prep Date:	10/5/2012	Analysis [Date: 1	0/7/2012	S	SeqNo: 1	74190	Units: mg/k	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		ND	0.050								
Toluene		ND	0.050								
Ethylbenzene		ND	0.050								
Xylenes, Total		ND	0.10								
Surr: 4-Brom	ofluorobenzene	1.1		1.000		110	80	120			
Sample ID	LCS-4146	SampT	Гуре: LC	s	Tes	tCode: E	PA Method	8021B: Vola	tiles		
Client ID:	LCSS	Batcl	h ID: 41	46	F	RunNo: 6	045				
Prep Date:	10/5/2012	Analysis E	Date: 1	0/7/2012	S	SeqNo: 1	74191	Units: mg/H	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		1.1	0.050	1.000	0	107	76.3	117			
Toluene		1.1	0.050	1.000	0	106	80	120			
Ethylbenzene		1.1	0.050	1.000	0	108	77	116			
Xylenes, Total		3.2	0.10	3.000	0	108	76.7	117			
Surr: 4-Brome	ofluorobenzene	1.2		1.000		116	80	120			
Sample ID	1210344-001AMS	SampT	Гуре: М	6	Tes	tCode: E	PA Method	8021B: Vola	tiles		
Client ID:	BatchQC	Batcl	h ID: 41	46	F	RunNo: 6	045				
Prep Date:	10/5/2012	Analysis E	Date: 1	0/7/2012	ę	SeqNo: 1	74193	Units: mg/ł	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		0.86	0.049	0.9794	0.005819	87.4	67.2	113			
Toluene		0.86	0.049	0.9794	0	88.0	62.1	116			
Ethylbenzene		0.88	0.049	0.9794	0	90.0	67.9	127			
Xylenes, Total		2.6	0.098	2.938	0	89.7	60.6	134			
Surr: 4-Bromo	ofluorobenzene	1.1		0.9794		114	80	120			
Sample ID	1210344-001AMS	D Samp1	Type: MS	SD	Tes	tCode: El	PA Method	8021B: Vola	tiles		
Client ID:	BatchQC	Batcl	h ID: 41	46	F	RunNo: 6	045				
Prep Date:	10/5/2012	Analysis E	Date: 1	0/7/2012	5	SeqNo: 1	74194	Units: mg/ł	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		0.82	0.047	0.9337	0.005819	87.3	67.2	113	4.85	14.3	
Toluene		0.82	0.047	0.9337	0	88.0	62.1	116	4.86	15.9	
Ethylbenzene		0.84	0.047	0.9337	0	89.8	67.9	127	5.00	14.4	

Qualifiers:

Xylenes, Total

Value exceeds Maximum Contaminant Level. *

2.5

1.1

0.093

2.801

0.9337

0

E Value above quantitation range

Surr: 4-Bromofluorobenzene

- Analyte detected below quantitation limits J
- Р Sample pH greater than 2

- Analyte detected in the associated Method Blank В
- Holding times for preparation or analysis exceeded Н

60.6

80

- ND Not Detected at the Reporting Limit
 - R RPD outside accepted recovery limits

88.9

115

12.6

0

5.70

0

134

120

HALL ENVIRONMENTAL ANALYSIS LABORATORY

4.2

Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105 TEL: 505-345-3975 FAX: 505-345-410; Website: www.hallenvironmental.com

Sample Log-In Check List

Clier		ork Order Number: 1210355
Rec	eived by/date:	
Logg	ged By: Anne Thorne 10/4/2012 10:34:00 AM	ame the
Com	npleted By: Anne Thorne 10/5/2012	an Him
Revi	lewed By: 6 (0)0510	-
<u>Cha</u>	in of Custody	
1.	Were seals intact?	Yes 🗌 No 🗔 Not Present 🗹
2.	Is Chain of Custody complete?	Yes 🗹 No 🔲 Not Present 🗍
3.	How was the sample delivered?	Courier
<u>Log</u>	<u>In</u>	
4.	Coolers are present? (see 19. for cooler specific information)	Yes 🗹 No 🗌 🛛 NA 🗌
5.	Was an attempt made to cool the samples?	Yes 🗹 No 🗌 NA 🗍
6.	Were all samples received at a temperature of >0° C to 6.0°C	Yes 🗹 No 🗌 🛛 NA 🗌
7.	Sample(s) in proper container(s)?	Yes 🗹 No 🗔
8.	Sufficient sample volume for indicated test(s)?	Yes 🗹 No 🗌
9.	Are samples (except VOA and ONG) properly preserved?	Yes 🗹 No 🗌
10.	Was preservative added to bottles?	Yes 🗌 No 🗹 🛛 NA 🗌
11.	VOA vlais have zero headspace?	Yes 🔲 No 💭 No VOA Vials 🗹
12.	Were any sample containers received broken?	Yes No 🗹
	Does paperwork match bottle labels? (Note discrepancies on chain of custody)	Yes V No H # of preserved bottles checked for pH:
14.	Are matrices correctly identified on Chain of Custody?	Yes ☑ No
15.	Is it clear what analyses were requested?	Yes V No Adjusted?
	Were all holding times able to be met? (If no, notify customer for authorization.)	Yes 🗹 No 🗌 Checked by:
Spec	cial Handling (if applicable)	
	Was client notified of all discrepancies with this order?	Yes 🗌 No 💭 🛛 NA 🗹
	Person Notified: Date	
	By Whom: Via:	eMail Phone Fax In Person
	Regarding:	
	Client Instructions:	
I		

18. Additional remarks:

19. Cooler Information

Cooler No	Temp °C	Condition	Seal Intact	Seal No	Seal Date	Signed By
1	1.0	Good	Yes			

,

С	hain-	of-Cu	istody Record	Turn-Around	Time:	· · · · · · · · · · · · · · · · · · ·								_			• •			-		
Client:	BLAG	K EN	GINEERWG INC.	Standard	🗆 Rush	1														ENT ATC		
	BP	Ami	Thick .	Project Name	9:				. در هم	an distant		www										
Mailing	Address	P.0.	ERICA Box 87	BOL	Aek 31	2			49	01 H									7109			
			D NM 87413	Project #:						el. 50					-	-	-345					
			632-1199							and the second se												40 °
email or				Project Mana	ger:										Ĩ							
QA/QC F	^p ackage: dard		Level 4 (Full Validation)	J- E Sampler: J	xAGs			WB's (8021)	TPH (Gas only)	(Gas/Diesel)					PO4,SC	PCB's						
Accredi	tation	Othe	r	Sampler: J Ohluke:	- BLAC	•6 		BW1-1	+ TPH	15B (G	18.1)	04.1)	(HA)		0 ₃ ,NO ₂ ,	: / 8082		A)		1		or N)
	(Type)_			Sample Tem	VERTIFICATION OF T				Ш	d 80	4 p	0d 5	Р Р	Itals	N	ides	a	Ň				
Dáte	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	12 /m	AEN6	BTEX + WHEE	BTEX + MTBE	TPH Method 8015B	TPH (Method 418.1)	EDB (Method 504.1)	8310 (PNA or PAH)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	Cr_			Air Bubbles (Y
20/2	1420	501L		402×1	COUL		-601	X		X	X								Х		-†	+
11	1432	ι(21 BGT 5-P6@7'	L (Ч		-002	X		У	X			-+					X			+
												_							<u>``</u>			+
																						+-
																	_	_		-+		+
_																						+
																						-
																						+
												- ·					<u> </u>					+
																				\neg	\uparrow	+
							8															+
												T										
Date:	Time: Jくんの	Relinquishe	ld By:	Received by:	1 . L		Time - 1508			s: (0	OA	18	3019	5B				
Date:	Time:	Relinquiste	ed by:)]	Received by:	-weith	15/12 Date	Time	1		B			-									
73/12	1712	7 Juli	attre Uceles	A T	≥ 10	JD411	2103	ΥB.	PO	ONY	'Aei	-:	Je	FF	= F	PEF	<i>lek</i>	2_				

If necessary, samples submitted to Hall Environmental may be subcontracted to other accredited haboratories. It his serves as notice of this possibility Any sub-contracted data will be clearly notated on the analytical report



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

August 31, 2012

bp

• بر د

> Bureau of Land Management Mark Kelly 1235 La Plata Hwy Farmington, NM 87401

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: BOLACK 003E

Dear Mark Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about September 19, 2012. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

9D Velker

Jerry Van Riper Surface Land Negotiator BP America Production Company

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

September 13, 2012

× (

+

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

BOLACK 003E API 30-045-25552 (M) Section 20 – T28N – R08W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 21 bbl. BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Buddy Shaw BP Environmental Advisor

(505) 320-0401

