Submit 3 Copies To Appropriate District Office District I	State of New Me Energy, Minerals and Natu		Form C-103 Jun 19, 2008
1625 N. French Dr., Hobbs, NM 88240 District II	2		WELL API NO.
1301 W. Grand Ave., Artesia, NM 88210 District III			30-045-35460 5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410	, Aztec, NM 87410 1220 South St. Francis Dr. Santa Fe, NM 87505		STATE FEE
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	Sama re, Nivi 8	7303	6. State Oil & Gas Lease No. B-11479-59
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name State Gas Com A	
1. Type of Well: Oil Well Gas Well Other		8. Well Number 1E	
2. Name of Operator		9. OGRID Number	
ConocoPhillips Company		217817	
3. Address of Operator P.O. Poy 4389, Ferminator, NM, 87400, 4389		10. Pool name or Wildcat	
P.O. Box 4289, Farmington, NM 87499-4289		Blanco Mesaverde / Basin Dakota	
4. Well Location			
Unit Letter N: 700 feet from the South line and 1360 feet from the West line			
Section 36		ange 12W	NMPM San Juan County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 5880' GR			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
			SEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON ☐ CHANGE PLANS ☐	REMEDIAL WORK	_
TEMPORARILY ABANDON DULL OR ALTER CASING	CHANGE PLANS ☐ MULTIPLE COMPL ☐	CASING/CEMENT	
DOWNHOLE COMMINGLE			
_			OIL CONS. DIV.
OTHER: OTHER: SPUD REPORT 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date			
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion			
or recompletion.			
10/13/14 MIRU MOTE 207. Spud w/12 ½" bit @ 7:45 hrs on 10/13/14. Drilled ahead to 236. Circ hole & RIH w/7 jts, 9 5/8", 32.3#, H-40, ST&C csg set @ 231. RU to cmt. Pumped 5 bbls pre-flush & circ 15 bbls FW spacer. Pumped 76sx(122cf-22bbls=1.61yld), Type I-II cmt w/20% Fly-ash. Dropped plug & displaced w/14 bbls FW. Circ 5 bbls good cmt to surface. RD cmt. WOC. ND BOPE. RD RR @ 13:00 hrs on 10/13/14.			
PT will be conducted by Drilling Rig. Results will appear on next report.✓			
•			
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE TITLE Staff Regulatory Technician DATE 10-14-14			
Type or print name Dollie L. Busse E-mail address: dollie.l.busse@cop.com PHONE: 505-324-6104			
For State Use Only The St			
APPROVED BY:	TITLE	and a AMA II	DATE 10/24/14
Conditions of Approval (if any):	N		

PC