						ORM APPROVED DMB No. 1004-0137 pires: October 31, 2014
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an1 7 201 abandoned well. Use Form 3160-3 (APD) for such proposals.					5. Lease Serial No. NMNM-049989A 6. If Indian, Allottee or TOHENGONS. DIV DIST. 3 N/A	
SUBMIT IN TRIPLICATE - Other instructions on page 2.					7. If Unit of CA/Agreement, Name and/or No. N/A	
Type of Well Gas Well Other					8. Well Name and No.	
2. Name of Operator					Lybrook M35-2308 01H 9. API Well No. 30-045-35526	
Encana Oil & Gas (USA) Inc. 3a. Address	(include area cod	e)	10. Field and Pool or Exploratory Area			
370 17th Street, Suite 1700 Denvor, CO 8020	720-876-5867			Alamito-Gallup Pool		
4. Location of Well <i>(Footage, Sec., T.</i> SHL: 316 FSL and 1288 FWL Sec 35, T23N, I BHL: 330 FSL and 920 FWL Sec 2, T22N, R8	11. County or Parish, State San Juan County, NM					
12. CHE	CK THE APPROPRIATE BOX	K(ES) TO IND	CATE NATURE	OF NOTIO	CE, REPORT OR OTHE	ER DATA
TYPE OF SUBMISSION		TYPE OF ACTION				
Notice of Intent	of Intent Acidize		n re Treat	_	uction (Start/Resume)	Water Shut-Off
Subsequent Report	Casing Repair	New (	Construction	Reco	mplete	Other Production Liner
	Change Plans	Plug a	ind Abandon		porarily Abandon er Disposal	
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.) Utilized high performance water based mud from intermediate casing point (5157'MD) to TD of lateral. Kicked off lateral at 3712' on 9/27/14. Landed lateral at 5376' on 10/01/14. Length of lateral: 4565'. <u>TD of 9941'MD/4761'TVD</u> reached <u>10/03/14</u> . Set production liner 10/04/14. Hole diameter: <u>6.125</u> ", production string diameter: <u>4.5</u> ", production string weight and grade: <u>11.6# SB80</u> LTC. Depth of 6.125" hole from 5240'-9941'MD. Float shoe at 9939'MD. Float collar at 9893'MD. Production liner set from <u>4951'-9941'MD</u> . Set 13 external swellable casing packers for isolation of production string at the following depths: (1) 9537 (2) 9178' (3) 8852' (4) 8493' (5) 8173' (6) 7811' (7) 7446' (8) 7086' (9) 6735' (10) 6378' (11) 6025' (12) 5679' (13) 5332' Rig released 10/05/14						
					BY:_ <i>Will</i>	Field OFFICE
14. I hereby certity that the foregoing is true and correct. Name (Printed/Typed)			Title Operations Technician			
Cristi Bauer						
Signature CRISH BALLER Date 10/15/14						
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
Approved by	7.4			<b>.</b> .		
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would office conduct operations thereon.						
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.						
(Instructions on page 2)						

.

.

.