District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

Alternative Method:

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
12291 Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration OIL CONS. DIV DIST. 3
1 i = DD6 = 1 = 1 clinit of a pit of proposed ancimative method
Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration OCT 2 2 2014
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID#:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Allen A 1
API Number:3004508851 OCD Permit Number:
U/L or Qtr/QtrDSection1Township29NRange12WCounty:San Juan
Center of Proposed Design: Latitude36.76022 Longitude108.05615 NAD: ☐1927 ☒ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3,
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☑ Visible sidewalls only ☐ Other _Single walled/Double bottomed
Liner type: Thicknessmil

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
☐ Screen ☐ Netting ☐ Other	
Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
8. Variances and Exceptions:	<u> </u>
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank:	
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. ☐ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC	
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.	Yes No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)	☐ Yes ☐ No
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No							
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image								
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site								
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pit Non-low chloride drilling fluid								
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No							
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No							
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No							
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No							
Permanent Pit or Multi-Well Fluid Management Pit								
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No							
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.								
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No							
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.								
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC								
Previously Approved Design (attach copy of design) API Number: or Permit Number:								
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.								
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	15.17.9 NMAC							
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC								
Previously Approved Design (attach copy of design) API Number: or Permit Number:								

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.	documents are									
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment										
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC										
 □ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC □ Quality Control/Quality Assurance Construction and Installation Plan □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Nuisance or Hazardous Odors, including H₂S, Prevention Plan □ Emergency Response Plan □ Oil Field Waste Stream Characterization 										
 Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC 										
13.										
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.										
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative	luid Management Pit									
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)										
On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial										
Alternative Closure Method										
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC										
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable soun provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.										
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No									
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA									
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No									
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No									
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No									
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance										

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification: Learney certify that the information submitted with this application is to be a controlled to the controlled to th	. C
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 1/06/	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 1/06/	2014 the closure report.
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Title: OCD Permit Number: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 8/26/2014_ 20.	2014 the closure report.
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 1/06/2 Title: OCD Permit Number: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 8/26/2014	the closure report.

₹.

22.	
Operator Closure Certification:	and the true comments and comments to the heat of any large place and
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirements.	
Name (Print):Jeff Peace	Title: Area Environmental Advisor
Signature: Joff Poses	Date: _October 17, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Allen A 1 API No. 3004508851 Unit Letter D, Section 1, T29N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	52
Chlorides	US EPA Method 300.0 or 4500B	250 or background	12.2

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

* Attach Additional Sheets If Necessary

State of New Mexico Energy Minerals and Natural Resources

Form C-141
Revised August 8, 2011
Submit 1 Copy to appropriate District Office in

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	cation	and Co	orrective A	ction				
						OPERA'	ГOR		lnitial	Report	\boxtimes	Final Repor
Name of Co	ompany: B	3P				Contact: Jef	f Peace					
			ngton, N	M 87401								
Facility Na	me: Allen	<u>A 1</u>				Facility Typ	e: Natural gas v	vell				
Surface Ow	ner: Priva	te		Mineral (Owner: P	Private		AP	I No.	30045088	51	
				LOCA	ATION	OF RE	LEASE					
Unit Letter D	Section 1	Township 29N	Range 12W	Feet from the 790	North/S North	South Line	Feet from the 790	East/West L West	ine	County: Sa	n Juan	
		Lati	tude36	5.76022		Longitude	-108.05615_					
				NAT	TURE (OF REL	EASE					
Source of Re	lease: belov	w grade tank –	- 95 bbl			1	Iour of Occurrenc	e: Date	and H	lour of Disc	overy:	N/A
Was Immedi	ate Notice (Given?					Whom?	J <u></u> -				
			Yes [No 🛛 Not R	equired							
By Whom?												
Name of Company_BP Address: 200 Energy Court, Farmington, NM 87401 Telephone No: 505-326-9479 Facility Name: Allen A 1 Facility Name: Allen A 1 Facility Name: Allen A 1 Facility Spe: Natural gas well												
If a Watercon	ırse was Im	pacted, Descr	ibe Fully.*	k		<u> </u>						
		•										
									oval to	ensure no	soil imp	pacts from
the BGT. So	il analysis i	resulted in TPI	H, BTEX a	and chlorides belo	ow standa	ards. Analys	is results are attac	ched.				
Describe Are	a Affected	and Cleanup A	Action Tak	ren * BGT was re	moved a	nd the area u	nderneath the BG	T was sample	1 The	e area under	r the B(GT was
					illo rea al	na are area a	nderneum me Bo	1 was sample	J. 1110	area under	. the BC	31 Wd5
ı												
should their	perations h	nave failed to a	dequately	investigate and r	emediate	contaminati	on that pose a thre	eat to ground v	vater,	surface wat	ter, hum	nan health
				tance of a C-141	report do	es not reliev	e the operator of	responsibility f	for cor	npliance wi	ith any	other
rederal, state.	or local la	ws and/or regu	nations.				OIL CON	SERVATION	NI I	OIVISIO	N	
(OPP.	Roals	2				OIL COIN	JLIC VILLIC	JIN I	<u> </u>	11	
Signature:	MO	V SZE				Annawad hu	Environmental S	nooialist				
Printed Name	e: Jeff Peac	e						pecialist.				
Title: Area E	nvironmen	tal Advisor			A	Approval Dat	e:	Expirat	tion D	ate:		
E-mail Addre	ess: peace.j	effrey@bp.cor	Miner LO Downship Range 12W 790 Latitude 36.76022 Nade tank – 95 bbl In? Yes No No Ited, Describe Fully.* And Remedial Action Taken.* San Ited in TPH, BTEX and chlorides Cleanup Action Taken.* BGT was in ited in TPH, BTEX and chlorides Cleanup Action Taken.* BGT was in ited in the active well are in items. The acceptance of a C-141 failed to adequately investigate action, NMOCD acceptance of a C-ind/or regulations.			Conditions of	Approval:			Attached		
Date: Octob	Phone	e: 505-326 - 9479		•	•				_			

CLIENT: BP		X 87, BLOOMFI	ELD, NM 87413		ANK ID	Α.	
FIELD REPORT:	(circle one): BGT CON	FIRMATION / RELEASE INVE	STIGATION / OTHER:	P	AGE #:	1 of	f <u>1</u>
SITE INFORMATI	ON: SITE NAME:	ALLEN A#1		DA	TE STARTED:	08/2	2/14
QUAD/UNIT: D SEC: 1 T	MP: 29N RNG: 1	2W PM: NM C	NTY: SJ ST: N	M DA	TE FINISHED:		
1/4-1/4/FOOTAGE: 790'N / 7 9	0'W NW/N\	N LEASE TYPE: FEDER		N EN			
LEASE #:	PROD. FORMATION:	DK CONTRACTOR:	MBF - J. POWELL	SPI	ECIALIST(S):		B
REFERENCE POI	NT: WELL HEAD	(W.H.) GPS COORD.:	36.76010 X 108.05	5630	GL ELE	≣V.: 5 ,	,906'
1) 95 BGT (SW/DB)	GPS COORD.:_	36.76022 X 1	08.05615 DISTAN	NCE/BEARING I	FROM W.H.:	72', N	N53E
2)	Color Colo						
P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199 FIELD REPORT: (strie one): BST COMPRIATION; PRELASE INVESTIGATION / OTHER SITE INFORMATION: MWINW LEASE TYPE: PEDERAL ISTATE (FEE) INDIAN SPECIALISTIS: SITE INFORMATION: SITE INFORMATI							
	 ,			NCE/BEARING F	FROM W.H.:		
		_					
	•					(CI)	0.0
							
		ILTY SAND SILT / SILTY CLAY	// CLAY / GRAVEL / OTHER	· 			
\(\frac{1}{2}\)		,	•				LY PLASTIC
						HARD	
MOISTURE: DRY SLIGHTLY MOIST MOIS	T / WET / SATURATED / SUPER S	ATURATED				•	
		ANY AREAS DISF	PLAYING WETNESS: YES NO E	Explanatio	N		
		E EQUIDMENT: VES NO EVEL	ANATION				
APPARENT EVIDENCE OF A RELEASE OBS	ERVED AND/OR OCCURRED : YE	ES NO EXPLANATION:					
SOIL IMPACT DIMENSION ESTIMAT	ION: NA # X	NA n X N	J ∆ ff EXCAVATIO	N ESTIMA	TION (Cubic Ya	rds) ·	NΔ
	<u> </u>				•		^
SITE SKETCH	BGT Located: off	on site PLOT	PLAN circle: attached	OVM CALIF	READ = 52	9 nnn	1 55 050
1 1				, I	-		10 0.02
		(X)	< SECURITY ■	1 1			
		X X X	FENCE W	I N	ISCELL	NOT	FS
_			SEPARATOR	1			
			or with the				
	W.H.			PK:			
4 '	\			PJ#:		<u>-</u>	
			PROD.		,_,		
	-+		TANK				
P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199 FIELD REPORT: SITE INFORMATION: SITE OBSERVATIONS:							
	OLI AIGHOR		V CDD	11-2-			
NOTES: BGT = BFLOWLGRADE TANK: F.D. = FY/	AVATION DEPRESSION: B.G. = BELON	VGRADE: B = RELOW: TH = TEST HO		_	T Sidewalls Visi	ible: Y / I	٧
P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199 FIELD REPORT: Gride onth: BST CONFIRMATION RELEASE INVESTIGATION / OTHER PAGE # 1 of 1 ANALIZE IN FORMATION: SITE INFORMATION:							
	IINGLE WALL; DW - DOUBLE WALL; S			11			



PO Box 87

Bloomfield NM, 87413

Project Name:

Allen A #1

Project Number: Project Manager: 94034-0011

Jeff Blagg

Reported:

26-Aug-14 14:32

Analyical Report for Samples

Client Sample ID	Lab Sample ID	Matrix	Sampled	Received	Container
95 BGT 5-pt @ 6'	P408099-01A	Soil	08/22/14	08/22/14	Glass Jar, 4 oz.



Project Name:

Allen A #1

PO Box 87

Project Number:

94034-0011

Reported:

Bloomfield NM, 87413

Project Manager:

Jeff Blagg

26-Aug-14 14:32

95 BGT 5-pt @ 6' P408099-01 (Solid)

•									
		Reporting							
Analyte	Result	Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
Volatile Organics by EPA 8021									
Benzene	ND	0.05	mg/kg	1	1435004	08/25/14	08/25/14	EPA 8021B	
Toluene	ND	0.05	mg/kg	I	1435004	08/25/14	08/25/14	EPA 8021B	
Ethylbenzene	ND	0.05	mg/kg	1	1435004	08/25/14	08/25/14	EPA 8021B	
p,m-Xylene	ND	0.10	mg/kg	1	1435004	08/25/14	08/25/14	EPA 8021B	
o-Xylene	ND	0.05	mg/kg	1	1435004	08/25/14	08/25/14	EPA 8021B	
Total Xylenes	ND	0.05	mg/kg	l	1435004	08/25/14	08/25/14	EPA 8021B	
Total BTEX	ND	0.05	mg/kg	1	1435004	08/25/14	08/25/14	EPA 8021B	
Surrogate: Bromochlorobenzene		101 %	50-	150	1435004	08/25/14	08/25/14	EPA 8021B	
Surrogate: 1,3-Dichlorobenzene		97.4 %	50-	150	1435004	08/25/14	08/25/14	EPA 8021B	
Total Petroleum Hydrocarbons by 418.1									
Total Petroleum Hydrocarbons	52.0	35.0	mg/kg	I	1435005	08/25/14	08/25/14	EPA 418.1	
Cation/Anion Analysis									
Chloride	12.2	9.95	mg/kg	I	1435003	08/25/14	08/25/14	EPA 300.0	



Bloomfield NM, 87413

Project Name:

Allen A #1

PO Box 87

Project Number: Project Manager: 94034-0011

Jeff Blagg

Reported:

26-Aug-14 14:32

Volatile Organics by EPA 8021 - Quality Control

Envirotech Analytical Laboratory

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch 1435004 - Purge and Trap EPA 5030A										
Blank (1435004-BLKI)				Prepared: 2	25-Aug-14	Analyzed:	26-Aug-14			
Benzene	ND	0.05	mg/kg							
Toluene	ND	0.05	"							
Ethylbenzene	ND	0.05	"							
p,m-Xylene	ND	0.10	II.							
o-Xylene	ND	0.05	11							
Total Xylenes	ND	0.05	11							
Total BTEX	ND	0.05	**							
Surrogate: 1,3-Dichlorobenzene	52.4		ug/L	50.0		105	50-150			
Surrogate: Bromochlorobenzene	52.1		"	50.0		104	50-150			
Duplicate (1435004-DUPI)	Sou	rce: P408099-	01	Prepared: 2	25-Aug-14	Analyzed:	26-Aug-14			
Benzene	ND	0.05	mg/kg	•	ND				30	
Toluene	ND	0.05	**		ND				30	
Ethylbenzene	ND	0.05	**		ND				30	
p,m-Xylene	ND	0.10	u u		ND				30	
o-Xylene	ND	0.05	n		ND				30	
Surrogate: 1,3-Dichlorobenzene	49.3		ug/L	50.0		98.6	50-150	-		
Surrogate: Bromochlorobenzene	47.7		"	50.0		95.5	50-150			
Matrix Spike (1435004-MS1)	Sou	rce: P408099-	01	Prepared: 25-Aug-14 Analyzed: 26-Aug-14						
Benzene	47.6		ug/L	50.0	ND	95.3	39-150			
Toluene	49.2		n n	50.0	ND	98.3	46-148			
Ethylbenzene	49.1		11	50.0	ND	98.1	32-160			
p,m-Xylene	98.3		н	100	ND	98.3	46-148			
o-Xylene	48.8		11	50.0	ND	97.6	46-148			
Surrogate: 1,3-Dichlorobenzene	50.6	•	"	50.0		101	50-150			
Surrogate: Bromochlorobenzene	50.7		"	50.0		101	50-150			



Project Name:

Allen A #1

PO Box 87

Project Number: Project Manager: 94034-0011

Bloomfield NM, 87413

Jeff Blagg

Reported: 26-Aug-14 14:32

Total Petroleum Hydrocarbons by 418.1 - Quality Control

Envirotech Analytical Laboratory

		Reporting		Spike	Source		%REC		RPD	
Analyte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch 1435005 - 418 Freon Extraction										
Blank (1435005-BLK1)				Prepared &	Analyzed:	25-Aug-14				
Total Petroleum Hydrocarbons	ND	34.9	mg/kg							
Duplicate (1435005-DUP1)	· Sour	Prepared &	Analyzed:	25-Aug-14						
Total Petroleum Hydrocarbons	59.9	35.0	mg/kg		52.0			14.2	30	
Matrix Spike (1435005-MS1)	Sour	Prepared &	Analyzed:	25-Aug-14						
Total Petroleum Hydrocarbons	1880	34.9	mg/kg	2020	52.0	90.3	80-120			



Blagg Engineering PO Box 87

Project Name:

Allen A #1

Project Number:

94034-0011 Jeff Blagg

Reported:

Bloomfield NM, 87413

Project Manager:

26-Aug-14 14:32

Cation/Anion Analysis - Quality Control

Envirotech Analytical Laboratory

		Spike	Source		%REC		RPD			
Analyte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch 1435003 - Anion Extraction EPA	300.0									
Blank (1435003-BLK1)				Prepared &	Analyzed:	25-Aug-14	ļ			
Chloride	ND	9.97	mg/kg							
LCS (1435003-BSI)				Prepared &	Analyzed:	25-Aug-14	ļ.			
Chloride	· 481	9.92	mg/kg	496		96.9	90-110			
Matrix Spike (1435003-MS1)	Sour	Source: P408099-01			z Analyzed:	25-Aug-14	ļ			
Chloride	496	9.93	mg/kg	496	12.2	97.5	80-120			
Matrix Spike Dup (1435003-MSD1)	Sour	ce: P408099-	01	Prepared &	. Analyzed:	25 - Aug-14				
Chloride	492	9.85	mg/kg	493	12.2	97.5	80-120	0.716	20	



Project Name:

Allen A #1

PO Box 87

Bloomfield NM, 87413

Project Number: 94
Project Manager: Je

94034-0011

Jeff Blagg

Reported:

26-Aug-14 14:32

Notes and Definitions

DET

Analyte DETECTED

ND

Analyte NOT DETECTED at or above the reporting limit

NR

Not Renorted

dry

Sample results reported on a dry weight basis

RPD

Relative Percent Difference

CHAIN OF CUSTODY RECORD

17358

Client: BUSE BUSE	Eymeny	Project Name / Location: ALLEN A # 1								ANALYSIS / PARAMETERS													
Client: But Explain Froject Name / Location: ALEN A # 1 Email results to: jeff chlagge AUL Com Sampler Name: Peace je fray e Br. Com J. But 66 Client Phone No.: Client No.: G4034-0011								TPH (Method 8015)	BTEX (Method 8021)	VOC (Method 8260)	RCRA 8 Metals	' Anion		ith H/P	CO Table 910-1	18.1)	IDE		-	Cool	Intact		
Sample No:/ Identification	Sample Date	Sample Time	Lab No.	No./Volume of Containers		Preservative		ive	TPH (M	BTEX (VOC (N	RCRA	Cation / Anion	RCI	RCI	TCLP with H/P	CO Tab	TPH (418.1)	CHLORIDE			Sample Cool	Sample Intact
95 BGY 5-pe e 6	3/22/4	1352	P408099-01	١٧	402					X							×	X			У	У	
						-																	
					 	-		,						1			P		3				
												Bi	u	ک	CA.	j 26_							
						<u> </u>																	
															•								
Relinquished by: (Signature) Relinquished by: (Signature)			ج ج	Date 22/4		Rece	ved b	y: (S	ignati	ure)				n				•		Date	1	ime 4/%	
Relinguished by: (Signature)						Rece	ived b	y: (S	ignati	ure)											3		
Sample Matrix Soil Solid Sludge	Aqueous [] Other []																				
☐ Sample(s) dropped off after	r hours to se	cure drop c	ff area.	3 €	Anal	ytic) to	e (atory	Ì		ĺ	У,	Ц						1	<u>.</u>		
5795 US Highway &	34 • Farmingt	on, NM-874	01 • 505-632-0615 • 1	hree.Spri	ngs • 65 M	herca	do Stre	eet, S	uite 1	15,:D	urang	go, C	0.813	301 •	labo	ratory	⁄@en	virote	ch-inc	ccom			

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

August 20, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

ALLEN A 001 API 30-045-98851 (D) Section 1 – T29N – R12W San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around August 22, 2014.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

August 20, 2014

Animas Valley Land and Water Co. LLC PO Box 5520 Farmington, NM 57401

VIA CERTIFIED MAIL-RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: Allen A 001

To Whom it May Concern:

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about August 22, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

9D Vake

Surface Land Negotiator

BP America Production Company



