District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

· State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application Type of action: Below grade tank registration OIL CONS. DIV DIST. 3
25-23793 Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration OCT 3 0 2014
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID#:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Gallegos Canyon Unit 283
API Number:3004523793OCD Permit Number:
U/L or Qtr/Qtr B Section 29 Township 29N Range 12W County: San Juan
Center of Proposed Design: Latitude36.70218 Longitude108.12190 NAD: ☐1927 ☒ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no ☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Double walled/double bottomed; side walls not visible
Liner type: Thicknessmil
4. Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	•
 Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No

Oil Conservation Division

Form C-144

Page 2 of 6

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Wishin 200 fort from a name and maid and only in the first of the firs	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	cuments are
attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC	15.17.9 NMAC
Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
 □ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC □ Quality Control/Quality Assurance Construction and Installation Plan □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Nuisance or Hazardous Odors, including H₂S, Prevention Plan 	
 ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan 	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain.	Yes No
- FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 1//	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date:	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 1//	the closure report.
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date:	the closure report.
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 1/7/ Title: OCD Permit Number: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 1/3/2014	the closure report.

Form C-144 Oil Conservation Division Page 5 of 6

Operator Closure Certification:	
	ith this closure report is true, accurate and complete to the best of my knowledge and closure requirements and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Jeff Pasce	Date:October 29, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gallegos Canyon Unit 283 API No. 3004523793 Unit Letter B, Section 29, T29N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	86

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the raised compressor pad and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the raised compressor pad and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the raised compressor pad and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following:
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action OPERATOR Initial Report Final Report Name of Company: BP Contact: Jeff Peace Address: 200 Energy Court, Farmington, NM 87401 Telephone No.: 505-326-9479 Facility Name: Gallegos Canyon Unit 283 Facility Type: Natural gas well API No. 3004523793 Surface Owner: Private Mineral Owner: Private LOCATION OF RELEASE Unit Letter Section Township Feet from the North/South Line East/West Line Range Feet from the County: San Juan 29 29N 12W 990 2,500 В North East **Latitude** 36.70218 **Longitude** 108.12190 NATURE OF RELEASE Type of Release: none Volume of Release: N/A Volume Recovered: N/A Source of Release: below grade tank - 95 bbl, Tank A Date and Hour of Occurrence: Date and Hour of Discovery: Was Immediate Notice Given? If YES, To Whom? ☐ Yes ☐ No ☒ Not Required By Whom? Date and Hour Was a Watercourse Reached? If YES, Volume Impacting the Watercourse. ☐ Yes ☒ No If a Watercourse was Impacted, Describe Fully.* Describe Cause of Problem and Remedial Action Taken.* Sampling of the soil beneath the BGT was done during removal to ensure no soil impacts from the BGT. Soil analysis resulted in TPH, BTEX and chloride below standards. Analysis results are attached. Describe Area Affected and Cleanup Action Taken.* BGT was removed and the area underneath the BGT was sampled. The area under the BGT was backfilled and compacted and is still within the active well area. I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations. OIL CONSERVATION DIVISION Signature: Approved by Environmental Specialist: Printed Name: Jeff Peace Title: Field Environmental Coordinator Approval Date: Expiration Date: E-mail Address: peace.jeffrey@bp.com Conditions of Approval: Attached

Phone: 505-326-9479

Date: October 29, 2014

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG ENGINEEI P.O. BOX 87, BLOOMFI (505) 632-1	ELD, NM 87413	API #: 3004523793 TANK ID (if applicble): A
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVE		PAGE #: of
	29N RNG: 12W PM: NM CONTRACTOR:	ELKHORN MBF - S, GLYNN	DATE STARTED: 12/19/13 DATE FINISHED: ENVIRONMENTAL SPECIALIST(S): NJV
1) <u>95 BGT (DW/DB)</u> 2) 3)	WELL HEAD (W.H.) GPS COORD.: GPS COORD.: GPS COORD.: GPS COORD.: GPS COORD.:	08.12190 DISTANCE/BEA DISTANCE/BEA DISTANCE/BEA	RING FROM W.H.: 58', N71E RING FROM W.H.: RING FROM W.H.:
SAMPLING DATA: 1) SAMPLE ID:	CHAIN OF CUSTODY RECORD(S) # OR LAB USED: 15 SAMPLE DATE: 12/19/13 SAMPLE THE SAMPLE DATE: SAMPLE THE SAMPLE DATE: SAMPLE THE SAMPLE DATE: SAMPLE THE	### HALL ##: 1110 LAB ANALYSIS: 418.1/3 ###################################	8015B/8021B/300.0(CI) NA
	COHESIVE COHESIVE / HIGHLY COHESIVE DENSITY (COHESIVE FIRM) DENSE / VERY DENSE HC ODOR DETECT T / SATURATED / SUPER SATURATED OF PTS		
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE	S: LOST INTEGRITY OF EQUIPMENT: YES NO EXPL DAND/OR OCCURRED: YES NO EXPLANATION: (ES) NO EXPLANATION - COMPRESSOR LIFT V		
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <50' N SITE SKETCH	AREST WATER SOURCE: <1,000' NEAREST SU	RFACE WATER: <200' NMOO PLAN circle: attached 0VM	TIMATION (Cubic Yards) :
	PBGTL T.B. ~ 5' B.G.	BERM MP	MISCELL. NOTES /O: N15170279 O#: K: ZEVH01BGT2 J#: Z2-006Q0
w.н. ⊕ X - S.P.D.	✓ CC	MPRESSOR P	ermit date(s): 06/14/10 CD Appr. date(s): 02/19/13 OVM = Organic Vapor Meter ppm = parts per million BGT Sidewalls Visible: Y N BGT Sidewalls Visible: Y N
NOTES: BGT = BELOW-GRADE TANK, E.D. = EXCAVATION T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL	N DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H. = TEST H W-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; DB - DOUBLE E ONSI	R.W. = RETAINING WALL; NA - NOT NOTOM.	BGT Sidewalls Visible: Y / N lagnetic declination: 10° E

Analytical Report

Lab Order 1312A44

Date Reported: 1/3/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB@5' (95)

Project: GCU # 283

Collection Date: 12/19/2013 11:10:00 AM

Lab ID: 1312A44-001

Matrix: SOIL R

Received Date: 12/20/2013 10:00:00 AM

Analyses	Result	RL Qu	ıal Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	E ORGANICS				· Analys	st: JME
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	12/24/2013 11:30:00 F	PM 10940
Surr: DNOP	106	66-131	%REC	1	12/24/2013 11:30:00	PM 10940
EPA METHOD 8015D: GASOLINE RA	NGE				Analys	st: NSB
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	12/24/2013 6:24:18 Pi	M 10957
Surr: BFB	91.5	74.5-129	%REC	1	12/24/2013 6:24:18 P	M 10957
EPA METHOD 8021B: VOLATILES					Analys	st: NSB
Benzene	ND	0.047	mg/Kg	1	12/24/2013 6:24:18 PI	M 10957
Toluene	ND	0.047	mg/Kg	1	12/24/2013 6:24:18 PI	M 10957
Ethylbenzene	ND	0.047	mg/Kg	1	12/24/2013 6:24:18 PI	M 10957
Xylenes, Total	ND	0.094	mg/Kg	1	12/24/2013 6:24:18 PI	M 10957
Surr: 4-Bromofluorobenzene	102	80-120	%REC	1	12/24/2013 6:24:18 Pi	M 10957
EPA METHOD 300.0: ANIONS					Analys	st: JRR
Chloride	86	30	mg/Kg	20	12/26/2013 2:10:16 PI	M 10997
EPA METHOD 418.1: TPH					Analys	st: JME
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	12/23/2013	10942

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSD limit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit Page 1
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1312A44 03-Jan-14

Client:

Blagg Engineering

Project:

GCU # 283

Sample ID MB-10997

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 10997

RunNo: 15755

Prep Date: 12/26/2013 Analysis Date: 12/26/2013

SeqNo: 454831

Units: mg/Kg

Result **PQL**

SPK value SPK Ref Val %REC LowLimit

HighLimit

RPDLimit

Qual

Analyte Chloride

ND 1.5

Sample ID LCS-10997

SampType: LCS

TestCode: EPA Method 300.0: Anions

%RPD

Prep Date:

LCSS Client ID:

Batch ID: 10997

RunNo: 15755

12/26/2013

Analysis Date: 12/26/2013

SeqNo: 454832

Units: mg/Kg

Analyte

PQL SPK value SPK Ref Val

%REC

LowLimit

HighLimit

Qual

Result

Chloride

15.00

92.5

90

110

%RPD **RPDLimit**

14 1.5

Qualifiers:

Value exceeds Maximum Contaminant Level.

Spike Recovery outside accepted recovery limits

Value above quantitation range Е

Analyte detected below quantitation limits

RSD is greater than RSDlimit О

RPD outside accepted recovery limits R

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

P

Page 2 of 6

RLReporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1312A44

03-Jan-14

Client:

Blagg Engineering

Project:

GCU # 283

Sample ID MB-10942

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID:

Batch ID: 10942

RunNo: 15691

Prep Date: 12/23/2013 Analysis Date: 12/23/2013

SeqNo: 452690

Units: mg/Kg

Analyte

Client ID:

Result

SPK value SPK Ref Val %REC LowLimit

HighLimit

RPDLimit

Qual

Petroleum Hydrocarbons, TR Sample ID LCS-10942 ND

SampType: LCS

PQL

20

TestCode: EPA Method 418.1: TPH

RunNo: 15691

Prep Date: 12/23/2013

LCSS

Batch ID: 10942

Analysis Date: 12/23/2013

SeqNo: 452720

Units: mg/Kg

120

%RPD

Analyte Petroleum Hydrocarbons, TR Result **PQL**

SPK value SPK Ref Val

%REC 106

HighLimit LowLimit

%RPD

RPDLimit Qual

110 20 100.0

TestCode: EPA Method 418.1: TPH

Sample ID LCSD-10942

Client ID: LCSS02 Prep Date: 12/23/2013 SampType: LCSD Batch ID: 10942

RunNo: 15691 SeqNo: 452724

Units: mg/Kg

RPDLimit

Qual

Petroleum Hydrocarbons, TR

Result 100

Analysis Date: 12/23/2013 **PQL**

20

SPK value SPK Ref Val %REC 100.0

104

HighLimit 120 %RPD 1.16

20

Qualifiers:

Value exceeds Maximum Contaminant Level.

Spike Recovery outside accepted recovery limits

Value above quantitation range

Analyte detected below quantitation limits

RSD is greater than RSDlimit Ο

RPD outside accepted recovery limits

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

Reporting Detection Limit RL

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1312A44

03-Jan-14

Client:

Blagg Engineering

Project:

GCU # 283

Sample ID	MB-10939

SampType: MBLK

TestCode: EPA Method 8015D: Diesel Range Organics

Client ID: PBS

Batch ID: 10939

RunNo: 15679

Prep Date: 12/23/2013 Analysis Date: 12/24/2013

SeqNo: 452732

Units: %REC

Analyte

Result

101

Surr: DNOP

10

SPK value SPK Ref Val 10.00

%REC LowLimit HighLimit

131

RPDLimit

Qual

Sample ID MB-10940 PBS

SampType: MBLK

RunNo: 15679

TestCode: EPA Method 8015D: Diesel Range Organics

66

66

%RPD

%RPD

Client ID: Prep Date: Batch ID: 10940

Units: mg/Kg

Analyte

12/23/2013

Analysis Date: 12/24/2013

SeqNo: 452733

Result **PQL** ND

SPK value SPK Ref Val %REC LowLimit

HighLimit

RPDLimit

Qual

Diesel Range Organics (DRO) Surr: DNOP

10 10.00

SPK Ref Val

117

131

Sample ID LCS-10939

Client ID:

LCSS

SampType: LCS Batch ID: 10939

12

TestCode: EPA Method 8015D: Diesel Range Organics RunNo: 15679

Analyte Surr: DNOP

Prep Date: 12/23/2013

12/23/2013

Result

6.3

Analysis Date: 12/24/2013

SPK value

5.000

50.00

5.000

SeqNo: 452735

LowLimit

66

Units: %REC HighLimit

%RPD

Qual

RPDLimit

SampType: LCS

POL

Analysis Date: 12/24/2013

10

TestCode: EPA Method 8015D: Diesel Range Organics

%REC

RunNo: 15679

140

131

126

Prep Date:

Sample ID LCS-10940 Client ID: LCSS

Batch ID: 10940

Units: mg/Kg

131

131

Analyte Diesel Range Organics (DRO)

Surr: DNOP

Result **PQL**

70

6.5

SPK value SPK Ref Val

n

SeqNo: 452736 %REC

LowLimit

60.8

66

HighLimit 145 %RPD

RPDLimit Qual

Qualifiers:

Value exceeds Maximum Contaminant Level.

Spike Recovery outside accepted recovery limits

- Analyte detected below quantitation limits
- R RPD outside accepted recovery limits
- Value above quantitation range Е
- 0 RSD is greater than RSDIimit

- Analyte detected in the associated Method Blank В
- Not Detected at the Reporting Limit
- p Sample pH greater than 2 for VOA and TOC only.
- Reporting Detection Limit

Н

Holding times for preparation or analysis exceeded Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

Result

27

960

5.0

WO#: 13

1312A44 03-Jan-14

Client:

Blagg Engineering

Project:

Analyte

Surr: BFB

Gasoline Range Organics (GRO)

GCU # 283

Sample ID MB-10957	SampType: MBLK	TestCode: EPA Method	8015D: Gasoline Rang	e
Client ID: PBS	Batch ID: 10957	RunNo: 15727		
Prep Date: 12/23/2013	Analysis Date: 12/24/2013	SeqNo: 453870	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qua
Gasoline Range Organics (GRO)	ND 5.0			
Surr: BFB	880 1000	87.7 74.5	129	
Sample ID LCS-10957	SampType: LCS	TestCode: EPA Method	8015D: Gasoline Rang	e
Client ID: LCSS	Batch ID: 10957	RunNo: 15727		
Prep Date: 12/23/2013	Analysis Date: 12/24/2013	SeqNo: 453871	Units: mg/Kg	

LowLimit

74.5

74.5

109

95.6

HighLimit

126

129

%RPD

RPDLimit

Qual

SPK value SPK Ref Val , %REC

0

25.00

1000

Qua	ľ	i	fī	e	r	S
-----	---	---	----	---	---	---

* Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

O RSD is greater than RSDlimit

R RPD outside accepted recovery limits

S Spike Recovery outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

P Sample pH greater than 2 for VOA and TOC only.

RL Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1312A44

03-Jan-14

Client:

Blagg Engineering

Project:

GCU # 283

Sample ID MB-10957	Samp	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles							
Client ID: PBS	Batch ID: 10957 113 Analysis Date: 12/24/2013			F	RunNo: 1	5727						
Prep Date: 12/23/2013				S	SeqNo: 4	53911	Units: mg/K	g				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Benzene	ND	0.050					-					
Toluene	ND	0.050										
Ethylbenzene	ND	0.050										
Xylenes, Total	ND	0.10										
Surr: 4-Bromofluorobenzene	0.99		1.000		99.4	80	120					

Sample ID LCS-10957	s	TestCode: EPA Method 8021B: Volatiles											
Client ID: LCSS Batch ID: 10957					RunNo: 15727								
Prep Date: 12/23/2013	12/23/2013 Analysis Date: 12/24/2013 SeqNo: 453912			53912	Units: mg/Kg								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	1.1	0.050	1.000	0	108	80	120						
Toluene	1.0	0.050	1.000	0	104	80	120						
Ethylbenzene	1.1	0.050	1.000	0	106	80	120						
Xylenes, Total	3.1	0.10	3.000	0	105	80	120						
Surr: 4-Bromofluorobenzene	1.1		1.000		106	80	120						

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 6 of 6



Hall Environmental Analysis Laboratory
4901 Hawkins NE
Albuquerque, NM 87105
TEL: 505-345-3975 FAX: 505-345-4107
Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name:	BLAGG		Work Order Nu	mber: 1312A44		RcptNo	: 1
Received by/da	te:		12/20/13				
Logged By:	Lindsay Ma	angin	12/20/2013 10:00):00 AM	Julyth	<i>€</i> 0	
Completed By:	Lin d say Ma	angin	12/21/2013/9:27:	27 AM	Juney He	p o	
Reviewed By:	4	≥ 1	H 23/13				
Chain of Cus	stody	()	10-21-2				
1. Custody sea	als intact on sa	mple bottles?		Yes 🗌	No [Not Present ✓	
2. Is Chain of	Custody compl	ete?		Yes 🗹	No [□ Not Present □	
3. How was the	e sample delive	ered?		Courier			
<u>Log In</u>							
4. Was an atte	empt made to	cool the samples?		Yes 🗹	No [□ NA □	
5. Were all sar	mples received	l at a temperature	of >0° C to 6.0°C	Yes 🗹	No 🗆] NA □	
6. Sample(s) i	n proper conta	iner(s)?		Yes 🗸	No [
7. Sufficient sa	imple volume f	or indicated test(s))?	Yes 🗹	No [
8. Are samples	except VOA	and ONG) properly	y preserved?	Yes 🗹	No 🗆]	
9. Was presen	vative added to	bottles?		Yes 🗌	No ⊻	na 🗆	
10.VOA vials h	ave zero heads	space?		Yes 🗌	No 🗆	No VOA Vials ✓	
11. Were any s	ample contains	ers received broke	n?	Yes	No 🛚	# of preserved	
12.Does papen	work motob bo	Hla inhola?		Yes 🔽	No 🗆	bottles checked	
	pancies on cha		•	162	110 _		or >12 unless noted)
13. Are matrices	s correctly iden	tified on Chain of (Custody?	Yes 🗹	No 🗆	Adjusted?	
14. Is it clear wh				Yes 🗹	No L		
15. Were all hole (If no, notify	ding times able customer for a			Yes 🗹	No L	Checked by:	***************************************
Special Hand	lling (if app	licable)			_		
16. Was client r	otified of all di	screpancies with the	nis order?	Yes 🗆	No [NA 🗹	_
Perso	n Notified:		Da	ate:	CONTRACTOR OF WATERWAYS TO THE		
By Wi	<u>E</u>		Vi	a: 🗌 eMail 🛚] Phone [] Fa	ax 🗌 In Person	
Regar	· ·	ngana ana 11 sa asawa sarraman ar kara shusan sa tu abad daga l	and a present the second s				
17. Additional r	Instructions:		Alberton states seates seates and military makes	gers temporal a service para del de tra componente	COMPANY OF THE PROPERTY OF THE	Control of the second of the s	
18. Cooler Info	o <u>rmation</u> lo Temp°C	Condition Se	al Intact Seal N	o Seal Date	Signed By	77.77 Sayal	
1	1.0	Good Yes					

Chain-of-Custody Record			Turn-Around Time:				l .				I A I			MM	T E	2	MB	ИF	NT	ΑI		
Client:	BLAGE	める	R. BP AMERICA	Standard 🗆 Rush]	200	_												7
				Project Name:				ANALYSIS LABORATORY www.hallenvironmental.com														
Mailing Address: P.O. BOX 87 BLOCKT IELD, NM 87413			GCN # 283				4901 Hawkins NE - Albuquerque, NM 87109															
			Project #:	Project #:				Tel. 505-345-3975 Fax 505-345-4107														
Phone #: (505) 63 2 - 1199			1				Analysis Request															
			Project Mana	ger:		7nV	8	(yle	₽	/		*)4)								
QA/QC Package: Standard □ Level 4 (Full Validation)			NELSON VELEZ TIV				4B's (8021g)	TPH (Gas only)	DRO / MRO	The		SIMS)		,PO ₄ ,S(PCB's			0,		T.	,	
Accreditation □ NELAP □ Other			Sampler: On Ice Vest and No.				TAND	+	(GRO / DF	418.1)	04.1)	8270		O ₃ ,NO ₂	s / 8082		(Y (320		Posn	or N)	
□ EDD (Type)			Sample Tem	perature.	O		19E	品	(G	8 P	g	ō 0	etals	N,	cide	(Y	<u> </u>	13		wa	\	
Date	Time	Matrix		Type and #	Preservative Type		AENO	BTEX +₩	BTEX + MTBE	TPH 8015B	TPH (Method	EDB (Method 504.1)	PAH's (8310 or	RCRA 8 Metals	Anions (F,CI,NO3,NO2,PO4,SO4)	8081 Pesticides / 8082 PCB's	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE		5 PT. C	Air Bubbles (Y or N)
419/13	1110	5016	5PC-TB & 5 (95)	402 -1	COOL		-001	V													7/	1
																					1	\top
												_								\neg	1	†
					• ***																1	+
																					+	+
								1													+	+-
<u> </u>	<u> </u>															_			\vdash		+	+-
								1											$\mid - \mid$		+	+
		·														_			$\vdash \vdash$	+	+	+-
								\vdash				$\neg \dashv$			_	\vdash	 		$\vdash \vdash$	_	+	+-
	-							+								-			\vdash	-	+	+-
	<u> </u>	 			1			T				_					_		\vdash	-	+	+-
Date: / 2/19/13	Time:	Relinquish	had by	Received by: Date Time Language Z/19/13/15/15/15				Remarks: BILL DILECTLY TO BP											Т_			
Date: 12/19/13	Time:	Relinquist	hed by: (Received by: Date Time 13/2013					WORK ORDER: NIS170279 O PAYKEY: ZEVHOIBETZ													
tentra	If necessary		brnitted to Hall Environmental may be sub	contracted to other a	ccredited laboratoric	es. This serv	es as notice of this	s possi	bility.	, , ,		<u> </u>	l data v	will be	dear	y nota	ited on	the a	nalytica	al report.		

B



