•		
 District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 	State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-144 Revised June 6, 2013 For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
	Pit, Below-Grade Tank, or	n na haran n
12311 Proposed Alter	rnative Method Permit or Closure F	Plan Application
Type of action: 🔲 Below	grade tank registration	OIL CONS. DIV DIST. 3
☐ Modifi	of a pit or proposed alternative method e of a pit, below-grade tank, or proposed alternati cation to an existing permit/or registration e plan only submitted for an existing permitted or	
or proposed alternative meth	iod ie application (Form C-144) per individual pit, below-	anada tank an altamatina naquast
Please be advised that approval of this request does not	t relieve the operator of liability should operations result in f its responsibility to comply with any other applicable go	n pollution of surface water, ground water or the
1. Operator: BP America Production Compan	y OGRID #:7	778
Address: 200 Energy Court, Farmington,	NM 87401	
Facility or well name: Gallegos Canvon U	nit 152	
	OCD Permit Number:	
	Township29NRange12W	
	0745Longitude108.11012	
^{2.} <u> Pit:</u> Subsection F, G or J of 19.15.17.11 NM	IAC	
Temporary: Drilling Workover		
Lined Unlined Liner type: Thickness	P&A Multi-Well Fluid Management Lo mil LLDPE HDPE PVC Ot	
☐ String-Reinforced Liner Seams: ☐ Welded ☐ Factory ☐ Other _	Volume:bbl	Dimensions: Lx Wx D
3. Below-grade tank: Subsection I of 19.15.17.	.11 NMAC Tank A	<u> </u>
	e of fluid:Produced water	
Tank Construction material:Steel		
	Visible sidewalls, liner, 6-inch lift and automatic ov	verflow shut-off
	alls only \boxtimes Other Double walled/double bott	
	HDPE PVC Other	
4.	· · · · · · · · · · · · · · · · · · ·	

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Page 1 of 6

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify

,

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other_

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting	
<u>Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.</u> - ☐ NM Office of the State Engineer - iWATERS database search; ☐ USGS; ☐ Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗋 Yes 🗌 No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	📋 Yes 🗌 No
Below Grade Tanks	
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗋 Yes 🗍 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes 🗋 No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes 🗌 No
<u>Permanent Pit or Multi-Well Fluid Management Pit</u>	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes 🗌 No
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Design Plan - Approximation (ettersh ecem of design) Applicable) - Appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	cuments are 9 NMAC 15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	.15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

•

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the a attached.	documents are			
 Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment 				
 Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC 				
 Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC 				
 Sperating and Mandematice Frain - based upon the appropriate requirements of 19.15.17.11 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan 				
 Oil Field Waste Stream Characterization Monitoring and Inspection Plan 				
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC				
^{13.} <u>Proposed Closure</u> : 19.15.17.13 NMAC <i>Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.</i>				
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fl	luid Management Pit			
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial				
Alternative Closure Method				
 <u>Waste Excavation and Removal Closure Plan Checklist</u>: (19.15.17.13 NMAC) <i>Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached.</i> Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC 	attached to the			
 Commutation Subjection C of 19.15.17.15 NWAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 				
^{15.} <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.				
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA			
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA			
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	 Yes No NA 			
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No			
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗍 No			
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗍 No			
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No			
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance				

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗍 No
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
Within an unstable area.	
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes 🗌 No
Within a 100-year floodplain. - FEMA map	Yes No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure p by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cant Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC 15.17.11 NMAC
17. Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and below Name (Print):	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) Glosure Plan (only) OCD Conditions (see attachment) OCD Representative Signature:	2014
19.	· · · · · · · · · · · · · · · · · · ·
<u>Closure Report (required within 60 days of closure completion)</u> : 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do no section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
Closure Completion Date:1/24/2013_	
 20. Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-In If different from approved plan, please explain. 	oop systems only)

^r, ^{22.} <u>Operator Closure Certification</u>:

.

I hereby	certify that the inform	mation and attachments	submitted with this c	losure report is true,	accurate and com	plete to the best of	my knowledge and
belief.	also certify that the	closure complies with al	l applicable closure r	equirements and cor	ditions specified i	n the approved clos	ure plan.

Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Jaff Pare	Date:October 29, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Gallegos Canyon Unit 152, BGT Tank A (95 bbl)</u> <u>API No. 3004507975</u> <u>Unit Letter M, Section 21, T29N, R12W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

No notice was made due to misunderstanding of the BGT notice requirements at that time.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)

0

- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)
 All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.
- 4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50 .	ND
TPH	US EPA Method SW-846 418.1	100	120
Chlorides	US EPA Method 300.0 or 4500B	250 or background	150

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

> Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. TPH was 120 ppm by Method 418.1, but was only 49 ppm by Method 8015B. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

3

- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP BGT Closure Plan 04-01-2010

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

•

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Revised August 8, 2011 Copy to appropriate District Office in

Form C-141

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

1220 S. St. Francis Dr., Santa Fe, NM 87505 Santa	a Fe, NM 87505	
Release Notificat	tion and Corrective A	ction
	OPERATOR	🔲 Initial Report 🛛 Final Repo
Name of Company: BP	Contact: Jeff Peace	
Address: 200 Energy Court, Farmington, NM 87401	Telephone No.: 505-326-94	79
Facility Name: Gallegos Canyon Unit 152	Facility Type: Natural gas w	
Surface Our on Federal		
Surface Owner: Federal Mineral Own	ler: Federal	API No. 3004507975
LOCAT	ION OF RELEASE	
	orth/South Line Feet from the buth 1,110	East/West Line County: San Juan West
Latitude36.70745	Longitude108.11012	
NATU	RE OF RELEASE	
Type of Release: none	Volume of Release: N/A	Volume Recovered: N/A
Source of Release: below grade tank – 95 bbl, Tank A	Date and Hour of Occurrence	
Was Immediate Notice Given?	If YES, To Whom?	······································
🗌 Yes 🔲 No 🛛 Not Requi	red	
By Whom?	Date and Hour	
Was a Watercourse Reached?	If YES, Volume Impacting the	he Watercourse.
Yes X No		
If a Watercourse was Impacted, Describe Fully.*		
the BGT. Soil analysis resulted in TPH, BTEX and chloride below sta 8015D. Analysis results are attached. Describe Area Affected and Cleanup Action Taken.* BGT was remov backfilled and compacted and is still within the active well area.		
I hereby certify that the information given above is true and complete regulations all operators are required to report and/or file certain releas public health or the environment. The acceptance of a C-141 report by should their operations have failed to adequately investigate and reme- or the environment. In addition, NMOCD acceptance of a C-141 report federal, state, or local laws and/or regulations.	se notifications and perform correct y the NMOCD marked as "Final Re diate contamination that pose a thre	tive actions for releases which may endanger eport" does not relieve the operator of liability eat to ground water, surface water, human health
Signature: Joff Pooce	<u>OIL CONS</u>	SERVATION DIVISION
Printed Name: Jeff Peace	Approved by Environmental Sp	pecialist:
Title: Field Environmental Coordinator	Approval Date:	Expiration Date:
E-mail Address: peace.jeffrey@bp.com	Conditions of Approval:	Attached
Date: October 29, 2014 Phone: 505-326-9479		

* Attach Additional Sheets If Necessary

?	CLIENTE BP	BLAGG ENGINEERING, INC.	API# 3004507975
	CLIENT:	P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	TANK ID (if applicble): A & B
	FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER:	PAGE #: _1_ of _1_
	SITE INFORMATION QUAD/UNIT: M SEC: 21 TWP:		DATE STARTED: 01/17/13
	1/4 -1/4/FOOTAGE: 1,010'S / 1,110'	N SW/SW LEASE TYPE: FEDERAL/ STATE / FEE / INDIAN	DATE FINISHED: ENVIRONMENTAL SPECIALIST(S):NJV
ł	LEASE #: NM 078391C REFERENCE POINT	PROD. FORMATION: DK CONTRACTOR: MBF - C. ZELLITTI WELL HEAD (W.H.) GPS COORD.: 36.70766 X 108.1099	
	1) 95 BGT (DW/DB) - A 2)	GPS COORD.: 36.70745 X 108.11072 DISTANCE/	BEARING FROM W.H.: 115', S39W
	3)		BEARING FROM W.H.:
	· · · · · · · · · · · · · · · · · · ·	GPS COORD.: DISTANCE/	BEARING FROM W.H.:
		CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL SAMPLE DATE: 01/17/13 SAMPLE TIME: 1435 LAB ANALYSIS: 418 01/17/13 SAMPLE TIME: 1435 LAB ANALYSIS: 418	READING (ppm) 3.1/8015/8021/300.0(Cl) NA
	 2) SAMPLE ID:	SAMPLE DATE: 01/17/13 SAMPLE TIME: 1305 LAD AVAILYSIS 418 SAMPLE DATE:	2.1/8015/8021/300.0(Cl) NA-
	4) SAMPLE ID:	SAMPLE DATE:	
	ANY AREAS DISPLAYING WETNESS: YES NO	T SATURATED / SUPER SATURATED HC ODOR DETECTED: YES NO EXPLANATION - 5 OF PTS. 5 YES NO EXPLANATION - VARYING GRAYS BENEATH BOTH BGTS. EXPLANATION - BENEATH 21 BOT (SATURATED)	PLANATION - "<u>DENEATH 21 DGT-</u> WEEN 8'-10' B.G.
	ADDITIONAL COMMENTS: RECOMMEN	BSERVED AND/OR OCCURRED : YES NO EXPLANATION : DISCOLORED SO DED TO CREW TO DILUTE & AERATE IMPACTED/DISCOLORED SOILS & LEAN	VE IN PLACE AT BOTH BGTS.
	SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: N		STIMATION (Cubic Yards) : <u>NA</u> OCD TPH CLOSURE STD: <u>100</u> ppm
	SITE SKETCH	₩.H. N 1	WM CALIB. READ. = NA ppm WM CALIB. GAS = NA ppm ME: NA am/pm DATE: MISCELL. NOTES WO: N15073570
	210 E		РО #: РК: ZEVH01BGT2
	DOWN SLOPE DIRECTION	SEP. (95) X X X X T.B. ~ 6' B.G. (95) - 10'X10'X3' X - S.P.D.	PJ #: Z2-00690-C Permit date(s): 06/14/10 OCD Appr. date(s): 07/17/12 Tairk OVM = Organic Vapor Meter ID ppm = parts per million A BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N
	T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW-SINGLE	N DEPRESSION, B.G. = BELOW GRADE; B = BELOW, T.H. = TEST HOLE; ~ = APPROX.; W.H. = WELL HEAD; DW-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING WALL; NA - NOT WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; DB - DOUBLE BOTTOM. ONSITE: 01/17/13	Magnetic declination: 10° E
	TRAVEL NOTES: CALLOUT:	ONSITE:	

٠.

Hall Environmental Analy	sis Labora	tory, Inc.			b Order 1301606 te Reported: 1/24/2013
CLIENT: Blagg Engineering Project: GCU #152 Lab ID: 1301606-001	Matrix:	SOIL		ate: 1/17/2	'B @ 7' (95) 013 2:35:00 PM 013 9:53:00 AM
Analyses	Result	RL Qu	al Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	E ORGANICS				Analyst: MMD
Diesel Range Organics (DRO)	49	10	mg/Kg	1	1/23/2013 10:14:37 PM
Surr: DNOP	88.3	72.4-120	%REC	1	1/23/2013 10:14:37 PM
EPA METHOD 8015B: GASOLINE RA	NGE				Analyst: NSB
Gasoline Range Organics (GRO)	ND	4.6	mg/Kg	1	1/22/2013 3:19:24 AM
Surr: BFB	98.6	84-116	%REC	1	1/22/2013 3:19:24 AM
EPA METHOD 8021B: VOLATILES					Analyst: NSB
Benzene	ND	0.046	mg/Kg	1	1/22/2013 3:19:24 AM
Toluene	ND	0.046	mg/Kg	1	1/22/2013 3:19:24 AM
Ethylbenzene	ND	0.046	mg/Kg	1	1/22/2013 3:19:24 AM
Xylenes, Total	ND	0.092	mg/Kg	1	1/22/2013 3:19:24 AM
Surr: 4-Bromofluorobenzene	104	80-120	%REC	1	1/22/2013 3:19:24 AM
EPA METHOD 300.0: ANIONS					Analyst: JRR
Chloride	150	30	mg/Kg	20	1/22/2013 3:10:24 PM
EPA METHOD 418.1: TPH					Analyst: ECH
Petroleum Hydrocarbons, TR	120	20	mg/Kg	1	1/23/2013 12:00:00 PM

Analytical Report

of 7

.

۱ ب

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Method Blank
C C	E	Value above quantitation range	Н	Holding times for preparation or analysis exceeded
	J	Analyte detected below quantitation limits	ND	Not Detected at the Reporting Limit
	Р	Sample pH greater than 2	R	RPD outside accepted recovery limits
	RL	Reporting Detection Limit	S	Spike Recovery outside accepted recovery limits

Hall Environmental Analysis Laboratory, Inc.

Client:Blagg EngineeringProject:GCU #152

۱ ۹.

Sample ID MB-5770	SampType: MBLK	TestCode: EPA Method	300.0: Anions				
Client ID: PBS	Batch ID: 5770	RunNo: 8194					
Prep Date: 1/22/2013	Analysis Date: 1/22/2013	SeqNo: 236972	Units: mg/Kg				
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual			
Chloride	ND 1.5						
Sample ID LCS-5770	SampType: LCS	SampType: LCS TestCode: EPA Method 300.0: Anions					
	Batch ID: 5770 RunNo: 8194						
Client ID: LCSS	Batch ID: 5770	RunNo: 8194					
Client ID: LCSS Prep Date: 1/22/2013	Batch ID: 5770 Analysis Date: 1/22/2013	RunNo: 8194 SeqNo: 236973	Units: mg/Kg				
	Analysis Date: 1/22/2013			RPDLimit Qual			

Qualifiers:

* Value exceeds Maximum Contaminant Level.

- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
 - R RPD outside accepted recovery limits

24-Jan-13

WO#: 1301606

Hall Environmental Analysis Laboratory, Inc.

Client:	Blagg Engineering
Project:	GCU #152

. .

Sample ID MB-5758	SampType: MBLK	TestCode: EPA Method	418.1: TPH		
Client ID: PBS	Batch ID: 5758	RunNo: 8206			
Prep Date: 1/21/2013	Analysis Date: 1/23/2013	SeqNo: 237357	Units: mg/Kg		
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual
Petroleum Hydrocarbons, TR	ND 20				
Sample ID LCS-5758	SampType: LCS	TestCode: EPA Method	418.1: TPH		
Client ID: LCSS	Batch ID: 5758	RunNo: 8206			
Prep Date: 1/21/2013	Analysis Date: 1/23/2013	SeqNo: 237358	Units: mg/Kg		
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual
Petroleum Hydrocarbons, TR	97 20 100.0	0 97.1 80	120		
Sample ID LCSD-5758	SampType: LCSD	TestCode: EPA Method	418.1: TPH		
Client ID: LCSS02	Batch ID: 5758	RunNo: 8206			
Prep Date: 1/21/2013	Analysis Date: 1/23/2013	SeqNo: 237359	Units: mg/Kg		
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit	Qual
Petroleum Hydrocarbons, TR	100 20 100.0	0 101 80	120 4.08	20	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits

Page 4 of 7

,

24-Jan-13

WO#: 1301606

Hall Environmental Analysis Laboratory, Inc.

Client:	Blagg Engineering GCU #152
Project:	

•

Sample ID MB-5753	SampT	ype: ME	BLK	TestCode: EPA Method 8015B: Diesel Range Organics									
Client ID: PBS	Batch	n ID: 57	53	F	RunNo: 8								
Prep Date: 1/21/2013	Analysis D	ate: 1/	23/2013	5	SeqNo: 2 :	37449	Units: mg/H	(g					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Diesel Range Organics (DRO) Surr: DNOP	ND 9.8	10	10.00		98.4	72.4	120						
Sample ID LCS-5753	SampT	ype: LC	S	Tes	tCode: El	PA Method	8015B: Dies	el Range C)rganics				
Sample ID LCS-5753 Client ID: LCSS	•	ype: LC			tCode: El RunNo: 8 :		8015B: Dies	el Range ()rganics				
•	•	n ID: 57		F		204	8015B: Diese Units: mg/K	5	Drganics				
Client ID: LCSS	Batch	n ID: 57	53 23/2013	F	RunNo: 8 :	204		5	Drganics RPDLimit	Qual			
Client ID: LCSS Prep Date: 1/21/2013	Batch Analysis D	n ID: 57 ate: 1 /	53 23/2013	F S	RunNo: 8 : SeqNo: 2 :	204 37450	Units: mg/K	(g		Qual			

Qualifiers:

•

* Value exceeds Maximum Contaminant Level.

- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits

WO#: 1301606

24-Jan-13

Hall Environmental Analysis Laboratory, Inc.

Analysis Date: 1/22/2013

PQL

SPK value SPK Ref Val

1000

Result

1100

Client: Project:	Blagg E GCU #	Engineering								
Sample ID	MB-5742	SampType: M	BLK	Tes	tCode: E!	PA Method	8015B: Gasc	line Rang	je	
Client ID:	PBS	Batch ID: 57	742	F	RunNo: 8	172				
Prep Date:	1/18/2013	Analysis Date: 1	/21/2013	Ę	SeqNo: 2 :	36303	Units: mg/K	٢g		
Analyte		Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
	ge Organics (GRO)	ND 5.0								
Surr: BFB	<u> </u>	970	1000		97.5	84	116			
Sample ID	LCS-5742	SampType: L(cs	Tes	tCode: El	PA Method	8015B: Gaso	line Rang	e	
Client ID:	LCSS	Batch ID: 57	742	F	RunNo: 8	172				
Prep Date:	1/18/2013	Analysis Date: 1	/21/2013	દ	SeqNo: 2	36304	Units: mg/K	(g		
Analyte		Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
L	ge Organics (GRO)	25 5.0	25.00	0	98.5	74	117			· · · · · · · · · · · · · · · · · · ·
Surr: BFB		860	1000		86.1	84	116			
Sample ID	MB-5759	SampType: M	BLK	Tes	tCode: El	PA Method	8015B: Gaso	line Rang	e	
Client ID:	PBS	Batch ID: 57	759	F	RunNo: 81	181				
Prep Date:	1/21/2013	Analysis Date: 1	/22/2013	દ	SeqNo: 2:	37033	Units: %RE	с		
Analyte		Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: BFB		1000	1000		100	84	116			
Sample ID	 LCS-5759	SampType: LC	 CS	Tes	tCode: El	PA Method	8015B: Gaso	line Rang	 e	
Client ID:		Batch ID: 57			RunNo: 81				-	

Analyte Surr: BFB

Prep Date: 1/21/2013

Qualifiers:

Value exceeds Maximum Contaminant Level. *

E Value above quantitation range

J Analyte detected below quantitation limits

Sample pH greater than 2 Р

- в Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н

Not Detected at the Reporting Limit ND

RPD outside accepted recovery limits R

SeqNo: 237034

LowLimit

84

%REC

106

Units: %REC

116

%RPD

RPDLimit

Qual

HighLimit

24-Jan-13

1301606

WO#:

Client:	Blagg Eng	gineering									
Project:	GCU #15	2									
Sample ID M	IB-5742	Samp	Гуре: МІ	BLK	Tes	tCode: El	PA Method	8021B: Vola	tiles		
Client ID: PI	BS	Batc	h ID: 57	42	F	RunNo: 8	172				
Prep Date:	1/18/2013	Analysis [Date: 1	/21/2013	5	SeqNo: 2	36326	Units: mg/H	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		ND	0.050								
Toluene .		ND	0.050								
Ethylbenzene		ND	0.050								
Xylenes, Total		ND	0.10								
Surr: 4-Bromofi	uorobenzene	1.1		1.000		105	80	120			
Sample ID LO	CS-5742	Samp	ype: LC	s	Tes	tCode: El	PA Method	8021B: Vola	tiles		
Client ID: LO	css	Batc	n ID: 57	42	F	RunNo: 8 '	172				
Prep Date: 1	1/18/2013	Analysis E	Date: 1/	21/2013	S	SeqNo: 2:	36327	Units: mg/H	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		0.99	0.050	1.000	0	98.8	80	120			
Toluene		0.99	0.050	1.000	0	98.9	80	120			
Ethylbenzene		1.0	0.050	1.000	0	100	80	120			
Xylenes, Total		3.0	0.10	3.000	0	100	80	120			
Surr: 4-Bromoflu	uorobenzene	0.84		1.000		84.3	80	120			
Sample ID M	B-5759	Samp1	уре: М	BLK	Tes	tCode: EF	PA Method	8021B: Vola	tiles		
Client ID: PI	BS	Batcl	n ID: 57	59	F	RunNo: 8	181				
Prep Date: 1	1/21/2013	Analysis E)ate: 1 /	22/2013	S	SeqNo: 2	37107	Units: %RE	с		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromoflu	uorobenzene	1.1		1.000		110	80	120			
Sample ID LO	CS-5759	SampT	ype: LC	s	Tes	tCode: EF	PA Method	8021B: Vola	tiles		
Client ID: LO	css	Batcl	n ID: 57	59	F	RunNo: 8 [,]	181				
Prep Date: 1	1/21/2013	Analysis D	0ate: 1 /	22/2013	S	SeqNo: 2	37108	Units: %RE	с		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromoflu	uorobenzene	1.1		1.000		113	80	120			

Hall Environmental Analysis Laboratory, Inc.

• •

Qualifiers:

Value exceeds Maximum Contaminant Level. *

- E Value above quantitation range
- Analyte detected below quantitation limits J
- P Sample pH greater than 2

- Analyte detected in the associated Method Blank В
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
 - RPD outside accepted recovery limits R

WO#: 1301606 24-Jan-13

....

AN/	L VIRONMENTAL NLYSIS FORATORY	Hall Environmental Albu TEL: 505-345-3975 Website: www.hai	4901 querque FAX: 50	Haw e, NI 95-3	Sample Log-In Check Li						
Client Name Received by	1.CI	01/18/13	ork Ord	der I	Num	ber:	1301606				
Logged By:	Michelle Garcia	1/18/2013 9:53:00 AM				m	unite Garine				
Completed B	y: Michelle Garcia	1/18/2013 1:34:48 PM				m	winthe Ganna				
Reviewed By	-	01/18/2013				~ r	and game				
Chain of C		0118 2013									
1. Were se			Yes		No	П	Not Present				
	of Custody complete?				No		Not Present				
	the sample delivered?		Couri								
<u>Log In</u>					м.		🗖				
4. Coolers	are present? (see 19. for coo	pler specific information)	Yes		NO	ĿJ					
5. Was an	attempt made to cool the sa	mples?	Yes	⊻	No		NA 🗌				
6. Were all	samples received at a temp	erature of >0° C to 6.0°C	Yes	∕	No						
7 Sample(s) in proper container(s)?		Yes		No						
	t sample volume for indicate	d test(s)?	Yes								
9. Are sam	ples (except VOA and ONG)	properly preserved?	Yes	✓	No						
10. Was pre	servative added to bottles?		Yes		No	✓					
11 VOA via	s have zero headspace?		Yes		No		No VOA Vials 🗹				
	y sample containers receive	d broken?	Yes		No						
13. Does pa	perwork match bottle labels? crepancies on chain of custo	,	Yes		No		# of preserved bottles checked for pH:				
14. Are matr	ices correctly identified on C	hain of Custody?	Yes	\checkmark	No		(<2 or >12 unless no				
15. Is it clea	r what analyses were reques	ted?	Yes			_	Adjusted?				
	holding times able to be me tify customer for authorization		Yes	2	No		Checked by:				
Special Ha	ndling (if applicable)										
17. Was clie	nt notified of all discrepancie	s with this order?	Yes		No		NA 🗹				
Ву	son Notified: Whom: garding:	Date: Date: Via:] eMail] Ph	none	Fax In Person				

18. Additional remarks:

19. Cooler Information

Cooler No	Temp °C	Condition	Seal Intact	Seal No	Seal Date	Signed By
1	1.0	Good	Yes			

Client:			/ BP AMERICA	Standard	🗌 Rush												MEI RA		
<u></u>	, <u> </u>			Project Name:								haller							Γ Ν . Τ
Mailing A	ddress:	P.O. BO	K:87		GCU # 15	2		49	01 H								7109		
••		BLOOM	FIELD, NM 87413	Project #:				Te	I. 50	5-349	-397	5	Fax	505	-345	-410	17		
Phone #:		(505) 63	2-1199									Ana	ysiš	Req	lifes	t s			
email or F	ax#:			Project Manag	er:								S04)						
_	Accreditation:			NELSON VE	ELEZ	s (8021B)	anly)	Diesel					PCB's						
Standard Level 4 (Full Validation)		Fill I				(Gas	(Gas/		ł		102	82 PC					mple		
	>	Other		Onlice:	a led formed and share a strength of the strength of the strength of the strength of the	🗆 No		TPH (Gas	115B	18.1)	(1-1) 1-1		33, N	/ 8082		7			e sa
🗆 EDD (1	Гуре)		<u></u>	Sample Tempe	eratúre: <u>/ /</u>)℃		+	d 80	4 bo		tals	Ň,	ides	2	ļ Ņ	0.0	e e	osit
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO. 1301000		BTEX + MTBE	TPH Method 8015B (Gas/Diesel)	TPH (Method 418.1)	EUB (Method 504.1) 8310 (PNA or PAH)	RCRA 8 Metals	Anions (F, Cl, NO3, NO2, PO4,	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (300.0)	Grab sample	5 pt. composite sample
1/17/13	1435	SOIL	5PC-TB @ 🦙 ' (95)	4 oz 2	Cool	-001	۷			V							V		V
													1						
1/17/13	1305	SOIL	5PC-TB @ 🥱 ' (21)	4 oz 2		-002-	4		-	√		1					-		~
												1							
											+	┼──						+	
												-							
<u></u>									\neg		+	+				-†			
<u> </u>									-			+							
			· · · · · · · · · · · · · · · · · · ·							+									
			· · · · · · · · · · · · · · · · · · ·						-+			+			-				
									\neg			+						+	
Date: /17/13	Time:	Relinquish	ed by:	Received by:	<u> </u>	Date Time	Ren	narks	L	TPH (8015	5B) -	GRC	8	DRO	ON	LY.		
·	1525	90	in Vj	Mistine	Walten	1/17/13 1525	1			Y TO		ourt,	Farm	ingt		NA 0-	7401		
Date:	Time:	Relinquishe	ed by:	Received by:	1	Date Time	F					3570		-			401 EVH01	RGTO	
1/1/12	1737	Phi	in the loo Ales	DCA-	2 61/18/	13 19953		JIK U	i del l	<u> </u>	1007	3370		Pay	укеу:			0012	<u> </u>

•



