<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources · Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration OIL CONS. DIV DIST, 3
45-25996 Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method NOV 07 2014
☐ Modification to an existing permit/or registration ☐ Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Bolack B 8E
API Number:3004525996OCD Permit Number:
U/L or Qtr/QtrBSection33Township28NRange8WCounty:San Juan
Center of Proposed Design: Latitude36.62226 Longitude107.68195 NAD: ☐1927 ☒ 1983
Surface Owner: 🔀 Federal 🗌 State 🔲 Private 🔲 Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no ☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection 1 of 19.15.17.11 NMAC Tank B
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☑ Visible sidewalls only ☐ Other _Single walled/double bottomed
Liner type: Thicknessmil
4.
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	,
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	. Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	
	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.	
and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	cuments are
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	.15.17.9 NMAC
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	documents are
Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	'luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality.	om the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral	Division	☐ Yes ☐ No
Within an unstable area.		
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Society; Topographic map	Resources; USGS; NM Geological	☐ Yes ☐ No
Within a 100-year floodplain.		
- FEMA map		☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following is by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection II Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMA Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings of Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17 Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.18 Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.19	19.15.17.10 NMAC E of 19.15.17.13 NMAC uirements of Subsection K of 19.15.17.1 pon the appropriate requirements of 19.1 C 19.15.17.13 NMAC NMAC or in case on-site closure standards cannot .13 NMAC 7.13 NMAC	1 NMAC 5.17.11 NMAC
17.		
Operator Application Certification:	•	
I hereby certify that the information submitted with this application is true, accurate and comple	te to the best of my knowledge and belie	ef.
Name (Print): Title:		
Signature: Date	:	<u> </u>
e-mail address: Telepho	ne:	
18. OCD Approval: ☐ Permit Application (including closure plan) ☑ Closure Plan (only) ☐	OCD Conditions (see attachment)	7
	Approval Date: 11/21	1004
	Approval Date.	/ 6011
Title: Comprance Office OCD Permit	Number:	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing. The closure report is required to be submitted to the division within 60 days of the completion	of the closure activities. Please do not c	
section of the form until an approved closure plan has been obtained and the closure activities Closure	Completion Date:9/22/2011	
	Completion Date:9/22/2011	
⊠ Closure		p systems only)
20. Closure Method: ☐ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Me	ethod	icate, by a check

Form C-144 Oil Conservation Division Page 5 of 6

22. Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure requirer I	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Name (Print):Jeff Peace	Date:November 4, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Bolack B 8E BGT Tank B (95 bbl) API No. 3004525996 Unit Letter B, Section 33, T28N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT, Tank B	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	110
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. TPH was 110 ppm by Method 418.1 but was only 18 ppm by Method 8015D. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rel	ease Notifi	catio	n and Co	rrective A	ction			
					•	OPERA	ΓOR	☐ Init	ial Report	\boxtimes	Final Report
Name of Co						Contact: Jef	f Peace				
Address: 20			nington, N	IM 87401		Telephone No.: 505-326-9479					
Facility Na	me: Bolack	B 8E				Facility Typ	e: Natural gas v	gas well			
Surface Ow	ner: Feder	al		Mineral (Owner:	Federal	·	APIN	o. 30045259	96	
				LOC	ATIO	N OF REI	LEASE				
Unit Letter	Section	Township	Range	Feet from the		/South Line	Feet from the	East/West Line	County: Sa	n Juai	1
В	33	28N	8W	1,000	North		1,450	East			<u> </u>
		La	ititude 3	6.62226		Longitud	e107.68195_				
						OF RELI					
Type of Rele	ase: none			IVA	UKE		Release: N/A	Volume	Recovered: N	J/Δ	
Source of Re		grade tank	- 95 bbl, T	ank B			lour of Occurrenc		Hour of Dis		:
Was Immedi		liven?				If YES, To					
			Yes [] No 🛛 Not R	equired						
By Whom?						Date and H					
Was a Water	course Reac		☐ Yes 🗵	7 No		If YES, Vo	lume Impacting t	he Watercourse.			
If a Watercou	ırse was İm _l	pacted, Desc	cribe Fully.	*							
								ne during removal			
				and chloride belo	w stand	ards. TPH wa	s 110 ppm by Me	thod 418.1 but wa	is only 18 pp	m by N	Method
8015D. Ana	iysis results	are attached	1.								Ì
- T	A CC / 1	1.01	A	* D.O.T.	1	. 141	1 11 00	cr 1 1 cr	<u> </u>	41 . D	- COTE
				cen.* BGT was re active well area.	moved	and the area u	nderneath the BG	T was sampled. T	he area unde	r the B	GI was
buckinied an	a compactor	and 19 Still	Within the	don'to tron diod.							
I hereby certi	fy that the i	nformation	oiven above	e is true and comm	lete to t	he hest of my	knowledge and u	nderstand that pur	suant to NM	OCD r	ules and
								tive actions for re			
								eport" does not rel			
should their o	perations h	ave failed to	adequately	investigate and r	report d	e contaminati	on that pose a three	eat to ground wate esponsibility for o	r, surface wa	ter, hu	man health
federal, state,				nance of a C-141	report	ioes not tenev	e the operator of t	esponsionity for c	omphanee w	mir ang	y other
		Ω				OIL CONSERVATION DIVISION					
Ci atuma	\alk	Vara 2									
Signature:	XPV	V June				Anneared by	Environmental S ₁	- anialist			
Printed Name	e: Jeff Peace	<u>, </u>				Approved by	Environmentar S	pecialist.			
Title, Dield D	nuironma-t	al Coordina	tor			Approval Dat	۵۰	Expiration	Date:		
Title: Field E	arvironment	ai Coordina	101			Approvai Dai	· .	Expiration	Date.		
E-mail Addre	ess: peace.je	ffrey@bp.c	om			Conditions of	Approval:		Attached		
D : 33	1 4 0014		DI.	505 227 0470					7 Italiania		
Date: Noven	nber 4, 2014	·	Pnor	ne: 505-326-9479							

^{*} Attach Additional Sheets If Necessary

BP		•	440	API#: 3004	4525996
CLIENI:		•	#13	TANK ID (if applicble):	В
FIELD REPORT:	(circle one): BGT CONFIRMATION / REL	EASE INVESTIGATION / OTHER:		PAGE#:	1 of 1
SITE INFORMATION	J: SITE NAME: BOLACK F	3 #8E		DATE STARTED:	02/07/13
QUAD/UNIT: B SEC: 33 TWP:	28N RNG: 8W PM: N	NM CNTY: SJ ST:	NM_	DATE FINISHED:	
		ELVUODN		ENVIRONMENTAL	A1 IN /
		RACTOR: MBF - S. GENTE			
· · · · · ·					113', S65.5E
P.O. BOX 87, BLOOMFILED, NM 87413 (505) 632-1199 FIELD REPORT: (dircle one): [BGTCONFRIBITION] RELEASE IMMESTIGATION / OTHER PAGE # 1 of 1 DATE INFORMATION: SITEMANE BOLACK B #8E JUANDAMENT B SEC 33 TOP 28N PRIO 8W PM NM CHITY SJ SI NM IMMEDIATE INFORMATION: NWINE LEASETYPE [FEDERAL STATE / FEE / INDIAN JUANDAMENT B SEC 33 TOP 28N PRIO 8W PM NM CHITY SJ SI NM JUANDAMENT B SEC 33 TOP 28N PRIO 8W PM NM CHITY SJ SI NM JUANDAMENT B SEC 30 TOP 28N PRIO 8W PM NM CHITY SJ SI NM DEFENSIVE CONTROL OF STATE PRIOR STATE / STATE / FEE / INDIAN ESEFTE RENCE POINT: WELL HEAD (WHI.) GRE COORD: 36.62224 X 107.68128 JUANDAMENT SJ STATE / FEE / INDIAN JUANDAMENT SJ STATE / FE					
				04 ED 10004 D 1001	(mgg)
					J.U(CI) NA
					
SOIL COLOR: MOD	ERATE BROWN				
		, ,			
		l l			
		HC ODOR DETECTED: YES		ANATION	
DISCOLORATION/STAINING OBSERVED): YES NO EXPLANATION -				
ANY ADEAS DISPLAYING METNESS: VES / N/	JEAN VIVILLE				
		NO EXPLANATION:			
ADDITIONAL COMMENTS:					
SOIL IMPACT DIMENSION ESTIMATION	: NA ft. X NA ft.	X NA ft. EXCA	VATION EST	IMATION (Cubic Yard	ds): NA
DEPTH TO GROUNDWATER: <50'			<u>000'</u> имос	D TPH CLOSURE STD:	100 ppm
SITE SKETCH		PLOT PLAN circle: att	ached	CALIB, READ. = NA	ppm pr = 0.50
			♦ ovm		
•			N TIME:	. NA am/pm DA	ate: <u>Na</u>
	~		۱۲-	MISCELL.	NOTES
1	DDCTI		<u>w</u>	o: N150598	27
	T.B. ~ 7'		1		
			1 -		
	DEHY.	E.D. ~ 5' B.G.		· · · · · · · · · · · · · · · · · · ·	
	UNIT		Tan	k OVM = Organic	Vapor Meter
FIELD REPORT: (archerole) BOTCOMFRIATION) RELAKE INVESTIGATION OTHER: FIELD REPORT: (archerole) BOTCOMFRIATION) RELAKE INVESTIGATION OTHER: SITE INFORMATION: MAIN OF CORPORATION DIVIDENT FEEDERS AND SITE INFORMATION AND SITE OF COORD: SITE INFORMATION: SITE INFORMATION: SITE INFORMATION: SITE INFORMATION: SITE INFORMATION: MAIN OF COORD: SITE INFORMATION:					
			-		
			LL HEAD;		
		DB - DOUBLE BOTTOM.		lagnetic declination	on: 10 E
TRAVEL NOTES: CALLOUT:		ONSITE: 02/07/13	}		

revised: 08/01/12 BEI1005E-5.SKF

Analytical Report

Lab Order 1302323

Date Reported: 2/18/2013

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Lab ID:

Project: BOLACK B # 8E

1302323-001

Matrix: SOIL

Client Sample ID: 5PC-TB @ 7' (95) Collection Date: 2/7/2013 12:10:00 PM

Received Date: 2/9/2013 11:15:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	SE ORGANICS				Analyst: MMD
Diesel Range Organics (DRO)	18	9.9	mg/Kg	1	2/12/2013 10:26:55 AM
Surr: DNOP	93.1	72.4-120	%REC	1	2/12/2013 10:26:55 AM
EPA METHOD 8015B: GASOLINE RA	ANGE				Analyst: NSB
Gasoline Range Organics (GRO)	ND	4.9	mg/Kg	1	2/12/2013 3:59:00 PM
Surr: BFB	109	84-116	%REC	1	2/12/2013 3:59:00 PM
EPA METHOD 8021B: VOLATILES					Analyst: NSB
Benzene	ND	0.049	mg/Kg	1	2/12/2013 3:59:00 PM
Toluene	ND	0.049	mg/Kg	1	2/12/2013 3:59:00 PM
Ethylbenzene	ND	0.049	mg/Kg	1	2/12/2013 3:59:00 PM
Xylenes, Total	ND	0.098	mg/Kg	1	2/12/2013 3:59:00 PM
Surr: 4-Bromofluorobenzene	110	80-120	%REC	1	2/12/2013 3:59:00 PM
EPA METHOD 300.0: ANIONS					Analyst: JRR
Chloride	ND	7.5	mg/Kg	5	2/15/2013 11:36:13 AM
EPA METHOD 418.1: TPH					Analyst: ECH
Petroleum Hydrocarbons, TR	110	20	mg/Kg	1	2/13/2013 2:30:00 PM

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2
- RL Reporting Detection Limit

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits Page 1 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1302323

18-Feb-13

Client:

Blagg Engineering

Project:

BOLACK B # 8E

Sample ID MB-6135

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID: PBS Batch ID: 6135

RunNo: 8675

HighLimit

Prep Date: 2/15/2013

PQL

SeqNo: 249146

Analysis Date: 2/15/2013

SPK value SPK Ref Val %REC LowLimit Units: mg/Kg

RPDLimit Qual

Analyte Chloride

ND 1.5

Result

Sample ID LCS-6135 Client ID: LCSS

SampType: LCS

TestCode: EPA Method 300.0: Anions

Prep Date: 2/15/2013 Batch ID: 6135

RunNo: 8675

Units: mg/Kg

Analysis Date: 2/15/2013

SeqNo: 249147

Analyte

Qualifiers:

Е

Value exceeds Maximum Contaminant Level

Analyte detected below quantitation limits

Value above quantitation range

Sample pH greater than 2

SPK value SPK Ref Val %REC LowLimit Result

0

Chloride

1.5

Analyte detected in the associated Method Blank

Not Detected at the Reporting Limit

RPD outside accepted recovery limits

Holding times for preparation or analysis exceeded

%RPD

15

15.00

97.9

HighLimit

%RPD

Н

ND

RPDLimit

Page 2 of 6

Qual

Hall Environmental Analysis Laboratory, Inc.

WO#:

1302323

18-Feb-13

Client:

Blagg Engineering

Project:

BOLACK B # 8E

Sample iD MB-6092

SampType: MBLK

Analysis Date: 2/13/2013

TestCode: EPA Method 418.1: TPH

PBS Client ID:

Prep Date:

Batch ID: 6092

RunNo: 8631 SeqNo: 248031

Units: mg/Kg

Analyte

Result

Result

110

PQL

20

SPK value SPK Ref Val %REC LowLimit

HighLimit

RPDLimit %RPD

Qual

Petroleum Hydrocarbons, TR

ND

SampType: LCS Batch ID: 6092

TestCode: EPA Method 418.1: TPH

Sample ID LCS-6092

Client ID: LCSS

RunNo: 8631

120

Analyte

Prep Date: 2/12/2013

2/12/2013

Analysis Date: 2/13/2013

SeqNo: 248032

7.660

Units: mg/Kg

Qual

Petroleum Hydrocarbons, TR

PQL 20

SPK value SPK Ref Val %REC 100.0

98.1

LowLimit HighLimit 80

%RPD

RPDLimit Qual

Sample ID LCSD-6092

SampType: LCSD

Batch ID: 6092

PQL

20

TestCode: EPA Method 418.1: TPH

RunNo: 8631 SeqNo: 248033

Units: mg/Kg

Analyte

Prep Date: 2/12/2013

Client ID: LCSS02

Petroleum Hydrocarbons, TR

Analysis Date: 2/13/2013

Result

110

SPK value SPK Ref Val %REC 100.0 7.660

99.4

LowLimit

HighLimit 120

RPDLimit %RPD

1.24

20

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range Е

Analyte detected below quantitation limits J

Sample pH greater than 2

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit RPD outside accepted recovery limits

ND

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1302323

18-Feb-13

Client:

Blagg Engineering

Project:

BOLACK B # 8E

Sample ID MB-6070	SamnT	Type: ME		Tac	TestCode: EPA Method 8015B: Diesel Range Organics					
·	SampType: MBLK			ų ų						
Client ID: PBS		Batch ID: 6070			RunNo: 8570					
Prep Date: 2/11/2013	Analysis D	Analysis Date: 2/11/2013		SeqNo: 246528			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10		•						
Surr: DNOP	10		10.00		100	72.4	120			

Sample ID LCS-6070	SampType: LCS			TestCode: EPA Method 8015B: Diesel Range Organics							
Client ID: LCSS	Batch ID: 6070			RunNo: 8570							
Prep Date: 2/11/2013	Analysis D	Analysis Date: 2/11/2013			SeqNo: 246529			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HìghLimit	%RPD	RPDLimit	Qual	
Diesel Range Organics (DRO)	42	10	50.00	0	84.6	47.4	122				
Surr: DNOP	4.8		5.000		96.5	72.4	120				

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits

P Sample pH greater than 2

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1302323

18-Feb-13

Client:

Blagg Engineering

Project:

BOLACK B #8E

Sample ID MB-6071

SampType: MBLK

TestCode: EPA Method 8015B: Gasoline Range

Client ID: PBS Batch ID: 6071

RunNo: 8602

Prep Date: 2/11/2013 Analysis Date: 2/12/2013

Units: mg/Kg

PQL Result

SeqNo: 247592

Analyte

ND 5.0

Gasoline Range Organics (GRO)

SPK value SPK Ref Val %REC LowLimit

1000

SPK value SPK Ref Val

HighLimit %RPD

RPDLimit Qual

1000

104

116

Surr: BFB

Sample ID LCS-6071

SampType: LCS

PQL

0

84

TestCode: EPA Method 8015B: Gasoline Range

Client ID:

LCSS

Batch ID: 6071

RunNo: 8602

Analyte

2/11/2013

Analysis Date: 2/12/2013

Result

28

1200

SeqNo: 247593 %REC

Units: mg/Kg HighLimit

Qual

Gasoline Range Organics (GRO) Surr: BFB

Prep Date:

5.0 25.00 1000 113 118 62.6 84

LowLimit

136 116 %RPD **RPDLimit**

S

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits 1

Sample pH greater than 2

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit RPD outside accepted recovery limits Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1302323

18-Feb-13

Client: Project:

Blagg Engineering BOLACK B # 8E

Sample ID MB-6071 SampType: MBLK Client ID: PBS Batch ID: 6071				TestCode: EPA Method 8021B: Volatiles									
				F	RunNo: 80	602							
Prep Date: 2/11/2013	Analysis D	Date: 2/	12/2013	SeqNo: 247629			Units: mg/K	(g					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	ND	0.050											
Toluene	ND	0.050											
Ethylbenzene	ND	0.050											
Xylenes, Total	ND	0.10											
Surr: 4-Bromofluorobenzene	1.0		1.000		105	80	120						

Sample ID LCS-6071	s	TestCode: EPA Method 8021B: Volatiles												
Client ID: LCSS	71	F												
Prep Date: 2/11/2013	Analysis Date: 2/12/2013			S	SeqNo: 2	47630	Units: mg/K	ίg						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Quai				
Benzene	0.95	0.050	1.000	0	95.2	80	120							
Toluene	0.94	0.050	1.000	0	93.6	80	120							
Ethylbenzene	0.94	0.050	1.000	0	94.0	80	120							
Xylenes, Total	2.9	0.10	3.000	0	95.6	80	120							
Surr: 4-Bromofluorobenzene	1.1		1.000		113	80	120							

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits

P Sample pH greater than 2


B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

Page 6 of 6



11au Environmeniai Anaiysis Luvoraiory 4901 Hawkins NE Albuquerque, NM 87105

Sample Log-In Check List

TEL: 505-345-3975 FAX: 505-345-410% Website: www.hallenvironmental.com Client Name: **BLAGG** Work Order Number: 1302323 Received by/date: Logged By: **Lindsay Mangin** 2/9/2013 11:15:00 AM Completed By: **Lindsay Mangin** 2/11/2013 8:30:42 AM Reviewed By: 02/11/2013 Chain of Custody Yes No 🗌 1. Were seals intact? Not Present Yes 🗹 No 🗌 Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Courier <u>Log In</u> Yes 🗹 No 🗌 NA 🗌 4. Coolers are present? (see 19. for cooler specific information) Yes 🗸 No 🗌 NA 🗌 5. Was an attempt made to cool the samples? Yes 🗹 No 🗌 NA 🗆 6. Were all samples received at a temperature of >0° C to 6.0°C Yes 🗸 No 🗌 7. Sample(s) in proper container(s)? Yes 🗸 No 🗌 8. Sufficient sample volume for indicated test(s)? Yes 🗹 No 🗌 9 Are samples (except VOA and ONG) properly preserved? NA 🗆 10. Was preservative added to bottles? Yes 🗌 No 🗹 Yes No 🗆 No VOA Vials 🗹 11. VOA vials have zero headspace? Yes 🗆 No 🗹 12. Were any sample containers received broken? # of preserved Yes 🗹 No 🗌 13. Does paperwork match bottle labels? bottles checked (Note discrepancies on chain of custody) for pH: Yes 🔽 No 🗌 14. Are matrices correctly identified on Chain of Custody? (<2 or >12 unless noted) Yes 🗹 No 🗌 Adjusted? 15. Is it clear what analyses were requested? Yes 🗹 No 🗌 16. Were all holding times able to be met? (If no, notify customer for authorization.) Checked by: Special Handling (if applicable) 17. Was client notified of all discrepancies with this order? Yes D No D NA 🗹 Person Notified: Date: By Whom: ☐ eMail ☐ Phone ☐ Fax ☐ In Person Regarding: Client Instructions: 18. Additional remarks: 19. Cooler Information Cooler No Temp °C Condition Seal Intact Seal No Seal Date Signed By

Good

Yes

Chain-of-Custody Record						HALL ENVIRONMENTAL														
Client: BLAGG ENGR. / BP AMERICA		☑ Standard ☐ Rush				.0														
									-									•	-	
Mailing Address: P.O. BOX 87		BOLACK B # OF																		
BLOOMFIELD, NM 87413		· · · · · · · · · · · · · · · · · · ·																		
		Project #: 			p v												-74		······································	
Phone #: (505) 632-1199									To be	-	Anal	ysis	Red	ques	i.		Parage produ		4 4	
email or Fax#:		Project Manager:										(4)								
QA/QC Package: Standard Level 4 (Full Validation)		NELSON VELEZ				only}	/Diesel]	į		-	<u> </u> 	P04,	CB's		ì	į			اها	
Accreditation:		Sampler: NELSON VELEZ 7W			8	(Gas	Gas					05,	32 P						립	
		On ice: b⊈Yes □ No				PH.	15B (8.1)	4.1)	Ŧ		3, N	808						Sa	
□ EDD (Type)		Sample Temperature			E	E + 1	801	d 41	d 50	rPA	sle	Š	des] _	δ	0.0		e l	Sit	
Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEALNÖ,	BTEX +-WITE	BTEX + MTB	TPH Method	TPH (Metho	EDB (Metho	8310 (PNA o	RCRA 8 Met	Anions (F, Cl	8081 Pestici	8260B (VOA	8270 (Semi-A	Chloride (30		Grab samp	5 pt. composite sample
1210	SOIL	5PC-TB @ 7' (95)	4 oz 2	Cool	-00/	V		V	_								V			V
	 											<u> </u>		-			\neg	\dashv		_
	<u> </u>			 													\dashv			_
																		_		
													l			,	, ,	_		
					•						-									
																				\exists
						-											$\overline{}$	\dashv	_	\dashv
<u> </u>																-	\dashv			-+
			<u> </u>				-1	_										_	}	}
																				\bot
ate: Time: Relinquished by: 1315 Muli		Matri Walter 2/8/13/3/5			BILL DIRECTLY TO BP:															
Date: Time: Relinquished by: 2/8/13 1757 Mut Wolfe		nt Walte	Received by: Date Time				Work Order: N15059827 Paykey: ZEVH01BGT2													
	BLAG ddress: ax#: ckage: ard ion: 7ype) Time 1210 Time: /3/5	BLAGG ENGR. ddress: P.O. BO BLOOM (505) 63 ax#: ckage: ard	BLAGG ENGR. / BP AMERICA ddress: p.o. Box 87 BLOOMFIELD, NM 87413 (505) 632-1199 ax#: ckage: ard	BLAGG ENGR. / BP AMERICA Project Name ddress: p.o. BOX 87 BLOOMFIELD, NM 87413 (505) 632-1199 ax#: ckage: ard	BLAGG ENGR. / BP AMERICA Standard Rush Project Name: BOLACK B # BOLACK B # BOLACK B #	BLAGG ENGR. / BP AMERICA Project Name: BOLACK B # 8E BLOOMFIELD, NM 87413 (505) 632-1199 Project Manager: Project Manager: Project Manager: Project Manager: NELSON VELEZ No. Other	BLAGG ENGR. / BP AMERICA Standard Rush Project Name:	BLAGG ENGR. / BP AMERICA Project Name: BOLACK B # 8E 49 BLOOMFIELD, NM 87413 (505) 632-1199 ax#: Chage: ard Level 4 (Full Validation) Sampler: NELSON VELEZ NELS	BLAGG ENGR. / BP AMERICA Project Name: BLOOMFIELD, NM 87413 (505) 632-1199 ax#: Project Manager: RESON VELEZ Project Manager: NELSON VELEZ NO Date Time Matrix Sample Request ID Container Type and # Type Adv 2 Cool N V V Time: Reinquished by: Received by: Date Time Remarks: BILL DIRECT Iff Peace, Work Order Work Order	BLAGG ENGR. / BP AMERICA Standard	BLAGG ENGR. / BP AMERICA Standard Rush Rush	BLAGG ENGR. / BP AMERICA Project Name: Project Name: ANAL Www.h.	BLAGG ENGR. / BP AMERICA Standard Rush Rush	BLAGG ENGR. / BP AMERICA Standard Rush Rush	BLAGG ENGR. / BP AMERICA Standard Rush RNS RN	BLAGG ENGR. / BP AMERICA Standard	BLAGG ENGR. / BP AMERICA Project Name: Www.hallenvironmental.com A901 Hawkins NE - Albuquerque, NM & Tel. 505-345-3975 Fax 505-345-341	BLAGG ENGR. / BP AMERICA Standard Rush Project Name: BOLACK B # 8E BOLACK B # 8E	BLAGG ENGR. / BP AMERICA Standard Rush Roughland Rush Rush	BLAGG ENGR. / BP AMERICA Standard Rush Project Name: www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109 Tel. 505-345-3975 Fax 505-345-4107 Tel. 505-345-3975 Tel. 505-345-3107 Tel. 505-345-3975 Tel. 505-345-345-345-345-345-345-345-345-345-34





BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

November 12, 2012

Bureau of Land Management Mark Keily 1235 La Plata Hwy Farmington, NM 87401

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: BOLACK B 008E

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about November 13 2012. If there aren't any unforescen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper Surface Land Negotiator

90 Valju

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

November 14, 2012

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

BOLACK B 008E API 30-045-25996 (M) Section 33 – T28N – R08W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl. BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Buddy Shaw BP Environmental Advisor

(505) 320-0401



