District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division

1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Proposed Alternative Method Permit or Closure Plan Application
Proposed Alternative Method Permit or Closure Plan Application Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:W. D. Heath A 1A
API Number:3004522663 OCD Permit Number:
U/L or Qtr/QtrP Section9 Township29N Range9W County:San Juan
Center of Proposed Design: Latitude36.73550Longitude107.77835NAD: ☐1927 ☒ 1983 Surface Owner: ☒ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank B
Volume:21.0bbl Type of fluid:Produced water
Tank Construction material:Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
 □ Visible sidewalls and liner □ Visible sidewalls only □ Other _Single walled/single bottomed Liner type: Thickness mil □ HDPE □ PVC □ Other
Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
☐ Screen ☐ Netting ☐ Other ☐ Monthly inspections (If netting or screening is not physically feasible)	
involuting inspections (if netting of screening is not physically reasible)	
Signs: Subsection C of 19.15.17.11 NMAC	
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
<u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	,
 □ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. □ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	☐ Yes ☐ No
 NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9	uments are
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.	
and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment	
 ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC 	
☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
 ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Emergency Response Plan 	
Oíl Field Waste Stream Characterization Monitoring and Inspection Plan	
☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative	luid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)	
☐ On-site Closure Method (Only for temporary pits and closed-loop systems) ☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. It 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain FEMA map	Yes No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ief.
Name (Print): Title:	
Signature: Date:	
e-mail address:	- · · · · · · · · · · · · · · · · · · ·
OCD Approval: Permit Application (including glosure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 2/1/ Title: OCD Permit Number:	2014
OCD Approval: Permit Application (including dosure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Title: OCD Permit Number: Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report.
OCD Approval: Permit Application (including dosure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 2/1/ Title: OCD Permit Number: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 9/8/2014	the closure report.
OCD Approval: Permit Application (including dosure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Title: OCD Permit Number: Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report.

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirements.	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Signature:	Date:November 17, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

W. D. Heath A 1A BGT Tank B (21 bbl) API No. 3004522663 Unit Letter P, Section 9, T29N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT, Tank B	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-141

Revised August 8, 2011

			Rele	ease Notifi	catio	and Co	orrective A	ction				
						OPERA'	ГOR		Initia	al Report		Report
Name of Co		 				Contact: Jef				-		
		Court, Farmi	ngton, N	M 87401			No.: 505-326-94					
Facility Nar	ne: W. D.	Heath A 1A				Facility Typ	e: Natural gas v	well				
Surface Owner: Federal Mineral Owner						Federal		Ţ	API No	. 30045226	663	
				LOCA	ATIO	N OF REI	LEASE					
Unit Letter P	Section 9	Township 29N	Range 9W	Feet from the 1,160	North/ South	South Line	Feet from the 790	East/Wo	est Line	County: Sa	ın Juan	
				1,100				Lust .				
		Lati	itude3	6.73550		_ Longitud	e107.77835_					
				NAT	TURE	OF REL	EASE					
Type of Rele							Release: N/A			Recovered: N		
Source of Re	lease: belov	v grade tank –	21 bbl, Ta	ank B		Date and F	lour of Occurrenc	e:	Date and	Hour of Dis	covery: N/A	
Was Immedia	ate Notice (If YES, To	Whom?					
			Yes _	No 🛛 Not R	equired							
By Whom?		1 10				Date and F		****				
Was a Water	course Read		Yes 🛚	No		If YES, Vo	lume Impacting t	ne Water	course.			
If a Watercou	rse was Im	pacted, Descri	be Fully.*			1						
							the BGT was dor		removal t	to ensure no	soil impacts fr	om
the BGT. So	il analysis r	esulted in TPI	H, BTEX a	and chlorides belo	ow stand	ards. Analys	is results are attac	ched.				
				ten.* BGT was re active well area.	moved a	nd the area u	nderneath the BG	T was sar	npled. Tl	he area unde	r the BGT was	;
Dackinied and	1 compacted	u anu is sum w	inin ine a	ictive wen area.								
L hereby certi	fy that the i	nformation gi	ven ahove	is true and comp	lete to th	ne best of my	knowledge and u	nderstand	I that purs	uant to NM(OCD rules and	
regulations al	loperators	are required to	o report an	ıd/or file certain r	elease no	otifications ar	nd perform correc	tive action	ns for rele	eases which	may endanger	l
public health	or the envi	ronment. The	acceptanc	e of a C-141 repo	ort by the	NMOCD m	arked as "Final Ro	eport" do	es not reli	eve the oper	ator of liability	/
or the enviror	perations n	ave tailed to a ddition. NMO	idequatery CD accen	investigate and r	renegiate report de	e contaminati oes not reliev	on that pose a three the operator of r	eat to groi responsibi	una water ility for co	, suriace wa ompliance w	ier, numan nea ith anv other	uu
federal, state,									_			
	0 00	0					OIL CONS	SERV <i>A</i>	ATION	DIVISIO	<u>N</u>	
Signature:	Volk	Peace										
Approved by Environmental Specialist:												
Printed Name	: Jeff Peace											
Title: Field E	nvironment	al Coordinato	r			Approval Dat	e:	Ex	xpiration l	Date:	······	
E-mail Addre	ss: peace.jo	effrey@bp.com	n			Conditions of	`Approval:			Attached		
Date: Noven	nber 17. 20	14	Pho	one: 505 - 326-947	9						- -	

^{*} Attach Additional Sheets If Necessary

CLIENT: BP		G ENGINEERI 7, BLOOMFIEL	•		API#: 300	4522	663
		(505) 632-119	•		TANK ID (if applicble):	NA	1
FIELD REPORT:	(circle one): BGT CONFIRM	IATION / RELEASE INVESTIG	GATION / OTHER:		PAGE#:	1 of	1
SITE INFORMATION					DATE STARTED:	09/0	3/14
			_	<u>IM</u>	DATE FINISHED:		
1/4-1/4/FOOTAGE: 1,160'S / 790		LEASE TYPE: FEDERAL	TOUZE	AN_	ENVIRONMENTAL	JC	,D
LEASE # SF076337 REFERENCE POINT	PROD. FORMATION: M				SPECIALIST(S):		
1) 95 BGT (SW/DB)		H.) GPS COORD.:			GLELE	:V.: <u>5,</u>	
2) 21 BGT (SW/SB)			77025			101', S8	
3)							
	GPS COORD.:						
SAMPLING DATA:	CHAIN OF CUSTODY RECOR	RD(S) # OR LAB USED:	HALL_				OVM READING (ppm)
1) SAMPLEID:	SAMPLE DATE:	09/03/14 SAMPLE TIME:	0950 LAB ANALYSIS:	418	. 1/8021B/300.0	(CI)	0.0
2) SAMPLE ID: 21 BGT 5-pt. (@_ 5' SAMPLE DATE:	09/03/14 SAMPLE TIME:	LAB ANALYSIS:	418	.1/8021B/300.0	(CI)	0.0
3) SAMPLE ID:						-	
4) SAMPLE ID:SOIL DESCRIPTION	SAMPLE DATE:						
SOIL COLOR: DARK YEL COHESION (ALL OTHERS): NON COHESIVE) SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY SLIGHTLY MOIST / MOIST / W SAMPLE TYPE: GRAB COMPOSITE -# DISCOLORATION/STAINING OBSERVED: YES N	Y COHESIVE / COHESIVE / HIGHLY CO DOSE / FIRM / DENSE / VERY DET / SATURATED / SUPER SATUR # OF PTS. 5 IO EXPLANATION -	DENSITY (COHESINDENSE HC ODOR DETECTED ANY AREAS DISPLAY	NON PLASTIC / SLIGHTLY PLA /E CLAYS & SILTS): SOFT D: YES NO EXPLANATION ING WETNESS: YES NO	/ FIRM / : - 	STIFF / VERY STIFF / I	HARD	
SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER: BOTH BGTS HAD PORTIONS OF	D AND/OR OCCURRED: YES N YES NO EXPLANATION -	O EXPLANATION:					
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X	NA ft. X NA	ft. EXCAVATION	ON EST	IMATION (Cubic Yar	rds):	NA
	IEAREST WATER SOURCE:	>1,000' NEAREST SURFA	CE WATER: <200'	NMOC	D TPH CLOSURE STD:	100	ppm
SITE SKETCH [BGT Located : off	on site PLOT PL	AN circle: attached	↑ OVM	CALIB. READ. = 52 . CALIB. GAS = 10 6:10 ampm D		1(1 -0.02
METER RUN		STEEL CONTAINMENT RING	PROD. TANK	_	MISCELL. 0: N150531 0#:		ES
BERM (21) PBGTL	W . H. ⊕			1 -	J#: Z2-006 Q		08
T.B. ~ 5' B.G.	DEHYDRATOR	TO MANZANARES / WASH	X - S.P.[O(Tan ID	CD Appr. date(s): k OVM = Organic ppm = parts pe	08/27/ Vapor Meter r million	08 er
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGLE	OW-GRADE TANK LOCATION; SPD =	.DE; B = BELOW; T.H. = TEST HOLE; SAMPLE POINT DESIGNATION; R.W	~ = APPROX.; W.H. = WELL HEA ! = RETAINING WALL; NA - NOT OM.	D;]	BGT Sidewalls Visil agnetic declination		
NOTES:		ONSITE	09/03/14				

Analytical Report

Lab Order 1409141

Date Reported: 9/8/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering W. D. Heath A 1A Project:

Client Sample ID: 21 BGT 5-pt @ 5'

Collection Date: 9/3/2014 10:07:00 AM

1409141-002 Lab ID:

Matrix: SOIL

Received Date: 9/4/2014 7:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8021B: VOLATILES					Analyst	:: NSB
Benzene	ND	0.036	mg/Kg	1	9/4/2014 12:12:43 PM	R20986
Toluene	ND	0.036	mg/Kg	1	9/4/2014 12:12:43 PM	R20986
Ethylbenzene	ND	0.036	mg/Kg	1	9/4/2014 12:12:43 PM	R20986
Xylenes, Total	ND	0.072	mg/Kg	1	9/4/2014 12:12:43 PM	R20986
Surr: 4-Bromofluorobenzene	104	80-120	%REC	1	9/4/2014 12:12:43 PM	R20986
EPA METHOD 300.0: ANIONS					Analyst	:: LGP
Chloride	ND	30	mg/Kg	20	9/4/2014 10:55:42 AM	15114
EPA METHOD 418.1: TPH					Analyst	BCN
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	9/4/2014 2:00:00 PM	15108

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range E
- Analyte detected below quantitation limits
- 0 RSD is greater than RSDImit
- R RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank В
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 2 of 5

- Sample pH greater than 2. P
- Reporting Detection Limit

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1409141

08-Sep-14

Client:

Blagg Engineering

Project:

W. D. Heath A 1A

Sample ID MB-15114

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 15114

RunNo: 21014

Prep Date: 9/4/2014 Analysis Date: 9/4/2014

SeqNo: 611765

Units: mg/Kg

%RPD

Analyte

Result

SPK value SPK Ref Val %REC LowLimit

HighLimit

RPDLimit

Qual

Chloride

PQL ND 1.5

Sample ID LCS-15114 LCSS

SampType: LCS Batch ID: 15114 TestCode: EPA Method 300.0: Anions

Prep Date: 9/4/2014

RunNo: 21014 SeqNo: 611767

Units: mg/Kg

Analysis Date: 9/4/2014

SPK value SPK Ref Val

%REC

HighLimit

%RPD **RPDLimit**

Qual

Analyte

Client ID:

15.00

93.6

90

110

14

Chloride

1.5

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range Ε

Analyte detected below quantitation limits

RSD is greater than RSDlimit 0

RPD outside accepted recovery limits R

Spike Recovery outside accepted recovery limits S

Analyte detected in the associated Method Blank В

Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit

Page 3 of 5

Sample pH greater than 2.

Reporting Detection Limit

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#: 1409141

08-Sep-14

Client:

Blagg Engineering

Project:

W. D. Heath A 1A

Sample ID MB-15108

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID:

Analyte

PBS

Batch ID: 15108

RunNo: 20989

Prep Date: 9/4/2014

Analysis Date: 9/4/2014

SeqNo: 610928

Units: mg/Kg

SPK value SPK Ref Val %REC LowLimit Result PQL 20

HighLimit

%RPD **RPDLimit**

Qual

Petroleum Hydrocarbons, TR

Sample ID LCS-15108

ND

SampType: LCS

Batch ID: 15108

PQL

20

TestCode: EPA Method 418.1: TPH RunNo: 20989

Client ID: LCSS

Result

97

Units: mg/Kg

Prep Date: 9/4/2014

Analysis Date: 9/4/2014

SeqNo: 610929

%REC

96.5

HighLimit

120

%RPD **RPDLimit** Qual

Analyte Petroleum Hydrocarbons, TR

Sample ID LCSD-15108

SampType: LCSD

TestCode: EPA Method 418.1: TPH

80

LowLimit

Batch ID: 15108

RunNo: 20989

Client ID: LCSS02 Prep Date: 9/4/2014

Analysis Date: 9/4/2014

SeqNo: 610930

Units: mg/Kg

Analyte

%REC

%RPD **RPDLimit** Qual

PQL SPK value SPK Ref Val 20

0

93.6

LowLimit HighLimit

3.11

Petroleum Hydrocarbons, TR

Result 94

100.0

100.0

SPK value SPK Ref Val

120

20

Qualifiers:

Value exceeds Maximum Contaminant Level.

Е Value above quantitation range

Analyte detected below quantitation limits J

О

R RPD outside accepted recovery limits

RSD is greater than RSDlimit

S Spike Recovery outside accepted recovery limits Analyte detected in the associated Method Blank

Η Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Sample pH greater than 2.

Reporting Detection Limit

Page 4 of 5

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

Analysis Date: 9/4/2014

Result

1.1

WO#: 1409141

08-Sep-14

Client:	Blagg Engineering
Project:	W. D. Heath A 1A

Sample ID MB-15090 MK	Samp	Туре: МЕ	BLK	Tes	tCode: El	A Method	8021B: Vola	tiles		
Client ID: PBS	Bate	ch ID: R2	0986	F	RunNo: 20986					
Prep Date:	Analysis	Date: 9/	4/2014	5	SeqNo: 6	11373	Units: mg/h	(g		
Analyte	Resuit	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050							·	
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.2		1.000		118	80	120			
Sample ID LCS-15090 MF	Samp	Type: LC	s	Tes	tCode: EF	PA Method	8021B: Vola	tiles		<u> </u>
Client ID: LCSS	Bato	Batch ID: R20986			RunNo: 20986					
Prep Date:	Analysis	Date: 9/	4/2014	S	SeqNo: 6	11374	Units: mg/K	ίg		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.90	0.050	1.000	0	90.2	80	120			
Toluene	0.90	0.050	1.000	0	89.7	80	120			
Ethylbenzene	0.94	0.050	1.000	0	93.6	80	120			
Xylenes, Total	2.9	0.10	3.000	0	97.4	80	120			
Surr; 4-Bromofluorobenzene	1.1		1.000		105	80	120			
Sample ID MB-15090	Samp	Туре: МЕ	BLK	Tes	Code: EF	PA Method	8021B: Volat	tiles		
Client ID: PBS	Bato	ch ID: 15	090	F	RunNo: 20	986				
Prep Date: 9/3/2014	Analysis	Date: 9 /-	4/2014	S	SeqNo: 6	11384	Units: %RE	С		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorobenzene	1.2		1.000		118	80	120			
Sample ID LCS-15090	Samp	Type: LC	s	Test	Code: EF	A Method	8021B: Volat	iles		
Client ID: LCSS		h ID: 150		_	unNo: 20					

Oua	lifiers

Prep Date:

Analyte

* Value exceeds Maximum Contaminant Level.

E Value above quantitation range

9/3/2014

Surr: 4-Bromofluorobenzene

J Analyte detected below quantitation limits

O RSD is greater than RSDlimit

R RPD outside accepted recovery limits

S Spike Recovery outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

SeqNo: 611385

105

LowLimit

80

%REC

SPK value SPK Ref Val

1.000

Units: %REC

120

HighLimit

%RPD

RPDLimit

Qual

P Sample pH greater than 2.

Page 5 of 5

RL Reporting Detection Limit



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107

Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name	: BLAGG		Work O	rder Numi	ber: 1409	141			Ropti	No:	1
Received by	date:	A 09	104/14	· · · · · · · · · · · · · · · · · · ·							
Logged By:	Anne Thor	ne	9/4/2014	7:00:00 Al	М		Anne S Anne S	Ham	_		
Completed B	y: Anne Thor	ne	9/4/2014				ane !	Am	_		
Reviewed By		<u> </u>	09/04	1/16/							
Chain of C	ustody			((, -, -							
1. Custody	seals intact on sa	mple bottles?			Yes		No		Not Present	✓	
2. Is Chain	of Custody compl	lete?			Yes	V	No		Not Present [
3. How was	the sample delive	ered?			Cou	rier					
<u>Log In</u>						·					
4. Was an	attempt made to	cool the sample	es?		Yes	V	No		· NA		
5. Were all	samples received	i at a temperat	ure of >0° C t	o 6.0°C	Yes	\checkmark	No [NA [
6. Sample(s) in proper conta	iner(s)?			Yes	V	No				
7. Sufficient	sample volume f	for indicated te	st(s)?		Yes	V	No				
8. Are samp	les (except VOA	and ONG) pro	perly preserve	d? .	Yes	✓	No [
9. Was pres	ervative added to	bottles?			Yes		No	Y	na [
10.VOA vials	s have zero head	space?			Yes		No		No VOA Vials	✓	•
	/ sample contain	•	oken?		Yes		No	V	· · · · · · · · · · · · · · · · · · ·		
	•								# of preserved bottles checked	i	
	erwork match bo				Yes	✓	No		for pH:		-45
(Note discrepancies on chain of custody)								(° Adjusted?		>12 unless noted)	
13. Are matrices correctly identified on Chain of Custody?						V	No No				
14. Is it clear what analyses were requested?15. Were all holding times able to be met?				Yes Yes		No l		Checked b	y:		
	ify customer for a				163	ŒJ	110	_			
	ndling (if app					_		r=1	1		
16. Was clier	nt notified of all di	screpancies w	ith this order?		Yes		No		NA (<u> </u>	
	son Notified:			Date	;	·					
'	Whom:	e man to seem to a man and a read to		Via:	eM	ail [_	Phone	Fax	In Person	-	
1	garding:	a construction a	area and a second a	Sample of Section 1995	<u> </u>		galanta salaga kalangi ing pinakanan na		and the latter are the second	-	
L	ent Instructions:					• • •	to and anneadones a		Annual Control of the		
17. Addition											
18. <u>Cooler I</u> Coole	(A.). (1) B. (1)	Condition	Seal Intact	Seal No	Seal D	ate	Signed B	v			
1	2.1	Good	Yes	Ocal IVO	Ocal.D	-10	i Gigiled D	.			
<u> </u>		1		·					•		

Client: BP AMERICA BLAGE EVER Mailing Address: P.O. Box 87 BLOWFIELD NM 87413		SAMEDAY Standard Krush				LALL HALL ENVIRONMENTAL															
						ANALYSIS LABORATORY www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109															
		Project Name: W- D- HEATH A 1A Project #:																			
)5-34				Fax 505-345-4107									
			32-1199					Analysis Request													
email or Fax#:			Project Manager: J- BLA66				nly)	30)					(4)								
QA/QC Package: Standard □ Level 4 (Full Validation)			J-BLAGG Sampler: J-BLAGG				(Gas only)	O / MF			SIMS)		O4,S(PCB's							
Accreditation NELAP Other			Sampler: J - BA66 On Ice Yes - No.				трн (O / DR	8.1)	4.1)			3,NO ₂ ,F	, 8082						ź	
	(Type) _			Sample Temperature:				3E +	(GR(d 47	d 50	or 8	als	Š.	des /		VOA				\ <u>{</u>
Date	Time	Matrix	Sample Request ID	A .aimital	Preservative Type	HEALS NO. 1755		BTEX + MTBE	TPH 8015B (GRO / DRO / MRO)	TPH (Method 418.1)	EDB (Method 504.1)	PAH's (8310 or 8270	RCRA 8 Metals	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	CHUPPINE			Air Rubbles (Y or N)
3/14	10000	Soil	OR 95 BAT	403×1	CEUL	-01	X			×								~		\top	\top
11	1007	11	5-pt @ 6 21 B67 5-pt @ 5	11	15	702	X			×								×	-		\dagger
																					T
	ļ																				Γ
			-																		
																		\dashv			ot
														\sqcup						1	\perp
							-							igdash				-		 	\perp
	-						ļ <u>.</u>				_							_		+-	\vdash
																		\dashv		+	\vdash
Date:	Time:	Relinquish	led b <u>y</u> :	Received by: Date Time				Remarks: Biu BP													
3/14	1127	Jell Blogg		Motuporle 33/2014 1127			PATKEY: ZEVHOIBGTZ														
Date:	Time:	Relinquish	ed by:	Received by: Date Time						ļ	AT	NEJ	-		-V F	L	ق ريد	. ~			
9/3/14	2024	1/ Uni	the Warles	nu 1	09/04/14 0700								J.								
. ′ 1	f necessary,	samples subr	nitted to Hall Environmental may be subc	ontracted to other ac	credited laboratorie	es. This serves as notice of this	s possib	oility. A	Any su	ıb-con	tracted	d data	will be	clear	v nota	ted on	the ar	nalytica	report		

L

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

September 2, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: W D HEATH A 001A

AP1#: 3004510843

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about September 4, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

9 Ducke

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

September 2, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

W D HEATH A 001A API 30-045-22663 (P) Section 9 – T29N – R09W San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 21 bbl BGT and a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around September 4, 2014.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



