District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Form C-144 Revised June 6, 2013

Pit, Below-Grade Tank, or

Proposed Alternative Method Permit or Closure Plan Application Oll CONS. DIV DIST. 3
1 type of action.
Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method NOV 17 2014
45-29 Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Gallegos Canyon Unit 170E
API Number:3004524175 OCD Permit Number:
U/L or Qtr/Qtr E Section 35 Township 29N Range 12W County: San Juan
Center of Proposed Design: Latitude36.68554 Longitude108.07407 NAD: □1927 ☒ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
□ String-Reinforced Liner Seams: □ Welded □ Factory □ Other
3. Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Single walled/double bottomed; side walls not visible
Liner type: Thicknessmil
4.
Alternative Method: Submitted of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptate are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)	Yes No NA Yes No NA Yes No NA
 Written confirmation or verification from the municipality; Written approval obtained from the municipality Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	cuments are
 □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC □ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit
Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)	and management i it
On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be	attached to the
closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	mucneu to the
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P. 19.15.17.10 NMAC for guidance.	ce material are lease refer to
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland.	
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☐ No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	
Within a 100-year floodplain. FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plants are composed by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17.	
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	of.
Name (Print): Title:	
Signature: Date:	
e-mail address:Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 2/1	12014
Title: Ompliance Office OCD Permit Number:	
Title: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	complete this

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure requires	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Jeff Posee	Date:November 17, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gallegos Canyon Unit 170E API No. 3004524175 Unit Letter E, Section 35, T29N, R12W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141

Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

			Rela	ease Notific	eatio	n and Co	orrective A	ction				
						OPERA	TOR		Initi	al Report 🛛 Final Repor		
Name of Co						Contact: Jef						
		Court, Farmi				Telephone No.: 505-326-9479 Facility Type: Natural gas well						
Facility Nai	ne: Ganeg	gos Canyon U	JIIIL I /OE	<u> </u>		Facility Typ	e: Naturai gas v	wen				
Surface Ow	ner: Priva	te		Mineral C)wner:	ner: Private API No. 3004524175						
				LOCA	OITA	N OF REI	LEASE					
Unit Letter	Section	Township	Range	Feet from the		/South Line	Feet from the	1	est Line	County: San Juan		
E	35	29N	12W	1,/33	North	1	910	West				
	1	Lati	itude3	6.68554		Longitud	e108.07407_					
				NAT	URE	OF REL	EASE					
						- 	Release: N/A			Recovered: N/A		
Source of Release: below grade tank – 95 bbl						Date and F	lour of Occurrenc	e:	Date and	Hour of Discovery: N/A		
Was Immedia	ate Notice (Yes [No ⊠ Not Re	quired	If YES, To	Whom?					
By Whom?						Date and H	our					
	course Read		Yes 🛛	No	-		lume Impacting t	the Water	rcourse.			
If a Watercou	irse was Im											
Tra Watercoo		pacted, 2 coor										
									g removal t	o ensure no soil impacts from		
					noved	and the area u	nderneath the BG	T was sa	impled. Ti	ne area under the BGT was		
regulations al public health should their o or the enviror	I operators or the envi- perations h ment. In a	are required to ronment. The ave failed to a ddition, NMO	report an acceptance dequately CD accep	d/or file certain re e of a C-141 repo investigate and re	elease n rt by th emediat	notifications ar e NMOCD mate contamination	nd perform correctarked as "Final Room that pose a three	tive action eport" do eat to gro	ons for rele ses not reli ound water	eases which may endanger eve the operator of liability , surface water, human health		
		_					OIL CONS	SERV	ATION	DIVISION		
Signature:	John !	Jace										
-	•			-		Approved by	Environmental S _I	pecialist:				
			r			Approval Dat	e:	E	xpiration I	Date:		
E-mail Addre	Latitude36.68554					Conditions of	Approval:			Attached		
Date: Novem	ber 17, 20	14	Pho	one: 505 - 326-9479)							

^{*} Attach Additional Sheets If Necessary

CLIENT: BP		NGINEERING, II BLOOMFIELD, N		API#: 3004	524175
	(50	05) 632-1199		TANK ID (if applicble):	Α
FIELD REPORT:	(circle one): BGT CONFIRMATION]/ RELEASE INVESTIGATION /	OTHER:	PAGE #:	_ of 1 _
SITE INFORMATION	I: <u>SITE NAME: GCU #</u>	170E		DATE STARTED:	09/24/14
QUAD/UNIT: E SEC: 35 TWP:	29N RNG: 12W PM	: NM CNTY: SJ	ST: NM	DATE FINISHED:	
1/4 -1/4/FOOTAGE: 1,755'N / 91	O'W SW/NW LEASE PROD. FORMATION: DK C	TYPE: FEDERAL/STATE STRIKE CONTRACTOR: MBF - S		ENVIRONMENTAL SPECIALIST(S):	NJV
REFERENCE POINT				GL ELEV.:	5.345'
1) 95 BGT (SW/DB)	GPS COORD.:	86.68554 X 108.07407	DISTANCE/BEA	RING FROM W.H.:	71', N68E
2)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
3)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
4)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) #	OR LAB USED: HALI			OVM READING (ppm)
1) SAMPLE ID: 5PC - TB@6'	(95) SAMPLE DATE: 09/24	1/14 SAMPLETIME: 1100	LAB ANALYSIS: 418	.1/8021B/300.0 (CI	
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
SOIL DESCRIPTION	SOIL TYPE: SAND / SILTY SAND	SILT / SILTY CLAY / CLAY / GRAV	/EL / OTHER		
SOIL COLOR: DARK YEL		PLASTICITY (CLAYS): NON PLAST		OHESIVE / MEDIUM PLASTIC	/ HIGHLY PLASTIC
COHESION (ALL OTHERS): NON COHESIVE/ SLIGHTL	COHESIVE / COHESIVE / HIGHLY COHESIVE				
CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY SLIGHTLY MOIST MOIST / W		HC ODOR DETECTED: YES NO	EXPLANATION		
SAMPLE TYPE: GRAB COMPOSITE -#		ANY AREAS DISPLAYING WETNE	ESS VES / NO EXPLAN	IATION - POSSIBLY GR	
DISCOLORATION/STAINING OBSERVED: YES IN				@ BGT BOTTO	
SITE OBSERVATION	S: LOST INTEGRITY OF EQUIPMEN	T: YES NO EXPLANATION -			
APPARENT EVIDENCE OF A RELEASE OBSERVE					
EQUIPMENT SET OVER RECLAIMED AREA: OTHER:	YES/NO EXPLANATION - UNKNC	DWN AT THIS TIME.			
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <50' N		ft. X <u>NA</u> ft.		IMATION (Cubic Yards)	400
	EAREST WATER SOURCE: >1,000			D TPH CLOSURE STD:	100 ppm
SITE SKETCH [BGT Located: off on sit	te PLOT PLAN cir		Calib, read, = NA	ppm RF =0.52
STEE CONTAIN	/ \	aoua arada tank	i l	CALIB. GAS = NA	ppm
RING		oove-grade tank	N LIME		
			1	MISCELL. N	IOTES
PROD.		•	L —	o: N15168983	<u> </u>
TANK		∖ PBGTL		0#:)TO
	$(x \stackrel{\widehat{X}}{x} x)$	T.B. ~ 5' B.G.	I —	K: ZEVH01B0 J#: Z2-006Q0	312
FENCE		Д. В. С.	_		/14/10
FENCE			_		6/12/13
ТО	SEPA	RATOR	Tan ID	k OVM = Organic Vap	or Meter
W.H.	TO		Ā	1	_
_	√ METER ▼ RUN	•	X - S.P.D.	BGT Sidewalls Visible:	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION	ON DEPRESSION; B.G. = BELOW GRADE; B = E	BELOW, T.H. = TEST HOLE; ~ = APPROX.	.; W.H. = WELL HEAD;	BGT Sidewalls Visible:	
T,B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGLE	OW-GRADE TANK LOCATION; SPD = SAMPLE = WALL: DW - DOUBLE WALL: SB - SINGLE BO	POINT DESIGNATION; R.W. = RETAININ TTOM: DB - DOUBLE BOTTOM	G WALL; NA - NOT M	lagnetic declination:	10 E
NOTES:	The state of the s		24/14		

Analytical Report

Lab Order 1409C36

Date Reported: 9/26/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC - TB @ 5' (95)

Project: GCU #170E

Collection Date: 9/24/2014 11:00:00 AM

Lab ID: 1409C36-001

Matrix: MEOH (SOIL) Received Date: 9/25/2014 7:00:00 AM

Analyses	Result	RL Qua	al Units	DF	Date Analyzed	Batch
EPA METHOD 8021B: VOLATILES			-		Analys	t: NSB
Benzene	ND	0.033	mg/Kg	1	9/25/2014 10:44:25 AN	R21449
Toluene	ND	0.033	mg/Kg	1	9/25/2014 10:44:25 AN	R21449
Ethylbenzene	ND	0.033	mg/Kg	1	9/25/2014 10:44:25 AN	/ R21449
Xylenes, Total	ND	0.066	mg/Kg	1	9/25/2014 10:44:25 AN	1 R21449
Surr: 4-Bromofluorobenzene	91.8	80-120	%REC	1	9/25/2014 10:44:25 AN	1 R21449
EPA METHOD 300.0: ANIONS					Analys	t: SRM
Chloride	ND	30	mg/Kg	20	9/25/2014 11:14:37 AM	1 15510
EPA METHOD 418.1: TPH					Analys	t: BCN
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	9/25/2014 5:00:00 PM	15501

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 4

- P Sample pH greater than 2.
- RL Reporting Detection Limit

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1409C36

26-Sep-14

Client:

Blagg Engineering

Project:

GCU #170E

Sample ID MB-15510

SampType: MBLK

PQL

1.5

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 15510

RunNo: 21476

Prep Date: 9/25/2014 Analysis Date: 9/25/2014 Result

SeqNo: 627974

Units: mg/Kg

Analyte

HighLimit

SPK value SPK Ref Val %REC LowLimit

TestCode: EPA Method 300.0: Anions

%RPD **RPDLimit**

Qual

Chloride

ND

SampType: LCS

RunNo: 21476

Client ID: LCSS

Sample ID LCS-15510

Batch ID: 15510

Prep Date: 9/25/2014

Analysis Date: 9/25/2014 **PQL**

1.5

SeqNo: 627975

Units: mg/Kg

HighLimit

%RPD **RPDLimit**

Qual

Analyte Chloride

%REC 93.7

90

14

15.00

SPK value SPK Ref Val

110

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range E
- Analyte detected below quantitation limits
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- S Spike Recovery outside accepted recovery limits
- В Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- Not Detected at the Reporting Limit ND Sample pH greater than 2.
- Reporting Detection Limit

Page 2 of 4

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#: 1409C36

26-Sep-14

Client:

Blagg Engineering

Project:

GCU #170E

Sample ID MB-15501

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID:

PBS

Batch ID: 15501

PQL

20

RunNo: 21445

Prep Date:

Result

ND

Analyte

9/25/2014

Analysis Date: 9/25/2014

SeqNo: 626909

Units: mg/Kg

HighLimit

Qual

Petroleum Hydrocarbons, TR

TestCode: EPA Method 418.1: TPH

RPDLimit %RPD

Sample ID LCS-15501

SampType: LCS

PQL

20

RunNo: 21445

%REC

119

Client ID:

LCSS

Batch ID: 15501

SeqNo: 626910

SPK value SPK Ref Val %REC LowLimit

80

LowLimit

Units: mg/Kg

Analyte

Prep Date: 9/25/2014

Analysis Date: 9/25/2014

Result

Result

120

120

SPK value SPK Ref Val

100.0

HighLimit

RPDLimit

Petroleum Hydrocarbons, TR

100.0

TestCode: EPA Method 418.1: TPH

120

Qual

Sample ID LCSD-15501

Client ID:

Prep Date:

LCSS02

SampType: LCSD Batch ID: 15501

RunNo: 21445

Units: mg/Kg

120

Qual

Analyte Petroleum Hydrocarbons, TR

9/25/2014

Analysis Date: 9/25/2014 **PQL**

20

0

SeqNo: 626911

117

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD 1.27

%RPD

RPDLimit

20

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range E

Analyte detected below quantitation limits

Spike Recovery outside accepted recovery limits

RSD is greater than RSDlimit O

RPD outside accepted recovery limits R

В

ND Not Detected at the Reporting Limit

Sample pH greater than 2. P

Reporting Detection Limit

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

Page 3 of 4

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1409C36

26-Sep-14

Client:

Blagg Engineering

Project:

GCU #170E

Sample ID MB-15490 MK	Samp1	SampType: MBLK TestCode				PA Method 8021B: Volatiles				
Client ID: PBS	Batcl	n ID: R2	1449	F	1449					
Prep Date:	Analysis D	nalysis Date: 9/25/2014 SeqNo: 0			SeqNo: 627632			(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene ·	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.91		1.000		91.4	80	120			

Sample ID LCS-15490 MK	Samp	Type: LC	s	Tes	TestCode: EPA Method 8021B: Volatiles					
Client ID: LCSS	Batc	Batch ID: R21449 RunNo: 21449								
Prep Date: Analysis Date: 9/25/2014			nalysis Date: 9/25/2014 SeqNo: 627633 Units: m			Units: mg/F	(g			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.0	0.050	1.000	0	102	80	120			
Toluene	1.0	0.050	1.000	0	100	80	120			
Ethylbenzene	1.0	0.050	1.000	0	104	80	120			
Xylenes, Total	3.1	0.10	3.000	0	103	80	120			
Surr: 4-Bromofluorobenzene	1.0		1.000		100	80	120			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 4



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG Work Order Number: 1409C36 RcptNo: 1 Received by/date: Logged By: Lindsay Mangin 9/25/2014 7:00:00 AM Completed By: Lindsay Mangin 9/25/2014 7:42:47 AM Reviewed By: Chain of Custody Yes 🗌 Not Present 1. Custody seals intact on sample bottles? No 🔲 Yes 🗹 No 🗌 Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Courier Log In NA 🗌 No 🗌 Yes 🔽 4. Was an attempt made to cool the samples? 5. Were all samples received at a temperature of >0° C to 6.0°C No 🗌 NA 🗌 Yes 🗹 No \square Sample(s) in proper container(s)? Yes 🗹 7. Sufficient sample volume for indicated test(s)? Yes 🗹 No 🗀 8. Are samples (except VOA and ONG) properly preserved? Yes V No 🗆 Yes No 🗹 NA 🗌 9. Was preservative added to bottles? No VOA Vials No 🗌 10.VOA vials have zero headspace? Yes 🗌 Yes □ No 🗹 11. Were any sample containers received broken? # of preserved bottles checked No 🔲 for pH: Yes 🗹 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? Yes 🗸 No \square 13. Are matrices correctly identified on Chain of Custody? Yes 🗹 No 🗆 14. Is it clear what analyses were requested? No 🗌 Checked by: Yes 🔽 15. Were all holding times able to be met? (If no, notify customer for authorization.) Special Handling (if applicable) Yes 🗌 16. Was client notified of all discrepancles with this order? No 🗆 NA 🔽 Person Notified: Date: By Whom: eMail Phone Fax Regarding: **Client Instructions:** 17. Additional remarks: 18. Cooler Information Cooler No Temp C Condition Seal Intact Seal No Seal Date Signed By 1.5 Good

Chain-of-Custody Record				I um-Around	IIIIO.	SAME	1	i l	1 1	-	i Ai		F	W	T R	20	NF	4FI	NTA	A.J			
Client:	Client: BLAGG ENGR. / BP AMERICA				☑ Rush _	DAY				A	N.	AL	YS	SIS	S L	.AE	30	RA	TOI	_	<i>r</i> .		
Mailing Address: P.O. BOX 87				GCU # 170E				www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109															
			FIELD, NM 87413	Project #:				Tel. 505-345-3975 Fax 505-345-4107															
Phone #: (505) 632-1199												Â	naly	/sis	Rec	ues	t 📜				02 2007		
email or Fax#:				Project Manager:				4	N]			4)				न			Ţ		
QA/QC Package: Standard			Level 4 (Full Validation)	NELSON VELEZ			5 (8021B)	+ TPH (Gas only)	/mwa			1S)		PO4,SO	2 PCB's			ter - 300.1)		l a			
Accreditation:			Sampler:	NELSON VI	ELEZ -nr	- 8	(Gas		ਜ਼	ਜ਼	SIS		102,	8082			/ water		μ				
□ NELAP □ Other			On Ice	X Yes	the manager of the late of the	1	ᄺ		418	504	827	اي	03,1	_		8	8		e sa	1			
□ EDD (Type)			Sample Temp	erature () 55		Į.	3E +	(GR	pot	ğ	ō	etal	S,	cid	<u>র</u>	-i-	-3	e e	osit	2			
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO	BTEX + -MTB	BTEX + MTBE	TPH 8015B (GRO / DRO	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0	Grab sample	5 pt. composite sample	Air Dukhla		
9/24/14	1100	SOIL	5PC - TB @ 5' (95)	4 oz 1	Cool	-001	٧			٧								٧		٧.	Γ		
	***************************************			-												\neg							
																\neg			1		Γ		
													\neg						1		Γ		
			RUN TPH 8015B IF TPH 418.1 > 100 mg/Kg															1	1		L		
											\dashv		\dashv			\dashv	\dashv	+	-	-	\vdash		
, .					<u> </u>											\dashv	\dashv	+	-	\vdash	-		
									-	\dashv			\dashv			\dashv	\dashv	+	_	\vdash	-		
									\dashv				-	_		\dashv	\dashv		+		-		
		<u> </u>										\dashv	_	\dashv		\dashv		+	+-	\vdash	L		
				ļ								_					\dashv				\vdash		
		D. V lak		Deseived hou		Bata The				1					[L		
Date: 9/24/14	Time:	Relinquish	er of	Received by: Date Time 924/N 1716																			
Date: Time: Relinquished by:			Received by Date Time				Jeff Peace, 200 Energy Court, Farmington, NM 87401																
7/24/14	1915	1/100	strellatters	09/25/12/0700 Work Order: N151																			
1	If necess	arly, samples s	submitted to Hall Environmental may be s	subcontracted to other	accredited laboratorie	s. This serves as notice of	this po	ossibili	ity. An	y sub-	contra	acted d	lata wi	ll be c	dearly	notate	d on th	ne analy	lical repo	ort.	_		





BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

November 21, 2013

LA Ascencion LLC PO Box 6724 Farmington, NM 87499

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: GALLEGOS CANYON UNIT 170E

Dear LA Ascencion LLC,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about January 21, 2013. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper Surface Land Negotiator

9 Doller

BP America Production Company

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

November 21, 2013

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

GALLEGOS CANYON UNIT 170E API 30-045-24175 (G) Section 35 – T29N – R12W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



