<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources** Department Oil Conservation Division

1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or 12378 Proposed Alternative Method Permit or Closure Plan Application
1 Toposed Thermative Method 1 elimit of Closure I fail Application
Type of action: Below grade tank registration OIL CONS. DIV DIST. 3
Closure of a pit, below-grade tank, or proposed alternative method
Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID#:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Dryden 1M
API Number:3004532474OCD Permit Number:
U/L or Qtr/QtrO Section28 Township28N Range8W County:San Juan
Center of Proposed Design: Latitude36.62721 Longitude107.68610 NAD: ☐1927 ☒ 1983
Surface Owner: X Federal X State Private Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no
☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. Below-grade tank: Subsection 1 of 19.15.17.11 NMAC Tank A
Volume: 95.0 bbl Type of fluid: Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Double walled/double bottomed; side walls not visible
Liner type: Thicknessmil
4.
Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

٠,٠

Form C-144

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	cuments are
attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC	
Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Form C-144 Oil Conservation Division Page 3 of 6

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13. D	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial	luid Management Pit
Alternative Closure Method	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Fig. 15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17.	
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believes.	ef
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 12/1	12014
Title: OCD Permit Number:	
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
☐ Closure Completion Date:3/2/2012	
20. Closure Method: Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-loc ☐ If different from approved plan, please explain.	op systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please incomark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)	licate, by a check

22. Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure repelled. I also certify that the closure complies with all applicable closure requirements.	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Posee	Date:November 18, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Dryden 1M</u> <u>API No. 3004532474</u> <u>Unit Letter O, Section 28, T28N, R8W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows:

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	23

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

with in the active process area

- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

- 13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover
 - BP will seed the area when the well is plugged and abandoned as part of final reclamation.
- 14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.
 - BP will notify NMOCD when re-vegetation is successful.
- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following:
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 8750 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease	Notific	atio	n and Co	orrective A	ction				
							OPERA	ГOR	ĺ	Initia	al Report	\boxtimes	Final Repor
Name of Co							Contact: Jef						
		Court, Farmi	ington, N	M 874	101			No.: 505-326-94					
Facility Nar	ne: Dryde	n lM					Facility Typ	e: Natural gas v	well				
Surface Ow	ner: Feder	al			Mineral O	wner:	Federal			API No	. 30045324	74	
					LOCA	TIO	N OF REI	LEASE					
Unit Letter	Section	Township	Range	Feet 1			South Line	Feet from the	East/W	est Line	County: Sa	n Juan	
0	28	28N	8W	815		South		2,470	East		, ,		
		Lati	itude3	6.6272	21		Longitud	e107.68610_	l		<u> </u>		ye
					NAT	URE	OF RELI	EASE					
Type of Relea	ase: none							Release: N/A		Volume F	Recovered: N	/A	
		v grade tank –	95 bbl					lour of Occurrenc	e:	Date and	Hour of Disc	overy:	
Was Immedia	ite Notice (Yes	No	☑ Not Red	quired	If YES, To	Whom?					
By Whom?							Date and H						
Was a Watero	course Read		Yes 🗵	No			If YES, Vo	lume Impacting t	he Water	course.			
If a Watercou	rse was Im	pacted, Descri	ibe Fully.*	:									-
			-										
the BGT. Soi	l analysis r	esulted in TPI	H, BTEX a	and chl	oride below	stand	ards. Analysis	the BGT was dor s results are attach	ned.			,	
Describe Area backfilled and						oved :	and the area u	nderneath the BG	T was sai	npled. Th	ne excavated	area w	as
regulations al public health should their o	operators or the envirus or the envirus herations herations had been to be a second to be a seco	are required to onment. The ave failed to a ddition, NMO	o report an acceptance dequately CD accept	d/or fil e of a (investi	e certain rel C-141 repor gate and rer	lease n t by th mediat	otifications ar e NMOCD ma e contamination	knowledge and und perform corrector arked as "Final Rector that pose a three the operator of rector of rector and under the operator of rector of rector and under the operator of rector	tive actio eport" do eat to gro	ns for rele es not reli und water	eases which reve the opera , surface wat	nay end itor of er, hun	danger liability nan health
Signature:	ell h	2000						OIL CONS	SERV <i>A</i>	ATION	DIVISIO	N	
Printed Name	: Jeff Peace						Approved by	Environmental Sp	pecialist:				
Title: Field E	nvironment	al Coordinato	r				Approval Dat	e:	Ex	epiration I	Date:		
E-mail Addre	ss: peace.je	ffrey@bp.com	n				Conditions of	Approval:			Attached		
Date: Novem	ber 18, 201	4	Pho	ne: 505	-326-9479								

^{*} Attach Additional Sheets If Necessary

CLIENT: BP		IGINEERING, IN		API #: 300	4532474
		•		TANK ID (if applicble):	Α
FIELD REPORT:	(circle one): BGT CONFIRMATION /	RELEASE INVESTIGATION / C	OTHER:	PAGE #:	1 of 1
		I#1M		DATE STARTED:	02/23/12
QUAD/UNIT: O SEC: 28 TWP:	28N RNG: 8W PM:	NM CNTY: SJ	ST: NM	DATE FINISHED:	
1/4-1/4/FOOTAGE: 815'S / 2,47 0	E SW/SE LEASE TY	PE: FEDERAL STATE	/ FEE / INDIAN	ENVIRONMENTAL	
LEASE #: NM012200	PROD. FORMATION: MV CO	NTRACTOR: MBF	N 	SPECIALIST(S):	JCB
REFERENCE POINT	T: WELL HEAD (W.H.) GPS (COORD.: 36.6272	7 X 107.68585	GL ELE	≣∨: 5.788 '
1) 95 BGT (DW/DB)					99', S68W
2)	GPS COORD.:		DISTANCE/BE	EARING FROM W.H.:	
3)	GPS COORD.:		DISTANCE/BE	ARING FROM W.H.:	
4)	GPS COORD.:		DISTANCE/BE	ARING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR	LAB USED: HAL	L	******	OVM READING
1) SAMPLE ID: 95 BGT 5-pt. (6' SAMPLE DATE: 02/23/12	SAMPLETIME: 1105	LAB ANALYSIS: 418.1/8	8015B/8021/B/30	0.0 (CI) 0.0
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
SOIL DESCRIPTION	SOIL TYPE: SAND / SILTY S	SAND/SILT SILTY CLAY / (CLAY / GRAVEL / OT	HER	
SOIL COLOR: DARK YEL	LOWISH ORANGE				
		PLASTICITY (CLAYS): NON PL	ASTIC / SLIGHTLY PLASTIC /	COHESIVE / MEDIUM PLASTI	C / HIGHLY PLASTIC
		,	ŕ		
		HC ODOR DETECTE	D: YES (NO) EXPL	ANATION	
		M DCT ODSEDVED			
		JW BGT OBSERVED.			
		NA NIA			
				•	· — —
	E WEST WILL COST OF THE STATE O				
SHESKETOH		PLOTPLAN circ			Kr - 0.32
	\oplus		1 1		
	WELL HEAD				
	DATE INFORMATION: SITENME DRYDEN#1M ONTO SITENME 02/23/12 LIADRUNT O SEC 28 TWAP 28N PMS 8W PM NM ONTO SJ ST NM DATE PINISHED ALPARATOR SHIP SITENME DRYDEN PMS 8W PM NM ONTO SJ ST NM DATE PINISHED ALPARATOR SHIP SITENME DRYDEN PMS 8W PM NM ONTO SJ ST NM DATE PINISHED ALPARATOR SHIP SITENME DRYDEN PMS 8W PM NM ONTO SJ ST NM DATE PINISHED ALPARATOR SHIP SITENME DRYDEN PMS 8W PM NM ONTO SJ ST NM DATE PINISHED AMPLEID PRODUCTIONE BENEFIT STATE FEET PMS EXPONENTIAL SHIP STATE FEET PMS BENEFIT				
			_		
(505) 632-1199 GPAPICHOP TANK ID (505) 632-1199 GPAPICHOP GPAPICHOP TANK ID STEINFORMATION: SIEMANE DRYDEN# IM DATE STRUTE DO2/23/12 DATE STRUTE INFORMATION: SIEMANE DRYDEN# IM DATE STRUTE DO2/23/12 DATE STRUTE INFORMATION: SIEMANE DRYDEN# IM DATE STRUTE DO2/23/12 DATE STRUTE INFORMATION: SIEMANE DRYDEN# IM DATE STRUTE DATE STRUTE DO2/23/12 DATE STRUTE INFORMATION: SIEMANE DRYDEN# IM DATE STRUTE DATE STRUTE DO2/23/12 DATE STRUTE INFORMATION: SIEMANE DRYDEN # IM DATE STRUTE DATE STRUTE DO2/23/12 DATE STRUTE INFORMATION: SIEMANE DRYDEN # IM DATE STRUTE DATE STRUTE DO2/23/12 DATE STRUTE INFORMATION: SIEMANE DRYDEN # IM DATE STRUTE DATE STRUTE DO2/23/12 DATE STRUTE INFORMATION: DATE DATE STRUTE DATE STRUTE DATE STRUTE DO2/23/12 DATE STRUTE INFORMATION: DATE DATE STRUTE DATE STRUTE DATE STRUTE DO2/23/12 DATE STRUTE INFORMATION: DATE STRUTE D					
				-	<u> </u>
			-	-J - Z2-00690-C	
			-	ermit date/s): N6/	14/10
	XXX		_		
	×		Tar	ık	
		•			ble: Y /N/ NA
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAN	/ATION DEPRESSION; B.G. = BELOW GRADE; I			BGT Sidewalls Visi	
T.B. = TANK BOTTOM; PBGTL = PREVIOUS	BELOW-GRADE TANK LOCATION; SPD = SAMI	PLE POINT DESIGNATION; R.W. = F	RETAINING WALL; 📙 👠	lagnetic declinati	on: 10°E
TDAYEL NOTEC:	, OTT OUTOLE TAPLE, DAY - DOODLE ANDER, OF				···

Analytical Report

Lab Order 1202889

Date Reported: 3/2/2012

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 95 BGT 5-pt @ 6'

Project: Dryden 1M

Collection Date: 2/23/2012 11:05:00 AM

Lab ID: 1202889-001

Matrix: SOIL Recei

Received Date: 2/28/2012 10:20:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	E ORGANICS				. Analyst: JMP
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	2/29/2012 9:03:44 AM
Surr: DNOP	88.3	77.4-131	%REC	1	2/29/2012 9:03:44 AM
EPA METHOD 8015B: GASOLINE RA	NGE				Analyst: RAA
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	2/29/2012 4:55:10 PM
Surr: BFB	111	69.7-121	%REC	1	2/29/2012 4:55:10 PM
EPA METHOD 8021B: VOLATILES					Analyst: RAA
Benzene	ND	0.047	mg/Kg	1	2/29/2012 4:55:10 PM
Toluene	ND	0.047	mg/Kg	1	2/29/2012 4:55:10 PM
Ethylbenzene	ND	0.047	mg/Kg	1	2/29/2012 4:55:10 PM
Xylenes, Total	ND	0.093	mg/Kg	1	2/29/2012 4:55:10 PM
Surr: 4-Bromofluorobenzene	110	85.3-139	%REC	1	2/29/2012 4:55:10 PM
EPA METHOD 300.0: ANIONS					Analyst: BRM
Chloride	23	7.5	mg/Kg	5	2/29/2012 2:36:07 PM
EPA METHOD 418.1: TPH					Analyst: JMP
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	2/29/2012

Qualifiers:

- */X Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202889

02-Mar-12

Client:

Blagg Engineering

Project:

Dryden 1M

Sample ID MB-882

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 882

RunNo: 1194

Prep Date: 2/29/2012 Analysis Date: 2/29/2012

PQL

SeqNo: **34005**

SPK value SPK Ref Val %REC LowLimit

Units: mg/Kg

HighLimit

%RPD **RPDLimit**

Qual

Analyte Chloride

ND 1.5

Result

Qualifiers:

Value exceeds Maximum Contaminant Level. */X

Value above quantitation range Е

Analyte detected below quantitation limits

RPD outside accepted recovery limits

Analyte detected in the associated Method Blank В

Holding times for preparation or analysis exceeded Н

Not Detected at the Reporting Limit ND

Page 2 of 6

Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202889

02-Mar-12

Client:

Blagg Engineering

Project:

Dryden 1M

Sample ID MB-873

SampType: MBLK

TestCode: EPA Method 418.1: TPH

PBS Client ID:

2/28/2012

Batch ID: 873

RunNo: 1167 SeqNo: 33247

Units: mg/Kg

Prep Date: Analyte

Client ID:

Result

Analysis Date: 2/29/2012

SPK value SPK Ref Val %REC LowLimit

HighLimit %RPD

RPDLimit

Qual

Petroleum Hydrocarbons, TR

SampType: LCS

20

PQL

TestCode: EPA Method 418.1: TPH

Sample ID LCS-873

ND

Batch ID: 873

RunNo: 1167

Units: mg/Kg

Analyte

2/28/2012 Prep Date:

LCSS

Analysis Date: 2/29/2012 Result **PQL**

20

SPK value SPK Ref Val

%REC

SeqNo: 33248

LowLimit 87.8 HighLimit 115

RPDLimit

Qual

Petroleum Hydrocarbons, TR

Sample ID LCSD-873

SampType: LCSD Batch ID: 873

100.0

RunNo: 1167 SeqNo: 33249

Units: mg/Kg

Analyte

Client ID:

Prep Date: 2/28/2012

LCSS02

Analysis Date: 2/29/2012

%REC LowLimit

TestCode: EPA Method 418.1: TPH

HighLimit 115 %RPD

Qual **RPDLimit**

Petroleum Hydrocarbons, TR

Result 110

SPK value SPK Ref Val 20

100.0

110

0.937

%RPD

8.04

Qualifiers:

R

Value exceeds Maximum Contaminant Level */X

Value above quantitation range Е

Analyte detected below quantitation limits J RPD outside accepted recovery limits

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit Reporting Detection Limit

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202889

02-Mar-12

Client:

Blagg Engineering

Project: Bragg Dryder	n IM					
Sample ID MB-872	SampType: MBLK	TestCode: EPA Method	8015B: Diesel Range (Organics		
Client ID: PBS	PBS Batch ID: 872 RunNo: 1169					
Prep Date: 2/28/2012	Analysis Date: 2/29/2012	SeqNo: 33257	Units: mg/Kg			
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual		
Diesel Range Organics (DRO) Surr: DNOP	ND 10 8.7 10.00	86.7 77.4	131			
Sample ID LCS-872	SampType: LCS	TestCode: EPA Method	8015B: Diesel Range C	Organics		
Client ID: LCSS	Batch ID: 872	RunNo: 1169				
Prep Date: 2/28/2012	Analysis Date: 2/29/2012	SeqNo: 33258	Units: mg/Kg			
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual		
Diesel Range Organics (DRO)	45 10 50.00	0 90.2 62.7	139			
Surr: DNOP	4.4 5.000	87.7 77.4	131			
Sample ID MB-891	SampType: MBLK	TestCode: EPA Method	8015B: Diesel Range C)rganics		
Client ID: PBS	Batch ID: 891	RunNo: 1195				
Prep Date: 2/29/2012	Analysis Date: 3/1/2012	SeqNo: 34033	Units: %REC			
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual		
Surr: DNOP	8.6 10.00	86.2 77.4	131			
Sample ID LCS-891	SampType: LCS	TestCode: EPA Method	8015B: Diesel Range C	rganics		
Client ID: LCSS	Batch ID: 891	RunNo: 1195				
Prep Date: 2/29/2012	Analysis Date: 3/1/2012	SeqNo: 34034	Units: %REC			
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual		
Surr: DNOP	4.5 5.000	89.5 77.4	131			

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

Е Value above quantitation range

Analyte detected below quantitation limits

RPD outside accepted recovery limits

В Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit

Reporting Detection Limit

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202889

02-Mar-12

Client:

Blagg Engineering

Project:

Dryden 1M

Sample ID MB-871	SampType: MBLK			Tes	tCode: El	е				
Client ID: PBS	Batc	n ID: 87	1	F	RunNo: 1	184				
Prep Date: 2/28/2012	Analysis [)ate: 2 /	29/2012	9	SeqNo: 3	4142	Units: mg/F	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND	5.0								
Surr: BFB	1,100		1,000		110	69.7	121			
Sample ID LCS-871	Samp	ype: LC	s	Tes	tCode: El	PA Method	8015B: Gaso	line Rang	e	
Client ID: LCSS	Batc	n ID: 87	1	F	lunNo: 1	184				

Sample ID LCS-871	TestCode: EPA Method 8015B: Gasoline Range													
Client ID: LCSS	Batch	n ID: 87	1	F	RunNo: 1	184								
Prep Date: 2/28/2012	Analysis Date: 2/29/2012			S	SeqNo: 3	4147	Units: mg/Kg							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Gasoline Range Organics (GRO)	30	5.0	25.00	0	120	98.5	133							
Surr: BFB	1,200		1,000		119	69.7	121							

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

R RPD outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

RL Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202889

02-Mar-12

Client:

Blagg Engineering

Project:

Dryden 1M

Sample ID MB-871 SampType: MBLK				TestCode: EPA Method 8021B: Volatiles											
Client ID: PBS	Batch	Batch ID: 871			RunNo: 1	184		•							
Prep Date: 2/28/2012	Analysis Date: 2/29/2012			S	SeqNo: 3	4176	Units: mg/M								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Benzene	ND	0.050													
Toluene	ND	0.050													
Ethylbenzene	ND	0.050													
Xylenes, Total	ND	0.10													
Surr: 4-Bromofluorobenzene	1.2		1.000		116	85.3	139								

Sample ID LCS-871	Samn ⁻	Type: LC	:s	TestCode: EPA Method 8021B; Volatiles											
1	•	· ·													
Client ID: LCSS	Batc	h ID: 87	1	ŀ	RunNo: 1	184									
Prep Date: 2/28/2012	Analysis Date: 2/29/2012			5	SeqNo: 3	4180	Units: mg/F	(g							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Benzene	1.0	0.050	1.000	0	100	83.3	107								
Toluene	0.98	0.050	1.000	0	98.2	74.3	115								
Ethylbenzene	1.0	0.050	1.000	0	104	80.9	122								
Xylenes, Total	3.2	0.10	3.000	0	107	85.2	123								
Surr: 4-Bromofluorobenzene	1.2		1.000		120	85.3	139								

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

R RPD outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

RL Reporting Detection Limit

Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuanerane, NM 87105

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Albuquerque. NM 87105 Sample Log-In Check List

Client Name:	BLAGG		ork Order Number: 1202889											
Received by/date:	May 2/21	3/12					•							
Logged By:	Michelle Garcia 2/28/2012 10:20:00 A						mi	helle Ganus						
Completed By:	Michelle Garcia	2/28/2012 10:	58:09 AM			•	mi	halle Garries						
Reviewed By:	maka /28	110						, -						
Chain of Custo		//2												
1. Were seals in	tact?		•	Yes		No		Not Present	v					
2. Is Chain of Cu	ustody complete?			Yes	v	No		Not Present						
3. How was the	sample delivered?			Cour	<u>ier</u>									
<u>Log In</u>														
4. Coolers are present? (see 19. for cooler specific information)					~	No		NA						
5. Was an attern	5. Was an attempt made to cool the samples?					No		NA						
6. Were all same	6. Were all samples received at a temperature of >0° C to 6.0°C					No		NA						
7. Sample(s) in	proper container(s)?	٠		Yes	~	No								
8. Sufficient san	8. Sufficient sample volume for indicated test(s)?					No								
9. Are samples ((except VOA and ONG)	properly preserved?		Yes	~	No								
10. Was preserva	tive added to bottles?			Yes		No	✓	NA						
11 VOA vials hav	ve zero headspace?			Yes		No		No VOA Vials	~					
	nple containers receive	d broken?		Yes		No	✓							
	ork match bottle labels? ancies on chain of custo			Yes	~	No		# of pre bottles of for pH:	served checked	I				
14. Are matrices	correctly identified on C	hain of Custody?		Yes	✓	No		•	{•	<2 or >1	12 unless	noted)		
15. Is it clear wha	t analyses were reques	ted?		Yes	V	No		A	djusted?	•				
	ng times able to be mel ustomer for authorizatio			Yes	~	No		Ch	ecked b	oy:				
Special Handli	ng (if applicable)													
17. Was client no	tified of all discrepancie	s with this order?		Yes		No		NA	~					
Person N	Notified:		Date:			en etc.mic	***************************************	Carlo Ca						
By Whor	n:	AND PROPERTY AND	Via:	eMai		Ph	one	Fax In	Person	W744 - 1, 21/201				
Regardir				NAME OF TAXABLE AND ADDRESS OF TAXABLE AND AD						26.45.44.44.44.				
Client Ins	structions:													
18. Additional rem	narks:													
19. Cooler Inform		1	. 1			1		1						
Cooler No	Temp © Condition 4.9 Good	Yes	INO∣ Se	al Dat	e		Signe	d By						

Chain-of-Custody Record				Turn-Around Time:					F H MALL ENVIRONMENTAL													
Client: BLAGG ENGINEERWG INC.				Standard □ Rush				HALL ENVIRONMENTAL ANALYSIS LABORATORY														
BP AMERICA			Project Name	9:			www.hallenvironmental.com															
Mailing	Address	DO	Box 87	DRYD	EN 1M	l																
				Project #:			· · · · · · · · · · · · · · · · · · ·	4901 Hawkins NE - Albuquerque, NM 87109														
			NM 97413	1				Tel. 505-345-3975 Fax 505-345-4107 Analysis Request														
email o		05-6	32-1199	Project Mana																		
	Package:			7	-			(8021)	only)	iese					20	3's						
Stan	_		☐ Level 4 (Full Validation)	J. T	SCAGG			(8)	Gas	g/SE					°04,	PCB'						
Accredi			<u> </u>	Sampler: J	T. R. N.			TMB 's	TPH (Gas	Ğ)					O ₂ ,F	/ 8082						
□ NELAP □ Other			Office -	Makes	E NO		Ħ		15B	18.1	4.	AH)		3,N	/ 8(€				Į,	
□ EDD	(Type)			Samplevijem	vei(al@ife: **)	4 9			BE	d 80	4 b	d 5	or P	tals	I,N	ides	7	.VO	DE			Į
	 			0	Preservative			+	+ MTBE	TPH Method 8015B (Gas/Diesel)	TPH (Method 418.1)	et	NA	Me	(F,C	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE			100
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	Н	AL No.		*	I Me	3	<u>∞</u>	D (P	₹A 8	Suc	1 Pe) BC	S) (77			14.
_				,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	,,,,,	168		втех	BTEX	T	ם		831	RCF	Anic	808	826	827(0	ŀ	·	۸ ت
2/23/17	1105	SOIL	95 BGT 5-Pt C6	402×1	cool		- I	X		X	Х								X	十	\top	T
	1100					 														十	_	十
				 		<u> </u>						-							\dashv	+	+	╁
							·	\vdash				\dashv							\dashv	\dashv	+	┿
		 		 			<u> </u>							-						\dashv	+	+
				<u> </u>		ļ					-						<u> </u>			_		\downarrow
	<u> </u>																			\dashv	\bot	\bot
																					\perp	\perp
						ļ																
		<u></u>																				
		<u> </u>																				
																				\Box		1
																						T
Date:	Time:	Relinquish	ed by:	Received by: Date Time				Ren	narks	3: <i>(</i>	580	→ }	PO	0	18	015			L			ш,
727/12	0928	1 4	11 15logg	Mistre	Wooler	3/27/1	0928	Remarks: GRO+ DRO an 9015 N 1535207														
Date:	Time:	Relinquish	ed by:	Received by: Date Time					SCH	Wi	LB	T	•									
27/12	11644/	Thru	stere! Jetes	MULLIPPOTURE 2/28/12/1000 JEFF PEACE																		
 _	f necessary	samples sub	mitted to Hall Environmental may be sub-	contracted to other a	paraditad laboratori	an Thin and		:1	. :024	A		-		*** *								



