 District 1 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 	State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-144 Revised June 6, 2013 For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
	Pit, Below-Grade Tank, or	
12385 Proposed Alterr	native Method Permit or Closure	Plan Application
45 - 08697 🖾 Closure Modifica	f a pit or proposed alternative method of a pit, below-grade tank, or proposed alterna ation to an existing permit/or registration plan only submitted for an existing permitted of	NOV 2 1 2014
Instructions: Please submit one	application (Form C-144) per individual pit, below	v-grade tank or alternative request
Please be advised that approval of this request does not r environment. Nor does approval relieve the operator of i	elieve the operator of liability should operations result	in pollution of surface water, ground water or the
I. Operator: BP America Production Company	OGRID #:	778
Address:200 Energy Court, Farmington, N		
Facility or well name:Archuleta Gas Com /		
API Number:3004508697	OCD Permit Number:	
U/L or Qtr/Qtr Section5	Township29N Range9W Co	ounty:San Juan
Center of Proposed Design: Latitude36.752	17 Longitude107.79787	NAD: 🔲 1927 🖾 1983
Surface Owner: 🗍 Federal 🗍 State 🛛 Private 🗌 7	Fribal Trust or Indian Allotment	
 2. Pit: Subsection F, G or J of 19.15.17.11 NMA Temporary: Drilling Workover Permanent Emergency Cavitation P& Lined Unlined Liner type: Thickness String-Reinforced Liner Seams: Welded Factory Other 	A 🗌 Multi-Well Fluid Management I mil 🔲 LLDPE 🗌 HDPE 🗌 PVC 🗌 C	
3.		· · · · · · · · · · · · · · · · · · ·
Below-grade tank: Subsection 1 of 19.15.17.1	1 NMAC Tank A	
Volume:95.0bbl Type of	of fluid:Produced water	
Tank Construction material:Steel		
Secondary containment with leak detection		
Visible sidewalls and liner Uisible sidewall		
Liner type: Thicknessmil	HDPE PVC Other	
 <u>Alternative Method</u>: Submittal of an exception request is required. Exce 	ptions must be submitted to the Santa Fe Environm	ental Bureau office for consideration of approval.

25

s. <u>Fencing</u> : Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school institution of the strange of the	l, hospital,
<i>institution or church)</i> Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	·
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
8.	
Variances and Exceptions:	
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. <i>Please check a box if one or more of the following is requested, if not leave blank:</i>	
Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC	
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acc	eptable source
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	
Conorol siting	
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.	Yes 🗌 No
- INM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	I NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.	│
NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes 🗌 No
 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	Yes No
Within an unstable area. (Does not apply to below grade tanks)	
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	Yes No
Society; Topographic map	☐ Yes ☐ No
 Within a 100-year floodplain. (Does not apply to below grade tanks) FEMA map 	
Below Grade Tanks	

Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).
 Topographic map; Visual inspection (certification) of the proposed site
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.
 NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site

Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)

Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)
- Topographic map; Visual inspection (certification) of the proposed site

Form C-144

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	🔲 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes 🗌 No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	TYes No
- Topographic map; Visual inspection (certification) of the proposed site	
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes 🗌 No
 Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	Yes 🗌 No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
^{10.} <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do	
 attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC 	
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	cuments are
 Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC 	.15.17.9 NMAC
 Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

^{12.} <u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.</i>	documents are			
 Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC 				
 Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan 				
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriaté requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan 				
 Industries of Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization 				
 Monitoring and Inspection Plan Erosion Control Plan 				
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC				
^{13.} <u>Proposed Closure</u> : 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.				
Type: 🗌 Drilling 🗌 Workover 🔲 Emergency 🗌 Cavitation 🔲 P&A 🔲 Permanent Pit 🔲 Below-grade Tank 🗍 Multi-well F	luid Management Pit			
 Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) 				
 On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial 				
Alternative Closure Method				
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC				
15. Siting Criteria (negarding on site closure methods arbs), 10.15.17.10.NMAC				
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.				
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA			
 Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA			
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA			
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No			
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗋 Yes 🗌 No			
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗍 No			
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No			
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance				
Form C-144 Oil Conservation Division Page 4 o	f 6			

 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 	
	🗌 Yes 🗌 No
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	Yes 🗌 No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes 🗌 No
Within a 100-year floodplain. - FEMA map	$\square Yes \square No$
 On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure play a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannow Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	.11 NMAC 15.17.11 NMAC
 Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed. 	ief.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) Image: Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Orall D. / Celly Approval Date: 12/11/ Title: Compliance Office OCD Permit Number:	12014
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Oracle Very Approval Date: 12/11 Title: Compliance Office OCD Permit Number: 19.	/27014
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 12/11/ Title: Configurate Office O	the closure report. complete this
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 12/11 Title: Conclusion Office Office Office OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not	the closure report.
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 12/11/ Title: Configurate Office O	complete this

Operator Closure Certification:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print): _____Jeff Peace_

Signature:

22.

Jeff Pare

Title: Field Environmental Coordinator

_____ Date: ___November 20, 2014_____

e-mail address: __peace.jeffrey@bp.com_

______ Telephone: ___(505) 326-9479______

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Archuleta Gas Com A 2</u> <u>API No. 3004508697</u> <u>Unit Letter I, Section 5, T29N, R9W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. **Notice is attached.**
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	60.6

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

> Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Groundwater beneath the BGT was also sampled, with BTEX below the limits. Sampling data is attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

1220 South St. Francis Dr. Santa Fe, NM 87505

Oil Conservation Division

Release Notification and Corrective Action

OPERATOR 🗌 Initial Report 🛛 Final Report	
Contact: Jeff Peace	Name of Company: BP
Telephone No.: 505-326-9479	Address: 200 Energy Court, Farmington, NM 87401
Facility Type: Natural gas well	Facility Name: Archuleta Gas Com A 2

Surface Owner: Private

Mineral Owner: Private

API No. 3004508697

LOCATION OF RELEASE

Unit Letter	Section	Township	Range	Feet from the	North/South Line	Feet from the	East/West Line	County: San Juan
Ι	5	29N	9W	1,850	South	1,060	East	-

Latitude___36.75217______

__ Longitude__-107.79787_____

NATURE OF RELEASE

Type of Release: none	Volume of Release: N/A	Volume R	ecovered: N/A
Source of Release: below grade tank – 95 bbl	Date and Hour of Occurrence: N/A	Date and H	Iour of Discovery: N/A
Was Immediate Notice Given?	If YES, To Whom?		
🗌 Yes 🔲 No 🛛 Not Required			
By Whom?	Date and Hour		
Was a Watercourse Reached?	If YES, Volume Impacting the Wa	tercourse.	
Yes X No			
If a Watercourse was Impacted, Describe Fully.*			
Describe Cause of Problem and Remedial Action Taken.* Sampling of the			
the BGT. Soil analysis resulted in TPH, BTEX and chlorides below stand	ards. Water beneath the BGT was al	so sampled, v	vith BTEX below the limits.
Analysis results are attached.			
Describe Area Affected and Cleanup Action Taken.* BGT was removed a	nd the area underneath the BGT was	sampled. Th	e area under the BGT was
backfilled and compacted and is still within the active well area.			
		1.1.	
I hereby certify that the information given above is true and complete to the regulations all operators are required to report and/or file certain release not			
public health or the environment. The acceptance of a C-141 report by the			
should their operations have failed to adequately investigate and remediate			
or the environment. In addition, NMOCD acceptance of a C-141 report do federal, state, or local laws and/or regulations.	bes not relieve the operator of respon	sibility for co	mpliance with any other
lederal, state, or local laws and/or regulations.	OIL CONSER		
Note D a	<u>OIL CONSER</u>	VATON I	
Signature: Signature:			
	Approved by Environmental Speciali	st:	
Printed Name: Jeff Peace			
Title: Field Environmental Coordinator	Approval Date: Expiration Date:		
E-mail Address: peace.jeffrey@bp.com	Conditions of Approval:		Attached
Date: November 20, 2014 Phone: 505-326-9479			
Date. November 20, 2014			

* Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG ENGINEERING, INC. API #:				
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER: PAGE #: 1 o	f _1_			
	SITE NAME: ARCHULETA GC A # 2 DATE STARTED: 10/1 29N RNG: 9W PM: NM CNTY: SJ ST: NM	16/14			
	O'E NE/SE LEASE TYPE: FEDERAL / STATE / FEE / INDIAN ENVIRONMENTAL STRIKE PROD. FORMATION: PC CONTRACTOR: MBF - B. SCHUMAN SPECIALIST(S): N	JV			
1) 95 BGT (DW/DB) 2) 3)	WELL HEAD (W.H.) GPS COORD.: 36.75185 X 107.79746 GL ELEV.: 5 GPS COORD.: 36.75217 X 107.79787 DISTANCE/BEARING FROM W.H.: 165.5', GPS COORD.: DISTANCE/BEARING FROM W.H.: 165.5',	, N46W			
SAMPLING DATA:	GPS COORD.:	OVM READING (ppm)			
2) SAMPLE ID: GW @ 5' (98	Solution Sample Date 10/16/14 Sample Time: 1150 Lab analysis: 300.0 (CI) 5)	NA NA			
4) SAMPLE ID:	SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS:				
SOIL DESCRIPTION: SOIL TYPE: SAND / SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER SOIL COLOR: MODERATE BROWN COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE / HIGHLY COHESIVE / HIGHLY COHESIVE / HIGHLY COHESIVE / COHESIVE / LOOSE / FIRM / DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC CONSISTENCY (NON COHESIVE / SLIGHTLY MOIST / MOIST / WET / SATURATED / SUPER SATURATED PLASTICITY (CLAYS): NON PLASTIC / COHESIVE / HIGHLY PLASTIC / COHESIVE / HIGHLY PLASTIC / COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD MOISTURE: DRY / SLIGHTLY MOIST / MOIST / WET / SATURATED / SUPER SATURATED ANY AREAS DISPLAYING WETNESS: YES / NO EXPLANATION - MOSCOLORATION/STAINING OBSERVED: YES NO EXPLANATION - BLACK CLAY NEAR GW INTERFACE (SWAMP) GRADE. SITE OBSERVATIONS: LOST INTEGRITY OF EQUIPMENT: YES NO EXPLANATION - EXPLANATION - APPARENT EVIDENCE OF A RELEASE OBSERVED AND/OR OCCURRED : YES NO EXPLANATION - EXPLANATION - APPARENT EVIDENCE OF A RELEASE OBSERVED AND/OR OCCURRED : YES NO EXPLANATION - LOW PROFILE ABOVE-GRADE TANK TO BE SET ATOP BGT POSITION.					
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <50' N		NA			
SITE SKETCH	BGT Located : off on site PLOT PLAN circle: attached OWN CALIB. READ. = <u>NA</u> ppr OWN CALIB. GAS = <u>NA</u> ppr OWN CALIB. GAS = <u>NA</u> ppr IME: <u>NA</u> arripm DATE: MISCELL. NOT WO: <u>N15509775</u> PO #: PK: <u>ZEVH01BGT2</u> PJ #: <u>Z2-006Q0</u> Permit date(s): <u>06/14/</u> OCD Appr. date(s): <u>07/18</u> Tank OVM = Organic Vapor Met	/10 /14			
	X - S.P.D. (SOIL) • S.P.D. (SOIL) • S.P.D. (WATER) N DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H. = TEST HOLE; ~ = APPROX; W.H. = WELL HEAD;	N) N			
	DW-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING WALL; NA - NOT Magnetic declination: 10 WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; DB - DOUBLE BOTTOM. Magnetic declination: 10 ONSITE: 10/16/14	<u> </u>			

٠



BP America Production Co.	Project Name:	Archuleta GC A #2	
PO Box 22024	Project Number:	03143-0424	Reported:
Tulsa OK, 74121-2024	Project Manager:	Jeff Blagg	20-Oct-14 14:55

Analyical Report for Samples

Client Sample ID	Lab Sample ID	Matrix	Sampled	Received	Container
4 PC- SW @ 2'-3' (95)	P410064-01A	Soil	10/16/14	10/16/14	Glass Jar, 4 oz.
GW @ 5' (95)	P410064-02A	Aqueous	10/16/14	10/16/14	Poly 500mL
	P410064-02B	Aqueous	10/16/14	10/16/14	Voa vial, 40mL, HCl
	P410064-02C	Aqueous	10/16/14	10/16/14	Voa vial, 40mL, HCl

5796 US Highway 64, Farmington, NM 87401	Ph (505) 632-0615 Fx (505) 632-1865	envirotech-inc.com
Three Springs • 65 Mercado Street, Suite 115, Durango, CO 81301	Ph (970) 259-0615 Fr (800) 362-1879	laboratory@envirotech-inc.com -



BP America Production Co. PO Box 22024 Tulsa OK, 74121-2024	Proje	ct Name: ct Number: ct Manager:	0314 Jeff	uleta GC A s 3-0424 Blagg	#2			Reported: 20-Oct-14 14	
		4 PC- S P4100	w @ 2'- 64-01 (Se						
Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
Volatile Organics by EPA 8021									
Benzene	ND	0.10	mg/kg	1	1442036	10/17/14	10/17/14	EPA 8021B	
Toluene	ND	0.10	mg/kg	1	1442036	10/17/14	10/17/14	EPA 8021B	
Ethylbenzene	ND	0.10	mg/kg	1	1442036	10/17/14	10/17/14	EPA 8021B	
p,m-Xylene	ND	0.20	mg/kg	1	1442036	10/17/14	10/17/14	EPA 8021B	
o-Xylene	ND	0.10	mg/kg	1	1442036	10/17/14	10/17/14	ÉPA 8021B	
Total Xylenes	ND	0.10	mg/kg	1	1442036	10/17/14	10/17/14	ÉPA 8021B	
Total BTEX	ND	0.10	mg/kg	1	1442036	10/17/14	10/17/14	EPA 8021B	
Surrogate: 4-Bromochlorobenzene-PID		98.6 %	50	-150	1442036	10/17/14	10/17/14	EPA 8021B	
Total Petroleum Hydrocarbons by 418.1									
Total Petroleum Hydrocarbons	ND	35.0	mg/kg	1	1442042	10/17/14	10/17/14	EPA 418.1	
Cation/Anion Analysis						_			
Chloride	60.6	9.92	mg/kg	I	1442037	10/17/14	10/17/14	EPA 300.0	



BP America Production Co. PO Box 22024 Tulsa OK, 74121-2024	Project	Name: Number: Manager:	0314	nuleta GC A 13-0424 Blagg	#2			Reported: 20-Oct-14 14	
		GW	' @ 5' (9	95)					
		P41000	64-02 (W	ater)					
Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
Volatile Organics by EPA 8021									
Benzene	ND	0.001	mg/L	1	1442038	10/17/14	10/17/14	EPA 8021B	
Toluene	ND	0.001	nıg/L	1	1442038	10/17/14	10/17/14	EPA 8021B	
Ethylbenzene	ND	0.001	mg/L	1	1442038	10/17/14	10/17/14	EPA 8021B	
p,m-Xylene	ND	0.002	mg/L	1	1442038	10/17/14	10/17/14	EPA 8021B	
o-Xylene	ND	0.001	mg/L	1	1442038	10/17/14	10/17/14	EPA 8021B	
Total Xylenes	ND	0.001	mg/L	I	1442038	10/17/14	10/17/14	EPA 8021B	
Total BTEX	ND	0.001	mg/L	1	1442038	10/17/14	10/17/14	EPA 8021B	
Surrogate: 4-Bromochlorobenzene-P1D		105 %	50	-150	1442038	10/17/14	10/17/14	EPA 8021B	
Cation/Anion Analysis									
Chloride	38.4	2.00	mg/L	2	1442041	10/17/14	10/17/14	EPA 300.0	

5796 US Highway 64, Farmington, NM 87401	Ph (505) 632-0615	Fx (505) 632-1865	envirotech-inc.com
Three Springs • 65 Mercado Street, Suite 115, Durango, CO 81301	Ph (970) 259-0615	Fr (800) 362-1879	laboratory@envirotech-inc.com



BP America Production Co.	Project Name:	Archuleta GC A #2	
PO Box 22024	Project Number:	03143-0424	Reported:
Tulsa OK., 74121-2024	Project Manager:	Jeff Blagg	20-Oct-14 14:55

Volatile Organics by EPA 8021 - Quality Control

Envirotech Analytical Laboratory

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch 1442036 - Purge and Trap EPA 5030A										
Blank (1442036-BLK1)				Prepared &	Analyzed	17-Oct-14				
Benzene	ND	0.10	mg/kg							
Toluene	ND	0.10	н							
Ethylbenzene	ND	0.10	u							
p,m-Xylene	ND	0.20	н							
o-Xylene	ND	0.10	5							
Total Xylenes	ND	0.10								
Total BTEX	ND	0.10	н							
Surrogate: 4-Bromochlorobenzene-PID	0.387		"	0.399		96.9	50-150			
LCS (1442036-BS1)				Prepared &	Analyzed:	17-Oct-14				
Benzene	20.8	0.10	mg/kg	20.0		104	75-125			
Foluene	19.7	0.10		20.0		98.8	70-125			
Ethylbenzene	19.5	0.10	11	20.0		97.3	75-125			
o,m-Xylene	38.6	0.20	11	40.0		96.5	80-125			
p-Xylene	19.0	0.10	"	20.0		95.1	75-125			
Surrogate: 4-Bromochlorobenzene-PID	0.408		"	0.400		102	50-150			
Matrix Spike (1442036-MS1)	Sou	rce: P410064-	-01	Prepared &	Analyzed:	17-Oct-14				
Benzene	19.2	0.10	mg/kg	19.9	ND	96.4	75-125			
Foluene	19.3	0.10	n	19.9	ND	97.0	70-125			
Ethylbenzene	19.5	0.10	"	19.9	ND	97.9	75~125			
p,m-Xylene	39.5	0.20	0	39.9	ND	99.0	80-125			
p-Xylene	19.6	0.10	0	19.9	ND	98.2	75-125			
Surrogate: 4-Bromochlorobenzene-PID	0.407		"	0.399		102	50-150			
Matrix Spike Dup (1442036-MSD1)	Sou	rce: P410064-	01	Prepared &	Analyzed	17-Oct-14				
Benzene	19.3	0.10	mg/kg	20.0	ND	96.7	75-125	0.431	15	
Foluene	19.5	0.10	•	20.0	ND	97.9	70-125	1.03	15	
Ethylbenzene	19.6	0.10	"	20.0	ND	98.2	75-125	0.393	15	
o,m-Xylene	39.7	0.20		39.9	ND	99.4	80-125	0.472	15	
p-Xylene	19.7	0.10		20.0	ND	98.7	75-125	0.665	15	
Surrogate: 4-Bromochlorobenzene-P1D	0.408		"	0.399		102	50-150			

5796 US Highway 64, Farmington, NM 87401	Ph (505) 632-0615 Fx (505) 632-1865	envirotech=inc.com
Three Springs • 65 Mercado Street, Suite 115, Durango, CO 81301	Ph (970) 259-0615 Fr (800) 362-1879	laboratory@envirotech-inc.com



	BP America Production Co.	Project Name:	Archuleta GC A #2	
l	PO Box 22024	Project Number:	03143-0424	Reported:
	Tulsa OK, 74121-2024	Project Manager:	Jeff Blagg	20-Oct-14 14:55

Volatile Organics by EPA 8021 - Quality Control

Envirotech Analytical Laboratory

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch 1442038 - Purge and Trap EPA 5030A										
Blank (1442038-BLK1)				Prepared &	Analyzed:	17-Oct-14				
Benzene	ND	0.001	mg/L							
Foluene	ND	0.001	н							
Ethylbenzene	ND	0.001	"							
o,m-Xylene	ND	0.002	18							
p-Xylene	ND	0.001	п							
Fotal Xylenes	ND	0.001	11							
Fotal BTEX	ND	0.001	"							
urrogate: 4-Bromochlorobenzene-P1D	0.210	-	"	0.200		105	50-150			
LCS (1442038-BS1)				Prepared &	Analyzed:	17-Oct-14				
Benzene	0.21	0.001	mg/L	0.200		104	80-120	_		
oluene	0.21	0.001	**	0.200		104	75-120			
Ethylbenzene	0.21	0.001	н	0.200		105	75-125			
n,m-Xylene	0.43	0.002	н	0.400		106	75-130			
o-Xylene	0.21	0.001	"	0.200		105	80-120			
Surrogate: 4-Bromochlorobenzene-PID	0.214		"	0.200		107	50-150			
Matrix Spike (1442038-MS1)	Sou	rce: P410046-	01	Prepared &	Analyzed:	20-Oct-14				
Benzene	0.19	0.001	mg/L	0.200		95.9	80-120			
Toluene	0.19	0.001		0.200		96.9	75-120			
Ethylbenzene	0.20	0.001	"	0.200		97.8	75-125			
o,m-Xylene	0.40	0.002	"	0.400		99. I	75-130			
o-Xylene	0.20	0.001	"	0.200		97.6	80-120			
Surrogate: 4-Bromochlorobenzene-PID	0.181		"	0.200		90.6	50-150			
Matrix Spike Dup (1442038-MSD1)	Sou	rce: P410046-	01	Prepared &	Analyzed:	20-Oct-14				
Benzene	0.20	0.001	mg/L	0.200		99.5	80-120	3.63	15	
oluene	0.20	0.001	н	0.200		101	75-120	3.81	15	
Ethylbenzene	0.20	0.001	н	0.200		101	75-125	3.46	15	
,m-Xylene	0.41	0.002	u	0.400		103	75-130	3.58	15	
p-Xylene	0.20	0.001		0.200		101	80-120	3.89	15	
Surrogate: 4-Bromochlorobenzene-PID	0.189		"	0.200		94.4	50-150			

5796 US Highway 64, Farmington, NM 87401	Ph (505) 632-0615 Fx (505) 632-1865	envirotech-inc.com
Three Springs • 65 Mercado Street, Suite 115, Durango, CO 81301	Ph (970) 259-0615 Fr (800) 362-1879	laboratory@envirotech-inc.com -



BP America Production Co.	Project Name:	Archuleta GC A #2	
PO Box 22024	Project Number:	03143-0424	Reported:
Tulsa OK, 74121-2024	Project Manager:	Jeff Blagg	20-Oct-14 14:55

Total Petroleum Hydrocarbons by 418.1 - Quality Control

Envirotech	Analytical	Laboratory
------------	------------	------------

Analyte	Result	Reporting Limit	Units	Spike	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
	Kesun	Lunit	Units	Level	Result	%KEC	Linnts	KPD		INDIES
Batch 1442042 - 418 Freen Extraction										
Blank (1442042-BLK1)				Prepared &	Analyzed:	17-Oct-14				
Total Petroleum Hydrocarbons	ND	35.0	mg/kg							
Duplicate (1442042-DUP1)	Sourc	e: P410064-	01	Prepared &	Analyzed:	17-Oct-14				
Total Petroleum Hydrocarbons	ND	35.0	mg/kg		ND				30	
Matrix Spike (1442042-MS1)	Sourc	e: P410064-	01	Prepared &	Analyzed:	17-Oct-14				
Total Petroleum Hydrocarbons	1890	34.9	mg/kg	2020	ND	93.9	80-120			

5796 US Highway 64, Farmington, NM 87401	Ph (505) 632-0615 Fx (505) 632-1865	envirotech-inc.com
Three Springs • 65 Mercado Street, Suite 115, Durango, CO 81301	Ph (970) 259-0615 Fr (800) 362-1879	laboratory@envirotech-inc.com



BP America Production Co.	Project Name:	Archuleta GC A #2	
PO Box 22024	Project Number:	03143-0424	Reported:
Tulsa OK, 74121-2024	Project Manager:	Jeff Blagg	20-Oct-14 14:55

Cation/Anion Analysis - Quality Control

Envirotech Analytical Laboratory

		Reporting		Spike	Source		%REC		RPD	
Analyte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch 1442037 - Anion Extraction EPA 300.0										
Blank (1442037-BLK1)				Prepared &	Analyzed:	17-Oct-14				
Chloride	ND	9.96	mg/kg							
LCS (1442037-BS1)				Prepared &	Analyzed:	17-Oct-14				
Chloride	494	9.96	mg/kg	498		99.2	90-110			
Matrix Spike (1442037-MS1)	Sou	·ce: P410065-	01	Prepared &	Analyzed:	17-Oct-14				
Chloride	491	9.91	mg/kg	496	ND	99.2	80-120			
Matrix Spike Dup (1442037-MSD1)	Sour	·ce: P410065-	01	Prepared &	Analyzed:	17-Oct-14				
Chloride	489	9.86	mg/kg	493	ND	99.3	80-120	0.383	20	

5796 US Highway 64, Farmington, NM 87401	Ph (505) 632-0615 Fx (505) 632-1865	envirotech-inc.com
Three Springs • 65 Mercado Street, Suite 115, Durango, CO 81301	Ph (970) 259-0615 Fr (800) 362-1879	laboratory@envirotech-inc.com -



BP America Production Co.	Proje	ect Name:	А	rchuleta GC .	A #2					
PO Box 22024	Proje	ect Number:	. 0	3143-0424					Report	ted:
Tulsa OK, 74121-2024	Proje	ect Manager:	Je	eff Blagg					20-Oct-14	14:55
	Catio	on/Anion A	nalysis	- Quality	Control					
	En	virotech A	Analyti	cal Labor	atory					
		Reporting		Spike	Source		%REC		RPD	
Analyte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch 1442041 - Anion Extraction EPA 3 Blank (1442041-BLK1)	00.0			Prepared &	 z Analyzed:	17-Oct-14				
Chłoride	ND	1.00	mg/L	·						
LCS (1442041-BS1)				Prepared &	Analyzed:	17-Oct-14				
Chloride	49.0	1.00	mg/L	50.0		98.0	90-110			
Matrix Spike (1442041-MS1)	Sour	ce: P410064-	02	Prepared &	Analyzed:	17-Oct-14	-			
Chloride	133	2.00	mg/L	100	38.4	94.9	80-120			
Matrix Spike Dup (1442041-MSD1)	Sour	ce: P410064-	02	Prepared &	Analyzed:	17-Oct-14	_			
Chloride	135	2.00	mg/L,	100	38.4	96.5	80-120	1.23	20	

5796 US Highway 64, Farmington, NM 87401	Ph (505) 632-0615 Fx (505) 632-1865	envirotech-inc.com
Three Springs • 65 Mercado Street, Suite 115, Durango, CO 81301	Ph (970) 259-0615 Fr (800) 362-1879	laboratory@envirotech-inc.com -



BP America Production Co.	Project Name:	Archuleta GC A #2	
PO Box 22024	Project Number:	03143-0424	Reported:
Tulsa OK, 74121-2024	Project Manager:	Jeff Blagg	20-Oct-14 14:55

Notes and Definitions

DET	Analyte DETECTED
ND	Analyte NOT DETECTED at or above the reporting limit
NR	Not Reported

dry Sample results reported on a dry weight basis

RPD Relative Percent Difference

5796 US Highway 64, Farmington, NM 87401	Ph (505) 632-0615 Fx (505) 632-1865	envirotech-inc.com
Three Springs • 65 Mercado Street, Suite 115, Durango, CO 81301	Ph (970) 259-0615 Fr (800) 362-1879	laboratory@envirotech-inc.com

CHAIN OF CUSTODY RECORD

Project Name / Location: Client: BP AMERICA **ANALYSIS / PARAMETERS** ARCHULETA GE A # 2 Email results to JEFEC BLACE @ AOL. COM PEACE, JEFFREY @ BP. COM NELSO DVELEZ 4519 @ MSN. COM Sampler Name: BTEX (Method 8021) VOC (Method 8260) TPH (Method 8015) FLET NELSON RCRA 8 Metals CO Table 910-1 TCLP with H/P Cation / Anion Client Phone No. 305. 320. 3489 Client No.: Sample Intact TPH (418.1) Sample Cool CHLORIDE 03143-0424 Preservative Sample Sample No./Volume Š Sample No./ Identification Lab No. of Containers Date Time HNO2 HCI 4PC-SWCZ-3 (95) 10/16/14 P410064-01 1- 402 1210 P410064-02 2 - 40x1 GW @ 5'(95) 19/16/14 1155 10/18/14 EN C5' (95) 1 - 500m115.51 AJAP 4.54 418.1 100 749 Ka TRA ≻ 8015 THE KUN Received by: (Signature) Date Time Date Relinquished by: (Signature)-Time .1400 1400 i6 10 Received by: (Signature) Relinquished by: (Signature) 19/6/14 1606 10/10/14/1006 DIRECTLY CONTROL TEFF PERCE Sample Matrix Soil 🗙 Solid 🗋 Sludge 🗋 Aqueous 😾 Other 🗋 PRYKEY: ZEVHO IBETZ WORK ORDER #: NISS69775 Sample(s) dropped off after hours to secure drop off area. envirotech 15.21 15.7 Analytical Laboratory 5.6 5795 US Highway 64 • Farmington, NM 87401 • 505-632-0615 • Three Springs • 65 Mercado Street, Suite 115, Durango, CO 81301 • laboratory@envirotech-ind

17448

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

August 6, 2014

Leo Pacheco PO Box 777 Bloomfield, NM 87413

VIA CERTIFIED MAIL – RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: ARCHULETA GC A 002

Dear Mr. Pacheco,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about August 21, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper Surface Land Negotiator BP America Production Company

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

October 17, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

ARCHULETA GC A 002 API 30-045-08697 (1) Section 5 – T29N – R09W San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around October 21, 2014.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

R Peace

Jeff Peace BP Field Environmental Advisor

(505) 326-9479



