District 1 1625 N. French Dr., Hobbs, NM 88240 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Form C-144

Revised June 6, 2013

1220 South St. Francis Dr. Santa Fe, NM 87505 to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
12388 Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration OIL CONS. DIV DIST. 3
Permit of a pit or proposed alternative method 15-08755
Modification to an existing permit/or registration NOV 2 1 2014
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
I.
Operator: BP America Production Company OGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Jaquez Gas Com A 1
API Number:3004508755OCD Permit Number:
U/L or Qtr/QtrGSection5Township29NRange9WCounty:San Juan
Center of Proposed Design: Latitude36.75636 Longitude107.79990 NAD: □1927 ⋈ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: ☐ Drilling ☐ Workover ☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Single walled/Double bottomed; side walls not visible
Liner type: Thickness mil
4. Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital, .
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	:
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application.Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
 initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.	
and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents of the standard of the standar	cuments are
attached. □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC □ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	.15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Form C-144 Oil Conservation Division Page 3 of 6

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
 ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan 	
 □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Nuisance or Hazardous Odors, including H₂S, Prevention Plan □ Emergency Response Plan □ ONE AND CONTROLLED 	
☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan	
☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal	luid Management Pit
☐ Waste Removal (Closed-loop systems only) ☐ On-site Closure Method (Only for temporary pits and closed-loop systems) ☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	attached to the
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	- 20 🗀 110

- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	□ Vas □ Na
Within a 100-year floodplain FEMA map	☐ Yes ☐ No☐ Yes ☐ No
16. On Site Cleaner Plan Checklists (10.15.17.12.) MACO Languagian Ford CH. CH. C. H. C. H	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 12/11/2 Title: OCD Permit Number:	રવ4
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:10/10/2014_	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	complete this

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirem	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Joff Paoce	Date:November 20, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>API No. 3004508755</u> Unit Letter G, Section 5, T29N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15,17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)
 - All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	100
Chlorides	US EPA Method 300.0 or 4500B	250 or background	170

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. TPH was 100 ppm by Method 418.1 but was only 20 ppm by Method 8015D. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

* Attach Additional Sheets If Necessary

State of New Mexico Energy Minerals and Natural Resources

Form C-141

Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notifi	catior	and Co	orrective A	ction				
						OPERA	ГOR		Initia	al Report	\boxtimes	Final Report
Name of Co			for all			Contact: Jef	f Peace					
		Court, Farm		M 87401			No.: 505-326 - 94					
Facility Nat	ne: Jaquez	z Gas Com A	. 1			Facility Type: Natural gas well						
Surface Ow	ner: Priva	te .		Mineral (Owner: 1	Private			API No	. 3004508′	755	
				LOCA	ATIO	OF REI	LEASE					
Unit Letter G	Section 5	Township 29N	Range 9W	Feet from the 1,650		South Line	Feet from the 1,650	East/We East	st Line	County: S	an Juan	1
		Lati	tude36	5.75636		Longitude	107.79990_					
				NAT	TURE	OF RELI						
Type of Rele							Release: N/A			Recovered: N		
Source of Release: below grade tank – 95 bbl, Tank A						Date and H N/A	our of Occurrenc	e: D	Date and	Hour of Dis	covery:	: N/A
Was Immedia	ate Notice (Yes 🗀	No 🛛 Not R	equired	If YES, To	Whom?	'				
By Whom?						Date and H	our					
Was a Watercourse Reached? ☐ Yes ☒ No						If YES, Vo	lume Impacting t	he Waterco	ourse.			
If a Watercou	ree was Im	pacted, Descri	he Fully *									
Describe Cau	se of Probl	em and Remed	lial Action	n Taken.* Sampli			the BGT was dor as 100 ppm by M					
8015D. Anal	ysis results	are attached.										
				en.* BGT was re ctive well area.	moved a	nd the area u	nderneath the BG	T was sam	pled. Th	ne area unde	r the B	GT was
backimed and	л сотрасте	u anu 18 stiii w	iumi uie a	ettive well alea.								
regulations al public health should their o or the environ	I operators or the envi- perations h nment. In a	are required to ronment. The ave failed to a	report an acceptanc dequately CD accep	d/or file certain r e of a C-141 repo investigate and r	elease no ort by the emediate	tifications ar NMOCD ma contamination	knowledge and und perform corrector as "Final Reform that pose a three the operator of r	tive action eport" does eat to grou- responsibil	s for rele s not reli nd water lity for co	eases which eve the oper , surface wa ompliance w	may en ator of ter, hur ith any	ndanger Tliability man health
	1 00	0					OIL CONS	SERVA	TION	DIVISIO	N	
Signature:	VIII 1	Pesco										
Printed Name	: Jeff Peace	e			A	Approved by	Environmental Sp	pecialist:				
Title: Field E	nvironment	tal Coordinato	*		1	Approval Dat	e;	Exp	piration I	Date:		
E-mail Addre	ss: peace.je	effrey@bp.com	1		(Conditions of	Approval:			Attached		
Date: Novem	ber 20-20	14	Pho	me: 505-326-947	a							

CLIENT: BP	P.O. BOX 87,	ENGINEERI BLOOMFIEI 505) 632-119	_D, NM		API #: 300 TANK ID (if applicble):	04508755 A & D
FIELD REPORT:	(circle one): BGT CONFIRMATIO			ER:		1 of 1
SITE INFORMATION				A18.8	DATE STARTED:	10/08/14
QUAD/UNIT: G SEC: 5 TWP: 1/4-1/4/F00TAGE: 1,650'N / 1,6			Y: SJ	ST: NM	DATE FINISHED:	
	PROD. FORMATION: MV	C.	TDIVE		ENVIRONMENTAL SPECIALIST(S):	NJV
REFERENCE POINT	- WELL HEAD (W.H.) (SPS COORD.:	36.75665			
1) 95 BGT (SW/DB) - A					RING FROM W.H.:	
2) -21 BGT (SW/DB) - B	GPS COORD.:	36.75616 X 107	.80000	DISTANCE/BEA	RING FROM W.H.:	167.5', S11E
3)						
	GPS COORD.:			DISTANCE/BEA	RING FROM W.H.:	OVM
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S)					READING (ppm)
1) SAMPLE ID: 5PC-TB@5'(9	•					
2) SAMPLE ID:						
SAMPLE ID: SAMPLE ID:						
SOIL DESCRIPTION	· · · · · · · · · · · · · · · · · · ·					
CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY SLIGHTLY MOIST MOIST / W SAMPLE TYPE: GRAB COMPOSITE - # DISCOLORATION/STAINING OBSERVED: YES N SITE OBSERVATION APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: [OTHER: 95 BGT FALSE BOTTOM LOST IN	T / SATURATED / SUPER SATURATED OF PTS O EXPLANATION - LOST INTEGRITY OF EQUIPMI D AND/OR OCCURRED : YES NO E YES NO EXPLANATION - LOW	ANY AREAS DISPLAY ENT: YES NO EXPLANA XPLANATION: PROFILE ABOVE-GR	TING WETNESS:	YES NO EXPLA		
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA	ft. X NA	ft. I	EXCAVATION EST	IMATION (Cubic Ya	irds): NA
	EAREST WATER SOURCE: >1,0				D TPH CLOSURE STE	
SITE SKETCH	BGT Located: off on	site PLOT PL	AN circle:	attached 0VM	CALIB. READ. = N	A ppm RF =0.52
_	TO SOUND W		\			A ppm RF =0.52
	W.H. COMPRESSOR		X			DATE: NA
	()	95) IGTL		· '\ =	MISCELL.	NOTES
	T.B	. ~ 5'		SECURITY W	o: N15488	997
	SEPARATOR		7	PERIMETER P	O <u>#:</u>	
	OEI AIVAI OIV	$\bigcup L(x\hat{x}x)$		-	k: ZEVH01	
		\longrightarrow	*		J#: Z2-0060 ermit date(s):	06/14/10
		BER	M		CD Appr. date(s):	05/10/11
		DEN		Tar IC	k OVM = Organic	c Vapor Meter
			1	Δ	BGT Sidewalls Vis	ible: Y /N
				- S.P.D.		
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL					BGT Sidewalls Vis	
APPLICABLE OR NOT AVAILABLE; SW-SINGLE			OM.		lagnetic declinat	ion; iu <u>e</u>
NOTES:		ONSITE	10/08/	14		

Analytical Report

Lab Order 1410437

Date Reported: 10/10/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering **Project:** Jaquez GC A #1

Client Sample ID: 5PC - TB @ 5' (95) - A Collection Date: 10/8/2014 9:40:00 AM

Lab ID: 1410437-001

Matrix: MEOH (SOIL)

Received Date: 10/9/2014 7:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGE	ORGANICS				Analyst	: JME
Diesel Range Organics (DRO)	20	10	mg/Kg	1	10/9/2014 12:11:15 PM	1 15814
Surr: DNOP	86.9	57.9-140	%REC	1	10/9/2014 12:11:15 PM	1 15814
EPA METHOD 8015D: GASOLINE RAN	GE				Analyst	: NSB
Gasoline Range Organics (GRO)	ND	4.2	mg/Kg	1	10/9/2014 11:21:19 AM	R21782
Surr: BFB	90.1	80-120	%REC	1	10/9/2014 11:21:19 AM	R21782
EPA METHOD 8021B: VOLATILES					Analyst	: NSB
Benzene	ND	0.042	mg/Kg	1	10/9/2014 11:21:19 AM	R21782
Toluene	ND	0.042	mg/Kg	1	10/9/2014 11:21:19 AM	R21782
Ethylbenzene	ND	0.042	mg/Kg	1	10/9/2014 11:21:19 AM	R21782
Xylenes, Total	ND	0.085	mg/Kg	1	10/9/2014 11:21:19 AM	R21782
Surr: 4-Bromofluorobenzene	91.3	80-120	%REC	1	10/9/2014 11:21:19 AM	R21782
EPA METHOD 300.0: ANIONS					Analyst	: LGP
Chloride	170	30	mg/Kg	20	10/9/2014 11:24:59 AM	15819
EPA METHOD 418.1: TPH					Analyst	: JME
Petroleum Hydrocarbons, TR	100	20	mg/Kg	1	10/9/2014 12:00:00 PM	15787

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 7

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1410437

10-Oct-14

Client:

Blagg Engineering

Project:

Jaquez GC A #1

Sample ID MB-15819

SampType: MBLK

TestCode: EPA Method 300.0: Anions

LowLimit

Client ID:

PBS

Batch ID: 15819

RunNo: 21796

Prep Date: 10/9/2014 Analysis Date: 10/9/2014

SeqNo: 640524

Units: mg/Kg

Result PQL

%REC

HighLimit

RPDLimit

Qual

Analyte Chloride

ND 1.5

Sample iD LCS-15819

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID:

LCSS

Batch ID: 15819

RunNo: 21796

LowLimit

Units: mg/Kg

Prep Date: 10/9/2014 Analysis Date: 10/9/2014

SeqNo: 640525 %REC

Analyte

Result **PQL**

SPK value SPK Ref Val

0

90.5

Qual

110

%RPD HighLimit

%RPD

Chloride

15.00

14

1.5

SPK value SPK Ref Val

90

RPDLimit

Qualifiers:

S

Value exceeds Maximum Contaminant Level.

Spike Recovery outside accepted recovery limits

Value above quantitation range Е

Analyte detected below quantitation limits

RSD is greater than RSDlimit O

RPD outside accepted recovery limits R

RL

Analyte detected in the associated Method Blank Holding times for preparation or analysis exceeded Н

ND

Reporting Detection Limit

Sample pH greater than 2.

Not Detected at the Reporting Limit Page 3 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#:

1410437

10-Oct-14

Client:

Blagg Engineering

Project:

Jaquez GC A #1

Sample ID MB-15787

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID: PBS

Batch ID: 15787

RunNo: 21766

Analysis Date: 10/9/2014

SeqNo: 639405

Units: mg/Kg

HighLimit

%RPD

%RPD

RPDLimit Qual

Analyte Petroleum Hydrocarbons, TR

Prep Date:

Result **PQL**

ND 20

SampType: LCS

TestCode: EPA Method 418.1: TPH

Client ID: LCSS

Sample ID LCS-15787

Batch ID: 15787

RunNo: 21766

SPK value SPK Ref Val

SPK value SPK Ref Val %REC LowLimit

Prep Date: 10/8/2014

10/8/2014

Analysis Date: 10/9/2014

SeqNo: 639406 %REC

Units: mg/Kg

RPDLimit Qual

Analyte Petroleum Hydrocarbons, TR

Result **PQL** 120 20

100.0

TestCode: EPA Method 418.1: TPH

LowLimit

HighLimit 120

Qual

Sample ID LCSD-15787

Client ID: LCSS02

SampType: LCSD Batch ID: 15787

RunNo: 21766

Units: mg/Kg

Analyte

Prep Date: 10/8/2014 Analysis Date: 10/9/2014

110

SPK value SPK Ref Val

%REC

LowLimit

HighLimit

%RPD **RPDLimit**

Petroleum Hydrocarbons, TR

Result 20

100.0

0

112

SeqNo: 639407

80

120

6.37

20

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Е Value above quantitation range
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- S Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank В
- Holding times for preparation or analysis exceeded Н
- Sample pH greater than 2.

ND

- Reporting Detection Limit
- Not Detected at the Reporting Limit Page 4 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#:

1410437

10-Oct-14

Client:

Blagg Engineering

Project:

Jaquez GC A #1

Sample ID MB-15814	Samp	Гуре: МЕ	BLK	TestCode: EPA Method 8015D: Diesel Range Organics						
Client ID: PBS	Batcl	h ID: 15	D: 15814 RunNo: 21764							
Prep Date: 10/9/2014	Analysis [Date: 10	0/9/2014	SeqNo: 639341			Units: mg/F			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Surr: DNOP	9.5		10.00		95.5	57.9	140			

Sample ID LCS-15814	SampT	ype: LC	s	Test	TestCode: EPA Method 8015D: Diesel Range Organics					
Client ID: LCSS	Batch ID: 15814 RunNo: 21764									
Prep Date: 10/9/2014	10/9/2014 Analysis Date: 10/9/2014					39456	Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	63	10	50.00	0	126	68.6	130			
Surr: DNOP	3.9		5.000		77.1	57.9	140			

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 5 of 7

Hall Environmental Analysis Laboratory, Inc.

970

1000

WO#:

1410437

10-Oct-14

Client:

Blagg Engineering

Project:

Jaquez GC A #1

Project: Jaquez C	JC A #1										
Sample ID MB-15760 MK	SampType: MBLK TestCode: EPA Method					8015D: Gase	oline Rang	e			
Client ID: PBS	Batch ID: R	21782	F	RunNo: 2							
Prep Date:	Analysis Date: 1	S	SeqNo: 6	40373	Units: mg/Kg						
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Gasoline Range Organics (GRO)	ND 5.0										
Surr: BFB	880	1000		87.7	80	120					
Sample ID LCS-15760 MK	SampType: LCS TestCode: EPA Method 8015D: Gasoline Range										
Client ID: LCSS	Batch ID: R	21782	R	lunNo: 2	1782						
Prep Date:	Analysis Date: 1	SeqNo: 640374			Units: mg/k						
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Gasoline Range Organics (GRO)	26 5.0	25.00	0	103	65.8	139					
Surr: BFB	970	1000		96.9	80	120					
Sample ID MB-15760	SampType: MBLK TestCode: EPA Method 8015D: Gasoline Range										
Client ID: PBS	Batch iD: 15760 RunNo: 21782				1782						
Prep Date: 10/8/2014	Analysis Date: 1	0/9/2014	SeqNo: 640380			Units: %RE	C				
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Surr: BFB	880	1000		87.7	80	120	-				
Sample ID LCS-15760	SampType: LCS TestCode: EPA Method 8015D: Gasoline Range										
Client ID: LCSS	Batch ID: 15	Batch ID: 15760 RunNo: 21782									
Prep Date: 10/8/2014	Analysis Date: 1	0/9/2014	S	eqNo: 6	40381	Units: %RE	С				
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		

Qualifiers:

Analyte Surr: BFB

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range Е
- J Analyte detected below quantitation limits
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- Not Detected at the Reporting Limit ND

96.9

80

120

- Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 7

Hall Environmental Analysis Laboratory, Inc.

WO#: 1410437

10-Oct-14

Client:

Blagg Engineering

Project:

Jaquez GC A #1

Sample ID MB-15760 MK	SampT	ype: ME	3LK	Tes											
Client ID: PBS	Batch ID: R21782 RunNo: 21782					1782									
Prep Date:	Analysis D	ate: 10)/9/2014	SeqNo: 640422			Units: mg/Kg								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Benzene	ND	0.050		-											
Toluene	ND	0.050													
Ethylbenzene	ND	0.050													
Xylenes, Total	ND	0.10													
Surr: 4-Bromofluorobenzene	0.91		1.000		90.7	80	120								
Sample ID LCS-15760 MK	SampT	ype: LC	:S	Tes	PA Method	8021B: Volat	tiles								
Client ID: LCSS	Batch	Batch ID: R21782 RunNo: 21782													
Prep Date:	Analysis Da	Date: 10/9/2014 SeqNo: 640423					Units: mg/K	(g							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Benzene	0.97	0.050	1.000	0	97.0	80	120								
Toluene	0.96	0.050	1.000	. 0	96.5	80	120								
Ethylbenzene	1.0	0.050	1.000	0	100	80	120								
Xylenes, Total	3.0	0.10	3.000	0	99.6	80	120								
Surr: 4-Bromofluorobenzene	0.97		1.000		97.5	80	120								
Sample ID MB-15760	SampTy	ype: MB	3LK	Tes	tCode: El	PA Method	8021B: Volat	iles							
Client ID: PB\$	Batch	ID: 15 7	760	RunNo: 21782											
Prep Date: 10/8/2014	Analysis Da	ate: 10)/9/2014	S	SeqNo: 64	40424	Units: %REG	С							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Surr: 4-Bromofluorobenzene	0.91		1.000		90.7	80	120								
Sample ID LCS-15760	SampType: LCS TestCode: EPA Method 8021B: Volatiles														
Client ID: LCSS	Batch	ID: 157	760	R	RunNo: 2	1782									
Prep Date: 10/8/2014	Analysis Da	ate: 10	/9/2014	S	SeqNo: 64	40425	Units: %REG	С							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					

Qualifiers:

Value exceeds Maximum Contaminant Level.

0.97

1.000

E Value above quantitation range

Surr: 4-Bromofluorobenzene

- Analyte detected below quantitation limits
- О RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded

80

120

Not Detected at the Reporting Limit ND

97.5

- P Sample pH greater than 2.
- Reporting Detection Limit

Page 7 of 7



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

BLAGG RcptNo: 1 Client Name: Work Order Number: 1410437 Received by/date: Logged By: Lindsay Mangin 10/9/2014 7:00:00 AM Lindsay Mangin Completed By: 10/9/2014 7:44:59 AM 10/09/14 Reviewed By: Chain of Custody No \square Not Present 1. Custody seals intact on sample bottles? Yes 🗌 No 🗌 Yes 🐼 Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Courier Log in No □ NA 🗌 4. Was an attempt made to cool the samples? NA 🔲 5. Were all samples received at a temperature of >0° C to 6.0°C No 🗆 Sample(s) in proper container(s)? No 🔲 7. Sufficient sample volume for indicated test(s)? No 🗌 8. Are samples (except VOA and ONG) properly preserved? No 🗹 NA 🗌 9. Was preservative added to bottles? Yes 🗌 No 🗌 No VOA Vials 10.VOA vials have zero headspace? No 🖈 Yes 11. Were any sample containers received broken? # of preserved bottles checked for pH: No 🗂 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? No 🗌 13. Are matrices correctly identified on Chain of Custody? No 🗌 14. Is it clear what analyses were requested? Ves Yes 🗷 Checked by: No 🔲 15. Were all holding times able to be met? (if no, notify customer for authorization.) Special Handling (if applicable) No 🗌 NA 🜌 Yes 🗌 16. Was client notified of all discrepancies with this order? Person Notified: Date: eMail Phone Fax In Person Via: By Whom: Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Cooler No Temp C Condition Seal Intact Seal No Seal Date 3.1 Good Yes

Chain-ot-Custody Record		SAME			HALL ENVIRONMENTAL																
Client: BLAGG ENGR. / BP AMERICA		☐ Standard	☑ Rush _	DAY												RA					
			Project Name			1			_										14.	1	
Mailing Address: P.O. BOX 87 BLOOMFIELD, NM 87413		JAQUEZ GC A # 1				www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109															
		Project #:				Tel. 505-345-3975 Fax 505-345-4107															
Ohone #						Salar a					W V"		ysis	v 0 - 0	en mente	TARN T	Sec. 1	· 萨···莱·		, t.	
Phone #: (505) 632-1199 email or Fax#:		Project Manager:									- A			2.4				A . 65	Ť		
QA/QC Pa									1					204	3,c			300.1)			
✓ Standard		NELSON VELEZ				<u>8</u>	Talka)			(S		Ŏ,	PCB's			1 1		"			
Accreditat	Accreditation:		Sampler: NELSON VELEZ			5 (8021B)	+ TPH (Gas only)		a	7	8270SIMS)		0,5	/ 8082			water) du	-	
□ NELAP □ Other		Ondice: XYes Is I □ No			1	표	5	118.	92	3270		N.S.	8/8		A)	300.0 /		e sa	. :		
□ EDD (Type)		Sample Temp	efature :			E +	(GR)	po po	g	o	tals	Ž	cide	(A)	j-VC	1 1 1	يوا	osit			
			Container	Preservative		Ħ	+ MTBE	15B	(Method 418.1)	(Method 504.1)	310	ž	F,	esti	(VC	(Semi-VOA)	e (so	amb	composite sample	. .	
Date	Time	Matrix	Sample Request ID	Type and #	Туре	HEALNO.	BTEX +	BTEX +	TPH 8015B (GRO / DRO	TPH (EDB (N	PAH (8310	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Chloride (soil	Grab sample	5 pt. c	
10/8/14	0940	SOIL	5PC - TB @ 5' (95) - A	4 oz 1	Cool	LE TOURS TO	V	<u>B</u>	Ë	F √	Ξ	P,	~	₹	8	8.	8.	₹	15	√	
						-001	•			-								-	+	+	十
_10/0/11	9945	50H	5PG TB @ 4' (21) B	4 oz. 1	Goal	002	-		_	-/		-	ļ	· -					+	+-	+
-10/0/1 4	9343	-50nc	510 156 1 (6.)	7 OL: 1	5501	-002	1			•								*	丰	╀	1
			RUN TPH 8015B IF TPH																_	+	+
			418.1 > 100 mg/Kg																+	+	十
								_											+	+-	十
							-												+	+-	十
														<u> </u>					+	+-	+
																			+	+	十
														_					+-	+	十
																			+	+	十
Date:	Time:	Relinquish	ed by:	Received by: Date Time		Ren	nark	 s:				L	l								
10/8/14/713 =//m/J				Mist Walte 10/8/14 1713			BILL DIRECTLY TO BP:														
Date: Time: Relinquished by:			Received by Date Time			Jeff Peace, 200 Energy Court, Farmington, NM 87401															
19/8/11 1830 A Musture Library Submitted to Hall Environmental may be su			Work Order: N15488997 Paykey: ZEVHO1 Work Order: N15488997 Paykey: ZEVHO1 De subcontracted to other accredited laboratories. This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytic																		





BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (506) 326-9200

August 6, 2014

Arthur A Jaquez Jr. 335A Road 4599 Blanco, NM 87412

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank. Well Name: JAQUEZ GC A 001

Dear Mr. Jaquez,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about September 9, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

September 29, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

JAQUEZ GAS COM A 001 API 30-045-08755 (G) Section 5 – T29N – R09W San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 21bbl and a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around October 3, 2014.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



