<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources** Department Oil Conservation Division

1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method OIL CONS. DIV DIST. 3
U5-20341 Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration NOV 21 2014
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:E. E. Elliott B 10
API Number:3004520341OCD Permit Number:
U/L or Qtr/QtrA Section27 Township30N Range9W County:San Juan
Center of Proposed Design: Latitude36.78601 Longitude107.73606 NAD: ☐1927 ☒ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2.
☐ <u>Pit</u> : Subsection F, G or J of 19.15.17.11 NMAC Temporary: ☐ Drilling ☐ Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Single walled/double bottomed; side walls not visible
Liner type: Thicknessmil
4. Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC	
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
<u>Variances and Exceptions</u> : Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. ☐ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	□ Vog □ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	cuments are
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Form C-144 Oil Conservation Division Page 3 of 6

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	1
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Line Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Vac 🗆 Na
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	
Within a 100-year floodplain.	☐ Yes ☐ No
- FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.13 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	II NMAC 5.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ef
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: ☐ Permit Application (including closure plan) ☐ Closure Plan (only) ☐ OCD Conditions (see attachment) OCD Representative Signature: ☐ Approval Date: 12/10/2 Title: ☐ OCD Permit Number:	1914
Title: Own Williams	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not a section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
☐ Closure Completion Date:2/16/2012	
20. Closure Method: Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-loc ☐ If different from approved plan, please explain.	op systems only)
21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indianark in the box, that the documents are attached.	** . * * *

22.	· · · · · · · · · · · · · · · · · · ·
Operator Closure Certification:	•
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure requirer	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Jeff Posce	Date:November 19, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

Form C-144 Oil Conservation Division Page 6 of 6

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

E. E. Elliott B 10 API No. 3004520341 Unit Letter A, Section 27, T30N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

 Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.
 - Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141

Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

			Rele	ease Notific	atior	and Co	rrective A	ction				
					<u>.</u>	OPERA		[Initia	al Report	\boxtimes	Final Report
Name of Co						Contact: Jef						
		Court, Farmi	ngton, N	M 87401		Telephone No.: 505-326-9479						
Facility Nan	ne: E. E. 1	emott B 10				Facility Type: Natural gas well						
Surface Own	ner: Feder	al		Mineral C	wner:	ner: Federal			API No	. 30045203	41	
				LOCA	TIOI	N OF REI	LEASE					
Unit Letter	Section	Township	Range	Feet from the	North/	South Line	Feet from the	East/W	est Line	County: Sa	ın Juar	1
Α	27	30N	9W	1,180	North		1,000	East				
		Lat	itude3	6.78601		Longitude	107.76306					
				NAT	URE	OF RELI	EASE					
Type of Relea						Volume of	Release: N/A			Recovered: N		
		v grade tank –	95 bbl				our of Occurrenc	e:	Date and	Hour of Dis	covery	:
Was Immedia	ite Notice (Yes	No 🛛 Not Re	quired	If YES, To	Whom?					ļ
By Whom?						Date and H						
Was a Watercourse Reached? ☐ Yes ☒ No						lf YES, Vo	lume Impacting t	he Water	course.			
If a Watercou	rse was Im	pacted, Descr	ibe Fully.*			<u> </u>						
												,
the BGT. Soi	l analysis ı	esulted in TPl	H, BTEX a	n Taken.* Samplin and chloride belov	v standa	ırds. Analysis	s results are attacl	hed.				
				en.* BGT was rei active well area.	noved a	and the area u	nderneath the BG	T was sa	mpled. Th	ne excavated	area v	vas
regulations al public health should their o	l operators or the enviperations had been the envi	are required to ronment. The lave failed to a ddition, NMC	o report an acceptance dequately OCD accep	is true and completed of a C-141 repoinvestigate and retained of a C-141 repoinvestigate and retained of a C-141 repoinvestigate.	elease no rt by the emediate	otifications ar e NMOCD ma e contamination	nd perform correct arked as "Final Room that pose a three	tive action eport" do eat to gro	ons for rele es not reli and water	eases which eve the oper , surface wa	may er ator of ter, hu	idanger Tliability man health
Signature:	Jola	Pear					OIL CONS	SERV <i>i</i>	<u>ATION</u>	<u>DIVISIO</u>	N	
Printed Name	Jeff Peac		, , , , , , , , , , , , , , , , , , , ,			Approved by	Environmental S	pecialist:				
Title: Field E	nvironmen	tal Coordinato	r			Approval Dat	e:	E	xpiration I	Date:		
E-mail Addre	ss: peace.jo	effrey@bp.cor	n			Conditions of	Approval:			Attached		
Date: Novem	ber 19, 20	14	Pho	ne: 505-326-9479								

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG ENG P.O. BOX 87, BLG	GINEERING, INC		API#: 3004	1520341
OLILINI.) 632-1199	07413	TANK ID (if applicble):	Α
FIELD REPORT:	(circle one): BGT CONFIRMATION / R	ELEASE INVESTIGATION / OT	HER:	PAGE #: 1	of 1
SITE INFORMATION		OTT B # 10		DATE STARTED:	02/07/12
QUAD/UNIT: A SEC: 27 TWP:		NM CNTY: SJ	st: NM	DATE FINISHED:	
1/4 -1/4/F00TAGE: 1,180'N / 1,00 LEASE #: SF078139	DO'E NE/NE LEASE TYP PROD. FORMATION: PC CON	FLICTION		ENVIRONMENTAL SPECIALIST(S):	JCB
REFERENCE POINT					
1) 95 BGT (SW/DB)	GPS COORD.: 36.7	78601 X 107.76306	DISTANCE/BE	ARING FROM W.H.:	84', N58W
2)	GPS COORD.:		DISTANCE/BE/	ARING FROM W.H.:	
3)	GPS COORD.:		DISTANCE/BE	ARING FROM W.H.:	
4)				ARING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR I	LAB USED: HALL			OVM READING (ppm)
1) SAMPLEID: 95 BGT 5-pt. @).0 (CI) 0.0
2) SAMPLE ID:					
3) SAMPLE ID:					1 1
4) SAMPLE ID:					
SOIL DESCRIPTION SOIL COLOR: DARK YEL COHESION (ALL OTHERS): NON COHESIVE / SLIGHTL CONSISTENCY (NON COHESIVE SOILS) L MOISTURE: DRY / SLIGHTLY MOIST / MOIST / M SAMPLE TYPE: GRAB COMPOSITE # OF PTS. DISCOLORATION/STAINING OBSERVED ANY AREAS DISPLAYING WETNESS: YES NC ADDITIONAL COMMENTS: NO APPARI TANK REMOVED WITH CRANE. TANK	COMSH ORANGE Y COHESIVE / COHESIVE / HIGHLY COHESIVE DOSE FIRM / DENSE / VERY DENSE ET / SATURATED / SUPER SATURATED 5 : YES NO EXPLANATION - EXPLANATION - ENT EVIDENCE OF A RELEASE FRO	PLASTICITY (CLAYS): NON PLAY DENSITY (COHESIVE CI HC ODOR DETECTED M BGT OBSERVED.	STIC/SLIGHTLY PLASTIC/OLAYS & SILTS): SOFT	COHESNE / MEDIUM PLASTIC / / FIRM / STIFF / VERY S ANATION -	STIFF / HARD
SOIL IMPACT DIMENSION ESTIMATION DEPTH TO GROUNDWATER: <u>>100'</u> N		n. X NA ft. NEAREST SURFACE WATER:		IMATION (Cubic Yards D TPH CLOSURE STD: _	
SITE SKETCH	PBGTL TB ~ 4'	PLOT PLAN circle	N TIME	CALIB. READ. = 52.7 CALIB. GAS = 100	ppm RF - 0.32 TE: 02/07/12
(X)	B.G.	WELL HEAD ⊕	<u> </u>	PO - 70639 PK - ZSCHWLLBG PJ - Z2-00690-C ermit date(s): 06/0	
	BELOW-GRADE TANK LOCATION; SPD = SAMP	= BELOW, T.H. = TEST HOLE; ~ = A LE POINT DESIGNATION; R.W. = RI	C - S.P.D. A PPROX.; ETAINING WALL;	CD Appr. date(s): '	12/27/11 le: Y / N / NA le: Y / N / NA
NA-NOT APPLICABLE OR NOT AVAILABLE TRAVEL NOTES: CALLOUT:	E; SW - SINGLE WALL; DW - DOUBLE WALL; SB	- <u>SINGLE BOTTOM; DB - DOUBLE E</u> ONSITE: 02/07/1			

Analytical Report

Lab Order 1202326

Date Reported: 2/16/2012

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 95 BGT 5-point@5'

Project: E.E. Elliott B 10

Collection Date: 2/7/2012 8:50:00 AM

Lab ID: 1202326-001

Received Date: 2/9/2012 9:50:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	E ORGANICS				Analyst: JMP
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	2/10/2012 12:59:06 PM
Surr: DNOP	86.4	77.4-131	%REC	1	2/10/2012 12:59:06 PM
EPA METHOD 8015B: GASOLINE RA	ANGE				Analyst: RAA
Gasoline Range Organics (GRO)	ND	5.0	mg/Kg	1	2/10/2012 2:56:34 PM
Surr: BFB	103	69.7-121	%REC	1	2/10/2012 2:56:34 PM
EPA METHOD 8021B: VOLATILES					Analyst: RAA
Benzene	ND	0.050	mg/Kg	1	2/10/2012 2:56:34 PM
Toluene	ND	0.050	mg/Kg	1	2/10/2012 2:56:34 PM
Ethylbenzene	ND	0.050	mg/Kg	1	2/10/2012 2:56:34 PM
Xylenes, Total	ND	0.10	mg/Kg	1	2/10/2012 2:56:34 PM
Surr: 4-Bromofluorobenzene	101	85.3-139	%REC	1	2/10/2012 2:56:34 PM
EPA METHOD 300.0: ANIONS					Analyst: BRM
Chloride	ND	7.5	mg/Kg	5	2/10/2012 1:54:46 PM
EPA METHOD 418.1: TPH					Analyst: JMP
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	2/15/2012

Matrix: SOIL

Qualifiers:

- */X Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202326

16-Feb-12

Client:

Blagg Engineering

Project:

E.E. Elliott B 10

Sample ID MB-674

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 674

PQL

RunNo: 898

Prep Date: 2/10/2012 Analysis Date: 2/10/2012

Units: mg/Kg

Analyte

Result

SPK value SPK Ref Val %REC LowLimit

SeqNo: 25516

%RPD

%RPD

HighLimit

RPDLimit

Qual

Chloride

ND 1.5

Sample ID LCS-674

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS Batch ID: 674

RunNo: 898

Prep Date: 2/10/2012

SeqNo: 25517

Units: mg/Kg

Analysis Date: 2/10/2012

Qual

Analyte

PQL SPK value SPK Ref Val %REC

92.3

HighLimit

Chloride

1.5

15.00

LowLimit

RPDLimit

14

110

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

Value above quantitation range

Analyte detected below quantitation limits

RPD outside accepted recovery limits R

Analyte detected in the associated Method Blank В

Holding times for preparation or analysis exceeded Η

Not Detected at the Reporting Limit

Reporting Detection Limit

Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1202326

16-Feb-12

Client:

Blagg Engineering

Project:

E.E. Elliott B 10

Sample ID MB-708

2/14/2012

SampType: MBLK

Analysis Date: 2/15/2012

PQL

20

20

TestCode: EPA Method 418.1: TPH

Client ID: Prep Date:

PBS

Batch ID: 708

RunNo: 955

Units: mg/Kg

SeqNo: 27726 SPK value SPK Ref Val %REC LowLimit

%RPD **RPDLimit**

Qual

Analyte Petroleum Hydrocarbons, TR

ND

Sample ID LCS-708

2/14/2012

SampType: LCS

TestCode: EPA Method 418.1: TPH

HighLimit

Prep Date:

Client ID: LCSS

Batch ID: 708

RunNo: 955

SeqNo: 27727

Units: mg/Kg

115

Analyte Petroleum Hydrocarbons, TR

PQL Result 100

110

Result

Analysis Date: 2/15/2012

SPK value SPK Ref Val

100.0

%REC LowLimit 104

RunNo: 955

HighLimit

%RPD **RPDLimit** Qual

Qual

Sample ID LCSD-708

SampType: LCSD

TestCode: EPA Method 418.1: TPH

87.8

Client ID: LCSS02 Prep Date: 2/14/2012

Batch ID: 708 Analysis Date: 2/15/2012

SeqNo: 27728

Units: mg/Kg

Analyte

Result **PQL**

SPK value SPK Ref Val %REC

105

87.8

HighLimit

%RPD **RPDLimit** 1.01

8.04

Petroleum Hydrocarbons, TR

20 100.0

115

Qualifiers:

Value exceeds Maximum Contaminant Level. */X

Value above quantitation range

Analyte detected below quantitation limits

В

Н Holding times for preparation or analysis exceeded

Analyte detected in the associated Method Blank

Not Detected at the Reporting Limit ND

Reporting Detection Limit RL

Page 3 of 6

RPD outside accepted recovery limits R

Hall Environmental Analysis Laboratory, Inc.

Result

41

4.2

PQL

10

WO#:

1202326

16-Feb-12

Client:

Blagg Engineering

Project:

Analyte

Surr: DNOP

Diesel Range Organics (DRO)

E.E. Elliott B 10

Sample ID MB-660	SampType: M	TestCode: EPA Method 8015B: Diesel Range Organics							
Client ID: PBS	Batch ID: 66	Rı	RunNo: 874 SeqNo: 24990						
Prep Date: 2/9/2012	Analysis Date: 2	Se				Units: mg/Kg			
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND 10								
Surr: DNOP	8.3	10.00		83.0	77.4	131			
Sample ID LCS-660	SampType: L0	s	Test	Code: El	PA Method	8015B: Diese	el Range (Drganics	
Client ID: LCSS	Batch ID: 66	0	Ru	ınNo: 8	74				
Prep Date: 2/9/2012	Analysis Date: 2	/10/2012	Se	egNo: 2	4991	Units: ma/K	(a		

%REC

82.9

84.0

LowLimit

62.7

77.4

HighLimit

139

131

%RPD

RPDLimit

Qual

SPK value SPK Ref Val

50.00

5.000

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

R RPD outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Page 4 of 6

RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202326 16-Feb-12

Client:

Blagg Engineering

Project:

E.E. Elliott B 10

Sample ID MB-659 SampType: MBLK

TestCode: EPA Method 8015B: Gasoline Range

Client ID:

PBS

2/9/2012

2/9/2012

Batch ID: 659

RunNo: 888

LowLimit

Units: mg/Kg

Prep Date: Analyte

Analysis Date: 2/10/2012 **PQL**

5.0

5.0

SeqNo: 26028 %REC

HighLimit

RPDLimit

Qual

Gasoline Range Organics (GRO)

ND

SPK value

79.5

69.7

TestCode: EPA Method 8015B: Gasoline Range

%RPD

Surr: BFB

Prep Date:

800

Result

1,000

25.00

1,000

121

Sample ID LCS-659 Client ID: LCSS

Batch ID: 659

SampType: LCS

RunNo: 888

SeqNo: 26031

Units: mg/Kg

%RPD

Qual

Analyte Gasoline Range Organics (GRO) Surr: BFB

Analysis Date: 2/10/2012 Result PQL

28

980

SPK value SPK Ref Val %REC 0

SPK Ref Val

LowLimit 111 98.4 69.7

HighLimit 98.5

133 121 **RPDLimit**

Qualifiers:

R

Value exceeds Maximum Contaminant Level. */X

Value above quantitation range

Analyte detected below quantitation limits RPD outside accepted recovery limits

В Analyte detected in the associated Method Blank

I-I Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit Page 5 of 6

Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202326

16-Feb-12

Client: Project: Blagg Engineering

E.E. Elliott B 10

Sample iD MB-659	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS	Batch ID: 659			F	RunNo: 888					
Prep Date: 2/9/2012	Analysis [Date: 2/	10/2012	8	SeqNo: 26064 Units: mg/Kg			(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050							-	•
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.83		1.000		82.7	85.3	139			S

Sample ID LCS-659	TestCode: EPA Method 8021B: Volatiles											
Client ID: LCSS	Batch	h ID: 65	9	F								
Prep Date: 2/9/2012	p Date: 2/9/2012 Analysis Date: 2/10/2012			S	SeqNo: 2	6067	Units: mg/K	(g				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Benzene	0.94	0.050	1.000	0	93.5	83.3	107					
Toluene	0.89	0.050	1.000	0	88.7	74.3	115					
Ethylbenzene	0.95	0.050	1.000	0	95.1	80.9	122					
Xylenes, Total	3.0	0.10	3.000	0	98.8	85.2	123					
Surr: 4-Bromofluorobenzene	1.1		1.000		112	85.3	139					

Qualifiers:

Page 6 of 6

^{*/}X Value exceeds Maximum Contaminant Level.

Value above quantitation range Е

Analyte detected below quantitation limits

R RPD outside accepted recovery limits

Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Reporting Detection Limit



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105 TEL: 505-345-3975 FAX: 505-345-410;

Sample Log-In Check List

Website: www.hallenvironmental.com Client Name: BLAGG Work Order Number: 1202326 Received by/date Logged By: Michelle Garcia 2/9/2012 9:50:00 AM Completed By: Michelle Garcia 2/9/2012 12:50:19 PM Reviewed By: Chain of Custody Yes No 🗌 Not Present 1 Were seals Intact? Yes 🔽 No 🗌 Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Courier Log In Yes V No NA 🗌 4. Coolers are present? (see 19. for cooler specific information) Yes 🗹 No 🗌 NA 🗆 5. Was an attempt made to cool the samples? NA 🗆 Yes V No 🗌 6 Were all samples received at a temperature of >0° C to 6.0°C Yes 🗸 No 🗌 7 Sample(s) in proper container(s)? Yes 🗸 No 🗌 8 Sufficient sample volume for indicated test(s)? Yes ✓ No 🗆 9. Are samples (except VOA and ONG) properly preserved? Yes 🗌 No 🗹 NA 🗆 10. Was preservative added to bottles? Yes No No VOA Vials 11. VOA vials have zero headspace? Yes 🗌 No 🗹 12. Were any sample containers received broken? # of preserved 13 Does paperwork match bottle labels? Yes 🗹 No 🗌 bottles checked (Note discrepancies on chain of custody) for pH: Yes 🗹 No 🗌 14. Are matrices correctly identified on Chain of Custody? (<2 or >12 unless noted) Yes 🗹 No 🗌 Adjusted? 15. Is it clear what analyses were requested? Yes 🗹 No 🗌 16. Were all holding times able to be met? (If no, notify customer for authorization.) Checked by: Special Handling (if applicable) Yes D No D NA 🗹 17. Was client notified of all discrepancies with this order? Person Notified: Date: By Whom: Via: eMail Phone Fax In Person

18. Additional remarks:

Regarding: Client Instructions:

19. Cooler Information

. =			-				
	Cooler No	Temp °C	Condition.	Seal Intact	Seal No	Seal Date	Signed By
	1	2.3	Good	Yes			

Chain-of-Custody Record Client: BLAGE ENEWERWG INC.				Turn-Around Time: A Standard Rush				HALL ENVIRONMENTAL ANALYSIS LABORATORY													
																				7	BP B
BP AMERICA Mailing Address: P.O. Box 87			E.E. ELLIOTT B 10				4901 Hawkins NE - Albuquerque, NM 87109														
E	BLOOM	FIELD,	NM 87413	Project #:		•					5-34					5-345					
Phone a	#: 5	05-6	32-1199					April April		749	* 43	of a training	Αı	nalys	is Re	ques	trice			A Market	
email o				Project Mana)	only)	(les					74)						
QA/QC I	Package: dard	•	□ Level 4 (Full Validation)	J. /	BLAGG			王TMBS (8021)	TPH (Gas or	as/Die				0	704,97, PCB's						
Accredi	itation			Sampler:	J BLAG	. 6		#	PH	B (6	=	=		2		2					
□ NEL	AP	□ 'Othe	ř	Onlice 21	y/ies-ca	□ No.			+	315	18	9.	<u>₹</u>	, 2			₹	اما			٩ ام
□ EDD	(Type)_			Sample Tem	iejalyjeseZ			開	BE.)8 p	2d 4	0d 5	o F	state	ָבְּיִּין בְּיִּבְּיִין בְּיִבְּיִין	<u> </u>		3			ځ
Date	Time	Matrix	Sample Request ID		Preservative Type			BTEX +: WIBE	BTEX + MTBE	TPH Method 8015B (Gas/Diesel)	TPH (Method 418.1)	EDB (Method 504.1)	8310 (PNA or PAH)	RCRA 8 Metals	Anions (F.C.,NO3,NO2,1	8260B (VOA)	8270 (Semi-VOA)	CHORDE			Air Bubbles (Y or N)
1/12	0850	SOIL	95 BGT 5-POINT 05	402×1	COOL	T	-	X			X				\			X			\uparrow
7																					丅
															+					\dashv	十
				1								\dashv	$\neg \dagger$			 			_	+	+
											+	-		-			-		\dashv	+	+
											-		\dashv			-	 	\vdash	\dashv	+	+
												\dashv		+	-	. [-		\dashv	+	+
						<u> </u>	· · · · · · · · · · · · · · · · · · ·					_	\dashv	_	+				_	\dotplus	+
											-	_		- -	-	-	<u> </u>			_	+
							***							_		-				+	+
										\Box		-			<u> </u>	+-	<u> </u>	\vdash	_		+
						<u></u>						_		- -	-	-	-		_	_	+
Deter	Timo:	Polinguich	nd hy:	Received by:		Data	Timo	Dan	2016				<u> </u>			2		Щ			<u></u>
Date:	Time: 0950	Relinguishe	13199	Ma. t.	سينتل ووليا	3/9/12	Time 0950							U	ON	80	75				
Date:	Time:	Refinquish	ed by:	Received by:		Date	Time	l '			WL										
18/12	1612	Mri	oten Westers	The North	Alle 18)2/9/	12 1950	מפש	TAE	T 1 6	JEA	F 8	E AC	Ē_				1			





BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

January 23, 2012

Bureau of Land Management Mark Kelly 1235 La Plata Hwy Farmington, NM 87401

VIA CERTIFIED MAIL - RETURN RECEIPT REUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: E E ELLIOTT B 010

Dear Mark Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about January 24, 2012. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

9. Duelle

Surface Coordinator/Business Security Representative

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

January 23, 2011

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

E E ELLIOTT B 010 API 30-045-20341A (M) Section 27 – T30N – R09W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl. BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Buddy Shaw BP Environmental Advisor

(505) 320-0401



