District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

Liner type: Thickness_

Alternative Method:

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration OIL CONS DIV DIST 3
Permit of a pit or proposed alternative method V5: 20453 Closure of a pit, below, grade table or proposed alternative method
☐ Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Florance C LS 13
API Number:3004520453OCD Permit Number:
U/L or Qtr/QtrCSection29Township28NRange8WCounty:San Juan
Center of Proposed Design: Latitude36.63707 Longitude107.70842 NAD: ☐1927 ☒ 1983
Surface Owner: 🛮 Federal 🗌 State 🔲 Private 🔲 Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover
Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
■ Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:21.0bbl Type of fluid:Produced water
Tank Construction material:Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☑ Visible sidewalls only ☐ Other _Single walled/double bottomed

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,				
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)					
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC					
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.					
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source				
General siting					
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No☐ NA				
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No				
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No				
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 					
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map					
Below Grade Tanks					
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No				
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site					
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)					
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No				

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No					
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 						
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site						
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site						
Temporary Pit Non-low chloride drilling fluid						
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site						
	│ □ Yes □ No					
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No					
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 300 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Permanent Pit or Multi-Well Fluid Management Pit						
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No					
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of						
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.						
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.13.17.13 NMAC						
Previously Approved Design (attach copy of design) API Number: or Permit Number:						
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC						
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	uments are					
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC					
☐ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC						
Previously Approved Design (attach copy of design) API Number: or Permit Number:						

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Deliver of Type: De	luid Managaman Die
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be	attached to the
closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ 1 c2 ☐ 140

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
written communition of vormeation non-the mannerparity, written approval obtained from the mannerparity	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	
Within a 100-year floodplain FEMA map	☐ Yes ☐ No ☐ Yes ☐ No
- T BWITTHILD	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ef
Name (Print): Title:	
e-mail address: Date:	
18.	
OCD Approval: Permit Application (including closure plan), Closure Plan (only) OCD Conditions (see attachment)	
OCD Representative Signature: Approval Date: 12/1/2	e14
() $()$	
Title: OMPHINCE OFFICE OCD Permit Number:	
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not a section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 3/6/2012	
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not a section of the form until an approved closure plan has been obtained and the closure activities have been completed.	complete this

Form C-144 Oil Conservation Division Page 5 of 6

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure require	
Name (Print) Leff Peace	Title: Field Environmental Coordinator
Signature: Aff Peace	Date:November 19, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

Form C-144 Oil Conservation Division Page 6 of 6

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Florance C LS 13 API No. 3004520453 Unit Letter C, Section 29, T28N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	eatio	on and Co	orrective A	ction	
		_				OPERA	ГOR	☐ Init	al Report 🛛 Final Report
Name of Company: BP				Contact: Jef					
Address: 200 Energy Court, Farmington, NM 87401 Facility Name: Florance C LS 13					No.: 505-326-94				
Facility Nai	me: Floran	ice C LS 13				Facility Typ	e: Natural gas v	well	
Surface Ow	ner: Feder	al		Mineral C	wner	: Federal		API N	o. 3004520453
				LOCA	ATIC	ON OF RE	LEASE		
Unit Letter	Section	Township	Range	Feet from the		h/South Line	Feet from the	East/West Line	County: San Juan
C	29	28N	8W	900	Nort	h	1,450	West	
	<u> </u>	Lat	itude3	6.63707		Longitud	e107.70842_	<u></u>	J
				NAT	URI	E OF RELI	EASE		
Type of Rele						Volume of	Release: N/A	Volume	Recovered: N/A
		v grade tank –	- 21 bbl				Iour of Occurrence	e: Date and	Hour of Discovery:
Was Immedia	ate Notice (Yes [No 🛭 Not Ro	equirec	If YES, To	Whom?		
By Whom?						Date and I			
Was a Watercourse Reached? ☐ Yes ☑ No					If YES, Volume Impacting the Watercourse.				
If a Watercou	ırse was Im	pacted, Descr	ibe Fully.*						
the BGT. So	il analysis r	resulted in TP	H, BTEX :	and chloride belo	w stand	dards. Analysi	s results are attacl	hed.	to ensure no soil impacts from
				en.* BGT was re active well area.	moved	I and the area u	nderneath the BG	T was sampled. T	he excavated area was
regulations al public health should their or or the environ	If operators or the envi operations h nment. In a	are required to ronment. The lave failed to a	o report ar acceptance adequately OCD accep	nd/or file certain r te of a C-141 report investigate and r	elease ort by t emedia	notifications and he NMOCD mate contaminati	nd perform correct arked as "Final R on that pose a thr	ctive actions for rel eport" does not rel eat to ground wate	suant to NMOCD rules and eases which may endanger ieve the operator of liability r, surface water, human health ompliance with any other
		<u> </u>					OIL CON	SERVATION	DIVISION
Signature:	sel t	ene							
Printed Name	e: Jeff Peac	e			·	Approved by	Environmental S	pecialist:	
		tal Coordinate	or			Approval Da	e:	Expiration	Date:
E-mail Addre	ess: peace.jo	effrey@bp.co	m			Conditions of	Approval:		Attached
Date: Noven	nber 19, 20	14	Pho	ne: 505-326-9479))				

^{*} Attach Additional Sheets If Necessary

CLIENT: BP		GINEERING, INC. OOMFIELD, NM 87413	API#: 3004520453	
	•	632-1199	TANK ID (if applicble):	
FIELD REPORT:	(circle one): BGT CONFIRMATION / RI	ELEASE INVESTIGATION / OTHER:	PAGE #: 1 of	1_
SITE INFORMATION	SITE NAME: FLORANC	CE C LS # 13	DATE STARTED: 02/27/12	•
QUAD/UNIT: C SEC: 29 TWP:	28N RNG: 8W PM:	NM CNTY: SJ ST: N	DATE FINISHED:	
1/4-1/4/FOOTAGE: 900'N / 1,450	W NE/NW LEASE TYPE	E: FEDERAL STATE / FEE / INDIAN		
	PROD. FORMATION: PC CONT	ELKHORN TRACTOR: MBF	SPECIALIST(S): JCB	
REFERENCE POINT		OORD.: 36.63715 X 107.708	340 GLELEV.: 5,843'	
1) 21 BGT (SW/DB)	GPS COORD.: 36.6	53707 X 107.70842 DISTAN	CE/BEARING FROM W.H.: 20', S38W	
2)			CE/BEARING FROM W.H.:	
3)			CE/BEARING FROM W.H.:	
<u> </u>	GPS COORD.:		CE/BEARING FROM W.H.:	
SAMPLING DATA:	•	AB USED: HALL	READII (ppm	NG 1)
. •		SAMPLE TIME:1355 LAB ANALYSIS: 418		
		SAMPLE TIME: LAB ANALYSIS:		_
		SAMPLE TIME: LAB ANALYSIS:		\dashv
The state of the s		SAMPLE TIME: LAB ANALYSIS:		
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SA	AND / SILT / SILTY CLAY / CLAY / GRAVEL	/OTHER	
SOIL COLOR: DARK YELL COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY		DI ACTICITY (CLAVC). AICALDI ACTIC / CLICHTI V DI A	STIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC	—
CONSISTENCY (NON COHESIVE SOILS) LO		' '	SOFT / FIRM / STIFF / VERY STIFF / HARD	
MOISTURE: DRY/SLIGHTLYMOIST/MOIST/WE		HC ODOR DETECTED: YES NO E	EXPLANATION -	_
SAMPLE TYPE: GRAB COMPOSITE # 0F PTS. DISCOLORATION/STAINING OBSERVED:			AME.	_
DIGOCCIVATION NOTALINA OBSERVED.				
ANY AREAS DISPLAYING WETNESS: YES NO			10 10 10 10 10 10 10 10 10 10 10 10 10 1	_
ADDITIONAL COMMENTS: NO APPARE	NT EVIDENCE OF A RELEASE FROM	M BGT OBSERVED.		_
SOIL IMPACT DIMENSION ESTIMATION:			ESTIMATION (Cubic Yards) : NA	_
	EAREST WATER SOURCE: >1,000' N		NMOCD TPH CLOSURE STD: 1,000 ppm	_
SITE SKETCH		PLOT PLAN circle: attached	OVM CALIB. READ. = 53.3 ppm RF = 0.	.52
			OVM CALIB. GAS = 100 ppm	
	WELL	N	TIME: 2:00 am(pm) DATE: 02/27/13	$\underline{\parallel}$
l'	\oplus Well Head	•	MISCELL. NOTES	
l'			WO - N1535941	
		•	PO - 77156	
PBGTL			PK - ZVALENOLAB	
TB ~4' = B.G.	$\longrightarrow (\stackrel{\times}{\underset{\times}{\underset{\times}{\times}}})$			—
w. w.			Permit date(s): 06/14/10	
			OCD Appr. date(s): 02/08/12	
			Tank ID	
		X - S.P.D.	A BGT Sidewalls Visible: Y (N)/ NA	_
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVA		= BELOW, T.H. = TEST HOLE; ~ = APPROX.;	BGT Sidewalls Visible: Y / N / NA	
	BELOW-GRADE TANK LOCATION;	E POINT DESIGNATION; R.W. = RETAINING WALL; SINGLE BOTTOM; DB - DOUBLE BOTTOM.	Magnetic declination: 10° E	
TRAVEL NOTES: CALLOUT:		ONSITE: 02/27/12		_

Analytical Report

Lab Order 1202932

Date Reported: 3/6/2012

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 21 BGT 5-pt @ 4'

Project: Florance C LS 13

Collection Date: 2/27/2012 1:55:00 PM

Lab ID: 1202932-001

Received Date: 2/29/2012 9:30:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANGE	ORGANICS				Analyst: JMP
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	3/1/2012 12:38:00 PM
Surr: DNOP	89.2	77.4-131	%REC	1	3/1/2012 12:38:00 PM
EPA METHOD 8015B: GASOLINE RAM	NGE				Analyst: RAA
Gasoline Range Organics (GRO)	ND	4.6	mg/Kg	1	3/1/2012 5:19:38 PM
Surr: BFB	116	69.7-121	%REC	1	3/1/2012 5:19:38 PM
EPA METHOD 8021B: VOLATILES					Analyst: RAA
Benzene	ND	0.046	mg/Kg	1	3/1/2012 5:19:38 PM
Toluene	ND	0.046	mg/Kg	1	3/1/2012 5:19:38 PM
Ethylbenzene	ND	0.046	mg/Kg	1	3/1/2012 5:19:38 PM
Xylenes, Total	ND	0.092	mg/Kg	1	3/1/2012 5:19:38 PM
Surr: 4-Bromofluorobenzene	107	85.3-139	%REC	1	3/1/2012 5:19:38 PM
EPA METHOD 300.0: ANIONS					Analyst: BRM
Chloride	ND	7.5	mg/Kg	5	3/5/2012 2:00:13 PM
EPA METHOD 418.1: TPH					Analyst: JMP
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	3/1/2012

Matrix: SOIL

Qualifiers:

- */X Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202932 06-Mar-12

Client:

Blagg Engineering

Project:

Florance C LS 13

Sample ID MB-945

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 945

RunNo: 1281

3/5/2012

Analysis Date: 3/5/2012

SegNo: 36376

Units: mg/Kg

Prep Date:

Result

HighLimit

RPDLimit %RPD

Qual

Analyte Chloride

ND 1.5

PQL

Sample ID LCS-945

LCSS

SampType: LCS

TestCode: EPA Method 300.0: Anions

RunNo: 1281

%REC LowLimit

Prep Date: 3/5/2012

Batch ID: 945 Analysis Date: 3/5/2012

SeqNo: 36377

Units: mg/Kg

Analyte

Client ID:

PQL

RPDLimit

%RPD

90

Result 14

15.00

HighLimit

Chloride

1.5

SPK value SPK Ref Val

SPK value SPK Ref Val

%REC 90.3

LowLimit

110

Qual

Qualifiers:

Value exceeds Maximum Contaminant Level. */X

Value above quantitation range

Analyte detected below quantitation limits

Analyte detected in the associated Method Blank Holding times for preparation or analysis exceeded Η

Not Detected at the Reporting Limit ND

Page 2 of 6

RPD outside accepted recovery limits R

Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#: 1202932

06-Mar-12

Client:

Blagg Engineering

Project:

Analyte

Florance C LS 13

Sample ID MB-892 SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID:

PBS

Batch ID: 892

PQL

20

RunNo: 1198

2/29/2012

Prep Date:

Analysis Date: 3/1/2012

Result

Result

110

SeqNo: 34076

Units: mg/Kg HighLimit

%RPD **RPDLimit**

Qual

Petroleum Hydrocarbons, TR

ND

Sample ID LCS-892

SampType: LCS

TestCode: EPA Method 418.1: TPH

%RPD

Client ID:

LCSS

Batch ID: 892

RunNo: 1198

%REC LowLimit

Units: mg/Kg

Analyte

Prep Date: 2/29/2012 Analysis Date: 3/1/2012

PQL

20

SeqNo: 34077 SPK value SPK Ref Val

%REC LowLimit

109

HighLimit

RPDLimit

Qual

Petroleum Hydrocarbons, TR

Sample ID LCSD-892

SampType: LCSD

TestCode: EPA Method 418.1: TPH

115

Client ID: LCSS02 2/29/2012 Prep Date:

Batch ID: 892 Analysis Date: 3/1/2012

RunNo: 1198 SeaNo: 34081

Units: mg/Kg HighLimit

RPDLimit Qual

Analyte Petroleum Hydrocarbons, TR **PQL**

20

SPK value SPK Ref Val

100.0

%REC

87.8

LowLimit

87.8

115

8.04

Result 110

100.0

SPK value SPK Ref Val

1.88

%RPD

Qualifiers:

R

Value exceeds Maximum Contaminant Level. */X

Value above quantitation range Ε

Analyte detected below quantitation limits RPD outside accepted recovery limits

В Analyte detected in the associated Method Blank

Η Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit Reporting Detection Limit

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1202932

06-Mar-12

Client:

Blagg Engineering

Project: Florance	ce C LS'13		
Sample ID MB-891	SampType: MBLK	TestCode: EPA Method	8015B: Diesel Range Organics
Client ID: PBS	Batch ID: 891	RunNo: 1195	
Prep Date: 2/29/2012	Analysis Date: 3/1/2012	SeqNo: 34033	Units: mg/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Diesel Range Organics (DRO) Surr: DNOP	ND 10 8.6 · 10.00	86.2 77.4	131
Sample ID LCS-891	SampType: LCS	TestCode: EPA Method	8015B: Diesel Range Organics
Client ID: LCSS	Batch ID: 891	RunNo: 1195	
Prep Date: 2/29/2012	Analysis Date: 3/1/2012	SeqNo: 34034	Units: mg/Kg
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Diesel Range Organics (DRO)	48 10 50.00	0 95.7 62.7	139
Surr: DNOP	4.5 5.000	89.5 77.4	131
Sample ID MB-888	SampType: MBLK	TestCode: EPA Method	8015B: Diesel Range Organics
Client ID: PBS	Batch ID: 888	RunNo: 1195	
Prep Date: 2/29/2012	Analysis Date: 3/1/2012	SeqNo: 34319	Units: %REC
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Surr: DNOP	8.7 10.00	87.2 77.4	131
Sample ID LCS-888	SampType: LCS	TestCode: EPA Method	8015B: Diesel Range Organics
Client ID: LCSS	Batch ID: 888	RunNo: 1195	
Prep Date: 2/29/2012	Analysis Date: 3/1/2012	SeqNo: 34348	Units: %REC
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual
Surr: DNOP	4.5 5.000	89.4 77.4	131

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

Value above quantitation range Е

Analyte detected below quantitation limits

RPD outside accepted recovery limits R

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit ND

Page 4 of 6

Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202932

06-Mar-12

Client:

Blagg Engineering

Project:

Florance C LS 13

89

SampType: MBLK

TestCode: EPA Method 8015B: Gasoline Range

Client ID: PBS

Batch ID: 889

RunNo: 1220

Prep Date: 2/29/2012 Analysis Date: 3/1/2012

SeqNo: 34762

Units: mg/Kg

%RPD

Result **PQL** ND 5.0 SPK value SPK Ref Val %REC LowLimit HighLimit

RPDLimit Qual

Gasoline Range Organics (GRO)

880

Surr: BFB

1,000

88.4

121

Sample ID LCS-889

LCSS Client ID:

SampType: LCS Batch ID: 889

TestCode: EPA Method 8015B: Gasoline Range RunNo: 1220

Prep Date:

2/29/2012

Analysis Date: 3/1/2012

SeqNo: 34766

%REC

Units: mg/Kg HighLimit

Qual

Analyte Gasoline Range Organics (GRO) Surr: BFB

Result PQL.

SPK value

25.00 1,000

118 96.8

98.5

LowLimit

69.7

133

%RPD **RPDLimit**

29 970

5.0

SPK Ref Val

0

69.7

121

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range Е

Analyte detected below quantitation limits

Analyte detected in the associated Method Blank

Н

ND Not Detected at the Reporting Limit

Reporting Detection Limit

Holding times for preparation or analysis exceeded

Page 5 of 6

RPD outside accepted recovery limits

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202932

06-Mar-12

Client: Project: Blagg Engineering Florance C LS 13

Sample ID MB-889	SampType: MBLK Batch ID: 889			Tes						
Client ID: PBS				RunNo: 1220						
Prep Date: 2/29/2012	Analysis Date: 3/1/2012			SeqNo: 34834			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.93		1.000		92.6	85.3	139			

Sample ID LCS-889	SampType: LCS Batch ID: 889 Analysis Date: 3/1/2012			TestCode: EPA Method 8021B: Volatiles							
Client ID: LCSS				F	RunNo: 1	220					
Prep Date: 2/29/2012				SeqNo: 34873			Units: mg/Kg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	1.0	0.050	1.000	0	101	83.3	107				
Toluene	1.0	0.050	1.000	0	100	74.3	115				
Ethylbenzene	1.1	0.050	1.000	0	106	80.9	122				
Xylenes, Total	3.3	0.10	3.000	0	109	85.2	123				
Surr: 4-Bromofluorobenzene	1.3		1.000		127	85.3	139				

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits

RPD outside accepted recovery limits

Analyte detected in the associated Method Blank В

Holding times for preparation or analysis exceeded Н

Not Detected at the Reporting Limit Reporting Detection Limit

Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105

TEL: 505-345-3975 FAX: 505-345-410; Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: BLAGG Work Order Number: 1202932 2/29/1 Received by/date: Logged By: Michelle Garcia 2/29/2012 9:30:00 AM Completed By: Michelle Garcia 2/29/2012 10:11:51 AM Reviewed By: Chain of Custody Yes 🗍 No 🗍 Not Present 1 Were seals intact? Yes 🗹 No 🗌 Not Present 2 Is Chain of Custody complete? 3. How was the sample delivered? Courier Log In 4. Coolers are present? (see 19. for cooler specific information) Yes 🗹 No 🗌 NA 🗍 Yes 🗹 No 🗌 NA 🗀 5. Was an attempt made to cool the samples? 6. Were all samples received at a temperature of >0° C to 6.0°C Yes V No 🗌 NA 🗌 Yes 🗸 No 🗌 7 Sample(s) in proper container(s)? 8 Sufficient sample volume for indicated test(s)? Yes V No Yes 🗸 No 🗌 9. Are samples (except VOA and ONG) properly preserved? NA 🗌 Yes No V 10. Was preservative added to bottles? Yes No No VOA Vials 11. VOA vials have zero headspace? Yes 🗌 No 🗹 12. Were any sample containers received broken? # of preserved Yes 🗹 No 🗌 13. Does paperwork match bottle labels? bottles checked (Note discrepancies on chain of custody) for pH: 14. Are matrices correctly identified on Chain of Custody? Yes 🗹 No 🗌 (<2 or >12 unless noted) Yes 🗹 No 🗌 Adjusted? 15. Is it clear what analyses were requested? Yes 🗹 No 🗌 16. Were all holding times able to be met? (If no, notify customer for authorization.) Checked by: Special Handling (if applicable) Yes 🗌 No 🗍 NA 🗹 17. Was client notified of all discrepancies with this order? Person Notified: Date: eMail Phone Fax In Person By Whom: Regarding: Client Instructions: 18. Additional remarks: 19 Cooler Information Cooler No Temp C Condition Seal Intact Seal No Seal Date Good

Turn-Around Time: **Chain-of-Custody Record** HALL ENVIRONMENTAL Client: BLAGG ENGINEZRING INC. X Standard □ Rush **ANALYSIS LABORATORY** BP AMERICA

Mailing Address: P.O. Box 27 Project Name: www.hallenvironmental.com FLORANCE C LS 13 4901 Hawkins NE - Albuquerque, NM 87109 BLOOMFIELD NM 87413 Project #: Tel. 505-345-3975 Fax 505-345-4107 Analysis Request Phone #: 505-632-1199 Project Manager: BTEX + MTBE + TPH (Gas only) TPH Method 8015B (Gas/Diesel) email or Fax#: Anions (F,CI,NO3,NO2,PO4,SO4) **TME**'s (8021) PCB's QA/QC Package: J. BLAGO Standard ☐ Level 4 (Full Validation) Sampler: J. B.AL 6 8081 Pesticides / 8082 Accreditation □ NELAP: □ Other _____ 8270 (Semi-VOA) Bubbles (Yor RCRA 8 Metals Sample Temperature ☐ EDD (Type) BTEX CENTRA 8260B (VOA) Container Preservative Sample Request ID Date Matrix Time Type and # Type 21 BG+ 5-pt@4 402 x1 1355 SOIL COOL Received by: Remarks: GRO + BLO ON 9015 28/12 1245 241 July 3/28/12 1245 N 1535941 ZVALENOLAB

₹,



