District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

	Pit,	<u>Bel</u>	ow-	<u>Grade</u>	e Tanl	k, or
1 A 1	, n	Æ .1	1 70			1

12411 Proposed Alternative Method Permit or Closure Plan Application	CONS. DIV DIST. 3
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, belo or proposed alternative method	DEC 0 1 2014 w-grade tank,
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative and Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules.	ground water or the
Operator: BP America Production CompanyOGRID #:778	
Address:200 Energy Court, Farmington, NM 87401	
Facility or well name:Martinez Gas Com H 1	
API Number:3004521311OCD Permit Number:	
U/L or Qtr/Qtr N Section 32 Township 32N Range 10W County: San Juan	
Center of Proposed Design: Latitude36.937474 Longitude107.909736 NAI Surface Owner: Federal State Private Tribal Trust or Indian Allotment	
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: □ Drilling □ Workover □ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management □ Low Chloride Drilling Fluid □ Lined □ Unlined □ Liner type: Thicknessmil □ LLDPE □ HDPE □ PVC □ Other □ String-Reinforced	
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x	WX D
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A Volume:21.0bbl Type of fluid:Produced water Tank Construction material:Steel Secondary containment with leak detection □ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off □ Visible sidewalls and liner □ Visible sidewalls only □ Other _Single walled/double bottomed; side walls not vi	isible
Liner type: Thicknessmil ☐ HDPE ☐ PVC ☐ Other	
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for considerations.	ideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)							
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,						
Four foot height, four strands of barbed wire evenly spaced between one and four feet							
Alternate. Please specify	**						
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)							
Screen Netting Other							
Monthly inspections (If netting or screening is not physically feasible)							
7. Signs: Subsection C of 19.15.17.11 NMAC							
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers							
Signed in compliance with 19.15.16.8 NMAC							
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.							
Please check a box if one or more of the following is requested, if not leave blank: ☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. ☐ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.							
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source						
General siting							
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA						
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No						
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No						
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No						
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No						
Below Grade Tanks							
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)							
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	NMAC 15.17.9 NMAC
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached,	documents are
☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Climatological Factors Assessment	
☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC	
Quality Control/Quality Assurance Construction and Installation Plan	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan	
Emergency Response Plan	
Oil Field Waste Stream Characterization	
Monitoring and Inspection Plan	
☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Closure Tian Cased upon the appropriate requirements of Guissection C of 19.13.17.9 MMAC and 19.13.17.13 MMAC	
Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit
☐ Alternative	rana management i
Proposed Closure Method: Waste Excavation and Removal	
Waste Removal (Closed-loop systems only)On-site Closure Method (Only for temporary pits and closed-loop systems)	
In-place Burial On-site Trench Burial	
Alternative Closure Method	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC	
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.	☐ Yes ☐ No
- NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	
Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 200 feet of a wetland	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

	Yes No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map	Yes No
Within a 100-year floodplain. - FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plant a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	
Name (Print): Title:	
Signature: Date:	
e-mail address:	
18.	
OCD Approval: Permit Application (including closure plan) M Closure Plan (only) OCD Conditions (see attachment)	J_{L}
OCD Representative Signature: Approval Date: 12/12	1/14
OCD Representative Signature: Approval Date: 12/12	2)14
OCD Representative Signature: Approval Date: 12/12	the closure report.
OCD Representative Signature: Title: OCD Permit Number: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not	the closure report.
OCD Representative Signature: Title: DUS Jones L. OCD Permit Number: OCD Permit Number: Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	complete this

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure	
belief. I also certify that the closure complies with all applicable closure requirer	nents and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Joff Pone	Date:November 25, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Martinez Gas Com H 1 API No. 3004521311 Unit Letter N, Section 32, T32N, R10W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)

- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and will be reclaimed since the well was recently plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT will be reclaimed as part of final reclamation since the well was recently plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT will be reclaimed as part of final reclamation since the well was recently plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT will be reclaimed as part of final reclamation since the well was recently plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation since the well was recently plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-141 Revised August 8, 2011

Release Notification and Corrective Action												
						OPERA	ΓOR		☐ Initia	al Report	\boxtimes	Final Report
Name of Co						Contact: Jef	f Peace					
		Court, Farm		M 87401			No.: 505-326 - 94					
Facility Nar	ne: Martir	nez Gas Com	H 1			Facility Typ	e: Natural gas v	vell				
Surface Ow	ner: Priva	te		Mineral C	wner:	Private			API No	. 30045213	311	
				LOCA	TIOI	N OF REI	LEASE					
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	East/V	Vest Line	County: Sa	an Juan	
N	32	32N	10W	1,150	South		1,460	West				
		Latit	ude36	.937474		_ Longitud	e107.909736_					
				NAT	URE	OF REL	EASE					
Type of Rele							Release: N/A			Recovered: N		
		w grade tank –	21 bbl				our of Occurrenc	e:	Date and	Hour of Dis	covery:	
Was Immedia	ate Notice (Yes [No 🛛 Not Re	equired	If YES, To	Whom?					
By Whom?						Date and H	our					
Was a Water	course Read	ched?					lume Impacting t	he Wate	ercourse.			
			Yes 🛚	No		, , ,	······································					
If a Watercou	irse was Im	pacted, Descr	ibe Fully.*									
		•	-									
				n Taken.* Sampli and chloride belov					g removal	to ensure no	soil im	pacts from
				en.* BGT was resince the well was				T was s	ampled. T	ne excavated	l area v	vas
regulations al public health should their o or the environ	I operators or the envi perations h nment. In a	are required to ronment. The nave failed to a	o report an acceptance dequately CD accep	is true and comp ad/or file certain rule of a C-141 repo investigate and ru tance of a C-141	elease no rt by the emediate	otifications ar e NMOCD m e contaminati	nd perform correctarked as "Final Room that pose a three	tive acti eport" d eat to gr	ons for rele oes not reli ound water	eases which eve the oper surface wa	may en ator of ter, hur	ndanger Tliability man health
A	• 0	Ω					OIL CONS	SERV	ATION	DIVISIO	N	
Signature:	Ilh	Pasel	/									
Printed Name	v Jeff Peac	e				Approved by	Environmental S _I	pecialist	:			
		tal Coordinato	г	-		Approval Dat	e.		Expiration	Date:		
									zipiration .			
E-mail Addre	ss: peace.j	effrey@bp.com	n			Conditions of	`Approval:			Attached		
Date: Noven	ber 25, <u>20</u>	14	Pho	ne: 505-326-9479	<u> </u>							

^{*} Attach Additional Sheets If Necessary

GHENE BP	1	GINEERING, INC. OOMFIELD, NM 87	7.4.4.2	API#: 3004521311						
CLIENT:	1	5) 632-1199	413	TANK ID (if applicble):						
FIELD REPORT:	(circle one): BGT CONFIRMATION /	RELEASE INVESTIGATION / OTHER:		PAGE #: 1 of 1						
SITE INFORMATION	J: SITE NAME: MARTIN	EZ GC H #1		DATE STARTED: 11/13/13						
QUAD/UNIT: N SEC: 32 TWP:	D/UNIT: N SEC: 32 TWP: $32N$ RNG: $10W$ PM: NM CNTY: SJ ST: NN									
1/4-1/4/FOOTAGE: 1,150'S / 1,46	D'W SE/SW LEASE TY		INDIAN	ENVIRONMENTAL						
LEASE #:	PROD. FORMATION: PC COM	CROSSFIRE NTRACTOR: MBF - T. PETE	RSON	SPECIALIST(S): JCB						
REFERENCE POINT	Γ: WELL HEAD (W.H.) GPS (COORD.: 36.93779 X	107.90995	GL ELEV: 6,079'						
1) 21 BGT (SW/DB)				ARING FROM W.H.: 126', S27E						
2)	GPS COORD.:		_ DISTANCE/BE	ARING FROM W.H.:						
3)	GPS COORD.:		DISTANCE/BE	ARING FROM W.H.:						
4)	GPS COORD.:		_ DISTANCE/BE							
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR	LAB USED: HALL		OVM READING (ppm)						
1) SAMPLE ID: 21 BGT. 5-pt. @ \$	5' SAMPLE DATE: 11/13/13	SAMPLE TIME: 0925 LAB AN	ALYSIS: 418.1/ 8	3015B/8021B/300.0(CI) 4.2						
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANA	ALYSIS:							
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB AN/	ALYSIS:							
4) SAMPLE ID:										
SOIL DESCRIPTION SOIL COLOR: DARKY	SOIL TYPE: SAND / SILTY S	SAND SILT / SILTY CLAY / CLAY /	GRAVEL / OT	HER						
COHESION (ALL OTHERS): NON COHESIVE (SLIGHTL		PLASTICITY (CLAYS): NON PLASTIC / S	SLIGHTLY PLASTIC / (COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC						
CONSISTENCY (NON COHESIVE SOILS): Le	OOSE FIRM / DENSE / VERY DENSE	1		/ FIRM / STIFF / VERY STIFF / HARD						
MOISTURE: DRY SLIGHTLY MOIST MOIST / W SAMPLE TYPE: GRAB COMPOSITE		HC ODOR DETECTED: YE	S NO EXPL	ANATION -						
DISCOLORATION/STAINING OBSERVED										
ANY AREAS DISPLAYING WETNESS: YES / NO										
APPARENT EVIDENCE OF A RELEASE OF ADDITIONAL COMMENTS: GAS WELL										
SOIL IMPACT DIMENSION ESTIMATION DEPTH TO GROUNDWATER: >100' N				IMATION (Cubic Yards): NA D TPH CLOSURE STD: 5,000 ppm						
SITE SKETCH	⊕ P&A	PLOT PLAN circle: a	nttached 0VM	CALIB. READ. = 101.0 ppm RF = 1.00						
	MARKER		↑ ow	CALIB. GAS =ppm						
			N TIME	8:30 ampm DATE: <u>11/13/13</u>						
			'┌	MISCELL. NOTES						
			<u> </u>	/ 0:						
)	O#:						
				k: ZFEIRKOSJS						
	PBGTL		_	J#:						
	T.B. ~ 5'	(X)	1 -	ermit date(s): 06/14/10 CD Appr. date(s): 08/21/13						
	~~		Tar	k OVM = Organic Vapor Meter						
			<u> </u>							
		X - S.P.	D. 🗀	BGT Sidewalls Visible: Y / N						
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATI		OW; T.H. = TEST HOLE; ~ = APPROX.; W.H. = V	VELL HEAD;	BGT Sidewalls Visible: Y / N						
	LOW-GRADE TANK LOCATION;		NA-NOT <u>N</u>	lagnetic declination: 10° E						
NOTES:	O	ONSITE: 11/13/13	3							

Analytical Report

Lab Order 1311621

Date Reported: 11/22/2013

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Project: Matinez GC H#1

Lab ID: 1311621-001

Client Sample ID: 21 BGT 5-pt@5'

Collection Date: 11/13/2013 9:25:00 AM

Received Date: 11/14/2013 10:00:00 AM

Analyses	Result	RL Qu	ıal Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	SE ORGANICS				Analy	st: BCN
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	11/15/2013 12:42:44	PM 10337
Surr: DNOP	97.8	66-131	%REC	1	11/15/2013 12:42:44	PM 10337
EPA METHOD 8015D: GASOLINE RA	ANGE				Analy	st: NSB
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	11/16/2013 4:36:12	AM 10349
Surr: BFB	93.7	74.5-129	%REC	1	11/16/2013 4:36:12 A	M 10349
EPA METHOD 8021B: VOLATILES					Analy	st: NSB
Benzene	ND	0.047	mg/Kg	1	11/16/2013 4 :36:12 A	M 10349
Toluene	ND	0.047	mg/Kg	1	11/16/2013 4:36:12	M 10349
Ethylbenzene	ND	0.047	mg/Kg	1	11/16/2013 4:36:12 A	M 10349
Xylenes, Total	ND	0.093	mg/Kg	1	11/16/2013 4:36:12 A	M 10349
Surr: 4-Bromofluorobenzene	109	80-120	%REC	1	11/16/2013 4:36:12 A	M 10349
EPA METHOD 300.0: ANIONS					Analy	st: JRR
Chloride	ND	1.5	mg/Kg	1	11/18/2013 8:51:49 F	M 10359
EPA METHOD 418.1: TPH					Analy	st: BCN
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	11/19/2013	10341

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Ε Value above quantitation range
- Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- Not Detected at the Reporting Limit ND

- Sample pH greater than 2 for VOA and TOC only. P
- RL Reporting Detection Limit

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1311621

22-Nov-13

Client:

Blagg Engineering

Project:

Matinez GC H #1

Sample ID MB-10359

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

11/15/2013

Batch ID: 10359

PQL

RunNo: 14851

Analysis Date: 11/15/2013

SeqNo: 428021

Units: mg/Kg

Analyte

Prep Date:

Result

SPK value SPK Ref Val %REC LowLimit

HighLimit

RPDLimit

Qual

Chloride

ND 1.5

Sample ID LCS-10359

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

Prep Date: 11/15/2013

Batch ID: 10359

Analysis Date: 11/15/2013

RunNo: 14851

%REC

SeqNo: 428022

Units: mg/Kg

%RPD

%RPD

Qual

Analyte

PQL Result

SPK value SPK Ref Val

90

LowLimit

HighLimit

RPDLimit

1.5

14 15.00 95.8 Chloride

110

Qualifiers:

Value exceeds Maximum Contaminant Level.

Spike Recovery outside accepted recovery limits

Value above quantitation range Е

Analyte detected below quantitation limits

RSD is greater than RSDlimit

RPD outside accepted recovery limits R

Analyte detected in the associated Method Blank В

Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

Reporting Detection Limit

Н

Page 2 of 6

OC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1311621

22-Nov-13

Client:

Blagg Engineering

Project:

Matinez GC H #1

Sample ID MB-10341

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID: **PBS**

Batch ID: 10341

PQL

RunNo: 14899

Prep Date: 11/14/2013 Analysis Date: 11/19/2013

SeqNo: 429708

HighLimit

Units: mg/Kg

Analyte

RPDLimit Qual

Petroleum Hydrocarbons, TR

Result

ND 20

Sample ID LCS-10341

SampType: LCS

TestCode: EPA Method 418.1: TPH

Client ID:

LCSS

Batch ID: 10341

RunNo: 14899

TestCode: EPA Method 418.1: TPH

SeqNo: 429709

Units: mg/Kg

Analyte

Prep Date: 11/14/2013

Analysis Date: 11/19/2013

%REC

HighLimit LowLimit

%RPD

%RPD

Petroleum Hydrocarbons, TR

PQL 20

SPK value SPK Ref Val 100.0

104

80 120 **RPDLimit**

Qual

Sample ID LCSD-10341

Client ID: LCSS02

SampType: LCSD Batch ID: 10341

20

SPK value SPK Ref Val %REC LowLimit

RunNo: 14899 SeqNo: 429710

Units: mg/Kg

Qual

Analyte Petroleum Hydrocarbons, TR

Prep Date: 11/14/2013

Analysis Date: 11/19/2013 Result

100

Result

100

SPK value SPK Ref Val 100.0

%REC 0

104

LowLimit

HighLimit 120 %RPD 0

RPDLimit 20

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits

Spike Recovery outside accepted recovery limits

RSD is greater than RSDlimit 0

RPD outside accepted recovery limits R

В

Analyte detected in the associated Method Blank Н Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

Page 3 of 6

Reporting Detection Limit

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1311621

22-Nov-13

Client:

Blagg Engineering

Project:

Matinez GC H #1

Sample ID LCS-10337	SampType: LCS			Tes	TestCode: EPA Method 8015D: Diesel Range Organics						
Client ID: LCSS	Batch	1D: 10	337	F	RunNo: 1	4826					
Prep Date: 11/14/2013	Analysis D	ate: 1	1/15/2013	8	SeqNo: 4	27453	Units: mg/K	(g	•		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Diesel Range Organics (DRO)	44	10	50.00	0	87.4	62.1	127				
Surr: DNOP	4.4		5.000		87.3	66	131				

Sample ID MB-10337 SampType: MBLK Client ID: PBS Batch ID: 10337			TestCode: EPA Method 8015D: Diesel Range Organics											
			F	RunNo: 1	4826									
Prep Date: 11/14/2013	Analysis Date: 11/15/2013			SeqNo: 427454			Units: mg/Kg							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Diesel Range Organics (DRO)	ND	10												
Surr: DNOP	8.2		10.00		81.6	66	131							

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 4 of 6

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1311621

22-Nov-13

Client:

Blagg Engineering

Project:

Analyte

Analyte

Matinez GC H #1

Sample ID MB-10349

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

PBS Client ID:

RunNo: 14837

Prep Date: 11/14/2013

Batch ID: 10349 Analysis Date: 11/15/2013

PQL

5.0

SPK value SPK Ref Val

1000

SeqNo: 427700

74.5

LowLimit

LowLimit

Units: mg/Kg

129

HighLimit

RPDLimit Qual

Gasoline Range Organics (GRO)

ND 900

Result

89.8

Surr: BFB

Sample ID LCS-10349

SampType: LCS

TestCode: EPA Method 8015D: Gasoline Range

%REC

Client ID: LCSS

Batch ID: 10349

RunNo: 14837

Prep Date: 11/14/2013

Analysis Date: 11/15/2013

SeqNo: 427707 %REC

Units: mg/Kg

HighLimit Qual

%RPD

Gasoline Range Organics (GRO) Surr: BFB

Result **PQL** SPK value SPK Ref Val 25 5.0 25.00 980 1000

99.2 98.0 74.5 74.5

126 129

%RPD **RPDLimit**

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range Е

J Analyte detected below quantitation limits

0 RSD is greater than RSDlimit

RPD outside accepted recovery limits R

Spike Recovery outside accepted recovery limits

В Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Η

Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

Reporting Detection Limit RL

Page 5 of 6

OC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1311621

22-Nov-13

Client:

Blagg Engineering

Project:

Matinez GC H #1

Sample ID MB-10349 MK

SampType: MBLK

TestCode: EPA Method 8021B: Volatiles

80

Client ID:

PBS

Batch ID: R14837

RunNo: 14837

Prep Date:

Analysis Date: 11/15/2013

SeqNo: 427778

Units: %REC

PQL

Analyte

Result

SPK value SPK Ref Val %REC LowLimit

%RPD

%RPD

RPDLimit Qual

Surr: 4-Bromofluorobenzene

1.1

1.000

107

HighLimit 120

Sample ID LCS-10349 MK

SampType: LCS

TestCode: EPA Method 8021B: Volatiles

Client ID:

LCSS

Batch ID: R14837

RunNo: 14837 SeqNo: 427779

Units: %REC

Analyte

Prep Date: Analysis Date: 11/15/2013

LowLimit

Qual

Surr: 4-Bromofluorobenzene

PBS

Result 1.1

ND

ND

ND

1.1

1.0

1.0

SPK value SPK Ref Val 1.000

%REC 113

HighLimit 120 **RPDLimit**

Client ID:

Prep Date:

Sample ID MB-10349

SampType: MBLK Batch ID: 10349

TestCode: EPA Method 8021B: Volatiles

RunNo: 14837

Result **PQL**

ND 0.050

Analysis Date: 11/15/2013

SeqNo: 427782 SPK value SPK Ref Val %REC LowLimit

Units: mg/Kg HighLimit

%RPD **RPDLimit**

Qual

Analyte Benzene Toluene

Ethylbenzene Xylenes, Total

11/14/2013

0.050 0.050

0.10

1.000

120

Sample ID LCS-10349

Surr: 4-Bromofluorobenzene

LCSS

SampType: LCS

Batch ID: 10349

1.000

1.000

TestCode: EPA Method 8021B: Volatiles

107

RunNo: 14837

LowLimit

80

80

80

HighLimit

120

120

120

120

120

Prep Date: 11/14/2013 Analyte Benzene

Client ID:

Analysis Date: 11/15/2013 Result **PQL**

0.050

0.050

SeqNo: 427783

0

0

0

0

Units: mg/Kg

%RPD **RPDLimit** Qual

Toluene Ethylbenzene Xylenes, Total

Surr: 4-Bromofluorobenzene

1.1 0.050 1.000 3.2 0.10 3.000 1.1 1.000

SPK value SPK Ref Val

105 105 113

%REC

101

104

80 80 80

Qualifiers:

J

Value exceeds Maximum Contaminant Level.

Analyte detected below quantitation limits

Spike Recovery outside accepted recovery limits

- Value above quantitation range E
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R

- Analyte detected in the associated Method Blank В
- Н Holding times for preparation or analysis exceeded
- Not Detected at the Reporting Limit Sample pH greater than 2 for VOA and TOC only.
- RLReporting Detection Limit

Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

BLAGG Client Name: Work Order Number: 1311621 RcptNo: 1 Received by/date: Logged By: Ashley Gallegos 11/14/2013 10:00:00 AM Completed By: **Ashley Gallegos** 1,1/14)2013 2:05:58 PM 11/14/13 Reviewed By: Chain of Custody Not Present ✓ 1. Custody seals intact on sample bottles? No Yes 2. Is Chain of Custody complete? No : Not Present Yes IV 3. How was the sample delivered? Courier Log In No 🗔 NA [...] 4. Was an attempt made to cool the samples? Yes 🛂 NA 1 5. Were all samples received at a temperature of >0° C to 6.0°C 6. Sample(s) in proper container(s)? 7. Sufficient sample volume for indicated test(s)? No 8. Are samples (except VOA and ONG) properly preserved? Yes 🗸 No L Yes 📋 9. Was preservative added to bottles? No V NA . : Yes 10. VOA vials have zero headspace? No L No VOA Vials Yes 🛄 11. Were any sample containers received broken? No # of preserved bottles checked 12. Does paperwork match bottle labels? for pH: No (Note discrepancies on chain of custody) (<2 or >12 unless noted) Adjusted? No 13. Are matrices correctly identified on Chain of Custody? Nο 14. Is it clear what analyses were requested? Checked by: 15. Were all holding times able to be met? No (If no, notify customer for authorization.) Special Handling (if applicable) Yes NA 🗸 16. Was client notified of all discrepancies with this order? No Person Notified: Date: By Whom: Via: eMail Phone In Person Fax Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Cooler No Temp C Condition Seal Intact | Seal No Good

Client: BLAGG Engineering INC.			Standard □ RushProject Name:				L	- 60										NTA TO		
Client: BLAGG Engineering INC. BP AMERICA Mailing Address: P.O. Box 87																		1 42 1		
		MARTINEZ GC H #1					www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109													
ī	SLOOMF	IELS N	M 97413	Project #:							5-34			Fax						
			z· 1199																	e e de la companya de
	rFax#:			Project Mana	iger:			_	<u>رک</u>											
QA/QC Package: Standard □ Level 4 (Full Validation)		J- BLAGG					(Gas ol	科 (0)		(4)	CINIO	PO ₄ ,S(PCB's	:						
Accreditation		Sampler: J - BLAGE					王	<u>P</u>	=			Š,	082							
□ NELAP □ Other		Onice Yes Exco				于耶路 (8021)	 	8	118.	8 8	S	l os	8 / S		8					
J EDD	(Type)	<u> </u>		Sample (Gri	perature:			帽	置	9	pog (<u> </u>	eta 2	N,C	cide	<u>₹</u>	-i=	اليا		
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type			BTEX +************************************	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO / DRO / 本語の)	TPH (Method 418.1)	EDB (Method 504.1)	RCRA 8 Metals	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	CHURIDE		
12013	0925	Soil	21 BGT 5-pt 0.5	4 02 ×1	COOL		01	×	-		×			Ì	-			×		
_											1		1							
										_										
										一		十	T	<u> </u>	-				_	
							-			一	\dashv	\top	\dagger	-					1	
								\neg	\dashv	\neg	_	_	╁	<u> </u>						1
				 						\neg		\top			_					
									1	十	十			 					_	+
		<u>, , , , , , , , , , , , , , , , , , , </u>								\neg	-		+							
										\dashv	+		+-					\dashv		\vdash
										_			+							
								+	\dashv		\dashv	\dashv	+					\dashv		+
ate:	Time: 1153			Received by:	Received by: Date Time 11/13/2013 1153				Remarks: BILL BP PARKEY: ZFEIRKOSJS											
ate:	Time:	Relinquishe	otrele meters	Received by:	<u> </u>		ime (///)						JEF				•			



