<u>District 1</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy

Form C-144

Revised June 6, 2013

Santa Fe, NM 87505 to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or	
12404 Proposed Alternative Method Permit or Closure Plan Application	
Type of action: Below grade tank registration OIL CONS. DIV DIS	T. 3
Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration NOV 2 4 2014	
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method	
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request	
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the	
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinal	nces.
Operator: BP America Production CompanyOGRID #:778	
Address:200 Energy Court, Farmington, NM 87401	
Facility or well name:Sammons Gas Com A 1A	
API Number:3004522135OCD Permit Number:	
U/L or Qtr/Qtr PSection 6 Township 31N Range 10W County: San Juan	
Center of Proposed Design: Latitude36.922558 Longitude107.918862 NAD: ☐1927 ☒ 1983	
Surface Owner: Federal State Private Tribal Trust or Indian Allotment	
Pit: Subsection F, G or J of 19.15.17.11 NMAC	
Temporary: Drilling Workover	
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no	
☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other	
☐ String-Reinforced	
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D	
3.	
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A	
Volume:95.0bbl Type of fluid:Produced water	
Tank Construction material:Steel	
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	
☐ Visible sidewalls and liner ☑ Visible sidewalls only ☐ Other _Single walled/double bottomed	
Liner type: Thicknessmil	
4.	\equiv
Alternative Method:	
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	.



Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet	hospital,
Alternate. Please specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Page 2 of 6

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Natructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Authors and Compatibility Assessment Quality Control/Quality Assurance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Inspection Plan Operating and Inspection Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Closure Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) based upon the appropriate requirements of Schools and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC	attached to the
 □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	rce material are Please refer to
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.	
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	Yes ☐ No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.1 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.1 Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards canno Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	1 NMAC 5.17.11 NMAC
17.	
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belie	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address:	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	
OCD Representative Signature: Approval Date:	
Title: OCD Permit Number:	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting to the closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not a section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
☐ Closure Completion Date:2/18/2013	
Closure Completion Date:2/18/2013 20. Closure Method: ☐ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-loo ☐ If different from approved plan, please explain.	op systems only)

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure requires	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Name (Print):Jeff Peace Signature:	Date:November 24, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Sammons Gas Com A 1A API No. 3004522135 Unit Letter P, Section 6, T31N, R10W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	23
Chlorides	US EPA Method 300.0 or 4500B	250 or background	24

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Revised August 8, 2011

Form C-141

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notifi	catio:	n and Co	orrective A	etion				
						OPERA'	ГOR		☐ Initi	al Report	\boxtimes	Final Repor
Name of C	ompany: B	P				Contact: Jef	f Peace					
Address: 20	00 Energy	Court, Farmi	ington, N	M 87401		Telephone 1	No.: 505-326-94	479				
Facility Na	me: Samm	ons Gas Cor	n A 1A			Facility Typ	e: Natural gas v	well				
Surface Ov	vner: Priva	te		Mineral	Owner:	Private			API No	o. 3004522	135	
				LOC	ATIO	N OF REI	LEASE		-			
Unit Letter	Section	Township	Range	Feet from the		/South Line	Feet from the	East/W	est Line	County: S	San Juar	n
Р	6	31N	10W	830	South		1,000	East				
		Lati	tude 36	.922558		_ Longitude	107.918862_					
				NA	TURE	OF RELI	 E ase					
Type of Rele	ease: none			1111			Release: N/A	T	Volume F	Recovered:	N/A	
		v grade tank –	- 95 bbl				lour of Occurrence	ce:		Hour of Di		
	Was Immediate Notice Given?						Whom?					
			Yes [No 🛛 Not F	Required							
By Whom?		_				Date and H	lour		***			
Was a Water	course Read					If YES, Vo	lume Impacting t	the Water	rcourse.			
			Yes 🛚	No								
If a Waterco	urse was Im	pacted, Descri	ibe Fully.*			<u> </u>						
		•	•									
D 11 0	CD 11	1.0	11 1 4	<u></u>		9.1						
the BGT So	il analysis r	em and Remed	dial Actioi H RTEY	1 Taken.* Sampl	ing of th	e soil beneath	the BGT was do	ne during abad	g removal	to ensure no	soil in	ipacts from
the BOT. Se	ni anaiysis i	csuited iii 11 i	ii, bila	and emonde bei	ow stand	aius. Aliaiys	is resurts are atta	ciicu.				
<u>.</u>												
					emoved a	and the area u	nderneath the BG	iT was sa	mpled. T	he area und	er the B	GT was
backfilled an	d compacted	and is still w	ithin the a	ctive well area.								
I hereby certi	ify that the i	nformation gi	ven above	is true and comp	olete to the	he best of my	knowledge and u	nderstan	d that purs	suant to NM	OCD rı	ules and
							d perform correc					
							arked as "Final R					
							on that pose a three the operator of i					
		vs and/or regu	-	tance of a C-141	report u	oes not renev	the operator of i	responsit	ility for Co	omphance v	vitii airy	oulei
1000101, 20000	Λ 4	\wedge		•			OIL CONS	SERV	ATION	DIVISIO)N	
	10/0	Va - 0			i		OIL COIN	<u>DLIC VI</u>	111011	DIVIDIO	211	
Signature:	Y	Jack										
Printed Name	<i>U ∥ V</i> e: Teff Peace	.				Approved by	Environmental S _l	pecialist:				
Timed Name	c. Jeli i cacc											
Title: Field E	Environment	al Coordinato	r			Approval Dat	e:	E	xpiration l	Date:		
m		cc C'				0 11.1						
E-mail Addre	ess: peace.je	ffrey@bp.con	n			Conditions of	Approval:			Attached		
Date: Noven	nber 24, 201	4	Pho	ne: 505-326-947	9							

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, BL	GINEERING, II OOMFIELD, N) 632-1199		API #:300 TANK ID (if applicble):	045221 A	135
FIELD REPORT:	(circle one): BGT CONFIRMATION / R		OTHER:	PAGE #:	_	1
SITE INFORMATION	I: SITE NAME: SAMMON	IS GC A #1A		DATE STARTED:	02/07	7/13
QUAD/UNIT: P SEC: 6 TWP:			st: NM	DATE FINISHED:		
1/4 -1/4/FOOTAGE: 830'S/1,000'W	SE/SE LEASE TYP		FEE INDIAN	ENVIRONMENTAL		
LEASE#: -	PROD. FORMATION: MV CON	EL KHOR	N		<u>NJ</u>	V
REFERENCE POINT				GLEU	FV: 5.8	 RAQ'
1) 95 BGT (SW/DB)				EARING FROM W.H.:	4701 07	
2)						
3)						
4)	GPS COORD.:		DISTANCE/BE	ARING FROM W.H.:		
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR L	AB USED: HA	LL			OVM READING
1) SAMPLE ID:	J			8015B/8021B/30	00.0(CI)	(ppm) NA
2) SAMPLEID:						
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:			
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:			
SOIL COLOR: MODERATE BROWN COHESION (ALL OTHERS): NON COHESIVE SUGHTLY CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY SLIGHTLY MOIST MOIST / M SAMPLE TYPE: GRAB COMPOSITE # DISCOLORATION/STAINING OBSERVED ANY AREAS DISPLAYING WETNESS: YES NO APPARENT EVIDENCE OF A RELEASE C ADDITIONAL COMMENTS: BGT PLACE	DOSE / FIRM DENSE / VERY DENSE ET / SATURATED / SUPER SATURATED OF PTS5 : YES NO EXPLANATION EXPLANATION BSERVED AND/OR OCCURRED: YES	DENSITY (COHESIVE HC ODOR DETECT		T / FIRM / STIFF / VER ANATION -	Y STIFF / HA	RD
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER:<100' N		t. X <u>NA</u> ft. NEAREST SURFACE WATER		FIMATION (Cubic Ya		NA _ ppm
	TO COMPR. TO W. PBGTL. I.B. ~ 6' B.G.	0	N OW	MISCELL VO: N15658 O #: K: ZEVH01 U #: Z2-0069 ermit date(s): ICD Appr. date(s):	DATE: NOTE 81 BGT2 00-C 06/14/109/17/1	10 12
	SEP. ON DEPRESSION; B.G. = BELOW GRADE; B = BELOV OW-GRADE TANK LOCATION; SPD = SAMPLE POINT WALL; DW-DOUBLE WALL; SB - SINGLE BOTTOM	M, T.H. = TEST HOLE; ~ = APPROX. I DESIGNATION; R.W. = RETAININ I; DB - DOUBLE BOTTOM.	S.P.D. ; WH. = WELL HEAD; GWALL; NA- NOT 77/13	ppm = parts p	er million ible: Y / N ible: Y / N ible: Y / N	

Analytical Report

Lab Order 1302324

Date Reported: 2/18/2013

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 6' (95)

Project: SAMMONS GC A # 1A

Collection Date: 2/7/2013 2:05:00 PM

Lab ID: 1302324-001

Matrix: SOIL

Received Date: 2/9/2013 11:15:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	SE ORGANICS				Analyst: MMD
Diesel Range Organics (DRO)	ND	9.8	mg/Kg	1	2/12/2013 1:29:12 PM
Surr: DNOP	106	72.4-120	%REC	1	2/12/2013 1:29:12 PM
EPA METHOD 8015B: GASOLINE RA	ANGE				Analyst: NSB
Gasoline Range Organics (GRO)	ND	4.9	mg/Kg	1	2/12/2013 4:27:44 PM
Surr: BFB	109	84-116	%REC	1	2/12/2013 4:27:44 PM
EPA METHOD 8021B: VOLATILES					Analyst: NSB
Benzene	ND	0.049	mg/Kg	1	2/12/2013 4:27:44 PM
Toluene	ND	0.049	mg/Kg	1	2/12/2013 4:27:44 PM
Ethylbenzene	ND	0.049	mg/Kg	1	2/12/2013 4:27:44 PM
Xylenes, Total	ND	0.098	mg/Kg	1	2/12/2013 4:27:44 PM
Surr: 4-Bromofluorobenzene	110	80-120	%REC	1	2/12/2013 4:27:44 PM
EPA METHOD 300.0: ANIONS					Analyst: JRR
Chloride	24	7.5	mg/Kg	5	2/15/2013 10:21:44 AM
EPA METHOD 418.1: TPH					Analyst: ECH
Petroleum Hydrocarbons, TR	23	20	mg/Kg	1	2/13/2013 2:30:00 PM

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2
- RL Reporting Detection Limit

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits

Hall Environmental Analysis Laboratory, Inc.

WO#:

1302324

18-Feb-13

Client:

Blagg Engineering

Project:

SAMMONS GC A # 1A

Sample ID MB-6135

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID: PBS

Batch ID: 6135

RunNo: 8675

Prep Date: 2/15/2013

Analysis Date: 2/15/2013

SeqNo: 249146

Units: mg/Kg

HighLimit

%RPD

RPDLimit Qual

Analyte Chloride

Result **PQL** ND 1.5

Sample ID LCS-6135

SampType: LCS Batch ID: 6135 TestCode: EPA Method 300.0: Anions RunNo: 8675

Prep Date: 2/15/2013

LCSS

Analysis Date: 2/15/2013

SeqNo: 249147

Units: mg/Kg

Analyte

Client ID:

SPK value SPK Ref Val %REC

%RPD

Qual

Result

15.00

0

SPK value SPK Ref Val %REC LowLimit

RPDLimit

Chloride

110

1.5

97.9

LowLimit

HighLimit

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range Е

Analyte detected below quantitation limits Sample pH greater than 2

Analyte detected in the associated Method Blank В

Н Holding times for preparation or analysis exceeded Not Detected at the Reporting Limit

RPD outside accepted recovery limits

Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1302324

18-Feb-13

Client:

Blagg Engineering

Project:

SAMMONS GC A # 1A

Sample ID MB-6092

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID:

PBS

Batch ID: 6092

PQL

20

RunNo: 8631

Prep Date: 2/12/2013 Analysis Date: 2/13/2013 Result

ND

SeqNo: 248031

Units: mg/Kg HighLimit

%RPD

RPDLimit Qual

Analyte Petroleum Hydrocarbons, TR

SampType: LCS

7.660

SPK value SPK Ref Val %REC

SPK value SPK Ref Val

100.0

100.0

TestCode: EPA Method 418.1: TPH

LowLimit

Client ID:

Analyte

LCSS

Batch ID: 6092

PQL.

20

RunNo: 8631

Prep Date: 2/12/2013

Petroleum Hydrocarbons, TR

Sample ID LCS-6092

Result

110

110

Analysis Date: 2/13/2013

SeqNo: 248032 %REC

98.1

Units: mg/Kg

120

LowLimit HighLimit **RPDLimit** Qual

Qual

Sample ID LCSD-6092

SampType: LCSD

TestCode: EPA Method 418.1: TPH

LCSS02

Batch ID: 6092

RunNo: 8631

Prep Date: 2/12/2013

Analysis Date: 2/13/2013

SeqNo: 248033

Units: mg/Kg

HighLimit

Analyte Petroleum Hydrocarbons, TR

Client ID:

Result SPK value SPK Ref Val

20

%REC 7.660

99.4

LowLimit

80

120

%RPD 1.24

%RPD

RPDLimit

20

Qualifiers:

Value exceeds Maximum Contaminant Level.

Ė Value above quantitation range

Analyte detected below quantitation limits 1

Sample pH greater than 2

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

RPD outside accepted recovery limits

ND Not Detected at the Reporting Limit Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

4.8

WO#: 1302324

18-Feb-13

Client:

Blagg Engineering

Project:

Surr: DNOP

SAMMONS GC A # 1A

Sample ID MB-6070	SampТуре: МВLК	SampType: MBLK TestCode: EPA Method 8015B: Diesel Range Organics							
Client ID: PBS	Batch ID: 6070	RunNo: 8570							
Prep Date: 2/11/2013	Analysis Date: 2/11/2013	SeqNo: 246528 Units: mg/Kg							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual							
Diesel Range Organics (DRO)	ND 10								
Surr: DNOP	10 10.00	100 72.4 120							
Sample ID LCS-6070	SampType: LCS	TestCode: EPA Method 8015B: Diesel Range Organics							
Client ID: LCSS	Batch ID: 6070	RunNo: 8570							
Prep Date: 2/11/2013	Analysis Date: 2/11/2013	SeqNo: 246529 Units: mg/Kg							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit HighLimit %RPD RPDLimit Qual							
Diesel Range Organics (DRO)	42 10 50.00	0 84.6 47.4 122							

96.5

72.4

120

5.000

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1302324

18-Feb-13

Client:

Blagg Engineering

Project:

Analyte

SAMMONS GC A # 1A

Sample ID MB-6071

SampType: MBLK

TestCode: EPA Method 8015B: Gasoline Range

Client ID: PBS

Batch ID: 6071

RunNo: 8602

Prep Date: 2/11/2013 Analysis Date: 2/12/2013

Units: mg/Kg

SeqNo: 247592

HighLimit

%RPD **RPDLimit** Qual

Gasoline Range Organics (GRO)

PQL 5.0

104

SPK value SPK Ref Val %REC LowLimit

84

62.6

84

Surr: BFB

1000

Result

ND

TestCode: EPA Method 8015B: Gasoline Range

116

Sample ID LCS-6071 Client ID: LCSS

SampType: LCS Batch ID: 6071

5.0

RunNo: 8602

Prep Date: 2/11/2013

Analysis Date: 2/12/2013

28

1200

SeqNo: 247593

Units: mg/Kg

HighLimit

%RPD

Analyte Gasoline Range Organics (GRO) Surr: BFB

Result PQL

SPK value SPK Ref Val 25.00 1000

1000

%REC LowLimit 113 118

136 116 **RPDLimit** Qual

S

Qualifiers:

Value exceeds Maximum Contaminant Level.

Е Value above quantitation range

Analyte detected below quantitation limits J

Sample pH greater than 2 P

Analyte detected in the associated Method Blank

RPD outside accepted recovery limits

Holding times for preparation or analysis exceeded Н

ND Not Detected at the Reporting Limit Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1302324

18-Feb-13

Client:

Blagg Engineering

Project:

SAMMONS GC A # 1A

Sample ID MB-6071	Samp ⁻	Гуре: МЕ	BLK	TestCode: EPA Method 8021B: Volatiles						
Client ID: PBS Batch ID: 6071 RunNo: 8602										
Prep Date: 2/11/2013	Analysis [Date: 2/	12/2013	S	SeqNo: 2	47629	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	1.0		1.000		105	80	120			

Sample ID LCS-6071	SampType: LCS Batch ID: 6071 Analysis Date: 2/12/2013			TestCode: EPA Method 8021B: Volatiles										
Client ID: LCSS				F										
Prep Date: 2/11/2013				S	SeqNo: 2	47630	Units: mg/h	(g						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Benzene	0.95	0.050	1.000	0	95.2	80	120							
Toluene	0.94	0.050	1.000	0	93.6	80	120							
Ethylbenzene	0.94	0.050	1.000	0	94.0	80	120							
Xylenes, Total	2.9	0.10	3.000	0	95.6	80	120							
Surr: 4-Bromofluorobenzene	1.1		1.000		113	80	120							

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

P Sample pH greater than 2

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

Page 6 of 6



4901 Hawkins NE Albuquerque, NM 87105 TEL: 505-345-3975 FAX: 505-345-410;

Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: **BLAGG** Work Order Number: 1302324 Received by/date: Logged By: Lindsay Mangin 2/9/2013 11:15:00 AM Completed By: 2/11/2013 8:48:13 AM Lindsay Mangin Reviewed By: Chain of Custody 1 Were seals intact? Yes 🗌 No 🔲 Not Present Yes V No Not Present 2. Is Chain of Custody complete? 3 How was the sample delivered? Courier Log In Yes 🔽 No 🗌 NA 🗌 4. Coolers are present? (see 19. for cooler specific information) Yes V No NA 🗆 5. Was an attempt made to cool the samples? Yes 🗹 No 🗌 NA 🗌 6. Were all samples received at a temperature of >0° C to 6.0°C Yes 🗸 No 🗌 7 Sample(s) in proper container(s)? Yes 🗹 No 🗌 8. Sufficient sample volume for indicated test(s)? Yes 🗹 No 🗌 9 Are samples (except VOA and ONG) properly preserved? Yes 🗌 No 🗹 NA 🗆 10. Was preservative added to bottles? Yes No No VOA Vials 🗹 11. VOA vials have zero headspace? Yes No 🗸 12. Were any sample containers received broken? # of preserved 13. Does paperwork match bottle labels? Yes 🔽 No 🗌 bottles checked (Note discrepancies on chain of custody) for pH: Yes 🗹 No 🗌 14. Are matrices correctly identified on Chain of Custody? (<2 or >12 unless noted) Adjusted? Yes 🗹 No 🗌 15. Is it clear what analyses were requested? Yes 🗹 No 🗌 16. Were all holding times able to be met? (If no, notify customer for authorization.) Checked by: Special Handling (if applicable) 17. Was client notified of all discrepancies with this order? Yes No 🗆 NA 🗹 Person Notified: Date: By Whom: eMail Phone Fax In Person Regarding: Client Instructions: 18. Additional remarks: 19 Cooler Information Cooler No Temp °C Condition Seal Intact Seal No Seal Date Signed By Good

Chain-of-Custody Record			Lurn-Around Lime:				HALL ENVIRONMENTAL															
Client: BLAGG ENGR. / BP AMERICA			Standard Rush				ANALYSIS LABORATORY															
			Project Name:				www.hallenvironmental.com															
Mailing Address: P.O. BOX 87			SAMMONS GC A # 1A				4901 Hawkins NE - Albuquerque, NM 87109															
BLOOMFIELD, NM 87413		Project #:				Tel. 505-345-3975 Fax 505-345-4107																
Phone #: (505) 632-1199		-					H			Å	ınal	ysis	Rec	ļues	ť			. e	* 5 . J	200		
email or Fax#:		Project Manager:										504)								_		
QA/QC Package: Standard Level 4.(Full Validation)		NELSON VELEZ			MB5 (8021B)	only)	/Diese						CB's						e			
Accreditation:		Sampler: NELSON VELEZ -NV				(Gas	(Gas		(VO2,	/8082 PCB's						du			
□ NELAP □ Other		On ice X Yes D No.			F	TPH	315B	18.1	04.1	AH)		03, 1	3/80		₹	<u></u>	1		te s	:		
□ EDD (1	ype)			Sample Temp	eraturek, /		1	BE +)d 8(od 4	od 5	or P	tals	S,	cide	F	-V0	00.0		음	posi	:
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO /	BTEX +- NATE	BTEX + MTBE + TPH (Gas only)	TPH Method 8015B (Gas/Diesel)	TPH (Method 418.1)	EDB (Method 504.1)	8310 (PNA or PAH)	RCRA 8 Metals	Anions (F, Cl, NO3, NO2, PO4,	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (300.0)		Grab sample	5 pt. composite sample	:
2/7/13	1405	SOIL	5PC-TB @ 6' (95)	4 oz 2	Cool	-001	٧		٧	٧								٧			٧	_
		_							·												1	_
																			\neg	寸		_
																					\top	
																					\neg	_
				, .															\neg	\top	\top	
																				7	1	_
																			\top		\neg	
																						_
																				\neg		_
																				\top		_
																					\exists	
Date: 78/13			Received by: Date Time 2/8//3/3/5				Remarks: TPH (8015B) - GRO & DRO ONLY. BILL DIRECTLY TO BP:															
Date:: Time: Relinquished by:		Received by: Date Time				Jeff Peace, 200 Energy Court, Farmington, NM 87401																
2/8/13 1757 Rhrist Walter																						
	If necess	ary samples.s	submitted to Hall Environmental may be	subcontracted to other	accredited laboratorie	as. This convoc se notice o	f thie r	vecihi	like A	b			d = 4 = ·	20 A			•	••				



