District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico **Energy Minerals and Natural Resources** Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
)2405 Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration OIL CONS. DIV DIST.
Permit of a pit or proposed alternative method  Closure of a pit, below-grade tank, or proposed alternative method  Mov 2 4 2014  Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinance.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Uptegrove Gas Com 1A
API Number:3004522142 OCD Permit Number:
U/L or Qtr/QtrI Section33 Township32N Range10W County:San Juan
Center of Proposed Design: Latitude36.938869 Longitude107.882127 NAD: ☐1927 ☒ 1983
Surface Owner:  Federal State Private Tribal Trust or Indian Allotment
2.  Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary:  Drilling  Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. Below-grade tank: Subsection 1 of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
Secondary containment with leak detection   Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Single walled/double bottomed; side walls not visible
Liner type: Thicknessmil
4. Alternative Method:



Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6. Netting: Subsection F. of 10.15.17.11.NIMAC.(4.17.4	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
<u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	
<ul> <li>□ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.</li> <li>□ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.</li> </ul>	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	otable source
<b>General siting</b>	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. ( <b>Does not apply to below grade tanks</b> )  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks)  - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Form C-144

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 100 feet of a wetland.	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,	
or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock	
watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
10.	MAG
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.	15 17 0 NMAC
and 19.15.17.13 NMAC	13.17.9 INMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	<u>.</u>
11.	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	cuments are
attached.  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
☐ A List of wells with approved application for permit to drill associated with the pit. ☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19	15 17 9 NMAC
and 19.15.17.13 NMAC	
<ul> <li>☐ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC</li> <li>☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC</li> </ul>	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Form C-144 Oil Conservation Division Page 3 of 6

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC    Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.10 NMAC    Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC    Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC    Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC    Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC    Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC    Quality Control/Quality Assurance Construction and Installation Plan    Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC    Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC    Nuisance or Hazardous Odors, including H₂S, Prevention Plan    Emergency Response Plan    Oil Field Waste Stream Characterization    Monitoring and Inspection Plan    Erosion Control Plan    Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative  Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached.  □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Fig. 15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

	☐ Yes ☐ No
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	<u>.</u>
Within a 100-year floodplain.	Yes No
- FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification:  I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18.  OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	· /
OCD Representative Signature: Approval Date: 12/12	
OCD Representative Signature: Approval Date: 12/12	//4
Title: En in montal Coc OCD Permit Number:	
Title: OCD Permit Number:  19.  Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not	
Title: Government Government Government Super Grant Number:  Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	complete this

22. Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure requirer	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Iff Pape	Date:November 24, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

### BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

#### BELOW-GRADE TANK CLOSURE PLAN

# Uptegrove Gas Com 1A BGT Tank A (95 bbl) API No. 3004522142 Unit Letter I, Section 33, T32N, R10W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

### **General Closure Plan**

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
  - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
  - Notice is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	470
Chlorides	US EPA Method 300.0 or 4500B	250 or background	2.9

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and BTEX and chloride levels were below the stated limits. TPH was 470 ppm by Method 418.1 but was only 72 ppm by Method 8015B, which is below the standard. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.** 

- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
  - Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the raised compressor pad and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the raised compressor pad and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the raised compressor pad and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.
    - Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

### State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notifi	icatio	and Co	rrective A	ction				
						OPERA'	ГOR		Initi	al Report	$\boxtimes$	Final Report
Name of Co						Contact: Jeff Peace						
		Court, Farmi rove Gas Co		M 87401		Telephone No.: 505-326-9479						
	•		III IA			Facility Type: Natural gas well						
Surface Ow	ner: Priva	te		Mineral	Owner:	Private			API No	3004522	142	
				LOC	ATIO	N OF REI	LEASE					
Unit Letter	Section 33	Township 32N	Range 10W	Feet from the 1,470	North/ South	South Line	Feet from the 1,190	East/W East	est Line	County: S	an Juar	1
1	1 33	<u> </u>	1	.938869		Longitud	e107.882127			<u> </u>		
		Latit	.uue30			_ Longitud OF RELI						
Type of Rele	ase: none			INA	LOKE	.,	Release: N/A		Volume I	Recovered: 1	N/A	****
		w grade tank –	- 95 bbl, T	ank A			Iour of Occurrence			Hour of Dis		:
Was Immedi	ate Notice (			No 🛛 Not F		If YES, To	Whom?					
D WI9			res _	NO M MOLE		Date and F						
By Whom? Was a Water	course Read	ched?	<del> </del>				olume Impacting t	the Water	course.			
Trus a Trus	☐ Yes ⊠ No											
If a Waterco	urse was Im	pacted, Descr	ibe Fully.	k		.1			-			
the BGT. So which is belo	oil analysis in the stance	resulted in BT lard. Analysis	EX and cl results ar	nloride below sta e attached.	ndards. 1	ΓPH was 470	the BGT was do ppm by Method	418.1 but	was only	72 ppm by	Method	1 8015B,
				ken.* BGT was r active well area.	emoved a	and the area u	nderneath the BC	GT was sa	mpled. T	he area undo	er the B	3GT was
regulations a public health should their or the enviro	Il operators or the envi operations h nment. In a	are required t ronment. The nave failed to a	o report and acceptant adequately OCD accep	nd/or file certain ce of a C-141 rep investigate and	release n oort by the remediat	otifications ar e NMOCD m e contaminati	knowledge and und perform correct arked as "Final R on that pose a three the operator of	ctive actio Leport" do reat to gro	ons for rel ses not rel ound water	eases which ieve the ope r, surface wa	may er rator of ater, hu	ndanger Fliability man health
	Λ Λ A	$\cap$					OIL CON	SERV	<u>ATION</u>	DIVISIO	<u>NC</u>	
Signature: Printed Nam	e: Jeff Peac	Poue	ν			Approved by	Environmental S	Specialist:	<del>.</del> .			<del></del>
Title: Field I	Environmen	tal Coordinate	or			Approval Dat	te:	E	xpiration	Date:		
E-mail Addr	ess: peace.j	effrey@bp.co	m			Conditions of Approval:			Attached			
Date: Nover				one: 505-326-947	79							

BP BP	BLAGG EN		API #: 30	04522142	
CLIENT:	•	LOOMFIELD, NM   5) 632-1199	87413	TANK ID (if applicble):	A & B
FIELD REPORT:	(circle one): BGT CONFIRMATION /	RELEASE INVESTIGATION / OTH	IER:	PAGE#:	1_ of _1
SITE INFORMATION	I: SITE NAME: UPTEGI	ROVE GC # 1A		DATE STARTED:	01/17/13
QUAD/UNIT: SEC: 33 TWP:	32N RNG: 10W PM:	NM CNTY: SJ	st: NM	DATE FINISHED:	
1/4 -1/4/FOOTAGE: 1,470'S / 1,190'	E NE/SE LEASE T	YPE: FEDERAL/STATE FI	EE INDIAN	ENVIRONMENTAL	
LEASE #: -	PROD. FORMATION: MV CC	ONTRACTOR: MBF - C. McI	INNES	SPECIALIST(S):	NV
REFERENCE POINT		COORD.: 36.93863	X 107.88248	GL EL	EV.: <b>6,864</b> '
1) 95 BGT (SW/DB) - A		938869 X 107.882127		ARING FROM W.H.:	136.5', N48E
2) <b>21 BGT (SW/DB) - D</b>	GPS COORD.: 36.	<del>938977 X 107.882378</del>	DISTANCE/BE/	ARING FROM W.H.:	<del>134.5', N13E</del>
3)	GPS COORD.:		DISTANCE/BE/	ARING FROM W.H.:	
4)	GPS COORD.:			ARING FROM W.H.:	OVM
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # O				READING (ppm)
1) SAMPLEID:					
2) SAMPLEID:	1) SAWIPLE DATE	SAMPLE TIME: 1025 DA	BAVALISIS. <u>419.1</u>	<del>/8045/8024/30</del> 6	0.0 (CI) NA
3) SAMPLE ID:					
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LA	BANALYSIS:		
SOIL DESCRIPTION		SAND SILT SILTY CLAY / CLAY		HER GRAVEL SIZ	ZE VARIES FROM
SOIL COLOR: MODERATE BE		PEBBLES TO SMALL		ACUEAN E LIEDUINIO AC	TION HOLINA PLANTING
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC		PLASTICITY (CLAYS): NON PLAST DENSITY (COHESIVE CLA			
MOISTURE: DRY/SLIGHTLYMOIST/MOIST/W		HC ODOR DETECTED:			
SAMPLE TYPE: GRAB (COMPOSITE) - #					
DISCOLORATION/STAINING OBSERVED	: YES (NO) EXPLANATION -				
ANY AREAS DISPLAYING WETNESS: YES / NO	EXPLANATION -				
APPARENT EVIDENCE OF A RELEASE C		EXPLANATION:			
ADDITIONAL COMMENTS: FROZEN SU	RFACE CONDITIONS	TO 2 FT. BELC	OW GRADE.		
SOIL IMPACT DIMENSION ESTIMATION:	<b>NA</b> ft. X <b>NA</b>	ft. X NA ft. I	EXCAVATION EST	TMATION (Cubic Y	ards) : NA
DEPTH TO GROUNDWATER: <50' N	EAREST WATER SOURCE: <1,000	NEAREST SURFACE WATER:	<1,000' NMOC	D TPH CLOSURE ST	D: <u>100</u> ppm
SITE SKETCH		PLOT PLAN circle:	attached 0\M	CALIB. READ. = N	<b>IA</b> ppm RF = 0.52
		300 BBL	<b>♦</b> own	CALIB. GAS = N	111 - 0.02
		PROD. TANK	N TIME	: <u>NA</u> am/pm	DATE: <b>NA</b>
		STEEL	_ ا	MISCELL	NOTES
-		CONTAINMENT	l w	/O: <b>N15561</b>	60
∕ TO		SYSTEM	P	o#: <b>79138</b>	
COMPR.			PI	k: ZEVH0	1BGT2
& BLDG		(95) PBGTL	BERM P.	J#: <b>Z2-006</b> 9	
		T.B. ~ 6' (x x x)	I —	ermit date(s):	06/09/10
		B.G.	O Tan	CD Appr. date(s): OVM = Organ	03/14/12 nic Vapor Meter
,		, TO	ID A		
√ to √ w.h.	V 655	TO SEP.	A	BCT Sidewalle Vi	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION	X - S.P.D. DN DEDRESSION: B.G. = RELOWIGRADE: B.= RE	VUNIT  I OW! TH = TESTHOLE: ~= APPROX : \WH	- WELL HEAD	BGT Sidewalls Vi	
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL	OW-GRADE TANK LOCATION; SPD = SAMPLE PO	DINT DESIGNATION; R.W. = RETAINING WA		lagnetic declina	ition: 10° ⊑
TO M /EL NOTEO	E WALL; DW - DOUBLE WALL; SB - SINGLE BOTT	A 4 1 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
TRAVEL NOTES: CALLOUT:		ONSITE: <u>01/17/</u>	<u> </u>		

### **Analytical Report**

### Lab Order 1301605

Date Reported: 1/24/2013

# Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Lab ID: 1301605-001

Project:

**UPTEGROVE GC #1A** 

Matrix: SOIL

Client Sample ID: 5PC-TB @ 6' (95)

**Collection Date:** 1/17/2013 10:30:00 AM

Received Date: 1/18/2013 9:53:00 AM

Result	RL Qu	al Units	DF	Date Analyzed
ORGANICS				Analyst: <b>MMD</b>
72	9.8	mg/Kg	1	1/24/2013 4:55:22 AM
98.2	72.4-120	%REC	1	1/24/2013 4:55:22 AM
GE				Analyst: <b>NSB</b>
ND	5.0	mg/Kg	1	1/22/2013 2:22:00 AM
97.5	84-116	%REC	1	1/22/2013 2:22:00 AM
				Analyst: NSB
ND	0.050	mg/Kg	1	1/22/2013 2:22:00 AM
ND	0.050	mg/Kg	1	1/22/2013 2:22:00 AM
ND	0.050	mg/Kg	1	1/22/2013 2:22:00 AM
ND	0.099	mg/Kg	1	1/22/2013 2:22:00 AM
105	80-120	%REC	1	1/22/2013 2:22:00 AM
				Analyst: <b>JRR</b>
ND	7.5	mg/Kg	5	1/22/2013 1:43:30 PM
				Analyst: ECH
470	20	mg/Kg	1	1/23/2013 12:00:00 PM
	ORGANICS 72 98.2 GE ND 97.5 ND	ORGANICS  72 9.8 98.2 72.4-120  GE  ND 5.0 97.5 84-116  ND 0.050 ND 0.050 ND 0.050 ND 0.050 ND 0.099 105 80-120  ND 7.5	ORGANICS  72 9.8 mg/Kg 98.2 72.4-120 %REC  GE  ND 5.0 mg/Kg 97.5 84-116 %REC  ND 0.050 mg/Kg ND 0.099 mg/Kg ND 0.099 mg/Kg ND 0.099 mg/Kg ND 0.099 mg/Kg ND 7.5 mg/Kg	ORGANICS  72 9.8 mg/Kg 1 98.2 72.4-120 %REC 1  GE  ND 5.0 mg/Kg 1 97.5 84-116 %REC 1  ND 0.050 mg/Kg 1 ND 0.050 mg/Kg 1 ND 0.050 mg/Kg 1 ND 0.050 mg/Kg 1 ND 0.050 mg/Kg 1 ND 0.050 mg/Kg 1 ND 0.050 mg/Kg 1 ND 0.050 mg/Kg 1 ND 0.050 mg/Kg 1 ND 0.050 mg/Kg 5

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range Ε
- Analyte detected below quantitation limits
- Sample pH greater than 2
- RLReporting Detection Limit

- Analyte detected in the associated Method Blank В
- Holding times for preparation or analysis exceeded H
- Not Detected at the Reporting Limit
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits Page 1 of 7

## Hall Environmental Analysis Laboratory, Inc.

WO#:

1301605 24-Jan-13

Client:

Blagg Engineering

Project:

**UPTEGROVE GC #1A** 

Sample ID MB-5770

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 5770

PQL

RunNo: 8194

Prep Date:

1/22/2013

Analysis Date: 1/22/2013

Result

SeqNo: 236972

Units: mg/Kg

HighLimit

**RPDLimit** 

Qual

Analyte Chloride

ND 1.5

Sample ID LCS-5770

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID:

LCSS

Batch ID: 5770

RunNo: 8194

Prep Date: 1/22/2013

Analysis Date: 1/22/2013

SeqNo: 236973

Units: mg/Kg

**RPDLimit** 

Analyte

PQL SPK value SPK Ref Val %REC

0

SPK value SPK Ref Val %REC LowLimit

15.00

97.5

90

110

1.5

Chloride

15

LowLimit

HighLimit

%RPD

%RPD

Qual

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range Е

j Analyte detected below quantitation limits

Sample pH greater than 2

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit ND

RPD outside accepted recovery limits

Page 3 of 7

## Hall Environmental Analysis Laboratory, Inc.

WO#:

1301605 24-Jan-13

Client:

Blagg Engineering

Project:

**UPTEGROVE GC #1A** 

Sample ID MB-5758

SampType: MBLK

TestCode: EPA Method 418.1: TPH

LowLimit

Client ID: PBS

Batch ID: 5758

**PQL** 

20

20

RunNo: 8206

Prep Date: 1/21/2013 Analysis Date: 1/23/2013 Result

ND

SeqNo: 237357

Units: mg/Kg

HighLimit

%RPD **RPDLimit** 

Qual

Analyte Petroleum Hydrocarbons, TR

SampType: LCS

TestCode: EPA Method 418.1: TPH

SPK value SPK Ref Val %REC

Client ID: LCSS Batch ID: 5758

RunNo: 8206

Prep Date: 1/21/2013

Sample ID LCS-5758

Analysis Date: 1/23/2013

SeqNo: 237358

Units: mg/Kg

HighLimit %RPD **RPDLimit** Qual

Petroleum Hydrocarbons, TR

Result **PQL** 97

100.0

SPK value SPK Ref Val %REC 97.1 0

LowLimit 120 80

Qual

Sample ID LCSD-5758

SampType: LCSD

TestCode: EPA Method 418.1: TPH

Client ID: LCSS02 Batch ID: 5758

Result

100

RunNo: 8206

Units: mg/Kg

Analyte

Prep Date:

Analyte

1/21/2013

Analysis Date: 1/23/2013

SeqNo: 237359 SPK value SPK Ref Val %REC

0

LowLimit

HighLimit

%RPD 4.08 **RPDLimit** 

Petroleum Hydrocarbons, TR

100.0

101

80

120

20

Qualifiers:

Value exceeds Maximum Contaminant Level

Ē Value above quantitation range

Analyte detected below quantitation limits

Sample pH greater than 2

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Н

ND Not Detected at the Reporting Limit

RPD outside accepted recovery limits

Page 4 of 7

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1301605

24-Jan-13

Client:

Blagg Engineering

Project:

**UPTEGROVE GC #1A** 

Sample ID MB-5753	Samp <sup>-</sup>	Гуре: М	BLK	TestCode: EPA Method 8015B: Diesel Range Organics						
Client ID: PBS	Batc	h ID: <b>57</b>	53	RunNo: <b>8204</b>						
Prep Date: 1/21/2013	Analysis [	Date: 1/	23/2013	SeqNo: 237449			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Surr: DNOP	9.8		10.00		98.4	72.4	120			

Sample ID LCS-5753	SampT	ype: LC	s	Tes	TestCode: EPA Method 8015B: Diesel Range Organics					
Client ID: LCSS	Batch	ID: <b>57</b>	53	RunNo: <b>8204</b>						
Prep Date: 1/21/2013	Analysis Date: 1/23/2013			SeqNo: <b>237450</b>			Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	51	10	50.00	0	102	47.4	122			
Surr: DNOP	5.3		5.000		106	72.4	120			

#### Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits

P Sample pH greater than 2

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

Page 5 of 7

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1301605

24-Jan-13

Client:

Blagg Engineering

Project:

**UPTEGROVE GC #1A** 

Sample ID MB-5742	SampType: MBLK TestCode: EPA Method 8015B: Gasoline Range									
Client ID: PBS	Batch ID: 5742	RunNo: 8172								
Prep Date: 1/18/2013	Analysis Date: 1/21/2013	SeqNo: 236303	Units: mg/Kg							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual							
Gasoline Range Organics (GRO)	ND 5.0									
Surr: BFB	970 1000	97.5 84	116							
Sample ID LCS-5742	SampType: LCS TestCode: EPA Method 8015B: Gasoline Range									
Client ID: LCSS	Batch ID: 5742	RunNo: 8172								
Prep Date: 1/18/2013	Analysis Date: 1/21/2013	SeqNo: <b>236304</b>	Units: mg/Kg							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual							
Gasoline Range Organics (GRO)	25 5.0 25.00	0 98.5 74	117 .							
Surr: BFB	860 1000	86.1 84	116							
Sample ID MB-5759	SampType: <b>MBLK</b>	TestCode: EPA Method	8015B: Gasoline Range							
Client ID: PBS	Batch ID: 5759	RunNo: 8181								
Prep Date: 1/21/2013	Analysis Date: 1/22/2013	SeqNo: 237033	Units: %REC							
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual							
Surr: BFB	1000 1000	100 84	116							
Sample ID LCS-5759	SampType: LCS TestCode: EPA Method 8015B: Gasoline Range									

Sample ID I	LC2-5/59	Samp rype.	LUS	resi	6015B: Gase	onne Kang	е			
Client ID:	LCSS	Batch ID:	5759	R						
Prep Date:	1/21/2013	Analysis Date:	1/22/2013	013 SeqNo: 237034		Units: %RE	C			
Analyte		Result Po	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: BFB		1100	1000		106	84	116			

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

P Sample pH greater than 2

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

Page 6 of 7

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1301605

24-Jan-13

Client:

Blagg Engineering

Project: UPTEG	ROVE GC#	1A													
Sample ID MB-5742	SampType: MBLK TestCode: EPA Method 8021B: Volatiles														
Client ID: PBS	Batch	ID: <b>57</b> 4	12	F	RunNo: 8	172									
Prep Date: 1/18/2013	Analysis Da	ite: 1/2	21/2013	5	SeqNo: <b>236326</b>			Units: mg/Kg							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit %RPD		RPDLimit	Qual					
Benzene	ND	0.050													
Toluene	ND	0.050													
Ethylbenzene	ND	0.050													
Xylenes, Total	ND	0.10													
Surr: 4-Bromofluorobenzene	1.1		1.000		105	80	120								
Sample ID LCS-5742	SampTy	pe: LC	s	Tes	TestCode: EPA Method 8021B: Volatiles										
Client ID: LCSS	Batch	ID: <b>57</b> 4	12	F	RunNo: 8	172									
Prep Date: 1/18/2013	Analysis Da	ite: 1/2	21/2013	S	SeqNo: 2	36327	Units: mg/K								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit .	%RPD	RPDLimit	Qual					
Benzene	0.99	0.050	1.000	0	98.8	80	120								
Toluene	0.99	0.050	1.000	0	98.9	80	120								
Ethylbenzene	1.0	0.050	1.000	0	100	80	120								
Xylenes, Total	3.0	0.10	3.000	0	100	80	120								
Surr: 4-Bromofluorobenzene	0.84		1.000		84.3	80	120								
Sample ID MB-5759	SampTy	ре: МВ	LK	Tes	tCode: El	PA Method	8021B: Volat	iles							
Client ID: PBS	Batch	ID: <b>575</b>	59	F	tunNo: 8	181									
Prep Date: 1/21/2013	Analysis Da	ite: 1/2	22/2013	8	SeqNo: 2	37107	Units: %REG								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Surr: 4-Bromofluorobenzene	1.1		1.000		110	80	120								
Sample ID LCS-5759	SampType: LCS TestCode: EPA Method 8021B: Volatiles														
Client ID: LCSS	Batch	ID: <b>575</b>	59	F	lunNo: 8	181									
Prep Date: 1/21/2013	Analysis Da	te: 1/2	22/2013	8	SeqNo: 2	37108	Units: %REC								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					

#### Qualifiers:

Value exceeds Maximum Contaminant Level.

1.1

1.000

Value above quantitation range

Analyte detected below quantitation limits

Sample pH greater than 2

Surr: 4-Bromofluorobenzene

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

113

80

120

RPD outside accepted recovery limits

Page 7 of 7



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105 TEL: 505-345-3975 FAX: 505-345-410;

Website: www.hallenvironmental.com

# Sample Log-In Check List

Client Name: BLAGG Work Order Number: 1301605 Received by/date Logged By: Michelle Garcia 1/18/2013 9:53:00 AM Completed By: Michelle Garcia 1/18/2013 1:20:03 PM 01/10/2013 Reviewed By: Chain of Custody Yes No 🗌 1. Were seals intact? Not Present Yes V No 🗆 Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Courier Log In Yes 🗹 No 🗌 NA 🗀 4. Coolers are present? (see 19. for cooler specific information) Yes 🗹 No 🗌 NA 🗌 5. Was an attempt made to cool the samples? Yes 🗸 No 🗌 6. Were all samples received at a temperature of >0° C to 6.0°C NA 🗌 Yes 🗸 No 🗌 7. Sample(s) in proper container(s)? Yes 🗹 No 🗌 8 Sufficient sample volume for indicated test(s)? Yes 🗹 No 🗌 9. Are samples (except VOA and ONG) properly preserved? Yes No 🗹 NA 🔲 10. Was preservative added to bottles? Yes No No VOA Viais 🗹 11. VOA vials have zero headspace? Yes No 🗹 12. Were any sample containers received broken? # of preserved Yes V No 13. Does paperwork match bottle labels? bottles checked (Note discrepancies on chain of custody) for pH: Yes 🗹 No 🗌 14. Are matrices correctly identified on Chain of Custody? (<2 or >12 unless noted) Yes 🗹 No 🗌 Adjusted? 15. Is it clear what analyses were requested? Yes 🗸 No 🗌 16. Were all holding times able to be met? (If no, notify customer for authorization.) Checked by: Special Handling (if applicable) 17. Was client notified of all discrepancies with this order? Yes 🗌 No 🗌 NA 🔽 Person Notified: Date: By Whom: eMail Phone Fax In Person Via: Regarding: Client Instructions: 18 Additional remarks: 19 Cooler Information Cooler No | Temp °C | Condition | Seal Intact | Seal No | Seal Date 1.0 Good Yes

Chain-of-Custody Record		Turn-Around Time:				L L HALL ENVIRONMENTAL															
Client: BLAGG ENGR. / BP AMERICA			✓ Standard ☐ Rush					F	_						-						
				Project Name:				ANALYSIS LABORATORY  www.hallenvironmental.com													
Mailing Address: P.O. BOX 87		UPTEGROVE GC # 1A				4901 Hawkins NE - Albuquerque, NM 87109															
BLOOMFIELD, NM 87413			Project #:					Tel. 505-345-3975 Fax 505-345-4107													
Phone #: (505) 632-1199					٠٠. (* زاد ده		ه چه دی	in the	ر وزوانه الم	1	\nal	ysis	Rec	ques	t,			, w			
email or Fax#:		Project Manag	jer:		Π							504)						Ĭ	T		
QA/QC Package:  Standard Level 4 (Full Validation)		NELSON VELEZ			FWB5=(8021B)	+ TPH (Gas only)	Diesel)						B's								
Accreditat			, , ,	Sampler: NELSON VELEZ nv				Gas (	Gas/					02, F	2 PCB						ם
□ NELAP		□ Other		Onlice: (13. Yes □ No				H.	15B (	418.1)	4.1)	(H		3, N	/ 8082						Sal :
□ EDD (T	ype)			Sample Temperature: $\sqrt{\hat{\mathcal{C}}^c}$					801	d 41	d 50	r PA	sle	NO,	des /	_	/0A	0.0)		ا	.   Sire
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO:	BTEX +-MTB	BTEX + MTBE	TPH Method 8015B (Gas/Diesel)	TPH (Method	EDB (Method 504.1)	8310 (PNA or PAH)	RCRA 8 Metals	Anions (F, Cl, NO3, NO2, PO4,	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (300.0)	-1	ab   t	5 pt. composite sample
1/17/13	1030	SOIL	5PC-TB @ 6' (95)	4 oz 2	Cool	-001	V		٧	<b>V</b>								٧			V
																				_	+
1/17/13	1025	SOIL	5PC TB @ 6.5' (21)	4 oz. 2	Cool	002	1		7	v								N/		١,	止
							╁╌		Ť	Ť										+	+
							<del>                                     </del>													+	+
							-									$\vdash \vdash$			-+	╫	+
																			-+	+	+
																			$\vdash$	$\dashv$	+
																				- -	+
				<u> </u>			-													_	
							<u> </u>												$\vdash$	_	$\bot$
	_				_		<u> </u>													$\perp$	_
			<b>A</b> :	<u> </u>					·								]				
Date: 1/17/13	Time: 152 <i>5</i>	Relinquish	In V	Received by: Date Time  Matine Was Inc. 1/17/13 1525		Remarks: TPH (8015B) - GRO & DRO ONLY.  BILL DIRECTLY TO BP:															
Date:	IO とう Time:	Relinquishe	ed by:	Received by: Date Time			Jeff Peace, 200 Energy Court, Farmington, NM 87401														
1/11/13	1737	1 / Wistre Weller		01/18/13 0953			"	Work Order: N1556160 Paykey: ZEVH01BGT2													





BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

June 4, 2012

Sandra L. Townsend Trust PO Box 1292 Aztec, NM 87410

### VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: UPTEGROVE GC 001A

Dear Mark Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about May 27, 2012. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

AD Valla

Surface Coordinator/Business Security Representative

**BP America Production Company** 

### **BP America Production Company**

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

### SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

June 11, 2012

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

UPTEGROVE GAS COM 001A API 30-045-22142 (M) Section 33 – T32N – R10W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl. BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Buddy Shaw BP Environmental Advisor

(505) 320-0401



