 <u>District 1</u> <u>1625</u> N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87 	1220 South St. Francis Dr.
12344 <u>Propo</u> Type of action: 45-26450	Pit, Below-Grade Tank, or sed Alternative Method Permit or Closure Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternation Modification to an existing permit/or registration

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

12344 Proposed Alternative Method Permit or Closure Plan Application OIL CONS. DIV DIST. 3
Type of action: Below grade tank registration
\square Permit of a pit or proposed alternative method NOV 1 0 2014
135-26450 Closure of a pit, below-grade tank, or proposed alternative method Movie Correction Movie Correction
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1. Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Moncrief Federal 1E
API Number:
U/L or Qtr/Qtr
Center of Proposed Design: Latitude36.71691Longitude108.09177NAD: □ 1927 ⊠ 1983
Surface Owner: 🛛 Federal 🗔 State 🗔 Private 🗋 Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
□ String-Reinforced Liner Seams: □ Welded □ Factory □ Other Volume:bbl Dimensions: L x W x D
3. Subsection I of 19.15.17.11 NMAC Tank A
Volume:21.0bbl Type of fluid:Produced water
Tank Construction material:Steel
Secondary containment with leak detection 🔲 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
□ Visible sidewalls and liner ⊠ Visible sidewalls only □ Other _Single walled/double bottomed
Liner type: Thicknessmil
4.

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

^{5.} Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)				
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital,				
institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet				
Alternate. Please specify				
6.				
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)				
Screen Netting Other				
Monthly inspections (If netting or screening is not physically feasible)				
7. Signs: Subsection C of 19.15.17.11 NMAC				
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers				
Signed in compliance with 19.15.16.8 NMAC				
8.				
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.				
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.				
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.				
9. Siting Critovic (recording permitting): 10.15.17.10 NMAC				
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept	ntable source			
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	shiple source			
General siting				
 Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA			
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.	Yes No			
NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	🗌 NA			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	🗌 Yes 🗌 No			
 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 				
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)				
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No			
Within an unstable area. (Does not apply to below grade tanks)	🗌 Yes 🗌 No			
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 				
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	🗋 Yes 🗌 No			
Below Grade Tanks				
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured	🗌 Yes 🗌 No			
from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site				
Vithin 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site				
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)				
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)	Yes No			
- Topographic map; Visual inspection (certification) of the proposed site				

.

ø

 Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
^{10.} <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 N <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the dot attached.</i>	
 Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC 	9 NMAC
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC 	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number: or Permit Number:	14
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC	
 Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

-

نه

 Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the 	documents are			
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Muisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC				
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.				
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fl	uid Management Pit			
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)				
On-site Closure Method (Only for temporary pits and closed-loop systems)				
In-place Burial On-site Trench Burial Alternative Closure Method				
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 				
is. <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P. 19.15.17.10 NMAC for guidance.				
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA			
 Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA			
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 				
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No			
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No			
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No			
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗋 Yes 🗌 No			
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance				
Form C-144 Oil Conservation Division Page 4 of	6			

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.						
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗋 Yes 🗌 No					
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division						
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological 						
Society; Topographic map	🗌 Yes 🗌 No					
Within a 100-year floodplain. - FEMA map	🗌 Yes 🗌 No					
16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Bitting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetatio						
Signature: Date:						
e-mail address: Telephone:						
18. <u>OCD Approva</u> l: Permit Application (including closure plan) Closure Plan (costy) OCD Conditions (see attachment)	· /					
OCD Representative Signature: Approval Date:/2/	/14					
Title: <u>Environmental Spec</u> OCD Permit Number:						
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not a section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 10/19/2012						
 20. Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-loc If different from approved plan, please explain. 	op systems only)					
 21. <u>Closure Report Attachment Checklist</u>: Instructions: Each of the following items must be attached to the closure report. Please intermark in the box, that the documents are attached. A Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number 	licate, by a check					

	this closure report is true, accurate and complete to the best of my knowledge and sure requirements and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature:	Date:November 7, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

4.4

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Moncrief Federal 1E BGT Tank A (21 bbl)</u> <u>API No. 3004526450</u> <u>Unit Letter D, Section 22, T29N, R12W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

3

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number. **Notice is attached.**
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)

3

- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

ς.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-141

Submit I	Copy to appropriate	District Office in
	accordance with	19.15.29 NMAC.

API No. 3004526450

Release Notification and Corrective Action

	OPERATOR	Initial Report	🛛 Final Report
Name of Company: BP	Contact: Jeff Peace		
Address: 200 Energy Court, Farmington, NM 87401	Telephone No.: 505-326-9479	······································	
Facility Name: Moncrief Federal 1E	Facility Type: Natural gas well		

Surface Owner: Federal

Mineral Owner: Federal

LOCA	TION O	F RE	LEASE		
East Comments	NI-41/01-41	1 .		.1	m .

Unit Letter	Section	Township	Range	Feet from the	North/South Line	Feet from the	East/West Line	County: San Juan
D	22	29N	12W	1,000	North	1,450	East	

Latitude _____36.71691 ______Longitude ___108.09177 ______

NATURE OF RELEASE

Type of Release: none	Volume of Release: N/A	Volume Re	ecovered: N/A			
Source of Release: below grade tank – 21 bbl, Tank A	Date and Hour of Occurrence:	Date and H	lour of Discovery:			
Was Immediate Notice Given?	If YES, To Whom?					
Yes 🗌 No 🛛 Not Required						
By Whom?	Date and Hour					
Was a Watercourse Reached?	If YES, Volume Impacting the Wa	tercourse.				
🗌 Yes 🖾 No						
If a Watercourse was Impacted, Describe Fully.*						
Describe Cause of Problem and Remedial Action Taken.* Sampling of th	e soil beneath the BGT was done duri	ng removal to	ensure no soil impacts from			
the BGT. Soil analysis resulted in TPH, BTEX and chloride below stand		ng removar te				
	-					
Describe Area Affected and Cleanup Action Taken.* BGT was removed	and the area underreath the DCT was	compled Th	a area under the DCT was			
backfilled and compacted and is still within the active well area.	and the area underneath the BGT was	sampled. The	e area under the BGT was			
backfined and compacted and is surf within the delive wen area.						
I hereby certify that the information given above is true and complete to						
regulations all operators are required to report and/or file certain release r						
public health or the environment. The acceptance of a C-141 report by the should their operations have failed to adequately investigate and remedia						
or the environment. In addition, NMOCD acceptance of a C-141 report of						
federal, state, or local laws and/or regulations.						
	OIL CONSERVATION DIVISION					
Signature Jack Passa						
Signature: Signature:						
	Approved by Environmental Speciali	st:				
Printed Name: Jeff Peace						
Title: Field Environmental Coordinator	Approval Date:	Expiration D	ate:			
E-mail Address: peace.jeffrey@bp.com	Conditions of Approval:	Attached				
D + N + 7 2014 Discuss 505 206 0470						
Date: November 7, 2014 Phone: 505-326-9479						

* Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG EN P.O. BOX 87, BL (505)	API #:						
FIELD REPORT:	(circle one): BGT CONFIRMATION / R	ELEASE INVESTIGATION / O	THER:	PAGE #: <u>1</u> of <u>1</u>				
SITE INFORMATION QUAD/UNIT: D SEC: 22 TWP:	29N RNG: 12W PM:	NM CNTY: SJ	st: NM	DATE STARTED: 10/3/12 DATE FINISHED:				
	PROD. FORMATION: DK CON	, ELKHORN TRACTOR: MBF - C. Z		ENVIRONMENTAL SPECIALIST(S): JCB				
21 BGT (SW/DB) - A 2)	GPS COORD.: 36.7		DISTANCE/BE/	62 GL ELEV.: 5,480' ARING FROM WH.: 81', S29W ARING FROM WH.: 159', S33W				
3)				ARING FROM W.H.:				
SAMPLING DATA: 1) SAMPLE ID:21 BGT - 5pt. @ 8		SAMPLE TIME:	LAB ANALYSIS: 418.1,					
 2) SAMPLE ID:		SAMPLE TIME:	LAB ANALYSIS:					
SOIL DESCRIPTION	SOIL TYPE: SAND / SILTY S							
CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY/SLIGHTLY MOIST/MOIST/MOIST/W SAMPLE TYPE: GRAB (COMPOSITE)- # DISCOLORATION/STAINING OBSERVED: ANY AREAS DISPLAYING WETNESS: YES / NO	COHESION (ALL OTHERS): NON COHESIVE/ SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC CONSISTENCY (NON COHESIVE SOILS): LOOSE/ FIRM / DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC MOISTURE: DRY/SLIGHTLY MOIST / WET / SATURATED / SUPER SATURATED PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / HIGHLY PLASTIC SAMPLE TYPE: GRAB (COMPOSITE) - # OF PTS. 5 DISCOLORATION/STAINING OBSERVED: YES (NO) EXPLANATION - ANY AREAS DISPLAYING WETNESS: YES / NO) EXPLANATION - APPARENT EVIDENCE OF A RELEASE OBSERVED AND/OR OCCURRED : YES (NO) EXPLANATION :							
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER:		t. X NA ft. NEAREST SURFACE WATER:		IMATION (Cubic Yards) : NA D TPH CLOSURE STD: <u>100</u> ppm				
R.W.	⊕ WELL HEAD 3GTL 3. ~ 7' 3.G.			ppm = parts per million BGT Sidewalls Visible: (Y) N				
NOTES: BGT = BELOWGRADE TANK, E.D. = EXCAVATIO T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW- SINGLE TRAVEL NOTES: CALLOUT:	n Depression; B.G. = Below Grade; B = Belo Dwgrade Tank Location; SPD = Sample Poin Wall; DW - Double Wall; SB - Single Botton	T DESIGNATION; R.W. = RETAINING \	WALL; NA - NOT <u>N</u>	lagnetic declination: 10° E				

•

.

Analytical Report Lab Order 1210358 Date Reported: 10/19/2012

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering Client Sample ID: 21 BGT 5-pt @ 8' **Project:** Moncrief Fed 1E Collection Date: 10/3/2012 9:25:00 AM Lab ID: 1210358-001 Matrix: SOIL Received Date: 10/5/2012 10:10:00 AM Analyses Result **RL** Qual Units DF **Date Analyzed** EPA METHOD 8015B: DIESEL RANGE ORGANICS Analyst: JMP Diesel Range Organics (DRO) 10/10/2012 12:10:50 PM ND 10 ma/Ka 1

Dicaci Kange Organica (DICO)	ND	10	mg/kg		10/10/2012 12:10:50 PM
Surr: DNOP	92.7	77.6-140	%REC	1	10/10/2012 12:10:50 PM
EPA METHOD 8015B: GASOLINE RANGE					Analyst: NSB
Gasoline Range Organics (GRO)	ND	4.9	mg/Kg	1	10/9/2012 3:59:24 PM
Surr: BFB	102	84-116	%REC	1	10/9/2012 3:59:24 PM
EPA METHOD 8021B: VOLATILES					Analyst: NSB
Benzene	ND	0.049	mg/Kg	1	10/9/2012 3:59:24 PM
Toluene	ND	0.049	mg/Kg	1	10/9/2012 3:59:24 PM
Ethylbenzene	ND	0.049	mg/Kg	1	10/9/2012 3:59:24 PM
Xylenes, Total	ND	0.098	mg/Kg	1	10/9/2012 3:59:24 PM
Surr: 4-Bromofluorobenzene	109	80-120	%REC	1	10/9/2012 3:59:24 PM
EPA METHOD 300.0: ANIONS					Analyst: SRM
Chloride	ND	7.5	mg/Kg	5	10/10/2012 10:26:20 AM
EPA METHOD 418.1: TPH					Analyst: JMP
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	10/10/2012

Qualifiers:

*

Value exceeds Maximum Contaminant Level.

Е Value above quantitation range

J Analyte detected below quantitation limits

Р Sample pH greater than 2

Reporting Detection Limit RL

В Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Н

ND Not Detected at the Reporting Limit

RPD outside accepted recovery limits R

Spike Recovery outside accepted recovery limits S

٩.

WO#: 1210358 19-Oct-12

-

Hall Environmental Analysis Laboratory, Inc.

	g Engineering crief Fed 1E					
Sample ID MB-4224	SampType: MBLK	TestCode:	EPA Method	300.0: Anions		
Client ID: PBS	Batch ID: 4224	RunNo:	6131			
Prep Date: 10/10/2012	Analysis Date: 10/10/2	012 SeqNo:	176679	Units: mg/Kg		
Analyte	Result PQL SPK	value SPK Ref Val %RE	C LowLimit	HighLimit %F	RPD RPDLimit	Qual
Chloride	ND 1.5					
Sample ID LCS-4224	SampType: LCS	TestCode:	EPA Method	300.0: Anions		
Client ID: LCSS	Batch ID: 4224	RunNo:	6131			
Prep Date: 10/10/2012	Analysis Date: 10/10/2	012 SeqNo:	176680	Units: mg/Kg		
Analyte	Result PQL SPK	value SPK Ref Val %RE	C LowLimit	HighLimit %F	RPD RPDLimit	Qual
Chloride	14 1.5	15.00 0 93.	9 90	110		

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits

٠ ι

x.

Hall Environmental Analysis Laboratory, Inc.									
Client:	00	Engineering							
Project:	Moncr	ef Fed 1E							
Sample ID M	B-4193	SampType: MBLK	TestCode: EPA Method 418.1: TPH						

Sample ID MB-4193	SampType: MBLK	TestCode: EPA Method	418.1: TPH			
Client ID: PBS	Batch ID: 4193	RunNo: 6110				
Prep Date: 10/9/2012	Analysis Date: 10/10/2012	SeqNo: 176066	Units: mg/Kg			
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual		
Petroleum Hydrocarbons, TR	ND 20					
Sample ID LCS-4193	SampType: LCS	TestCode: EPA Method	418.1: TPH	<u> </u>		
Client ID: LCSS	Batch ID: 4193	RunNo: 6110				
Prep Date: 10/9/2012	Analysis Date: 10/10/2012	SeqNo: 176067	Units: mg/Kg			
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual		
Petroleum Hydrocarbons, TR	100 20 100.0	0 101 80	120			
Sample ID LCSD-4193	SampType: LCSD	TestCode: EPA Method	418.1: TPH			
Client ID: LCSS02	Batch ID: 4193	RunNo: 6110				
Prep Date: 10/9/2012	Analysis Date: 10/10/2012	SeqNo: 176068	Units: mg/Kg			
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual		
Petroleum Hydrocarbons, TR	100 20 100.0	0 104 80	120 2.67	20		

Qualifiers:

- Value exceeds Maximum Contaminant Level. *
- Value above quantitation range Е
- Analyte detected below quantitation limits J
- Sample pH greater than 2 Р

- Analyte detected in the associated Method Blank В
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RPD outside accepted recovery limits R

WO#: 1210358 19-Oct-12

،

	Engineering ief Fed 1E									
Sample ID MB-4192	SampT	ype: MI	e: MBLK TestCode: EPA Method 8015B: Diesel Range Organics							
Client ID: PBS	Batch	n ID: 41	92	F	RunNo: 6	108				
Prep Date: 10/9/2012	Analysis D	ate: 10	0/10/2012	S	SeqNo: 1	76064	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Surr: DNOP	11		10.00		106	77.6	140			
Sample ID LCS-4192	SampT	ype: LC	s	Tes	tCode: E	PA Method	8015B: Diese	el Range C	Drganics	
Client ID: LCSS	Batch	n ID: 41	92	F	RunNo: 6	108				
Prep Date: 10/9/2012	Analysis D	ate: 10	0/10/2012	S	SeqNo: 1	76065	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	39	10	50.00	0	78.5	52.6	130			
Surr: DNOP	4.5		5.000		89.4	77.6	140			

Hall Environmental Analysis Laboratory, Inc.

Qualifiers:

* Value exceeds Maximum Contaminant Level.

.

- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits

19-0ct-12

ς. Υ.

Hall Environmental Analysis Laborator	y, Inc.
---------------------------------------	---------

WO#:	1210358
	10 Oct 12

19-Oct-12

.....

Client: Project:	Blagg Er Moncrie	ngineering f Fed 1E									
Sample ID N	/B-4249	SampType	MBLK	Tes	TestCode: EPA Method 8015B: Diesel Range						
Client ID: P	ъвм	Batch ID:	4249	F	unNo: 6	146					
Prep Date:	10/11/2012	Analysis Date:	10/11/2012	S	eqNo: 1	77920	Units: %RE	с			
Analyte		Result P	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Surr: DNOP		1.1	1.000		112	79.5	166				
Sample ID L	.CS-4249	SampType	SampType: LCS TestCode: EPA Method 801								
Client ID: L	CSW	Batch ID:	4249	Я	tunNo: 61	146					
Prep Date:	10/11/2012	Analysis Date:	10/11/2012	S	eqNo: 17	77921	Units: %RE	с			
Analyte		Result P	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Surr: DNOP		0.53	0.5000		105	79.5	166				
Sample ID L	.CSD-4249	SampType	LCSD	Tes	Code: EF	PA Method	8015B: Diese	el Range			
Client ID: L	CSS02	Batch ID:	4249	R	unNo: 61	146					
Prep Date:	10/11/2012	Analysis Date:	10/11/2012	S	eqNo: 17	77922	Units: %RE	с			
Analyte		Result P	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Surr: DNOP		0.50	0.5000		101	79.5	166	0	0		

Qualifiers:

- Value exceeds Maximum Contaminant Level. *
- Е Value above quantitation range
- Analyte detected below quantitation limits J
- Р Sample pH greater than 2

- Analyte detected in the associated Method Blank В
- Holding times for preparation or analysis exceeded H
- ND Not Detected at the Reporting Limit
- RPD outside accepted recovery limits R

. .

-

	Engineering ef Fed 1E									
Sample ID MB-4182	SampT	SampType: MBLK TestCode: EPA Method 8015B: Gasoline Range								
Client ID: PBS	Batch	n ID: 41	82	F	RunNo: 6	117				
Prep Date: 10/8/2012	Analysis D	ate: 10	0/9/2012	S	SeqNo: 1	76252	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND	5.0								
Surr: BFB	1000		1000		102	84	116			
Sample ID LCS-4182	SampT	ype: LC	S	Tes	tCode: El	PA Method	8015B: Gaso	line Rang	e	
Client ID: LCSS	Batch	n ID: 41	82	F	RunNo: 6	117				
Prep Date: 10/8/2012	Analysis D	ate: 10	0/9/2012	S	SeqNo: 1	76254	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	26	5.0	25.00	0	103	74	117			
Surr: BFB	1100		1000		105	84	116			

Hall Environmental Analysis Laboratory, Inc.

WO#: 1210358

19-Oct-12

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits

Hall Environmental Analysis Laboratory, Inc.

Client:	Blagg Engineering									
Project:	Moncrief Fed 1E					•				
Sample ID MB-418	2 Samp	Туре: МЕ	BLK	Tes	tCode: El	PA Method	8021B: Volat	iles		
Client ID: PBS	Bato	:h ID: 41	82	F	RunNo: 6	117				
Prep Date: 10/8/20	012 Analysis I	Date: 10	0/9/2012	S	SeqNo: 1	76280	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluoroben	zene 1.1		1.000		110	80	120			
Sample ID LCS-418	32 Samp	Type: LC	s	Tes	tCode: El	PA Method	8021B: Volat	iles		
Client ID: LCSS	Batc	h ID: 41	82	F	RunNo: 6	117				
Prep Date: 10/8/20	012 Analysis I	Date: 10	0/9/2012	5	SeqNo: 1	76281	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	1.1	0.050	1.000	0	109	76.3	117			
Toluene	1.1	0.050	1.000	0	107	80	120			
Ethylbenzene	1.1	0.050	1.000	0	108	77	116			
Xylenes, Total	3.3	0.10	3.000	0	108	76.7	117			
Surr: 4-Bromofluoroben	zene 1.2		1.000		117	80	120			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits

WO#: 1210358

19-Oct-12

_

HALL ENVIRONMENTAL ANALYSIS LABORATORY

• •

Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105 TEL: 505-345-3975 FAX: 505-345-410; Website: www.hallenvironmental.com

Sample Log-In Check List

Clie	nt Name:	BLAGG			Wo	rk Or	der N	lumi	ber:	12103	58				
Rec	eived by/date	AT	LM,	10/05/12											
Logo	jed By:	Anne Thome		10/5/2012 10:10	:00 AM				Am	u An	~				
Com	pleted By:	Anne Thome		10/5/2012					Arm	u An	~				
Revi	ewed By:	mg		10/05/12											
<u>Cha</u>	in of Cust	tody													
1.	Were seals i	intact?				Yes		No		No	t Present	\checkmark			
2.	Is Chain of C	Custody complet	ie?			Yes	✓	No		Not	t Present				
3.	How was the	sample deliver	ed?			Cour	er								
Log	<u>In</u>														
4.	Coolers are j	present? (see 1	9. for cooler s	pecific information)	•	Yes		No			NA				
5.	Was an atter	mpt made to co	ol the samples	3?		Yes		No			NA				
6.	Were all sam	nples received a	it a temperatu	re of >0° C to 6.0°	С	Yes		No			NA				
7.	Sample(s) in	proper containe	ər(s)?			Yes		No							
8.	Sufficient sa	mple volume for	indicated test	t(s)?		Yes	\checkmark	No							
9.	Are samples	(except VOA a	nd ONG) prop	erly preserved?		Yes	✓	No							
10.	Was preserv	vative added to b	ottles?			Yes		No	V		NA				
11.	VOA vials ha	ave zero headsp	ace?			Yes		No		No V	OA Vials				
12.	Were any sa	mple containers	received brol	ken?		Yes		No	✓	Г					
		vork match bottl pancies on chair				Yes		No			# of pre bottles for pH:	served checked			
14.	Are matrices	correctly identii	fied on Chain	of Custody?		Yes	\checkmark	No				(<:	2 or >1	2 unless	noted)
15.	Is it clear what	at analyses wer	e requested?			Yes		No			A	djusted?			
		ding times able I customer for au				Yes	<	No			Cł	necked by	r:		}
Spe	cial Handl	ling (if applic	<u>cable)</u>							L					
17.	Was client no	otified of all disc	repancies with	n this order?		Yes		No			NA				
	Person	Notified:	<u></u>		Date				<u> </u>		-				
	By Who	om:		· · · · · · · · · · · · · · · · · · ·	/ia: 📋	eMai] Ph	one	🗌 Fa	ax 🗌 Ir	Person			
	Regard	ling:													
	Client I	nstructions:	···	· · · · · · · · · · · · · · · · · · ·	·		· · ·				•		····		

18. Additional remarks:

19. Cooler Information

٦	Cooler No	Temp °C	Condition	Seal Intact	Seal No	Seal Date	Signed By
	1	1.4	Good	Yes			

Page 1 of 1

Chain-of-Custody Record	Turn-Around Time:	,] 						
Client: BLAGG ENGINEERING INC. BP AMERICA Mailing Address: P.O. BOX 87 BLOOMFIELD, NM 87413 Phone #: 505-632-1199	Project Name: MONCRIEF FED 1E Project #:	HALL ENVIRONMENTAL ANALYSIS LABORATORY www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109 Tel. 505-345-3975 Fax 505-345-4107 Analysis Request						
email or Fax#: QA/QC Package: X Standard □ Level 4 (Full Validation Accreditation □ NELAP □ Other	Sampler: J. BACC	He's (8021) H (Gas only) (Gas/Diesel))))))))))))))						
Date Time Matrix Sample Request I	Container Type and # Type							
0/3/12, 0925 Soil 21 B67 S-P+€ 8' 94/12 1205 Soil 5-P+€6	4 oz x1 COUL -001							
Date: Time: Relinquished by: 19/4/13 14113 Juff Blugg	Received by: Date Time	Remarks: GRO + DRO ON BOISB						
Date: Time: Relinquished by: 14/12 1708 Christin Deles	Received by Date Time	BILL BP WO: NI555735 PK: ZSCHWLLBGT CONTACT: Jeff PEACE						

.

.

If necessary, samples submitted to Hall Environmental may be subcontracted to other accredited laboratories. This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

June 4, 2012

· (+-'

Bureau of Land Management Mark Kelly 1235 La Plata Hwy Farmington, NM 87401

VIA CERTIFIED MAIL – RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: MONCRIEF FEDERAL 001E

Dear Mark Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about June 25, 2012. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

AP Vallip

Jerry Van Riper Surface Coordinator/Business Security Representative BP America Production Company

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

June 11, 2012

\$

•

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

;

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

MONCRIEF FEDERAL 001E API 30-045-26450 (M) Section 22 – T29N – R12W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 21 bbl. BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Buddy Shaw BP Environmental Advisor

(505) 320-0401

