District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

Alternative Method:

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration OIL CONS. DIV DIST. 3
Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method NOV 2 4 2014
Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Case C 1
API Number:3004527521 OCD Permit Number:
U/L or Qtr/QtrN Section17 Township31N Range11W County:San Juan
Center of Proposed Design: Latitude36.894941 Longitude108.01775 NAD: □1927 ⋈ 1983
Surface Owner: X Federal X State Private Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Double walled/double bottomed; side walls not visible
Liner type: Thickness mil

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6. Notting: Subsection F of 10.15.17.11 NIMAC (Applies to resumment wife and resumment of the start of the st	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
8. Variances and Exceptions:	
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Uariance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acce	ntabla sauraa
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	piuvie source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - \[\sum \text{NM Office of the State Engineer - iWATERS database search; } \sum \text{USGS; } \sum \text{Data obtained from nearby wells} \]	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)	☐ Yes ☐ No
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Li res Li No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured	Yes No
from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	103 11.10
	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	NMAC 5.17.9 NMAC
II. Multi Wall Fluid Managament Pit Chacklist. Subsection B of 19 15 17 9 NMAC	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	Iuid Management Pit
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC ot be achieved)
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beling the large true, accurate and complete to the best of my knowledge and beling the large true, accurate and complete to the best of my knowledge and beling the large true, accurate and complete to the best of my knowledge and beling true, accurate and complete to the best of my knowledge and beling true, accurate and complete to the best of my knowledge and beling true, accurate and complete to the best of my knowledge and beling true, accurate and complete to the best of my knowledge and beling true, accurate and complete to the best of my knowledge and beling true, accurate and complete to the best of my knowledge and beling true, accurate and complete to the best of my knowledge and beling true, accurate and complete to the best of my knowledge and beling true, accurate and complete to the best of my knowledge and beling true, accurate and complete to the best of my knowledge and beling true, accurate and complete to the best of my knowledge and beling true, accurate and complete to the best of my knowledge and beling true, accurate and complete to the best of my knowledge and beling true, accurate and complete true accurate accura	
Signature: Date:	
e-mail address:	
	12014
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 12/12/	the closure report.
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 12/12/ Title: OCD Permit Number: OCD Permit Number: OCD Permit Number: Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report. complete this

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure requ	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Jeff Perce	Date:November 24, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479_

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Case C 1</u> <u>API No. 3004527521</u> <u>Unit Letter N, Section 17, T31N, R11W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - Notice is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	14

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and has been reclaimed since the well was plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT has been reclaimed since the well was plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT has been reclaimed since the well was plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT has been reclaimed since the well was plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

BP has seeded the area as part of final reclamation since the well was plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
 - DD shall contify that all information in the remark and attachments is account

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141

Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

		Rele	ease Notific	catio	n and Co	rrective A	ction	-		
					OPERA	ГOR	☐ Initi	al Report	\boxtimes	Final Report
					Contact: Jef	f Peace				
		ington, N	M 87401							
Facility Na	me: Case C 1				Facility Typ	e: Natural gas v	vell			
Surface Ow	ner: Federal		Mineral C)wner:	Federal		API No	. 30045275	521	
			LOCA	TIO	N OF REI	LEASE				
Unit Letter N	Section Township 17 31N	Range 11W	Feet from the 1,250	1		Feet from the 1,370	East/West Line West	County: Sa	an Juan	
	Lati	tude36	5.894941		Longitud	le108.01775_	ı			
1			NAT	URE						
Type of Rele	ase: none						Volume I	Recovered: N	J/A	_
		95 bbl								
Was Immedi		Yes [No 🛛 Not Re	equired	If YES, To	Whom?				
Name of Company: BP										
Contact: Left Peace										
Surface Company: BP										
If a Watercou	irse was Impacted, Descr	ibe Fully.*			1					
								to ensure no	soil im	pacts from
								he area unde	r the B	GT was
regulations al public health should their cor the environ	of operators are required to or the environment. The operations have failed to an addition, NMC	o report an acceptance dequately CD accep	d/or file certain re e of a C-141 repo investigate and re	elease n ort by the emediate	otifications ar e NMOCD ma e contamination	nd perform correct arked as "Final Re on that pose a thre	tive actions for rele eport" does not reli eat to ground water	eases which the eve the oper in the contract was surface was	may en ator of ter, hun	danger liability nan health
Signature:	Off Peace					OIL CONS	SERVATION	DIVISIO	N	
	e: Jeff Peace				Approved by	Environmental Sp	pecialist:			
		r			Approval Dat	e:	Expiration	Date:		
E-mail Addre	ess: peace.jeffrey@bp.com	n			Conditions of	Approval:		Attached		

Date: November 24 2014

Phone: 505-326-9479

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, BL			API #: 300	Α	1
		632-1199		(if applicble):	Α	
FIELD REPORT:	(circle one): BGT CONFIRMATION / R		OTHER:	PAGE #: _	1 of _	1_
SITE INFORMATION				DATE STARTED:	08/28/1	3_
QUAD/UNIT: N SEC: 17 TWP:		NM CNTY: SJ		DATE FINISHED:		
1/4-1/4/FOOTAGE: 1,250'S / 1,37	O'W SE/SW LEASE TYP	E: FEDERAL/STATE	/ FEE / INDIAN	ENVIRONMENTAL		
		TRACTOR: MBF - S.	PEREZ	SPECIALIST(S):	<u>JCB</u>	
REFERENCE POINT					EV.: <u>6,168</u>	3'
1) 95 BGT (DW/DB)				_	90', S38E	=
2)						
3)						
4)				ARING FROM W.H.:		OVM
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR L		L<u>L</u>		REA (pr	ADING pm)
1) SAMPLE ID: 95 BGT 5-pt. @ (` '	1.3
2) SAMPLE ID:						
3) SAMPLE ID:						
4) SAMPLE ID:						
SOIL COLOR: MOI COHESION (ALL OTHERS): NON COHESIVE SLIGHTI CONSISTENCY (NON COHESIVE SOILS): L MOISTURE: DRY/SLIGHTLY MOIST MOIST/W SAMPLE TYPE: GRAB COMPOSITE DISCOLORATION/STAINING OBSERVED ANY AREAS DISPLAYING WETNESS: YES / NO.	DERATE BROWN YCOHESIVE COHESIVE / HIGHLY COHESIVE DOSE FIRM DENSE / VERY DENSE JET / SATURATED / SUPER SATURATED OF PTS5 YES /NO EXPLANATION -	PLASTICITY (CLAYS): NON P DENSITY (COHESIVE HC ODOR DETECTI	PLASTIC / SLIGHTLY PLASTIC / CLAYS & SILTS): SOFT ED: YES NO EXPL	COHESNE / MEDIUM PLAST - / FIRM / STIFF / VER' ANATION -	Y STIFF / HARD	
APPARENT EVIDENCE OF A RELEASE (ADDITIONAL COMMENTS: GAS WELL						
ADDITIONAL COMMENTS: GAS WELL	RECENTLY PLUGGED AND ABANDO	NEU (P & A).				
SOIL IMPACT DIMENSION ESTIMATION DEPTH TO GROUNDWATER: <100'		t. X <u>NA</u> ft. NEAREST SURFACE WATER:		TIMATION (Cubic Ya CD TPH CLOSURE STO	,	
SITE SKETCH	THE WILL SOURCE.				, <u>1,000</u> pp	
SHE SKETCH	⊕ P & A MARKER	PLOT PLAN cir	_ OVM	CALIB. READ. =		= 1.00
			<u> </u>	MISCELL VO: N15269 O #: K: ZFEIRK	705	3
	PBGTL			K: ZFEIRK J#:	0000	
	T.B. $\sim 6' \longrightarrow (x \ x \ x)$		1 -	ermit date(s):	06/14/10	
	B.G. x		O	CD Appr. date(s):	09/11/13 c Vapor Meter	
			<u> </u>	DOT Cide - U- VC-		
		Y _	S.P.D.	BGT Sidewalls Vis		
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATI	ON DEPRESSION; B.G. = BELOW GRADE: B = BELOV		; W.H. = WELL HEAD;	BGT Sidewalls Vis	·	
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BE	.OW-GRADE TANK LOCATION; SPD = SAMPLE POIN E WALL; DW - DOUBLE WALL; SB - SINGLE BOTTON	T DESIGNATION; R.W. = RETAINING	G WALL; NA - NOT	lagnetic declinat	ion: 10° E	
TRAVEL NOTES: CALLOUT:	E 18/16 DIT - DOUBLE TANCE OF - CHACLE DO LION		/28/13			

Analytical Report

Lab Order 1308C95

Hall Environmental Analysis Laboratory, Inc. Date Reported: 9/6/2013

CLIENT: Blagg Engineering

Client Sample ID: 95 BGT 5-pt @ 6'

Project: Case C 1 Collection Date: 8/28/2013 9:45:00 AM

1308C95-001 Lab ID:

Matrix: SOIL Received Date: 8/29/2013 10:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGI	ORGANICS				Analyst	BCN
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	8/30/2013 8:27:55 PM	9101
Surr: DNOP	94.9	63-147	%REC	1	8/30/2013 8:27:55 PM	9101
EPA METHOD 8015D: GASOLINE RAI	NGE				Analyst	: NSB
Gasoline Range Organics (GRO)	ND	4.9	mg/Kg	1	8/31/2013 2:43:45 AM	9106
Surr: BFB	85.6	80-120	%REC	1	8/31/2013 2:43:45 AM	9106
EPA METHOD 8021B: VOLATILES					Analyst	: NSB
Benzene	ND	0.049	mg/Kg	1	8/31/2013 2:43:45 AM	9106
Toluene	ND	0.049	mg/Kg	1	8/31/2013 2:43:45 AM	9106
Ethylbenzene	ND	0.049	mg/Kg	1	8/31/2013 2:43:45 AM	9106
Xylenes, Total	ND	0.097	mg/Kg	1	8/31/2013 2:43:45 AM	9106
Surr: 4-Bromofluorobenzene	92.8	80-120	%REC	1	8/31/2013 2:43:45 AM	9106
EPA METHOD 300.0: ANIONS					Analyst	JRR
Chloride	14	1.5	mg/Kg	1	8/30/2013 1:02:10 PM	9115
EPA METHOD 418.1: TPH					. Analyst	BCN
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	9/3/2013	9107

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- Analyte detected below quantitation limits J
- Ο RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits
- В Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- Not Detected at the Reporting Limit ND
- Not Detected at the Reporting Limit $Page \ 1 \ of \ 6$ Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1308C95

06-Sep-13

Client:

Blagg Engineering

Project:

Case C 1

Sample ID: 1308C94-001AMS

SampType: MS

TestCode: EPA Method 300.0: Anions

LowLimit

58.8

Client ID:

BatchQC

Batch ID: 9115

RunNo: 13012

Prep Date: 8/30/2013 Analysis Date: 8/30/2013

SeqNo: 371630

Units: mg/Kg

%RPD

%RPD

0.451

Analyte

Result

Qual

Chloride

130

PQL SPK value SPK Ref Val 7.5 15.00

%REC 181

HighLimit 109 **RPDLimit** S

Sample ID: 1308C94-001AMSD

SampType: MSD

TestCode: EPA Method 300.0: Anions

Client ID:

BatchQC

Batch ID: 9115

7.5

RunNo: 13012

SeqNo: 371631

Units: mg/Kg

Prep Date: 8/30/2013 Analysis Date: 8/30/2013

140

SPK value SPK Ref Val

107.5

%REC LowLimit HighLimit

RPDLimit

Qual

Analyte Chloride

PQL

15.00

107.5

185

58.8

109

20

S

Qualifiers:

R

Value exceeds Maximum Contaminant Level.

Value above quantitation range Ε Analyte detected below quantitation limits

RSD is greater than RSDlimit O

RPD outside accepted recovery limits Spike Recovery outside accepted recovery limits Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit ND

Sample pH greater than 2 for VOA and TOC only.

Reporting Detection Limit

Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1308C95 06-Sep-13

Client:

Blagg Engineering

Project:

Case C 1

Sample ID: MB-9107

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID: PBS

8/29/2013

Batch ID: 9107

Analysis Date: 9/3/2013

RunNo: 13029 SegNo: 371996

Units: mg/Kg

HighLimit

%RPD **RPDLimit** Qual

Qual

Petroleum Hydrocarbons, TR

Result ND

PQL

20

TestCode: EPA Method 418.1: TPH

Sample ID: LCS-9107

Prep Date:

Analyte

Analyte

SampType: LCS

RunNo: 13029

Client ID: LCSS Prep Date: 8/29/2013

Batch ID: 9107 Analysis Date: 9/3/2013

%REC

96.7

Units: mg/Kg HighLimit

SPK value SPK Ref Val

SeqNo: 371997

80

%RPD

RPDLimit Qual

Petroleum Hydrocarbons, TR

97 20

PQL

20

SPK value SPK Ref Val %REC LowLimit

TestCode: EPA Method 418.1: TPH

LowLimit

120

Sample ID: LCSD-9107

Client ID: LCSS02

SampType: LCSD Batch ID: 9107

RunNo: 13029

Units: mg/Kg

120

Prep Date: 8/29/2013

Analysis Date: 9/3/2013

95

SeqNo: 371999

RPDLimit

Analyte Petroleum Hydrocarbons, TR

Result

SPK value SPK Ref Val %REC 100.0

100.0

95.3

LowLimit HighLimit 80

%RPD 1.38

20

Qualifiers:

Value exceeds Maximum Contaminant Level.

Ε Value above quantitation range

Analyte detected below quantitation limits J

RSD is greater than RSDlimit 0

RPD outside accepted recovery limits R Spike Recovery outside accepted recovery limits Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Н

ND Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

Reporting Detection Limit RL

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1308C95

06-Sep-13

Client:

Blagg Engineering

Project:	Case C 1										
Sample ID:	MB-9101	SampT	ype: Mi	BLK	Tes	TestCode: EPA Method 8015D: Diesel Range Organics					
Client ID:	PBS	Batch	n ID: 91	01	F	RunNo: 1	2963				
Prep Date:	8/29/2013	Analysis D	ate: 8/	29/2013	S	SeqNo: 3	70092	Units: mg/k	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	.HighLimit	%RPD	RPDLimit	Qual
Diesel Range	Organics (DRO)	ND	10			·					
Surr: DNOP		7.9		10.00		78.5	63	147			
Sample ID:	LCS-9101	SampT	ype: LC	s	Tes	tCode: El	PA Method	8015D: Dies	el Range C	Organics	-
Client ID:	LCSS	Batch	ID: 91	01	F	RunNo: 1	2963				
Prep Date:	8/29/2013	Analysis D	ate: 8/	29/2013	9	SeqNo: 3	70093	Units: mg/F	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range (Organics (DRO)	59	10	50.00	0	119	77.1	128			<u>-</u> ·
Surr: DNOP		4.1		5.000		82.1	63	147			
Sample ID:	1308C34-002AMSI) SampT	уре: М .S	SD	Tes	tCode: Ef	PA Method	8015D: Dies	el Range C	rganics	
Client ID:	BatchQC	Batch	ID: 91	01	F	RunNo: 1	2997				
Prep Date:	8/29/2013	Analysis D	ate: 8/	30/2013	SeqNo: 370991			Units: mg/Kg			
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range (Organics (DRO)	54	10	49.75	15.25	77.1	61.3	138	7.90	20	
Surr: DNOP		4.5		4.975		91.0	63	147	0	0	
Sample ID:	1308C34-002AMS	SampT	ype: MS	3	Tes	tCode: EF	PA Method	8015D: Diese	el Range C	rganics	
Client ID:	BatchQC	Batch	ID: 91	01	F	RunNo: 12	2997				
Prep Date:	8/29/2013	Analysis D	ate: 8/	30/2013	S	SeqNo: 370995 Units					
Analyte		Result	PQL		SPK Ref Val		LowLimit	HighLimit	%RPD	RPDLimit	Qual
_	Organics (DRO)	50	9.9	49.70	15.25	69.0	61.3	138			
Surr: DNOP		4.2		4.970		85.2	63	147			

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range Е
- Analyte detected below quantitation limits
- RSD is greater than RSDlimit O
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits S
- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
 - Sample pH greater than 2 for VOA and TOC only.
- Reporting Detection Limit RL

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1308C95

06-Sep-13

Client:

Blagg Engineering

Project:	Case C 1										
Sample ID: ME	B-9106	SampT	ype: ME	BLK	TestCode: EPA Method 8015D: Gasoline Range						
Client ID: PE	BS	Batch ID: 9106			F	RunNo: 1:	2996				
Prep Date: 8	/29/2013	Analysis D	ate: 8/	30/2013	5	SeqNo: 3	71549	Units: mg/l	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Or	rganics (GRO)	ND	5.0								
Surr: BFB		930		1000		93.0	80	120			
Sample ID: LC	S-9106	SampT	ype: LC	s	Tes	tCode: EF	PA Method	8015D: Gaso	oline Rang	e	
Client ID: LC	ss	Batch	ID: 91	06	F	RunNo: 1	2996				
Prep Date: 8.	/29/2013	Analysis Date: 8/30/2013			S	SeqNo: 3	71550	Units: mg/h	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Or	rganics (GRO)	26	5.0	25.00	0	104	74.5	126			
Surr: BFB		1000		1000	<u></u>	102	80	120			
Sample ID: 130	08C81-001AMS	SampT	уре: МS	3	Tes	tCode: EF	PA Method	8015D: Gaso	oline Rang	е	
Client ID: Ba	tchQC	Batch	ID: 91	06	RunNo: 12996						
Prep Date: 8	/29/2013	Analysis D	ate: 8/	30/2013	SeqNo: 371552			Units: mg/h	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Or	ganics (GRO)	29	4.9	24.49	0	117	76	156			
Surr: BFB		1000		979.4		104	80	120			
Sample ID: 130	08C81-001AMSD) SampT	/pe: MS	SD	Tes	tCode: EF	A Method	8015D: Gaso	line Rang	e	
Client ID: Ba	tchQC	Batch	ID: 910	06	R	RunNo: 12	2996				
Prep Date: 8/	/29/2013	Analysis Da	ate: 8/	30/2013	S	SeqNo: 37	71553	Units: mg/k	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Or	ganics (GRO)	28	4.9	24.51	0	116	76	156	0.797	17.7	
Surr: BFB		1000		980.4		103	80	120	0	0	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1308

1308C95 06-Sep-13

Client:

Blagg Engineering

Project:

Case C 1

Sample ID: MB-9106	Samp	SampType: MBLK			TestCode: EPA Method 8021B: Volatiles								
Client ID: PBS	Batc	h ID: 91 6	06	F	RunNo: 1	2996							
Prep Date: 8/29/2013	Analysis [Date: 8/	30/2013	SeqNo: 371610 U		Units: mg/K							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	ND	0.050	•										
Toluene	ND	0.050											
Ethylbenzene	ND	0.050											
Xylenes, Total	ND	0.10											
Surr: 4-Bromofluorobenzene	1.0		1.000		105	80	120						
Sample ID: LCS-9106	Tes	tCode: El	PA Method	8021B: Volat	iles								

Sample ID: LCS-9106	S	Tes	tCode: El	PA Method	8021B: Volat	tiles				
Client ID: LCSS	Batc	h ID: 91 0	06	F	RunNo: 1.	2996				
Prep Date: 8/29/2013	Analysis [Date: 8/	30/2013	SeqNo: 371611			Units: mg/K			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.97	0.050	1.000	0	96.7	80	120			
Toluene	0.97	0.050	1.000	0	96.8	80	120			
Ethylbenzene	0.99	0.050	1.000	0	99.1	80	120			
Xylenes, Total	3.0	0.10	3.000	0	99.1	80	120			
Surr: 4-Bromofluorobenzene	1.0		1.000		102	80	120	•		

Sample ID: 1308C93-001AN	TestCode: EPA Method 8021B: Volatiles											
Client ID: BatchQC	Batc	Batch ID: 9106 Analysis Date: 8/30/2013			RunNo: 12996							
Prep Date: 8/29/2013	Analysis [SeqNo: 3	71613	Units: mg/K					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Benzene	1.0	0.048	0.9533	0	105	67.3	145					
Toluene	1.0	0.048	0.9533	0.004317	105	66.8	144					
Ethylbenzene	1.0	0.048	0.9533	0	106	61.9	153					
Xylenes, Total	3.1	0.095	2.860	0	107	65.8	149					
Surr: 4-Bromofluorobenzene	1.0		0.9533		105	80	120					

Sample ID: 1308C93-001AMS	D SampT	ype: MS	D	8021B: Volat	iles					
Client ID: BatchQC	Batch	ID: 91 0	06	F						
Prep Date: 8/29/2013	Analysis D	ate: 8/	30/2013	S	SeqNo: 3	71614	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit %RP		RPDLimit	Qual
Benzene	0.92	0.048	0.9524	0	96.4	67.3	145	8.62	20	
Toluene	0.92	0.048	0.9524	0.004317	95.9	66.8	144	8.98	20	
Ethylbenzene	0.94	0.048	0.9524	0	98.5	61.9	153	7.43	20	
Xylenes, Total	2.8	0.095	2.857	57 0 98.3 65.8			149	8.54	20	
Surr: 4-Bromofluorobenzene	0.98		0.9524		103	80	120	0	0	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
 - P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name:	BLAGG	r: 1308C9	5			RcptNo: 1								
Received by/dat	te:										:			
Logged By:	Ashley Gall	egos	8/29/2013	10:00:00 A	M	5	47							
Completed By:	Ashley, Gall	egos	8/29/2013	12:06:36 P	М	~	A							
Reviewed By:	M		1	ala			, 0							
Chain of Cus	stody \		0 = 12	7113										
1. Custody sea	V	mple bottles?			Yes :	i	No	: :	Not Present	~				
2. Is Chain of 0					Yes 🗸		No		Not Present	:				
3. How was the	-				Courier									
Log In														
4. Was an atte	empt made to c	cool the sample	s?		Yes N		No	!!	NA					
5. Were all sar	mples received	at a temperatu	re of >0°C to	o 6.0°C	Yes 🗸	'i	No i		NA :	·				
6. Sample(s) i	in proper contai	iner(s)?			Yes N		No	1:						
7. Sufficient sample volume for indicated test(s)?					Yes	/	No							
8. Are samples	s (except VOA	and ONG) prop	erly preserve	d?	Yes 🗸	r i	No	:						
9. Was preser	vative added to	bottles?			Yes	i	No		NA !					
10.VOA vials h	ave zero heads	space?			Yes	1	No	: :	No VOA Vials	V				
11. Were any s	sample contains	ers received bro	ken?		Yes	İ	No	V						
									# of preserved bottles checked	į				
12.Does paper					Yes 🔻		No	1	for pH:	·-2 ~	r >12 unless noted)			
		ain of custody)	of Curtody?		Yes	ø!	No		Adjusted		1 > 12 uniess noteu)			
13. Are matrice 14. Is it clear w			or Custody r		Yes V		No	i						
15. Were all ho					Yes •		No		Checked I	by:				
(If no, notify	customer for a	authorization.)						·						
Special Hand	dling (if app	olicable)												
16. Was client	notified of all di	screpancies wit	h this order?		Yes	1	No	!	NA	✓,				
Perso	n Notified:	TAPANTANA TATATA PARISANA AND AND AND AND AND AND AND AND AND	**************************************	Date:		And the Control of the Control	THE PROPERTY AND ADDRESS.	nentant.			:			
By W	į.	(#) by: 8°07/47/877/873 with 18°19/19/19/19/19/19/19	**************************************	Via:	i ¦ eMail	Pho	ne :	Fax	! !In Person					
Rega	i i	THE RESERVE THE PROPERTY OF TH	t de empleo de la la la desenta de la Carta de la Cart	Contract Con		KANTON AND AND AND AND AND AND AND AND AND AN	TAND NITH DRAW	en an en en en en en en	THE RESERVE OF THE PROPERTY OF THE PARTY OF	eur				
Client	t Instructions:					Television of the features.								
17. Additional	remarks:										•			
18. Cooler Inf	ormation													
Cooler	No Temp °C	-	Seal Intact	Seal No	Seal Date	s	igned E	Ву						
1	1.0	Good Y	'es			<u></u>								

Chain-of-Custody Record			Turn-Around Time:										_	813 <i>4</i>		. ~		.a =		A I		
Client:	BLAGE	e ENGL	NEELING INC.	X Standard □ Rush						HALL ENVIRONMENTAL ANALYSIS LABORATORY												
	BP B	MERICA	\ .	Project Name: CASE C 1				www.hallenvironmental.com														
Mailing	Address	P.O.	Box 87						49	01 H	Hawkins NE - Albuquerque, NM 87109											
	BiMM	F(E).D.	NM 87413	Project #:				}	Τe	el. 50	5-34	5-39	975	5 Fax 505-345-4107								
Phone			32-1199	·									Ã	Analysis Request:						in poet	i i	
email o		<u> </u>		Project Mana	ger:				<u>{</u>	(P)					(†							Т
QA/QC Package: Standard Level 4 (Full Validation)			1	3LAG6			EMB\$ (8021)	Gas or	财 / O:			SIMS)		PO ₄ ,SC	PCB's	:						
Accred				Sampler:	BLAGG	-		貸		DR.			S O		0,	082				,		
□ NEL	□ NELAP □ Other		On Ice:	22865 :: :			1	 	Š	18.1	9.	827		3,8	8/9		F	W	.		ا ام	
□ EDD (Type)		On ice: 12/2/20/es 12/3/Ne 14/2/Sample: Temperature 1/2/20/20/20/20/20/20/20/20/20/20/20/20/2				H	9	d 4	3d 5	o C	tals	Ž.	ides	7	-VO	2			≥			
Date	Time	Matrix	Sample Request ID	ł	Preservative Type		LNo. よ	BTEX + ₩	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO / DRO / MEC)	TPH (Method 418.1)	EDB (Method 504.1)	PAH's (8310 or 8270	RCRA 8 Metals	Anions (F,CI,NO3,NO2,PO4,SO4)	8081 Pesticides / 8082 PCB's	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE			Air Bubbles (Y or N)
9/28/12	0945	SOIL	95 Bit 5-p= @6"	402×1	COUL		001	×		×	X								Х		\top	T
1/13							<u> </u>	 													_	+
		· · · · · · · · · · · · · · · · · · ·						\vdash								i					+	+
							<u> </u>	<u> </u>			$\vdash \vdash$		_						\sqcup			_
																				.		
																						T
																						1
																			\square		+-	十
	 							-								_			\vdash		+	╬
	<u> </u>	 		1				-	ļ <u>.</u>									_		 		+
		<u> </u>				<u>.</u>		-											1	· ·		+
	<u> </u>							_	ļ								_				\perp	_
	<u> </u>																					
Date: 3/28/3	Time: 10:35	Relinquish	ed by: Shipsy	Received by: Date Time Page 10:35			Rer	nark		AKE AKE	L		FE.	IR	KG)S:	TS					
Date:	Time:	Reknquish	ed by:	Received by:	4	Date	lime								_							
8] ₂₈] ₁₃	1710	L/Jhai	othe Walters	1 4		7	31000				DNY;		٤		FF					-		
•	f necessary,	samples sub	mitted to Hall Environmental may be sub-	contracted to other	ccredited laboratori	es. This serves	as notice of this	s possi	bility.	Any sı	ıb-cont	racted	data	wili be	cleari	ly nota	ted or	the a	nalytic	al report		





BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

May 5, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: CASE C 001 API #: 3004527521

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America. Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about May 6, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper Surface Land Negotiator

ADVELYR

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

May 29, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

CASE C 001 API 30-045-27521 (G) Section 17-T31N-R11W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



