<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or	
1242 Proposed Alternative Method Permit or Closure Plan Application	
Type of action: Below grade tank registration OIL CONS. DIV DIST.	3
Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method DEC 0.2 2014	
Modification to an existing permit/or registration	
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method	
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request	
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinary.	ances.
Operator: BP America Production CompanyOGRID#:778	
Address:200 Energy Court, Farmington, NM 87401	
Facility or well name:McCulley LS 2A	
API Number:3004529305OCD_Permit Number:11423	
U/L or Qtr/Qtr E Section 14 Township 28N Range 9W County: San Juan	
Center of Proposed Design: Latitude36.664914 Longitude107.764360 NAD: ☐1927 ☒ 1983	
Surface Owner: ☐ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment	
2.	
Pit: Subsection F, G or J of 19.15.17.11 NMAC	
Temporary: Drilling Workover	
Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no ☐ Lined ☐ Unlined Liner type: Thickness mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other	
String-Reinforced	
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D	
3.	
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank B	
Volume:21.0bbl Type of fluid:Produced water	
Tank Construction material:Steel	
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	
☐ Visible sidewalls and liner ☑ Visible sidewalls only ☐ Other _Single walled/double bottomed	
Liner type: Thicknessmil	

Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

5.	
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6. Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
8.	
<u>Variances and Exceptions</u> : Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accematerial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
	i .

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC	,
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC	
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	
- Terrotatij Typro od Beorgii (attaun edy) of debright	

Form C-144 Oil Conservation Division Page 3 of 6

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	·
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	Suid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	·
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable south provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	103 <u></u> 110

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	
Within a 100-year floodplain FEMA map	
- 1 LiviA map	163 140
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believes the complete to the best of my knowledge and believes the complete to the best of my knowledge.	of.
Name (Print): Title:	
Signature: Date:	
e-mail address:Telephone:	
18. OCD Approval: ☐ Permit Application (including closure plan) ☐ Closure Plan (only) ☐ OCD Conditions (see attachment)	
OCD Representative Signature:	2014
Title: Compliance Office Office Office OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report.
Title: Compliance Occident OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not	the closure report.
Title: Compliance Office Office Office OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report. complete this

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure require	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Jeff Passe	Date:December 2, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

McCulley LS 2A, BGT Tank B (21 bbl) API No. 3004529305 Unit Letter E, Section 14, T28N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)

- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)
 - All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.
- 4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT, Tank B	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	90
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141** is attached.

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed as part of final reclamation when the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed as part of final reclamation when the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed as part of final reclamation when the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative

BP will seed the area as part of final reclamation when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141

Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Release Notification	on and Corrective Acti	ion		
	OPERATOR	☐ Initia	l Report 🛛	Final Report
Name of Company: BP	Contact: Jeff Peace		·	1
Address: 200 Energy Court, Farmington, NM 87401	Telephone No.: 505-326-9479			
Facility Name: McCulley LS 2A	Facility Type: Natural gas well			
Surface Owner: Federal Mineral Owner	:: Federal	API No.	3004529305	
LOCATIO	ON OF RELEASE			
	th/South Line Feet from the Ea	ast/West Line 'est	County: San Jua	n
Latitude 36.664914	Longitude107.764360			
NATUR	E OF RELEASE			
Type of Release: none	Volume of Release: N/A	Volume Re	ecovered: N/A	
Source of Release: below grade tank – 21 bbl, Tank B	Date and Hour of Occurrence:		lour of Discover	y:
Was Immediate Notice Given? ☐ Yes ☐ No ☒ Not Require	If YES, To Whom?			
By Whom?	Date and Hour			
Was a Watercourse Reached?	If YES, Volume Impacting the V	Watercourse.		
☐ Yes ☒ No				
If a Watercourse was Impacted, Describe Fully.*				
Describe Cause of Problem and Remedial Action Taken.* Sampling of	the soil beneath the BGT was done d	uring removal to	ensure no soil in	npacts from
the BGT. Soil analysis resulted in TPH, BTEX and chloride below stan				•
Describe Area Affected and Cleanup Action Taken.* BGT was removed	I and the area underneath the BGT w	as sampled. The	e area under the l	3GT was
backfilled and compacted and is still within the active well area.				
			······································	
I hereby certify that the information given above is true and complete to				
regulations all operators are required to report and/or file certain release public health or the environment. The acceptance of a C-141 report by				
should their operations have failed to adequately investigate and remedi	ate contamination that pose a threat t	o ground water,	surface water, hu	ıman health
or the environment. In addition, NMOCD acceptance of a C-141 report	does not relieve the operator of response	onsibility for co	mpliance with an	y other
federal, state, or local laws and/or regulations.	OIL CONSEI	PVATIONI	OIVISION	
0.00	OIL CONSEI	KVATIONI	<u> </u>	
Signature: VIK Josee				
Printed Name: Jeff Peace	Approved by Environmental Specia	alist:	,	
Title: Field Environmental Coordinator	Approval Date:	Expiration D	ate:	
E-mail Address: peace.jeffrey@bp.com	Conditions of Approval:		A441- 1 🔽	
			Attached	
Date: December 2, 2014 Phone: 505-326-9479				

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, BLO	INEERING, INC. OMFIELD, NM 87413	API #: 3004529305
	(505)	632-1199	(if applicable):
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELI	EASE INVESTIGATION / OTHER:	PAGE #: 1 of 1
SITE INFORMATION	1: SITE NAME: MCCULLEY	′LS#2A	DATE STARTED: 09/19/13
QUAD/UNIT: E SEC: 14 TWP:	28N RNG: 9W PM; N	IM CNTY: SJ ST: NN	DATE FINISHED:
1/4-1/4/FOOTAGE: 1,545'N / 895"	W SW/NW LEASE TYPE:	FEDERAL/STATE/FEE/INDIAN	ENVIRONMENTAL
LEASE #: NM04208	PROD. FORMATION: PC CONTR	ELKHORN ACTOR: MBF - K. AMBROSE	SPECIALIST(S): NJV
REFERENCE POINT	T: WELL HEAD (W.H.) GPS COC	ORD.: 36.66522 X 107.763	392 GL ELEV.: 5,778'
1) 21 BGT (SW/DB)	GPS COORD.: 36.664	914 X 107.764360 DISTANC	CE/BEARING FROM W.H.: 97', S45W
2)	GPS COORD.:	DISTANC	CE/BEARING FROM W.H.:
3)	GPS COORD.:	DISTANC	CE/BEARING FROM W.H.:
4)	GPS COORD.:	DISTANC	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAB	USED: HALL	OVM READING (ppm)
1) SAMPLE ID: 5 PC-TB @ 6' (21) SAMPLE DATE: 09/19/13	SAMPLETIME:0915 LAB ANALYSIS: 418	3.1/8015B/8021B/300.0(CI) NA
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANALYSIS:	
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANALYSIS:	
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANALYSIS:	
SOIL DESCRIPTION	SOIL TYPE: SAND/SILTY SAN	D/SILT/SILTYCLAY/CLAY/GRAVEL	OTHER
SOIL COLOR: MOE			
COHESION (ALL OTHERS): NON COHESIVE SLIGHTL CONSISTENCY (NON COHESIVE SOILS): L MOISTURE: DRY / SLIGHTLY MOIST MOIST / MOIST / W SAMPLE TYPE: GRAB COMPOSITE TO SISCOLORATION/STAINING OBSERVED	DOSE / FIRM / DENSE / VERY DENSE ET / SATURATED / SUPER SATURATED # OF PTS	, ,	STIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC SOFT / FIRM / STIFF / VERY STIFF / HARD XPLANATION -
	EXPLANATION - FROM RECENT PRECIPIT		
	DBSERVED AND/OR OCCURRED: YES (S SHARED WITH BP'S McCULLEY LS#		cCULLEY LS # 4S.
			ESTIMATION (Cubic Yards): NA MOCD TPH CLOSURE STD: 100 ppm
SITE SKETCH	·	PLOT PLAN circle: attached	OVM CALIB. READ. = NA ppm RF = 0.52
	PROD. TANK	#4S ⊕ N	OVM CALIB. GAS = <u>NA</u> ppm Time: <u>NA</u> am/pm date: <u>NA</u>
	/		MISCELL. NOTES
	BERM		wo: N15293637
COMPRESSOR	OD.	A 0.11	PO#: 4300183308
	NK	#2A W.H. ⊕	PK:
			PJ#:
95 BBL		#8 P&A Marker	Permit date(s): 04/07/11
DW/DB BGT		\oplus wooden	OCD Appr. date(s): 10/04/13 Tank OVM = Organic Vapor Meter
	PBGTL T.B. ~ 6'	R.W.	D ppm = parts per million B BGT Sidewalls Visible:(Y)/ N
SEPARAT	OR B.G.	YEDD	BGT Sidewalls Visible: Y / N
NOTES: BGT = BELOW-GRADE TANK, E.D. = EXCAVATI	ON DEPRESSION; B.G. = BELOW GRADE: B = BELOW; T	X - S.P.D. TH. = TEST HOLE; ~ = APPROX.; W.H. = WELL HEAD;	BGT Sidewalls Visible: Y / N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL	OW-GRADE TANK LOCATION; SPD = SAMPLE POINT DI	ESIGNATION; R.W. = RETAINING WALL; NA - NOT	Magnetic declination: 10° E
TRAVEL NOTES: CALLOUT	E WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; DI	ONSITE: 09/19/13	

Analytical Report Lab Order 1309B13

Date Reported: 10/4/2013

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Project: McCulley LS #2A

Lab ID:

1309B13-001 Matrix: SOIL

Client Sample 1D: 5PC-TB @ 6' (21)

Collection Date: 9/19/2013 9:15:00 AM

Received Date: 9/24/2013 10:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	GE ORGANICS				Analysi	: JME
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	9/26/2013 2:00:49 PM	9463
Surr: DNOP	92.3	63-147	%REC	1	9/26/2013 2:00:49 PM	9463
EPA METHOD 8015D: GASOLINE R	ANGE				Analyst	: NSB
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	9/26/2013 2:36:40 PM	9491
Surr: BFB	84.2	80-120	%REC	1	9/26/2013 2:36:40 PM	9491
EPA METHOD 8021B: VOLATILES					Analyst	: NSB
Benzene	ND	0.047	mg/Kg	1	9/26/2013 2:36:40 PM	9491
Toluene	ND	0.047	mg/Kg	1	9/26/2013 2:36:40 PM	9491
Ethylbenzene	ND	0.047	mg/Kg	1	9/26/2013 2:36:40 PM	9491
Xylenes, Total	ND	0.093	mg/Kg	1	9/26/2013 2:36:40 PM	9491
Surr: 4-Bromofluorobenzene	92.5	80-120	%REC	1	9/26/2013 2:36:40 PM	9491
EPA METHOD 300.0: ANIONS					Analyst	: JRR
Chloride	ND	7.5	mg/Kg	5	9/30/2013 10:02:36 AM	9548
EPA METHOD 418.1: TPH					Analyst	: JME
Petroleum Hydrocarbons, TR	90	20	mg/Kg	1	9/30/2013	9480

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 6

- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Cl	nain-c	of-Cus	stody Record	i um-Around	ıme:		1.			£	AL			7 17	et e	20	. R.I I	ME	AIT		
Client:	BLAG	G ENGR.	/ BP AMERICA	✓ Standard Project Name	Rush_						\N	AL	YS	SI	S L	_AI	ВО	ME RA			
Mailing Ad	dress:	P.O. BO	X 87	 N	COULLEY LS	# 2A		49	01 H						nme			n 37109	ı		
		BLOOM	FIELD, NM 87413	Project #:			7		el. 50						505						
Phone #:		(505) 63	2-1199					. 7		GLJF.	2	Ĭ	Inal	ysis	Red	ques	st ,		p ph.		
email or F	ax#:			Project Manag	јег.			Γ.	nu					\$				ਜ	T		T
QA/QC Pad Standa	_		Level 4 (Full Validation)	_	NELSON VE	ELEZ	#B5=(8021B)	1	1		į	15)		PO4,SO.	PCB's) · 		er - 300.1)			e l
Accreditat	ion:			Sampler:	NELSON VE	ELEZ nu	Î	(Gas	/ DRO /	त्	(T:	OSIN		02	8082			/ water			힐
□ NELAP		☐ Other		On ice	YÛYes			HAT	1/0	418.1)	504.1)	827	ι,	0,50	_		₹ (¥)	0.00			8 :
□ EDD (T	ype)			Sample Temp	efature ×2	<u>, </u>	4	## ##	(GR	bot	pot	ō	etal	S	cide	Æ)- <u>-</u> (1	ا ا	<u> </u>
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO. 1309813.	BTEX ++NTB	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO	TPH (Method	EDB (Method	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 /		Grab sample	5 pt. composite sample
9/19/13	0915	SOIL	5PC - TB @ 6' (21)	4 oz 1	Cool	-001	V		V	7								٧		1	_
																			\neg		十
																				\top	十
		 					1	1									\Box	-	+	_	十
							1-	\vdash											+	\top	+
				 	·		 	╁						_					+	┪	十
		1		<u> </u>		 	+								-			-	-	+	+
		 		<u> </u>			+												+	+	+
							╁	_	-		_			-	-	-			\dashv	+	+
							╁	├-	-										+	-	+
l							+	-	-									-	-		+
				<u> </u>			-	-											+	_	+
Date:	Time:	Relinquish	ed by:	Received by:	<u> </u>	Date Time	1000									لـــا					
9/20/13	ISDO	MA	in Vf	Christin	Walter	9/20/13 1580	S	nark end i	s: nvoi	e to		egg E	ngin	eeri	ng, Ir	ıc.					
Date:	Time:	Relinquish	Matter Woller Carbonities to Hall Environmental may be s	Recaived by	× 09/2	Date Time US 00	1				P.C Blo	o. Bo	x 87 ield,	NM	874	13					

Hall Environmental Analysis Laboratory, Inc.

WO#: 1309B13

04-Oct-13

Client: Project:

Blagg Engineering

Sample ID MB-9548

McCulley LS #2A

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 9548

RunNo: 13733

9/30/2013

Analysis Date: 9/30/2013

PQL

PQL

1.5

SeqNo: 391761

Units: mg/Kg

HighLimit

Prep Date:

%RPD

RPDLimit Qual

Analyte Chloride

ND 1.5

Sample ID LCS-9548

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

Batch ID: 9548

RunNo: 13733

%REC LowLimit

110

Prep Date: 9/30/2013 Analysis Date: 9/30/2013

Result

15

Result

SeqNo: 391762

Units: mg/Kg

%RPD **RPDLimit**

Analyte Chloride

SPK value SPK Ref Val 15.00

SPK value SPK Ref Val

15.00

15.00

SPK value SPK Ref Val

%REC 97.7

LowLimit HighLimit Qual

Sample ID 1309B13-001AMS

SampType: MS

TestCode: EPA Method 300.0: Anions

90

RunNo: 13733

LowLimit

58.8

58.8

Client ID: Prep Date:

5PC-TB @ 6' (21)

Batch ID: 9548

SeqNo: 391765

99.0

%REC

Units: mg/Kg HighLimit

109

Analyte

9/30/2013

Analysis Date: 9/30/2013

PQL

7.5

n

RPDLimit Qual

Chloride

9/30/2013

Sample ID 1309B13-001AMSD

SampType: MSD

TestCode: EPA Method 300.0: Anions

Client ID:

5PC-TB @ 6' (21)

Batch ID: 9548

RunNo: 13733

Prep Date:

Units: mg/Kg

Analysis Date: 9/30/2013

SeqNo: 391766

98.9

109

Analyte

Result

20

POL SPK value SPK Ref Val

%REC

HighLimit LowLimit

%RPD 0.141

%RPD

RPDLimit Qual

Chloride

15 7.5

Client ID:

BatchQC

SampType: MS

Prep Date: 9/30/2013

Sample ID 1309721-001AMS

Batch ID: 9548

RunNo: 13734

Result

31

Analysis Date: 9/30/2013

SeqNo: 391780

Units: mg/Kg

PQL

SPK value SPK Ref Val %REC

0

LowLimit

TestCode: EPA Method 300.0: Anions

HighLimit

109

Analyte

30 1.5

16.32 15.00

58.8 93.0

%RPD

RPDLimit Qual

Chloride

Sample ID 1309721-001AMSD

BatchQC

SampType: MSD

TestCode: EPA Method 300.0: Anions RunNo: 13734

Qual

Analyte Chloride

Client ID:

Prep Date: 9/30/2013

Batch ID: 9548 Analysis Date: 9/30/2013

PQL

1.5

15.00

16.32

SPK value SPK Ref Vai

SeqNo: 391781

%REC

101

LowLimit 58.8 HighLimit 109

Units: mg/Kg %RPD

3.68

RPDLimit

20

Page 2 of 6

0

Qualifiers: Value exceeds Maximum Contaminant Level.

Е Value above quantitation range Analyte detected in the associated Method Blank

Sample pH greater than 2 for VOA and TOC only. Reporting Detection Limit

Analyte detected below quantitation limits J

RSD is greater than RSDlimit RPD outside accepted recovery limits R

Н Holding times for preparation or analysis exceeded Not Detected at the Reporting Limit ND

Spike Recovery outside accepted recovery limits

Hall Environmental Analysis Laboratory, Inc.

WO#: 1309B13

04-Oct-13

Client:

Blagg Engineering

Project:

McCulley LS #2A

Sample ID MB-9480

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID: PBS

Batch ID: 9480

RunNo: 13692

Prep Date: 9/25/2013

SeqNo: 390205

Units: mg/Kg

Qual

Analyte

Analysis Date: 9/30/2013 PQL

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD **RPDLimit**

Petroleum Hydrocarbons, TR

Result ND

SampType: LCS

TestCode: EPA Method 418.1: TPH

Sample ID LCS-9480 Client ID:

Prep Date:

Analyte

LCSS

9/25/2013

Batch ID: 9480

Result

92

RunNo: 13692

80

LowLimit

PQL

20

20

20

Analysis Date: 9/30/2013

SPK value SPK Ref Val

100.0

100.0

SeqNo: 390206

Units: mg/Kg HighLimit

RPDLimit

Qual

Qual

Petroleum Hydrocarbons, TR

Sample ID LCSD-9480

Petroleum Hydrocarbons, TR

SampType: LCSD

TestCode: EPA Method 418.1: TPH

%REC

922

96.2

120

Client ID:

LCSS02

Batch ID: 9480

RunNo: 13692

Units: mg/Kg

120

%RPD

Analyte

Prep Date: 9/25/2013

Analysis Date: 9/30/2013

96

SeqNo: 390207

0

SPK value SPK Ref Val %REC

0

LowLimit HighLimit

80

%RPD

4.27

RPDLimit

20

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- Analyte detected below quantitation limits .
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits S
- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2 for VOA and TOC only.
- Reporting Detection Limit RL

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

Result

65

3.5

PQL

10

WO#: 1309B13

04-Oct-13

Client: Project:

Blagg Engineering

Analyte

Surr: DNOP

Diesel Range Organics (DRO)

McCulley LS #2A

Sample ID MB-9463	SampType: MBLK TestCode: EPA Method 8015D: Diesel Range Organics											
Client ID: PBS	Batch	ID: 94	63	F	RunNo: 1	3592						
Prep Date: 9/24/2013	Analysis Da	ite: 9/	25/2013	9	SeqNo: 3	87680	Units: mg/K	ζg				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Diesel Range Organics (DRO)	ND	10										
Surr: DNOP	8.6		10.00		86.5	63	147					
Sample ID LCS-9463	SampTy	pe: LC	s	Tes	tCode: El	PA Method	8015D: Diese	el Range C	Organics			
Client ID: LCSS	Batch	ID: 94	63	F	RunNo: 1	3592						
Prep Date: 9/24/2013	Analysis Da	te: 9 /	25/2013	S	SeqNo: 3	87681	Units: mg/K	g				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Diesel Range Organics (DRO)	47	10	50.00	0	94.3	77.1	128					
Diesel Range Organics (DRO) Surr: DNOP	47 4.0	10	50.00 5.000	0	94.3 80.8	77.1 63	128 147					
	4.0		5.000		80.8	63		el Range C)rganics			
Surr: DNOP	4.0	ре: МЅ	5.000	Tesi	80.8	63 PA Method	147	el Range C)rganics			

Surr: DNOP	3.1		5.045		60.8	63	147			S
Sample ID 1309A82-00	IAMSD SampT	ype: MS	SD.	Tes	tCode: El	PA Method	8015D: Dies	el Range (Organics	
Client ID: BatchQC	Batch	ID: 946	63	F	RunNo: 1	3619				
Prep Date: 9/24/2013	Analysis D	ate: 9/	26/2013	S	SeqNo: 3	88114	Units: mg/F	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	92	9.9	49.70	23.82	138	61.3	138	34.8	20	R

23.82

%REC

81.5

70.6

LowLimit

61.3

63

HighLimit

138

147

SPK value SPK Ref Val

50.45

4.970

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 4 of 6

RPDLimit

0

Qual

%RPD

0

Hall Environmental Analysis Laboratory, Inc.

WO#:

1309B13 04-Oct-13

Client:

Blagg Engineering

Project:	McCulley	LS #2A									
Sample ID N	/IB-9491	SampT	ype: MI	BLK	TestCode: EPA Method 8015D: Gasoline Range						
Client ID: P	BS	Batch	n ID: 94	91	F	RunNo: 1	3633				
Prep Date:	9/25/2013	Analysis E)ate: 9	/26/2013	S	SeqNo: 3	89025	Units: mg/l	√ g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range	Organics (GRO)	ND	5.0								
Surr: BFB		860		1000		86.4	80	120			
Sample ID L	.CS-9491	SampT	ype: LC	s	Tes	tCode: E	PA Method	8015D: Gase	oline Rang	e	
Client ID: L	.css	Batch	n ID: 94	91	F	RunNo: 1	3633				
Prep Date:	9/25/2013	Analysis D)ate: 9/	26/2013	5	SeqNo: 3	89026	Units: mg/l	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range (Organics (GRO)	26	5.0	25.00	0	106	74.5	126			
Surr: BFB		930		1000		93.5	80	120			
Sample ID 1309B39-001AMS SampType: MS				TestCode: EPA Method 8015D: Gasoline Range							
Client ID: B	BatchQC	Batch ID: 9491			RunNo: 13633						
Prep Date:	9/25/2013	Analysis D	ate: 9/	26/2013	S	SeqNo: 3	89028	Units: mg/l	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range (Organics (GRO)	28	4.7	23.43	1.525	114	76	156			
Surr: BFB		950		937.2		102	80	120			
Sample ID 1309B39-001AMSD SampType: MSD TestCode: EPA Method 8015D: Gasoline Range											
Client ID: B	BatchQC	Batch	1D: 94	91	R	lunNo: 1	3633				
Prep Date:	9/25/2013	Analysis D	ate: 9/	26/2013	S	SeqNo: 3	89029	Units: mg/h	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range (Organics (GRO)	29	4.7	23.45	1.525	119	76	156	4.45	17.7	
Surr: BFB		960		938.1		102	80	120	0	0	

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Е Value above quantitation range
- Analyte detected below quantitation limits
- RSD is greater than RSDlimit 0
- R RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits S
- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2 for VOA and TOC only. P
- RLReporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1309B13

04-Oct-13

Client: Project:

Blagg Engineering McCulley LS #2A

Sample ID MB-9491 SampType: MBLK TestCode: EPA Method 8021B: Volatiles Client ID: PBS Batch ID: 9491 RunNo: 13633 Prep Date: 9/25/2013 Analysis Date: 9/26/2013 Units: mg/Kg SeqNo: 389063 Analyte Result PQL SPK value SPK Ref Val %REC LowLimit **RPDLimit** HighLimit %RPD Qual Benzene ND 0.050 Toluene ND 0.050 Ethylbenzene ND 0.050 Xylenes, Total ND 0.10 Surr: 4-Bromofluorobenzene 0.97 1.000 96.8 80 120

Sample ID LCS-9491 SampType: LCS TestCode: EPA Method 8021B: Volatiles Client ID: LCSS Batch ID: 9491 RunNo: 13633 Prep Date: 9/25/2013 Analysis Date: 9/26/2013 SeqNo: 389064 Units: mg/Kg Analyte Result PQL SPK value SPK Ref Val %REC HighLimit %RPD **RPDLimit** LowLimit Qual 0.96 Benzene 0.050 1.000 n 95.6 80 120 Toluene 0.99 0.050 1.000 0 99.4 80 120 Ethylbenzene 0.050 1.000 n 102 80 1.0 120 Xylenes, Total 3.0 3.000 0 100 0.10 80 120 Surr: 4-Bromofluorobenzene 1.0 1.000 99.9 80 120

Sample ID 1309B13-001AMS TestCode: EPA Method 8021B: Volatiles SampType: MS Client ID: 5PC-TB @ 6' (21) Batch ID: 9491 RunNo: 13633 Prep Date: 9/25/2013 Analysis Date: 9/26/2013 SeqNo: 389073 Units: mg/Kg Analyte Result **PQL** SPK value SPK Ref Val %REC LowLimit HighLimit %RPD **RPDLimit** Qual Benzene 0.94 0.047 0.9443 100 67.3 145 Toluene 0.96 0.047 0.9443 0.006514 101 66.8 144 Ethylbenzene 0.99 0.047 0.9443 105 61.9 153 Xylenes, Total 3.0 0.094 2.833 0.01150 104 65.8 149 Surr: 4-Bromofluorobenzene 0.99 0.9443 105 80 120

Sample ID 1309B13-001AMSI	o SampTy	/pe: MS	SD	Tes	tCode: E	PA Method	8021B: Volat	tiles		
Client ID: 5PC-TB @ 6' (21)	Batch	ID: 94	91	F	RunNo: 1	3633				
Prep Date: 9/25/2013	Analysis Da	ate: 9/	26/2013	5	SeqNo: 3	89074	Units: mg/K	ζg		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.92	0.047	0.9452	0	97.3	67.3	145	2.61	20	
Toluene	0.93	0.047	0.9452	0.006514	98.2	66.8	144	3.12	20	
Ethylbenzene	0.98	0.047	0.9452	0	104	61.9	153	0.865	20	
Xylenes, Total	2.9	0.095	2.836	0.01150	103	65.8	149	0.533	20	
Surr: 4-Bromofluorobenzene	0.97		0.9452		103	80	120	0	0	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE

Albuquerque, NM 87109

Sample Log-In Check List

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Client Name: BLAGG Wor	k Order Number: 1309B13		RcptNo: 1
Received by/date	2413		
Logged By: Ashley Gallegos 9/24/2	013 10:00:00 AM	A	
Completed By: Ashley Gallegos 9/24/2	013 6:07:05 PM	A	
Reviewed By:	5-/13	, d	
Chain of Custody			
1. Custody seals intact on sample bottles?	Yes 🗌	No 🗆	Not Present 🗹
2. Is Chain of Custody complete?	Yes 🗹	No 🗌	Not Present
3. How was the sample delivered?	<u>Courier</u>		
<u>Log In</u>			
4. Was an attempt made to cool the samples?	Yes 🗹	No 🗌	NA 🗆
5. Were all samples received at a temperature of >0°	C to 6.0°C Yes ✓	No 🗆	na 🗆
6. Sample(s) in proper container(s)?	Yes 🗹	No 🗌	
7. Sufficient sample volume for indicated test(s)?	Yes 🗹	No 🗌	
8. Are samples (except VOA and ONG) properly prese	erved? Yes	No 🗌	
9. Was preservative added to bottles?	Yes 🗌	No 🗹	NA 🗆
10.VOA vials have zero headspace?	Yes 🗌	No 🗆	No VOA Vials
11. Were any sample containers received broken?	Yes 🗆	No 🗹 🛚	# of preserved
12. Does paperwork match bottle labels?	Yes 🗸	No 🗆	bottles checked for pH:
(Note discrepancies on chain of custody)	ies 🖭		(<2 or >12 unless noted)
13. Are matrices correctly identified on Chain of Custod	y? Yes ✓	` No □	Adjusted?
14. Is it clear what analyses were requested?	Yes 🗹	No 🗆	
15. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes 🗹	No 🗌	Checked by:
Special Handling (if applicable)	_		-
16. Was client notified of all discrepancies with this order	er? Yes 🗌	No 🗔	NA 🗹
Person Notified:	Date		
By Whom:	Via: ☐ eMail ☐ Pt	none 🔲 Fax	☐ In Person
Regarding:			
Client Instructions:			
17. Additional remarks:			
18. Cooler Information	a I godanii i Sanka Villi II d	d	
Cooler No Temp °C Condition Seal Intact	ct Seal No Seal Date	Signed By	
).4 Good 1es			



