District I	
1625 N. French Dr., Hobbs, NM 88240	F
District II	-
811 S. First St., Artesia, NM 88210	
District III	
1000 Rio Brazos Road, Aztec, NM 87410	
District IV	
1220 S. St. Francis Dr., Santa Fe, NM 87505	

A

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

<u>Pit, Below-Grade Tank, or</u>						
12419 Proposed Alternative Method Permit or Closure Plan Application OIL CONS. DIV DIST. 3						
Type of action: Below grade tank registration						
U_{5} A_{7} 5_{4} Δ_{7} Permit of a pit or proposed alternative method DEC A 2 2014						
Closure of a pit, below-grade tank, or proposed alternative method						
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,						
or proposed alternative method						
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request						
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.						
Deperator: BP America Production CompanyOGRID #:778						
Address:200 Energy Court, Farmington, NM 87401						
Facility or well name:Jones A LS 2						
API Number:						
U/L or Qtr/QtrMSection11Township28NRange8WCounty:San Juan						
Center of Proposed Design: Latitude36.67150 Longitude107.65623 NAD: □1927 ⊠ 1983						
Surface Owner: 🔀 Federal 🗔 State 🔲 Private 🗔 Tribal Trust or Indian Allotment						
2.						
Pit: Subsection F, G or J of 19.15.17.11 NMAC						
Temporary: Drilling Workover						
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no						
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other						
String-Reinforced Universe Reinforced Universe Reinforced Universe Reinforced						
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D						
3.						
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A						
Volume:95.0bbl Type of fluid:Produced water						
Tank Construction material:Steel						
Secondary containment with leak detection 🗌 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off						
🗌 Visible sidewalls and liner 🗌 Visible sidewalls only 🛛 Other _Double walled/double bottomed; side walls not visible						
Liner type: Thicknessmil						
4.						
Alternative Method:						
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.						



 ^{5.} Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	, hospital,			
6.				
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)				
Screen Netting Other				
Monthly inspections (If netting or screening is not physically feasible)				
7. Signer Subsection C of 10.15.17.11 NMAC				
Signs: Subsection C of 19.15.17.11 NMAC				
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers				
Signed in compliance with 19.15.16.8 NMAC				
 8. <u>Variances and Exceptions</u>: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. <i>Please check a box if one or more of the following is requested, if not leave blank:</i> Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 				
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acce material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source			
General siting				
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank	Yes No			
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.	\square Yes \square No			
NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	LI NA			
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗌 Yes 🗌 No			
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	🗌 Yes 🗌 No			
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗋 Yes 🗌 No			
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map				
Below Grade Tanks				
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	🗋 Yes 🗌 No			
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No			

Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)

Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, 🗌 Yes 🗌 No or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) -

Topographic map; Visual inspection (certification) of the proposed site

÷

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No			
application.				
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image				
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.				
NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site				
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No			
Temporary Pit Non-low chloride drilling fluid				
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes 🗌 No			
Within 200 fast from a normanant maidance school besuited institution as should institute a table in the state				
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes 🗌 No			
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	Yes No			
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes 🗌 No			
Permanent <u>Pit or Multi-Well Fluid Management Pit</u>				
Within 200 fact of a continuously flowing watercourse on 200 fact of any other size (from the day of the day o				
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).				
- Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No			
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.				
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	🗌 Yes 🗌 No			
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of				
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No			
Within 500 feet of a wetland.				
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No			
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N	IMAC			
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the down and the application of the following items must be attached to the application.				
attached.				
 Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	NMAC			
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC				
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC 	15.17.9 NMAC			
Previously Approved Design (attach copy of design) API Number: or Permit Number:				
11.				
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	cuments are			
<i>attached.</i> Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC				
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC				
 A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 	.15.17.9 NMAC			
and 19.15.17.13 NMAC				
 Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 				
Previously Approved Design (attach copy of design) API Number: or Permit Number:				

÷

12. <u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	e documents are
 attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 	
 Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC 	
 Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC 	
 Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan 	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
 Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan 	
 Emergency Response Plan Oil Field Waste Stream Characterization 	
 Monitoring and Inspection Plan Erosion Control Plan 	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
13. <u>Proposed Closure</u> : 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	Fluid Management Pit
Alternative Proposed Closure Method: Waste Excavation and Removal	
. Waste Removal (Closed-loop systems only)	
 On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial 	
Alternative Closure Method	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached.	attached to the
 Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC 	
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)	
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC	
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sou provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency.	rce material are Please refer to
19.15.17.10 NMAC for guidance.	······
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗍 No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

•

 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 	Yes No
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
Within an unstable area.	
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
Within a 100-year floodplain. - FEMA map	Yes No
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure planet by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannet Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	11 NMAC 15.17.11 NMAC
17. Oncenter Application Contification	
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ef.
Name (Print):	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) Image: Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Image: Closure Plan (only) OCD Conditions (see attachment) Ittle: Image: Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Image: Closure Plan (only) Approval Date: 12/15 Title: Image: Compliance Image: Closure Plan (only) OCD Permit Number:	79014
19.	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report. complete this
Closure Completion Date:2/6/2013	
20. <u>Closure Method:</u> ⊠ Waste Excavation and Removal □ On-Site Closure Method □ Alternative Closure Method □ Waste Removal (Closed-loc □ If different from approved plan, please explain.	op systems only)
 21. <u>Closure Report Attachment Checklist</u>: Instructions: Each of the following items must be attached to the closure report. Please intermark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique 	licate, by a check
Site Reclamation (Photo Documentation)	

÷

22. Operator Closure Certification:

v

3

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Jeff Peace	Date:December 1, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Jones A LS 2 API No. 3004507543 Unit Letter M, Section 11, T28N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

No notice was made due to misunderstanding of the BGT notice requirements at that time.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)

.

- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)
 - All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.
- 4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	120

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.
- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

٠

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

٠

•

Oil Conservation Division 1220 South St. Francis Dr.

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

1220 S. St. Eropois Dr. Sonto Eo. NM 97505		St. Franc , NM 875						
Release Notifi		· · · · · · · · · · · · · · · · · · ·		ction			· =	
		OPERA			🗌 Initi	al Report		Final Repor
Name of Company: BP		Contact: Jef						<u> </u>
Address: 200 Energy Court, Farmington, NM 87401	1	Felephone 1	No.: 505-326-94	79				,,
Facility Name: Jones A LS 2	F	Facility Typ	e: Natural gas v	vell				
Surface Owner: Federal Mineral	Owner: E	Gederal			ADING	0. 3004507:	342	
					AFIN	. 3004307.		
Unit Letter Section Township Range Feet from the		OF RE South Line	Feet from the	East/W	est Line	County: S	an Juar	, <u>.</u>
M 11 28N 8W 1,150	South		890	West			_	
Latitude36.67150		_ Longitud	e_107.65623_					
	TURE	OF REL	EASE					
Type of Release: none			Release: N/A			Recovered: N		·
Source of Release: below grade tank – 95 bbl Was Immediate Notice Given?			lour of Occurrenc	e:	Date and	Hour of Dis	covery	
Yes No X Not R	Required	If YES, To	wnom?					
By Whom?		Date and H	lour		······			
Was a Watercourse Reached?			lume Impacting t	he Water	course.			
🗌 Yes 🖾 No								
Describe Cause of Problem and Remedial Action Taken.* Sampl the BGT. Soil analysis resulted in TPH, BTEX and chloride belo Describe Area Affected and Cleanup Action Taken.* BGT was re backfilled and compacted and is still within the active well area.	ow standar	rds. Analysi	s results are attach	ned.				
I hereby certify that the information given above is true and comp regulations all operators are required to report and/or file certain public health or the environment. The acceptance of a C-141 rep should their operations have failed to adequately investigate and or the environment. In addition, NMOCD acceptance of a C-141 federal, state, or local laws and/or regulations.	release no oort by the remediate	tifications an NMOCD m contaminati	nd perform correc arked as "Final Ro on that pose a thre	tive actic eport" do eat to gro	ons for rel es not rel und wate	eases which ieve the oper r, surface wa	may en ator of ter, hui	idanger liability man health
Signature: Store			OIL CONS			DIVISIC	<u> N</u>	
Printed Name: Jeff Peace	A	Approved by	Environmental S	pecialist:				
Title: Field Environmental Coordinator	A	Approval Dat	e:	E	xpiration	Date:		
E-mail Address: peace.jeffrey@bp.com	C	Conditions of	Approval:			Attached		
Date: December 1, 2014 Phone: 505-326-9479								

Attach Additional Sheets If Necessary

	P.O. BOX 87, BLO	INEERING, INC. OMFIELD, NM 87 532-1199	7413	API #: 300 TANK ID (if applicble):	A		
FIELD REPORT:	(circle one): BGT CONFIRMATION / REL		:	PAGE #:			
	28N RNG: 8W PM: N	M CNTY: SJ S	TE NM	Date started: _ Date finished: _	01/23/13		
	PROD. FORMATION: MV CONTR	ELKHORN ACTOR: MBF - B. SCHL	JRMAN		NJV		
REFERENCE POINT 1) 95 BGT (DW/DB) 2)	GPS COORD.: GPS COORD.: GPS COORD.:	150 X 107.65623	DISTANCE/BEA	RING FROM W.H.: RING FROM W.H.: RING FROM W.H.:			
SAMPLING DATA: 1) SAMPLE ID:5PC-TB @ 5' (95)	CHAIN OF CUSTODY RECORD(S) # OR LAB		A18 1/	 8015B/8021B/300	OVM READING (ppm)		
1) SAMPLE ID: 2) SAMPLE ID: 3) SAMPLE ID: 4) SAMPLE ID:	SAMPLE DATE: SAMPLE DATE:	SAMPLE TIME: LAB AN SAMPLE TIME: LAB AN	IALYSIS:				
SOIL DESCRIPTION: SOIL TYPE: SAND / SILTY SAND / SILTY CLAY / CLAY / GRAVEL / OTHER SOIL COLOR: MODERATE BROWN COHESION (ALL OTHERS): NON COHESIVE / SUGHTLY COHESIVE / COHESIV							
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER:	DR TO W.H.	AREST SURFACE WATER:	1,000' NMOCE attached 0/M (0/M (MATION (Cubic Yar DTPH CLOSURE STD: CALIB. READ. = <u>NA</u> CALIB. GAS = <u>NA</u> MISCELL.	ppmRF = 0.52 ppm ATE:NA		
300 BBL PROD. TANK BERM	SEP. SEP. PBGTL T.B. ~5' B.G.	X - S.P.	PY PJ Pe OC Tami	0: N150806 0 #: (: ZEVH011 1 #: Z2-0069(rmit date(s): CD Appr. date(s): VM = Organic	BGT2 D-C 06/14/10 08/14/12 Vapor Meter rmillion ble: Y (N)		
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELO APPLICABLE OR NOT AVAILABLE; SW- SINGLE	N DEPRESSION; B.G. = BELOW GRADE; B = BELOW, T. DW-GRADE TANK LOCATION; SPD = SAMPLE POINT DE WALL; DW- DOUBLE WALL; SB- SINGLE BOTTOM; DE	H. = TEST HOLE; ~ = APPROX.; W.H. = V Signation; R.W. = Retaining Wall; M 3 - Double Bottom.	MELL HEAD; NA - NOT	BGT Sidewalls Visit			
TRAVEL NOTES: CALLOUT:		ONSITE: 01/23/13	<u>}</u>				

.

•

Analytical Report Lab Order 1301961 Date Reported: 2/6/2013

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering Client Sample ID: 5PC-TB @ 5' (95) **Project:** Jones A LS #2 Collection Date: 1/23/2013 2:18:00 PM 1301961-001 Lab ID: Matrix: SOIL Received Date: 1/30/2013 10:30:00 AM Analyses Result **RL** Qual Units DF **Date Analyzed** EPA METHOD 8015B: DIESEL RANGE ORGANICS Analyst: MMD

Diesel Range Organics (DRO)	ND	10	mg/Kg	1	2/5/2013 11:11:20 AM
Surr: DNOP	93.6	72.4-120	%REC	1	2/5/2013 11:11:20 AM
EPA METHOD 8015B: GASOLINE RANG	GE				Analyst: NSB
Gasoline Range Organics (GRO)	ND	4.9	mg/Kg	1	2/1/2013 12:51:54 PM
Surr: BFB	104	8 4 -116	%REC	1	2/1/2013 12:51:54 PM
EPA METHOD 8021B: VOLATILES					Analyst: NSB
Benzene	ND	0.049	mg/Kg	1	2/1/2013 12:51:54 PM
Toluene	ND	0.049	mg/Kg	1	2/1/2013 12:51:54 PM
Ethylbenzene	ND	0.049	mg/Kg	1	2/1/2013 12:51:54 PM
Xylenes, Total	ND	0.098	mg/Kg	1	2/1/2013 12:51:54 PM
Surr: 4-Bromofluorobenzene	104	80-120	%REC	1	2/1/2013 12:51:54 PM
EPA METHOD 300.0: ANIONS					Analyst: JRR
Chloride	120	30	mg/Kg	20	2/4/2013 11:18:44 AM
EPA METHOD 418.1: TPH					Analyst: ECH
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	2/6/2013 11:00:00 AM

Qualifiers:

Value exceeds Maximum Contaminant Level. *

E Value above quantitation range

- J Analyte detected below quantitation limits
- Р Sample pH greater than 2
- Reporting Detection Limit RL

- Analyte detected in the associated Method Blank В
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
- RPD outside accepted recovery limits R
- Spike Recovery outside accepted recovery limits S

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

•

WO#: 1301961

06-Feb-13

Client: Project:	Blagg Engineerin Jones A LS #2	g								
Sample ID MB-5	970 Sam	рТуре: М	BLK	Tes	tCode: El	PA Method	300.0: Anion	s		
Client ID: PBS	Ba	tch ID: 59	70	F	RunNo: 8	439				
Prep Date: 2/4/	2013 Analysis	Date: 2	/4/2013	S	SeqNo: 2	43119	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Chloride	ND	1.5							_	
Sample ID LCS-	5970 Sam	рТуре: LC	s	Tes	tCode: El	PA Method	300.0: Anion	s		
Client ID: LCSS	Ba Ba	ich ID: 59	70	F	lunNo: 8 4	439				
Prep Date: 2/4/2	2013 Analysis	Date: 2	/4/2013	S	eqNo: 24	43120	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Chloride	15	1.5	15.00	0	98.7	90	110			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pl-I greater than 2

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
 - Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits

ND

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

•

WO#: 1301961

06-Feb-13

Client:	Blagg B	Engineering									
Project:	Jones A	LS #2									
Sample ID	MB-5975	SampTyp	e: Me	BLK	Tes	tCode: E	PA Method	418.1: TPH			
Client ID:	PBS	Batch I	D: 59	75	F	lunNo: 8	474				
Prep Date:	2/4/2013	Analysis Date	e: 2/	6/2013	S	eqNo: 2	44184	Units: mg/K	g		
Analyte		Result I	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Petroleum Hydr	rocarbons, TR	ND	20								
Sample ID	LCS-5975	SampTyp	e: LC	S	Tes	tCode: E	PA Method	418.1: TPH			
Client ID:	LCSS	Batch ID	D: 59	75	ĥ	tunNo: 8	474				
Prep Date:	2/4/2013	Analysis Date	e: 2 /	6/2013	S	eqNo: 2	44185	Units: mg/K	g		
Analyte		Result F	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Petroleum Hydr	ocarbons, TR	100	20	100.0	7.840	94.1	80	120			
Sample ID	LCSD-5975	SampTyp	e: LC	SD	Tes	Code: E	PA Method	418.1: TPH			
Client ID:	LCSS02	Batch ID	D: 59	75	Я	unNo: 8	474				
Prep Date:	2/4/2013	Analysis Date	e: 2 /	6/2013	S	eqNo: 2	44186	Units: mg/K	g		
Analyte		Result F	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Petroleum Hydr	ocarbons, TR	110	20	100.0	7.840	98.1	80	120	3.87	20	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
 - Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits

ND

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

•

WO#: 1301961

06-Feb-13

Client: Project:	Blagg En Jones A I	gineering LS #2									
Sample ID	MB-5946	SampTy	/pe: MI	BLK	Tes	tCode: El	PA Method	8015B: Dies	el Range (Organics	<u> </u>
Client ID:	PBS	Batch	ID: 59	46	F	RunNo: 8	445				
Prep Date:	2/1/2013	Analysis Da	ate: 2	/5/2013	S	GeqNo: 24	43401	Units: mg/ł	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range (Organics (DRO)	ND	10								
Surr: DNOP		9.4		10.00		94.4	72.4	120			
Sample ID	LCS-5946	SampTy	vpe: LC	s	Tes	tCode: El	PA Method	8015B: Dies	el Range (Organics	
Client ID:	LCSS	Batch	ID: 59	46	F	RunNo: 84	445				
Prep Date:	2/1/2013	Analysis Da	ate: 2/	/5/2013	S	SeqNo: 24	43402	Units: mg/k	٢g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range (Drganics (DRO)	45	10	50.00	0	90.6	47.4	122			
Surr: DNOP		4.5		5.000		89.3	72.4	120			
Sample ID	1301961-001AMS	SampTy	pe: MS	S	Tes	tCode: El	PA Method	8015B: Dies	el Range (Organics	
Client ID:	5PC-TB @ 5' (95)	Batch	ID: 59	46	F	RunNo: 84	445				
Prep Date:	2/1/2013	Analysis Da	ate: 2 /	5/2013	5	SeqNo: 24	43432	Units: mg/M	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range (Drganics (DRO)	44	10	50.61	0	87.7	12.6	148			
Surr: DNOP		4.4		5.061		87.8	72.4	120			
Sample ID	1301961-001AMS) SampTy	pe: M \$	SD	Tes	tCode: EF	PA Method	8015B: Dies	el Range C	Organics	
Client ID:	5PC-TB @ 5' (95)	Batch	ID: 59	46	F	RunNo: 8 4	445				
Prep Date:	2/1/2013	Analysis Da	ate: 2/	5/2013	S	SeqNo: 24	43433	Units: mg/M	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range (Drganics (DRO)	45	10	50.20	0	90.2	12.6	148	2.04	22.5	
Surr: DNOP		4.5		5.020		89.7	72.4	120	0	0	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits

QC SUMMARY REPORT

WO#: 1301961

06-Feb-13

Hall Environmental	Analysis	Laboratory, Inc	c.
	J		

	Engineering A LS #2									
Sample ID MB-5926	SampTyp	e: MBI	LK	Tes	tCode: E	PA Method	8015B: Gaso	oline Rang	e	
Client ID: PBS	Batch IC	D: 592	6	R	RunNo: 8	435				
Prep Date: 1/31/2013	Analysis Date	e: 2/1	/2013	S	BeqNo: 2	43027	Units: mg/H	۲g		
Analyte	Result I	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND	5.0								
Surr: BFB	1000		1000		103	84	116			<u></u> .
Sample ID LCS-5926	SampTyp	e: LCS	3	Tes	tCode: E	PA Method	8015B: Gaso	line Rang	e	
Client ID: LCSS	Batch ID	D: 592	6	R	lunNo: 8	435				
Prep Date: 1/31/2013	Analysis Date	e: 2/1	/2013	S	SeqNo: 2	43028	Units: mg/H	۲g		
Analyte	Result F	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	28	5.0	25.00	0	113	74	117			
Surr: BFB	1100		1000		107	84	116			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- R RPD outside accepted recovery limits

QC SUMMARY REPO	PRT
-----------------	------------

¢

			J 515 1		01) , 110						00-1 20-1.
Client: Project:	Blagg En Jones A I	igineering LS #2									
Sample ID	MB-5926	SampT	ype: M	BLK	Tes	tCode: E	PA Method	8021B: Vola	tiles		
Client ID:	PBS	Batch	n ID: 59	26	F	RunNo: 8	435				`
Prep Date:	1/31/2013	Analysis D)ate: 2	/1/2013	S	SegNo: 2	43066	Units: mg/K	a		
Analyte		Result	PQL		SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		ND	0.050				LOWEINK	riigheinn	7011111		
Toluene		ND	0.050								
Ethylbenzene		ND	0.050								
Xylenes, Total		ND	0.10								
Surr: 4-Brom	ofluorobenzene	1.0		1.000		104	80	120			
Sample ID	LCS-5926	SampT	ype: LC	s	Tes	tCode: El	PA Method	8021B: Volat	tiles		
Client ID:	LCSS	Batch	n ID: 59	26	F	RunNo: 8	435				
Prep Date:	1/31/2013	Analysis D	ate: 2/	1/2013	ę	SeqNo: 2	43067	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		0.96	0.050	1.000	0	96.0	80	120		-	
Toluene		0.93	0.050	1.000	0	93.4	80	120			
Ethylbenzene		0.94	0.050	1.000	0	93.8	80	120			
Xylenes, Total		2.9	0.10	3.000	0	95.3	80	120			
Surr: 4-Brom	ofluorobenzene	1.0		1.000		104	80	120			
Sample ID	1301961-001AMS	SampT	ype: M \$	3	Tes	tCode: El	PA Method	8021B: Volat	iles		
Client ID:	5PC-TB @ 5' (95)	Batch	1D: 59	26	F	tunNo: 8	435				
Prep Date:	1/31/2013	Analysis D	ate: 2/	1/2013	S	eqNo: 2	43069	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		1.1	0.050	0.9921	0	109	67.2	113			
Toluene		1.1	0.050	0.9921	0	109	62.1	116			
Ethylbenzene		1.1	0.050	0.9921	0	110	67.9	127			
Xylenes, Total		3.4	0.099	2.976	0	113	60.6	134			
Surr: 4-Brom	ofluorobenzene	1.0		0.9921		101	80	120			
Sample ID	1301961-001AMSE) SampT	ype: MS	SD	Test	Code: EF	PA Method	8021B: Volat	iles		
Client ID:	5PC-TB @ 5' (95)	Batch	ID: 59	26	R	unNo: 84	435				
Prep Date:	1/31/2013	Analysis D	ate: 2/	1/2013	S	eqNo: 24	43071	Units: mg/K	g		

SPK value SPK Ref Val %REC

0

0

0

0

0.9862

0.9862

0.9862

2.959

0.9862

Hall Environmental Analysis Laboratory, Inc.

Value exceeds Maximum Contaminant Level. * Е Value above quantitation range

Result

1.0

1.0

1.1

3.2

0.98

PQL

0.049

0.049

0.049

0.099

J Analyte detected below quantitation limits

Р Sample pH greater than 2

Analyte

Benzene

Toluene

Ethylbenzene

Xylenes, Total

Qualifiers:

Surr: 4-Bromofluorobenzene

В Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Н

LowLimit

67.2

62.1

67.9

60.6

80

HighLimit

113

116

127

134

120

%RPD

3.24

4.37

3.51

4.74

0

RPDLimit

14.3

15.9

14.4

12.6

0

Qual

ND Not Detected at the Reporting Limit RPD outside accepted recovery limits R

106

105

107

108

99.6

WO#: 1301961 06-Feb-13

HALL ENVIRONMENTAL ANALYSIS LABORATORY	Hall Environmental A Albua TEL: 505-345-3975 J Website: www.hal	4901 Hav querque, N FAX: 505-3	vkins M 87. 845-4.	NE 105 10;	Sample Log-In Check L
Client Name: BLAGG	W	ork Order	Num	ber:	1301961
Received by/date	3013				
Logged By: Ashley Gallegos 1/	, 30/2013 10:30:00 AM			A	F
	30/2013 12:30:35 PM			4	
Reviewed By:	3013				7
Chain of Custody	1 1				
1. Were seals intact?		Yes 🗌	No		Not Present 🗹
2. Is Chain of Custody complete?		Yes 🔽	No		Not Present
3. How was the sample delivered?		<u>Courier</u>			
<u>Log In</u>					
4. Coolers are present? (see 19. for cooler speci	fic information)	Yes 🔽	No		
5. Was an attempt made to cool the samples?		Yes 🗹	No		NA 🗔
6. Were all samples received at a temperature of	>0° C to 6.0°C	Yes 🗹	No		
7 Sample(s) in proper container(s)?		Yes 🗹	No		
8. Sufficient sample volume for indicated test(s)?		Yes 🗸	No		
9. Are samples (except VOA and ONG) properly	preserved?	Yes 🗹	No		
10, Was preservative added to bottles?		Yes 🗌	No	\checkmark	NA 🗆
11 VOA vials have zero headspace?		Yes	No		No VOA Vials 🗹
12. Were any sample containers received broken?	•	Yes			
13. Does paperwork match bottle labels? (Note discrepancies on chain of custody)		Yes 🗹			# of preserved bottles checked for pH:
14. Are matrices correctly identified on Chain of C	ustody?		No		(<2 or >12 unless no
15. Is it clear what analyses were requested?		Yes 🗹		_	Adjusted?
 Were all holding times able to be met? (If no, notify customer for authorization.) 		Yes 🗹	No		Checked by:
<u>Special Handling (if applicable)</u>					
17. Was client notified of all discrepancies with this	s order?	Yes 🗌	No		
Person Notified: By Whom: Regarding: Client Instructions:	Date: Date: Via:] eMail] P	hone	Fax In Person

19. Cooler Information

Cooler No	Temp °C	Condition	Seal Intact	Seal No	Seal Date	Signed By
1	1.0	Good	Yes			

_ _ _

. —

~____

-

Chain-	of-Cus	stody Record	I urn-Around	ıme:		Ι.			LI	A I 1	EI	DIM	тс		A IA	J E I	NTA	
Client: BLA	GG ENGR.	/ BP AMERICA	Standard	🗌 Rush _				J 										
			Project Name		<u>.</u>	ANALYSIS LABORATORY www.hailenvironmental.com												
Mailing Address:	P.O. BO	X 87	4	JONES A LS	# 2	4901 Hawkins NE - Albuquerque, NM 87109												
	BLOOM	FIELD, NM 87413	Project #:			1	Tel. 505-345-3975 Fax 505-345-4107											
Phone #:	(505) 63		-4								Analy		-					·
email or Fax#:			Project Manag	ect Manager:					T			SO4)						
QA/QC Package:		Level 4 (Full Validation)		NELSON VI	ELEZ	, (8021B)	+ TPH (Gas only)	(Gas/Diesel)		1		PO4, SC	S'B's					
Accreditation:			Sampler:	NELSON VI	ELEZ nV		(Gas	(Gas/				02,	/ 8082 PCB's					- John
		•		Q Mes Sta	⊡_No		ΗdΤ	158	(18.1)	F F		33, N	/ 80		2			e sa
EDD (Type)		·····	Sample Temp	erature:				d 80	24 J		tals	J, NC	ides			0.0	le	losit
Date Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEALNO 1307761	BTEX + MTE	BTEX + MTBE	TPH Method 8015B	TPH (Method 418.1)	EUB (Method 504.1) 8310 (PNA or PAH)	RCRA 8 Metals	Anions (F, Cl, NO3, NO2, PO4,	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (300.0)	Grab sample	5 pt. composite sample
1/23/13 1418	SOIL	5PC-TB @ 5' (95)	4 oz 2	Cool	-001	V			V							V	-	V
				· · · ·												-		
				· ·													1	
																	+	
																-	+	
					<u>}</u>			-			+						+	
			1	· · · · · · · · · · · · · · · · · · ·				-+										
				· · · · ·				-+		+								┟──┤
											┼──┤				-	+-	+	┟╾╼┤
				<u> </u>			$\left - \right $				╂─┨			┝─┤		-+	+	┟──┤
······································						-								┝─┤				
										+-	-			┝──┤			_	
Date: / Time:	Relinquist	led by:	Received by:		Date Time	Ren	nark	. 1		 8015	B) - (GRO) ይ 		ÔN			L
1/29/13 1401	71.	In VI	Mistere 1	Dada	1/29/13 1401	ві	LL DI	RECTL	у то	BP:	-							
Date: Time:	Relinquish	ied by:	Received by:	\ \	Date Time	i i				ergy Co 1508	-		-				<u>18GT2</u>	•
129/13/1710	Chri	the Walters	AD	01/30/13	5 10:30			i uer :		100		·	rð	укеу,		<u>_vnv</u> ,	10012	
lf neces	sarvisamples	submitted to Hall Environmental may be	subcontracted to other	accredited laboratorie	es. This serves as notice of	f this o	ossibil	itv. Anv	v sub-ci	ntracter	l data w	vill be o	clearty	r notate	ed on t	he anal	utical repr	ut

٠

