, <del>ĉ</del>		
District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-144 Revised June 6, 2013 For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
Type of action: Belo General Belo Bero Bero Close Close Close or proposed alternative m Instructions: Please submit Please be advised that approval of this request does	nit of a pit or proposed alternative method sure of a pit, below-grade tank, or proposed alternation lification to an existing permit/or registration sure plan only submitted for an existing permitted or	OIL CONS. DIV DIST. 3 ive method DEC 11 2014 r non-permitted pit, below-grade tank, -grade tank or alternative request in pollution of surface water, ground water or the
Address:200 Energy Court, Farmingto Facility or well name:Smyers Com LS API Number:3004511002 U/L or Qtr/QtrM Section	DanyOGRID #:OGRID #:OGRID #:         1OCD Permit Number:         2Township31NRange11W         .92367Longitude107.965037         : [] Tribal Trust or Indian Allotment	County:San Juan
Lined Unlined Liner type: Thickness	NMAC P&A Multi-Well Fluid Management L mil LLDPE HDPE PVC 0 verbb	ther
Tank Construction material:      Steel         Secondary containment with leak detection         Visible sidewalls and liner       Visible sidewalls and liner	Sype of fluid:Produced water	verflow shut-off tomed; side walls not visible
	Exceptions must be submitted to the Santa Fe Environme	ental Bureau office for consideration of approval.

×

21

<b>↓</b>	
<ul> <li>5.</li> <li>Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)</li> <li>Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)</li> <li>Four foot height, four strands of barbed wire evenly spaced between one and four feet</li> <li>Alternate. Please specify</li></ul>	hospital,
<ul> <li>6.</li> <li><u>Netting</u>: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)</li> <li>Screen Netting Other</li> <li>Monthly inspections (If netting or screening is not physically feasible)</li> </ul>	
<ul> <li>7.</li> <li>Signs: Subsection C of 19.15.17.11 NMAC</li> <li>□ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers</li> <li>□ Signed in compliance with 19.15.16.8 NMAC</li> </ul>	
<ul> <li>8. <u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.</li> <li><i>Please check a box if one or more of the following is requested, if not leave blank:</i> Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.</li> </ul>	
<sup>9.</sup> Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank	□ Yes □ No □ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
<ul> <li>Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)</li> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> </ul>	🗌 Yes 🗌 No
<ul> <li>Within the area overlying a subsurface mine. (Does not apply to below grade tanks)</li> <li>Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division</li> </ul>	Yes 🗌 No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	Yes No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	🗋 Yes 🗌 No
Below Grade Tanks	
<ul> <li>Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).</li> <li>Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗍 No
<ul> <li>Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.</li> <li>NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site</li> </ul>	🔲 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	

Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site

Form C-144

٩

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
<ul> <li>application.</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
<ul> <li>Within 100 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	Yes No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	Yes 🗋 No
<ul> <li>Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>	🗌 Yes 🗌 No
<ul> <li>Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;</li> <li>NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site</li> </ul>	Yes No
<ul> <li>Within 300 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	Yes 🗌 No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	Yes No
<ul> <li>Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
<ul> <li>Within 500 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	🗌 Yes 🗌 No
<sup>10.</sup> <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 N <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do</i>	
<ul> <li>attached.</li> <li>Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC</li> <li>Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9</li> <li>Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC</li> <li>Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC</li> </ul>	) NMAC
<ul> <li>Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC</li> <li>Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC</li> </ul>	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. <u>Multi-Well Fluid Management Pit Checklist</u> : Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.	cuments are
<ul> <li>Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC</li> <li>A List of wells with approved application for permit to drill associated with the pit.</li> </ul>	
<ul> <li>Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC</li> <li>Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC</li> </ul>	.15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

٠

۲

12. Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached.	
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC	
<ul> <li>Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC</li> <li>Climatological Factors Assessment</li> </ul>	
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC	
Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC	
Quality Control/Quality Assurance Construction and Installation Plan	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including $H_2S$ , Prevention Plan	
Emergency Response Plan	
Oil Field Waste Stream Characterization	
Monitoring and Inspection Plan	
Erosion Control Plan	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
n roposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Fype: 🗌 Drilling 🔲 Workover 🗌 Emergency 🗌 Cavitation 🗍 P&A 🔲 Permanent Pit 🗍 Below-grade Tank 🗌 Multi-well F	luid Management Pit
Alternative	fald Management I ft
Proposed Closure Method: 🔲 Waste Excavation and Removal	
Waste Removal (Closed-loop systems only)	
On-site Closure Method (Only for temporary pits and closed-loop systems)	
In-place Burial Don-site Trench Burial Alternative Closure Method	
4.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be	attached to the
closure plan. Please indicate, by a check mark in the box, that the documents are attached.	
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC	
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC	
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)	
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on site cleaning methods only), 10 15 17 10 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour	rca matarial ara
provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F	lease refer to
19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
-	L] NA
Ground water is between 25-50 feet below the bottom of the buried waste	🗌 Yes 🗌 No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	🗌 NA
Ground water is more than 100 feet below the bottom of the buried waste.	🗌 Yes 🗌 No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	🗖 NA 🗌
Vithin 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa	🗌 Yes 🗌 No
ike (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	
/ithin 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Vithin 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence	🗌 Yes 🗌 No
t the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	
ritten confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Vithin 300 feet of a wetland.	
JS Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

\*

.

<ul> <li>adopted pursuant to NMSA 1978, Section 3-27-3, as amended.</li> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> </ul>	Yes No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	🗌 Yes 🗌 No
<ul> <li>Within an unstable area.</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	
Within a 100-year floodplain.	🗋 Yes 🗌 No
- FEMA map	🗋 Yes 🗌 No
<ul> <li>16.</li> <li>On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure play a check mark in the box, that the documents are attached.</li> <li>Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC</li> <li>Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC</li> <li>Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.</li> <li>Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC</li> <li>Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC</li> <li>Confirmation Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC</li> <li>Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards canned Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC</li> <li>Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC</li> </ul>	11 NMAC 5.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believes	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan)	
OCD Representative Signature: Kelly Approval Date: 12/23	3/2014
Title: <u>Opplance Office</u> OOCD Permit Number:	
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 11/5/2014_	the closure report. complete this
<ul> <li>20.</li> <li>Closure Method:</li> <li>Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-loo If different from approved plan, please explain.</li> </ul>	op systems only)

۶

Ň

#### 22. Operator Closure Certification:

÷

ι

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.					
Name (Print):Jeff Peace	Title: Field Environmental Coordinator				
Signature: Stop Peace	Date:December 9, 2014				

	UVV
e-mail address:_	_peace.jeffrey@bp.com

\_\_\_\_\_\_ Telephone: \_\_\_(505) 326-9479\_

•

## BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

### BELOW-GRADE TANK CLOSURE PLAN

## Smyers Com LS 1 API No. 3004511002 Unit Letter M, Section 2, T31N, R11

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

## **General Closure Plan**

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number. **Notice is attached.**
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)

s

į.

- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
  - BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.

÷

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

## BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

State of New Mexico Energy Minerals and Natural Resources

> Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

**Release Notification and Corrective Action** 

Revised August 8, 2011 Submit 1 Copy to appropriate District Office in

Form C-141

Submit		19.15.29	

#### **OPERATOR** Initial Report Final Report Name of Company: BP Contact: Jeff Peace Address: 200 Energy Court, Farmington, NM 87401 Telephone No.: 505-326-9479 Facility Name: Smyers Com LS 1 Facility Type: Natural gas well Surface Owner: Federal Mineral Owner: Federal API No. 3004511002 LOCATION OF RELEASE Feet from the Unit Letter Section Township North/South Line Feet from the East/West Line County: San Juan Range М 2 31N 11W 1.190 South 1.015 West Latitude 36.92367 Longitude 107.965037 NATURE OF RELEASE Type of Release: none Volume of Release: N/A Volume Recovered: N/A Source of Release: below grade tank – 95 bbl Date and Hour of Occurrence: Date and Hour of Discovery: N/A N/A Was Immediate Notice Given? If YES, To Whom? Yes No X Not Required By Whom? Date and Hour Was a Watercourse Reached? If YES, Volume Impacting the Watercourse. ☐ Yes ⊠ No If a Watercourse was Impacted, Describe Fully.\* Describe Cause of Problem and Remedial Action Taken.\* Sampling of the soil beneath the BGT was done during removal to ensure no soil impacts from the BGT. Soil analysis resulted in TPH, BTEX and chlorides below standards. Analysis results are attached. Describe Area Affected and Cleanup Action Taken.\* BGT was removed and the area underneath the BGT was sampled. The area under the BGT was backfilled and compacted and is still within the active well area. I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations. OIL CONSERVATION DIVISION Keace Signature: Approved by Environmental Specialist: Printed Name: Jeff Peace Title: Field Environmental Coordinator Approval Date: Expiration Date: Conditions of Approval: E-mail Address: peace.jeffrey@bp.com Attached Phone: 505-326-9479 Date: December 9, 2014 \* Attach Additional Sheets If Necessary

				in the same of the state of the
	NGINEERING, INC.	GINEERING, INC. DOMFIELD, NM 87413		
	Р.О. ВОХ 87, В (50	(if applicble): A		
FIELD REPORT:	(circle one): BGT CONFIRMATION	RELEASE INVESTIGATION / OTHER:		PAGE #: <u>1</u> of <u>1</u>
SITE INFORMATION	I: SITE NAME: SMYER	S COM LS #1		DATE STARTED: 10/29/14
QUAD/UNIT: M SEC: 2 TWP:			NM	DATE FINISHED:
<u>1/4 -1/4/FOOTAGE: 1,190'S / 1,0</u> LEASE #: NM073245		YPE: FEDERALY STATE / FEE / IN STRIKE ONTRACTOR: MBF - S. GLYNN		ENMRONMENTAL SPECIALIST(S): NJV
REFERENCE POINT				GL ELEV.: <b>5,900'</b>
1) 95 BGT (DW/DB)	GPS COORD.: 36	6.92367 X 107.965037		RING FROM W.H.: 57.5', N55E
2)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:
3)				
4)				RING FROM W.H.:
SAMPLING DATA:		OR LAB USED: HALL		READING (ppm)
1) SAMPLE ID: 5 PC-TB @ 5'				
2) SAMPLE ID:				
3) SAMPLE ID:				
	·			
SOIL DESCRIPTION				
COHESION (ALL OTHERS): NON COHESIVE / SLIGHTL		PLASTICITY (CLAYS): NON PLASTIC (SLIGHTL) DENSITY (COHESIVE CLAYS & SILTS): SC		
CONSISTENCY (NON COHESIVE SOILS): LC	OSE FIRM/ DENSE / VERY DENSE	HC ODOR DETECTED: YES NO EXPLANAT		
MOISTURE: DRY (SLIGHTLY MOIST / MOIST) W SAMPLE TYPE: GRAB (COMPOSITE) #		ANY AREAS DISPLAYING WETNESS: YES /		
DISCOLORATION/STAINING OBSERVED: YES		ANTAREAS DISECTING WEINESS. TES /		Anon
SITE OBSERVATION				
APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA:			·····	
OTHER:				
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA	ft. X NA ft. EXCAV	ATION EST	IMATION (Cubic Yards) : NA
DEPTH TO GROUNDWATER: N	EAREST WATER SOURCE: >1,000			D TPH CLOSURE STD: ppm ,
SITE SKETCH	BGT Located : off on sit	e PLOT PLAN circle: attac	hed 0W	CALIB. READ. = <u>NA</u> ppm <sub>RF =0.52</sub>
			<b>♦</b> ovm	CALIB. GAS = <b>NA</b> ppm
	~		N TIME	: <b>NA</b> am/pm DATE: <b>NA</b>
	SEPARATOR			MISCELL. NOTES
			W	O: N15502077
		BERM		
				k: <u>ZEVH01BGT2</u> J#: Z2-006Q0
ı		1		ermit date(s): 06/14/10
W.H.	PBGTL T.B. ~ 5'			CD Appr. date(s): 07/18/14
$\oplus$	B.G.		Tan ID	k OVM = Organic Vapor Meter ppm = parts per million
			A	
		X - S.P		BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N
	OW-GRADE TANK LOCATION; SPD = SAMPLE F	POINT DESIGNATION; R.W. = RETAINING WALL; NA - N		lagnetic declination: <b>10°</b> E
APPLICABLE OR NOT AVAILABLE; SW - SINGLI		40/00/44		
NOTES: GOOGLE EARTH IMAGE	RY DATE: 11/17/2013.	ONSITE: 10/29/14		· · · · · · · · · · · · · · · · · · ·

¢

.

Analytical Report Lab Order 1410E20 Date Reported: 11/5/2014

## Hall Environmental Analysis Laboratory, Inc.

₹**•** 

.

 CLIENT: Blagg Engineering
 Client Sample ID: 5PC-TB @ 5' (95)

 Project: Smyers Com LS #1
 Collection Date: 10/29/2014 12:30:00 PM

 Lab ID: 1410E20-001
 Matrix: MEOH (SOIL)
 Received Date: 10/31/2014 8:45:00 AM

 Analyses
 Result
 RL
 Qual
 Units
 DF
 Date Analyzed
 Batch

 EPA METHOD 8021B: VOLATHES
 Analyses
 Analyses
 Analyses
 Analyses

EPA METHOD 8021B: VOLATILES					Analyst: <b>NSB</b>
Benzene	ND	0.034	mg/Kg	1	10/31/2014 10:33:06 AM R22266
Toluene	ND	0.034	mg/Kg	1	10/31/2014 10:33:06 AM R22266
Ethylbenzene	ND	0.034	mg/Kg	1	10/31/2014 10:33:06 AM R22266
Xylenes, Total	ND	0.067	mg/Kg	1	10/31/2014 10:33:06 AM R22266
Surr: 4-Bromofluorobenzene	94.7	80-120	%REC	1	10/31/2014 10:33:06 AM R22266
EPA METHOD 300.0: ANIONS					Analyst: LGP
Chloride	ND	30	mg/Kg	20	10/31/2014 12:32:37 PM 16181
EPA METHOD 418.1: TPH					Analyst: JME
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	10/31/2014 12:00:00 PM 16175

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Metho	od Blank
E	Value above quantitation range	H Holding times for preparation or analysis exceeded		s exceeded
<ul><li>J Analyte detected below quantitation limits</li><li>O RSD is greater than RSDlimit</li></ul>		ND	Not Detected at the Reporting Limit	Page 1 of 4
		Р	Sample pH greater than 2.	rage 1014
R	RPD outside accepted recovery limits	RL	Reporting Detection Limit	
S	Spike Recovery outside accepted recovery limits			
	* E J O R S	<ul> <li>E Value above quantitation range</li> <li>J Analyte detected below quantitation limits</li> <li>O RSD is greater than RSDlimit</li> <li>R RPD outside accepted recovery limits</li> </ul>	EValue above quantitation rangeHJAnalyte detected below quantitation limitsNDORSD is greater than RSDlimitPRRPD outside accepted recovery limitsRL	EValue above quantitation rangeHHolding times for preparation or analysisJAnalyte detected below quantitation limitsNDNot Detected at the Reporting LimitORSD is greater than RSDlimitPSample pH greater than 2.RRPD outside accepted recovery limitsRLReporting Detection Limit

# QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

٠

WO#: 1410E20

05-Nov-14

e	g Engineering ers Com LS #1			
Sample ID MB-16181	SampType: <b>MBLK</b>	TestCode: EPA Method	300.0: Anions	<u> </u>
Client ID: PBS	Batch ID: 16181	RunNo: 22290		
Prep Date: 10/31/2014	Analysis Date: 10/31/2014	SeqNo: 656723	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Chloride	ND 1.5			
Sample ID LCS-16181	SampType: LCS	TestCode: EPA Method	300.0: Anions	
Client ID: LCSS	Batch ID: 16181	RunNo: 22290		
Prep Date: 10/31/2014	Analysis Date: 10/31/2014	SeqNo: 656724	Units: <b>mg/Kg</b>	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Chloride	14 1.5 15.00	0 91.1 90	110	

Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 2 of 4

-

## QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

100

20

100.0

Client:	Blagg En	gineering												
Project:	Smyers C	Com LS #1												
Sample ID MB-1	6175	SampT	уре: МІ	BLK	Tes	tCode: El	PA Method	418.1: TPH						
Client ID: PBS		Batch	Batch ID: 16175 RunNo: 22232											
Prep Date: 10/3	30/2014	Analysis D	ate: 1	0/31/2014	014 SeqNo: 655905 U				Units: <b>mg/Kg</b>					
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Petroleum Hydrocarbo	ons, TR	ND	20				-= "							
Sample ID LCS-	16175	SampType: LCS TestCode: EPA Method 418.1: TPH												
Client ID: LCS	6	Batch	n ID: 16	175	F	RunNo: 2	2232							
Prep Date: 10/3	30/2014	Analysis D	ate: 1	0/31/2014	S	SeqNo: 6	55906	Units: mg/H	ζg					
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Petroleum Hydrocarbo	ons, TR	95	20	100.0	0	95.1	80	120						
Sample ID LCSI	D-16175	SampType: LCSD TestCode: EPA Method 418.												
Client ID: LCS	602	Batch	D: 16	175	RunNo: 22232									
Prep Date: 10/3	80/2014	Analysis D	ate: 10	0/31/2014	S	SeqNo: 6	55907	Units: mg/K	(g					
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			

0

101

80

120

5.84

20

Qualifiers:

Petroleum Hydrocarbons, TR

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 3 of 4

1410E20 05-Nov-14

----

WO#:

## **QC SUMMARY REPORT** Hall Environmental Analysis Laboratory, Inc.

**Client:** Blagg Engineering Proje

ect:	Smyers	Com	LS	#1
	Singers	Com	ЪQ	

Sample ID MB-16174 MK	Samp	Гуре: М	BLK	Tes	PA Method	8021B: Volat	tiles			
Client ID: PBS	Batc	h ID: R2	2266	F	RunNo: 2	2266				
Prep Date:	Analysis [	Date: 10	0/31/2014	S	SeqNo: 656194 U			ζg		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Xylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.94		1.000		93.9	80	120			
Sample ID LCS-16174 MK	Samp	Гуре: LC	s	Tes	tCode: El	PA Method	8021B: Volat	tiles		
Client ID: LCSS	Batc	h ID: <b>R2</b>	2266	F	RunNo: 2	2266				
Prep Date:	Analysis [	Date: 10	0/31/2014	S	SeqNo: 6	56195	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.94	0.050	1.000	0	93.6	80	120			
Toluene	0.93	0.050	1.000	0	93.5	80	120			
Ether the enderse of	0.99	0.050	1.000	0	99.3	80	120			
Ethylbenzene	0.00	0.000								
Etnylbenzene Xylenes, Total	3.0	0.10	3.000	0	99.3	80	120			

Qualifiers:

- Value exceeds Maximum Contaminant Level. \*
- Е Value above quantitation range
- Analyte detected below quantitation limits J
- 0 RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- В Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
- Sample pH greater than 2. Р
- RL Reporting Detection Limit

Page 4 of 4

WO#: 1410E20 05-Nov-14

### HALL ENVIRONMENTAL ANALYSIS LABORATORY

#### Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

## Sample Log-In Check List

Client Name:	BLAGG	Work Order Numb	per: 1410E20	0		RcptNo:	1
Received by/dat	te: MJ	10/31/14	· · · · · · · · · · · · · · · · · · ·				
Logged By:	() Michelle Garci	a 10/31/2014 8:45:00	AM	Miire Miire	el Gan	un	
Completed By:	Michelle Garci	a 10/31/2014 8:59:39	AM	Min	el Cpr	un)	
Reviewed By:	$\Diamond$	10/31/14			,		
Chain of Cus	tody						
1. Custody sea	als intact on sampl	e bottles?	Yes	] No		Not Present 🗹	
2. Is Chain of (	Custody complete?	<b>)</b>	Yes 🔽	No No		Not Present	
3. How was the	e sample delivered	?	Courier				
<u>Log In</u>							
4. Was an atte	empt made to cool	the samples?	Yes 🖢	l No		NA 🗆	
5. Were all sar	mples received at a	a temperature of >0° C to 6.0°C	Yes 🗹	No			
6. Sample(s) i	n proper container	(s)?	Yes 🖢	No			
7. Sufficient sa	imple volume for ir	dicated test(s)?	Yes 🗹	No			
8. Are samples	s (except VOA and	ONG) properly preserved?	Yes 🗹	No			
9. Was presen	vative added to bo	tles?	Yes 🗌	] No		na 🗖	
10.VOA vials h	ave zero headspac	xe?	Yes 🗌	] No		No VOA Vials 🗹	
11. Were any s	ample containers r	eceived broken?	Yes 🗆	] No		the firm and	
				_		# of preserved bottles checked	
	work match bottle		Yes 🗸	No		for pH:	>12 unless noted)
	pancies on chain on chain on chain on chain on chain on chain an c	d on Chain of Custody?	Yes 🗹	No		Adjusted?	
	nat analyses were	-	Yes 🗹	_			_
15. Were all hol	ding times able to	be met?	Yes 🗹	No No		Checked by:	
(if no, notify	customer for auth	orization.)			L		
Special Hand	lling (if applic	able)					
		pancies with this order?	Yes	] <u>No</u>		NA 🗹	·
Perso	n Notified:	Date	:		1		
By Wi	hom:	Via:	eMail	Phone	Fax	In Person	
Regar	ding:	n en fallen einen seine seinen einen einen seinen seinen seinen seinen seinen seinen seinen seine seinen seine I vor fallen einen seine seine seine seinen seinen seinen seinen seinen seine seinen seine seinen seine seinen s		and a state with the system of the law on section of		Park ( Agric & / Parge A and a subset of the band of SAURY	
Client	Instructions:	n y na an				er internet and state for a set of a se	
17. Additional r	remarks: <i>PLV</i>	NU confection da	ters,	10/29/14	-		
18. <u>Cooler Info</u> Cooler N	ormation Ió Temp °C <u>C</u>	ondition Seal Intact Seal No.	Seal Date	tere to very since in the second	/3/// By	9	
1	1.0 Gc						

Page 1 of 1

Client: BLAGG ENGR. / BP AMERICA	Standard	(	SAME													A Diam
		🗹 Rush	DAY	<u>"</u>										1EN RAT		
	Project Name				- 1999 											
Mailing Address: P.O. BOX 87	SMYERS COM LS # 1				www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109											
BLOOMFIELD, NM 87413	Project #:			Tel. 505-345-3975 Fax 505-345-4107												
Phone #: (505) 632-1199									Ana	lysis	Req	uest		م موجوع می از		
email or Fax#:	Project Manag	jer:				nor			Τ	(		T	T	<del>,</del>		T
QA/QC Package:			ELEZ	<b>HB-</b> (8021B)	(Vluo	<b>JOHN</b>		(5)		04,50	PCB's			er - 300.1)		a
Accreditation:	Sampler:	NELSON V	ELEZ AV	<b>†</b>	(Gas	/ DRO /	<b>(</b>	504.1) 82705IMS1		05/1	8082			300.0 / water		sample
NELAP     Other	Qn lce:		🕞 No		Hdl		418.1)	504.1) 8270SI		O3,N			(A	0.0		e sa
EDD (Type)	Sample Temp	erature:	.0		+ 	GRC	p	b b	etals	Ň	cide	R	Š	1	e	osit
رتفاعالی Date Time Matrix Sample Request ID	Container Type and #	Preservative Type	HEAL NO	BTEX +-MTB	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO	TPH (Method	EDB (Method PAH (8310 or	RCRA 8 Metals	Anions (F,Cl,NO <sub>3</sub> ,NO <sub>2</sub> ,PO <sub>4</sub> ,SO <sub>4</sub> )	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil	Grab sample	5 pt. composite
10/ <b>30</b> /14 1230 SOIL 5PC - TB @ 5' (95)	4 oz 1	Cool	-60 )	<u></u>			$\overline{\mathbf{v}}$					<u> </u>	<u></u>	V		V
				1			-1									
					<b> </b>		-+					-+			<u> </u>	
RUN TPH 8015B IF TPH																
418.1 > 100 mg/Kg				<u> </u>												
												T				
Date: Time: Relinquished by:	Received by:	ـــــــــــــــــــــــــــــــــــــ	Date Time	Rer	nark	s:				<u> </u>	L4	ابي مسمعه			4	
10/30/14 1530 9/m 1	Mustu	Inbeler"	0/30/14 /530 Date Time			RECTI ice, 2		) BP: nergy C	ourt,	Farm	ningto	on, NI	M 87	401		
Date: Time: Relinquished by: 10/30/14 1810 Must Walls	Received by:	ut to 10	Date Time	l w				<u>N1550</u>				/key:_		EVH01	3GT2	

۶. ۲

1

If necessary, samples submitted to Hall Environmental may be subcontracted to other accredited laboratoriles. This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report.



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

October 20, 2014

OO

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

#### VIA CERTIFIED MAIL – RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: SMYERS COM LS 001 API #: 3004511002

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about October 22, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

9DUC

Jerry Van Riper Surface Land Negotiator BP America Production Company

### BP America Production Company 200 Energy Court

Farmington, NM 87401 Phone: (505) 326-9200

### SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

October 10, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

#### **RE:** Notice of Proposed Below-Grade Tank (BGT) Closure

SMYERS COM LS 001 API 30-045-23281 (M) Section 2 – T31N – R11W San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around October 17, 2014.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Pagee

Jeff Peace BP Field Environmental Advisor

(505) 326-9479



