Well:	Newberry Federal #1 930' FSL & 990' FWL	
Location:		
1	Sec 17 T31N R12W NMPM	
	San Juan County, New Mexico	
API:	30-045-10689	

Operator: Great Western Drilling Company				
Spud date:	11/20/60			
Elevations: KB	5,955'			
KB-GL	11.7'			
GL	5943.3'			

711 1: 00 040		<u> </u>
TOPS	NOTES	HOLE CASING
		SIZE & CEMENT
i	1	
		13 3/4"
		10 3/4" 32.75# J-55 set at 325'
1	336'	cmtd to GL w/ 200 sx
	······································	8 3/4"
· f		
•	4.	
		cement squeezed perfs in casing at 1,900' w/100 sx 10/64
Pictured Cliffs at 2,234'	4	
		cement squeezed perfs in casing at 2,399' w/100 sx 10/64
1		
I		cement squeezed hole in casing at 3,994' w/325 sx 10/64
I		
Point Lookout at 4,674'		cement squeezed holes in casing 3,910' - 4,960'
1		1 1 w/ 450 sx 11/88
Mancos at 4,903		
	•	
		DV tool at 4,919" cmtd 2nd stge w/ 175 sx
	;	TOC behind 5 1/2" from 1st atage not reported
Mancos at 4,903'		
- "		
Gallup at 5,995'		
		213 jts 2 3/8" 4.7# J-55 tubing with 7 jts 1 1/4" on bottom
	ı	
Oanaaham at 6 7441	!	
Greenhorn at 6,714'		
Graneras et 6 700'	•	
Graneros at 6,786'		
Dakota at 6,900'		
		fracd w/ ±,50,000 gal + 40,000# 20/40sand 1/7/61
		Dakota perfs 6,900 - 32'
	:	fracd w/ ±98,00 gal + 52,000# 20/40sand 12/31/60
	enf of tubing at 6,959'	Dakota perfs 6,950 - 90'
	em or tubing at 0,333 .	fracd w/ 75,00 gal + 130,000# 20/40sand 12/3/88
Morrison at 7,080'		pbtd 7,075' 5 1/2" 17# set at 7,114'
NIOTISUII EL 7,000	TD at 7,122	cmtd 1st stage w/ 325 sx
	10 01 7,122	Metalet 1, (4) IV Control 1st stage W/ 525 5A
	<u> </u>	