District 1
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or

12484 Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration OIL CONS. DIV DIST. 3
Permit of a pit or proposed alternative method Solution Closure of a pit, below-grade tank, or proposed alternative method DEC 23 2014
Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1.
Operator: BP America Production Company OGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Mudge LS 18
API Number:3004510744 OCD Permit Number:
U/L or Qtr/QtrGSection15 Township31N Range _ II W County:San Juan
Center of Proposed Design: Latitude36.901234 Longitude107.97347 NAD: ☐1927 ☒ 983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume: 45.0 bbl Type of fluid: Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other _Single walled/double bottomed; side walls not visible
Liner type: Thicknessmil
4.
Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	1
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	·
Screen Netting Other Other	•
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
8. Variances and Exceptions:	
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance of the compliance of the complianc	ntable source
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	omore source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)	☐ Yes ☐ No
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	☐ Yes ☐ No
Society; Topographic map	Yes No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured	Yes No
from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	
	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)	Yes No
- Topographic map; Visual inspection (certification) of the proposed site	

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	
	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
	☐ 1es ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	cuments are
attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	15.17.9 NMAC
Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached.	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. □ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC □ Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC □ Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. □ Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC □ Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
17. Operator Application Cartification:	
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address:	
18. OCD Approval: Permit Application (including closufe plan) Closufe Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 12/2/2	'm<
$\mathcal{O}_{\mathcal{A}}$	
Title: OCD Permit Number:	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
☐ Closure Completion Date:11/11/2011_	
20. Closure Method: ☐ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo ☐ If different from approved plan, please explain.	op systems only)
21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please incomark in the box, that the documents are attached. □ Proof of Closure Notice (surface owner and division) □ Proof of Deed Notice (required for on-site closure for private land only) □ Plot Plan (for on-site closures and temporary pits) □ Confirmation Sampling Analytical Results (if applicable)	dicate, by a check

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure requires. I also certify that the closure complies with all applicable closure requires	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Jeff Pose	Date:December 22, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

\$

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Mudge LS 18 API No. 3004510744 Unit Letter G, Section 15, T31N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	45 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	7.8

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed as part of final reclamation when the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed as part of final reclamation when the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed as part of final reclamation when the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.
 - Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	cation	n and Co	orrective A	ction	1			
						OPERA	ГOR		☐ Initia	al Report	\boxtimes	Final Report
Name of Co	ompany: B	P				Contact: Jef	f Peace					
		Court, Farming	gton, N	M 87401			No.: 505-326-94					
Facility Na	me: Mudg	e LS 18				Facility Typ	e: Natural gas v	vell				
Surface Ow	ner: Feder	al		Mineral ()wner:	Federal			API No	. 3004510′	744	
				LOCA	ATIO	N OF RE	LEASE					
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	East/V	West Line	County: S	an Juan	
G	15		11W	1,610	North		1,450	East				· · · · · · · · · · · · · · · · · · ·
		Latitu	ide 3	6.901234		Longitu	de 107.97347					
			_			—						
Type of Rele	ase: none			IVAI	UKE	,	Release: N/A		Volume R	Lecovered: N	J/A	
		w grade tank – 4	5 bbl				lour of Occurrence	e:		Hour of Dis		:
Was Immedi		Given?				If YES, To	11.4					
			Yes	No 🛛 Not R	equired							
By Whom?	,					Date and I-						
Was a Water	course Read		v \	l ar-		If YES, Vo	lume Impacting t	the Wate	ercourse.			
			Yes 🛚	•								
If a Waterco	ırse was Im	pacted, Describe	e Fully.*	•								
the BGT. So	il analysis i	esulted in TPH,	BTEX a	and chloride belo	w standa	ards. Analysi	the BGT was do s results are attack	hed.				·
regulations a public health should their or or the enviro	Il operators or the envi operations h nment. In a	are required to r ronment. The action ave failed to add	report and eceptance equately D accep	nd/or file certain r te of a C-141 repo investigate and r	elease no ort by the emediate	otifications a e NMOCD m e contaminati	knowledge and und perform correct arked as "Final Room that pose a threet the operator of the correct arked as "Final Room that pose a threet arked ar	tive act eport" d eat to gr	ions for rele loes not reli ound water	eases which eve the oper , surface wa	may en ator of ter, hur	danger Tiability nan health
	. 0.	. 0					OIL CON	SERV	ATION	DIVISIO	N	
Signature:	John	Mases	/									
Digitature.	XIV	V Star				Annroved by	Environmental S	necialis	t·			
Printed Name	e: Jeff Peac	e										
Title: Field E	nvironmen	tal Coordinator				Approval Dat	e:		Expiration I	Date:		
E-mail Addre	ess: peace.jo	effrey@bp.com			'	Conditions of	Approval:			Attached		
Date: Decen	ber 22, 20	14	Pho	ne: 505-326-9479)							

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, BLO	INEERING, INC. OMFIELD, NM 87413 632-1199	- 1	API #: 300451 TANK ID (if applicble):	0744 A
FIELD REPORT:	(circle one): BGT CONFIRMATION RELE	EASE INVESTIGATION / OTHER:		PAGE #: 1	of
SITE INFORMATION	I: SITE NAME: MUDGE LS	S # 18		DATE STARTED: 10	/28/11
QUAD/UNIT: G SEC: 15 TWP:	31N RNG: 11W PM: NN	CNTY: SJ ST: NM		DATE FINISHED:	
1/4-1/4/FOOTAGE: 1,610'N / 1,4	50'E SW/NE LEASE TYPE:			ENVIRONMENTAL	
LEASE #: SF078051	PROD. FORMATION: FT CON	ELKHORN ITRACTOR: MBF - C. McINESS		SPECIALIST(S):	JCB
REFERENCE POINT	: WELL HEAD (W.H.) GPS COC	ORD.: 36.90137 X 107	7.9735	GL ELEV.:	6,128'
1) 45 BGT (SW/DB)	GPS COORD.: 36.901				
2)	GPS COORD.:	DIST	ANCE/BEA	ARING FROM W.H.:	
3)	GPS COORD.:	DIST	ANCE/BEA	ARING FROM W.H.:	
4)	GPS COORD.:	DIST	ANCE/BEA	RING FROM W.H.:	
LAB INFORMATION:	CHAIN OF CUSTODY RECORD(S) # OR LAB	USED: HALL			OVM READING
1) SAMPLE ID: 45 BGT 5-pt. @	4' SAMPLE DATE: 10/29/11	SAMPLE TIME: 1230 LAB ANALYSIS:	418.1	/8015/8021/300.0 (C	(ppm) 7.1
2) SAMPLEID:	SAMPLE DATE:	SAMPLE TIME: LAB ANALYSIS:		1000	
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANALYSIS:			
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANALYSIS:			
SOIL COLOR: COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLE CONSISTENCY (NON COHESIVE SOILS): LO MOISTURE: DRY SLIGHTLY MOIST / MOIST / W SAMPLE TYPE: GRAB (COMPOSITE) + DISCOLORATION/STAINING OBSERVED ANY AREAS DISPLAYING WETNESS: YES / NO	DOSE / FIRM / DENSE VERY DENSE ET / SATURATED / SUPER SATURATED # OF PTS. SYMPTOTIC STREET OF PTS. EYES NO EXPLANATION - RUST FROM	PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY F DENSITY (COHESIVE CLAYS & SILTS; HC ODOR DETECTED: YES NO OM BGT BOTTOM. PRECIPITATION (rain storm).	PLASTIC / CO): SOFT /	OHESIVE / MEDIUM PLASTIC / HIGHI / FIRM / STIFF / VERY STIFF	Y PLASTIC
		t. X <u>NA</u> ft. cubic CAREST SURFACE WATER: <1,000'	-	cavated (if applicable): D TPH CLOSURE STD:	NA 1,000 PPM
SITE SKETCH	WELL HEAD METER	PLOT PLAN circle: attached	OVM C	CALIB. READ. = 53.3 CALIB. GAS = 100 12:40 ampm DATE: _ MISCELL. NO /O - N1409936	ppm RF = 0.52 ppm 10/28/11
T.B	RUN GGTL A. ~ 4' BGT EXCAVATION TO 4' B.G.		<u>P(</u>		D6/14/10
T.B. = TANK BOTTOM; PBGTL = PREVIOU	AVATION DEPRESSION; B.G. = BELOW GRADE; B = S BELOW-GRADE TANK LOCATION; SPD = SAMPLE .E; SW - SINGLE WALL; DW - DOUBLE WALL; SB - S	POINT DESIGNATION; R.W. = RETAINING WAL). _		: Y / N / NA

Hall Environmental Analysis Laboratory, Inc.

Date: 11-Nov-11 Analytical Report

CLIENT:

Blagg Engineering

Lab Order: 1111111

Project:

Mudge LS 18

Lab ID: 1111111-01 Client Sample ID: 45 BGT 5-pt @-4'

Collection Date: 10/28/2011 12:30:00 PM

Date Received: 11/1/2011 Matrix: SOIL

Analyses	Result	PQL	Qual Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	E ORGANICS		· · · · · · · · · · · · · · · · · · ·		Analyst: SCC
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	11/4/2011 6:00:34 PM
Surr: DNOP	97.7	73.4-123	%REC	1	11/4/2011 6:00:34 PM
EPA METHOD 8015B: GASOLINE RA	ANGE				Analyst: RAA
Gasoline Range Organics (GRO)	ND	4.8	mg/Kg	1	11/3/2011 7:37:14 PM
Surr: BFB	96.1	75.2-136	%REC	1	11/3/2011 7:37:14 PM
EPA METHOD 8021B: VOLATILES					Analyst: RAA
Benzene	ND	0.048	mg/Kg	1	11/3/2011 7:37:14 PM
Toluene	ND	0.048	mg/Kg	1	11/3/2011 7:37:14 PM
Ethylbenzene	ND	0.048	mg/Kg	1	11/3/2011 7:37:14 PM
Xylenes, Total	ND	0.096	mg/Kg	1	11/3/2011 7:37:14 PM
Surr: 4-Bromofluorobenzene	96.3	80-120	%REC	1	11/3/2011 7:37:14 PM
EPA METHOD 300.0: ANIONS					Analyst: BRM
Chloride	7.8	1.5	mg/Kg	1	11/4/2011 5:57:05 PM
EPA METHOD 418.1: TPH					Analyst: JB
Petroleum Hydrocarbons, TR	ND	· 20	mg/Kg	1	11/7/2011

Qualifiers:

- Value exceeds Maximum Contaminant Level
- Estimated value
- Analyte detected below quantitation limits
- NC Non-Chlorinated
- PQL Practical Quantitation Limit

- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Η
- MCL Maximum Contaminant Level
- ND Not Detected at the Reporting Limit
- Spike recovery outside accepted recovery limits

C	hain-	of-Cu	istody Record	Turn-Around	Time:			1		. *	E _	AL	¥ 0		nj W	7 1 12	·^	rji r	A E	NT	ΓAL	
Client:	BLAVAIL	ENGW	EERING IVC.	Standard	□ Rush	<u> </u>		<u> </u>		<u> </u>											OR	
72	DA	4450.04		Project Name		·			<u>)</u>								al.co					•
Mailing	Address:	Po. E	So× 97	MUDGE	E LS 18	}			49	01 H								л М 87	109			
			M 97413	Project #:														4107				
			32-1199	=						, g			Ā	nal	ysis	Req	uest					
email o			7	Project Mana	ger:				only)	sel)					(4)							
QA/QC I	Package: dard		☐ Level 4 (Full Validation)	J. B.	A66			s (8021)	ည္က	(Gas/Diesel)		ļ			PO ₄ ,S(PCB's						
Accredi	tation	□ Othe	er	Sampler: J	- BLAGE			igger 1	+ TPH		418.1)	04.1)	AH)) ₃ ,NO ₂ ,	, / 8082		₹				or N)
□ EDD	(Type)_			Sample Tem	oeratiure	854	and the second	出	38	28 p	4 bc	od 5	or P	stals	N.	ides	ৱ		r)			اخ
Date	Time	Matrix	Sample Request ID	Sampler: J Ondice Sample Tem Container Type and #	Preservative Type	HEAL	Norman Variation	BTEX +*₩	BTEX + MTBE	TPH Method 8015B	TPH (Method	EDB (Method 504.1)	8310 (PNA or PAH)	RCRA 8 Metals	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082 PCB	8260B (VOA)	8270 (Semi-VOA)	CHLURUDE			Air Bubbles (Y or N)
Pal II	1230	SOIL	45 BGT 5-p+e-4	402 × 1	Cex	-1		X		×	×		ĺ						X			
		_																				
														•	:	-						
										$\neg \dagger$											1	
																				\dashv	十	$\dashv \dashv$
											$\neg \dagger$						\neg				+	
											_									-	+	
		 -		<u> </u>													\neg	\neg		\dashv	+	+
				<u> </u>							$\neg \dagger$							\dashv	_	-	+	
										-	_			-						\dashv	+	-
				-															\dashv	\dashv	+	
																			\dashv	\dashv		+
Date:	Time:	Relinquish	ned by:	Received by:	!	Dațe	Time	Ren	narks	I S: _G	-Ro	√ 1		ب	لــــا ع نہر	10/5						
198/11	1467	THE	Beey	Christin	1 no ton	10/28/11	1467		14				•									
Date:	Time:	Relinquish	ned by:	Received by:		Date	Time	₹5	CHU	UB	ভো											
131/11	1502	Ch	ut Weete	Mile	U Caru	a Hh	9:00	JE	FF	†€/ 	Œ.			_								1
, li	necessary,	sam ples sub	mitted to Hall Environmental may be subd	ontracted to other ac	credited laboratorie	es. This serves a	s notice of this	possib	oility.	Any su	b-cont	racted	data	will be	clearl	y nota	led on	the ar	nalytica	il repor	rt.	

Date: 11-Nov-11

QA/QC SUMMARY REPORT

Client:

Blagg Engineering

Project:

Mudge LS 18

Work Order:

1111111

Analyte	Result	Units	PQL	SPK Va	SPK ref	%Rec L	owLimit Hi	ghLimit %RF	D RPDLimit	Qual
Method: EPA Method 418.1: Ti	PH									-
Sample ID: MB-29238		MBLK				Batch ID:	29238	Analysis Date	:	11/7/201
Petroleum Hydrocarbons, TR	ND	mg/Kg	20							
Sample ID: LCS-29238		LCS				Batch ID:	29238	Analysis Date	;	11/7/201
Petroleum Hydrocarbons, TR	97.94	mg/Kg	20	100	0	97.9	87.8	115		
Sample ID: LCSD-29238		LCSD				Batch ID:	29238	Analysis Date	;	11/7/201
Petroleum Hydrocarbons, TR	99.22	mg/Kg	20	100	0	99.2	87.8	115 1.3	8.04	
Method: EPA Method 8015B: I	Diesel Range	Organics								
Sample ID: MB-29201		MBLK				Batch ID:	29201	Analysis Date	11/4/2011 1	0:06:18 AN
Diesel Range Organics (DRO)	ND	mg/Kg	10							
Sample ID: LCS-29201		LCS				Batch ID:	29201	Analysis Date	11/4/2011 1	0:41:13 AN
Diesel Range Organics (DRO)	41.76	mg/Kg	10	50	3.707	76.1	66.7	119		
Method: EPA Method 8015B: 0	Sasoline Rai	nge								
Sample ID: MB-29187		MBLK				Batch ID:	29187	Analysis Date	11/4/2011	1:36:22 AN
Gasoline Range Organics (GRO)	ND	mg/Kg	5.0							
Sample ID: LCS-29187		LCS				Batch ID:	29187	Analysis Date	11/3/2011 1	2:07:26 PN
Gasoline Range Organics (GRO)	29.36	mg/Kg	5.0	25	0	117	86.4	132		
Method: EPA Method 8021B: V	/olatiles									•
Sample ID: MB-29187		MBLK				Batch ID;	29 18 7	Analysis Date	11/4/2011	1:36:22 AN
Benzene	ND	mg/Kg	0.050							
Toluene	ND	mg/Kg	0.050							
Ethylbenzene	ND	mg/Kg	0.050							
Xylenes, Total	ND	mg/Kg	0.10							
Sample ID: LCS-29187		LCS				Batch ID:	29187	Analysis Date	11/3/2011 1	2:37:30 PM
Benzene	1.028	mg/Kg	0.050	1	0.0226	101	83.3	107		
Toluene	0.9742	mg/Kg	0.050	1	0	97.4	74.3	115		
Ethylbenzene	1.075	mg/Kg	0.050	1	0.0051	107	80.9	122		
Xylenes, Total	3.294	mg/Kg	0.10	3	0	110	85.2	123		

Qualifiers:

E Estimated value

J Analyte detected below quantitation limits

ND Not Detected at the Reporting Limit

H Holding times for preparation or analysis exceeded

NC Non-Chlorinated

R RPD outside accepted recovery limits

Hall Environmental Analysis Laboratory, Inc.

Sample Receipt Checklist

Client Name BLAGG			Date Received	l:	11/1/2011
Work Order Number 1111111			Received by:	MMG	
Checklist completed by: Signature Adult	, Cjarua	// // /// Date	Sample ID la	bels checked b	y: Initials
Matrix:	Carrier name:	<u>FedEx</u>			
Shipping container/cooler in good condition?		Yes 🗹	No 🗌	Not Present	
Custody seals intact on shipping container/coole	er?	Yes 🗹	No 🗌	Not Present	☐ Not Shipped ☐
Custody seals intact on sample bottles?		Yes 🗌	No 🗌	N/A	✓
Chain of custody present?		Yes 🗹	No 🗆		
Chain of custody signed when relinquished and	received?	Yes 🗹	No 🗆		
Chain of custody agrees with sample labels?		Yes 🗹	No 🗌		
Samples in proper container/bottle?		Yes 🗹	No 🗌		
Sample containers intact?		Yes 🗹	No 🗌		
Sufficient sample volume for indicated test?		Yes 🗹	No 🗆		
All samples received within holding time?		Yes 🗹	No 🗌		Number of preserved bottles checked for
Water - VOA vials have zero headspace?	No VOA vials subm	nitted 🗹	Yes	No 🗌	pH:
Water - Preservation labels on bottle and cap m	atch?	Yes 🗌	No 🗆	N/A 🗹	
Water - pH acceptable upon receipt?		Yes 🗌	No 🗌	N/A 🗹	<2 >12 unless noted below.
Container/Temp Blank temperature?		1.8°	<6° C Acceptable		
COMMENTS:		If given sufficient time to cool.			
=======================================	======				
Client contacted	Date contacted:		Person contacted		
Contacted by:	Regarding:				
Comments:					
,					
	·				
Corrective Action					

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

September 29, 2011

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

MUDGE LS 018-FS API 30-045-10744 (M) Section 15 – T31N – R11W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl. BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Buddy Shaw BP Environmental Advisor

(505) 320-0401





BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

September 20, 2011

Bureau of Land Management Mark Kelly 1235 La Plata Hwy Farmington, NM 87401

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank

Well Name: MUDGE LS 018-FS

Dear Bureau of Land Management,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about September 26, 2011. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

AD Vale

Surface Coordinator/Business Security Representative

BP America Production Company



