Q<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 ' District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or

Santa Fe, NM 87505

12486 Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration OIL CONS. DIV DIST. 3
Permit of a pit or proposed alternative method
45 -22643
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances
1.
Operator: BP America Production CompanyOGRID#:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:State Gas Com L 1A
API Number:3004522643 OCD Permit Number:
U/L or Qtr/QtrCSection2Township29NRange9WCounty:San Juan
Center of Proposed Design: Latitude36.75837 Longitude107.75301 NAD: ☐1927 ☑ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Double walled/double bottomed; side walls not visible
Liner type: Thicknessmil
4.
Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school,	hospital,
institution or church) ☐ Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers ☐ Signed in compliance with 19.15.16.8 NMAC	
Signed in compnance with 19.13.10.8 NMAC	
8. Variances and Exceptions:	
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank:	
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. ☐ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC	
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance of the compliance for each siting criteria below in the application.	ptable source
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)	□ v □ N-
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	Yes No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proviously Approved Design (ettach corp. of design) - API Numbers	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Author of Paragraph* (1) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Report - based upon the requirements of Paragraph* (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	attached to the
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
· · · · · · · · · · · · · · · · · · ·	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain FEMA map	☐ Yes ☐ No ☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ief.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
e-mail address:	_
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 1/13/6	the closure report.
18. OCD Approval: Permit Application (including closure plan). Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 1/3/6 Title: OCD Permit Number: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report.

22. Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rep belief. I also certify that the closure complies with all applicable closure requireme	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: 19ff Posse	Date: _December 22, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

Page 6 of 6

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

State Gas Com L 1A API No. 3004522643 Unit Letter C, Section 2, T29N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows:

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	· 100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	7.6

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Groundwater found beneath the BGT was also sampled, with BTEX below the standards. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is covered by the LPT and is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1625 N. French Dr., Hobbs, NM 88240 · <u>District II</u> 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

* Attach Additional Sheets If Necessary

State of New Mexico **Energy Minerals and Natural Resources**

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notificati	on and Corrective Action	on a second seco				
	OPERATOR	☐ Initial Report ☐ Final Repor				
Name of Company: BP	Contact: Jeff Peace					
Address: 200 Energy Court, Farmington, NM 87401	Telephone No.: 505-326-9479					
Facility Name: State Gas Com L 1A	Facility Type: Natural gas well					
Surface Owner: Private Mineral Owner	r: Private	API No. 3004522643				
LOCATIO	ON OF RELEASE					
Unit Letter Section Township Range Feet from the C 2 29N 9W 900 Nor		t/West Line County: San Juan				
Latitude 36.75837	Longitude107.75301					
NATUR	E OF RELEASE					
Type of Release: none	Volume of Release: N/A	Volume Recovered: N/A				
Source of Release: below grade tank – 95 bbl	Date and Hour of Occurrence: N/A	Date and Hour of Discovery: N/A				
Was Immediate Notice Given?	If YES, To Whom?					
☐ Yes ☐ No ☒ Not Require	ed					
By Whom?	Date and Hour					
Was a Watercourse Reached? ☐ Yes ☑ No	If YES, Volume Impacting the Wa	atercourse.				
If a Watercourse was Impacted, Describe Fully.*						
, , , , , , , , , , , , , , , , , , , ,						
Describe Cause of Problem and Remedial Action Taken.* Sampling of the BGT. Soil analysis resulted in TPH, BTEX and chloride below star the standards. Analysis results are attached. Describe Area Affected and Cleanup Action Taken.* BGT was remove backfilled and compacted and is still within the active well area.	ndards. Groundwater found beneath th	e BGT was also sample, with BTEX below				
I hereby certify that the information given above is true and complete to regulations all operators are required to report and/or file certain release public health or the environment. The acceptance of a C-141 report by should their operations have failed to adequately investigate and remed or the environment. In addition, NMOCD acceptance of a C-141 report federal, state, or local laws and/or regulations.	e notifications and perform corrective at the NMOCD marked as "Final Report" iate contamination that pose a threat to	ctions for releases which may endanger does not relieve the operator of liability ground water, surface water, human health				
Δ Ο	OIL CONSER	VATION DIVISION				
Signature: Off Laxe						
Printed Name: Jeff Peace	Approved by Environmental Specialist:					
Title: Field Environmental Coordinator	Approval Date:	Expiration Date:				
E-mail Address: peace.jeffrey@bp.com	Conditions of Approval:	Attached				
Date: December 22, 2014 Phone: 505-326-9479						

CLIENT BP	API#: 3004522643						
CLIENT: DI	IM 87413	TANK ID (if applicble):	<u>.</u>				
FIELD REPORT:	(circle one): BGT CONFIRMATION	RELEASE INVESTIGATION /	OTHER:	PAGE #: 1 of	_		
SITE INFORMATION	I: SITE NAME: STAT	EGCL#1A		DATE STARTED: 09/2	2/11		
QUAD/UNIT: C SEC: 2 TWP:	29N RNG: 9W P	M: NM CNTY: SJ ST:	NM	DATE FINISHED:			
1/4-1/4/FOOTAGE: 900'N / 1,730		TYPE: FEDERAL / STATE	DNI	ENVIRONMENTAL	,		
	PROD. FORMATION: MV	CONTRACTOR: MBF - J	I. POWELL	SPECIALIST(S):			
REFERENCE POINT	: WELL HEAD (W.H.) GF	PS COORD.: 36.	75832 X 107.752	255 GL ELEV.: 5	5,612'		
	GPS COORD.:			EARING FROM W.H.: 135',	N81W		
2)				EARING FROM W.H.:			
3)				EARING FROM W.H.:			
LAB INFORMATION:	GPS COORD.:			EARING FROM W.H.:	OVM		
1) SAMPLE ID:GW - TB @ 4' (9	J		ALL	0024/200 4 (CI)	READING (ppm)		
1) SAMPLE ID: 4PC - SW @ 2' (1,	NA NA		
3) SAMPLE ID:				• •	INA		
4) SAMPLE ID:							
SOIL DESCRIPTION							
SOIL COLOR:	SUIL TYPE: SAND/ SIL	TY SAND / SILI Y SILI Y CLAT	CLAY / GRAVEL / O	THER			
COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY	COHESIVE / COHESIVE / HIGHLY COHESIV	E PLASTICITY (CLAYS): NON	PLASTIC / SLIGHTLY PLASTIC	COHESIVE / MEDIUM PLASTIC HIGHLY PL	ASTIC		
CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY/SLIGHTLY MOIST MOIST W		- I		T / FIRM STIFF / WERY STIFF / H.	ARD		
SAMPLE TYPE: GRAB / COMPOSITE - #		HC ODOK DETEC	IED: YES [NO] EXE	_ANATION -			
DISCOLORATION/STAINING OBSERVED:							
WELL BURN AND WETHERD WED IN	CPOLINDWATE	C A ET DEL ON COADE					
ANY AREAS DISPLAYING WETNESS: YES INDICATED NO APPARENTS: NO APPARENTS:	ARENT EVIDENCE OF A RELEA						
EXCAVATION DIMENSIONS (if applicable)	: <u>NA</u> ft. X <u>N</u> /	ft. X NA ft.	cubic vards ex	xcavated (if applicable):	NA		
, , , ,	EAREST WATER SOURCE: <1,00		•	CD TPH CLOSURE STD: 10			
SITE SKETCH TO	A	PLOT PLAN ci	ircle: attached OW	I CALIB. READ. = NA ppm			
PROD. TANK				M CALIB. GAS = NA ppm	111 - 0.02		
			NÎ		NA		
	AREA EXCAVATED TO REMOVE BGT		 	MISCELL. NOT	ES		
X			Ιv	NO - N1401050			
x () J			<u>F</u>	PO - 55300			
	PBGTL T.B. ~ 5'		TA -	PK - ZSCHWLLBGT			
	B.G.		WELL F	PJ - Z2-00690-C			
			. –	Permit date: 06/	14/10		
тс			I 11	nk	17110		
SÁN JU ~ 300	AN R.	X - SOIL S.	P()	BGT Sidewalls Visible: Y	/N) NA		
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCA	VATION DEPRESSION; B.G. = BELOW GR	ADE; B = BELOW; T.H. = TEST HOLE;	~=APPROX.;	BGT Sidewalls Visible: Y	/ N/NA		
T.B. = TANK BOTTOM; PBGTL = PREVIOUS NA - NOT APPLICABLE OR NOT AVAILABLE				Magnetic declination:	<u>10° E</u>		
TRAVEL NOTES: CALLOUT	TON ONIOCE TWEE, DIT BOODER TWE	ONSITE: 09/2					

Hall Environmental Analysis Laboratory, Inc.

Date: 04-Oct-11
Analytical Report

CLIENT:

Blagg Engineering

Client Sample ID: GW-TB @ 4' (95 BGT)

Lab Order:

1109915

Collection Date: 9/22/2011 9:30:00 AM

Project:

STATE GC L #1A

Date Received: 9/23/2011

Lab ID:

1109915-01

Matrix: AQUEOUS

Analyses	Result	PQL (Qual Units	DF	Date Analyzed
EPA METHOD 8021B: VOLATILES					Analyst: RAA
Benzene	ND	1.0	μg/L	1	9/28/2011 4:03:59 AM
Toluene	ND	1.0	μg/L	1	9/28/2011 4:03:59 AM
Ethylbenzene	ND	1.0	μg/L	1	9/28/2011 4:03:59 AM
Xylenes, Total	ND	2.0	μg/L	1	9/28/2011 4:03:59 AM
Surr: 4-Bromofluorobenzene	95.9	76.5-115	%REC	1	9/28/2011 4:03:59 AM
EPA METHOD 300.0: ANIONS					Analyst: LJB
Chloride	17	0.50	mg/L	1	9/26/2011 1:54:46 PM

Qualifiers:

- Value exceeds Maximum Contaminant Level
- E Estimated value
- J Analyte detected below quantitation limits
- NC Non-Chlorinated
- PQL Practical Quantitation Limit

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded

MCL Maximum Contaminant Level

- ND Not Detected at the Reporting Limit
- S Spike recovery outside accepted recovery limits

Hall Environmental Analysis Laboratory, Inc.

Date: 04-Oct-11 Analytical Report

CLIENT:

Blagg Engineering

Client Sample ID: 4PC-SW @2' (95 BGT)

Lab Order:

1109915

Project:

1109915-02

Collection Date: 9/22/2011 11:50:00 AM

Lab ID:

STATE GC L #1A

Date Received: 9/23/2011

Matrix: SOIL

Analyses	Result	PQL	Qual	Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	E ORGANICS					Analyst: JB
Diesel Range Organics (DRO)	ND	9.9		mg/Kg	1	9/28/2011 2:48:26 PM
Surr: DNOP	123	73.4-123	S	%REC	1	9/28/2011 2:48:26 PM
EPA METHOD 8015B: GASOLINE RA	ANGE					Analyst: RAA
Gasoline Range Organics (GRO)	ND	4.7		mg/Kg	1	9/30/2011 5:06:32 PM
Surr: BFB	95.3	75.2-136		%REC	1	9/30/2011 5:06:32 PM
EPA METHOD 8021B: VOLATILES						Analyst: RAA
Benzene	ND	0.047		mg/Kg	1	9/30/2011 5:06:32 PM
Toluene	ND	0.047		mg/Kg	1	9/30/2011 5:06:32 PM
Ethylbenzene	ND	0.047		mg/Kg	1	9/30/2011 5:06:32 PM
Xylenes, Total	ND	0.095		mg/Kg	1	9/30/2011 5:06:32 PM
Surr: 4-Bromofluorobenzene	98.5	80-120		%REC	1	9/30/2011 5:06:32 PM
EPA METHOD 300.0: ANIONS						Analyst: SRM
Chloride	7.6	7.5		mg/Kg	5	9/30/2011 1:25:36 AM
EPA METHOD 418.1: TPH						Analyst: JB
Petroleum Hydrocarbons, TR	ND	21		mg/Kg	1	9/29/2011

Qualifiers:

- Value exceeds Maximum Contaminant Level
- Estimated value Ε
- Analyte detected below quantitation limits
- NC Non-Chlorinated
- PQL Practical Quantitation Limit

- В Analyte detected in the associated Method Blank
- Η Holding times for preparation or analysis exceeded

MCL Maximum Contaminant Level

- ND Not Detected at the Reporting Limit
 - Spike recovery outside accepted recovery limits

	<u>hain-c</u>	nain-of-Custody Record Turn-Around Time:		HALL ENVIRONMENTAL											TA	5					
Client:	BLAG	G ENGR.	,,,,_,,_,,_,,,,,,,,,,,,,,,,,,,,,,,,,,	Standard	Rush _													TAS		_	
				Project Name:			i				١	ww.	halle	nviro	nme	ntal.	com				
Mailing /	Address:	P.O. BO	X 87	STATE	SC L3	# 1-A			490)1 Ha	wki	ns NE	- A	lbuqu	erqu	ue, N	IM 87	109			
		BLOOM	FIELD, NM 87413	Project #:	,				Te	l. 50 <u>!</u>	5-34	5-397	5	Fax	505-	345-	4107				
Phone #		(505) 63	32-1199						A 4 2	** S	A ST	13.	Ana	lysis	Red	ues	t		نام و معالیا منابع از مانیا		
email or				Project Manag	er:									(4				多			
QA/QC P			Level 4 (Full Validation)	NEUS	MELSON VELEZ 90V			5 (8021B)	only)	(Gas/Diesel)				PO4, SO4)	PCB's			DEADORS)		a	
Accredit	ation:			Sampler: No	ELSON VE	LET.	nr	- E	(Gas	(Gas,	ļ			NO2,	32 P(8		hpl	
□ NELA	ıP	□ Other		Onice	XSYes .	⊒ No.		1 €	H	15B (418.1)	4.1	Ē		/ 8082			300		s saı	2
□ EDD	(Type)			Sample Tempe	eature 33			E	1	803	d 41	950	<u> </u>	Cl, NO3,	des/		8	00	a l	osite	Z Or
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL	No:	BTEX +************************************	BTEX + MTBE + TPH (Gas only)	TPH Method	TPH (Method	EDB (Method 504.1)	831U (PNA OF PAH) PCRA 8 Metals	Anions (F, Cl	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (300.0)	Grab sample	\$ pt. composite sample	Air Bubbles (Y or N)
9/22/11	0930	WATEL	GW-TBC47(9585)	40ml - 2	HCI + cool	1109	715-1	V							1				1	4	20
9/2/11	6936	WATER	6W-TBE 4'(9586T)	125ml - 1	COOL													V	V		
		<u> </u>																	1		
9/22/11	1150	501L	4PC-5WC2	4622	COOL		-2	\vee		$\sqrt{}$	$\sqrt{}$				<u> </u>]		V	<u>. </u>		
			(95 BET)									_	_		<u>L</u>						
		 					,	_		_			\dashv	+-	_				-		
								-		\dashv		+	+	+	-				+-	-	
						·							T								
`											_				L						
		<u> </u>		<u> </u>		<u> </u>		_						1	L	<u>_</u>					
Date:	Time: 1530	Relinquish	ged by:	Received by:	, 1)	Date 9/	Time	Rer	nark BIL			l (80: LY TO	-	- GR	O &	DRC	ON	LY.			
Date:	Time:	Relinquish	ned by:	Received by:	- Walter	/22/i / Date	/530 Time	1	<u>Jef</u>	Peac	ce, 20	00 Ene	rgy Co							_	
9/23/11	810	1 Ch	Late Wollow Submitted to Hall Environmental may be s	1 David		9/23	<u>'</u>											SCHU			

Date: 04-Oct-11

QA/QC SUMMARY REPORT

Client:

Blagg Engineering

Project:

STATE GC L#1A

Work Order:

1109915

Troject. STATE OC	JUTIA								rk Order: 1109915
Analyte	Result	Units	PQL	SPK Va	a SPK ref	%Rec L	owLimit Hi	ghLimit %RF	PD RPDLimit Qual
Method: EPA Method 300.0: A	Anions							-	
Sample ID: MB-28618		MBLK	•			Batch ID:	28618	Analysis Date	: 9/29/2011 1:14:20 PM
Chloride	ND	mg/Kg	1.5						
Sample ID: LCS-28618		LCS				Batch ID:	28618	Analysis Date	: 9/29/2011 1:31:45 PM
Chloride	13.91	mg/Kg	1.5	15	0	92.7	90	110	
Method: EPA Method 300.0: A	Inions			***	,				
Sample ID: MB		MBLK				Batch (D:	R47990	Analysis Date	: 9/26/2011 12:10:18 PM
Chloride	ND	mg/L	0.50						
Sample ID: LCS		LCS				Batch ID:	R47990	Analysis Date	: 9/26/2011 12:27:42 PM
Chloride	4.823	mg/L	0.50	5	0	96.5	90	110	
Method: EPA Method 418.1: T	PH	MELV				Ratch ID:	20604	Analysis Data	: 9/29/2011
Sample ID: MB-28601		MBLK				Batch ID:	28601	Analysis Date	. 9/29/2011
Petroleum Hydrocarbons, TR	ND	mg/Kg	20			Dotah ID:	00004	Analysis Data	: 9/29/2011
Sample ID: LCS-28601		LCS			_	Batch ID:	28601	Analysis Date	. 9/29/2011
Petroleum Hydrocarbons, TR	100.5	mg/Kg	20	100	0	101	87.8	115	0/00/0044
Sample ID: LCSD-28601	4	LCSD			_	Batch ID:	28601	Analysis Date	
Petroleum Hydrocarbons, TR	103.2	mg/Kg	20	100	0	103	87.8	115 2.6	1 8.04
Method: EPA Method 8015B: I	Diesel Range	Organics							•
Sample ID: MB-28603	1	MBLK				Batch ID:	28603	Analysis Date	9/28/2011 9:54:16 AM
Diesel Range Organics (DRO)	ND	mg/Kg	10						•
Sample ID: LCS-28603	1	LCS				Batch ID:	28603	Analysis Date:	: 9/28/2011 10:28:40 AM
Diesel Range Organics (DRO)	55.22	mg/Kg	10	50	4.175	102	66.7	119	
Method: EPA Method 8015B: 0	Gasoline Ran	iae							
Sample ID: MB-28595		MBLK				Batch ID:	28595	Analysis Date:	9/29/2011 11:45:48 PM
Gasoline Range Organics (GRO)	ND	mg/Kg	5.0						
Sample ID: LCS-28595		LCS				Batch ID:	28595	Analysis Date:	9/29/2011 10:48:10 PM
Gasoline Range Organics (GRO)	28.48	mg/Kg	5.0	25	0	114	86.4	132	
Method: EPA Method 8021B: \									
Sample ID: MR-28595	voiatiles	MRIK				Batch ID:	28595	Analysis Date	9/29/2011 11:45:48 PM
Sample ID: MB-28595		MBLK	0.050			Batch ID:	28595	Analysis Date:	9/29/2011 11:45:48 PM
Benzene	ND	mg/Kg	0.050			Batch ID:	28595	Analysis Date:	9/29/2011 11:45:48 PM
Benzene Toluene	ND ND	mg/Kg mg/Kg	0.050			Batch ID:	28595	Analysis Date:	9/29/2011 11:45:48 PM
Benzene Toluene Ethylbenzene	ND	mg/Kg				Batch ID:	28595	Analysis Date:	: 9/29/2011 11:45:48 PM
Benzene Toluene Ethylbenzene	ND ND ND	mg/Kg mg/Kg mg/Kg	0.050 0.050			Batch ID:	28595 28595	Analysis Date: Analysis Date:	
Benzene Toluene Ethylbenzene Xylenes, Total	ND ND ND	mg/Kg mg/Kg mg/Kg mg/Kg	0.050 0.050	1	0.0141				
Benzene Toluene Ethylbenzene Xylenes, Total Sample ID: LCS-28595	ND ND ND	mg/Kg mg/Kg mg/Kg mg/Kg LCS	0.050 0.050 0.10		0.0141 0.0129	Batch ID:	28595	Analysis Date:	
Benzene Toluene Ethylbenzene Xylenes, Total Sample ID: LCS-28595 Benzene	ND ND ND ND	mg/Kg mg/Kg mg/Kg mg/Kg LCS mg/Kg	0.050 0.050 0.10 0.050	1		Batch ID: 100	28595 83.3	Analysis Date:	

Qualifiers:

E Estimated value

J Analyte detected below quantitation limits

ND Not Detected at the Reporting Limit

H Holding times for preparation or analysis exceeded

NC Non-Chlorinated

R RPD outside accepted recovery limits

Date: 04-Oct-11

QA/QC SUMMARY REPORT

Client:

Blagg Engineering

Project: STATE GC L #1A

Work Order:

1109915

Analyte	Result	Units	PQL	PQL SPK Va SPK ref %Rec LowLimit				ghLimit	%RPD	RPDLimit	Qual
Method: EPA Method 8021B:	Volatiles										
Sample ID: b1		MBLK				Batch ID:	R48017	Analysi	s Date:	9/27/2011 10	0:43:15 AN
Benzene	ND	μg/L	1.0								
Toluene	ND	μg/L	1.0			4					
Ethylbenzene	ND	μg/L	1.0								
Xylenes, Total	ND	μ g/L	2.0								
Sample ID: 100NG BTEX LCS		LCS				Batch ID:	R48017	Analysi	s Date:	9/27/2011	1:08:11 PM
Benzene	20.37	μg/L	1.0	20	0.4978	99,4	80	120			
Toluene	20.64	μg/L	1.0	20	0	103	80	120			
Ethylbenzene	20.66	μg/L	1.0	20	0	103	80	120			
Xylenes, Total	62.09	μg/L	2.0	60	0	103	80	120			

Qualifiers:

E Estimated value

J Analyte detected below quantitation limits

NC Non-Chlorinated

R RPD outside accepted recovery limits

Hall Environmental Analysis Laboratory, Inc.

Sample Receipt Checklist Client Name BLAGG Date Received: 9/23/2011 Work Order Number 1109915 Received by: DAM Sample ID labels checked by: Checklist completed by: Matrix: Carrier name: Greyhound Shipping container/cooler in good condition? No Not Present Custody seals intact on shipping container/cooler? No Not Present Yes Not Shipped Custody seals intact on sample bottles? No N/A Chain of custody present? No Chain of custody signed when relinquished and received? No Chain of custody agrees with sample labels? No Samples in proper container/bottle? No Sample containers intact? No

Yes 🗸

Yes :✓

No

No

Yes 🗸

No

Νo

No

N/A

N/A

Number of preserved

bottles checked for

<2 >12 unless noted

pH:

below.

Water - pH acceptable upon receipt? Yes 💉 Container/Temp Blank temperature? <6° C Acceptable 3.3° If given sufficient time to cool.

No VOA vials submitted

COMMENTS:

Client contacted

Sufficient sample volume for indicated test?

All samples received within holding time?

Water - VOA vials have zero headspace?

Water - Preservation labels on bottle and cap match?

Date contacted: Person contacted

Contacted by:

Regarding:

Comments:

Corrective Action



