<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

OIL CONS. DIV DIST. 3

JAN 0 5 2015

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or  Proposed Alternative Method Permit or Closure Plan Application
Type of action:    Below grade tank registration
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Boyd Gas Com 1A
API Number:3004522132OCD Permit Number:
U/L or Qtr/QtrCSection8Township31NRange10WCounty:San Juan
Center of Proposed Design: Latitude36.917178 Longitude107.909644 NAD: ☐1927 ☒ 1983
Surface Owner:  Federal State Private Tribal Trust or Indian Allotment
2.    Pit: Subsection F, G or J of 19.15.17.11 NMAC    Temporary:   Drilling   Workover   Permanent   Emergency   Cavitation   P&A   Multi-Well Fluid Management   Low Chloride Drilling Fluid   yes   no   Lined   Unlined   Liner type: Thickness   mil   LLDPE   HDPE   PVC   Other     String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.    Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank B    Volume: 95.0   bbl Type of fluid: Produced water
Tank Construction material:Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other _Single walled/double bottomed
Liner type: Thicknessmil
4.

Page 1 of 6

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Alternative Method:

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)  Four foot height, four strands of barbed wire evenly spaced between one and four feet  Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other  Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC  12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Page 2 of 6

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
10. <b>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist:</b> Subsection B of 19.15.17.9 N	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	cuments are
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	cuments are
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  A List of wells with approved application for permit to drill associated with the pit.  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC  Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.  Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Climatological Factors Assessment  Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC  Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC  Quality Control/Quality Assurance Construction and Installation Plan  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan  Emergency Response Plan  Oil Field Waste Stream Characterization  Monitoring and Inspection Plan  Erosion Control Plan  Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	Tuid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached.  □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC  Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC .15.17.11 NMAC
Operator Application Certification:  I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and below.	
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature: Approval Date: 1/28  Title: OCD Permit Number:	/2015
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report. complete this
☐ Closure Completion Date:1/26/2012_	
20. Closure Method:  Waste Excavation and Removal □ On-Site Closure Method □ Alternative Closure Method □ Waste Removal (Closed-lo□ If different from approved plan, please explain.	oop systems only)

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure requires	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Jeff Posse	Date:December 31, 2014
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-94/9

### BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

#### BELOW-GRADE TANK CLOSURE PLAN

Boyd Gas Com 1A BGT Tank B (95 bbl)

API No. 3004522132
Unit Letter C, Section 8, T31N, R10W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

#### **General Closure Plan**

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

  Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
  - Notice is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT, Tank B	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.** 

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.

    Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

### State of New Mexico Energy Minerals and Natural Resources

Form C-141
Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	atio	n and Co	rrective A	ction				
						<b>OPERA</b>	ГOR		Initia	al Report	$\boxtimes$	Final Repor
Name of Co	ompany: B	P				Contact: Jeff Peace						
Address: 20	0 Energy	Court, Farmi	ington, N	M 87401		Telephone 1	No.: 505-326-94	.79				
Facility Nar	ne: Boyd	Gas Com 1A				Facility Typ	e: Natural gas v	vell				
Surface Ow	ner: Privat	te		Mineral O	wner	: Private			API No	. 3004522	132	
				LOCA	TIO	N OF REI	FASE	'				
Unit Letter	Section	Township	Range	Feet from the		h/South Line	Feet from the	East/We	st Line	County: S	an Iuan	)
C	8	31N	10W	1,170	North		1,640	West	St Line	County. S	an saan	
		Latit	ude36	.917178		Longitud	e107.909644					
				NAT	URF	OF REL	EASE					
Type of Rele	ase: none						Release: N/A	1	Volume R	Recovered: N	V/A	
		v grade tank –	ank B		Date and H	lour of Occurrence	e: I	Date and	Hour of Dis	covery:		
Was Immedia	ate Notice (		_			If YES, To	Whom?					
			Yes	No Not Re	quired	I						
By Whom?						Date and H	lour					
Was a Water	course Read					If YES, Vo	lume Impacting t	he Waterc	ourse.			
			Yes 🛚	No								
If a Watercou	irse was Im	pacted, Descri	ibe Fully.*									
				n Taken.* Samplir and chloride belov					removal t	o ensure no	soil im	pacts from
backfilled and	d compacted	d and is still w	vithin the	en.* BGT was rer active well area.								
regulations al public health should their of or the environ	I operators or the envir operations hament. In a	are required to conment. The ave failed to a	acceptance acceptance adequately OCD accep	is true and compled/or file certain rece of a C-141 repoinvestigate and retained for a C-141 repoinvestigate and retained of a C-141 repoints.	elease rt by tl emedia	notifications ar ne NMOCD ma te contamination	nd perform correct arked as "Final Ro on that pose a thre	tive action eport" doe eat to grou	s for rele s not reli nd water	eases which eve the oper , surface wa	may en ator of ter, hur	danger liability man health
							OIL CONS	SERVA	TION	DIVISIO	N	
Signature:	alf 1	ane										
0	700 0					Approved by	Environmental Sp	pecialist:				
Printed Name	: Jeff Peace	2										
Title: Field E	nvironment	al Coordinato	r			Approval Dat	e:	Ex	Expiration Date:			
E-mail Addre	ss: peace.je	effrey@bp.com	n			Conditions of	Approval:		Attached			
Date: Decem	ber 31, 201	4	Pho	ne: 505-326-9479								

<sup>\*</sup> Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, BLO	NEERING, INC. OMFIELD, NM 874	413	API #: 300 TANK ID (if applicble):	)452213 <del>- A &amp;</del> B	
FIELD REPORT: (ci	rcle one): BGT CONFIRMATION / RELE	EASE INVESTIGATION / OTHER:		PAGE #:	<b>1</b> of	1
SITE INFORMATION: QUAD/UNIT: C SEC: 8 TWP: 3		#1A M cnty: SJ st:	NM	DATE STARTED: DATE FINISHED:	01/19/	12
1/4-1/4/FOOTAGE: <b>1,170'N / 1,640'V</b> LEASE#: - PRO		FEDERAL / STATE FEE / ELKHORN ACTOR: MBF - G. CLEA		ENVIRONMENTAL SPECIALIST(S):	JCB	
REFERENCE POINT:  1) 95 BGT (9W/DB) - A	WELL HEAD (W.H.) GPS COO	RD.: 36.91729 X 1		GL EL	EV: 6,42	20'
2) 95 BGT (SW/DB) - B		178 X 107.909644	DISTANCE/BE/	ARING FROM W.H.:	110.5', S8	31.5W
4)	GPS COORD.:			ARING FROM W.H.:		
CATALLET AC BATTA	AIN OF CUSTODY RECORD(S) # OR LAB	IIALL	_		RE	OVM EADING (ppm)
1) SAMPLE ID: 95 BGT (A) 5-pt. @ 6 2) SAMPLE ID: 95 BGT (B) 5-pt. @ 3				<del>015B/8021/B/3</del> 015B/8021/B/3	<del>00.0 (CI)</del>	0.0
SAMPLE ID:      SAMPLE ID:	SAMPLE DATE:  SAMPLE DATE:	SAMPLE TIME: LAB ANAL'  SAMPLE TIME: LAB ANAL'				
SOIL DESCRIPTION:	SOIL TYPE: SAND SILTY SANI					
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY COHE CONSISTENCY (NON COHESIVE SOILS): LOOSE MOISTURE: DRY SLIGHTLY MOIST MOIST / WET / S SAMPLE TYPE: GRAB / COMPOSITE - # OF PTS.  DISCOLORATION/STAINING OBSERVED: YES  ANY AREAS DISPLAYING WETNESS: YES NO EXP	FIRM DENSE / VERY DENSE ATURATED / SUPER SATURATED  5 S NO EXPLANATION -	PLASTICITY (CLAYS): NON PLASTIC / SL DENSITY (COHESIVE CLAYS & HC ODOR DETECTED: YES	SILTS): SOFT	/FIRM/STIFF/VER		
ADDITIONAL COMMENTS: NO APPARENT I	EVIDENCE OF A RELEASE FROM E	EITHER BGT OBSERVED.				
SOIL IMPACT DIMENSION ESTIMATION:  DEPTH TO GROUNDWATER: <a href="#">&lt;501</a> NEARE	NA         ft.         X         NA         ft.           EST WATER SOURCE:         <1,000'			TMATION (Cubic Ya D TPH CLOSURE STI		IA ppm
SITE SKETCH  (95)-B PBGTL T.B. ~ 3' B.G.	⊕ WELL HEAD	PLOT PLAN circle: att	N OWN TIME	CALIB. GAS = 1 12:10 am(pm)  MISCELL VO - N14652 O - 61560 PK - ZSCHWL D - Z2-00690  A Permit date  BET Sidewelle Vis	00 ppm DATE: 01/19 . NOTE 17 .LBGT -C	I-10
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELO NA-NOT APPLICABLE OR NOT AVAILABLE; SW- TRAVEL NOTES: CALLOUT:	W-GRADE TANK LOCATION; SPD = SAMPLE F	POINT DESIGNATION; R.W. = RETAININ	IG WALL;	BGT Sidewalls Vis lagnetic declina	0	

#### **Analytical Report**

Lab Order 1201599

Date Reported: 1/26/2012

### Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 95 BGT (B) 5-pt @3'

Project: Boyd GC 1A

Collection Date: 1/19/2012 12:04:00 PM

Lab ID: 1201599-002

Matrix: SOIL

Received Date: 1/20/2012 9:00:00 AM

Analyses	Result	RL Q	ual Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANGE	ORGANICS				Analyst: JMP
Diesel Range Organics (DRO)	ND	9.8	mg/Kg	1	1/23/2012 4:18:42 PM
Sum: DNOP	111	77.4-131	%REC	1	1/23/2012 4:18:42 PM
EPA METHOD 8015B: GASOLINE RANG	SE .				Analyst: RAA
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	1/23/2012 6:55:47 PM
Surr: BFB	93.3	69.7-121	%REC	1	1/23/2012 6:55:47 PM
EPA METHOD 8021B: VOLATILES					Analyst: RAA
Benzene	ND	0.047	mg/Kg	1	1/23/2012 6:55:47 PM
Toluene	ND	0.047	mg/Kg	1	1/23/2012 6:55:47 PM
Ethylbenzene	ND	0.047	mg/Kg	1	1/23/2012 6:55:47 PM
Xylenes, Total	ND	0.095	mg/Kg	1	1/23/2012 6:55:47 PM
Surr: 4-Bromofluorobenzene	99.7	85.3-139	%REC	1	1/23/2012 6:55:47 PM
EPA METHOD 300.0: ANIONS					Analyst: SRM
Chloride	ND	7.5	mg/Kg	5	1/23/2012 4:32:26 PM
EPA METHOD 418.1: TPH					Analyst: JMP
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	1/23/2012

#### Qualifiers:

- \*/X Value exceeds Maximum Contaminant Level.
  - E Value above quantitation range
- J Analyte detected below quantitation limits
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RL Reporting Detection Limit

### Hall Environmental Analysis Laboratory, Inc.

WO#:

1201599

26-Jan-12

Client:

Blagg Engineering

Project:

Boyd GC 1A

Sample ID: MB-391

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

Batch ID: 391

RunNo: 530

Prep Date: 1/23/2012

Result

SeqNo: 15436

**HighLimit** 

Analysis Date: 1/23/2012

Units: mg/Kg

**RPDLimit** Qual

Analyte Chloride

PQL ND

Sample ID: LCS-391

SampType: LCS

TestCode: EPA Method 300.0: Anions

LowLimit

LowLimit

Client ID: LCSS

Batch ID: 391

PQL

1.5

RunNo: 530

Prep Date: 1/23/2012

Analysis Date: 1/23/2012

14

Result

SPK value SPK Ref Val %REC

0

SPK value SPK Ref Val %REC

SeqNo: 15437

Units: mg/Kg

Analyte

94.1

HighLimit

110

%RPD **RPDLimit** Qual

**RPDLimit** 

Chloride

SampType: MS

TestCode: EPA Method 300.0: Anions

Sample ID: 1201626-002AMS

Client ID: BatchQC

Batch ID: 391

RunNo: 530

Prep Date: 1/23/2012

Analysis Date: 1/23/2012

SeqNo: 15440

40.4

Units: mg/Kg

%RPD

Analyte Chloride

Result

38

SPK value SPK Ref Val

15.00

15.00

15.00

%REC LowLimit HighLimit %RPD 118

Qual

S

Sample ID: 1201626-002AMSD

SampType: MSD

TestCode: EPA Method 300.0: Anions

74.6

Client ID: BatchQC

Batch ID: 391

RunNo: 530

118

Prep Date: 1/23/2012

Analysis Date: 1/23/2012

30

30

SeqNo: 15441

Units: mg/Kg

**RPDLimit** 

Qual S

Analyte Chloride

PQL

42

SPK value SPK Ref Val %REC 31.65

31.65

67.0 74.6

LowLimit

HighLimit

%RPD 10.1

Qualifiers:

Value exceeds Maximum Contaminant Level. \*/X

Value above quantitation range

Analyte detected below quantitation limits RPD outside accepted recovery limits

Analyte detected in the associated Method Blank B

Holding times for preparation or analysis exceeded H

Not Detected at the Reporting Limit Reporting Detection Limit

Page 3 of 8

### Hall Environmental Analysis Laboratory, Inc.

WO#:

1201599

26-Jan-12

Client:

Blagg Engineering

Project:

Boyd GC 1A

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Sample ID: MB-375 Client ID: PB\$

Batch ID: 375

RunNo: 509

Analysis Date: 1/23/2012

SeqNo: 14436

Units: mg/Kg

Analyte

Prep Date: 1/20/2012

Result PQL SPK value SPK Ref Val %REC LowLimit ND 20

HighLimit

**RPDLimit** 

Petroleum Hydrocarbons, TR Sample ID: LCS-375

SampType: LCS

TestCode: EPA Method 418.1: TPH

Client ID:

LCSS

RunNo: 509

Prep Date: 1/20/2012

Batch ID: 375 Analysis Date: 1/23/2012

SeqNo: 14437

Units: mg/Kg

Analyte

Petroleum Hydrocarbons, TR

PQL

20

SPK value SPK Ref Val 100.0 0

%REC LowLimit 101

HighLimit 87.8 115 %RPD **RPDLimit** 

%RPD

Qual

Sample ID: LCSD-375 Client ID: LC\$S02

SampType: LCSD Batch ID: 375

Result

Result

100

100

0

TestCode: EPA Method 418.1: TPH RunNo: 509

Prep Date: 1/20/2012

Analysis Date: 1/23/2012

SeqNo: 14439 %REC

Units: mg/Kg HighLimit

%RPD

**RPDLimit** Qual

Analyte Petroleum Hydrocarbons, TR POL SPK value SPK Ref Val 20

100.0

104

87.8

LowLimit

2.24

8.04

Qualifiers:

R

Value exceeds Maximum Contaminant Level. \*/X

Value above quantitation range E

Analyte detected below quantitation limits J RPD outside accepted recovery limits

B Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded

RL Reporting Detection Limit

Page 4 of 8

Not Detected at the Reporting Limit

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1201599

26-Jan-12

Client:

Blagg Engineering

Project:

Boyd GC 1A

Project:	Boya GC	IA									
Sample ID:	MB-373	SampT	ype: Mi	BLK	Tes	tCode: El	PA Method	8015B: Dies	el Range (	Organics	
Client ID:	PBS	Batch	ID: 37	3	F	RunNo: 517					
Prep Date:	1/20/2012	Analysis Da	ate: 1/	23/2012	8	SeqNo: 1	4910	Units: mg/K	ζg		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range (	Organics (DRO)	ND	10								
Surr: DNOP		10		10.00		104	77.4	131			
Sample ID:	LCS-373	SampTy	ype: LC	S	Tes	Code: El	PA Method	8015B: Diese	el Range C	Organics	
Client ID:	LCSS	Batch	ID: 37	3	F	tunNo: 5	17				
Prep Date:	1/20/2012	Analysis Da	ate: 1/	23/2012	8	eqNo: 1	4913	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range (	Organics (DRO)	43	10	50.00	0	85.5	62.7	139			
Surr: DNOP		6.1		5.000		122	77.4	131			
Sample ID: 1201584-001AMS SampType: MS TestCode: EPA Method 8015B: Diesel Range Organics											
Client ID:	BatchQC	Batch	ID: 37	3	RunNo: 517						
Prep Date:	1/20/2012	Analysis Da	ate: 1/	24/2012	S	eqNo: 1	5102	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range C	Organics (DRO)	38	9.9	49.65	0	75.9	57.2	146			
Surr: DNOP		7.2		4.965		145	77.4	131			S
Sample ID:	1201584-001AMSE	SampTy	ype: MS	D	Test	Code: EF	A Method	8015B: Diese	el Range C	Organics	
Client ID:	BatchQC	Batch	ID: 37:	3	R	unNo: 51	17				
Prep Date:	1/20/2012	Analysis Da	ate: 1/	24/2012	S	eqNo: 1	5200	Units: mg/K	g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range C	Organics (DRO)	43	10	50.00	0	86.9	57.2	146	14.2	26.7	
Surr: DNOP		7.5		5.000		151	77.4	131	0	0	S
Sample ID:	MB-409	SampTy	/pe: ME	BLK	Test	Code: EF	PA Method	8015B: Diese	el Range C	Organics	
Client ID:	PB\$	Batch	ID: 409	9		unNo: 51					
Prep Date:	1/24/2012	Analysis Da	ate: 1/	25/2012	S	eqNo: 16	3212	Units: %RE	С		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP		11		10.00		114	77.4	131			
Sample ID:	LCS-409	SampTy	/pe: LC	S	Test	Code: EF	A Method	8015B: Diese	el Range C	Organics	

#### Qualifiers:

Analyte

Surr: DNOP

Client ID: LCSS

Prep Date: 1/24/2012

\*/X Value exceeds Maximum Contaminant Level.

Batch ID: 409

Result

8.7

Analysis Date: 1/25/2012

E Value above quantitation range

J Analyte detected below quantitation limits

R RPD outside accepted recovery limits

B Analyte detected in the associated Method Blank

LowLimit

Units: %REC

HighLimit

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

RunNo: 517

SPK value SPK Ref Val %REC

5.000

SeqNo: 16213

174

RL Reporting Detection Limit

Page 5 of 8

**RPDLimit** 

Qual

### Hall Environmental Analysis Laboratory, Inc.

WO#:

1201599

26-Jan-12

Client:

Blagg Engineering

Project:

Boyd GC 1A

Sample ID: 1201639-004AMS

SampType: MS

TestCode: EPA Method 8015B: Diesel Range Organics

Client ID: BatchQC

Batch ID: 409

RunNo: 517

Prep Date: 1/24/2012

Analysis Date: 1/25/2012

8.5

Analyte Surr: DNOP Result

SPK value SPK Ref Val %REC

5.118

SeqNo: 16249

166

Units: %REC HighLimit

131

%RPD

**RPDLimit** Qual

S

Qual

Sample ID: 1201639-004AMSD

SampType: MSD

Client ID: BatchQC Batch ID: 409

RunNo: 517

TestCode: EPA Method 8015B: Diesel Range Organics

Prep Date: 1/24/2012

Analysis Date: 1/25/2012

SeqNo: 16251

Units: %REC

%RPD

Analyte

5.040

119

131

Surr: DNOP

6.0

%REC

SPK value SPK Ref Val

77.4

LowLimit

77.4

HighLimit

0

Qualifiers:

\*/X Value exceeds Maximum Contaminant Level

Value above quantitation range

Analyte detected below quantitation limits RPD outside accepted recovery limits

Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded ND Not Detected at the Reporting Limit

RL Reporting Detection Limit

Page 6 of 8

### Hall Environmental Analysis Laboratory, Inc.

WO#:

1201599 26-Jan-12

Client:

Blagg Engineering

Project:

Boyd GC 1A

Sample ID: MB-370

SampType: MBLK

TestCode: EPA Method 8015B: Gasoline Range

Client ID:

PBS

Batch ID: 370

RunNo: 522

69.7

LowLimit

LowLimit

LowLimit

72.4

69.7

86.4

69.7

Prep Date: 1/20/2012

Analysis Date: 1/23/2012

Result

SeqNo: 15530

Units: mg/Kg

Analyte

PQL

5.0

%REC

**HighLimit** 

Qual

Gasoline Range Organics (GRO)

ND 940

1,000

1,000

SPK value SPK Ref Val

93.9

121

**RPDLimit** 

Surr: BFB

SampType: LCS

5.0

TestCode: EPA Method 8015B: Gasoline Range

%RPD

%RPD

Sample ID: LCS-370 Client ID: LCSS

Batch ID: 370

RunNo: 522

%REC

Prep Date: 1/20/2012

Analysis Date: 1/23/2012

0

SeqNo: 15534

Units: mg/Kg

Analyte Gasoline Range Organics (GRO)

SPK value SPK Ref Val 25.00 0

SPK value SPK Ref Val

116 99.4 HighLimit 132

121

**RPDLimit** 

Qual

Qual

Qual

Sun: BFB

Sample ID: 1201584-001AMS SampType: MS

Result

29

990

TestCode: EPA Method 8015B: Gasoline Range

Client ID: BatchQC

Batch ID: 370

RunNo: 522

Prep Date:

1/20/2012

Analysis Date: 1/23/2012

SeqNo: 15535 %REC

Units: mg/Kg

149

HighLimit %RPD **RPDLimit** 

Analyte Gasoline Range Organics (GRO) Sum: BFB

26 4.8 23.97 970 958.8 110 101

121

Sample ID: 1201584-001AMSD

Client ID: BatchQC

SampType: MSD

TestCode: EPA Method 8015B: Gasoline Range RunNo: 522

Prep Date: Analyte

1/20/2012

Batch ID: 370 Analysis Date: 1/23/2012

PQL

4.9

SeqNo: 15536

Units: mg/Kg

HighLimit

%RPD **RPDLimit** 

Gasoline Range Organics (GRO) Sum: BFB

27 990 24.27 970.9

SPK value SPK Ref Val

%REC LowLimit 113

102

86 69.7 149 121

4.02 0

19.2

0

Qualifiers: Value exceeds Maximum Contaminant Level.

Value above quantitation range E

Analyte detected below quantitation limits

Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit

Page 7 of 8

RPD outside accepted recovery limits

Reporting Detection Limit

### Hall Environmental Analysis Laboratory, Inc.

WO#:

1201599

26-Jan-12

Client:

Blagg Engineering

Project:	Boyd GC	21A										
Sample ID:	MB-370	Sampl	ype: MI	BLK	TestCode: EPA Method 8021B: Volatiles							
Client ID:	PBS	Batcl	n ID: 37	0	F	RunNo: \$	522					
Prep Date:	1/20/2012	Analysis E	)ate: 1/	23/2012	8	SeqNo: 1	15549	Units: mg/F	Units: mg/Kg			
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	<b>RPDLimit</b>	Qual	
Benzene		ND	0.050				788	******				
Toluene		ND	0.050									
Ethylbenzene		ND	0.050									
Xylenes, Total		ND	0.10									
Surr: 4-Bron	nofluorobenzene	1.0		1.000		100	85.3	139			***	
Sample ID:	LCS-370	SampT	ype: LC	s	Tes	tCode: E	PA Method	8021B: Vola	tiles			
Client ID:	LCSS	Batcl	1D: 37	0	F	RunNo: 5	522					
Prep Date:	1/20/2012	Analysis D	ate: 1/	23/2012	8	SeqNo: 1	5553	Units: mg/F	(g	78		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	<b>RPDLimit</b>	Qual	
Benzene		0.98	0.050	1.000	0	98.2	83.3	107				
Toluene		1.0	0.050	1.000	0	101	74.3	115				
Ethylbenzene		1.0	0.050	1.000	0	101	80.9	122				
Xylenes, Total		3.0	0.10	3.000	0	101	85.2	123				
Surr: 4-Brom	nofluorobenzene	1.0		1.000		102	85.3	139				
Sample ID:	1201598-001AMS	SampT	ype: MS	3	Tes	tCode: E	PA Method	8021B: Vola	tiles		_	
Client ID:	BatchQC	Batch	ID: 37	0	RunNo: 522							
Prep Date:	1/20/2012	Analysis D	ate: 1/	23/2012	SeqNo: 15554 Units: r			Units: mg/k	(g			
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	<b>RPDLimit</b>	Qual	
Benzene		0.95	0.050	0.9921	0	96.1	67.2	113				
Toluene		0.95	0.050	0.9921	0	95.4	62.1	116				
Ethylbenzene		0.95	0.050	0.9921	0	96.1	67.9	127				
Xylenes, Total		2.8	0.099	2.976	0	95.6	60.6	134				
Surr: 4-Brom	ofluorobenzene	1.0		0.9921		102	85.3	139				
Sample ID:	1201598-001AMSE	SampT	ype: MS	BD	Test	tCode: E	PA Method	8021B: Volat	tiles			
Client ID:	BatchQC	Batch	ID: 370	0	R	lunNo: 5	22					
Prep Date:	1/20/2012	Analysis D	ate: 1/	23/2012	S	SeqNo: 1	5555	Units: mg/k	(g			
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	<b>RPDLimit</b>	Qual	
Benzene		0.91	0.050	0.9990	0	91.2	67.2	113	4.55	14.3		
Toluene		0.93	0.050	0.9990	0	93.0	62.1	116	1.86	15.9		
Ethylbenzene		0.95	0.050	0.9990	0	95.2	67.9	127	0.325	14.4		
Xylenes, Total		2.8	0.10	2.997	0	95.0	60.6	134	0.105	12.6		
Sur: 4-Rmm	offuorobenzene	1.0		0.9990		104	85.3	139	0	0		

#### Qualifiers:

\*/X Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

R RPD outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

RL Reporting Detection Limit

Page 8 of 8



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105 TEL: 505-345-3975 FAX: 505-345-410'

Website: www.hallenvironmental.com

### Sample Log-In Check List

Client Name: BLAGG Work Order Number: 1201599 Logged by: Ashley Gallegos 1/20/2012 9:00:00 AM Completed By: **Ashley Gallegos** 1/20/2012 12:04:53 PM 2012 Reviewed By: Chain of Custody 1. Were seals intact? Yes No Not Present ✓ 2. Is Chain of Custody complete? Yes V No Not Present 3. How was the sample delivered? **FedEx** Log In Yes V No NA 🗌 4. Coolers are present? (see 19. for cooler specific information) NA 🗌 5. Was an attempt made to cool the samples? Yes V No Yes V No NA 🗌 6. Were all samples received at a temperature of >0° C to 6.0°C 7. Sample(s) in proper container(s)? Yes V No 8. Sufficient sample volume for indicated test(s)? Yes V No Yes V No 9. Are samples (except VOA and ONG) properly preserved? Yes No V NA 🗌 10. Was preservative added to bottles? Yes ☐ No ☐ No VOA Vials ✔ 11. Is the headspace in the VOA vials less than 1/4 inch or 6 mm? Yes No V 12. Were any sample containers received broken? # of preserved Yes V No 13. Does paperwork match bottle labels? bottles checked (Note discrepancies on chain of custody) for pH: Yes V No 14. Are matrices correctly identified on Chain of Custody? (<2 or >12 unless noted) Yes V No Adjusted? 15. Is it clear what analyses were requested? Yes V No 16. Were all holding times able to be met? (If no, notify customer for authorization.) Checked by: Special Handling (if applicable) 17. Was client notified of all discrepancies with this order? Yes No NA V Person Notified: Date: By Whom: eMail Phone Fax In Person Regarding: Client Instructions: 18. Additional remarks: 19. Cooler Information Cooler No Temp °C Condition Seal Intact Seal No Seal Date Signed By Good

Client:		HALL ENVIRONMENTAL																
Client: BLAGS ENGWEERWG INC. Standard Rush_		ANALYSIS LABORATORY															-	
Project Name:							v.hal											
Mailing Address: BLWMFIELD, NM 87413 Boyd GC 1A			490	01 H			VE -						7109					
ISP AMERICA Project #:					5-34				•		-345							
Phone #: 505-632-1199							Table 1	No. of Contract	- Contractor	No. of Concession, Name of Street, or other	ues	AND DESCRIPTION OF THE PERSON NAMED IN						
email or Fax#: Project Manager:	1000		(Kl	sel)					)4)									
QA/QC Package: J- BLAGG	J. BLAGO		IS OF	(Gas/Diesel)					4,SC	PCB's								
Standard   Level 4 (Full Validation)		3) 8,	(Gg	3as/					Ъ.	2 PC								
Accreditation Sampler: J. BLAGGO On Ige VI Yes		HAR I	· TPH (Gas only)		8.1)	504.1)	AH)		3,NO <sub>2</sub>	/ 808		2	DE				(N	
□ EDD (Type) Sample Temperature		#	3E+	80,	d 41	d 50	or P/	as	S.	des		00	UPCL)				    }	
Date Time Matrix Sample Request ID Container Type and # Preservative Type		BTEX + WITSE = TMB's (8021)	BTEX + MTBE	TPH Method 8015B	TPH (Method 418.1)	EDB (Method	8310 (PNA or PAH)	RCRA 8 Metals	Anions (F,CI,NO3,NO2,PO4,SO4)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	CHURAD				Air Bubbles (Y or N)	
1/2/2 1150 501L 5-Pt 0.1 402 1 COOL		1		V							ω.	ω.	V				1	
	2	X		1	$\frac{1}{2}$			$\dashv$					X		$\dashv$	$\rightarrow$	$\dashv$	
11 1204 11 95 B67 (B) 1 11 11	-2	X		X	X								X		-		_	
					-									_	_		_	
				-	$\dashv$			-	-	_					-		_	
				_											_			
								_									_	
																$\Box$		
							-											
Date: Time: Relinquished by:  Received by:  Received by:  Received by:  Received by:  Received by:	Muster Labelon 1/9/2012 1365				365 Warkarder: N1465217													
If necessary, samples submitted to Hall Environmental may be subcontracted to other accredited laboratoric	1/20/120900	Mis possibility. Any sub-contracted data will be clearly notated on the analytical report.																

# bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

January 17, 2012

Charles Gaines 16817 US 550 Aztec, NM 87410

#### VIA CERTIFIED MAIL - RETURN RECEIPT REUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: BOYD GAS COM 001A

Dear Mr. Gaines,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about January 17, 2012. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

Surface Coordinator/Business Security Representative

BP America Production Company

#### **BP America Production Company**

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

#### SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

January 19, 2012

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

BOYD GAS COM 001A API 30-045-22132 (M) Section 08 – T31N – R10W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Buddy Shaw BP Environmental Advisor

(505) 320-0401



