District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

JAN 05 2015

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Smyers Com LS 1A
API Number:3004523045OCD Permit Number:
U/L or Qtr/QtrF Section2 Township31N Range11W County:San Juan
Center of Proposed Design: Latitude36.929474 Longitude107.963608 NAD: □1927 ⋈ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2. □ Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: □ Drilling □ Workover □ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined Liner type: Thickness mil □ LLDPE □ HDPE □ PVC □ Other □ String-Reinforced Liner Seams: □ Welded □ Factory □ Other Volume: bbl Dimensions: L x W x D
3.
☑ Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☒ Visible sidewalls only ☐ Other _Single walled/double bottomed
Liner type: Thicknessmil
4.

Form C-144

Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school,	hospital,							
institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet								
Alternate. Please specify								
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)								
☐ Screen ☐ Netting ☐ Other								
Monthly inspections (If netting or screening is not physically feasible)								
7. Signs: Subsection C of 19.15.17.11 NMAC								
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers								
☐ Signed in compliance with 19.15.16.8 NMAC								
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.								
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source							
General siting								
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No							
<u>Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.</u> NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No							
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No							
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No							
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No							
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No							
Below Grade Tanks								
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No							
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)								
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No							
application Visual inspection (certification) of the proposed site; Aerial photo; Satellite image								
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site								
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pit Non-low chloride drilling fluid								
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No							
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Permanent Pit or Multi-Well Fluid Management Pit								
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No							
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	□ Vas □ Na							
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No							
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	NMAC 5.17.9 NMAC							
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC								
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC								
Previously Approved Design (attach copy of design) API Number: or Permit Number:								

Form C-144 Oil Conservation Division Page 3 of 6

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are						
Proposed Closure: 19.15.17.13 NMAC							
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.							
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit						
Proposed Closure Method: Waste Excavation and Removal							
☐ Waste Removal (Closed-loop systems only)☐ On-site Closure Method (Only for temporary pits and closed-loop systems)							
☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method							
14.							
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC							
15. Siting Criteria (recording on site cleaner methods only), 10.15.17.10 NMAC							
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.							
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA						
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA						
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No NA NA							
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No						
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image							
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site							
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No						
Within 300 feet of a wetland.							
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance							

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef
Name (Print): Title:	
Signature: Date:	
e-mail address:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 1/25 Title: OCD Permit Number:	12015
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:7/1/2011	the closure report. complete this
^{20.} Closure Method: ☑ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-loc ☐ If different from approved plan, please explain.	op systems only)
21.	

22.								
Operator Closure Certification:								
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.								
Name (Print):Jeff Peace	Title: Field Environmental Coordinator							
Signature: Signature:	Date:December 31, 2014							
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479							

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Smyers Com LS 1A API No. 3004523045 Unit Letter F, Section 2, T31N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	26

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action

						OPERATOR Init			al Report	\boxtimes	Final Report	
Name of Company: BP					(Contact: Jeff Peace					•	
Address: 200 Energy Court, Farmington, NM 87401						Telephone No.: 505-326-9479						
Facility Name: Smyers Com LS 1A						Facility Type: Natural gas well						
Surface Ow	Surface Owner: State Mineral Owner								API No	. 30045230)45	
				LOCA	TION	OF RE	LEASE					
Unit Letter F	Section 2	Township 31N	Range 11W	Feet from the 1,775	North/South Line Feet from the East/West Line County: San Juan North 1,455 West							
	Latitude36.929474Longitude107.963608											
				NAT	URE	OF REL	EASE					
Type of Rele						Volume of	Release: N/A		Volume F	Recovered: N	J/A	
		v grade tank –	95 bbl, Ta	ank A			lour of Occurrenc	e:	Date and	Hour of Dis	covery:	
Was Immedia	ate Notice (Yes	No Not Re	equired	If YES, To	Whom?					
By Whom?						Date and H	lour					
Was a Watero	course Read	ched?	Yes 🗵	No		If YES, Vo	lume Impacting t	he Wate	rcourse.			
If a Watercou	rse was Im	pacted, Descri	be Fully.*									
							the BGT was dor s results are attach		g removal t	to ensure no	soil im	pacts from
				en.* BGT was reactive well area.	moved a	nd the area u	nderneath the BG	T was sa	ampled. Th	he area unde	r the B	GT was
regulations al public health should their o or the enviror	l operators or the envir perations h nment. In a	are required to conment. The ave failed to a	report an acceptance dequately CD accep	d/or file certain re e of a C-141 repo investigate and re tance of a C-141	elease no rt by the emediate	tifications ar NMOCD m contaminati	knowledge and und perform correct arked as "Final Reson that pose a three the operator of r	tive action eport" do eat to gro	ons for rele oes not reli ound water	eases which eve the oper , surface wa	may en ator of ter, hur	danger liability nan health
Signature:	eff (Pace					OIL CONS	SERV.	ATION	DIVISIO	N	
Printed Name	: Jeff Peace	2			A	Approved by	Environmental Sp	pecialist	:			
Title: Field E	nvironment	al Coordinato			A	Approval Dat	e:	Е	Expiration I	Date:		
E-mail Addre	ss: peace.je	ffrey@bp.com	1			Conditions of Approval:						
Date: Decem	ber 31, 201	4	Pho	ne: 505-326-9479								

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG ENG P.O. BOX 87, BLO	INEERING, INC. OMFIELD, NM 87	413	API #: 300	4523	045
	(505)	632-1199		TANK ID (if applic	cble):	A & B
FIELD REPORT:	(circle one): BGT CONFIRMATION REL	EASE INVESTIGATION OTHER:]	PAGE #:	1 of	1
SITE INFORMATION	SITE NAME: SMYERS	COM LS #1A		DATE STARTED:	06/1	1/11
QUAD/UNIT: F SEC: 2 TWP:	31N RNG: 11W PM: NN	CNTY: SJ ST: N	/	DATE FINISHED:		
		FEDERAL STATE FEE ELKHORN BP- J. GONZA		ENVIRONMENTAL SPECIALIST(S):	N	JV
REFERENCE POINT				82 GLELE	V.:	5,997'
1) - 21 BCT (SW/DB) - B		208 X 107.963451		ARING FROM W.H.:	731,	,
2) 95 BGT (SW/DB) - A	GPS COORD.: 36.929	9474 X 107.963608	DISTANCE/BE	ARING FROM W.H.:	69',	N16E
3)	GPS COORD.:		DISTANCE/BE	ARING FROM W.H.:		
4)	GPS COORD.:		DISTANCE/BE	ARING FROM W.H.:		0.44
LAB INFORMATION:						OVM READING (ppm)
1) SAMPLE ID: 5 PC - TB @ 6.5'					0 (CI)	NA
2) SAMPLE ID:						
3) SAMPLEID:						
	SAMPLE DATE:	SAMPLE TIME: LAB ANA	LYSIS:			
SOIL DESCRIPTION SOIL COLOR: DARK YE COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY	LOWISH BROWN	AND / SILT (SILTY CLAY) C PLASTICITY (CLAYS): NON PLASTIC			ASTIC HIGH	HLY PLASTIC
CONSISTENCY (NON COHESIVE SOILS) MOISTURE: DRY SLIGHTLY MOIST / MOIST SAMPLE TYPE: GRAB COMPOSITE DISCOLORATION/STAINING OBSERV	WET/SATURATED/SUPER SATURATED # OF PTS5		S & SILTS): SC	FT FIRM / STIFF V	ERY STIF	
ANY AREAS DISPLAYING WETNESS: YES /						
ADDITIONAL COMMENTS: NO APPA	ARENT EVIDENCE OF A RELEASE OBS	SERVED FROM BGT.				
EXCAVATION DIMENSIONS (if applicated DEPTH TO GROUNDWATER: _>100' N		ft. X NA ft. AREST SURFACE WATER: >1,		excavated (if applicable D TPH CLOSURE STD:		NA 00 PPM
SITE SKETCH		PLOT PLAN circle: atta	ached	CALIB. READ. =	A ppm	RF = 0.52
WOODEN →	XXX		♦ OVM	CALIB. GAS = NA		11 - 0.02
R.W.	X	(21) PBGTL	TIME	NA am/pm D	ATE:	NA
		T.B. ~ 7' B.G.		MISCELL.	NOT	ES
P	(95) BGTL SEPARATOR	D.G.	V	VO: N1374	902	
Т.	B. ~ 6' B.G.			O: 47058		
	/	WOODEN R.W.	P	K: ZAND	ECALS	SL
WELL _		/	-			
HEAD $^{\oplus}$	PROD.) / PEDM				
	TANK	→ BERM				
		\checkmark	TAN ID			
		X - S).P.U.I —	BGT SIDEWALLS VIS		N / NA
T.B. = TANK BOTTOM; PBGTL = PREVIOUS	VATION DEPRESSION; B.G. = BELOW GRADE; B = BELOW-GRADE TANK LOCATION; SPD = SAMPLE 	POINT DESIGNATION; R.W. = RETAINI	NG WALL;	agnetic declination		O°E
TRAVEL NOTES: CALLOUT:	06/21/11 - MORN.	ONSITE: 06/22/11 -	NOON (SO	CHED.)		

Hall Environmental Analysis Laboratory, Inc.

Date: 01-Jul-11

CLIENT:

Blagg Engineering

Client Sample ID: SPC-TB @ 6.5' (95 BGT)

Analytical Report

Lab Order:

Project:

1106975

Collection Date: 6/22/2011 11:45:00 AM

Lab ID:

SMYERS COM LS #1A 1106975-01

Date Received: 6/23/2011

Matrix: SOIL

Analyses	Result	PQL	Qual	Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANGE	ORGANICS					Analyst: JB
Diesel Range Organics (DRO)	ND	10		mg/Kg	1	6/24/2011 10:08:52 AM
Surr: DNOP	106	73.4-123		%REC	1	6/24/2011 10:08:52 AM
EPA METHOD 8015B: GASOLINE RAI	NGE					Analyst: RAA
Gasoline Range Organics (GRO)	ND	5.0		mg/Kg	1	6/25/2011 4:26:05 AM
Surr: BFB	102	75.2-136		%REC	1	6/25/2011 4:26:05 AM
EPA METHOD 8021B: VOLATILES						Analyst: RAA
Benzene	ND	0.050		mg/Kg	1	6/25/2011 4:26:05 AM
Toluene	ND	0.050		mg/Kg	1	6/25/2011 4:26:05 AM
Ethylbenzene	ND	0.050		mg/Kg	1	6/25/2011 4:26:05 AM
Xylenes, Total	ND	0.10		mg/Kg	1	6/25/2011 4:26:05 AM
Surr: 4-Bromofluorobenzene	89.9	92-130	S	%REC	1	6/25/2011 4:26:05 AM
EPA METHOD 300.0: ANIONS						Analyst: SRM
Chloride	26	7.5		mg/Kg	5	6/29/2011 2:02:07 PM
EPA METHOD 418.1: TPH						Analyst: JB
Petroleum Hydrocarbons, TR	ND	20		mg/Kg	1	6/30/2011

Qualifiers:

- Value exceeds Maximum Contaminant Level
- Estimated value E
- Analyte detected below quantitation limits
- NC Non-Chlorinated
- PQL Practical Quantitation Limit

- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded
- MCL Maximum Contaminant Level
- ND Not Detected at the Reporting Limit
 - Spike recovery outside accepted recovery limits

Date: 01-Jul-11

QA/QC SUMMARY REPORT

Client:

Blagg Engineering

Project:

SMYERS COM LS #1A

Work Order:

Project: SMYERS C	COM LS #1.	A							Work	Order:	1106975
Analyte	Result	Units	PQL	SPK Va	SPK ref	%Rec L	owLimit Hi	ghLimit	%RPD	RPDLimit	Qual
Method: EPA Method 300.0: A	nions										
Sample ID: MB-27417		MBLK				Batch ID:	27417	Analysi	s Date:	6/29/2011 1	2:00:12 PN
Chloride	ND	mg/Kg	1.5								
Sample ID: LCS-27417		LCS			*	Batch ID:	27417	Analysi	s Date:	6/29/2011 1	2:1 7 :37 PN
Chloride	14.46	mg/Kg	1.5	15	0	96.4	90	110			
Method: EPA Method 418.1: T	PH										
Sample ID: MB-27432		MBLK				Batch ID:	27.432	Analysi	s Date:		6/30/201
Petroleum Hydrocarbons, TR	ND	mg/Kg	20								
Sample ID: LCS-27432		LCS				Batch ID:	27432	Analysi	s Date:		6/30/201
Petroleum Hydrocarbons, TR	105.8	mg/Kg	20	100	0	106	81.4	118			
Sample ID: LCSD-27432	105.0	LÇSD	20	100	O	Batch ID:	27432	Analysi	s Dato:		6/30/201
	2111										0/30/201
Petroleum Hydrocarbons, TR	111.4	mg/Kg	20	100	0	111	81.4	118	5.14	8.58	
Method: EPA Method 8015B: I	Diesel Range	Organics									
Sample ID: MB-27330		MBLK				Batch ID:	27330	Analysi	s Date:	6/24/2011	7:52:17 AN
Diesel Range Organics (DRO)	ND	mg/Kg	10								
Sample ID: LCS-27330		LCS				Batch ID:	27330	Analysi	s Date:	6/24/2011 8	3:26:26 AN
Diesel Range Organics (DRO)	48.30	mg/Kg	10	50	0	96.6	66.7	119			
Sample ID: LCSD-27330	40.30	LCSD	10	50	U	Batch ID:	27330	Analysi	e Date:	6/24/2011 9	3.00.34 AA
Diesel Range Organics (DRO)	49.56	mg/Kg	10	50	0	99.1	66.7	119	2.59	18.9	7.00.54 AIV
	Aurilla		- 10			00.1	00.1	110	2.00	10.0	
Method: EPA Method 8015B: 0	Basoline Rar	-				D 1 1 1D			-	0.10.1.10.0.1.1.1	
Sample ID: MB-27326		MBLK				Batch ID:	27326	Analysi	s Date:	6/24/2011 8	3:42:14 PN
Gasoline Range Organics (GRO)	ND	mg/Kg	5.0								
Sample ID: MB-27326		MBLK				Batch ID:	27326	Analysis	s Date:	6/24/2011 10	0:55:38 PN
Gasoline Range Organics (GRO)	ND	mg/Kg	5.0								
Sample ID: LCS-27326		LCS				Batch ID:	27326	Analysis	s Date:	6/24/2011 7	1:15:37 PM
Gasoline Range Organics (GRO)	27.48	mg/Kg	5.0	25	0	110	88.8	124			
Sample ID: LCS-27326		LCS				Batch ID:	27326	Analysis	s Date:	6/25/2011 5	:26:04 AN
Gasoline Range Organics (GRO)	28.84	mg/Kg	5.0	25	0	115	88.8	124			
					27227						
Method: EPA Method 8021B: V	olatiles	MOLK				Datah ID.	27200	Analysis	Data	610410044 40	
Sample ID: MB-27326		MBLK				Batch ID:	27326	Analysis	s Date:	6/24/2011 10):55:38 PN
Benzene	ND	mg/Kg	0.050								
oluene	ND ·	mg/Kg	0.050								
Ethylbenzene	ND	mg/Kg	0.050								
(ylenes, Total	ND	mg/Kg	0.10			m				n/n=/=- / : :	
Sample ID: LCS-27326		LCS				Batch ID:	27326	Analysis	s Date:	6/25/2011 4	:55:58 AN
	4.040	mg/Kg	0.050	1	0.0053	101	83.3	107			
enzene	1.013										
	0.9280	mg/Kg	0.050	1	0	92.8	74.3	115			
Benzene Foluene Ethylbenzene			0.050 0.050	1	0	92.8 98.9	74.3 80.9	115 122			

0		R:	n.	MO
``	KIN	641	ш	LS

E Estimated value

R RPD outside accepted recovery limits

J Analyte detected below quantitation limits

ND Not Detected at the Reporting Limit

H Holding times for preparation or analysis exceeded

NC Non-Chlorinated

Hall Environmental Analysis Laboratory, Inc.

Sample Receipt Checklist

Client Name BLAGG		Date Receive	d:	6/23/2011
Work Order Number 1106975		Received by	: AT	1
Checklist completed by:	06/23 Date	Sample ID la	abels checked by:	Initials
Matrix: Carrier name	e: <u>Greyhound</u>			
Shipping container/cooler in good condition?	Yes 🗸	No 🗌	Not Present	
Custody seals intact on shipping container/cooler?	Yes 🗸	No 🗆	Not Present	Not Shipped
Custody seals intact on sample bottles?	Yes	No 🗌	N/A	
Chain of custody present?	Yes 🗸	No 🗆		
Chain of custody signed when relinquished and received?	Yes 🗸	No 🗌		
Chain of custody agrees with sample labels?	Yes 🗸	No 🗌		
Samples in proper container/bottle?	Yes 🗸	No 🗔		
Sample containers intact?	Yes 🗸	No 🗌		
Sufficient sample volume for indicated test?	Yes 🗸	No 🗌		
All samples received within holding time?	Yes 🗸	No 🗌		Number of preserved
Water - VOA vials have zero headspace? No VOA vials sub	omitted 🗸	Yes	No 🗌	bottles checked for pH:
Water - Preservation labels on bottle and cap match?	Yes	No 🗆	N/A	
Water - pH acceptable upon receipt?	Yes	No 🗌	N/A	<2 >12 unless noted below.
Container/Temp Blank temperature?	1.7°	<6° C Acceptable		Delow.
COMMENTS:		If given sufficient	time to cool.	
Client contacted Date contacted:		Pers	on contacted	
Contacted by: Regarding:	(1)			
Contacted by. Regarding.	.,,,			.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Comments:				
		1.00		1.00
		•••		· Aller
Corrective Action				•

Chain-of-Custody Record		Turn-Around Time:			HALL ENVIRONMENTAL																
Client: BLAGG ENGR. / BP AMERICA		✓ Standard ☐ Rush			ANALYSIS LABORATORY																
	Project Name:			www.hallenvironmental.com																	
Mailing Address: P.O. BOX 87		SMYERS COM LS # 1A			4901 Hawkins NE - Albuquerque, NM 87109																
BLOOMFIELD, NM 87413		Project #:			Tel. 505-345-3975 Fax 505-345-4107																
Phone #: (505) 632-1199										Α	naly	sis	Req	ues	t				1		
email or Fax#:		Project Manager:								1		504)						-			
QA/QC Pa			Level 4 (Full Validation)		NELSON VE	LEZ	VB's (8021B)	+ TPH (Gas only)	/Diesel					P04,	PCB's					_	ם
Accredita				Sampler:	NELSON VE	Marine Harris (M. Wilson Cherry Larry of Oracle (Marine Andrea	36	(Ga	(Ga				1	N02,	382 F					- Const	Sample N)
□ NELA		□ Other_		On ice	⊠Yes	□ No L / U	ŧ	-TP	015E	118.1	504.1	AH)		103,	8/8		(A)			5	or N
□ EDD (Type)			Sample Temp	erature:	H L	101	LBE +	od 8	pou	pou	York	etals	C, N	icide	(A)	J-VC	300.0		commocito	S (Y
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL No.	BTEX +-NATO	BTEX + MTBE	TPH Method 8015B (Gas/Diesel)	TPH (Method 418.1)	EDB (Method 504.1)	8310 (PNA or PAH)	RCRA 8 Metals	Anions (F, Cl, NO3,	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	Chloride (300.0)		7	ir Bu
6/22/11	1145	SOIL	5PC-TB @ 6.5' (95 BGT)	4 oz 1	Cool	-1	٧	8	٧	٧	Ш	8	Ž.	4	8	.00	80	٧		1	
				-																	
							L.												\perp	1	
																			\perp	_	
																				_	\perp
							_													1	
							-													\perp	
							-	-												\bot	4
Date	Time:	Relinquish	ad but	Paceived by:		Data Timo	Dor			TDU	/00	14 5 5	2)	CDC	10	DRC	101	IIV			
Date: 6/22/11	1530	70	Mu VIL	Received by: Date Time			BILL DIRECTLY TO BP:														
Date:	Time:	Relinquish	ed by:	Received by:	Received by: Date Time			Jeff Peace, 200 Energy Court, Farmington, NM 87401 Work Order: N1374902 Paykey: ZANDECALSL													
rugh	If necessa	y, samples s	ubmitted to Hall Environmental may be	subcontracted to other	accredited laboratorie	es. This serves as notice of	of this							will be	dearl						



