<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-144 Revised June 6, 2013 For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
Dulla Proposed Alter	Pit, Below-Grade Tank, or	lan Application
12499 Proposed Altern	native Method Permit or Closure P	OIL CONS. DIV DIST. 3
$\frac{1}{\sqrt{5-29182}} \xrightarrow{\square Permit o} \\ \boxed{\square Modification} \\ \square Modific$	f a pit or proposed alternative method of a pit, below-grade tank, or proposed alternati ation to an existing permit/or registration	ve method DEC 2 3 2014
or proposed alternative metho	plan only submitted for an existing permitted or d	non-permitted pit, below-grade tank,
	application (Form C-144) per individual pit, below-	grade tank or alternative request
Please be advised that approval of this request does not r environment. Nor does approval relieve the operator of	relieve the operator of liability should operations result in	pollution of surface water, ground water or the
1. Operator: BP America Production Company	OGRID #:7	78
	NM 87401	
	OCD Permit Number:	
	Township32NRange9WC	
	5504Longitude107.797858_	NAD: ∐1927 ⊠ 1983
Surface Owner: 🛛 Federal 🗌 State 🗌 Private 🗌	Iribal Irust or Indian Allotment	
^{2.} Pit: Subsection F, G or J of 19.15.17.11 NMA	C	
Temporary: Drilling Workover		
Permanent Emergency Cavitation P&	A 🗌 Multi-Well Fluid Management Lo	w Chloride Drilling Fluid 🗌 yes 🗌 no
Lined Unlined Liner type: Thickness	mil LLDPE HDPE PVC Ott	ner
String-Reinforced		
Liner Seams: Welded Factory Other	Volume:bbl	Dimensions: L x W x D
3.		
Below-grade tank: Subsection I of 19.15.17.1	1 NMAC Tank B	
Volume:95.0bbl Type 0	of fluid:Produced water	
Tank Construction material:Steel		
Secondary containment with leak detection	Visible sidewalls, liner, 6-inch lift and automatic ov	erflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewal	Is only \square Other _Double walled/double botter	omed; side walls not visible
Liner type: Thicknessmil	HDPE PVC Other	
4		
Alternative Method:		

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

×.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (*Required if located within 1000 feet of a permanent residence, school, hospital, institution or church*)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify

L

5

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting	
<u>Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.</u> - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	Yes No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	Yes No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	Yes No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Permanent Pit or Multi-Well Fluid Management Pit	
 Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
^{10.} <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 N <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.</i>	
 Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. 	
Previously Approved Design (attach copy of design) API Number: or Permit Number: _	
^{11.} <u>Multi-Well Fluid Management Pit Checklist</u> : Subsection B of 19.15.17.9 NMAC <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.</i>	cuments are
 Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC 	.15.17.9 NMAC
 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number: 	

п.		
	 Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Remergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	documents are
	13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
	 Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	
	^{15.} Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
	Ground water is less than 25 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
	 Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ Yes □ No □ NA
	 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA
	 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
	 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
	 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
	Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
	Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
	Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	
	Form C-144 Oil Conservation Division Page 4 o	f 6

r 1

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geology Society; Topographic map 	logical 🗌 Yes 🗌 No
Within a 100-year floodplain.	
- FEMA map	Yes No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC	of 19.15.17.11 NMAC nents of 19.15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowled	dge and belief.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. <u>OCD Approva</u> l: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attac	hment)
OCD Representative Signature: Approval Date:	1/28/2015
Title: Compliance office OCD Permit Number:	./ • • •
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC	
<i>Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and</i> <i>The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Plasection of the form until an approved closure plan has been obtained and the closure activities have been completed.</i>	ease do not complete this
Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Pla section of the form until an approved closure plan has been obtained and the closure activities have been completed.	/7/2014
Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Pla section of the form until an approved closure plan has been obtained and the closure activities have been completed.	ease do not complete this /7/2014

t, e

Operator Closure Certification:

22.

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print): Jeff Peace

Soft Peace Signature:

Title: Field Environmental Coordinator_____

Date:	December	23,	2014	

e-mail address:__peace.jeffrey@bp.com_

Telephone: __(505) 326-9479_

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Arnaud A 1 BGT Tank B (95 bbl)</u> <u>API No. 3004528182</u> <u>Unit Letter H, Section 17, T32N, R9W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

4

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. **Notice is attached.**
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and BTEX and chloride levels were below the stated limits. Sampling data is attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.

3

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

*

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr.

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

1220 S. St. Fran	ncis Dr., Santa	a Fe, NM 8750	5			e, NM 875					
			Rele	ase Notifi	catior	and Co	orrective A	ction			
						OPERA	ГOR	🗌 Init	ial Report	\boxtimes	Final Repo
Name of Co						Contact: Jef					
		Court, Farm	ington, N	M 87401		A	No.: 505-326-94				
Facility Nat	me: Arnau	dA1				Facility Typ	e: Natural gas v	well			
Surface Ow	mer: Feder	al		Mineral (Owner:]	Federal		API N	o. 3004528	182	
				LOCA	ATIO	N OF RE	LEASE				
Unit Letter H	Section 17	Township 32N	Range 9W	Feet from the 1,850	North/ North	South Line	Feet from the 1,090	East/West Line East	County: S	an Juan	1
		Latit	ude_36.	986504		Longitude	e107.797858		-		
				NAT	TURE	OF REL	EASE				
Type of Rele							Release: N/A		Recovered: 1		
Source of Re	lease: belov	v grade tank -	- 95 bbl, Ta	ank B		Date and H N/A	Iour of Occurrence	ce: Date and	d Hour of Dis	covery:	: N/A
Was Immedia	ate Notice (Yes	No 🛛 Not R	equired	If YES, To	Whom?				
By Whom?						Date and H					
Was a Water	course Reac		Yes 🛛	No		If YES, Vo	olume Impacting t	the Watercourse.			
the BGT. So	il analysis r	esulted in TP	H, BTEX a	and chlorides belo	ow stand	ards. Analy	sis results are atta				
				en.* BGT was re ctive well area.	moved a	nd the area u	nderneath the BG	T was sampled. ´	The area unde	er the B	GT was
regulations al public health should their o or the enviror	Il operators or the envir operations h nment. In a	are required t onment. The ave failed to a	o report an acceptanc adequately CD accep	d/or file certain r e of a C-141 repo investigate and r	elease no ort by the emediate	otifications and NMOCD m e contaminati	nd perform correct arked as "Final R on that pose a thr	nderstand that put tive actions for re eport" does not re eat to ground wate responsibility for	leases which lieve the oper er, surface wa	may en rator of iter, hui	danger liability nan health
(0.0	D					OIL CON	SERVATION	DIVISIO	DN	
Signature:	fb	Pear				Approved by	Environmental S	pecialist.			
Printed Name	e: Jeff Peace	•				-PP-Cred Of		F - 340000			
Fitle: Field E	nvironment	al Coordinato	r		1	Approval Dat	e:	Expiration	Date:		
E-mail Addre	ess: peace.je	ffrey@bp.com	n		(Conditions of	Approval:		Attached		
Date: Decem	ber 23, 20	14	Pho	ne: 505-326-947	9						

* Attach Additional Sheets If Necessary

2

+

4

BP BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199 API #: 30045281 TANK ID (ff applicble): FEELD REPORT: (circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER: PAGE #: 1 of SITE INFORMATION: SITE NAME: ARNAUD A #1 DATE STARTED: QUAD/UNIT: H SEC: 17 TWP: 32N RNG: 9W PM: NM CNTY: SJ ST: NM DATE STARTED: 11/04 1/4 -1/4/FOOTAGE: 1,850'N / 1,090'E SE/NE LEASE TYPE: FEDERAL/ STATE / FEE / INDIAN ENVIRONMENTAL REFERENCE POINT: WELL HEAD (W.H.) GPS COORD: 36.98667 X 107.79761 GLELEV: 6,5 1) 95 BGT (DW/DB) - A GPS COORD: 36.986504 X 107.797858 DISTANCE/BEARING FROM W.H: 96', SI 3) GPS COORD: GPS COORD: 0SA696504 X 107.797858 DISTANCE/BEARING FROM W.H: 96', SI 3) GPS COORD: GPS COORD: DISTANCE/BEARING FROM W.H: 96', SI 4) GPS COORD: DISTANCE/BEARING FROM W.H: 96', SI 3) GPS COORD: DISTANCE/BEARING FROM W.H: 96', SI 4) GPS COORD: DISTANCE/BEARING FROM W.H: 96', SI 3) GPS COORD: DISTANCE/BEARING FROM W.H: 96', SI	3 1 /14
CLIENT: DT F.O. BOX 87, BECONNITIEED, NW 87413 TANK ID (if applicble): TANK ID (if	3 1 /14
(505) 632-1199 (if applicble):	1 /14
FIELD KEPUKI: PAGE #: _1 of SITE INFORMATION: SITE NAME: ARNAUD A #1 QUAD/UNIT: H SEC: 17 TWP: 32N RNG: 9W PM: NM CNTY: SJ ST: NM DATE STARTED: _11/04 1/4 -1/4/FOOTAGE: 1,850'N / 1,090'E SE/NE LEASE TYPE: FEDERAL/STATE / FEE / INDIAN 1/4 -1/4/FOOTAGE: 1,850'N / 1,090'E SE/NE LEASE TYPE: FEDERAL/STATE / FEE / INDIAN ENTRIKE 1/4 -1/4/FOOTAGE: 1,850'N / 1,090'E SE/NE LEASE TYPE: FEDERAL/STATE / FEE / INDIAN ENTROMENTAL STRIKE STRIKE STRIKE STRIKE ENTROMENTAL SPECIALIST(S): NJ REFERENCE POINT: WELL HEAD (W.H.) GPS COORD: 36.98667 X 107.79761 GL ELEV: 6,9 1) 95 BGT (DW/DB) - A GPS COORD: 36.986504 X 107.797858 DISTANCE/BEARING FROM W.H.: 96', SE 3) GPS COORD: GPS COORD: 36.986504 X 107.797858 DISTANCE/BEARING FROM W.H.: 96', SE 3) GPS COORD: GPS COORD: DISTANCE/BEARING FROM W.H.: 96', SE 4) GPS COORD: DISTANCE/BEARING FROM W.H.: GPS', SE 3) GPS COORD: DISTANCE/BEARING FROM W.H.: GPS', SE 4) GPS COORD: DISTANCE/BEARING FROM W.H.: GPS',	
QUAD/UNIT: H SEC: 17 TWP: 32N RNG: 9W PM: NM CNTY: SJ ST: NM DATE FINISHED: Internished: Internishe	
QUAD/UNIT: H SEC: 17 TWP: 32N RNG: 9W PM: NM CNTY: SJ ST: NM DATE FINISHED:	/
LEASE #: SF078513 PROD. FORMATION: FT CONTRACTOR: MBF - B. SCHUMAN CINITION INTEL NJ REFERENCE POINT: WELL HEAD (W.H.) GPS COORD.: 36.98667 X 107.79761 GL ELEV.: 6,5 1) 95 BGT (SW/DB) - A GPS COORD.: 36.986504 X 107.797339 DISTANCE/BEARING FROM WH.: 104', C 2) 95 BGT (DW/DB) - B GPS COORD.: 36.986504 X 107.797858 DISTANCE/BEARING FROM WH.: 96', SE 3) GPS COORD.: GPS COORD.: DISTANCE/BEARING FROM WH.: 96', SE 4) GPS COORD.: DISTANCE/BEARING FROM WH.: 96', SE SAMPLING DATA: CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL	/
LEASE #: SF078513 PROD. FORMATION: FT CONTRACTOR: STRIKE MBF - B. SCHUMAN SPECIALIST(S): NJ REFERENCE POINT: WELL HEAD (W.H.) GPS COORD.: 36.98667 X 107.79761 GL ELEV.: 6,9 1)	/
1) -95 BGT (SW/DB) - A GPS COORD.: 36.98645 X 107.797339 DISTANCE/BEARING FROM WH.: 104', C 2) 95 BGT (DW/DB) - B GPS COORD.: 36.986504 X 107.797858 DISTANCE/BEARING FROM WH.: 96', S4 3)	
2) 95 BGT (DW/DB) - B GPS COORD.: 36.986504 X 107.797858 DISTANCE/BEARING FROM WH.: 96', S' 3) GPS COORD.: DISTANCE/BEARING FROM WH.: 96', S' 4) GPS COORD.: DISTANCE/BEARING FROM WH.: 96', S' SAMPLING DATA: CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL	36'
3) GPS COORD.: DISTANCE/BEARING FROM WH.: 4) GPS COORD.: DISTANCE/BEARING FROM WH.: SAMPLING DATA: CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL	44E -
4) GPS COORD.: DISTANCE/BEARING FROM WH.: SAMPLING DATA: CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL	5W
SAMPLING DATA: CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL	
1) SAMPLE ID:	OVM READING (ppm)
	NA
2) SAMPLE ID: 5 PC-TB @ 5' (95) - B SAMPLE DATE: 11/04/14 SAMPLE TIME: 1215 LAB ANALYSIS: 418.1/8021B/300.0 (CI)	NA
3) SAMPLE ID:	
4) SAMPLE ID:	
SOIL DESCRIPTION: SOIL TYPE: SAND (SILTY SAND) / SILT (SILTY CLAY) CLAY / GRAVEL (OTHER BEDROCK (SANDSTONE)	
SOIL COLOR: PALE YELLOWISH BROWN PLASTICITY (CLAYS): NON PLASTIC SLIGHTLY PLASTIC COHESIVE MEDIUM PLASTIC / HIGHLY	PLASTIC
COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE) COHESIVE / HIGHLY COHESIVE DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD	
CONSISTENCY (NON COHESIVE SOILS): LOOSE FIRM DENSE / VERY DENSE HC ODOR DETECTED: YES NO EXPLANATION	
SAMPLE TYPE: GRAB (COMPOSITE) # OF PTS. 5 ANY AREAS DISPLAYING WETNESS: YES NO EXPLANATION -	
DISCOLORATION/STAINING OBSERVED: YES NO EXPLANATION -	
SITE OBSERVATIONS: LOST INTEGRITY OF EQUIPMENT: YES NO EXPLANATION -	
APPARENT EVIDENCE OF A RELEASE OBSERVED AND/OR OCCURRED : YES NO EXPLANATION: EQUIPMENT SET OVER RECLAIMED AREA: YES NO EXPLANATION - 95 BGT DW/DB TO BE SET AT SAME POSITION 95 BGT SW/DB (TANK - A).	
OTHER:	
TANK B - PERMIT: 06/02/10; OCD APPROVAL DATE: 11/04/14. SOIL IMPACT DIMENSION ESTIMATION: NA ft. X NA ft. X NA ft. EXCAVATION ESTIMATION (Cubic Yards) :	
SOIL IMPACT DIMENSION ESTIMATION: <u>NA</u> ft. X <u>NA</u> ft. X <u>NA</u> ft. EXCAVATION ESTIMATION (Cubic Yards) :	NA ppm
SITE SKETCH PCT located : off lon site DLOT DLAN site attracted by an	
	RF =0.52
	A
BERM	
MISCELL. NOT	22
(95)-B PBGTL TB = 5 ^t (95)-B PBGTL TB = 5 ^t	
T.B. ~ 5' B.G. PK: ZEVH01BGT2	
PJ#: Z2-006Q0	
Permit date(s): 06/03/	0
OCD Appr. date(s): 06/27/	
COMPRESSOR Tank OVM = Organic Vapor Mete	
A BGT Sidowalle Visible: Y (N	
X - S.P.D.	1
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H. = TEST HOLE; ~= APPROX.; W.H. = WELL HEAD; T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELOW-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING WALL; NA-NOT	F
APPLICABLE OR NOT AVAILABLE; SW - SINGLE WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; DB - DOUBLE BOTTOM.	E
NOTES: GOOGLE EARTH IMAGERY DATE: 11/17/2013. ONSITE: 11/04/14	

*

•

Analytical Report Lab Order 1411112

Hall Environmental Analysis Laboratory, Inc.

Surr: 4-Bromofluorobenzene

EPA METHOD 300.0: ANIONS

EPA METHOD 418.1: TPH

Petroleum Hydrocarbons, TR

Chloride

. * *

Date Reported: 11/7/2014

Analyst: LGP

Analyst: JME

11/5/2014 11:09:58 AM R22348

11/5/2014 10:38:27 AM 16248

11/5/2014 12:00:00 PM 16251

CLIENT: Blagg Engineering			Client Sampl	e ID: 5P	С-ТВ @ 5' (95)-В	
Project: ARNAUD A #1			Collection	Date: 11	/4/2014 12:15:00 PM	
Lab ID: 1411112-001	Matrix: S	SOIL	Received	Date: 11.	/5/2014 7:30:00 AM	
Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8021B: VOLATILES					Analys	t: NSB
Benzene	ND	0.046	mg/Kg	1	11/5/2014 11:09:58 AM	/ R22348
Toluene	ND	0.046	mg/Kg	1	11/5/2014 11:09:58 AM	/ R22348
Ethylbenzene	ND	0.046	mg/Kg	1	11/5/2014 11:09:58 AM	/ R22348
Xylenes, Total	ND	0.093	mg/Kg	1	11/5/2014 11:09:58 AM	/ R22348

101

ND

ND

80-120

30

20

%REC

mg/Kg

mg/Kg

1

20

1

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associate
	Е	Value above quantitation range	Н	Holding times for preparation o
	J	Analyte detected below quantitation limits	ND	Not Detected at the Reporting L
	0	RSD is greater than RSDlimit	Р	Sample pH greater than 2.

- RPD outside accepted recovery limits R
- S Spike Recovery outside accepted recovery limits
- ated Method Blank

Page 1 of 5

- or analysis exceeded
- Limit
- RL Reporting Detection Limit

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

Client: Blagg Engineering **Project:** ARNAUD A #1

. .

Sample ID MB-16248	SampType: MBLK	TestCode: EPA Method	300.0: Anions	
Client ID: PBS	Batch ID: 16248	RunNo: 22370		
Prep Date: 11/5/2014	Analysis Date: 11/5/2014	SeqNo: 659130	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Chloride	ND 4.5			
Chionde	ND 1.5			
Sample ID LCS-16248	SampType: LCS	TestCode: EPA Method	300.0: Anions	
		TestCode: EPA Method RunNo: 22370	300.0: Anions	
Sample ID LCS-16248	SampType: LCS		300.0: Anions Units: mg/Kg	
Sample ID LCS-16248 Client ID: LCSS	SampType: LCS Batch ID: 16248 Analysis Date: 11/5/2014	RunNo: 22370		RPDLimit Qual

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- Е Value above quantitation range
- Analyte detected below quantitation limits J
- 0 RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits S
- В Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
 - Р Sample pH greater than 2.
 - RL Reporting Detection Limit

Page 3 of 5

07-Nov-14

WO#: 1411112

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

Client: Blagg Engineering **Project:** ARNAUD A #1

. .

Sample ID MB-16251	SampType: MBLK	TestCode: EPA Method	418.1: TPH								
Client ID: PBS	Batch ID: 16251										
Prep Date: 11/5/2014	Analysis Date: 11/5/2014	Units: mg/Kg	: mg/Kg								
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual							
Petroleum Hydrocarbons, TR	ND 20										
Sample ID LCS-16251 SampType: LCS TestCode: EPA Method 418.1: TPH											
Client ID: LCSS	Batch ID: 16251										
Prep Date: 11/5/2014	Analysis Date: 11/5/2014	SeqNo: 658458	Units: mg/Kg								
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual							
Petroleum Hydrocarbons, TR	120 20 100.0	0 118 80	120								
Sample ID LCSD-16251	SampType: LCSD	TestCode: EPA Method	418.1: TPH								
Client ID: LCSS02	Batch ID: 16251	RunNo: 22342									
Prep Date: 11/5/2014	Analysis Date: 11/5/2014	SeqNo: 658459	Units: mg/Kg								
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual							
Petroleum Hydrocarbons, TR	110 20 100.0	0 113 80	120 3.79	20							

Qualifiers:

- Value exceeds Maximum Contaminant Level. *
- Value above quantitation range Е
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- S Spike Recovery outside accepted recovery limits
- В Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
 - Р Sample pH greater than 2.
 - RL Reporting Detection Limit

Page 4 of 5

07-Nov-14

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, In	Hall	Environmental	Analysis	Laborato	rv. Inc.
--	------	---------------	----------	----------	----------

Client: Blagg Engineering Project: ARNAUD A #1

• • *

Sample ID MB-16232 MK	SampType: MBLK TestCode: EPA Method 8021B: Volatiles															
Client ID: PBS	Batch	Batch ID: R22348 RunNo: 22348														
Prep Date:	Analysis Da	te: 11	/5/2014	S	SeqNo: 6	58775	Units: mg/k	(g								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual						
Benzene	ND	0.050														
Toluene	ND	0.050														
Ethylbenzene	ND	0.050														
Xylenes, Total	ND	0.10														
Surr: 4-Bromofluorobenzene	1.0		1.000		102	80	120									
Sample ID LCS-16232 MK	SampType: LCS TestCode: EPA Method 8021B: Volatiles															
Client ID: LCSS	Batch	ID: R2	2348	F	RunNo: 22	2348										
Prep Date:	Analysis Da	te: 11	/5/2014	S	SeqNo: 65	58776	Units: mg/K	(g								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual						
Benzene	0.97	0.050	1.000	0	96.9	80	120									
Toluene	0.97	0.050	1.000	0	96.8	80	120									
Ethylbenzene	0.99	0.050	1.000	0	99.1	80	120									
Xylenes, Total	2.9	0.10	3.000	0	97.5	80	120									
Surr: 4-Bromofluorobenzene	1.1		1.000		107	80	120									
Sample ID MB-16232	SampTy	pe: ME	LK	Tes	tCode: EP	A Method	8021B: Volat	tiles								
Client ID: PBS	Batch I	D: 162	232	F	RunNo: 22	2348										
Prep Date: 11/4/2014	Analysis Da	te: 11	/5/2014	S	SeqNo: 65	58779	Units: %RE	С								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual						
Surr: 4-Bromofluorobenzene	1.0		1.000		102	80	120									
Sample ID LCS-16232	SampTy	pe: LC	S	Tes	tCode: EP	A Method	8021B: Volat	tiles								
Client ID: LCSS	Batch I	D: 162	232	R	unNo: 22	2348										
Prep Date: 11/4/2014	Analysis Dat	te: 11	/5/2014	S	eqNo: 65	58780	Units: %RE	С								
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual						
Surr: 4-Bromofluorobenzene	1.1		1.000		107	80	120									

Qualifiers:

* Value exceeds Maximum Contaminant Level.

E Value above quantitation range

- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
 - P Sample pH greater than 2.
 - RL Reporting Detection Limit

Page 5 of 5

07-Nov-14

1411112

WO#:

I ABORATORY	4901 Hawkins Albuquerque, NM 87 5-345-3975 FAX: 505-345-4 te: www.hallenvironmental.c	109 Sam	ple Log-In Check List
Client Name: BLAGG Work Orde	er Number: 1411112		RcptNo: 1
Received by/date: AT 11/05/14			
Logged By: Anne Thorne 11/5/2014 7:	30:00 AM	anne Ham	-
Completed By: Anne Thorne 11/5/2014	I	anne Ham	_
Reviewed By: AT 11051	2		
Chain of Custody	4		
1. Custody seals intact on sample bottles?	Yes 🗹	No 🗌	Not Present
2. Is Chain of Custody complete?	Yes 🖌	No	Not Present
3. How was the sample delivered?	Client		
Log in			
 Was an attempt made to cool the samples? 	Yes 🖌	No 🗌	NA 🗌
5. Were all samples received at a temperature of >0° C to 6	6.0°C Yes 🗹	No 🗌	
6. Sample(s) in proper container(s)?	Yes 🗹	No 🗌	
7. Sufficient sample volume for indicated test(s)?	Yes 🗹	No 🗌	
8. Are samples (except VOA and ONG) properly preserved?	Yes 🗹	No	
9. Was preservative added to bottles?	Yes 🗌	No 🗹	NA 🗆
10.VOA vials have zero headspace?	Yes	No 🗌	No VOA Vials 🗹
11. Were any sample containers received broken?	Yes 🗆	No 🗹	H of processed
12. Does paperwork match bottle labels? (Note discrepancies on chain of custody)	Yes 🔽	No 🗆	# of preserved bottles checked for pH: (<2 or >12 unless noted)
13. Are matrices correctly identified on Chain of Custody?	Yes 🔽	No 🗌	Adjusted?
14. Is it clear what analyses were requested?	Yes 🗹	No 🗌	
15. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes 🗹	No 🗌	Checked by:
Onesial Vandling (Kanstin-bis)			
<u>Special Handling (if applicable)</u> 16. Was client notified of all discrepancies with this order?	Yes	No 🗌	NA 🗹
TO, was cheft formed of an discrepancies with this order?	res 🗀		

Person Notified:		Date	1	1000 (1000 100 100 100 100 100 100 100 1	
By Whom:		Via:	eMail	Phone 🗍 Fax	In Person
Regarding:	مر ورود در این این این این این میرد این این میرد می این این این این این این این این این ای			مرد المردي الم	PE 11, 1, 14 & Product - and Exception of sec.
Client Instructions:	and the second se		e se deducti ale di 7 . es. e . es ^t er	14 You ALL STREET BERGER	

17. Additional remarks:

. .

18. Cooler Information

Cooler No-	Temp °C	Condition	Seal Intact	Seal No	Seal	Date	Signed By	1
1	1.0	Good	Not Present					

Cient:	BLAG	ig engr.	/ BP AMERICA	Standard Project Name	Rush	SAME DAY						AL	Y	SI	S L	A	80	R/			
Mailing Ad	dress:	P.O. BO	X 87	ARNAUD A # 1				www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109													
		BLOOM	FIELD, NM 87413	Project #:			Tel. 505-345-3975 Fax 505-345-4107														
Phone #:		(505) 63		1				10	1. 50	55-51	+3-3		-	ysis			State Party	,,			
email or Fax#:			Project Manager:					34.0	-										1		
QA/QC Pac			Level 4 (Full Validation)				(8021B)	only)	/oun			IS)		² O ₄ ,SO ₄	PCB's		•	er - 300.1)			0
Accreditat		Other		Sampler: On Ice:	NELSON VI	ELEZ AU	1915-(8(TPH (Gas	DRO	18.1)	(1.40)	270SIN		03, NO2, F	s / 8082		A)	0.0 / water			composite sample
	ype)			Sample Temp	CLARGE A MARTINE AND A DATA STATE AND A CARD AND A CARD	0	E	+	GRO	od 4	od 5	or 8	tals	J'NC	cide	(A)	07-	I - 30		e	osite
Date	Time	Matrix	Sample Request ID	Type and #	Preservative Type	HEAL NO.	BTEX + WITB	BTEX + MTBE	TPH 8015B (GRO /	TPH (Method 418.1)	EDB (Method 504.1)	PAH (8310 or 8270SIMS)	RCRA 8 Metals	Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil - 300.0 /		Grab sample	5 pt. comp
11/4/14	1215	SOIL	5PC - TB @ 5' (95) - B	4 oz 1	Cool		V			۷								٧		T	V
- 11/4/14 -	1220	SOIL	5PC - TB @ 6' (95) - A	f - () 4011	Cool	-7.02	4			V								*			*
			RUN TPH 8015B IF TPH 418.1 > 2,500 mg/Kg																		+
			· · · · · · · · · · · · · · · · · · ·																	_	
ate: 14/14 atę:	Time: 1746 Time:	Relinquisho	hr. f	Received by:	what	Date Time	, BIL		RECT				urt,	Farm	ingto	on, N	M 87	7401			
414	1840	SAU	A Walter ubmitted to Hall Environmental may be s	Ihno	accredited laboratorie	0730			ity. An							ykey	Z	EVH	01BC	<u>it2</u>	-

...

bp

*



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

October 30, 2014

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL – RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: ARNAUD A 001 API #: 3004528182

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about November 4, 2014. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

9 Dulp

Jerry Van Riper Surface Land Negotiator BP America Production Company

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

October 29, 2014

*

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

ARNAUD A 001 API 30-045-28182 (H) Section 17 – T32N – R09W San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around November 4 2014.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

f Passe

Jeff Peace BP Field Environmental Advisor

(505) 326-9479



