Form C-144 Revised June 6, 2013

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or 12645 Proposed Alternative Method Permit or Closure Plan Application ECEIVED
Type of action: Below grade tank registration Permit of a pit or proposed alternative method FEB 0 € 2015 Glosure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Gallegos Canyon Unit 176
API Number:3004507228 OCD Permit Number:
U/L or Qtr/Qtr C
Center of Proposed Design: Latitude36.63829
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: □ Drilling □ Workover Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management □ Low Chloride Drilling Fluid □ yes □ no □ Lined □ Unlined □ Liner type: Thicknessmil □ LLDPE □ PVC □ Other □ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A Volume:95.0
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Double walled/double bottomed; side walls not visible
Liner type: Thicknessmil
4. Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)					
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school,	hospital,				
institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet					
Alternate. Please specify	•				
6.					
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)					
☐ Screen ☐ Netting ☐ Other					
Monthly inspections (If netting or screening is not physically feasible)					
7. Signs: Subsection C of 19.15.17.11 NMAC					
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers					
Signed in compliance with 19.15.16.8 NMAC					
Variances and Exceptions:					
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank:					
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.					
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.					
9.					
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acce	ptable source				
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	•				
General siting					
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No				
<u>Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.</u> NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No				
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	L ICS LI NO				
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No				
Within an unstable area. (Does not apply to below grade tanks)	☐ Yes ☐ No				
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 					
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map					
Below Grade Tanks					
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured	Yes No				
from the ordinary high-water mark).	L Yes L No				
- Topographic map; Visual inspection (certification) of the proposed site					
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No				
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)					
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No				

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No									
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image										
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site										
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Temporary Pit Non-low chloride drilling fluid										
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).										
- Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No									
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No									
Permanent Pit or Multi-Well Fluid Management Pit										
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No									
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	- 1									
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No									
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.										
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.										
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.										
and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:										
11.										
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the dot attached.	cuments are									
 □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC 	.15.17.9 NMAC									
and 19.13.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC										
Previously Approved Design (attach copy of design) API Number: or Permit Number:										

Form C-144 Oil Conservation Division Page 3 of 6

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
 attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC 	
 □ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC □ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC □ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC □ Quality Control/Quality Assurance Construction and Installation Plan 	
 □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Nuisance or Hazardous Odors, including H₂S, Prevention Plan 	
 ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan 	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal	luid Management Pit
Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	
14.	-
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	attached to the
15	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.	
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	
Within a 100-year floodplain.	Yes No
- FEMA map	☐ Yes ☐ No
16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan	n. Please indicate.
by a check mark in the box, that the documents are attached.	n. Trease marcare,
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC	
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.1	
Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.1 Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC	5.17.11 NMAC
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC	•
 ☐ Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC ☐ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be appropriate to the control of th	at he achieved)
☐ Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	t be acmeved)
Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Site Regiantation Fiant - based upon the appropriate requirements of Subsection 11 of 19.13.17.13 MMAC	\
17.	
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	∘ f
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	
OCD Representative Signature: Approval Date: 2/12/	hars
7	2012
Title: (omplance Office O OCD Permit Number:	
19.	
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting and submitted	the closure report
The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not of	
section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
☐ Closure Completion Date: 4/14/2014	
20. Closure Method:	
Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-loc	op systems only)
☐ If different from approved plan, please explain.	
21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please ind	licate, by a check
mark in the box, that the documents are attached.	
☐ Proof of Closure Notice (surface owner and division) ☐ Proof of Deed Notice (required for on-site closure for private land only)	
Plot Plan (for on-site closures and temporary pits)	
13/1 A to a terminate on A termination of Complete and Atenny to Authority Complete by A.	
☐ Confirmation Sampling Analytical Results (if applicable) ☐ Waste Material Sampling Analytical Results (required for on-site closure)	
 Waste Material Sampling Analytical Results (required for on-site closure) ✓ Disposal Facility Name and Permit Number 	
 Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation 	
 Waste Material Sampling Analytical Results (required for on-site closure) ✓ Disposal Facility Name and Permit Number 	

Operator Closure Certification:	
	with this closure report is true, accurate and complete to the best of my knowledge and closure requirements and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Jeff Pose	Date:February 4, 2015
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Gallegos Canyon Unit 176 API No. 3004507228 Unit Letter C, Section 25, T28N, R13W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to a misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

No notice was made due to a misunderstanding of the BGT notice requirements at that time.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	29
Chlorides	US EPA Method 300.0 or 4500B	250 or background	740

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH and BTEX were below the stated limits. Chloride was 740 ppm, which is above the standard. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 - Sampling results indicate no hydrocarbon release occurred, but chloride was above the standard. Since this site is on sandstone bedrock BP will request a risk-based closure approval.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.
 - Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141 Revised August 8, 2011 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

			Rele	ease Notific	eation	i and Co	orrective A	ction	
						OPERA	FOR .	☐ Initia	al Report 🛛 Final Report
Name of Co	mpany: B	P				Contact: Jef			
		Court, Farmi	ngton, N	M 87401		Telephone 1	No.: 505-326 - 94	79	
		os Canyon U					e: Natural gas v		
Surface Ow	ner: Triba	1		Mineral C	wner: [Tribal		. API No	. 3004507288
				LOCA	TIOI	N OF REI	LEASE		
Unit Letter C	Section 25	Township 28N	Range 13W	Feet from the 800		South Line	Feet from the 2,180	East/West Line West	County: San Juan
		Lati	itude3	6.63829		_ Longitud	e108.17271		
				NAT	URE	OF REL	EASE		
Type of Rele	ase: unknov	wn, possibly p	roduced w				Release: unknow	n Volume F	Recovered: none
		v grade tank –				Date and H	lour of Occurrenc	e: Date and	Hour of Discovery: April 4,
						unknown		2014; 9:3	0 AM
Was Immedia	ate Notice (Yes 🗵	No 🗌 Not Re	quired	If YES, To	Whom?		
By Whom?						Date and F	lour		
Was a Water	course Read					If YES, Vo	lume Impacting t	he Watercourse.	
,			Yes 🗵	No					•
If a Watercou	rse was Im	pacted, Descr	ibe Fully.*						
		•	•						
the BGT. So	il analysis ı	esulted in TP	H and BTI	EX below standard	ds. Chlo	oride was 740	ppm, which is ab	pove the standard.	to ensure no soil impacts from Analysis results are attached. ampling results showed chloride
above the sta greater than 1	ndard. BP 100 feet. Ti	requests NMC he area under	OCD approthe BGT v	ove a risk-based cl was backfilled and	osure fo compac	or this site sin oted and is sti	ce it is located on Il within the activ	sandstone bedrock e well area.	and depth to groundwater is
regulations all public health should their of or the environ	I operators or the envi operations homent. In a	are required to ronment. The nave failed to a	o report ar acceptance dequately OCD accep	nd/or file certain rece of a C-141 reporting and re	elease no ort by the emediate	otifications a e NMOCD m e contaminati	nd perform correct arked as "Final Roon that pose a throether of the coperator of the coper	tive actions for reli eport" does not reli eat to ground water responsibility for c	want to NMOCD rules and eases which may endanger eve the operator of liability, surface water, human health ompliance with any other
(1-00 /	7 0					OIL CON	<u>SERVATION</u>	<u>DIVISION</u>
Signature:	YH K	earl							
Printed Name	e: Jeff Peac	e				Approved by	Environmental S	pecialist:	
Title: Field E	nvironmen	tal Coordinate	r			Approval Da	e:	Expiration	Date:
E-mail Addre	ess: peace.j	effrey@bp.coi	n			Conditions o	Approval:	J.	Attached
Date: Februa	ary 4, 2015	•	Phone	e: 505-326-9479					_

^{*} Attach Additional Sheets If Necessary

CLIENT: BP		GINEERING, INC. DOMFIELD, NM 87413	API#: 3004507228
	(505)	632-1199	(if applicable):
FIELD REPORT:	(circle one): BGT CONFIRMATION / RE	ELEASE INVESTIGATION / OTHER:	PAGE#: 1 of 1
SITE INFORMATION	ELD REPORT: (circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER: PAGE #: 1 of 1 DATE STATED: 04/04/14 DATE FINISHED: -1/4/FOOTAGE: 800'N / 2,180'W NE/NW LEASE TYPE: FEDERAL / STATE / FEE / INDIAN ASE #: I-149-IND-8471 PROD. FORMATION: DK CONTRACTOR: MBF - C. PARKS EFERENCE POINT: WELL HEAD (W.H.) GPS COORD: 36,63840 X 108.17217 GL ELEV: 5,983' 95 BGT (DW/DB) GPS COORD: 36,63829 X 108.17271 DISTANCE/BEARING FROM W.H: GPS COORD: DISTANCE/BEARING FROM W.H: GPS COOR		
		NM CNTY: SJ ST: NM	DATE FINISHED:
		CDOCCEIDE	
		TRACTOR: MBF - C. PARKS	SPECIALIST(S): JCB
,,			
			OVM
			(mqq)
			`
SOIL COLOR: DARK YELL COHESION (ALL OTHERS): NON COHESIVE SLIGHTL CONSISTENCY (NON COHESIVE SOILS): LO MOISTURE: DRY SLIGHTLY MOIST MOIST / W SAMPLE TYPE: GRAB COMPOSITE	COMSH ORANGE Y COHESIVE COHESIVE / HIGHLY COHESIVE DE DOSE TEIRM DENSE / VERY DENSE HC ET / SATURATED / SUPER SATURATED # OF PTS. 5	ASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC ENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRIT ODOR DETECTED: YES NO EXPLANATION -	M / STIFF / VERY STIFF / HARD
SITE OBSERVATION	S: LOST INTEGRITY OF EQUIPMENT: YE	S NO EXPLANATION -	
APPARENT EVIDENCE OF A RELEASE OBSERVI	ED AND/OR OCCURRED : YES NO EXPLANA	ATION:	
SOIL IMPACT DIMENSION ESTIMATION		. X NA ft. EXCAVATION E	STIMATION (Cubic Yards) : NA
DEPTH TO GROUNDWATER: >100' N	IEAREST WATER SOURCE: >1,000'	NEAREST SURFACE WATER: <1,000' NM	OCD TPH CLOSURE STD: 1,000 ppm
PROD. TANK	STEEL CONTAINMENT RING BERM PBGTL		MCALIB. READ. = 101.0 ppm RF = 1.00 MCALIB. GAS = 100 ppm ME: 7:22 mppm DATE: 04/04/14 MISCELL. NOTES WO: N15464158 PO #: PK: ZDCS01GEN1 PJ #: X5-005MD Permit date(s): 06/08/10
DOWN SLOPE DIRECTION NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION	T.B. ~ 5' B.G. SEPARATOR ON DEPRESSION: B.G. = RELOW GRADE: B.= RELOW	X - S.P.D.	OCD Appr. date(s): 01/14/14 Tank OVM = Organic Vapor Meter ppm = parts per million A BGT Sidewalls Visible: Y / N BGT Sidewalls Visible: Y / N
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BE	OW-GRADE TANK LOCATION; SPD = SAMPLE POIN	T DESIGNATION; R.W. = RETAINING WALL; NA - NOT	Magnetic declination: 10° E
APPLICABLE OR NOT AVAILABLE; SW - SINGL NOTES:	E WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM	; DB - DOUBLE BOTTOM. 11 ONSITE: 04/04/14	

Analytical Report

Lab Order 1404415

Date Reported: 4/14/2014

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 95 BGT 5-pt @ 5'

Project: GCU 176

Collection Date: 4/4/2014 9:30:00 AM

Lab ID: 1404415-001

Received Date: 4/9/2014 10:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGE	ORGANICS				Analyst	BCN
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	4/10/2014 8:56:31 PM	12624
Surr: DNOP	96.3	66-131	%REC	1	4/10/2014 8:56:31 PM	12624
EPA METHOD 8015D: GASOLINE RAN	NGE				Analyst	:: NSB
Gasoline Range Organics (GRO)	ND	4.8	mg/Kg	1	4/10/2014 11:37:38 PM	12623
Surr: BFB	86.6	74.5-129	%REC	1	4/10/2014 11:37:38 PM	12623
EPA METHOD 8021B: VOLATILES					Analyst	: NSB
Benzene	ND	0.048	mg/Kg	1	4/10/2014 11:37:38 PM	12623
Toluene	ND	0.048	mg/Kg	1	4/10/2014 11:37:38 PM	12623
Ethylbenzene	ND	0.048	mg/Kg	1	4/10/2014 11:37:38 PM	12623
Xylenes, Total	ND	0.096	mg/Kg	1	4/10/2014 11:37:38 PM	12623
Surr: 4-Bromofluorobenzene	102	80-120	%REC	1	4/10/2014 11:37:38 PM	12623
EPA METHOD 300.0: ANIONS					Analyst	: JRR
Chloride	740	30	mg/Kg	20	4/10/2014 4:32:58 PM	12646
EPA METHOD 418.1: TPH					Analyst	: BCN
Petroleum Hydrocarbons, TR	29	20	mg/Kg	1	4/10/2014	12560

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDImit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 6

- P Sample pH greater than 2.
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#: 1404415

14-Apr-14

Client:

Blagg Engineering

Project:

GCU 176

Sample ID MB-12646

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID:

PBS

Batch ID: 12646

RunNo: 17936

Prep Date:

4/10/2014

Analysis Date: 4/10/2014 **PQL**

1.5

SeqNo: 517496

Units: mg/Kg

Analyte

Result ND

SPK value SPK Ref Val %REC LowLimit

HighLimit

RPDLimit

Qual

Chloride

Sample ID LCS-12646

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

Prep Date: 4/10/2014

Batch ID: 12646

RunNo: 17936

Units: mg/Kg

Analyte

Analysis Date: 4/10/2014

SeqNo: 517497

%RPD **RPDLimit**

Qual

HighLimit

14

SPK value SPK Ref Val %REC

%RPD

Chloride 1.5 15.00 93.6 90 110

Qualifiers:

Ε

Value exceeds Maximum Contaminant Level.

J Analyte detected below quantitation limits RSD is greater than RSDlimit 0

R RPD outside accepted recovery limits

Value above quantitation range

Spike Recovery outside accepted recovery limits S

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Η

ND Not Detected at the Reporting Limit

P Sample pH greater than 2.

RLReporting Detection Limit Page 2 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404415

14-Apr-14

Client:

Blagg Engineering

Project:

GCU 176

Sample ID MB-12560

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID:

PBS

Batch ID: 12560

PQL

RunNo: 17911

SPK value SPK Ref Val %REC LowLimit

Prep Date:

Client ID:

Analyte

4/7/2014

Analysis Date: 4/10/2014

SeqNo: 516689

Units: mg/Kg

HighLimit

RPDLimit

Qual

Analyte Petroleum Hydrocarbons, TR

ND 20

Result

%RPD

%RPD

Sample ID LCS-12560

SampType: LCS Batch ID: 12560

TestCode: EPA Method 418.1: TPH RunNo: 17911

120

Prep Date: 4/7/2014

LCSS

Analysis Date: 4/10/2014

SeqNo: 516690

Units: mg/Kg

Qual

Qual

Petroleum Hydrocarbons, TR

Client ID: LCSS02

Result **PQL** 98

SPK value SPK Ref Val

%REC

97.8

HighLimit

RPDLimit

Sample ID LCSD-12560

SampType: LCSD

80 TestCode: EPA Method 418.1: TPH

LowLimit

20

Batch ID: 12560

RunNo: 17911

Prep Date: 4/7/2014

Analyte

Analysis Date: 4/10/2014

Result

SeqNo: 516691

Units: mg/Kg

120

%RPD **RPDLimit** HighLimit

Petroleum Hydrocarbons, TR

20

SPK value SPK Ref Val %REC 100.0

100.0

97.8

LowLimit

0

20

Qualifiers:

S

Value exceeds Maximum Contaminant Level.

Spike Recovery outside accepted recovery limits

Ε Value above quantitation range Analyte detected below quantitation limits J

RSD is greater than RSDlimit 0

R RPD outside accepted recovery limits

Analyte detected in the associated Method Blank

ND Not Detected at the Reporting Limit

р Sample pH greater than 2.

Reporting Detection Limit

Н Holding times for preparation or analysis exceeded

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404415

14-Apr-14

Client:

Blagg Engineering

Project:

GCU 176

Project: GCU I	70					
Sample ID MB-12644	SampType: MBLK	TestCode: EPA Method	8015D: Diesel Range Organics			
Client ID: PB\$	Batch ID: 12644	RunNo: 17898				
Prep Date: 4/10/2014	Analysis Date: 4/10/2014	SeqNo: 516499	Units: %REC			
Analyte	Result PQL SPK valu	e SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual			
Surr: DNOP	7.5 10.0	74.9 66	131			
Sample ID LCS-12644	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range Organics			
Client ID: LCSS	Batch ID: 12644	RunNo: 17898				
Prep Date: 4/10/2014	Analysis Date: 4/10/2014	SeqNo: 516503	Units: %REC			
Analyte	Result PQL SPK value	e SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual			
Surr: DNOP	3.8 5.00	75.5 66	131			
Sample ID MB-12624	SampType: MBLK TestCode: EPA Method 8015D: Diesel Range Organics					
Client ID: PB\$	Batch ID: 12624	RunNo: 17898				
Prep Date: 4/9/2014	Analysis Date: 4/10/2014	SeqNo: 516973	Units: mg/Kg			
Analyte	Result PQL SPK valu	e SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual			
Diesel Range Organics (DRO) Surr: DNOP	ND 10 9.5 10.0	95.4 66	131			
Sample ID LCS-12624	SampType: LCS	TestCode: EPA Method	8015D: Diesel Range Organics			
Client ID: LCSS	Batch ID: 12624	RunNo: 17898				
Prep Date: 4/9/2014	Analysis Date: 4/10/2014	SeqNo: 516974	Units: mg/Kg			
Analyte	Result PQL SPK value	e SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qual			
Diesel Range Organics (DRO)	46 10 50.0		145			
Surr: DNOP	4.4 5.00	0 87.9 66	131			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1404415

14-Apr-14

Client:

Blagg Engineering

Project:

GCU 176

Sample ID MB-12623	SampType: MBLK			Tes	TestCode: EPA Method 8015D: Gasoline Range					
Client ID: PBS	Batc	h ID: 12 6	623	F	RunNo: 1	7906				
Prep Date: 4/9/2014	Analysis [Date: 4/	10/2014	SeqNo: 51710		17100	Units: mg/Kg			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND	5.0								
Surr: BFB	870		1000		86.6	74.5	129			

Sample ID LCS-12623	SampT	ype: LC	S	Tes	tCode: E	PA Method	8015D: Gaso	oline Rang	je				
Client ID: LCSS	Batch	n ID: 12	623	F	RunNo: 17906								
Prep Date: 4/9/2014	Analysis Date: 4/10/2014			SeqNo: 517101			Units: mg/h						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Gasoline Range Organics (GRO)	25	5.0	25.00	0	102	71.7	134						
Surr: BEB	920		1000		92.2	74.5	129						

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1404415

14-Apr-14

Client:

Blagg Engineering

Project:

GCU 176

Sample ID MB-12623 SampType: MBLK Client ID: PBS Batch ID: 12623				TestCode: EPA Method 8021B: Volatiles RunNo: 17906									
Prep Date: 4/9/2014	Analysis [Units: mg/K						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	ND	0.050											
Toluene	ND	0.050											
Ethylbenzene	ND	0.050											
Xylenes, Total	ND	0.10											
Surr: 4-Bromofluorobenzene	1.0		1.000		105	80	120						
Sample ID LCS-12623	Samp	SampType: LCS			tCode: El	tiles							
Client ID: LCSS	LCSS Batch ID: 12623			RunNo: 17906									

Sample ID LCS-12623	SampType: LCS Batch ID: 12623 Analysis Date: 4/10/2014			TestCode: EPA Method 8021B: Volatiles								
Client ID: LCSS				F	RunNo: 1							
Prep Date: 4/9/2014				S	SeqNo: 5	17143	Units: mg/k	(g				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Benzene	1.1	0.050	1.000	0	109	80	120					
Toluene	1.0	0.050	1.000	0	102	80	120					
Ethylbenzene	1.0	0.050	1.000	0	102	80	120					
Xylenes, Total	3.0	0.10	3.000	0	100	80	120					
Surr: 4-Bromofluorobenzene	1.1		1.000		107	80	120					

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 6 of 6



uuu Environmeniui Anaiysis Laioviaiory 4901 Hawkins NE Albuquergue, NM 87105

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

BLAGG RcptNo: 1 Client Name: Work Order Number: 1404415 Received by/date:_ Michelle Garcia Logged By: 4/9/2014 10:00:00 AM Completed By: Michelle Garcia 4/9/2014 11:57:48 AM 04/09/14 Reviewed By: Chain of Custody Yes No 🗌 Not Present 🗹 1 Custody seals intact on sample bottles? Yes 🔽 No 🗌 Not Present 2. Is Chain of Custody complete? 3 How was the sample delivered? Courier Log In No 🗌 Yes 🗸 NA 🗌 4. Was an attempt made to cool the samples? Yes 🗸 No 🗌 NA 🔲 5. Were all samples received at a temperature of >0° C to 6.0°C Yes 🗸 No 🗌 Sample(s) in proper container(s)? Yes 🗹 7. Sufficient sample volume for indicated test(s)? V 8. Are samples (except VOA and ONG) properly preserved? Yes No 🗹 NA 🗌 Yes \square 9. Was preservative added to bottles? No VOA Vials 🗹 No 🗆 10.VOA vials have zero headspace? Yes \square No 🗹 11. Were any sample containers received broken? # of preserved bottles checked for pH: Yes 🗹 No . 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? Yes 🗹 No 🗆 13. Are matrices correctly identified on Chain of Custody? No 🗌 14. Is it clear what analyses were requested? V Checked by: Yes 🗹 No 🗆 15. Were all holding times able to be met? (If no, notify customer for authorization.) Special Handling (if applicable) Yes 🗌 No 🗌 NA 🗹 16. Was client notified of all discrepancies with this order? Person Notified: Date: By Whom: Via: eMail Phone Fax In Person Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Cooler No Temp C Condition Seal Intact Seal No Seal Date Good Yes 1.8

			···	Standard											TAI			
BP America				Project Nam														
Mailing Address: P.O. Box 87			www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109 Tel. 505-345-3975 Fax 505-345-4107															
Bloomfield, NM 87413															Project #:			
Phone #: (505)320-1183																1. 60.		
email or Fax#:			Project Mana															
QA/QC Packa			☐ Level 4 (Full Validation))	Jeff Blagg				<u>o</u>			:						
				Sampler: On ice:	Jeff Blagg ⊯Yes				RO/DR									S io
Date	Time	Matrix	Sample Request ID		perature::/ Preservative Type		BTEX (8021)		TPH 8015B (GRO / DRO)	TPH 418.1							Chloride	Air Bubbles (V
04/04/2014	9:30	Soil	95 BGT 5-pt @ 5'	1x 4oz	cool	-001	x			x		1				\neg	x	
					<u> </u>				7	7	1	1					1	1
										7	1	+-	+-		\Box	-	_	+
		- 		† -			+		+		+	+-	 			一	_	+
	 	 		 			+-		+	十	+	1-	+-		1	十	+	+
		 		 			+		+	+	+	+-	+		1	\dashv	-	+
		 		 	 		+		\dashv		+-	╁┈	┼		-	-+	-+	+
		+	}	 	 		+	┝╼┾	-	+	+		-			-	+	+
		 	 	 -	 		+		\dashv	+	+	-	┼─	\vdash	\vdash	\dashv	-+	+
		+	<u> </u>	<u> </u>			+		-+		+	+	┼-		-+	\dashv	_	+
				 	 		+		-	+	+-	+	├		-	+	\dashv	+
				 			+		\dashv		+-		╂			-+	-	-
Date: 1/8/2014	Time:	Relinquished by: July 13 legg		Repeived by: Date Time Mustulally 4/8/14 82/			Remarks: Bill BP Paykey: ZDCS01GEN1 BP Contact: Jeff Peace Please copy results to:											
Date:	Time:	Relinquish	istu ukulus laji Environmental may be subcontracti	Received by:	d laboratories. This	Date Time	peace.jeffrey@bp.com											



