 <u>Alternative Method</u>: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other _Double walled/double bottomed; side walls not visible Liner type: Thickness mil HDPE PVC Other
Tank Construction material:Steel
3. M Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A Volume: 95.0 bbl Type of fluid: Produced water
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
String-Reinforced
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover
Surface Owner: X Federal X State Private Tribal Trust or Indian Allotment
Center of Proposed Design: Latitude36.92877 Longitude107.99187 NAD: □1927 ⊠ 983
U/L or Qtr/QtrGSection4Township31NRange11WCounty:San Juan
API Number: 3004511057 OCD Permit Number: 5622
Facility or well name:Mudge LS 22
Address:200 Energy Court, Farmington, NM 87401
Operator: BP America Production CompanyOGRID #:778
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Closure plan only submitted for an existing permitted or non-permitted pit, below grade tank, or proposed alternative method
45-11057Permit of a pit or proposed alternative methodFEB 0 6 2015Closure of a pit, below-grade tank, or proposed alternative methodModification to an existing permit/or registrationFEB 0 6 2015
N2643 Proposed Alternative Method Permit or Closure Plan Application Type of action: □ Below grade tank registration
Pit, Below-Grade Tank, or
District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505State of New Mexico State of New Mexico Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505Form C-144 Revised June 6, 2013State of New Mexico Department District III
State of New Mexico Form C-144

٠

Page 1 of 6

18

.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting	
<u>Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.</u> NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	Yes No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	🗌 Yes 🗌 No
Below Grade Tanks	
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No				
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 					
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No				
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 					
<u>Temporary Pit Non-low chloride drilling fluid</u>					
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	TYes No				
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No				
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗍 No				
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No				
<u>Permanent Pit or Multi-Well Fluid Management Pit</u>					
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗍 No				
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 					
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of					
 initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No				
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 					
10. <u>Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist</u> : Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc					
 attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC 					
Previously Approved Design (attach copy of design) API Number: or Permit Number:					
III. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC □ Design Plan - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC □ Design Plan - based upon the appropriate requirement of Subsection C of 19 and 19.15.17.13 NMAC □ Design Plan - based upon the appropriate requirement of Subsection C of 19 and 19.15.17.13 NMAC □ Design Plan - based upon the appropriate requirement of Design Plan - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC □ Design Plan - based upon the appropriate requirement of Design Plan - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC □ Design Plan - based upon the appropriate requirement of Design Plan - based upon the appropriate requirement of Design Plan - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC □ Design Plan - based upon the appropriate requirement of Design Plan - based upon the appropriate requirement of Design Plan - based upon the appropriate requirement of Design Plan - based upon the appropriate requirement of Design Plan - based upon the approprise requirement of Design Plan - based upon the approp					
 Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 					
Previously Approved Design (attach copy of design) API Number: or Permit Number:					

.

.

12. <u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC	de a da anno 1944 anno
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that t attached.	ne aocuments are
 Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment 	
 Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC 	
 Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan 	
 Quarty Control Quarty Assurance Construction and Instantation Final Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC 	·
 Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan 	
 Oil Field Waste Stream Characterization Monitoring and Inspection Plan 	
 Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	
<u>Proposed Closure</u> : 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-we	ll Fluid Management Pit
Proposed Closure Method: Image: Waste Excavation and Removal Image: Waste Removal (Closed-loop systems only) Image: Waste Removal (Closed-loop systems only) Image: On-site Closure Method (Only for temporary pits and closed-loop systems)	
In-place Burial On-site Trench Burial	
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must	he attacked to the
waste Excavation and Removal Closure Fian Checkinst: (19.13.17.13 NMAC) Instructions: Each of the following items must closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC	
 Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NM. 	
 Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable s provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗍 No
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	Ce 🗌 Yes 🗍 No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

`

.

Oil Conservation Division

 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 							
	🗌 Yes 🗌 No						
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division							
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	Yes No						
Within a 100-year floodplain.							
- FEMA map	Ycs No						
 On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plane by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards canned Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	11 NMAC 15.17.11 NMAC						
17. Operator Application Certification:							
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.						
Name (Print): Title:							
Signature: Date:							
e-mail address: Telephone:							
18. <u>OCD Approva</u> l: Permit Application (including closure plan) X Closure Plan (only) OCD Conditions (see attachment)							
OCD Representative Signature: ON att. filly Approval Date: 2/23 Title: OCD Permit Number:	12015						
Title: OCD Permit Number: 19. OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Image: Closure Completion Date: 11/20/2014_	the closure report.						
Title: OCD Permit Number: 19. OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report. complete this						

.

Operator Closure Certification:

22.

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print):	Jeff Peace	Title: Field Environmental Coordinator
Signature:	Jeff Ponce	Date:February 4, 2015
e-mail address:	peace.jeffrey@bp.com	Telephone: (505) 326-9479

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Mudge LS 22</u> <u>API No. 3004511057</u> <u>Unit Letter G, Section 4, T31N, R11W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

No notice was made due to misunderstanding of the BGT notice requirements at that time.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)
 All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.
- 4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	0.203
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	0.624
TPH	US EPA Method SW-846 418.1	100	926
Chlorides	US EPA Method 300.0 or 4500B	250 or background	19

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and BTEX and chloride levels were below the stated limits. TPH was 926 ppm by Method 418.1 and 1,120 ppm by Method 8015. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. C-141 is attached.
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate a release occurred. The release was addressed through the spill and release guidelines and remediation was completed on November 20, 2014.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and will be reclaimed since the well was plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT will be reclaimed as part of final reclamation since the well was plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT will be reclaimed as part of final reclamation since the well was plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT will be reclaimed as part of final reclamation since the well was plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation since the well was plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

Closure report on C-144 form is included.

16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action												
						OPERA	ГOR	È [Initia	l Report	\boxtimes	Final Report
Name of Company: BP						Contact: Jeff Peace						
Address: 200 Energy Court, Farmington, NM 87401						Telephone No.: 505-326-9479						
Facility Name: Mudge LS 22						Facility Typ	e: Natural gas v	vell				
Surface Owner: Federal Mineral Owner					Owner:	Federal			API No	. 30045110)57	
LOCATI					ATIO	N OF REI	LEASE					,
Unit Letter	Section	Township	Range	Feet from the	North	orth/South Line Feet from the East/West Line County: San			an Juan			
G	4	31N	11W	1,850	North	North 1,450 East						
Latitude36.92877Longitude107.99187												
				NAT	URE	OF REL	EASE					
Type of Rele							Release: unknow			ecovered: n		
Source of Re	lease: BGT	, 95 bbl					lour of Occurrenc			Hour of Dis	covery:	March 9,
Was Immedia	ate Notice (liven?				unknown If YES, To	Whom?	·····	2010; 3:2	I PM		
iv us mineur	ne rionee e		Yes 🗵	No 🗌 Not R	equired	11 1 00, 10	whom:					
By Whom?						Date and H	lour:					
Was a Water	course Read	ched?					olume Impacting t	the Water	course.			
			Yes 🛛	No								
If a Watercou	irse was Im	pacted, Descr	ibe Fully.'	*								
	il analysis r	esulted in chl	oride and '	Total BTEX belo			the BGT was doi was 926 ppm by					
Describe Area Affected and Cleanup Action Taken.* BGT was removed and the area underneath the BGT was sampled. Sampling results indicate a release occurred. Impacted soil and sandstone bedrock was excavated and removed until all remaining soil samples resulted in less than 1,000 ppm TPH, which is the clean-up standard for this site. Approximately1,695 cubic yards were excavated and hauled to a landfarm for treatment. The area over the BGT was backfilled and compacted and will be reclaimed since the well has been plugged and abandoned.												
regulations al public health should their o	l operators or the envir perations h ment. In a	are required t ronment. The ave failed to a ddition, NMC	o report ar acceptanc adequately OCD accep	nd/or file certain r ce of a C-141 report investigate and r	elease n ort by th emediat	otifications ar e NMOCD m e contaminati	knowledge and u nd perform correc arked as "Final R on that pose a thr e the operator of	tive actio eport" do eat to gro	ns for rele es not reli und water	eases which eve the oper , surface wa	may en ator of ter, hun	danger liability nan health
		\wedge					OIL CON	SERVA	ATION	DIVISIC	<u>N</u>	
Signature:	ORK	Voil	/									
Printed Name	: Jeff Peace					Approved by	Environmental S	pecialist:				
Title: Field E	nvironment	al Coordinate	or			Approval Dat	e:	E>	xpiration I	Date:		
E-mail Addre	ss: peace.je	effrey@bp.co	n			Conditions of	Approval:			Attached		
Date: Februa		ate If Nacase		: 505-326-9479								

* Attach Additional Sheets If Necessary

CLIENT: BP	P.O. BOX 87, E	ENGINEERING, BLOOMFIELD, N 5) 632-1199		API#: 3004511057		
FIELD REPORT:	BGT CONFIRMATION TE (other)	MP. PIT CLOSURE / RELEASE	INVESTIGATION	PAGE No: of		
SITE INFORMATION	: <u>SITE NAME:</u> MU	DGE LS # 22		DATE STARTED: 03/09/10		
QUAD/UNIT: G SEC: 4 TW	-: 31N RNG: 11W F	рм: NM сnty: SJ	st: NM	DATE FINISHED:		
QTR-QTR/FOOTAGE: 1,85<u>0'N</u> /	1,450'E SW/NE LE	ASE TYPE: FEDERAL S	TATE / FEE / INDIAN	ENVIRONMENTAL		
LEASE #: SF078051	PROD. FORMATION: D	CONTRACTOR: EI	KHORN	SPECIALIST: JCB		
REFERENCE POINT	WELL HEAD (W.H	.) GPS COORD.:	36.92885 X 107.99	167 GL ELEV.: 6,160'		
1) 95 BGT (DW/DB)	 GPS COORD.:	·	07	ARING FROM W.H.: 75', S63W		
2)	GPS COORD.:		DISTANCE/BE	ARING FROM W.H.:		
3)				ARING FROM W.H.:		
4)	GPS COORD.:		DISTANCE/BE/	ARING FROM W.H.:		
5)	GPS COORD.:		DISTANCE/BE/	ARING FROM W.H.:		
LAB INFORMATION:	CHAIN OF CLIST	DY RECORD(S)	HARE Chrirot	ech		
1) SAMPLE ID:95 BGT 5-pt. @						
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:			
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:			
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:			
5) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:			
SOIL DESCRIPTION	SOIL TYPE: SAND	SILTY SAND SILT / SILTY	CLAY / CLAY / GRAVEL / OT	HER		
COHESION (ALL OTHERS): NON COHESIVE) SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / C DENSITY (COHESIVE CLAYS & SILTS): SOFT MOISTURE: DRY (SLIGHTLY MOIST / MOIST / WE	SOIL COLOR: COHESION (ALL OTHERS): NON COHESIVE/SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE CONSISTENCY (NON COHESIVE SOILS): LOOSE / FIRM / DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD MOISTURE: DRY (SLIGHTLY MOIST / MOIST / WET / SATURATED / SUPER SATURATED ADDITIONAL COMMENTS: _95 BGT SET @ 6', SIDEWALLS COVERED. USE CRANE TO PULL TANK, BACKHOE TO SAMPLE.					
EXCAVATION DIMENSIONS (if applicable)	i: NA ft. X	NA ft. X NA	ft. cubic yards ex	cavated (if applicable): NA		
SITE SKETCH	⊕ WE	OVM CALIB, TEAD. =		PLOT PLAN circle: Attached MISCELL. NOTES		
$12' \qquad \qquad \begin{array}{c} X \\ X \\ X \\ X \\ \end{array} \qquad \begin{array}{c} PBG \\ T.B. (a) \\ B.G \\ \end{array}$	96'			DW - DOUBLE WALLED DB - DOUBLE BOTTOM		
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVAT						
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BE		SAMPLE POINT DESIGNATION; R.T. =	RETAINING WALL.			
revised: 11/21/08		ONSITE:	03/09/10	BEI1005E.SKF		



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:	Blagg/BP	Project #:	94034-0010
Sample ID:	95 BGT 5-pt @ -7	Date Reported	03-12-10
Laboratory Number:	53320	Date Sampled:	03-09-10
Chain of Custody No:	8841	Date Received:	03-10-10
Sample Matrix:	Soil	Date Extracted:	03-10-10
Preservative:	Çool	Date Analyzed:	03-10-10
Condition:	Intact	Analysis Needed:	TPH-418.1

		Det.
1	Concentration	Limit
Parameter	<u>(mg/kg)</u>	(mg/kg)
		- nº 4

Total Petroleum Hydrocarbons 926 13.4

ND = Parameter not detected at the stated detection limit.

References: Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water, and Waste, USEPA Storet No. 4551, 1978.

Comments: Müdge LS #22

Analyst

Mustine m Walters



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Glient: Sample ID: Laboratöry Number: Chain of Custódy: Sample Matrix: Preservative: Condition:	Blágg/BP 95 BGT 5⊧pt @ ₌7' 53320 8841 Sóil CóoÎ Intact		Project #: Date Reported: Date Sampled: Date Received: Date Analyzed: Date Extracted: Analysis Requested:		94034-0010 03-11-10 03-09-10 03-10-10 03-11-10 03-11-10 8TEX
Parameter		Concentration (ug/Kg)	а ф	Det. Limit (ug/Kg)	
Benzene Toluene Ethylbenzene p.m-Xylene o-Xylene		.203 2,220 281 2,780 760		0,9 1.0 1.0 1.2 0,9	
Total BTEX		6,240			

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery						
	Fluõrobenzene	92.0 %						
	1,4-difluorobenzene	99.3 %						
	Bromochlorobenzene	95.5 %						

References Method 5030B, Purge and Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: Mudge LS #22

Analyst

Review

envirotech Analytical Laboratory

EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client: Sample ID: Laboratory Number: Chain of Custody No: Sample Matrix: Preservative: Condition:	Blagg/BP 95 BGT 5-pt @ -7' 53320 8841 Soil Cool Intact	Project # Date Reported: Date Sampled: Date Received: Date Extractéd: Date Analyzed: Analysis Requested:	94034-0010 03-11-10 03-09-10 03-10-10 03-10-10 03-11-10 8015 TPH					
Parameter		Concentration (mg/Kg)	Det. Limit (mg/Kg)					
Gasoline Rănge (C5	÷ C10)	524	0.2 0.1					
Diesel Range (C10 -	Ç28)	592						
Total Petroleum Hyd	rocarbons	1,120	0.2					

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: Mudge LS #22

Analyst

Review



EPA METHOD 418.1 TOTAL PETROLEUM HYROCARBONS QUALITY ASSURANCE REPORT

Çlient: Sample ID: Laboratory Number: Sample Mätrix; Preșervative; Condition:		QA/QC QA/QC 03-10-TPH_QA/C Freön-113 N/A N/A	IC 53308	Project #: Date Reported Date Sampled Date Analyzed Date Extracted Analysis Need	: 1: . 3: .	N/A Q3-10-10 N/A Q3-10-10 Q3-10-10 TRH
Calibration	I-Cal Datè 03-04-10	C-Cal Date 03-10-10	l-Ćal∖RF: 1,680	⁻ @≝©al <u>R</u> F 1,670	% Difference 0.6%	Âc <u>çêp</u> t, Range +/- 10%
Blank Conce (mc TPH	<u>/(Kg)</u>		Concentration: ND		-Detection Limi 13.4	
Duplicate Conc. TPH	(mg/Kg)		Sample 16.1	Duplicate- 17.4	% Difference, 8.1%	Accept: Range +/- 30%
Spike ^r Conc. (mg TPH	/Kg)	Samples 16.1	2,000	SpikeiRésúlt 1,680	83.3%	Accept Range 80 - 120%

ND = Parameter not detected at the stated detection limit.

Références: Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water and Waste, USERA Storet No. 4551, 1978.

Comments: QA/QC for Samples 53308, 53311 and 53319 - 53322;

Analys

(Miethe <u>x) (i) o eters</u> Review

CHAIN OF CUSTODY RECORD

8041

Client: Project Name / Location:					1	<u>.</u>				ANAL	rsis /	PÅR	AME	TERS														
BLACHE BLACHE BLACHE BLACHE Glient/Address: Sampler: Name:																												
Glient Address:		S					2	BTEX (Method 8021)										·										
J. BLAGE						TPH (Method 8015)	d 80	VQČ (Method 8260)	s	_		сi,																
Client Phòna Nó.: Client No.:					hod	olho	hod	Aeta	Diu		Ϋ́,		3.1)	Ш	,			lõõ	Itac									
			94034-	001	0				Met	N.	Met	RCRA 8 Metals	Cation / Anion		TCLP with H/P		TPH (418.1)	CHLORIDE				Sample Cool	Sample Intact					
Sample No./	Sample		Lab No.			No./Volume of	ne Preservative		o.Nolume Preservat		10.Nolume Prese		L H	L L	Ĕ	jõ,	ЦЧ	atior	RCI	сть С	Н¥Н.	He					gung	duie
Identification	Date	Time			Aatrix	of Containers	HçCl	HộCI, HCI			3	ď	Ö	1			F	0	<u> </u>	<u> </u>	<u> </u>	Š.	<u>ŏ</u>					
45 B.T. 3-266-7	3/9	1521	52200	Solid [.]	Sludge Āqueous	1- 402	.		玉	×)			it.	\times	بر ا		1			1						
3 7 0 12 1	110			Soil	Sludge		-	;		· ·	•				<u></u>				<u>. </u>									
				Solid	Aqueous														1									
	,			Soil Solid	.Šludge Aqueous								-															
				Soil Solid	Sludge Aqueous																							
· · · · · · · · · · · · · · · · · · ·			<u> </u>	Soil Solid	Sludge						1 			<u>.</u>					<u>}</u>	·		-						
· · · · · · · · · · · · · · · · · · ·	·		·,	Soil	Aqueous Sludge			;											<u> </u>									
· · · · · · · · · · · · · · · · · · ·	F) 	Solid Soli	Aqueous Sludge			: ;] †	1	 	1																	
			. <u> </u>	Solid	Aqueous				4					:						1 1								
			1.	Soil Solid	Sludge Aqueous															 -								
				Soil Solid	Sludge Aqueous																	.11						
	й И	-,		Soil Solid	Sludge Aqueous						<u>.</u>					·												
Relinquished by: (Sign	aiurė)	}	1			Time	\ F	Receive	i. ed by:	(Sign	ature)//	. <u> </u>	1	ļ	L	<u> </u>	<u>.l.</u>	<u> </u>	D	ate	Tir	me					
All B	Rich				Date 3/10/10	074	0				Z	/		F	<u>.</u>					3/1	10/10	79	40					
Rélinggished by: (Signature)		1		F	Received by: (Signature)																							
Relinguished by: (Signature)			t			Received by: (Signature)																						
1																	_											
	, , , , , , , , , , , , , , , , , , ,					en	V ľ) (ytic		e	C	h									•							
			579611	چېر. S Hiohwa	v 64 • Farmin								sh-inc	com														

