1625 N. French Dr., Hobbs, NM 88240 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.
For permanent pits submit to the Santa Fe

Form C-144 Revised June 6, 2013

Environmental Bureau office and provide a copy to the appropriate NMOCD District Office. Santa Fe, NM 87505

Operator: BP America Production Company OGRID #:778
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
lease be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground-water or the nvironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
I. Operator: RP America Production Company OCRUP #. 779
·
Facility or well name:Russell Com 1
API Number:3004523582OCD Permit Number:
U/L or Qtr/QtrMSection23 Township28N Range8W County:San Juan
Center of Proposed Design: Latitude36.64292 Longitude107.65657 NAD: □1927 ⋈ 1983
Surface Owner: X Federal X State X Private X Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no
☐ Lined ☐ Unlined Liner type: Thickness mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
<u>Below-grade tank:</u> Subsection I of 19.15.17.11 NMAC Tank B
Volume:21.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☑ Visible sidewalls only ☐ Other _Single walled/double bottomed
Liner type: Thicknessmil
4.
Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school,	homital
institution or church)	nospuai,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7. Signs: Subsection C of 19.15.17.11 NMAC	
☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
<u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	
 □ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. □ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptant material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	
	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the document attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents of the state of	cuments are
attached. □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC □ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	.15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
### Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	-
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Siring Criteria Compiliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	\ \
Within a 100-year floodplain FEMA map	☐ Yes ☐ No☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.1 Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	5.17.11 NMAC of 19.15.17.11 NMAC
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge an	d belief.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment OCD Representative Signature: Approval Date: 3/	
OCD Representative Signature: Approval Date:	7/203
Title: OCD Permit Number:	
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submittee closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please a section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date: 11/16/2	o not complete this
Closure Completion Date:11/10/2	
20. Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closure If different from approved plan, please explain.	sed-loop systems only)

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closur belief. I also certify that the closure complies with all applicable closure require	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Jeff Pasce	Date:February 17, 2015
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Russell Com 1, BGT Tank B (21 bbl) API No. 3004523582 Unit Letter M, Section 23, T28N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - Notice is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT, Tank B	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District 1
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141
Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Name of Company: BP												
						OPERA	TOR		☐ Initi	al Report	\boxtimes	Final Repor
	<u> </u>					Contact: Je:	ff Peace					
			gton, N	M 87401								
Facility Na	me: Russell	Com 1				Facility Typ	e: Natural gas	well				
Surface Ov	vner: Federa	al		Mineral (Owner:	Federal			API No	3004523	582	
				LOCA	ATIO	N OF RE	LEASE					
				Feet from the	North	/South Line	Feet from the	,	Vest Line	County: S	an Juar	า
		Latit	ude3	6.64292		Longitud	e 107.65657_					
				NAT	URE	OF REL	EASE					
Type of Rele	ease: none					-		•	Volume I	Recovered: N	√A	
Source of R	elease: below		21 bbl, T	ank B				ce:	Date and	Hour of Dis	covery	:
Was Immed	iate Notice G		Yes [No 🛛 Not R	equired		Whom?					
						Date and I	lour					
Was a Water	rcourse Reacl		Yes 🗵	No		If YES, Vo	olume Impacting	the Wate	ercourse.			
If a Waterco	urse was Imr	nacted, Describ	e Fully.	*	-							
	т. Б. Т.	,	١									
Danasiha Ca	£Dkl-	and Damadi	al Astis	m Takan * Camali	C 41		the DCT was do			40		
									g removai	to ensure no	SOII IN	npacts from
			,									
Describe Are	ea Affected a	nd Cleanup Ac	tion Tal	cen.* BGT was re	moved	and the area u	nderneath the BC	T was s	ampled. T	he area unde	r the F	BGT was
								31 Mag 5	p.1001. 1	ar va arra		
								F				
		Ω					OIL CON	SERV	ATION	DIVISIO	N	
Signature:	Vol L	House	_									
Signature.	XPV	معر پ				Approved by	Environmental S	necialist				
Printed Nam	e: Jeff Peace					Approved by	Environmentar 5	рестаны	•			
						Approval Date: Expiration			Date:			
E-mail Addr	ess: peace iet	ffrev@bn.com				Conditions of	f Approval:					
	.					_ 0.1.0.10.10.10.0	pp.v.m.			Attached	Ш	
Date: Febru	ary 17, 2015		Phon	e: 505-326-9479								

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	BLA P.O. BOX	GG ENGII		,		2	API #: 30	04523	502
	1.0. 00	•	32-1199	•	VI 0/41	.	TANK ID (if applicble):	A&	3
FIELD REPORT:	(circle one): BGT CONFI	RMATION / RELEA	ASE INVESTIGA	ITION / C	OTHER:		PAGE#: _	1 of	1
SITE INFORMATION		RUSSELL (COM #1				DATE STARTED:	11/02	2/12
QUAD/UNIT: M SEC: 23 TWP:	28N RNG: 8V			_SJ		NM_	DATE FINISHED:		
1/4 -1/4/FOOTAGE: 1,080'S / 815		LEASE TYPE:				DIAN	ENVIRONMENTAL	JC	D
LEASE# NM013860A REFERENCE POINT	PROD. FORMATION:	-				07 050	SPECIALIST(S):		
1) -45 BOT (SW/DB) - A	• WELL HEAD (1	W.H.) GPS COOF 36.642	ю.: 66 X 107.6				GLEL	.EV.: <u>5,8</u> 69', N	
2) 21 BGT (SW/DB) - B	GPS COORD.:		92 X 107.6				ARING FROM W.H.:	123', N	
3)	GPS COORD.:				DI	STANCE/BEA	ARING FROM W.H.:		
	GPS COORD.:				1D	STANCE/BEA	ARING FROM W.H.:		0).74
SAMPLING DATA:	CHAIN OF CUSTODY REC	, ,		HAL					OVM READING (ppm)
1) SAMPLE ID: 45 BGT 5-pt. (2) SAMPLE ID: 21 BGT 5-pt. (2)							3015B / 8021B / - 3015B / 8021B / -		0.6
3) SAMPLE ID:								300.0 (CI)	0.6
4) SAMPLE ID:									
SOIL DESCRIPTION	SOIL TYPE: SAI	ND / SILTY SAND]/ SILT / SILTY	CLAY / C	CLAY / GRA	VEL/OTH	-IER		
	ELLOWISH ORANGE							·	
COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY CONSISTENCY (NON COHESIVE SOILS): LC		1	•				OHESIVE / MEDIUM PLAS / FIRM / STIFF / VEF		
MOISTURE: DRY SLIGHTLY MOIST / WA	ET / SATURATED / SUPER SAT	1					ANATION -		
SAMPLE TYPE: GRAB (COMPOSITE) # DISCOLORATION/STAINING OBSERVED:		— DN -							
	<u> </u>								
ANY AREAS DISPLAYING WETNESS: YES / NO APPARENT EVIDENCE OF A RELEASE O		URRED: YES/N	O EXPLANA	ATION :					
ADDITIONAL COMMENTS:			91 2020						
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <100' N	NA ft. X EAREST WATER SOURCE:	NA ft		ft. EWATER:			IMATION (Cubic Ya D TPH CLOSURE ST		NA pom
SITE SKETCH			PLOT PLA	N circ					
		L	120112					2.5 ppm 00 ppm	RF = 0.52
WOODEN>	(21)				N	- 1 1	_	DATE:	2/12
R.W. $\begin{pmatrix} \hat{x} \\ \hat{x} \\ \hat{x} \end{pmatrix}$	PBGTL T.B. ~ 6'				_	`\	MISCELL	. NOTI	ES
	B.G.					<u>w</u>	1110000	77	
						<u>P(</u> Pk	<u>)#: 81361</u> K: ZEVH0 [,]	IRCT2	
						I —	#: Z2-006 9		
							ermit date(s):	06/14	4/10
						O(Tan	CD Appr. date(s): k OVM = Organ	04/1	<u>7/12</u>
						<u>ID</u>		er million_	
	W.H. ⊕			v	(- S.P.I) AB			
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIO	N DEPRESSION; B.G. = BELOW G	GRADE; B = BELOW; T.H	. = TEST HOLE; ~ =	= APPROX.; '	W.H. = WELL HE	AD;	BGT Sidewalls Vis	sible: Y / N	
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BELO APPLICABLE OR NOT AVAILABLE; SW - SINGLE					WALL; NA - NO	^Т <u>М</u>	agnetic declina	tion: 10°	<u> </u>
TRAVEL NOTES: CALLOUT:			ONSITE:		/12				

Analytical Report

Lab Order 1211359

Date Reported: 11/16/2012

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering Project:

Client Sample ID: 21 BGT 5-pt @ 6'

Russell COM 1 Collection Date: 11/2/2012 12:05:00 PM Matrix: SOIL

Lab ID: 1211359-002 Received Date: 11/8/2012 10:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	E ORGANICS		· · · · · · · · · · · · · · · · · · ·		Analyst: JMP
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	11/12/2012 12:56:34 PM
Surr: DNOP	101	77.6-140	%REC	1	11/12/2012 12:56:34 PM
EPA METHOD 8015B: GASOLINE RA	NGE				Analyst: NSB
Gasoline Range Organics (GRO)	ND	4.8	mg/Kg	1	11/12/2012 2:05:22 PM
Surr: BFB	98.6	84-116	%REC	1	11/12/2012 2:05:22 PM
EPA METHOD 8021B: VOLATILES					Analyst: NSB
Benzene	ND	0.048	mg/Kg	1	11/12/2012 2:05:22 PM
Toluene	ND	0.048	mg/Kg	1	11/12/2012 2:05:22 PM
Ethylbenzene	ND	0.048	mg/Kg	1	11/12/2012 2:05:22 PM
Xylenes, Total	ND	0.097	mg/Kg	1	11/12/2012 2:05:22 PM
Surr: 4-Bromofluorobenzene	104	80-120	%REC	1	11/12/2012 2:05:22 PM
EPA METHOD 300.0: ANIONS					Analyst: JRR
Chloride	ND	1.5	mg/Kg	1	11/9/2012 10:34:43 AM
EPA METHOD 418.1: TPH					Analyst: LRW
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	11/9/2012

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range Ε
- J Analyte detected below quantitation limits
- P Sample pH greater than 2
- Reporting Detection Limit RL

- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- Not Detected at the Reporting Limit ND
- R RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits 2 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#: 1211359 16-Nov-12

Client:

Blagg Engineering

Project:

Russell COM 1

SampType: LCS Sample iD LCS-4749 TestCode: EPA Method 418.1: TPH Client ID: LCSS Batch ID: 4749 RunNo: 6801 Prep Date: 11/8/2012 Analysis Date: 11/9/2012 SeqNo: 196882 Units: mg/Kg Result **PQL** SPK value SPK Ref Val %REC HighLimit %RPD **RPDLimit** Qual Analyte LowLimit 20 Petroleum Hydrocarbons, TR 110 100.0 0 108 80 120

Sample ID LCSD-4749	SampType: LCSD			Tes	TestCode: EPA Method 418.1: TPH					
Client ID: LCSS02	Batch	ı ID: 47	49	F	RunNo: 6	801				
Prep Date: 11/8/2012	Analysis Date: 11/9/2012			Analysis Date: 11/9/2012 SeqNo: 196884 Units: mg/Kg				(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Petroleum Hydrocarbons, TR	110	20	100.0	0	109	80	120	1.21	20	

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

Page 3 of 6

Hall Environmental Analysis Laboratory, Inc.

·WO#:

1211359

16-Nov-12

Client:

Blagg Engineering

Project:

Russell COM 1

Sample ID MB-4767	SampType: MBLK			Tes	TestCode: EPA Method 8015B: Diesel Range Organics						
Client ID: PBS	Batc	h ID: 47	67	F	RunNo: 6833						
Prep Date: 11/9/2012	Analysis [Date: 1 1	1/12/2012	5	SeqNo: 1	97925	Units: mg/k	(g			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Diesel Range Organics (DRO)	ND	10									
Surr: DNOP	9.7		10.00		97.1	77.6	140				
Sample ID LCS-4767	Samp	Type: LC	s	Tes	tCode: E	PA Method	8015B: Dies	el Range (Organics		
Client ID: LCSS	Batc	h ID: 47	67	F	RunNo: 6	833					
Prep Date: 11/9/2012	Analysis [Date: 11	1/12/2012	\$	SeqNo: 1	97938	Units: mg/k	(g			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Diesel Range Organics (DRO)	44	10	50.00	0	88.6	52.6	130				
Surr: DNOP	4.7		5.000		94.0	77.6	140				

Qualifiers:

Sample pH greater than 2

ND Not Detected at the Reporting Limit RPD outside accepted recovery limits Page 4 of 6

Value exceeds Maximum Contaminant Level.

Е Value above quantitation range

Analyte detected below quantitation limits

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

Hall Environmental Analysis Laboratory, Inc.

WO#:

1211359

16-Nov-12

Client:

Blagg Engineering

Project:

Russell COM 1

Sample ID MB-4761	Samp	ype: M	BLK	TestCode: EPA Method 8015B: Gasoline Range											
Client ID: PBS	Batc	Batch ID: 4761 RunNo: 6847													
Prep Date: 11/9/2012	Analysis Date: 11/12/2012			S	SeqNo: 1	98296	Units: mg/F	(g							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Gasoline Range Organics (GRO)	ND	5.0													
Surr: BFB	950		1000		95.0	84	116								
Sample ID LCS-4761	Sampi	ype: LC	s	Test	е										
011 115 1000				_											

Sample ID LCS-4761	SampT	ype: LC	s	TestCode: EPA Method 8015B: Gasoline Range									
Client ID: LCSS	Batch	ID: 47	61	R	RunNo: 6	847							
Prep Date: 11/9/2012	Analysis Date: 11/12/2012			S	SeqNo: 1	98297	Units: mg/Kg						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Gasoline Range Organics (GRO)	25	5.0	25.00	0	0 98.3 74		117						
Surr: BFB	990		1000		99.3	84	116						

Qualifiers:

P Sample pH greater than 2

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

Page 5 of 6

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

B , Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

Hall Environmental Analysis Laboratory, Inc.

WO#:

1211359

16-Nov-12

Client: Project: Blagg Engineering

Russell COM 1

Sample ID MB-4761	SampT	уре: М Е	BLK	TestCode: EPA Method 8021B: Volatiles									
Client ID: PBS	Batch ID: 4761			F	RunNo: 6	847							
Prep Date: 11/9/2012	Analysis E	vsis Date: 11/12/2012 SeqNo: 198437		Units: mg/K									
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit_	Qual			
Benzene	ND	0.050											
Toluene	ND	0.050											
Ethylbenzene	ND	0.050											
Xylenes, Total	ND	0.10											
Surr: 4-Bromofluorobenzene	1.0		1.000		101	80	120						

Sample ID LCS-4761	Samp ⁻	Type: LC	s	TestCode: EPA Method 8021B: Volatiles									
Client ID: LCSS	Batc	h ID: 47	61	F									
Prep Date: 11/9/2012	Analysis Date: 11/12/2012			S	SeqNo: 1	98438	Units: mg/k	(g					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	0.95	0.050	1.000	0	95.1	76.3	117	-					
Toluene	0.96	0.050	1.000	0	96.5	80	120						
Ethylbenzene	0.97	0.050	1.000	0	97.2	77	116						
Xylenes, Total	2.9	0.10	3.000	0	97.1	76.7	117						
Surr: 4-Bromofluorobenzene	1.0		1.000		104	80	120						

Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range Е

Analyte detected below quantitation limits

Sample pH greater than 2

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded

RPD outside accepted recovery limits

ND Not Detected at the Reporting Limit Page 6 of 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE

Sample Log-In Check List

Albuquerque, NM 87105 TEL: 505-345-3975 FAX: 505-345-410; Website: www.hallenvironmental.com

Client Name: BLAGG	Work Order Number: 1211359
Received by/date: ///ci//2	
Logged By: Anne Thorne 11/8/2012 10:00:00	ì
Completed By: Anne Thorne 11/8/2012	aone Ann
Reviewed By:	
Chain of Custody	
1. Were seals intact?	Yes ☐ No ☐ Not Present 🗹
2. Is Chain of Custody complete?	Yes ☑ No ☐ Not Present ☐
3. How was the sample delivered?	Courier
<u>Log In</u>	
4. Coolers are present? (see 19. for cooler specific information)	Yes ☑ No ☐ NÀ ☐
5. Was an attempt made to cool the samples?	Yes ☑ No □ NA □
6. Were all samples received at a temperature of >0° C to 6.0°C	Yes ☑ No ☐ NA ☐
7. Sample(s) in proper container(s)?	Yes ☑ No □
8 Sufficient sample volume for indicated test(s)?	Yes ☑ No □
Are samples (except VOA and ONG) properly preserved?	Yes ☑ No □
10. Was preservative added to bottles?	Yes □ No 🗹 NA □
11. VOA vials have zero headspace?	Yes ☐ No ☐ No VOA Vials ☑
12. Were any sample containers received broken?	Yes ₩ No ₩ # of preserved
13. Does paperwork match bottle labels? (Note discrepancies on chain of custody)	Yes No
14. Are matrices correctly identified on Chain of Custody?	Yes ✓ No ☐ (<2 or >12 unless noted)
15. Is it clear what analyses were requested?	Yes ☑ No ☐ Adjusted?
16. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes ✓ No U
Special Handling (if applicable)	Checked by:
17. Was client notified of all discrepancies with this order?	Yes □ No □ NA 🗹
Person Notified: Date	
By Whom: Via:	eMail Phone Fax In Person
Regarding:	
Client Instructions:	
18. Additional remarks:	•
19. Cooler Information	
Cooler No Temp °C Condition Seal Intact Seal No	Seal Date Signed By
1 1.0 Good Yes	

Chain-of-Custody Record				Turn-Around Time: Standard □ Rush Project Name:								1 A		-	A N N A	et e	•	B. F E			. .	
Client: BLAGG ENGINEERING INC. BP AMERICA Mailing Address: P.O. Box 87									☐ HALL ENVIRONMENTAL ☐ ANALYSIS LABORATORY													
			िक्के अन्तर्भ																			
			Russe	Russeu Com 1					www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109													
P	> > (0):04 F	4513 A	IM 87413	Project #:				Tel. 505-345-3975 Fax 505-345-4107														
Phone:	#: 50	5-63	52-1199	~			-													50.	. 5 . 5	1 1 2
email o				Project Mana	ger:			_							SO ₄)							Γ
QA/QC Package: Standard □ Level 4 (Full Validation)			J. B.	A66			s (8021)	+ TPH (Gas only)	as/Die		İ			PO ₄ ,S(PCB's							
Accred	itation			Sampler: J					PH	B (G	=	£	<u></u>		Š,	3082						ź
□ NEL	AP	□ Othe	r	Onicel Profession Plane Research						015	118.	90.	ַלֻן		ြိ	3 / S		₹	i l			[
	(Type)_			samelestem	oerature is	0		別	BE	æ	N N	g	b	stals	Ž	ide	A	٢	4		İ	∣≿
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type			BTEX + MFBE	BTEX + MTBE	TPH Method 8015B (Gas/Diesel)	TPH (Method 418.1)	EDB (Metho	8310 (PNA or PAH)	RCRA 8 Me	Anions (F,CI,NO ₃ ,NO ₂ ,PO ₄ ,S	8081 Pestic	8260B (VOA)	8270 (Semi-VOA)	CHURIDE			Air Bubbles
11/2/	1145	SOIL	45 BGT 5-P6@5	400	SOUC			<u> </u>		<u>, , , , , , , , , , , , , , , , , , , </u>	لب									_		十
11	120=	i(21 B6+ 5-p606	11	η		-001	χ		^ Х	X								×			
	_																					
										.												
																			\dashv		_	_
		<u> </u>									$-\downarrow$	_	\dashv	\dashv		_			_		ļ	_
							<u> </u>														_	1
W																			_		<u> </u>	1
				Did b	<u> </u>		7:		l										$\perp \perp$			
Date:	Time: 1120	Relinguish	ed by: By	Received by:	Malor	Date	Time 1120		narks LR			υO	: 1	1156	, OC	77	ı					
Date:	Time:	Relinquish	ed by:	Received by:	h h	Date	Time	PA	٠.				:≥	EV Q	H (5).	1B0 -	T 7	2				
11/12	<u> </u>	1 7 00	WILL WALLES	1 00	in-	7//00	110/00	1.6/	<u>(0,</u>	nta.	c* :	<u>275</u>	F	<i>r</i> &	-ACE	<u>-</u>						

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

June 4, 2012

Bureau of Land Management Mark Kelly 1235 La Plata Hwy Farmington, NM 87401

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: RUSSELL COM 001

Dear Mark Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about June 2, 2012. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

9DULRE

Surface Coordinator/Business Security Representative

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

June 11, 2012

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

RUSSELL COM 001 API 30-045-23582 (M) Section 23 – T28N – R08W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 21 bbl. BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Buddy Shaw BP Environmental Advisor

(505) 320-0401



