District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application CEIVED
Type of action: Below grade tank registration
Permit of a pit or proposed alternative method  FEB 1 8 2015
US-25590 Closure of a pit, below-grade tank, or proposed alternative method  Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below grade tank,
or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
1.
Operator: BP America Production Company OGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Price Com 5E
API Number:3004525590OCD Permit Number:
U/L or Qtr/QtrL Section11 Township28N Range8W County:San Juan
Center of Proposed Design: Latitude36.67267 Longitude107.65499 NAD: □1927 ⋈ 1983
Surface Owner: ⊠ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment
2.
Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary:  Drilling  Workover
Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no
Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other
☐ String-Reinforced
Liner Seams:  Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☒ Visible sidewalls only ☐ Other _Single walled/double bottomed
Liner type: Thickness mil
4
Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
☐ Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6.  Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7. Signer Subsection C of 10.15.17.11 NIMAC	
Signs: Subsection C of 19.15.17.11 NMAC  ☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
<u>Variances and Exceptions</u> :  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:  Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance.	ntable source
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	prante source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.	☐ Yes ☐ No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	☐ Yes ☐ No
Society; Topographic map	
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).	☐ Yes ☐ No
- Topographic map; Visual inspection (certification) of the proposed site	
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
<ul> <li>Within 300 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	•
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
10.  Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11.  Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached.	cuments are
<ul> <li>□ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>□ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC</li> <li>□ A List of wells with approved application for permit to drill associated with the pit.</li> <li>□ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC</li> </ul>	.15.17.9 NMAC
Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.    Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC   Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC   Climatological Factors Assessment   Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC   Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC   Quality Control/Quality Assurance Construction and Installation Plan   Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC   Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan   Gil Field Waste Stream Characterization   Monitoring and Inspection Plan   Erosion Control Plan   Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached.  □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	attached to the
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	□ Vas □ Na
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe	
Name (Print): Title:	<del> </del>
Signature: Date:	
e-mail address:Telephone:	· .
18.  OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature: Approval Date: 3/19/  Title: OCD Permit Number:	12015
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date:12/19/2012_	
20.  Closure Method:  Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo ☐ If different from approved plan, please explain.	op systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please incomark in the box, that the documents are attached.  □ Proof of Closure Notice (surface owner and division) □ Proof of Deed Notice (required for on-site closure for private land only) □ Plot Plan (for on-site closures and temporary pits) □ Confirmation Sampling Analytical Results (if applicable) □ Waste Material Sampling Analytical Results (required for on-site closure) □ Disposal Facility Name and Permit Number □ Soil Backfilling and Cover Installation □ Re-vegetation Application Rates and Seeding Technique □ Site Reclamation (Photo Documentation) □ On-site Closure Location: Latitude36.67267 Longitude107.65499 NAD: □19	

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirements.	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature:	Date:February 17, 2015
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

# BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

### BELOW-GRADE TANK CLOSURE PLAN

# Price Com 5E BGT Tank A (95 bbl) API No. 3004525590 Unit Letter L, Section 11, T28N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

### General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
  - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
  - Notice is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows:

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT, Tank A	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	53

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.** 

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.

    Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Form C-141

Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Release Notificat	ion and Corrective A	Action
	<b>OPERATOR</b>	☐ Initial Report ⊠ Final Repor
Name of Company: BP	Contact: Jeff Peace	
Address: 200 Energy Court, Farmington, NM 87401	Telephone No.: 505-326-9	479
Facility Name: Price Com 5E	Facility Type: Natural gas	well
Surface Owner: Federal Mineral Own	er: Federal	API No. 3004525590
LOCATI	ION OF RELEASE	
	orth/South Line Feet from the 1,230	East/West Line   County: San Juan   West
<b>Latitude</b> 36.67267	Longitude107.65499	
NATUF	RE OF RELEASE	
Type of Release: none	Volume of Release: N/A	Volume Recovered: N/A
Source of Release: below grade tank – 95 bbl, Tank A	Date and Hour of Occurren	ce: Date and Hour of Discovery:
Was Immediate Notice Given? ☐ Yes ☐ No ☒ Not Require	red If YES, To Whom?	
By Whom?	Date and Hour	
Was a Watercourse Reached? ☐ Yes ☒ No	If YES, Volume Impacting	the Watercourse.
If a Watercourse was Impacted, Describe Fully.*		
	•	
Describe Cause of Problem and Remedial Action Taken.* Sampling o the BGT. Soil analysis resulted in TPH, BTEX and chloride below sta		
·		
Describe Area Affected and Cleanup Action Taken.* BGT was remov	red and the area underneath the RO	GT was sampled. The area under the RGT was
backfilled and compacted and is still within the active well area.	ed and the area underneam the Bo	or was sampled. The area under the BOT was
determined and sompassed and is some warm the determined with an en-		
I hereby certify that the information given above is true and complete		
regulations all operators are required to report and/or file certain release		
public health or the environment. The acceptance of a C-141 report by should their operations have failed to adequately investigate and remove		
or the environment. In addition, NMOCD acceptance of a C-141 repo		
federal, state, or local laws and/or regulations.		
<b>A</b> O	OIL CON	SERVATION DIVISION
Signature: Off Peace		
Signature.	Approved by Environmental S	Specialist.
Printed Name: Jeff Peace	Approved by Environmental s	specialist.
Title: Field Environmental Coordinator	Approval Date:	Expiration Date:
E-mail Address: peace.jeffrey@bp.com	Conditions of Approval:	Attached
Date: February 17, 2015 Phone: 505-326-9479		

<sup>\*</sup> Attach Additional Sheets If Necessary

CLIENT: BP	BLAG P.O. BOX 8		-		API #:	04525590 A, <del>B, C</del>
FIELD REPORT:	(circle one): BGT CONFIRM	MATION / RELEA	SE INVESTIGATION	/ OTHER:	PAGE #: _	<b>1</b> of <b>1</b>
SITE INFORMATION QUAD/UNIT: L SEC: 11 TWP:	1: <u>SITE NAME: <b>PF</b></u> <b>28N</b> RNG: <b>8W</b>		_	J st. NM	DATE STARTED:  DATE FINISHED:	12/04/12
1/4 -1/4/FOOTAGE: 1,340'S / 1,23 LEASE#: SF078390	80'W NW/SW PROD. FORMATION: DI	_	FEDERAL STA ELKHO CTOR: MBF - F	TE / FEE / INDIAN RN R. RENICK	ENVIRONMENTAL SPECIALIST(S):	JCB
REFERENCE POINT  1) 95 BGT (SW/SB) - A		•	D.: 36	6.67247 X 107.655	GL EL	EV: <u>5,932'</u> 100', N56E
2) -21 BGT (SW/DB) - B	GPS COORD.:		33 X 107.654	00	EARING FROM W.H.:	78', S49E
3) <b>21 BGT (SW//SB) - C</b>	GPS COORD.:		2 <del>9 X 107.655</del> 4	40	EARING FROM W.H.:	108', S52VV
4)	GPS COORD.:				EARING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECO	RD(S) # OR LAB U	SED:	IALL		OVM READING
1) SAMPLE ID: 95 BGT (A) 5-pt. (	·	1010=140		2 LAB ANALYSIS: 418	1 8015 8021 30	(ppm)
2) SAMPLE ID: 21 BGT (B) 5-pt. (	_	1010 1140	SAMPLETIME: 130	_	.1, <del>8015, 8021, 3</del> 6	
3) SAMPLE ID: 21 BGT (C) 3-pt. (	<u> </u>		SAMPLETIME: 124		1, 8015, 8021, 30	
4) SAMPLE ID:	_		SAMPLE TIME:			
SOIL DESCRIPTION	· COULTYPE: CAN	DI CILTY CAND	/ CILT / CILTV CL /	AY / CLAY / GRAVEL / O	TUED	
	LOWISH ORANGE		/ SILI / SILI I CLA	AT / CLAT / GRAVEL / O		
COHESION (ALL OTHERS): NON COHESIVE   SLIGHTL		COHESIVE	PLASTICITY (CLAYS): N	ON PLASTIC / SLIGHTLY PLASTIC	/ COHESIVE / MEDIUM PLAS	TIC / HIGHLY PLASTIC
CONSISTENCY (NON COHESIVE SOILS): LC			•	IVE CLAYS & SILTS): SOF		
MOISTURE: DRY SLIGHTLY MOIST MOIST / W		RATED	HC ODOR DETE	CTED: YES NO EXP	LANATION	
SAMPLE TYPE: GRAB (COMPOSITE) # DISCOLORATION/STAINING OBSERVED		.   N-				
ANY AREAS DISPLAYING WETNESS: YES NO						
APPARENT EVIDENCE OF A RELEASE C					DEED 04 DOT (0)	OLV OLV OLDEED
ADDITIONAL COMMENTS: ALL BGTs I	N WOODEN CELLARS: 9	<u> 5 BGT (A) - 15 X</u>	15 X 6' DEEP; 21	I BĠ I (B) - 8, X 8, X 2, I	JEEP; 21 BGT (C)	-8 X 8 X 6 DEEP.
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <a href="#">&lt;50'</a>	<b>NA</b> ft. X	NA ft. 2 >1,000' NEAF	X <b>NA</b> ft. REST SURFACE WAT		TIMATION (Cubic Y	
SITE SKETCH			PLOT PLAN	circle: attached OV	M CALIB. READ. = 5	2.0 ppm RE = 0.52
	05 (4)			W CALIB. 12-7-12 OV		<b>2.0</b> ppm RF = 0.52
	95 (A) PBGTL	$\rightarrow (\widehat{\mathbf{x}}\widehat{\mathbf{x}}\widehat{\mathbf{x}})$	@ TII	ME イウンド・ピイ ハバハハー		DATE: <b>12/04/12</b>
	T.B. ~ 7' B.G.	(X)		<b>★</b> □	MISCELL	. NOTES
			WOODEN	N ,	NO: N15163	
W.H	1		WOODEN R.W.	11"	79416	002
				[ -	PK: <b>ZEVH0</b>	1BGT2
				l -	PJ#: <b>Z2-006</b>	
				-	Permit date(s):	06/14/10
					OCD Appr. date(s):	06/19/12
					ank OVM = Orgar ID ppm = parts	nic Vapor Meter
					BGT Sidewalls Vi	
				X - S.P.D.	B-BCT-Sidewalle Vi	
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION				ROX.; W.H. = WELL HEAD;	BGT Sidovalle Vi	
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGL				INING WALL; NA - NOT	<u>Magnetic declina</u>	ation: 10°E
TRAVEL NOTES: CALLOUT:		3030		12/04/12 & 12/07/	12	

### **Analytical Report**

### Lab Order 1212436

Date Reported: 12/19/2012

# Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 95 BGT (A) 5-pt @ 7'

**Project:** Price COM 5E

**Collection Date:** 12/7/2012 1:31:00 PM

**Lab ID:** 1212436-003

Matrix: SOIL

Received Date: 12/11/2012 10:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANGI	ORGANICS				Analyst: <b>MMD</b>
Diesel Range Organics (DRO)	ND	9.9	mg/Kg	1	12/12/2012 6:48:06 AM
Surr: DNOP	91.4	72.4-120	%REC	1	12/12/2012 6:48:06 AM
EPA METHOD 8015B: GASOLINE RA	NGE				Analyst: NSB
Gasoline Range Organics (GRO)	ND	4.6	mg/Kg	1	12/13/2012 4:26:08 PM
Surr: BFB	89.7	84-116	%REC	1	12/13/2012 4:26:08 PM
EPA METHOD 8021B: VOLATILES					Analyst: <b>NSB</b>
Benzene	ND	0.046	mg/Kg	1	12/13/2012 4:26:08 PM
Toluene	ND	0.046	mg/Kg	1	12/13/2012 4:26:08 PM
Ethylbenzene	ND	0.046	mg/Kg	1	12/13/2012 4:26:08 PM
Xylenes, Total	ND	0.092	mg/Kg	1	12/13/2012 4:26:08 PM
Surr: 4-Bromofluorobenzene	96.5	80-120	%REC	1	12/13/2012 4:26:08 PM
EPA METHOD 300.0: ANIONS					Analyst: <b>JRR</b>
Chloride	53	7.5	mg/Kg	5	12/14/2012 10:42:18 AM
EPA METHOD 418.1: TPH					Analyst: LRW
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	12/13/2012

### Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

P Sample pH greater than 2

RL Reporting Detection Limit

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

S Spike Recovery outside accepted recovery limits 9 3 of 8

# **OC SUMMARY REPORT**

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1212436

19-Dec-12

Client:

Blagg Engineering

Project:

Price COM 5E

Sample ID 1212385-002AMS

SampType: MS

TestCode: EPA Method 300.0: Anions

Client ID: **BatchQC** 

Batch ID: 5277

RunNo: 7529

Prep Date: 12/14/2012 Analysis Date: 12/14/2012 PQL

7.5

SeqNo: 218489

Units: mg/Kg

Analyte

Result

SPK value SPK Ref Val

%REC

130

15.00 123.2

Lowl imit 67.6 64.4

TestCode: EPA Method 300.0: Anions

HighLimit %RPD 117

**RPDLimit** Qual

Chloride

Sample ID 1212385-002AMSD

BatchQC

SampType: MSD Batch ID: 5277

RunNo: 7529

%REC

Prep Date: 12/14/2012 Analysis Date: 12/14/2012

SeqNo: 218490

Units: mg/Kg

Analyte

Client ID:

**RPDLimit** Qual

Chloride

130

15.00 7.5

66.0 123.2

64.4

LowLimit

HighLimit

%RPD

Client ID:

PBS

Prep Date: 12/14/2012

SampType: MBLK

TestCode: EPA Method 300.0: Anions

117

0.179 20

Sample ID MB-5277

Result

Batch ID: 5277 Analysis Date: 12/14/2012

PQL

RunNo: 7529

Units: mg/Kg

Analyte

Result PQL SeqNo: 218495

ND

SPK value SPK Ref Val

15.00

SPK value SPK Ref Val

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD **RPDLimit**  Qual

Chloride

1.5

TestCode: EPA Method 300.0: Anions

LowLimit

Sample ID LCS-5277 Client ID:

LCSS

SampType: LCS Batch ID: 5277

RunNo: 7529

Prep Date: 12/14/2012

Analysis Date: 12/14/2012

1.5

SeqNo: 218496

%REC

95.0

Units: mg/Kg

HighLimit

110

%RPD

Qual

Analyte Chloride

Sample ID 1212436-001AMS

Result

Result

Result

14

14

TestCode: EPA Method 300.0: Anions

Client ID:

SampType: MS

RunNo: 7529

Prep Date:

21 BGT (B) 5-pt @ 6' 12/14/2012

Batch ID: 5277

90

Units: mg/Kg

Analysis Date: 12/14/2012 PQL

SeqNo: 218498

**RPDLimit** 

**RPDLimit** 

Qual

Analyte Chloride

15.00 2.430

SPK value SPK Ref Val

Н

15.00

SPK value SPK Ref Val %REC LowLimit HighLimit %RPD

Sample ID 1212436-001AMSD

SampType: MSD

64.4

TestCode: EPA Method 300.0: Anions

Qual

Client ID: Prep Date: 12/14/2012 Analyte

21 BGT (B) 5-pt @ 6'

Batch ID: 5277

**PQL** 

7.5

Analysis Date: 12/14/2012

SeqNo: 218499

2.430

%REC 79.2

RunNo: 7529

LowLimit 64.4 Units: mg/Kg HighLimit 117

%RPD 0.210 **RPDLimit** 20

Chloride

Qualifiers: Value exceeds Maximum Contaminant Level.

Value above quantitation range E

Analyte detected in the associated Method Blank

ND Not Detected at the Reporting Limit Page 4 of 8

Analyte detected below quantitation limits Sample pH greater than 2

Holding times for preparation or analysis exceeded

RPD outside accepted recovery limits

# **OC SUMMARY REPORT**

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1212436

19-Dec-12

Client:

Blagg Engineering

Project:

Price COM 5E

Sample ID MB-5244

SampType: MBLK

TestCode: EPA Method 418,1: TPH

Client ID:

PBS

Prep Date: 12/12/2012

Batch ID: 5244

RunNo: 7478

Analysis Date: 12/13/2012

SeaNo: 216786

Units: mg/Kg

**RPDLimit** 

Result **PQL** 

20

SPK value SPK Ref Val %REC LowLimit

HighLimit

%RPD

Qual

Petroleum Hydrocarbons, TR Sample ID LCS-5244

Prep Date: 12/12/2012

Sample ID LCSD-5244

Client ID: LCSS02

Client ID: LCSS

ND

SampType: LCS Batch ID: 5244

TestCode: EPA Method 418.1: TPH

%RPD

Analyte

Analysis Date: 12/13/2012 **PQL** 20

SPK value SPK Ref Val

%REC 97.4

RunNo: 7478

SeqNo: 216787

LowLimit

HighLimit 120

Units: mg/Kg

**RPDLimit** 

Qual

Petroleum Hydrocarbons, TR

Result

Result

97

SampType: LCSD Batch ID: 5244

TestCode: EPA Method 418.1: TPH

RunNo: 7478

SeqNo: 216788

Units: mg/Kg

HighLimit

120

Analyte

Prep Date: 12/12/2012

Analysis Date: 12/13/2012

SPK value SPK Ref Val %REC LowLimit

80

%RPD **RPDLimit** 

Qual

20

Petroleum Hydrocarbons, TR

20

100.0

100.0

96.1

1.32

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits

Sample pH greater than 2

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded

RPD outside accepted recovery limits

Not Detected at the Reporting Limit

ND

Page 5 of 8

# QC SUMMARY REPORT

# Hall Environmental Analysis Laboratory, Inc.

Result

46

4.1

10

WO#:

%RPD

**RPDLimit** 

Qual

1212436

19-Dec-12

Client:

Analyte

Surr: DNOP

Diesel Range Organics (DRO)

Blagg Engineering

Project:

Price COM 5E

Sample ID MB-5212	SampType: MBLK	Tes	stCode: EPA Method	8015B: Diesel	Range (	Organics	
Client ID: PBS	Batch ID: 5212	F	RunNo: <b>7421</b>				
Prep Date: 12/11/2012	Analysis Date: 12/11/	2012	SeqNo: <b>215171</b>	Units: mg/Kg	I		
Analyte	Result PQL SPI	K value SPK Ref Val	%REC LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND 10						
Surr: DNOP	9.9	10.00	99.2 72.4	120			
Sample ID LCS-5212	SampType: LCS	Tes	tCode: EPA Method	8015B: Diesel	Range (	Organics	
Client ID: LCSS	Batch ID: 5212	F	RunNo: <b>7421</b>				
Prep Date: 12/11/2012	Analysis Date: 12/11/	2012	SegNo: <b>215172</b>	Units: mg/Kg	1		

%REC

91.4

81.1

LowLimit

47.4

72.4

HighLimit

122

120

SPK value SPK Ref Val

50.00

5.000

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits

P Sample pH greater than 2

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

R RPD outside accepted recovery limits

Page 6 of 8

# **QC SUMMARY REPORT**

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1212436

19-Dec-12

Client:

Blagg Engineering

Project:	Price CC	OM 5E														
Sample ID	MB-5216	Samp1	Гуре: <b>М</b> Е	BLK	TestCode: EPA Method 8015B: Gasoline Range											
Client ID:	PBS	Batcl	Batch ID: <b>5216</b>			RunNo: 7	477									
Prep Date:	12/11/2012	Analysis D	Date: 12	2/13/2012	SeqNo: <b>217182</b> U			Units: mg/k	nits: mg/Kg							
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Gasoline Rang	e Organics (GRO)	ND	5.0													
Surr: BFB		930		1000		93.5	. 84	116								
Sample ID LCS-5216 SampType: LCS TestCode: EPA Method 8015B: Gasoline Range																
Client ID:	LCSS	Batcl	h ID: <b>52</b>	16	RunNo: <b>7477</b>											
Prep Date:	Date: 12/11/2012 Analysis Date: 12/13/2012				5	SeqNo: 2	17183	Units: mg/k								
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Gasoline Range	e Organics (GRO)	22	5.0	25.00	0	87.5	74	117								
Surr: BFB		970		1000		97.1	84	116		<u>-</u>						
Sample ID	1212436-002AMS	Samp1	уре: М	3	Tes	TestCode: EPA Method 8015B: Gasoline Range										
Client ID:	21 BGT (C) 5-pt (	<b>@ 6'</b> Batch	n ID: <b>52</b>	16	RunNo: <b>7477</b>											
Prep Date:	12/11/2012	Analysis D	)ate: 12	2/13/2012	SeqNo: 217190 Units: mg/Kg											
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Gasoline Range	e Organics (GRO)	21	4.9	24.63	0	86.2	70	130								
Surr: BFB		930		985.2		94.2	. 84	116								
Sample ID 1212436-002AMSD SampType: MSD TestCode: EPA Method 8015B: Gasoline Range																
Client ID:	21 BGT (C) 5-pt (	<b>@ 6'</b> Batcl	h ID: <b>52</b>	16	F	RunNo: 7	477									
Prep Date:	12/11/2012	Analysis E	Date: 12	2/13/2012	\$	SeqNo: 2	17191	Units: mg/k	(g							
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual					
Gasoline Range	e Organics (GRO)	21	4.9	24.61	0	84.4	70	130	2.16	22.1						
Surr: BFB		920		984.3		93.3	84	116	0	0						

### Qualifiers:

R RPD outside accepted recovery limits

Page 7 of 8

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

P Sample pH greater than 2

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

# **QC SUMMARY REPORT**

# Hall Environmental Analysis Laboratory, Inc.

3.0

1.1

0.10

3.000

1.000

WO#:

1212436

19-Dec-12

Client:

Blagg Engineering

Project:

Xylenes, Total

Surr: 4-Bromofluorobenzene

Price COM 5E

Sample ID MB-5216	SampT	уре: <b>М</b> Е	BLK	TestCode: EPA Method 8021B: Volatiles									
Client ID: PBS	Batch	n ID: <b>52</b>	16	F	RunNo: 7								
Prep Date: 12/11/2012	Analysis Date: 12/13/2012			\$	SeqNo: 2	17333	Units: mg/Kg						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	ND	0.050											
Toluene	ND	0.050											
Ethylbenzene	ND	0.050											
Xylenes, Total	ND	0.10											
Surr: 4-Bromofluorobenzene	1.0		1.000	_	103	80	120						
Sample ID LCS-5216	SampT	ype: <b>LC</b>	s	TestCode: EPA Method 8021B: Volatiles									
Client ID: LCSS	Batch	n ID: <b>52</b>	16	RunNo: <b>7477</b>									
Prep Date: 12/11/2012	Analysis D	ate: 12	2/13/2012	9	SeqNo: 2	17334	Units: mg/K	(g					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	0.99	0.050	1.000	0	98.9	76.3	117						
Toluene	1.0	0.050	1.000	0	99.6	80	120						
Ethylbenzene	1.0	0.050	1.000	0	101	77	116						

Sample ID 1212436-001AMS	TestCode: EPA Method 8021B: Volatiles									
Client ID: 21 BGT (B) 5-pt @ 6' Batch ID: 5216				F						
Prep Date: 12/11/2012 Analysis Date: 12/13/2012			8	SeqNo: 2	ζg					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.94	0.047	0.9461	0	99.6	67.2	113			
Toluene	0.95	0.047	0.9461	0	100	62.1	116			
Ethylbenzene	0.97	0.047	0.9461	0	102	67.9	127			
Xylenes, Total	2.9	0.095	2.838	0	101	60.6	134			
Surr: 4-Bromofluorobenzene	0.97		0.9461		102	80	120			

0

101

105

Sample ID 1212436-001AMS	Tes	tCode: E	PA Method	8021B: Vola	tiles					
Client ID: 21 BGT (B) 5-pt	RunNo: <b>7477</b>									
Prep Date: 12/11/2012	Analysis Date: 12/13/2012			5	SeqNo: 2	17359	Units: mg/k	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.94	0.047	0.9470	0	99.0	67.2	113	0.456	14.3	
Toluene	0.94	0.047	0.9470	0	99.7	62.1	116	0.294	15.9	
Ethylbenzene	0.96	0.047	0.9470	0	102	67.9	127	0.405	14.4	
Xylenes, Total	2.9	0.095	2.841	0	101	60.6	134	0.255	12.6	
Surr: 4-Bromofluorobenzene	0.95		0.9470		100	80	120	0	0	

### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH greater than 2

B Analyte detected in the associated Method Blank

76.7

80

117

120

- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

RPD outside accepted recovery limits

Page 8 of 8



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105

TEL: 505-345-3975 FAX: 505-345-410', Website: www.hallenvironmental.com

# Sample Log-In Check List

Client Name: Work Order Number: 1212436 Received by/date: Logged By: Michelle Garcia 12/11/2012 10:00:00 AM Completed By: Michelle Garcia 12/11/2012 11:32:43 AM Reviewed By: 12/11/2012 Chain of Custody Yes No No Not Present ✓ 1 Were seals intact? Yes 🗸 No 🗌 Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Courier Log In Yes 🗸 No 🗌 NA 🗆 4. Coolers are present? (see 19. for cooler specific information) Yes 🗸 No 🗌 NA 🗍 5. Was an attempt made to cool the samples? Yes 🗹 No 🗌 NA 🗌 6 Were all samples received at a temperature of >0° C to 6.0°C Yes V No 7. Sample(s) in proper container(s)? Yes V No 8 Sufficient sample volume for indicated test(s)? Yes ✓ No 🗆 9 Are samples (except VOA and ONG) properly preserved? Yes No V NA 🗌 10. Was preservative added to bottles? Yes 🗌 No 🗀 No VOA Vials 🗹 11 VOA vials have zero headspace? Yes D No 🗹 12. Were any sample containers received broken? # of preserved Yes 🗹 No 🗌 13. Does paperwork match bottle labels? bottles checked (Note discrepancies on chain of custody) for pH: Yes V No 14. Are matrices correctly identified on Chain of Custody? (<2 or >12 unless noted) Yes 🗸 No 🗌 Adjusted? 15. Is it clear what analyses were requested? Yes 🗹 No 🗌 16. Were all holding times able to be met? (If no, notify customer for authorization.) Checked by: Special Handling (if applicable) Yes 🗌 No 🗍 NA 🗹 17. Was client notified of all discrepancies with this order? Person Notified: Date: By Whom: eMail Phone Fax In Person Regarding: **Client Instructions:** 18. Additional remarks: 19. Cooler Information Temp °C | Condition | Seal Intact | Seal No | Seal Date Good

Chain-of-Custody Record			Turn-Around			a ap	HALL ENVIRONMENTAL														
Client: BLAGG ENGINEERING INC.				Standard □ Rush																	
	Z.P. A			Project Name				ANALYSIS LABORATORY													
BP AMIERICA  Mailing Address: P.O. Box 87			PRICE	COM SE	<del>7</del>	www.hallenvironmental.com															
Walling Address. P.O. Box 87						4901 Hawkins NE - Albuquerque, NM 87109															
BLOOMFIELD, NM 87413			Project #:			Tel. 505-345-3975 Fax 505-345-4107 Analysis Request															
Phone #: 505 - 632-1199									¥,		A	naly	/sis	Req	uest						
email or Fax#:			Project Mana	iger:			<u> </u>	sel)					(†C								
QA/QC Package:  ☐ Level 4 (Full Validation)				J	BLAGE I. BLAG		TiviB's (8021)	(Gas o	as/Die					PO <sub>4</sub> ,S(	PCB's						
Accredi				Sampler:	I_ BLAG	6	7.월	표	9)		=			0,	082						
□ NEL	AP	□ Othe	Y	On Icel Tax	<b>V</b> Yes	ie No. 3		+	156	<u>8</u>	4.	ΑH		) <sub>3</sub> , h	8/8		F	w			닏
□ EDD (Type)			Samplestem	perature 1913			BE	88	d 4	g Q	민	tals	Ň,	ides	2	9	10/0			ځ	
Date	Time	Matrix	Sample Request ID		Preservative Type		BTEX + MTBE	BTEX + MTBE + TPH (Gas only)	TPH Method 8015B (Gas/Diesel)	TPH (Method 418.1)	EDB (Method 504.1)	8310 (PNA or PAH)	RCRA 8 Metals	Anions (F,CI,NO3,NO2,PO4,SO4)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	CHLORIDE			Air Bubbles (Y or N)
12/11	137		21 BGT(B)	11 11-	6000		<u> </u>	_Ш_			Ш.	-w	ш.	4		- 8	80			$\dashv$	+
77/12	1367	र्ज्ञ⊍ा∟	5-Pt 6 6	18# *	COUL	-00	<u> </u>											<del>-</del>	<del>-</del>		$+\!\!\!-$
1/12	1241	501L	21 Bit(r) 5-p=e6	11	,, \.(	-002	X		×	×					$\dashv$			<del>\</del>	-		
11	1332	16	95 BUT (A) 5-P+ @ 7	'n	K	-203	X		X	X					}			X	$\Box$		T
											-										
												Ī									
			·				+													+	
			· · · · · · · · · · · · · · · · · · ·				+				-							$\dashv$		_	+-
<u> </u>		-				-	+									_					<del> </del>
							+													_	$\bot$
																			$\bot$		
																					十
Date: Time: Relinquished by:  2/10/2017 1257 July Buy		Received by:	Received by: Date Time				Remarks: GRO & DRO ON BOIS B														
		Muste	7 BILL BP: WORKORDER: N1516352 PAYKEY: ZEVHOLBGTZ																		
Date:	Time:	Refinquish	ed by:	Received by Date Time				PAYKEY: ZEVHOIRGTO.													
1/1/12	2/11/12/1647 / Mustre Wallers			THE T	- izlu	12 1000	C	eN	+Ae	T:	Jē	:FF	Pè	-40	_ ح		<u>- 1</u>				
,	necessarv.	semples sub	mitted to Hall Environmental may be sub-	contracted to other ac	credited laboratorie	s. This serves as notice of thi	is possib	oility.	Any sı	b-cont	racted	data	will be	clearl	y notal	ted on	the ar	alytica	al repor	t.	





BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

July 3, 2012

Bureau of Land Management Mark Kelly 1235 La Plata Hwy Farmington, NM 87401

## VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: PRICE COM 005E

Dear Mark Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about July 10, 2012. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

Surface Coordinator/Business Security Representative

BP America Production Company

### **BP America Production Company**

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

# SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

July 18, 2012

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

PRICE COM 005E API 30-045-25590 (M) Section 11 – T28N – R08W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close two 21 bbl. BGT's that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Buddy Shaw BP Environmental Advisor

(505) 320-0401



