District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe
Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application ECEIVED
Type of action: Below grade tank registration
Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method MAR 0 2 2015
Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID #:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Fields LS 9
API Number:3004521176OCD Permit Number:
U/L or Qtr/QtrGSection34Township32NRange11WCounty:San Juan
Center of Proposed Design: Latitude36.94350 Longitude107.97356 NAD: □1927 ⋈ 983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Plan Per 19.15.17. Closure followed BP approved standard Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Plan.
□ Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management Low Chloride Drilling Fluid □ yes □ no Plan.
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:95.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other _Double walled/double bottomed; side walls not visible
Liner type: Thickness mil
4. Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
☐ Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) ☐ Screen ☐ Netting ☐ Other	
Monthly inspections (If netting or screening is not physically feasible)	
Trionany inspections (it noting is sevening is not physically reasons)	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☐ Signed in compliance with 19.15.16.8 NMAC	
8.	
<u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:	
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. ☐ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC	
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept	otable source
material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.	☐ Yes ☐ No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.	Yes No
NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	∐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☐ No
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)	☐ Yes ☐ No
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	L Tes L No
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	☐ Yes ☐ No
Society; Topographic map	
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).	Yes No
- Topographic map; Visual inspection (certification) of the proposed site	
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;	☐ Yes ☐ No
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole,	☐ Yes ☐ No
or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No					
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image						
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site						
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Temporary Pit Non-low chloride drilling fluid						
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No					
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Permanent Pit or Multi-Well Fluid Management Pit						
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No					
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 Natractions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	NMAC 15.17.9 NMAC					
n. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC						
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the docattached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number: or Permit Number:	.15.17.9 NMAC					

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
Proposed Closure: 19.15.17.13 NMAC	
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	la id November 1 Die
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Fig. 15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland.	
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
16.	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan of the check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 3/24/ Title: Compliance Office OCD Permit Number:	See front page 2015
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	
☐ Closure Completion Date:2/24/2009	
^{20.} Closure Method: ☑ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo☐ If different from approved plan, please explain.	op systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please incomark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number	dicate, by a check

22.						
Operator Closure Certification:						
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.						
Name (Print):Jeff Peace	Title: Field Environmental Coordinator					
Signature: Jeff Pesco	Date:February 26, 2015					
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479					

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Fields LS 9 API No. 3004521176 Unit Letter G, Section 34, T32N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	0.018
TPH	US EPA Method SW-846 418.1	100	19.2
Chlorides	US EPA Method 300.0 or 4500B	250 or background	80

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and has been reclaimed since the well was plugged and abandoned.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT has been reclaimed since the well was plugged and abandoned.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT has been reclaimed since the well was plugged and abandoned.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT has been reclaimed since the well was plugged and abandoned.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation since the well was plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

* District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Form C-141
Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	catio	n and Co	orrective A	ction				
						OPERA'	ГOR		Initi	al Report	\boxtimes	Final Repor
Name of Co	A					Contact: Jeff Peace						
Address: 200 Energy Court, Farmington, NM 87401			Telephone 1	No.: 505-326-94	479							
Facility Na	me: Fields	LS 9				Facility Typ	e: Natural gas	well				
Surface Ow	ner: Fede	ral		Mineral (Owner:	Federal			API No	. 3004521	176	
				LOC	ATIO	N OF REI	LEASE					
Unit Letter	Section	Township	Range	Feet from the		/South Line	Feet from the	Fast/W	est Line	County: Sa	an Imar	1
G	34	32N	11W	1,810	North		1,540	East	est Line	County. St	iii Juai	·
		Lati	tude 3	6.94350		Longitud	e 107.97356					
			_		TIDE	OF REL						
Type of Rele	ase none			NAI	UKE	_	Release: N/A		Volume I	Recovered: N	J/A	
		w grade tank –	95 bbl				Iour of Occurrence			Hour of Dis		
Was Immedi						If YES, To			z are are	11041 01 210	oo reign	5
			Yes	No Not R	equired							
By Whom?						Date and H	Iour					
Was a Water	course Rea			Car		If YES, Vo	olume Impacting t	the Water	course.			
☐ Yes ⊠ No												
If a Watercou	ırse was Im	pacted, Descri	be Fully.*	k								
Describe Cau	ise of Probl	em and Remed	dial Action	n Taken.* Sampli	ng of th	e soil beneath	the BGT was do	ne during	removal	to ensure no	soil im	pacts from
				and chloride below								
Describe Are	a Affected	and Cleanup A	ction Tak	en.* BGT was re	moved a	and the area u	nderneath the BG	T was sa	mpled. Ti	ne area unde	r the B	GT was
backfilled an	d compacte	d and has been	reclaime	d since the well w	vas plug	ged and aband	doned.					
I hereby certi	fy that the	information gi	ven above	is true and comp	lete to t	he best of my	knowledge and u	inderstand	that purs	uant to NMO	OCD rt	ales and
regulations a	ll operators	are required to	report an	d/or file certain r	elease n	otifications ar	nd perform correct	ctive actio	ns for rele	eases which	may en	ndanger
				e of a C-141 repo								
				investigate and retance of a C-141								
		ws and/or regu		tance of a C-141	report u	oes not renev	e the operator or	responsio	ility for Co	mphanee w	itii aiiy	other
-	0	Λ					OIL CON	SERVA	ATION	DIVISIO	N	
6'	Jalk.	1000									_	
Signature:	YIV	y de										
Printed Name	e: Jeff Peac	e				Approved by	Environmental S	pecialist:				
Title: Field E	nvironmen	tal Coordinato	r			Approval Dat	e:	E	xpiration l	Date:		
E-mail Addre	ess: peace.io	effrey@bp.con	n			Conditions of	Approval:					
										Attached		
Date: Februa	ry 26, 201:	5	Phone	e: 505-326-9479								

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	P.O	. BOX 87,	ENGINE BLOOMI 05) 632-1	FIELD,	6, INC. NM 87413	3	API#: 30	04521176
FIELD REPOR	BGT (oth		TEMP. PIT CLOSU	JRE / RELEA	SE INVESTIGATION		PAGE No:	1 of 1
SITE INFORMA	TION:	SITE NAME: FI	ELDS LS	#9			DATE STARTED:	02/19/09
QUAD/UNIT: G SEC:	34 TWP: 321	RNG: 11W	PM: NM	CNTY: SJ	ST: NM		DATE FINISHED:	
QTR-QTR/FOOTAGE: SV					STATE / FEE /		ENVIRONMENTAL SPECIALIST:	NV
LEASE#:					KEYSTONE (
REFERENCE P 5PC-TB@6'		WELL HEAD (M OORD.:		RD.: 0 X 107.9		X 107.973	ARING FROM W.H.:	€V: 6,139' 26', N80E
2)	GPS C	OORD.:				DISTANCE/BE	ARING FROM W.H.:	
3)	GPS C	OORD.:				DISTANCE/BE	ARING FROM W.H.:	
4)	GPS C	OORD.:				DISTANCE/BE	ARING FROM W.H.:	
5)	GPS C	OORD.:				DISTANCE/BE	ARING FROM W.H.:	
LAB INFORMAT	TON:	CHAIN OF CUS	TODY RECORI	D(S):	5947	,	418.1 / 8021	B / 4500B
1) SAMPLE ID: 5PC-	TB @ 6'		02/19/09	SAMPLE TIME:	1024	LAB ANALYSIS:	TPH / BTEX	
2) SAMPLE ID:		SAMPLE DATE:		SAMPLE TIME:		LAB ANALYSIS:		
3) SAMPLE ID:		SAMPLE DATE:		SAMPLE TIME:		LAB ANALYSIS:		
4) SAMPLE ID:		SAMPLE DATE:		SAMPLE TIME:		LAB ANALYSIS:		
5) SAMPLE ID:		SAMPLE DATE:		SAMPLE TIME:		LAB ANALYSIS:		
COHESION (ALL OTHERS): NON COHESIVE CONSISTENCY (NON COHESIVE PLASTICITY (CLAYS): NON PLASTIC / SLIGHT DENSITY (COHESIVE CLAYS & SIL MOISTURE: DRY / SLIGHTLY MOIST ADDITIONAL COMMENTS:	SOILS): LOOSE/FI LYPLASTIC/COHESIVE/ TS): SOFT/FIRM/ MOIST WET/SATU SITE IS BEING F	IRM / DENSE / VERY MEDIUM PLASTIC) HIGHL STIFF VERY STIFF IRATED / SUPER SATU PREP. FOR PLUG	/ DENSE YPLASTIC / HARD JRATED AND ABANDO	SAMPLE NMENT.	R DETECTED: YE TYPE: GRAB/ LECTED SAMPLE	OMPOSITE]- #		5 D, COMPETENT.
EXCAVATION DIMENSIONS (if	applicable):	NA ft. X	NA ft.	. x 1	NA ft.	cubic yards ex	xcavated (if applicable):	NA
SITE SKETCH								T PLAN Attached
							OCD: 36.94	
				/	PBGTL	1		97367
		P&A	Ð	XXX				
		MARKER		X				
				1	S.P.D.	- 1-		
						-		
						-		
NATES. DOT DELONIODADE TANK	D - EVOA (ATION DECC	DECCIONI D.O DELOIM		TII _ TEOT 1101	E ADDDOV			
NOTES: BGT = BELOW-GRADE TANK; E T.B. = TANK BOTTOM; PBGTL =								
TO AL FIL MOTEO		9/09 - MORN		ONSITE		- MORN.		

BEI1005E.SKF

1

revised: 11/21/08



EPA METHOD 418.1 TOTAL PETROLEUM **HYDROCARBONS**

Client:	Blagg/BP	Project #:	94034-0010
Sample ID:	5 PC-TB @ 6'	Date Reported:	02-24-09
Laboratory Number:	49031	Date Sampled:	02-19-09
Chain of Custody No:	5947	Date Received:	02-19-09
Sample Matrix:	Soil	Date Extracted:	02-23-09
Preservative:	Cool	Date Analyzed:	02-23-09
Condition:	Intact	Analysis Needed:	TPH-418.1

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

19.2

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

Fields LS #9, 5 PT. Composite Sample.

Mistle of Weller Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg/BP	Project #:	94034-0010
Sample ID:	5PC-TB @ 6'	Date Reported:	02-23-09
Laboratory Number:	49031	Date Sampled:	02-19-09
Chain of Custody:	5947	Date Received:	02-19-09
Sample Matrix:	Soil	Date Analyzed:	02-23-09
Preservative:	Cool	Date Extracted:	02-20-09
Condition:	Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene	ND 6.5 1.5 4.2 6.2	0.9 1.0 1.0 1.2 0.9	
Total BTEX	18.4		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery					
	Fluorobenzene	99.0 %					
	1,4-difluorobenzene	99.0 %					
	Bromochlorobenzene	99.0 %					

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Fields LS #9, 5 PT. Composite Sample.

Analyst

mistinen Water



Chloride

Project #: Client: Blagg/BP 94034-0010 Sample ID: 5 PC-TB @ 6' Date Reported: 02-24-09 Date Sampled: Lab ID#: 49031 02-19-09 Sample Matrix: Soil Date Received: 02-19-09 Date Analyzed: 02-24-09 Preservative: Cool Condition: Intact Chain of Custody: 5947

Parameter

Concentration (mg/Kg)

Total Chloride

80

Reference:

U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes", 1983. Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments:

Fields LS #9 5 Pt. Composite Sample.

Mister Walles
Review



EPA METHOD 418.1 TOTAL PETROLEUM **HYROCARBONS** QUALITY ASSURANCE REPORT

Detection Limit

N/A Project #: QA/QC Client: 02-24-09 Date Reported: QA/QC Sample ID: Date Sampled: N/A 02-23-TPH.QA/QC 49020 Laboratory Number: 02-23-09 Freon-113 Date Analyzed: Sample Matrix: 02-23-09 Date Extracted: N/A Preservative: TPH Analysis Needed: N/A Condition: % Difference Accept. Range C-Cal RF: I-Cal RF: Calibration I-Cal Date C-Cal Date

7.3% +/- 10% 1,500 1,610 02-23-09 02-13-09

Concentration Blank Conc. (mg/Kg) 16.8 ND TPH

% Difference Accept. Range Duplicate Sample Duplicate Conc. (mg/Kg) +/- 30% 180 6.3% 192 TPH

Spike Result % Recovery Accept Range Spike Added Sample Spike Conc. (mg/Kg) 80 - 120% 84.9% 2,000 1,860 192 **TPH**

ND = Parameter not detected at the stated detection limit.

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water References:

and Waste, USEPA Storet No. 4551, 1978.

QA/QC for Samples 49020 - 49023, 49031, 49033, 49081, 49084 and 49088. Comments:

Jones Bo

Christin of Walters



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A	Project #:	N/A
Sample ID:	02-23-BT QA/QC	Date Reported:	02-23-09
Laboratory Number:	49034	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	02-23-09
Condition:	N/A	Analysis:	BTEX

Calibration and	I-Cal RF:	C-Cal RF:	%Diff.	Blank	Detect.
Detection Limits (ug/L)		Accept. Rang	ge 0 - 15%	Conc	Limit
Benzene	6.7198E+004	6.7333E+004	0.2%	ND	0.1
Toluene	4.7914E+004	4.8010E+004	0.2%	ND	0.1
Ethylbenzene	4.0838E+004	4.0920E+004	0.2%	ND	0.1
p,m-Xylene	9.2788E+004	9.2974E+004	0.2%	ND	0.1
o-Xylene	4.0567E+004	4.0648E+004	0.2%	ND	0.1

Duplicate Conc. (ug/Kg)	Sample	Duplicate	%Diff.	Accept Range	Detect. Limit
Benzene	3.5	3.8	8.6%	0 - 30%	0.9
Toluene	51.0	47.9	6.1%	0 - 30%	1.0
Ethylbenzene	117	109	7.1%	0 - 30%	1.0
p,m-Xylene	92.2	89.9	2.5%	0 - 30%	1.2
o-Xylene	55.2	49.7	10.0%	0 - 30%	0.9

Spike Conc. (ug/Kg)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Range
Benzene	3.5	50.0	56.5	106%	39 - 150
Toluene	51.0	50.0	104	103%	46 - 148
Ethylbenzene	117	50.0	169	101%	32 - 160
p,m-Xylene	92.2	100	196	102%	46 - 148
o-Xylene	55.2	50.0	99.1	94.2%	46 - 148

ND - Parameter not detected at the stated detection limit.

References

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

QA/QC for Samples 49020 - 49023, 49025 - 49026, 49031, 49033, 49034 and 49037.

Analyst

Review

CHAIN OF CUSTODY RECORD

5047

Client: Project Name / Location FIELD 5 L.					: 5 # 9					ANALYSIS / PARAMETERS																
Client Address: Sampler Name:							8015)	(18051)	8260)	S						(4500 B)	5		PLE							
Client Phone No.:			Client No.:	10.: 94034 -0010			Client No.:			Ample No./Volume Preservative of HgQ, HQ 2044			BTEX (Method 8021)	VOC (Method 8260)	RCRA 8 Metals	Cation / Anion		TCLP with H/P		TPH (418.1)	CHLORIDE(4			T. COMP.	Sample Cool	Sample Intact
Sample No./ Identification	Sample Date	Time	Lab No.		ample Vlatrix	No./Volume of Containers	Pres HgCl ₂	HCI (5	ive HAL	BTEX	VOC (RCRA	Cation	RCI	TCLP	PAH	TPH	CHLO			S S	Samp	Samp			
5PC-TB @ 6'	2/19/03	1024	49031	Solid	Sludge Aqueous	1-402			/	/	1						/	\checkmark			/	V	4			
				Soil Solid	Sludge Aqueous																					
				Soil Solid	Sludge Aqueous																					
				Soil Solid	Sludge Aqueous																					
				Soil Solid	Sludge Aqueous																					
				Soil Solid	Sludge Aqueous																					
				Soil Solid	Sludge Aqueous																					
				Soil Solid	Sludge Aqueous																					
				Soil Solid	Sludge Aqueous																					
				Soil Solid	Sludge Aqueous																					
Relinquished by: (Signature)	ature)				Date 2/19/2	7516		Received by: (Signature)						1	ate 9/09		me 76									
Relinquished by: (Sign					14 //			lece	ived by	(Sigr	ature)				7					, - /					
Relinquished by: (Signature)					F	lece	ived by: (Signature)																			
					FOL	IDOS			1 11	10																

ENVIROTECH INC.

5796 U.S. Highway 64 • Farmington, NM 87401 • Tel 505-632-0615



