<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-144 Revised June 6, 2013 For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
12705 Proposed Alte	<u>Pit, Below-Grade Tank, or</u> ernative Method Permit or Closure F	Plan Application
Type of action: Below Permi Government Below Permi Closu Modi Closu or proposed alternative met Instructions: Please submit of	v grade tank registration it of a pit or proposed alternative method re of a pit, below-grade tank, or proposed alternati fication to an existing permit/or registration re plan only submitted for an existing permitted on hod one application (Form C-144) per individual pit, below	FEB 2 5 2015 r non-permitted pit, below-grade tank, grade tank or alternative request
environment. Nor does approval relieve the operator	ot relieve the operator of liability should operations result i of its responsibility to comply with any other applicable go	n pollution of surface water, ground water or the overnmental authority's rules, regulations or ordinances.
^{1.} Operator: BP America Production Compa	ny OGRID #:	778
Address:200 Energy Court, Farmington	n, NM 87401	
Facility or well name:Jones LS 1A		20
API Number:3004522833	OCD Permit Number:	
	Township29NRange8WCo	
Center of Proposed Design: Latitude36.6	57951Longitude107.64285	NAD: 1927 🛛 1983
Surface Owner: 🛛 Federal 🗌 State 🗌 Private [Tribal Trust or Indian Allotment	
Lined Unlined Liner type: Thickness	MAC P&A Multi-Well Fluid Management MINTERSON MULTI-Well Fluid Management MULTION MULTI-Well Fluid Management MULTION MULTI-WELLING MULTI-WEL	her
3		
Below-grade tank: Subsection I of 19.15.1		
	pe of fluid:Produced water	
	□ Visible sidewalls, liner, 6-inch lift and automatic ov	
	walls only 🛛 Other _Double walled/double bott il 🔲 HDPE 🗌 PVC 🔲 Other	
4.		

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Q.

21

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (*Required if located within 1000 feet of a permanent residence, school, hospital, institution or church*)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify_

.

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	□ Yes □ No □ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	Yes No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	Yes No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
 Within a 100-year floodplain. (Does not apply to below grade tanks) FEMA map 	🗌 Yes 🗌 No
Below Grade Tanks	
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	Yes No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	□ Yes □ No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Permanent Pit or Multi-Well Fluid Management Pit	
 Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	
 initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC 	suments are
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.10 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

4

12. Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC	documents are
13. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Alternative Proposed Closure Method: Waste Excavation and Removal On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
^{15.} <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	□ Yes □ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	
	2.4

٠

.

•	
 adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality; Written approval obtained from the municipality 	Yes No
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	Yes No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain. - FEMA map	Yes No
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plate by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards canned Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	11 NMAC 15.17.11 NMAC
17. Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) Image: Consure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Image: Consure Plan (only) OCD Conditions (see attachment) Title: Image: Consure Plan (only) OCD Permit Number:	12015
 ^{19.} Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. 	
20. Closure Method: Waste Excavation and Removal □ On-Site Closure Method □ Alternative Closure Method □ Waste Removal (Closed-lo If different from approved plan, please explain.	op systems only)
21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please ind mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude 36.67951 Longitude -107.64285 NAD: 192	dicate, by a check 7 ⊠ 1983

Operator Closure Certification:

*

. 22.

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print):	Jeff Peace	Title: Field Environmental Coordinator
Signature:	Jeff Pasce	Date:February 24, 2015
e-mail address:p	eace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Jones LS 1A API No. 3004522833 Unit Letter J, Section 35, T29N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B. D. or E of 19.15.17.17 NMAC.

General Closure Plan

- BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. No notice was made due to misunderstanding of the BGT notice requirements at that time.
- BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 No notice was made due to misunderstanding of the BGT notice requirements at

No notice was made due to misunderstanding of the BGT notice requiremen that time.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

- BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.
 - All equipment associated with the BGT has been removed.
- 6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	61
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.
- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

.

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division ain D 1220 South St Em

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

20 S St Francis Dr. Santa Fa NIM 97505	outh St. Francis I a Fe, NM 87505	Dr.				
Release Notificat	tion and Corr	ective A	ction			
	OPERATO	R	🗍 Ini	tial Report	Fir	nal Repor
Name of Company: BP	Contact: Jeff Pe			1		1
Address: 200 Energy Court, Farmington, NM 87401	Telephone No.:	505-326-94	179			
Facility Name: Jones LS 1A	Facility Type: N	latural gas	well			
Surface Owner: Federal Mineral Own	er: Federal	Federal API No. 3004522833				
	ION OF RELEA	ASE		10. 500 1522		
Unit Letter Section Township Range Feet from the N		et from the	East/West Line East	County: S	an Juan	
Latitude36.67951	Longitude	107.64285_				
NATU	RE OF RELEAS	SE				
Type of Release: none	Volume of Rele			Recovered: N		
Source of Release: below grade tank – 95 bbl	Date and Hour		ce: Date an	d Hour of Dis	covery:	
Was Immediate Notice Given?	If YES, To Wh	om?				
By Whom?	Date and Hour					
Was a Watercourse Reached? □ Yes ☑ No	If YES, Volum	e Impacting	the Watercourse.			
f a Watercourse was Impacted, Describe Fully.* Describe Cause of Problem and Remedial Action Taken.* Sampling of						
he BGT. Soil analysis resulted in TPH, BTEX and chloride below st Describe Area Affected and Cleanup Action Taken.* BGT was remove packfilled and compacted and is still within the active well area.				The area unde	er the BGT	was
hereby certify that the information given above is true and complete egulations all operators are required to report and/or file certain relea ublic health or the environment. The acceptance of a C-141 report b hould their operations have failed to adequately investigate and reme or the environment. In addition, NMOCD acceptance of a C-141 report ederal, state, or local laws and/or regulations.	ase notifications and per by the NMOCD marked rediate contamination the	erform correct d as "Final R nat pose a thr	etive actions for re- eport" does not re- eat to ground wat	eleases which elieve the open er, surface wa	may endan rator of liab iter, human	ger vility health
Signature: Jeff Pence	_	OIL CONSERVATION DIVISION				
Printed Name: Jeff Peace	Approved by Env	ironmental S	pecialist:			
itle: Field Environmental Coordinator	Approval Date:		Expiratio	n Date:		
E-mail Address: peace.jeffrey@bp.com	Conditions of App	proval:		Attached		
Date: February 24, 2015 Phone: 505-326-9479						
ttach Additional Sheets If Necessary						

CLIENT: BP	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	API #: 3004522833
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER:	PAGE #: <u>1</u> of <u>1</u>
QUAD/UNIT: J SEC: 35 TWP: 1/4 -1/4/FOOTAGE: 1,450'S / 1,74		
REFERENCE POINT	WELL HEAD (W.H.) GPS COORD.: 36.67934 X 107.643 GPS COORD.: 36.67951 X 107.64285 DISTANC GPS COORD.: DISTANC DISTANC GPS COORD.: DISTANC DISTANC	304 GL ELEV.: 5,980'
SAMPLING DATA: 1) SAMPLE ID: <u>5PC-TB@6'C (95</u> 2) SAMPLE ID:	CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL BGT) SAMPLE DATE: 04/20/12 SAMPLE TIME: LAB ANALYSIS: 418 SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS: LAB ANALYSI	OVM READING (ppm) NA
4) SAMPLE ID:	SAMPLE DATE:	
SOIL COLOR: MODER COHESION (ALL OTHERS): NON COHESIVE SLIGHTL CONSISTENCY (NON COHESIVE SOILS): CO MOISTURE: DRY (SLIGHTLY MOIST MOIST) W SAMPLE TYPE: GRAB (COMPOSITE) # 0F PTS. DISCOLORATION/STAINING OBSERVED	DOSE FIRM / DENSE / VERY DENSE DENSITY (COHESIVE CLAYS & SILTS): 3 ET / SATURATED / SUPER SATURATED HC ODOR DETECTED: YES NO E 5	STIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC SOFT / FIRM / STIFF / VERY STIFF / HARD EXPLANATION -
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA ft. X NA ft. X NA ft. EXCAVATION	I ESTIMATION (Cubic Yards) : NA
SITE SKETCH	PBGTL T.B. ~ 6' B.G. PLOT PLAN circle: attached N BERM BERM	MOCCD TPH CLOSURE STD: 100 ppm OVM CALIB. READ. = NA ppm OVM CALIB. GAS = NA ppm TIME: NA am/pm DATE: MISCELL. NOTES WO - N1550064 PO - 77378 PK - ZSCHWLLBGT PK - Z2-00690-C
WELL HEAD NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAV T.B. = TANK BOTTOM; PBGTL = PREVIOUS	STEEL CONTAINMENT RING ATTION DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H. = TEST HOLE; ~ = APPROX.; BELOW-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING WALL; ; SW- SINGLE WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM; DB - DOUBLE BOTTOM. 04/19/12 - After. ONSITE: 04/20/12 - Morn.	Permit Date: 06/14/10 OCD Appr. Date: 02/28/12 Tank ID A BGT Sidewalls Visible: Y / (N)/ NA BGT Sidewalls Visible: Y / N / NA Magnetic declination: 10° E

Analytical Report Lab Order 1204944 Date Reported: 5/1/2012

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering Client Sample ID: 5PC-TB @ 6' (95 BGT) Project: Jones LS #1A Collection Date: 4/20/2012 10:45:00 AM Lab ID: 1204944-001 Matrix: SOIL Received Date: 4/25/2012 8:00:00 AM Analyses Result RL Qual Units DE Date Analyzed

Analyses	Result	RL Qu	al Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RAN	GE ORGANICS				Analyst: JMP
Diesel Range Organics (DRO)	ND	9.8	mg/Kg	1	4/26/2012 1:44:47 PM
Surr: DNOP	98.5	77.4-131	%REC	1	4/26/2012 1:44:47 PM
EPA METHOD 8015B: GASOLINE R	ANGE				Analyst: NSB
Gasoline Range Organics (GRO)	ND	4.9	mg/Kg	1	4/28/2012 12:49:26 AM
Surr: BFB	97.5	69.7-121	%REC	1	4/28/2012 12:49:26 AM
EPA METHOD 8021B: VOLATILES					Analyst: NSB
Benzene	ND	0.049	mg/Kg	1	4/28/2012 12:49:26 AM
Toluene	ND	0.049	mg/Kg	1	4/28/2012 12:49:26 AM
Ethylbenzene	ND	0.049	mg/Kg	1	4/28/2012 12:49:26 AM
Xylenes, Total	ND	0.097	mg/Kg	1	4/28/2012 12:49:26 AM
Surr: 4-Bromofluorobenzene	88.5	80-120	%REC	1	4/28/2012 12:49:26 AM
EPA METHOD 300.0: ANIONS					Analyst: BRM
Chloride	ND	1.5	mg/Kg	1	4/27/2012 5:25:29 AM
EPA METHOD 418.1: TPH					Analyst: JMP
Petroleum Hydrocarbons, TR	61	20	mg/Kg	1	4/27/2012

Qualifiers:

- */X Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RL Reporting Detection Limit

Page 1 of 6

Client: Blagg Engineering Project: Jones LS #1A

.

.

Sample ID: MB-1703	SampType: MBLK	TestCode: EPA Method	300.0: Anions	
Client ID: PBS	Batch ID: 1703	RunNo: 2420		
Prep Date: 4/26/2012	Analysis Date: 4/27/2012	SeqNo: 67248	Units: mg/Kg	
Analyte	Result PQL SPK value S	PK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Chloride	ND 1.5			
Sample ID: LCS-1703	SampType: LCS	TestCode: EPA Method	300.0: Anions	
Sample ID: LCS-1703 Client ID: LCSS	SampType: LCS Batch ID: 1703	TestCode: EPA Method RunNo: 2420	300.0: Anions	
	1 31		300.0: Anions Units: mg/Kg	
Client ID: LCSS	Batch ID: 1703	RunNo: 2420 SeqNo: 67251		RPDLimit Qual

Qualifiers:

- */X Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- R RPD outside accepted recovery limits

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RL Reporting Detection Limit

WO#: **1204944** *01-May-12* .

WO#: **1204944**

01-May-12

	agg Engineering nes LS #1A					
Sample ID: MB-1698	SampType: MBLK	Те	stCode: EPA Method	d 418.1: TPH		
Client ID: PBS	Batch ID: 1698		RunNo: 2422			
Prep Date: 4/26/2012	Analysis Date: 4/27/201	2	SeqNo: 67237	Units: mg/Kg		
Analyte	Result PQL SPK	value SPK Ref Val	%REC LowLimit	HighLimit %RF	PD RPDLimit	Qual
Petroleum Hydrocarbons, TR	ND 20					
Sample ID: LCS-1698	SampType: LCS	Те	stCode: EPA Method	d 418.1: TPH		
Client ID: LCSS	Batch ID: 1698		RunNo: 2422			
Prep Date: 4/26/2012	Analysis Date: 4/27/201	2	SeqNo: 67238	Units: mg/Kg		
Analyte	Result PQL SPK	alue SPK Ref Val	%REC LowLimit	HighLimit %RF	PD RPDLimit	Qual
Petroleum Hydrocarbons, TR	98 20 1	00.0 0	97.6 87.8	115		
Sample ID: LCSD-1698	SampType: LCSD	Те	stCode: EPA Method	1 418.1: TPH		
Client ID: LCSS02	Batch ID: 1698		RunNo: 2422			
Prep Date: 4/26/2012	Analysis Date: 4/27/201	2	SeqNo: 67239	Units: mg/Kg		
Analyte	Result PQL SPK	alue SPK Ref Val	%REC LowLimit	HighLimit %RF	PD RPDLimit	Qual
Petroleum Hydrocarbons, TR	95 20 1	00.0 0	95.0 87.8	115 2.	78 8.04	

Qualifiers:

- */X Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- R RPD outside accepted recovery limits

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RL Reporting Detection Limit

.

WO#: 1204944

01-May-12

22	agg Engineering nes LS #1A										
Sample ID: MB-1688	TestCode: EPA Method 8015B: Diesel Range Organics										
Client ID: PBS	Batch ID	: 1688	F	RunNo: 23	375						
Prep Date: 4/25/2012	Analysis Date	4/26/2012	S	SeqNo: 66	6012	Units: mg/K	g				
Analyte	Result P	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Diesel Range Organics (DRO) Surr: DNOP	ND 10	10 10.00		101	77.4	131					
Sample ID: LCS-1688	SampType	E LCS	Test	tCode: EF	A Method	8015B: Diese	l Range C	Organics			
Client ID: LCSS	Batch ID	1688	R	RunNo: 23	375						
Prep Date: 4/25/2012	Analysis Date	4/26/2012	SeqNo: 66091		Units: mg/K	g					
Analyte	Result P	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Diesel Range Organics (DRO)	51	10 50.00	0	102	62.7	139					
Surr: DNOP	4.6	5.000		92.5	77.4	131					

Qualifiers:

- */X Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- R RPD outside accepted recovery limits

- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RL Reporting Detection Limit

WO#: 1204944

01-May-12

Client: Blagg	Engineering										
Project: Jones I	LS #1A										
Sample ID: MB-1687	SampType: MBLK	TestCode: EPA Method 8015B: Gasoline Range									
Client ID: PBS	Batch ID: 1687	RunNo: 2396									
Prep Date: 4/25/2012	Analysis Date: 4/26/2012	SeqNo: 67176	Units: mg/Kg								
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Q	ual							
Gasoline Range Organics (GRO)	ND 5.0										
Surr: BFB	930 1,000	92.6 69.7	121								
Sample ID: LCS-1687	SampType: LCS	TestCode: EPA Method	8015B: Gasoline Range								
Client ID: LCSS	Batch ID: 1687	RunNo: 2396									
Prep Date: 4/25/2012	Analysis Date: 4/26/2012	SeqNo: 67177	Units: mg/Kg								
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Q	ual							
Gasoline Range Organics (GRO)	29 5.0 25.00	0 116 98.5	133								
Surr: BFB	1,000 1,000	104 69.7	121								
Sample ID: MB-1721	SampType: MBLK	TestCode: EPA Method	8015B: Gasoline Range								
Client ID: PBS	Batch ID: 1721	RunNo: 2448									
Prep Date: 4/27/2012	Analysis Date: 4/29/2012	SeqNo: 68072	Units: %REC								
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Q	ual							
Surr: BFB	1,000 1,000	101 69.7	121								
Sample ID: LCS-1721	SampType: LCS	TestCode: EPA Method	8015B: Gasoline Range								
Client ID: LCSS	Batch ID: 1721	RunNo: 2448									
Prep Date: 4/27/2012	Analysis Date: 4/29/2012	SeqNo: 68073	Units: %REC								
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD RPDLimit Qu	ual							
Surr: BFB	1,100 1,000	107 69.7	121								

.

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

Value above quantitation range Е

- Analyte detected below quantitation limits J
- R RPD outside accepted recovery limits

- В Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
- RL Reporting Detection Limit

Client: Blagg Engineering

Jones LS #1A

Sample ID: MB-1687	Samp	Гуре: МЕ	BLK	Tes	tCode: EF	PA Method	8021B: Volat	tiles		
Client ID: PBS	Batc	h ID: 16	87	F	RunNo: 23	396				
Prep Date: 4/25/2012	Analysis E	Date: 4/	26/2012	S	SeqNo: 67	7197	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	0.050								
Toluene	ND	0.050								
Ethylbenzene	ND	0.050								
Kylenes, Total	ND	0.10								
Surr: 4-Bromofluorobenzene	0.84		1.000		83.9	80	120			
Sample ID: LCS-1687	SampT	ampType: LCS TestCode: EPA Method 8021B: Volatiles								
Client ID: LCSS	Batch	h ID: 168	37	F	RunNo: 23	396				
Prep Date: 4/25/2012	Analysis D	Date: 4/2	26/2012	S	eqNo: 67	7198	Units: mg/K	g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	0.90	0.050	1.000	0	90.5	83.3	107			
Toluene	0.93	0.050	1.000	0	93.1	74.3	115			
Ethylbenzene	0.92	0.050	1.000	0	92.4	80.9	122			
(ylenes, Total	2.8	0.10	3.000	0	91.8	85.2	123			
Surr: 4-Bromofluorobenzene	0.86		1.000		86.4	80	120			
Sample ID: MB-1721	SampT	уре: МВ	LK	Tes	Code: EF	A Method	8021B: Volat	iles		
Client ID: PBS	Batch	n ID: 172	21	R	unNo: 24	48				
Prep Date: 4/27/2012	Analysis D)ate: 4/2	29/2012	S	eqNo: 68	3122	Units: %RE	С		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorobenzene	0.92		1.000		92.4	80	120			
Sample ID: LCS-1721	SampT	ype: LC	S	Tes	Code: EF	A Method	8021B: Volat	iles		
Client ID: LCSS	Batch	n ID: 172	21	R	unNo: 24	48				
Prep Date: 4/27/2012	Analysis D	ate: 4/2	29/2012	S	eqNo: 68	3123	Units: %RE	С		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromofluorobenzene	0.97		1.000		96.8	80	120			

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

Value above quantitation range Е

- Analyte detected below quantitation limits J
- RPD outside accepted recovery limits R

- Analyte detected in the associated Method Blank В
- Holding times for preparation or analysis exceeded Η
- ND Not Detected at the Reporting Limit
- RL Reporting Detection Limit

Project:

ANALYSIS TEL: 505-345-3975	Analysis Laboratory 4901 Hawkins NE uquerque, NM 87105 5 FAX: 505-345-410; allenvironmental.con
Client Name: BLAGG Received by/date: MA 04/25/12	Nork Order Number: 1204944
Logged By: Michelle Garcia 4/25/2012 8:00:00 AM	Milalle Garrie
Completed By: Michellg Garcia 4/25/2012 8:20:22 AM	Mitrells Garries
Reviewed By:	- Januar Gunnar
Chain of Custody	
1. Were seals intact?	Yes 🗌 No 🗍 Not Present 🗹
2. Is Chain of Custody complete?	Yes V No Not Present
3. How was the sample delivered?	Courier
<u>Log In</u>	
4. Coolers are present? (see 19. for cooler specific information)	Yes 🗹 No 🗌 NA 🗌
5. Was an attempt made to cool the samples?	Yes 🗹 No 🗋 NA 🗌
6. Were all samples received at a temperature of $>0^{\circ}$ C to 6.0°C	Yes 🗹 No 🗌 NA 🗌
7. Sample(s) in proper container(s)?	Yes 🗹 No
8. Sufficient sample volume for indicated test(s)?	Yes 🗹 No
9. Are samples (except VOA and ONG) properly preserved?	Yes 🗹 No 🗌
10. Was preservative added to bottles?	Yes 🗌 No 🗹 🛛 NA 🗌
11. VOA vials have zero headspace?	Yes 🗌 No 🗌 No VOA Vials 🗹
12. Were any sample containers received broken?	Yes □ No □ No VOA Vials ♥ Yes □ No ♥
 13. Does paperwork match bottle labels? (Note discrepancies on chain of custody) 	Yes ✔ No
14. Are matrices correctly identified on Chain of Custody?	for pH: Yes ☑ No □ (<2 or >12 unless noted)
15. Is it clear what analyses were requested?	Yes 🗹 No 🗌 Adjusted?
16. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes 🗹 No 🗌 Checked by:
Special Handling (if applicable)	
17. Was client notified of all discrepancies with this order?	Yes No No NA
Person Notified: Date:	
By Whom: Via:	eMail 🔄 Phone 🔄 Fax 📋 In Person
Regarding:	
Client Instructions:	

18. Additional remarks:

4

¥

19. Cooler Information

Cooler No	Temp °C	Condition	Seal Intact	Seal No	Seal Date	Signed By
1	3.6	Good	Not Present			

С	hain-	of-Cus	stody Record	l'urn-Around	l'ime:									NI 3	/TE	20			:N7	-		
Client:	BLAG	G ENGR.	/ BP AMERICA	Standard	Rush														ATO			<i>r</i>
				Project Name	and the second s																	
Mailing A	ddress:	P.O. BO	X 87	JONES LS # 1A 4901 Hawkins NE - Albuquerque, NM																		
		BLOOM	FIELD, NM 87413	Project #: Tel. 505-345-3975 Fax 505-345-																		
Phone #:		(505) 63		-			1	T	21. 30	JJ-3	45-5	Contraction of the local division of the loc	-	Thursday.	Red	COLUMN TWO IS NOT	-					
email or Fax#:		Project Manag	ger:									100										
QA/QC Package:					5 (8021B)	only)	'Diesel)					PO4, SO4)	:B's									
Accreditation:		Sampler:	NELSON VI	ELEZ 910	18	Gas	Gas/					02,1	32 PC						mple			
NELAP Other		On Ice:	X Yes	🖾 No		Hd1	15B (8.1)	14.1)	(H))3, N	/ 808		-				e sai	1		
EDD (Type)			Sample Temp	erature:	3.6		3E + 3	d 80	od 41	od 50	or PA	tals	J, NG	ides	3	-VOA	(0.00		e	osit		
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO.	BTEX + MITI	BTEX + MTBE + TPH (Gas only)	TPH Method 8015B (Gas/Diesel)	TPH (Method 418.1)	EDB (Method 504.1)	8310 (PNA or PAH)	RCRA 8 Metals	Anions (F, Cl, NO3, NO2, PO4,	8081 Pesticides / 8082 PCB's	8260B (VOA)	8270 (Semi-VOA)	Chloride (300.0)		Grab sample	5 pt. composite sample	
4/20/12	1045	SOIL	5PC-TB @ 6' (95 BGT)	4 oz 2	Cool	-001	V		٧	٧								٧			٧	
and a state of the																		-				Г
																					-	Г
						-													1		-	
										-											-	Г
											_									-	-	Г
																		_	-	-	-	F
										-									-		-	F
													-								-	F
							-													-		-
									-											1	_	F
Date:	Time: 1535	Relinguished by:		Received by: Date Time Mustur Walter 4/24/12 1535				Remarks: TPH (8015B) - GRO & DRO ONLY. BILL DIRECTLY TO BP:											L			
Date:	Time:	Relinquishe	ed by:	Received by:	mart	Date Time												7401				
1/24/12 1536 Schust Walter		MulliConuic 04/25/120800 Work Order: N1550064 Paykey: ZSCHWLLBGT								-												

505-947-9900

anter as

BP AMERICA PRODUCTION COMPANY JONES LS 001A API 3004522833 LEASE NMSF079938 1450 FSL 1740 FEL (J) SEC 35 T29N R8W San Juan County ELEV 5980 *LAT 36° 40' 45.588" LONG 107° 38' 34.908"

