<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-144 Revised June 6, 2013 For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
Type of action: Belo 9 Perm 9 Sector State 9 Sector State	hit of a pit or proposed alternative method ure of a pit, below-grade tank, or proposed alternati ification to an existing permit/or registration ure plan only submitted for an existing permitted or	ive method MAR 0 5 2015 r non-permitted pit, below-prade tank, grade tank or alternative request n pollution of surface water, ground water or the
Address:200 Energy Court, Farmingto Facility or well name:Archuleta Gas Co API Number:3004508670 U/L or Qtr/QtrK Section5	any OGRID #:7 on, NM 87401 om A 1 OCD Permit Number: 5 Township29N Range9W Co 75073 Longitude107.80710 Tribal Trust or Indian Allotment	ounty:San Juan
☐ Lined ☐ Unlined Liner type: Thickness ☐ String-Reinforced	MAC P&A Multi-Well Fluid Management Lo mil LLDPE HDPE PVC Oth Volume:bbl	her
Tank Construction material:Steel Secondary containment with leak detection Visible sidewalls and liner Disible side Liner type: Thicknessn	ppe of fluid:Produced water	erflow shut-off med; side walls not visible
Alternative Method: Submittal of an exception request is required.	Exceptions must be submitted to the Santa Fe Environmer	ntal Bureau office for consideration of approval.

23

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (*Required if located within 1000 feet of a permanent residence, school, hospital, institution or church*)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other_

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

- Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.
- Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

o. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.							
General siting							
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	□ Yes □ No □ NA						
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA						
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗌 Yes 🗌 No						
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No						
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No						
Within a 100-year floodplain. (Does not apply to below grade tanks) FEMA map 							
Below Grade Tanks							
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No						
 /ithin 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 							
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)							
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No						

 Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No
 Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	Yes No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
 Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
 10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC 	ouments are
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.10 NMAC Sting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

٠

.

Prospect Closure: P1:517.13 NMAC Instructions: Please complete the applicable baxes, Baxes 14 through 18, in regards to the proposed closure plan. Multi-well Fluid Management Pit Proposed Closure flam Waste Excavation and Removal Below-grade Tank Multi-well Fluid Management Pit Proposed Closure Method: Waste Excavation and Removal On-site Closure theohol (Only for temporary pits and closed-loop systems) Implace Burial On-site Temporary the appropriate requirements or attached. Protocols and Procedures - based upon the appropriate requirements or Subsection C of 19.15.17.13 NMAC Implace Burial requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for flagdds, drilling fluids and drill cuttings) Subsection C of 19.15.17.13 NMAC Sting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each stilling fluids, and filling fluids and drill cuttings) Sting Criteria (regarding on-site closure methods only): 19.15.17.13 NMAC Instructions: Each stilling criteria requirements of Subsection H of 19.15.17.13 NMAC Instructions: Each stilling fluids, and filling fluids, and fill cuttings) Sting Criteria (regarding on-site closure methods only): 19.15.17.13 NMAC Instructions: Each stilling criteria	Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan 	documents are
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.	Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Alternative Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial	luid Management Pit
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 25 feet below the bottom of the buried waste.	Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells NA Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa I Yes No Na Yes No Yes No Yes No Yes No Yes No 	Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency.	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells NA Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Yes No Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 		
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells NA Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Yes No Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 		
lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Yes No - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Yes No Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence Yes No at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Yes No Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No		
 Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	lake (measured from the ordinary high-water mark).	🗌 Yes 🗌 No
at the time of initial application NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes No		🗌 Yes 🗌 No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Yes	at the time of initial application.	🗌 Yes 🗌 No
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 🗌 Yes 🗋 No	Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance		🗌 Yes 🗌 No
	Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

4

*

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No						
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No						
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 							
Within a 100-year floodplain.	Yes No						
- FEMA map	Yes No						
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 							
17. Operator Application Certification:							
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.						
Name (Print): Title:							
Signature: Date:							
e-mail address: Telephone:							
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: ONAL DATE Approval Date: 3/27 Title: Compliance Office OCD Permit Number:	7/2015						
19. <u>Closure Report (required within 60 days of closure completion)</u> : 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report. complete this						
Closure Completion Date:3/17/2014							
20. 20. 20. 20. 20. 20. 20. 20. 20. 20.	op systems only)						

.

.

Operator Closure Certification:

4

22.

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print):Jeff Peace	Title: Field Environmental Coordinator	
Signature: Jeff Peace	Date:March 3, 2015	<u>`</u>
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479	

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Archuleta Gas Com A 1</u> <u>API No. 3004508670</u> <u>Unit Letter K, Section 5, T29N, R9W</u>

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B. D. or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. **Notice is attached.**
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number. **Notice is attached.**
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	3.13
TPH	US EPA Method SW-846 418.1	100	33
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and BTEX and chloride levels were below the stated limits. TPH was only 33 ppm by Method 418.1 but was 218 ppm by Method 8015D. Sampling data is attached.

BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.

- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate a release occurred. The release was addressed through the spill and release guidelines.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and outside the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is outside the active well area. This area will be reclaimed and seeded per landowner request.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is outside the active well area. This area will be reclaimed and seeded per landowner request.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is outside the active well area. This area will be reclaimed and seeded per landowner request.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

~

4

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division

Form C-141 Revised August 8, 2011

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

District IV 1220 S. St. Fran	ncis Dr., Sant	a Fe, NM 8750	5			th St. Franc Fe, NM 875					
			Rele	ease Notifi	catio	n and Co	orrective A	ction			
Name of Company: BP						OPERATOR Initial Report Final Re Contact: Jeff Peace					Final Repor
Address: 200 Energy Court, Farmington, NM 87401						No.: 505-326-94	179				
		leta Gas Cor					be: Natural gas v				
Surface Ow	ner: Priva	te		Mineral (Owner:	Private		API	No. 3004508	3670	
				LOCA	ATIO	N OF RE	LEASE				
Unit Letter K	Section 5	Township 29N	Range 9W	Feet from the 1,510	Nortl Soutl	n/South Line n	Feet from the 1,510	East/West Lin West	ne County:	San Juan	1
		Lat	itude3	6.75073		Longitud	e107.80710_				
				NAT	TURE	OF REL	EASE				
Type of Rele		densate v grade tank –	05 661				Release: unknow		ne Recovered:		1
Source of Re	lease. Delov	v grade tank –	- 95 001			unknown	Iour of Occurrence		nd Hour of Di 11:40 AM	scovery:	: January 13,
Was Immedi	ate Notice (Yes 🛛	No 🗌 Not R	equired						
By Whom? Was a Water	course Read	hed?				Date and H		the Wetersource			
was a water	course recar		Yes 🛛	No		If YES, Volume Impacting the Watercourse.					
Describe Cau the BGT. So Analysis resu	il analysis r	esulted in BT	dial Action EX and ch	n Taken.* Sampli lorides below sta	ing of th indards.	ne soil beneath TPH was onl	the BGT was doi y 33 ppm by Met	ne during remov hod 418.1 but v	val to ensure no vas 218 ppm bj	o soil im y Metho	npacts from d 8015D.
release occur	red and rem	ediation was	completed	en.* BGT was re through the spill claimed and seed	and rel	and the area u ease guideline	nderneath the BG s. The area under	T was sampled r the BGT was	Sampling res backfilled and	ults indi compact	icated a ted and is
regulations al public health should their of or the environ	l operators or the envir operations h nment. In a	are required to conment. The ave failed to a	o report an acceptanc dequately OCD accep	d/or file certain r e of a C-141 repo investigate and r	elease i ort by th emedia	notifications ar ne NMOCD m te contaminati	knowledge and u nd perform correc arked as "Final Ro on that pose a thro e the operator of r	tive actions for eport" does not eat to ground w	releases which relieve the ope ater, surface w	n may en erator of ater, hur	idanger Tiability man health
Signature: OIL CONSERVATION DIVISION											
Printed Name	: Jeff Peace	2				Approved by	Environmental Sj	pecialist:			
Title: Field E	nvironment	al Coordinato	r			Approval Dat	e:	Expirati	on Date:		
E-mail Addre	ess: peace.je	ffrey@bp.com	n			Conditions of	Approval:		Attached	1	
Date: March Attach Addit	1	ets If Necessa)5-326-9479							

	PLACE	NGINEERING, INC.		0004500050			
	P.O. BOX 87, B	13	API #: 3004508670				
	(50		TANK ID (if applicble):				
FIELD REPORT: (circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER: PAGE #: 1 of 1							
SITE INFORMATION	I: SITE NAME: ARCHU	JLETA GC A #1		DATE STARTED: 01/13/14			
QUAD/UNIT: K SEC: 5 TWP:				DATE FINISHED:			
1/4 -1/4/FOOTAGE: 1,510'S / 1,510		EL KHORN		ENVIRONMENTAL SPECIALIST(S): JCB			
		ONTRACTOR: MBF - K. AMBRC					
1) 95 BGT (SW/DB)	- WELL HEAD (W.H.) GPS	6.75073 X 107.80710	7.80687	GL ELEV.: 5,586'			
2)							
				RING FROM W.H.:			
	GPS COORD.:			RING FROM W.H.:			
SAMPLING DATA:				OVM READING			
1) SAMPLE ID: 95 BGT 5-pt. (is: 418.1/8	015B/8021B/300.0 (CI) 0.0			
2) SAMPLE ID:				. ,			
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANALYS	IS:				
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME: LAB ANALYS	ilS:				
SOIL DESCRIPTION	SOIL TYPE: SAND / SILTY SAND	SILT / SILTY CLAY / CLAY / GRAVEL / OTHE	R				
SOIL COLOR: GR				DHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC			
COHESION (ALL OTHERS): NON COHESIVE / SLIGHTL							
CONSISTENCY (NON COHESIVE SOILS): LC MOISTURE: DRY/SLIGHTLY MOIST/MOIST		HC ODOR DETECTED: YES NO EXPLANA	non - Minc	DR			
SAMPLE TYPE: GRAB	¢ OF PTS. 4	ANY AREAS DISPLAYING WETNESS: YES	NO EXPLAN	ATION -			
DISCOLORATION/STAINING OBSERVED: YES /							
APPARENT EVIDENCE OF A RELEASE OBSERVE EQUIPMENT SET OVER RECLAIMED AREA: OTHER:	DAND/OR OCCURRED YES NO EXP						
SOIL IMPACT DIMENSION ESTIMATION	NA ft. X NA	ft. X NA ft. EXCA	VATION EST	IMATION (Cubic Yards) : NA			
DEPTH TO GROUNDWATER: <	EAREST WATER SOURCE: >1,000'			D TPH CLOSURE STD: 100 ppm			
SITE SKETCH	BGT Located : off on sit	te PLOT PLAN circle: atta	ched OVM	CALIB. READ. = 100.3 ppm RF = 1.00			
	то			CALIB. GAS = 100 ppm			
PBGTL	W.H.		N TIME:	12:00 an (pm) DATE: 01/13/14			
T.B. ~ 5' B.G.				MISCELL. NOTES			
	FENCE		W	O: N15165867			
			P	O #:			
	SEPARATOR		PI				
				J#: Z2-006Q0			
	BERM			ermit date(s): 06/14/10 CD Appr. date(s): 04/22/13			
ROAD			Tan	k OVM = Organic Vapor Meter			
B	ТО		A				
	PROD. TANK	X - S.P.D		BGT Sidewalls Visible: Y / N			
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATI		BELOW; T.H. = TEST HOLE; ~ = APPROX.; W.H. = WEL	L HEAD;	BGT Sidewalls Visible: Y / N			
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGL		POINT DESIGNATION; R.W. = RETAINING WALL; NA - TTOM; DB - DOUBLE BOTTOM.	M	agnetic declination: 10° E			
NOTES: GOOGLE EARTH IMAGE		ONSITE: 01/13/14					

*

Analytical Report
Lab Order 1401522

Hall Environmental Analysis Laboratory, Inc.

Date Reported: 1/16/2014 Client Sample ID: 95 BGT -5Pt @ 4'

CLIENT: Blagg Engineering **Project:** Archuleta GC A #1

1401522-001

Lab ID:

Collection Date: 1/13/2014 11:40:00 AM

Matrix: MEOH (SOIL) Received Date: 1/14/2014 10:00:00 AM

Analyses	Result	RL (Qual	Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	E ORGANICS					Analyst	BCN
Diesel Range Organics (DRO)	58	10		mg/Kg	1	1/14/2014 12:39:24 PM	11208
Surr: DNOP	97.7	66-131		%REC	1	1/14/2014 12:39:24 PM	11208
EPA METHOD 8015D: GASOLINE RA	NGE					Analyst	NSB
Gasoline Range Organics (GRO)	160	13		mg/Kg	4	1/14/2014 11:52:03 AM	R16058
Surr: BFB	533	74.5-129	S	%REC	4	1/14/2014 11:52:03 AM	R16058
EPA METHOD 8021B: VOLATILES						Analyst	NSB
Benzene	ND	0.067		mg/Kg	4	1/14/2014 11:52:03 AM	R16058
Toluene	ND	0.13		mg/Kg	4	1/14/2014 11:52:03 AM	R16058
Ethylbenzene	0.33	0.13		mg/Kg	4	1/14/2014 11:52:03 AM	R16058
Xylenes, Total	2.8	0.27		mg/Kg	4	1/14/2014 11:52:03 AM	R16058
Surr: 4-Bromofluorobenzene	136	80-120	S	%REC	4	1/14/2014 11:52:03 AM	R16058
EPA METHOD 300.0: ANIONS						Analyst	JRR
Chloride	ND	30		mg/Kg	20	1/14/2014 3:29:02 PM	11220
EPA METHOD 418.1: TPH						Analyst	JME
Petroleum Hydrocarbons, TR	33	20		mg/Kg	1	1/14/2014 12:00:00 PM	11195

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:	*	Value exceeds Maximum Contaminant Level.	В	Analyte detected in the associated Method Blank
	Е	Value above quantitation range	Н	Holding times for preparation or analysis exceeded
	J	Analyte detected below quantitation limits	ND	Not Detected at the Reporting Limit Page 1 of 6
	0	RSD is greater than RSDlimit	Р	Not Detected at the Reporting Limit Page 1 of 6 Sample pH greater than 2 for VOA and TOC only.
	R	RPD outside accepted recovery limits	RL	Reporting Detection Limit
	S	Spike Recovery outside accepted recovery limits		

Client:Blagg EngineeringProject:Archuleta GC A #1

Sample ID MB-11220	SampType: MBLK	TestCode: EPA Method 3		
Client ID: PBS	Batch ID: 11220	RunNo: 16083		
Prep Date: 1/14/2014	Analysis Date: 1/14/2014	SeqNo: 463152	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Chloride	ND 1.5			
Sample ID LCS-11220	SampType: LCS	TestCode: EPA Method 3	300.0: Anions	
Sample ID LCS-11220 Client ID: LCSS	SampType: LCS Batch ID: 11220	TestCode: EPA Method : RunNo: 16083	300.0: Anions	
1	1 31	RunNo: 16083	300.0: Anions Units: mg/Kg	
Client ID: LCSS	Batch ID: 11220 Analysis Date: 1/14/2014	RunNo: 16083		RPDLimit Qual

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 2 of 6

WO#: 1401522

16-Jan-14

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

WO#: 1401522

16-Jan-14

Client:Blagg EngineeringProject:Archuleta GC A #1

In the second				
Sample ID MB-11195	SampType: MBLK	TestCode: EPA Method	418.1: TPH	
Client ID: PBS	Batch ID: 11195	RunNo: 16049		
Prep Date: 1/13/2014	Analysis Date: 1/14/2014	SeqNo: 462659	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	ND 20			
Sample ID LCS-11195	SampType: LCS	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS	Batch ID: 11195	RunNo: 16049		
Prep Date: 1/13/2014	Analysis Date: 1/14/2014	SeqNo: 462660	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	96 20 100.0	0 95.7 80	120	
Sample ID LCSD-11195	SampType: LCSD	TestCode: EPA Method	418.1: TPH	
Client ID: LCSS02	Batch ID: 11195	RunNo: 16049		
Prep Date: 1/13/2014	Analysis Date: 1/14/2014	SeqNo: 462661	Units: mg/Kg	
Analyte	Result PQL SPK value	SPK Ref Val %REC LowLimit	HighLimit %RPD	RPDLimit Qual
Petroleum Hydrocarbons, TR	98 20 100.0	0 98.0 80	120 2.44	20

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 3 of 6

.

16-Jan-14

Client:	Blagg En	gineering								
Project:	Archuleta	a GC A #1								
Sample ID	MD 11171	SampType		Tor	tCodo: E	DA Mothod	8015D: Dies	al Pango (Organico	
Client ID:			: 11171		RunNo: 1		oursp. pies	er Kange (Jiganics	
	1/10/2014	Analysis Date			SeqNo: 4		Units: %RE	C		
Analyte				e SPK Ref Val		LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP		9.8	10.0		98.3	66	131	70KFD	KFDLIIIII	Quai
Sample ID	LCS-11171	SampType	E LCS	Tes	tCode: E	PA Method	8015D: Dies	el Range (Organics	
Client ID:			: 11171		RunNo: 1			er renige e	- gamee	
	1/10/2014	Analysis Date	1/14/2014		SeqNo: 4		Units: %RE	C		
Analyte		Result F	QL SPK valu	e SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP		5.3	5.00		106	66	131			
Sample ID	MB-11196	SampType	E MBLK	Tes	tCode: E	PA Method	8015D: Dies	el Range (Drganics	
Client ID:	PBS	Batch ID	: 11196	F	RunNo: 1	6046				
Prep Date:	1/13/2014	Analysis Date	1/14/2014	:	SeqNo: 4	62288	Units: %RE	С		
Analyte		Result P	QL SPK valu	e SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP		10	10.0	0	104	66	131			
Sample ID	LCS-11196	SampType	E LCS	Tes	tCode: E	PA Method	8015D: Dies	el Range C	Drganics	
Client ID:	LCSS	Batch ID	: 11196	F	RunNo: 1	6046				
Prep Date:	1/13/2014	Analysis Date	1/14/2014		SeqNo: 4	62296	Units: %RE	С		
Analyte		Result P	QL SPK valu	e SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: DNOP		5.1	5.00	0	102	66	131			
Sample ID	MB-11208	SampType	E MBLK	Tes	tCode: E	PA Method	8015D: Dies	el Range (Organics	
Client ID:	PBS	Batch ID	11208	F	RunNo: 1	6046				
Prep Date:	1/14/2014	Analysis Date	: 1/14/2014		SeqNo: 4	62437	Units: mg/k	٢g		
Analyte		Result P	QL SPK valu	e SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range C Surr: DNOP	Organics (DRO)	ND 9.7	10 10.0	0	97.2	66	131			
Sample ID	LCS-11208	SampType	e: LCS	Tes	tCode: E	PA Method	8015D: Dies	el Range C	Drganics	
Client ID:	LCSS	Batch ID	11208	ł	RunNo: 1	6046				
Prep Date:	1/14/2014	Analysis Date	1/14/2014	;	SeqNo: 4	62438	Units: mg/h	(g		
Analyte				e SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
	Organics (DRO)	50	10 50.0		101	60.8	145			
Surr: DNOP		5.1	5.00	0	103	66	131			

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 4 of 6

a roc only.

QC SUMMARY REPORT Hall Environmental Analysis Laboratory, Inc.

WO#: 1401522

16-Jan-14

Blagg Engineering **Client:**

Project: Archuleta GC A #1

Sample ID MB-11198 MK	SampType: MBLK TestCode: EPA Method 8					8015D: Gasc	line Rang	e					
Client ID: PBS	Batch ID: R1	R	unNo: 10	6058									
Prep Date:	Analysis Date: 1	/14/2014	S	eqNo: 40	62906	Units: mg/K	g						
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Gasoline Range Organics (GRO)	ND 5.0												
Surr: BFB	900	1000		90.0	74.5	129							
Sample ID LCS-11198 MK	SampType: LC	CS	Test	Code: EF	PA Method	8015D: Gaso	line Rang	е					
Client ID: LCSS	Batch ID: R1	16058	R	unNo: 16	6058								
Prep Date:	Analysis Date: 1	/14/2014	S	eqNo: 46	62907	Units: mg/K	g						
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Gasoline Range Organics (GRO)	29 5.0	25.00	0	117	74.5	126							
Surr: BFB	970	1000		96.8	74.5	129							
Sample ID MB-11198	SampType: MI	BLK	Test	Code: EF	PA Method	8015D: Gaso	line Rang	e					
Client ID: PBS	Batch ID: 11	198	RunNo: 16058										
Prep Date: 1/13/2014	Analysis Date: 1	/14/2014	S	eqNo: 46	62918	Units: %RE	С						
Analyte	Result PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual				
Surr: BFB	900	1000		90.0	74.5	129							
								SampType: LCS TestCode: EPA Method 8015D: Gasoline Range					
Sample ID LCS-11198	SampType: LC	s	Test	Code: EF	PA Method	8015D: Gaso	line Rang	e					
Sample ID LCS-11198 Client ID: LCSS	SampType: LC Batch ID: 11			Code: EF		8015D: Gaso	line Rang	e					
		198	R		6058	8015D: Gaso Units: %RE	0	e					
Client ID: LCSS	Batch ID: 11	198 /14/2014	R	unNo: 16 eqNo: 46	6058		0	e RPDLimit	Qual				

Qualifiers:

- Value exceeds Maximum Contaminant Level. *
- Е Value above quantitation range
- Analyte detected below quantitation limits J
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits R
- S Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank В
- Holding times for preparation or analysis exceeded Н
- ND Not Detected at the Reporting Limit
- Р Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.										16-Jan-14	
Client: Project:		ngineering a GC A #1									
Sample ID	MB-11198 MK	Samp	Гуре: МЕ	BLK	Tes	tCode: El	PA Method	8021B: Vola	tiles		
Client ID:	PBS	Batc	h ID: R1	6058	F	RunNo: 1	6058				
Prep Date:		Analysis [Date: 1/	14/2014	S	SeqNo: 4	62945	Units: mg/k	(g		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		ND	0.050								
Toluene		ND	0.050								
Ethylbenzene		ND	0.050								
Xylenes, Total		ND	0.10								
	ofluorobenzene	1.1	0110	1.000		109	80	120			
Sample ID	LCS-11198 MK	Samp	Гуре: LC	S	Tes	tCode: El	PA Method	8021B: Vola	tiles		
Client ID:	LCSS	Batc	h ID: R1	6058	F	RunNo: 1	6058				
Prep Date:		Analysis E	Date: 1/	14/2014	SeqNo: 462946			Units: mg/k			
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene		1.1	0.050	1.000	0	107	80	120			
Toluene		1.1	0.050	1.000	0	107	80	120			
Ethylbenzene		1.1	0.050	1.000	0	106	80	120			
Xylenes, Total		3.2	0.10	3.000	0	108	80	120			
, .	ofluorobenzene	1.1		1.000		112	80	120			
Sample ID	MB-11198	Samp1	Гуре: МЕ	BLK	Tes	tCode: EF	PA Method	8021B: Volat	iles		
Client ID:	PBS	Batcl	h ID: 11	198	F	RunNo: 10	6058				
Prep Date:	1/13/2014	Analysis E	Date: 1/	14/2014	5	SeqNo: 40	63002	Units: %RE	С		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromo	ofluorobenzene	1.1		1.000		109	80	120			
Sample ID	LCS-11198	SampT	ype: LC	S	Tes	tCode: EF	PA Method	8021B: Volat	iles		
Client ID:	LCSS	Batcl	n ID: 11	198	F	RunNo: 10	6058				
Prep Date:	1/13/2014	Analysis E)ate: 1/	14/2014	S	SeqNo: 40	63003	Units: %RE	С		
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Surr: 4-Bromo	ofluorobenzene	1.1		1.000		112	80	120			

Qualifiers:

٠

QC SUMMARY REPORT

٠

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Page 6 of 6

1401522

WO#:

ANALYSIS LABORATORY	environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105 505-345-3975 FAX: 505-345-4107 ibsite: www.hallenvironmental.com	San	nple Log-In Check List
Client Name: BLAGG Work O	rder Number: 1401522		RcptNo: 1
Received by/date	114		
Logged By: Ashley Gallegos 1/14/2014	10:00:00 AM	\$J	
Completed By: Ashley Gallegos 1/14/2014	10:24:26 AM 9	\$	
Reviewed By: 10 01/14	2014	U	
Chain of Custody			
1. Custody seals intact on sample bottles?	Yes	No 🗌	Not Present
2. Is Chain of Custody complete?	Yes 🗸	No 🗌	Not Present
3. How was the sample delivered?	Courier		
Log In			
4. Was an attempt made to cool the samples?	Yes 🗹	No 🗌	NA
5. Were all samples received at a temperature of $>0^\circ$ C to	o 6.0°C Yes ✔	No 🗌	NA 🗌
6. Sample(s) in proper container(s)?	Yes 🔽	No 🗌	
7. Sufficient sample volume for indicated test(s)?	Yes 🔽	No 🗌	
8. Are samples (except VOA and ONG) properly preserved	d? Yes 🗹	No 🗌	
9. Was preservative added to bottles?	Yes	No 🗸	NA 🗌
10.VOA vials have zero headspace?	Yes	No 🗌	No VOA Vials 🗹
11. Were any sample containers received broken?	Yes	No 🗸	# of preserved
12.Does paperwork match bottle labels? (Note discrepancies on chain of custody)	Yes 🗸	No 🗔	bottles checked for pH: (<2 or >12 unless noted)
13. Are matrices correctly identified on Chain of Custody?	Yes 🖌	No	Adjusted?
14. Is it clear what analyses were requested?	Yes 🖌	No 🗌	
15. Were all holding times able to be met? (If no, notify customer for authorization.)	Yes ✔	No 🗌	Checked by:
Special Handling (if applicable)			
16. Was client notified of all discrepancies with this order?	Yes 🗋	No 🗌	NA 🗹
Person Notified:	Date:		
By Whom:	Via: eMail Phone	e 🗌 Fax	In Person
Regarding:			
Client Instructions:			
17. Additional remarks:			

·····

.

18. Cooler Information

4 Cooler No	Temp °C	Condition	Seal Intact (Seal No	Seal Date	Signed By
1	1.8	Good	Yes			

Client:	00 0 0		□ Standard		1	ANALYSIS LABORAT											
	BP America			Project Name:													
Mailing Address: P.O. Box 87			Archuleta GC A #1			www.hallenvironmental.com 4901 Hawkins NE - Albuquerque, NM 87109											
			Project #:			-	Tel. 505-345-3975 Fax 505-345-4107										
Phone #:	Phone #: (505)320-1183		1				-			Anal	ysis	Requ	lest				
email or Fax	#:			Project Mana	ager:												
QA/QC Packa	ige:				Jeff Blagg												
Standard			Level 4 (Full Validation)					2 2								
Other				Sampler:	Jeff Blagg				(האט חאט)								R
EDD (Typ)		· · · · · · · · · · · · · · · · · ·		P Yes	□ No			r F								1
		1	I	Sample Tem	perature: / ı	<u> </u>	51)			_							2
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL No. 1401522	BTEX (8021)	100		1PH 418.						Chloride	Air Ruhhlas
01/13/2014	11:40	Soil	95 BGT - 5 Pt @ 4'	4oz x 1	cool	- 001	x		()	-					1	x	1
																	\square
										-	1						-
											+				-		-
				1						-	+-						+
									+	-	-	+			+		
										+	+						
									+	+	+	+					-
							-				+						
									+	+				-+			
									+	+		1					
									+	+						\vdash	
Date: 1/13/2014	Time: 1412	Relinquist	A Bregg	Received by:	u Wate	Date Time	Pay	harks: key: Zl tact:	EVH	01B			L			Ļ[1
Date:	Time:		- Walter	Received by:	Received by: 01/14/14/000						-						

.

٠

If necessary, samples subditted to Hall Environmental may be subcontracted to other accredited laboratories. This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report.

bp



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

November 21, 2013

Erlinda Miller 292 Road 4599 Blanco, NM 87412

VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: ARCHULETA GC A 001

Dear Mrs. Miller,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about December 13, 2013. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

AD Och

Jerry Van Riper Surface Land Negotiator BP America Production Company

BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

November 21, 2013

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

ARCHULETA GAS COM A 001 API 30-045-08670 (G) Section 5 – T29N – R09W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 95 bbl BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff love l

Jeff Peace BP Field Environmental Advisor

(505) 326-9479



