District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-144 Revised June 6, 2013 For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
Type of action: Below Permin 45-25943 Closur Modif Closur or proposed alternative meth	t of a pit or proposed alternative method re of a pit, below-grade tank, or proposed alternat fication to an existing permit/or registration re plan only submitted for an existing permitted of hod	ive method r non-permitted pit, below-grade tank,
Please be advised that approval of this request does no	<i>ne application (Form C-144) per individual pit, below</i> of relieve the operator of liability should operations result i of its responsibility to comply with any other applicable go	in pollution of surface water, ground water or the
Address:200 Energy Court, Farmington Facility or well name:Barrett A 1E API Number:3004525943 U/L or Qtr/QtrGSection20 Center of Proposed Design: Latitude36.8 Surface Owner: X Federal I State I Private I 2. Image: Pit: Subsection F, G or J of 19.15.17.11 NN Temporary: Image: Drilling I Workover Image: Permanent I Emergency I Cavitation I		MAR 0 5 2015 NMOCD Founty:San Juan NAD: □1927 ⊠ 1983
Liner Seams: 🗌 Welded 🗌 Factory 🗋 Other	Volume:bbl	Dimensions: Lx Wx D
☐ Visible sidewalls and liner ☐ Visible sidew		omed; side walls not visible
4. Alternative Method: Submittal of an exception request is required. Ex	ceptions must be submitted to the Santa Fe Environme	ntal Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Chain link, six feet in height, two strands of barbed wire at top (*Required if located within 1000 feet of a permanent residence, school, hospital, institution or church*)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

Alternate. Please specify_

5

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting							
<u>Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.</u> - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells							
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells							
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	Yes No						
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No						
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No						
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	🗌 Yes 🗌 No						
Below Grade Tanks							
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No						
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No						
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)							
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No						

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
Temporary Pit Non-low chloride drilling fluid	
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	
	Yes No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	Yes No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	
- Topographic map; Visual inspection (certification) of the proposed site	Yes No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
 Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the dot attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC	onternation number of the second s
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
II. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the dot attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

.

12. Description of the state of	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.	documents are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC	
 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment 	
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC	
Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
 Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC 	
Quality Control/Quality Assurance Construction and Installation Plan	
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC 	
\square Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan	
Emergency Response Plan	
 Oil Field Waste Stream Characterization Monitoring and Inspection Plan 	
Erosion Control Plan	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
^{13.} Proposed Closure: 19.15.17.13 NMAC	
<i>Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.</i> Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fl	luid Managamant D:
Alternative	iuna ivialiagement Pl
Proposed Closure Method: Waste Excavation and Removal	
 Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) 	
In-place Burial On-site Trench Burial	
Alternative Closure Method	
 Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P	
19.15.17.10 NMAC for guidance.	ieuse rejer io
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	□ NA □ Yes □ No
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa 	□ NA □ Yes □ No □ NA □ Yes □ No
 Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	□ NA □ Yes □ No □ NA □ Yes □ No □ NA
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence 	 NA Yes □ No NA Yes □ No NA Yes □ No NA Yes □ No
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. 	 NA Yes □ No NA Yes □ No NA Yes □ No Yes □ No Yes □ No
 NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 25-50 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	 NA Yes □ No NA Yes □ No NA Yes □ No Yes □ No Yes □ No Yes □ No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.							
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No						
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No						
Within an unstable area.							
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 							
Within a 100-year floodplain.	☐ Yes ☐ No ☐ Yes ☐ No						
- FEMA map							
16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC							
17. Operator Application Certification:							
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.						
Name (Print): Title:							
Signature: Date:							
Signature: Date: e-mail address: Telephone:							
e-mail address: Telephone: <u>OCD Approva</u> l: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: _3/27							
e-mail address: Telephone:	1)2015 the closure report.						
e-mail address: Telephone:	1)2015 the closure report.						
e-mail address: Telephone:	7)2015 the closure report. complete this						

4

22. Operator Closure Certification:

.

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.							
Name (Print): Jeff Peace Title: Field Environmental Coordinator							
Signature: Date: Date: March 4, 2015							
e-mail address:peace.jeffrey@bp.com Telephone:(505) 326-9479							

BP AMERICA PRODUCTION COMPANY SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

<u>Barrett A 1E – Tank B (21 bbl)</u> <u>API No. 3004525943</u> Unit Letter G, Section 20, T31N, R9W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

4

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement. **Notice is attached.**
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

No notice was made due to misunderstanding of the BGT notice requirements at that time.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

- BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.
 All equipment associated with the BGT has been removed.
- 6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	Tank B - 21 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- BP shall notify the division District III office of its results on form C-141.
 C-141 is attached.
- If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.
 Sampling results indicate no release occurred.
- 9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation. Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

.

State of New Mexico Energy Minerals and Natural Resources

> Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-141 Revised August 8, 2011

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notifi	catio	n and Co	orrective A	ction				
						OPERA '	ГOR	🗌 Initi	al Report	\boxtimes	Final Repo	
					Contact: Jeff Peace							
	Address: 200 Energy Court, Farmington, NM 87401					Telephone No.: 505-326-9479						
Facility Na	me: Barret	tA1E				Facility Typ	e: Natural gas	well				
Surface Ow	Surface Owner: Federal Mineral Owner:					Federal			API No	. 3004525	943	
LOCATI					ATIO	N OF RE	LEASE					
Unit Letter	Section	Township	Range	Feet from the	North	/South Line	Feet from the	East/W	lest Line	County: S	an Juan	1
G	20	31N	9W	1,640	North		2,215	East				
		Latit	ude 36	.886690		Longitud	e107.801949					
				NA	FURE	OF REL	EASE					
Type of Rele	ase: none			111 .	I UIU		Release: N/A		Volume F	Recovered: 1	N/A	
Source of Re	lease: below	w grade tank –	21 bbl Ta	ank B		Date and H	lour of Occurrence	ce:	Date and	Hour of Dis	covery:	
Was Immedi	ate Notice (If YES, To	Whom?					
			Yes] No 🛛 Not R	Required							
By Whom?						Date and H						
Was a Water	course Rea		Yes 🛛	No		If YES, Vo	lume Impacting t	the Wate	rcourse.			
If a Watercou	irse was Im	pacted, Descri	ibe Fully.*	k								
the BGT. So Describe Are	il analysis i a Affected	resulted in TPI and Cleanup A	H, BTEX	and chloride belo	ow standa	ards. Analysi	the BGT was do s results are attack	hed.				
regulations a public health should their o or the environ	Il operators or the envi operations h nment. In a	are required to ronment. The nave failed to a	o report ar acceptanc adequately OCD accep	nd/or file certain ce of a C-141 rep investigate and	release n ort by the remediat	otifications and e NMOCD m e contaminati	knowledge and und perform correct arked as "Final R on that pose a thr e the operator of the	ctive action eport" do reat to gro	ons for rele bes not reli bund water	eases which eve the open , surface wa	may en rator of ater, hur	idanger Tiability man health
	1 10	0					OIL CON	SERV	ATION	DIVISIC	N	
Signature:	eff	Year	e		~							
	000					Approved by	Environmental S	pecialist:				
Printed Name	e: Jeff Peac	e										
Title: Field E	nvironmen	tal Coordinato	r			Approval Dat	e:	E	xpiration	Date:		
E-mail Addre	ess: peace.je	effrey@bp.con	n			Conditions of	Approval:		Attached 🗌			
Date: March 4, 2015 Phone: 505-326-9479												

* Attach Additional Sheets If Necessary

	מח	BI AC	G ENGINEER	ING IN	C		2	00450	E0 4 2			
CLIENT:								API #: 3004525943				
(505) 632-1199								A	B			
FIELD REP	ORT:	(circle one): BGT CONFIR	MATION / RELEASE INVEST	igation / C)THER:		PAGE #:	1	of1			
SITE INFOR	RMATION	: SITE NAME: BA	ARRETT A #1E				DATE STARTED	08	29/11			
QUAD/UNIT: G SEC	C: 20 TWP:	31N RNG: 9W	PM: NM CN	ry: SJ	ST:	NM	DATE FINISHED):				
1/4 -1/4/FOOTAGE: 1, LEASE #: SF07		PROD. FORMATION:	LEASE TYPE: FEDERA	KHORN		IAN	ENVIRONMENTA SPECIALIST(S):		ICB			
REFERENC			(H.) GPS COORD.:		8 X 107.	80206	GL	ELEV.:	6,274'			
1)	W/DB) - A	GPS COORD.:	36.886600 X 10				ARING FROM W.H.:		, N41W			
2) 21 BGT (S	W/DB) - B	GPS COORD.:	36.886690 X 10	7.801949	DIS	STANCE/BEA	ARING FROM W.H.:	114	, N18E			
3)		GPS COORD.:			DIS	STANCE/BEA	ARING FROM W.H.:					
4)		GPS COORD.:			DIS	STANCE/BEA	ARING FROM W.H.:					
SAMPLING	DATA:	CHAIN OF CUSTODY RECO	RD(S) # OR LAB USED:	HAL	L				OVM READIN			
1) SAMPLE ID: 21	BGT 5-pt. @	6' SAMPLE DATE: 0	8/29/11 SAMPLE TIME:	1010	LAB ANALYSIS:	418.1/8	015B/8021B	/300.0 (C	(ppm) 0.0			
2) SAMPLE ID:	BGT 5-pt. @ (SAMPLE DATE: 6	6/29/11 SAMPLE TIME:	1122	LAB AWALYSIS:	418.1/8	015B/8021B	/300.0 (C) 0.0			
3) SAMPLE ID:		SAMPLE DATE:	SAMPLE TIME:		LAB ANALYSIS:							
4) SAMPLE ID:		SAMPLE DATE:	SAMPLE TIME:		LAB ANALYSIS:							
SOIL DESC	RIPTION	SOIL TYPE: SANI	D / SILTY SAND / SILT / SI	TY CLAY / C								
CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB /	COHESIVE <u>(SLIGHTLY</u> HESIVE SOILS): [LO <u>MOIST</u> / MOIST / WE (COMPOSITE]#		DENSE DENSITY RATED HC ODO	(COHESIVE C	CLAYS & SILT	S): SOFT	COHESIVE / MEDIUM PL } FIRM / STIFF / V ANATION	ERY STIFF				
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN	COHESIVE <u>{SLIGHTLY</u> HESIVE SOILS): <u>[LO</u> (<u>MOIST</u>) MOIST / WE (<u>COMPOSITE</u>]# IING OBSERVED:	COHESIVE / HIGHLY C OSE / FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS. <u>5</u> YES (NO EXPLANATION	DENSE DENSITY RATED HC ODO	(COHESIVE C	CLAYS & SILT	S): SOFT	FIRM / STIFF / V	ERY STIFF				
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE	COHESIVE (SLIGHTLY IESIVE SOILS): [LO (MOIST) MOIST / WE (COMPOSITE] # IING OBSERVED: TNESS: YES /[NO DF A RELEASE OF	COHESIVE / COHESIVE / HIGHLY C OSE / FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS5 YES (NO EXPLANATION EXPLANATION	DENSE DENSITY RATED HC ODO	(COHESIVE C	CLAYS & SILT	S): SOFT	FIRM / STIFF / V	ERY STIFF				
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE APPARENT EVIDENCE (COHESIVE <u>{SLIGHTLY</u> HESIVE SOILS); <u>LO</u> <u>MOIST</u> MOIST / WE <u>{COMPOSITE</u> # HING OBSERVED: TINESS: YES <u>/NO</u> DF A RELEASE OF TS: DN ESTIMATION:	COHESIVE / COHESIVE / HIGHLY C OSE / FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS5 YES (NO EXPLANATION EXPLANATION	DENSE DENSITY RATED HC ODO	(COHESIVE C R DETECTE ANATION : ft.	CLAYS & SILT D: YES (NO	S): SOFT D EXPLA	FIRM / STIFF / V	ERY STIFF	HARD NA			
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY [SLIGHTLY SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE APPARENT EVIDENCE C ADDITIONAL COMMENT SOIL IMPACT DIMENSIC	COHESIVE <u>{SLIGHTLY</u> HESIVE SOILS): <u>[LO</u> <u>(MOIST</u>) MOIST / WE <u>{COMPOSITE]</u> (COMPOSITE] (ING OBSERVED: ING OBSERVED: TNESS: YES / <u>NO</u> DF A RELEASE OE TS: ON ESTIMATION: R: SD' NE	COHESIVE / COHESIVE / HIGHLY COSE/ FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS. 5 YES (NO EXPLANATION EXPLANATION - 3SERVED AND/OR OCCUI	DENSE DENSITY RATED HC ODO	(COHESIVE C R DETECTE ANATION : ANATION : ft. ACE WATER:	CLAYS & SILT D: YES (NO	S): SOFT D EXPLA TION ESTI MMOCI	FIRM / STIFF / V ANATION IMATION (Cubic D TPH CLOSURE :	ERY STIFF /	NA D ppm			
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE APPARENT EVIDENCE (ADDITIONAL COMMENT SOIL IMPACT DIMENSIC DEPTH TO GROUNDWATER	COHESIVE <u>{SLIGHTLY</u> HESIVE SOILS): <u>[LO</u> <u>(MOIST</u>) MOIST / WE <u>{COMPOSITE]</u> (COMPOSITE] (ING OBSERVED: ING OBSERVED: TNESS: YES / <u>NO</u> DF A RELEASE OE TS: ON ESTIMATION: R: SD' NE	COHESIVE / COHESIVE / HIGHLY COSE/ FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS. 5 YES (NO EXPLANATION EXPLANATION - 3SERVED AND/OR OCCUI	DENSE DENSITY RATED HC ODO N	(COHESIVE C R DETECTE ANATION : ANATION : ft. ACE WATER:	EXCAVAT		FIRM / STIFF / V ANATION IMATION (Cubic D TPH CLOSURE : CALIB. READ. =	ERY STIFF / Yards) : STD:10 54.2	NA			
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE APPARENT EVIDENCE (ADDITIONAL COMMENT SOIL IMPACT DIMENSIC DEPTH TO GROUNDWATER	COHESIVE <u>{SLIGHTLY</u> HESIVE SOILS): <u>[LO</u> <u>(MOIST</u>) MOIST / WE <u>{COMPOSITE]</u> (COMPOSITE] (ING OBSERVED: ING OBSERVED: TNESS: YES / <u>NO</u> DF A RELEASE OE TS: ON ESTIMATION: R: SD' NE	COHESIVE / COHESIVE / HIGHLY COSE / FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS YES /NO EXPLANATION EXPLANATION - BSERVED AND/OR OCCUI NA ft. X EAREST WATER SOURCE:	DENSE DENSITY RATED HC ODO N	(COHESIVE C R DETECTE ANATION : ANATION : ft. ACE WATER: LAN circ PROD.	EXCAVAT		FIRM / STIFF / V ANATION IMATION (Cubic D TPH CLOSURE : CALIB. READ. =	• Yards) : std: 54.2 100	NA 0 ppm RF = 0.5			
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE APPARENT EVIDENCE (ADDITIONAL COMMENT SOIL IMPACT DIMENSIC DEPTH TO GROUNDWATER	COHESIVE <u>{SLIGHTLY</u> HESIVE SOILS): <u>[LO</u> <u>(MOIST</u>) MOIST / WE <u>{COMPOSITE]</u> (COMPOSITE] (ING OBSERVED: ING OBSERVED: TNESS: YES / <u>NO</u> DF A RELEASE OE TS: ON ESTIMATION: R: SD' NE	COHESIVE / COHESIVE / HIGHLY COSE / FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS. 5 YES (NO EXPLANATION EXPLANATION BSERVED AND/OR OCCUI AREST WATER SOURCE: STEEL CONTAINMENT	DENSE DENSITY RATED HC ODO N	(COHESIVE C R DETECTE ANATION : ANATION : ft. ACE WATER: LAN circ	EXCAVAT CALAYS & SILT D: YES N EXCAVAT _<1,000 le: attache		FIRM / STIFF / V ANATION IMATION (Cubic D TPH CLOSURE : CALIB. READ. = CALIB. GAS =	ERY STIFF / Yards) : _ STD:10 54.2 / 100 / DATE:	MA NA ppm ppm RF = 0.5 08/29/11			
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE APPARENT EVIDENCE (ADDITIONAL COMMENT SOIL IMPACT DIMENSIC DEPTH TO GROUNDWATER	COHESIVE <u>{SLIGHTLY</u> HESIVE SOILS): <u>[LO</u> <u>(MOIST</u>) MOIST / WE <u>{COMPOSITE]</u> (COMPOSITE] (ING OBSERVED: ING OBSERVED: TNESS: YES / <u>NO</u> DF A RELEASE OE TS: ON ESTIMATION: R: SD' NE	COHESIVE / COHESIVE / HIGHLY COSE / FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS YES (NO EXPLANATION EXPLANATION 3SERVED AND/OR OCCUI AREST WATER SOURCE: STEEL	DENSE RATED DENSITY HC ODO N- RRED : YES NC EXPL NA ft. X NA <1,000' NEAREST SURF. PLOT P	(COHESIVE C R DETECTE ANATION : ANATION : ft. ACE WATER: LAN circ PROD.	EXCAVAT CALAYS & SILT D: YES N EXCAVAT _<1,000 le: attache		FIRM / STIFF / V ANATION IMATION (Cubic D TPH CLOSURE : CALIB. READ. = CALIB. GAS = 10:15 (amjore)	ERY STIFF / Yards) : STD:10 54.2 100 DATE: L. NO	MA NA ppm ppm RF = 0.5 08/29/11			
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE APPARENT EVIDENCE (ADDITIONAL COMMENT SOIL IMPACT DIMENSIC DEPTH TO GROUNDWATER	COHESIVE <u>{SLIGHTLY</u> HESIVE SOILS): <u>[LO</u> <u>(MOIST</u>) MOIST / WE <u>{COMPOSITE]</u> (COMPOSITE] (ING OBSERVED: ING OBSERVED: TNESS: YES / <u>NO</u> DF A RELEASE OE TS: ON ESTIMATION: R: SD' NE	COHESIVE / COHESIVE / HIGHLY COSE / FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS. 5 YES (NO EXPLANATION EXPLANATION BSERVED AND/OR OCCUI AREST WATER SOURCE: STEEL CONTAINMENT	DENSE DENSITY RATED HC ODO N	(COHESIVE C R DETECTE ANATION : ANATION : ft. ACE WATER: LAN circ PROD.	EXCAVAT CALAYS & SILT D: YES N EXCAVAT _<1,000 le: attache		FIRM / STIFF / V ANATION IMATION (Cubic D TPH CLOSURE CALIB. READ. = CALIB. GAS = MISCEL	ERY STIFF / Yards) : STD:10 54.2 100 DATE: L. NO	MA NA ppm ppm RF = 0.5 08/29/11			
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE APPARENT EVIDENCE (ADDITIONAL COMMENT SOIL IMPACT DIMENSIC DEPTH TO GROUNDWATER	COHESIVE <u>{SLIGHTLY</u> HESIVE SOILS): <u>[LO</u> <u>(MOIST</u>) MOIST / WE <u>{COMPOSITE]</u> (COMPOSITE] (ING OBSERVED: ING OBSERVED: TNESS: YES / <u>NO</u> DF A RELEASE OE TS: ON ESTIMATION: R: SD' NE	COHESIVE / COHESIVE / HIGHLY COSE / FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS. 5 YES (NO EXPLANATION EXPLANATION BSERVED AND/OR OCCUI AREST WATER SOURCE: STEEL CONTAINMENT	DENSE RATED DENSITY HC ODO N- RRED : YES NC EXPL NA ft. X NA <1,000' NEAREST SURF. PLOT P	(COHESIVE C R DETECTE ANATION : ANATION : ft. ACE WATER: LAN circ PROD.	EXCAVAT CALAYS & SILT D: YES N EXCAVAT _<1,000 le: attache		FIRM / STIFF / V ANATION IMATION (Cubic D TPH CLOSURE CALIB. READ. = CALIB. GAS = 10:15 MISCEL O: D #: 52237	ERY STIFF / Yards) : STD:10 54.2 100 DATE: L. NO	NA D ppm pm <u>RF = 0.5</u> 08/29/11			
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE APPARENT EVIDENCE (ADDITIONAL COMMENT SOIL IMPACT DIMENSIC DEPTH TO GROUNDWATER	COHESIVE <u>{SLIGHTLY</u> HESIVE SOILS): <u>[LO</u> <u>(MOIST</u>) MOIST / WE <u>{COMPOSITE]</u> (COMPOSITE] (ING OBSERVED: ING OBSERVED: TNESS: YES / <u>NO</u> DF A RELEASE OE TS: ON ESTIMATION: R: SD' NE	COHESIVE / COHESIVE / HIGHLY COSE / FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS. 5 YES (NO EXPLANATION EXPLANATION BSERVED AND/OR OCCUI AREST WATER SOURCE: STEEL CONTAINMENT	DENSE RATED DENSITY HC ODO N- RRED : YES NC EXPL NA ft. X NA <1,000' NEAREST SURF. PLOT P	(COHESIVE C R DETECTE ANATION : ANATION : ft. ACE WATER: LAN circ PROD.	EXCAVAT CALAYS & SILT D: YES N EXCAVAT _<1,000 le: attache	S): SOFT D EXPLA TION ESTI MMOCL ad OVM (TIME: WM PC	FIRM / STIFF / V ANATION IMATION (Cubic D TPH CLOSURE CALIB. READ. = CALIB. GAS = 10:15 MISCEL O: D #: 52237	ERY STIFF / Yards) : STD: 54.2 100 DATE: L. NO 624	NA D ppm pm <u>RF = 0.5</u> 08/29/11			
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE APPARENT EVIDENCE (ADDITIONAL COMMENT SOIL IMPACT DIMENSIC DEPTH TO GROUNDWATER	COHESIVE <u>{SLIGHTLY</u> HESIVE SOILS): <u>[LO</u> <u>(MOIST</u>) MOIST / WE <u>{COMPOSITE]</u> (COMPOSITE] (ING OBSERVED: ING OBSERVED: TNESS: YES / <u>NO</u> DF A RELEASE OE TS: ON ESTIMATION: R: SD' NE	COHESIVE / COHESIVE / HIGHLY COSE / FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS. 5 YES (NO EXPLANATION EXPLANATION BSERVED AND/OR OCCUI AREST WATER SOURCE: STEEL CONTAINMENT	DENSE RATED DENSITY HC ODO N- RRED : YES NO EXPL NA ft. X NA <1,000' NEAREST SURF. PLOT P	(COHESIVE C R DETECTE ANATION : ANATION : ft. ACE WATER: LAN circ PROD. TANK	EXCAVAT CALAYS & SILT D: YES N EXCAVAT _<1,000 le: attache		FIRM / STIFF / V ANATION IMATION (Cubic D TPH CLOSURE CALIB. READ. = CALIB. GAS = 10:15 MISCEL O: D #: 52237	ERY STIFF / . Yards) :	NA D ppm pm <u>RF = 0.5</u> 08/29/11			
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE APPARENT EVIDENCE (ADDITIONAL COMMENT SOIL IMPACT DIMENSIC DEPTH TO GROUNDWATER	COHESIVE <u>{SLIGHTLY</u> HESIVE SOILS): <u>[LO</u> <u>(MOIST</u>) MOIST / WE <u>{COMPOSITE]</u> (COMPOSITE] (ING OBSERVED: ING OBSERVED: TNESS: YES / <u>NO</u> DF A RELEASE OE TS: ON ESTIMATION: R: SD' NE	COHESIVE / COHESIVE / HIGHLY (OSE) / FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS. 5 YES (NO EXPLANATION EXPLANATION - 3SERVED AND/OR OCCUI MA ft. X CONTAINMENT - SYSTEM WELL	DENSE RATED DENSITY HC ODO N- RRED : YES NO EXPL NA ft. X NA <1,000' NEAREST SURF. PLOT P (21) PBGTI T.B.~6	(COHESIVE C R DETECTE ANATION : ANATION : ft. ACE WATER: LAN circ PROD. TANK	EXCAVAT CALAYS & SILT D: YES N EXCAVAT _<1,000 le: attache	S): SOFT C EXPLA TON ESTI MMOCI M	FIRM / STIFF / V ANATION IMATION (Cubic D TPH CLOSURE CALIB. READ. = CALIB. GAS = 10:15 (am)pm MISCEL O: N1410 D #: 52237 C ZSCHV CD Appr. date	ERY STIFF / Yards) : STD:100 54.2 100 DATE: DATE: C NC 624 MLLBG : 05/	NA Dppm 08/29/11 TES T 25/11			
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE APPARENT EVIDENCE (ADDITIONAL COMMENT SOIL IMPACT DIMENSIC DEPTH TO GROUNDWATER	COHESIVE <u>{SLIGHTLY</u> HESIVE SOILS): <u>[LO</u> <u>(MOIST</u>) MOIST / WE <u>{COMPOSITE]</u> (COMPOSITE] (ING OBSERVED: ING OBSERVED: TNESS: YES / <u>NO</u> DF A RELEASE OE TS: ON ESTIMATION: R: SD' NE	COHESIVE / COHESIVE / HIGHLY C OSE / FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS. 5 YES (NO EXPLANATION EXPLANATION - 3SERVED AND/OR OCCUI AREST WATER SOURCE: STEEL CONTAINMENT	DENSE RATED DENSITY HC ODO N- RRED : YES NO EXPL NA ft. X NA <1,000' NEAREST SURF. PLOT P (21) PBGTI T.B.~6	(COHESIVE C R DETECTE ANATION : ANATION : ft. ACE WATER: LAN circ PROD. TANK	EXCAVAT <pre>EXCAVAT _<1,000' le: attache</pre>	S): SOFT D EXPLA TON ESTI NMOCI ad OVM (OVM (TIME: PH OC Tank ID	FIRM / STIFF / V ANATION IMATION (Cubic D TPH CLOSURE CALIB. READ. = CALIB. GAS = T0:15(am)pm MISCEL O: N1410 D #: 52237 C ZSCHV CD Appr. date CD Appr. date	ERY STIFF / Yards) :	NA Dppm 08/29/11 TES T 25/11			
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE APPARENT EVIDENCE (ADDITIONAL COMMENT SOIL IMPACT DIMENSIC DEPTH TO GROUNDWATER SITE SKETCI	COHESIVE (SLIGHTLY IESIVE SOILS): [(MOIST) MOIST / WE (COMPOSITE] # IING OBSERVED: TINESS: YES /[N0] DF A RELEASE OE 'S: DN ESTIMATION: R:SO' NE H	COHESIVE / COHESIVE / HIGHLY C OSE / FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS YES / NO EXPLANATION EXPLANATION 3SERVED AND/OR OCCUI AREST WATER SOURCE: STEEL CONTAINMENT SYSTEM WELL HEAD ⊕	DENSE RATED DENSITY HC ODO N- RRED : YES NO EXPL NA ft. X NA <1,000' NEAREST SURF PLOT P (21) PBGTI T.B. ~ 6 B.G.	(COHESIVE C R DETECTE ANATION : ANATION : ACE WATER: LAN circ PROD. TANK	EXCAVAT <pre> EXCAVAT </pre> <pre> EXCAVAT </pre>		FIRM / STIFF / V ANATION IMATION (Cubic D TPH CLOSURE CALIB. READ. = CALIB. GAS = 10:15 (am)pm MISCEL O: N1410 D #: 52237 C ZSCHV CD Appr. date	ERY STIFF / Yards) :	HARD NA ppm pm RF=0.2 08/29/11 TES T 25/11 14/10 14/10			
COHESION (ALL OTHERS): NON CONSISTENCY (NON COH MOISTURE: DRY <u>SLIGHTLY</u> SAMPLE TYPE: GRAB / DISCOLORATION/STAIN ANY AREAS DISPLAYING WE APPARENT EVIDENCE (ADDITIONAL COMMENT SOIL IMPACT DIMENSIC DEPTH TO GROUNDWATER SITE SKETCH	COHESIVE <u>{SLIGHTLY</u> HESIVE SOILS): <u>LO</u> (<u>MOIST</u>) MOIST / WE <u>{COMPOSITE</u>] # IING OBSERVED: TNESS: YES <u>[NO</u> DF A RELEASE OF 'S: ON ESTIMATION: R: NE H ANK; E.D. = EXCAVATIO 3GTL = PREVIOUS BELC	COHESIVE / COHESIVE / HIGHLY C OSE / FIRM / DENSE / VERY T / SATURATED / SUPER SATU OF PTS YES / NO EXPLANATION EXPLANATION 3SERVED AND/OR OCCUI AREST WATER SOURCE: STEEL CONTAINMENT SYSTEM WELL HEAD ⊕ N DEPRESSION; B.G. = BELOW GR WAGRADE TANK LOCATION; SPD =	DENSE RATED DENSITY HC ODO N- RRED : YES NO EXPL NA ft. X NA <1,000' NEAREST SURF. PLOT P (21) PBGTI T.B.~6	(COHESIVE C R DETECTE ANATION : ANATION : ANATION : ft. ACE WATER: LAN circ PROD. TANK	EXCAVAT CLAYS & SILT D: YES N EXCAVAT <1,000' Ie: attache N Attache N Attache N Attache N Attache N Attache N Attache N Attache		FIRM / STIFF / V ANATION IMATION (Cubic D TPH CLOSURE CALIB. READ. = CALIB. GAS = 10:15 MISCEL O: N1410 D #: 52237 C ZSCHV CD Appr. date CD Appr. date	ERY STIFF / Yards) :	HARD NA D ppm PPm RF = 0.3 08/29/11 TES T 25/11 14/10 N/NA N) NA			

CLIENT:	Blagg Engineering			Client Sample ID:	21 BGT 5	-pt @6'
Lab Order:	1109075			Collection Date:	8/29/2011	10:10:00 AM
Project:	Barrett A #1E			Date Received:	9/2/2011	
Lab ID:	1109075-01			Matrix:	SOIL	
Analyses		Result	PQL	Qual Units	DF	Date Analyzed
EPA METHOD	015B: DIESEL RANGE	ORGANICS				Analyst: JB
Diesel Range Or	rganics (DRO)	26	9,9	mg/Kg	1	9/7/2011 8:00:08 AM
Surr: DNOP		115	73.4-123	%REC	1	9/7/2011 8:00:08 AM
EPA METHOD 8	015B: GASOLINE RANG	GE				Analyst: RAA
Gasoline Range	Organics (GRO)	ND	4.9	mg/Kg	1	9/6/2011 4:14:59 PM
Surr: BFB		96.4	75.2-136	%REC	1	9/6/2011 4:14:59 PM
EPA METHOD 8	021B: VOLATILES					Analyst: RAA
Benzene		ND	0.049	mg/Kg	1	9/6/2011 4:14:59 PM
Toluene		ND	0.049	mg/Kg	1	9/6/2011 4:14:59 PM
Ethylbenzene		ND	0.049	mg/Kg	1	9/6/2011 4:14:59 PM
Xylenes, Total		ND	0.098	mg/Kg	1	9/6/2011 4:14:59 PM
Surr: 4-Bromo	fluorobenzene	97.3	80-120	%REC	1	9/6/2011 4:14:59 PM
EPA METHOD 3	00.0: ANIONS					Analyst: SRM
Chloride		ND	7.5	mg/Kg	5	9/9/2011 9:44:44 PM
EPA METHOD 4	18.1: TPH					Analyst: JB
Petroleum Hydro	carbons, TR	ND	20	mg/Kg	1	9/12/2011

Hall Environmental Analysis Laboratory, Inc.

Date: 14-Sep-11 Analytical Report

Qualifiers:

* Value exceeds Maximum Contaminant Level

E Estimated value

- J Analyte detected below quantitation limits
- NC Non-Chlorinated
- PQL Practical Quantitation Limit

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

MCL Maximum Contaminant Level

ND Not Detected at the Reporting Limit

S Spike recovery outside accepted recovery limits

.

QA/QC SUMMARY REPORT

		• •									
Client: Blagg Engin Project: Barrett A #3									Work	Outeur	1100070
									WOLK	Order:	1109075
Analyte	Result	Units	PQL	SPK Va	SPK ref	%Rec L	.owLimit Hi	ighLimit	%RPD	RPDLimi	t Qual
Method: EPA Method 300.0: A	nions										
Sample ID: MB-28356		MBLK				Batch ID:	28356	Analys	is Date:	9/8/2011	1:33:52 P
Chloride	ND	mg/Kg	1.5								
Sample ID: LCS-28356		LCS				Batch ID:	28356	Analys	is Date:	9/8/2011	1:51:17 P
Chloride	14.04	mg/Kg	1.5	15	0	93.6	90	110			2
Method: EPA Method 418.1: T	PH										
Sample ID: MB-28391		MBLK				Batch ID:	28391	Analys	is Date:		9/12/201
Petroleum Hydrocarbons, TR	ND	mg/Kg	20								
Sample ID: LCS-28391		LCS				Batch ID:	28391	Analys	is Date:		9/12/201
Petroleum Hydrocarbons, TR	100.7	mg/Kg	20	100	0	101	87.8	115			
Sample ID: LCSD-28391		LCSD				Batch ID:	28391	Analys	is Date:		9/12/201
Petroleum Hydrocarbons, TR	98.16	mg/Kg	20	100	0	98.2	87.8	115	2.55	8.04	
Method: EPA Method 8015B: [Diesel Range	Organics			110-1						
Sample ID: MB-28308	sibbor i (dinge	MBLK				Batch ID:	28308	Analys	is Date:	9/6/2011	11:18:49 A
Diesel Range Organics (DRO)	ND	mg/Kg	10					/			
Sample ID: LCS-28308		LCS	10			Batch ID:	28308	Analys	is Date:	9/6/2011	11:53:13 A
Diesel Range Organics (DRO)	52.45	mg/Kg	10	50	3.689	97.5	66.7	119		0/0/2011	
Sample ID: LCSD-28308	52.45	LCSD	10	50	0.000	Batch ID:	28308		is Date:	9/6/2011	12:27:34 P
Diesel Range Organics (DRO)	49.27	mg/Kg	10	50	3.689	91.2	66.7	119	6.25	18.9	
Method: EPA Method 8015B: C Sample ID: MB-28306	sasoline Kal	nge MBLK				Batch ID:	28306	Analyo	is Date:	0/6/2011	12:51:04 PI
	ND		5.0			Daton ID.	20300	Analys	is Date.	9/0/2011	12.51.04 F
Gasoline Range Organics (GRO)	ND	mg/Kg	5.0			Batch ID:	20200	Analuai	in Data:	0/6/2011	11:53:19 A
Sample ID: LCS-28306		LCS					28306		is Date:	9/0/2011	11:53:19 A
Gasoline Range Organics (GRO)	29.05	mg/Kg	5.0	25	0	116	86.4	132			
Method: EPA Method 8021B: V	olatiles/										
Sample ID: MB-28306		MBLK				Batch ID:	28306	Analysi	is Date:	9/6/2011	2:51:04 P
Benzene	ND	mg/Kg	0.050								
Foluene	ND	mg/Kg	0.050								
Ethylbenzene	ND	mg/Kg	0.050								
(ylenes, Total	ND	mg/Kg	0.10							0.10.15	
Sample ID: LCS-28306		LCS				Batch ID:	28306	Analysi	is Date:	9/6/2011 1	12:22:13 P
Benzene	0.9323	mg/Kg	0.050		0.0162	91.6	83.3	107			
Toluene	0.9707	mg/Kg	0.050	1	0	97.1	74.3	115			
Ethylbenzene	0.9465	mg/Kg	0.050	1	0	94.6	80.9	122			
Xylenes, Total	2.941	mg/Kg	0.10	3	0	98.0	85.2	123			

Qualifiers:

- E Estimated value
- J Analyte detected below quantitation limits

ND Not Detected at the Reporting Limit

- H Holding times for preparation or analysis exceeded
- NC Non-Chlorinated
- R RPD outside accepted recovery limits

Page 1

Hall Environmental Analysis Laboratory, Inc.

.

Sample	Rec	eipt Cl	necklist			
Client Name BLAGG			Date Receive	d:		9/2/2011
Work Order Number 1109075			Received by	MMG		
Checklist completed by:	Je) q/ Date	Sample ID la	bels checked	by:	Initials
Matrix: Carrier name:	Gre	yhound	e.			
Shipping container/cooler in good condition?	Yes	\checkmark	No 🗌	Not Present		
Custody seals intact on shipping container/cooler?	Yes	\checkmark	No 🗌	Not Present		Not Shipped
Custody seals intact on sample bottles?	Yes		No 🗌	N/A	\checkmark	
Chain of custody present?	Yes	\checkmark	No 🗌			
Chain of custody signed when relinquished and received?	Yes	\checkmark	No 🗔			
Chain of custody agrees with sample labels?	Yes	\checkmark	No			
Samples in proper container/bottle?	Yes	\checkmark	No 🗌			
Sample containers intact?	Yes	\checkmark	No 🗌			
Sufficient sample volume for indicated test?	Yes	\checkmark	No 🗌			
All samples received within holding time?	Yes		No 🗌			Number of preserved
Water - VOA vials have zero headspace? No VOA vials subm	itted		Yes	No		bottles checked for pH:
Water - Preservation labels on bottle and cap match?	Yes		No 🗌	N/A 🔽		
Water - pH acceptable upon receipt?	Yes		No 🗌	N/A 🗸		<2 >12 unless noted
Container/Temp Blank temperature?	3.	2°	<6° C Acceptabl	e		below.
COMMENTS:			If given sufficient	time to cool.		
				====		
Client contacted Date contacted:			Pers	on contacted		
Contacted by: Regarding:						
Comments:						2
						8
Corrective Action						

	hain-	of-Cu	stody Record	Turn-Around	Time:	19					1			E	MM	тс	20	DI B		NT	CAL	
Client:	BLAG	6 ENG	NEERING INC.	X Standard 🗆 Rush				HALL ENVIRONMENTAL														
				Project Name:				www.hallenvironmental.com														
BP AMERICA Mailing Address: P.O. Box 87				BARRETT A #1E				4901 Hawkins NE - Albuquerque, NM 87109														
				Project #:						el. 50								4107				
Phone #: 505-632-1199				-					10	1. 00	0-04	0-00	Statements.	Concernance.	of the local division of	COLUMN TWO IS NOT	uest	Statistics.	198			
email or Fax#:				Project Manager:					(yl	(les					04)							
QA/QC Package:				J. BLAGE				021	s or	Dies					4'SC	PCB's						
Standard Level 4 (Full Validation)								MB's (8021)	(Ga	Bas/					PO	2 PC						
				Sampler: J- BACC					TPH (Gas only)	TPH Method 8015B (Gas/Diesel)	÷.	·.1	T		Anions (F,Cl,NO ₃ ,NO ₂ ,PO ₄ ,SO ₄)	8081 Pesticides / 8082						î
NELAP Other EDD (Type)				Onice: Zives INS Sample Temperature: 2 ()				Н	+	8015	418	504.1)	(HAH)	S	203	es /		(VO)	N			or
	(Type)_			COCHADIC SHELM	SCHOLD C.	<u></u>		K-IMFBI	ATB	por	bod	thod	(PNA or	Meta	,CI,I	ticid	(YO)	V-im	RIC			es (
Date	Time	Matrix	Sample Request ID	Container	Preservative		Na		V + >	Meth	(Met	(Met	(PN	A 8 I	IS (F	Pes	B	(Sel	CHLURIDE			lddu
				Type and #	Туре		a-	BTEX	BTEX + MTBE	Hd	TPH (Method 418.1)	EDB (Method	8310 (RCRA 8 Metals	vnior	081	8260B (VOA)	8270 (Semi-VOA)	U			Air Bubbles (Y or N)
8/29/11	1010	SOIL	21 BGT -1	4oz XI	COUL	- 1		X	ш		×	m	80	UC.	A	8	8	00	×		+	4
11	1122	1	21 BGT 5-pt @ -6 95 BGT 5-pt @ -6	-lot x1	11	-2		X		x	x	-			-				\hat{x}		-	
	1122		5- 25 0-6			6		^				-			_				-	-	+	
				t								_							1		+	+
								-			_		-	-					-	-+	+	+
							2.5	-				-		_	-				-	-+	+	-
												_								-	+	-
								-				_							-	-	-+	+
-								-	-			_	_	-	_						+	
								-	-			_	_	_						-	+	
					1.0			-			<u> </u>									-	+	
																		-		-+	+	
Date:	Time:	Relinguish	ed by:	Received by: Date Time				Remarks: G-RO + DRO ON BUISB														
9/1/11	1304 Jeff Blogg			(have to 1) polar 9/11 1304					PAYKEY: ZSCHWIL BGT													
Date: Time: Relinquished by:			Received by: Date Time					NTA														
9/1/11	1612	Cha	iste Waller.	mi	w	ork	ioe t	NER	:1	14	106	,24										
			mitted to Hall Environmental may be sub-	contracted to other a	ccredited laboratori	es. This serves a	9:00 is notice of this	s possi	ibility.	Алу su	Jb-con	tracted	d data	will be	clear	ly nota	ated or	n the a	nalytic	al repo	rt.	

٧

*



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

August 16, 2011

bp

Bureau of Land Management Mark Kelly 1235 La Plata Hwy Farmington, NM 87401

VIA CERTIFIED MAIL – RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: BARRETT A 001E-MV/DK

Dear Bureau of Land Management,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about August 12, 2011. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

JDULAR

Jerry Van Riper Surface Coordinator/Business Security Representative BP America Production Company



