District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division

1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.
For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or
12783 Proposed Alternative Method Permit or Closure Plan Application LEIVED
Type of action:  Below grade tank registration  Permit of a pit or proposed alternative method  Closure of a pit, below-grade tank, or proposed alternative method  MAR 1 2 2015  MAR 1 2 2015  Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method  Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the
environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production CompanyOGRID#:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:State Gas Com K 1
API Number:3004510711OCD Permit Number:
U/L or Qtr/QtrLSection16Township31NRange11WCounty:San Juan
Center of Proposed Design: Latitude36.896228Longitude108.002427NAD: ☐1927 ☒ 1983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC     Temporary: Drilling Workover     Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no     Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other     String-Reinforced     Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3. Touls A
☑ Below-grade tank:       Subsection I of 19.15.17.11 NMAC       Tank A         Volume:       95.0       bbl Type of fluid:       Produced water
Tank Construction material:Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other Single walled/double bottomed; side walls not visible
Liner type: Thicknessmil
4.  Alternative Method:  Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Form C-144

`		
5.' Fencing: Subsection D of 19.15.17.11 NMAC (Applie	es to permanent pits, temporary pits, and below-grade tanks)	
	wire at top (Required if located within 1000 feet of a permanent residence, school,	hospital,
institution or church)  ☐ Four foot height, four strands of barbed wire evenly	y spaced between one and four feet	
Alternate. Please specify	<u> </u>	
6.		
Netting: Subsection E of 19.15.17.11 NMAC (Applied Screen ☐ Netting ☐ Other	s to permanent pits and permanent open top tanks)	
Monthly inspections (If netting or screening is not p	physically feasible)	
7.		
Signs: Subsection C of 19.15.17.11 NMAC		
12"x 24", 2" lettering, providing Operator's name,	site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC		
8.  Variances and Exceptions:  Justifications and/or demonstrations of equivalency are	; required. Please refer to 19.15.17 NMAC for guidance.	
	requested, if not leave blank: appropriate division district for consideration of approval. the Santa Fe Environmental Bureau office for consideration of approval.	
9.		
Siting Criteria (regarding permitting): 19.15.17.10 Instructions: The applicant must demonstrate complematerial are provided below. Siting criteria does not	iance for each siting criteria below in the application. Recommendations of accep	otable source
General siting		
Ground water is less than 25 feet below the bottom e - NM Office of the State Engineer - iWATER	of a low chloride temporary pit or below-grade tank.  RS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of NM Office of the State Engineer - iWATERS database	of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
adopted pursuant to NMSA 1978, Section 3-27-3, as ar	defined municipal fresh water well field covered under a municipal ordinance nended. (Does not apply to below grade tanks) nunicipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not - Written confirmation or verification or map fro	t apply to below grade tanks) om the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below gra- Engineering measures incorporated into the des Society; Topographic map	ide tanks) sign; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below - FEMA map	w grade tanks)	Yes No
Below Grade Tanks		
Within 100 feet of a continuously flowing watercourse, from the ordinary high-water mark).  - Topographic map; Visual inspection (certificat	significant watercourse, lake bed, sinkhole, wetland or playa lake (measured   ion) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water v - NM Office of the State Engineer - iWATERS of	well used for public or livestock consumption;. latabase search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Dr.	illing Fluid (maximum chloride content 15,000 mg/liter)	
	or any other significant watercourse or within 200 feet of any lakebed, sinkhole, nark). (Applies to low chloride temporary pits.)	☐ Yes ☐ No
Form C-144	Oil Conservation Division Page 2 of 6	

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
<ul> <li>application.</li> <li>Visual inspection (certification) of the proposed site; Aerial photo; Satellite image</li> </ul>	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.12 NMAC	
and 19.15.17.13 NMAC  Previously Approved Design (attach copy of design) API Number: or Permit Number:	
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	uments are
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  A List of wells with approved application for permit to drill associated with the pit.  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC  Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.	documents are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment	
☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC	
<ul> <li>Quality Control/Quality Assurance Construction and Installation Plan</li> <li>○ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC</li> <li>○ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC</li> <li>○ Nuisance or Hazardous Odors, including H₂S, Prevention Plan</li> <li>○ Emergency Response Plan</li> </ul>	
☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan	
☐ Erosion Control Plan	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative	Fluid Management Pit
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)	
On-site Closure Method (Only for temporary pits and closed-loop systems)	
☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method	
14.	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached.  □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sou provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
<ul> <li>Within an unstable area.</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	
Within a 100-year floodplain FEMA map	<ul><li>Yes ☐ No</li><li>Yes ☐ No</li></ul>
·	
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
Operator Application Certification:  I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature:  Title: OCD Permit Number:	12015
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date:8/10/2011	
20.	
Closure Method:  ☐ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-log ☐ If different from approved plan, please explain.	op systems only)

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure repelled. I also certify that the closure complies with all applicable closure requirements.	
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Voff Pose	Date:March 10, 2015
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

## BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

#### BELOW-GRADE TANK CLOSURE PLAN

### State Gas Com K 1 <u>API No. 3004510711</u> Unit Letter L, Section 16, T31N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

### **General Closure Plan**

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
  - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
  - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	7.5

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and will be reclaimed since it is outside the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT will be reclaimed since it is outside the active well area.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT will be reclaimed since it is outside the active well area.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT will be reclaimed since it is outside the active well area.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation since it is outside the active well area.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

## BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following:
  - a. proof of closure notification (surface owner and NMOCD)
  - b. sampling analytical reports; information required by 19.15.17 NMAC;
  - c. disposal facility name and permit number
  - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
  - e. site reclamation, photo documentation.
    - Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District 1 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

			Rele	ease Notific	catio	n and Co	orrective A	ction				
						OPERA'	ГOR		☐ Initia	al Report	$\boxtimes$	Final Report
						Contact: Jef	f Peace					
Unit Letter   Section   Township   Range   Feet from the   1,650    Latitude _ 36.896228				Telephone 1	No.: 505-326-94	179						
Name of Company: BP  Address: 200 Energy Court, Farmington, NM 87401  Facility Name: State Gas Com K 1  Surface Owner: State    Mineral County Courty			Facility Typ									
Name of Company: BP Address: 200 Energy Court, Farmington, NM 87401 Facility Name: State Gas Com K 1  Surface Owner: State  Unit Letter Section Township Range I Feet from the 1 10 16 31N 11W 1,650  Latitude 36.896228  NA  Type of Release: none Source of Release: below grade tank – 95 bbl Was Immediate Notice Given?  Yes No Not  By Whom?  Was a Watercourse Reached?  Yes No  If a Watercourse was Impacted, Describe Fully.*  Describe Cause of Problem and Remedial Action Taken.* Sampthe BGT. Soil analysis resulted in TPH, BTEX and chloride belong the solution of the soluti				Owner:	State			API No	. 3004510	711		
				LOCA	ATIO	N OF REI	LEASE					
Unit Letter	Section	Township	Range		,	South Line	Feet from the	East/W	est Line	County: S	an Juar	n
	1	_			South		790	West				
		Latit	ude 36.	896228		Longitud	e108.002427					
			_		ממוזי		-					
Type of Rele	ase: none		<del></del>	NAI	UKE	Volume of	Release: N/A		Volume F	Recovered: N		
		v grade tank –	95 bbl				lour of Occurrence	ce:		Hour of Dis		·:
						If YES, To						
			Yes 🗌	No 🛛 Not R	equired							
							lour	***				
Was a Water	course Read		🗖			If YES, Vo	lume Impacting t	the Water	course.			
		L	Yes 🔀	No								
If a Watercou	irse was Im	pacted, Descri	be Fully.*									
Describe Cau	se of Proble	em and Remed	dial Action	Taken * Sampli	no of th	e soil beneath	the BGT was do	ne during	removal	o ensure no	soil in	nnacts from
									, removar	o chaute no	3011 111	ipacis irom
	•		,			J						
Describe Are	o Affected	and Cleanup A	Notion Tols	on * DCT was ra	moved o	and the eree u	ndamaath tha DC	T was so	mpled Ti		ur tha D	OCT was
							nderneam me bo	ii was sa	ilipied. Ti	ic area unde	a uic b	od i was
I haraby aarti	fu that tha	nformation of	van abava	is two and samn	loto to ti	a boot of my	lenoveladaa and u	n danstan	d that man	want to NIM	OCD	ulos and
				tance of a C-141	report d	oes not reliev	e the operator of i	responsib	oility for co	ompliance w	ith any	, other
rederal, state,	or local lav	vs and/or regu	iations.				OIL CONS	SEDW.	ATION	DIVISIO		
	00	$\mathcal{L}$					OIL COIN	SEIX V Z	ALION	DIVISIC	<u> </u>	
Signature:	V9945	Pasel										
Printed Name	O V V					Approved by Environmental Specialist:						
Fillited Name	. Jen reace	·			-							
Title: Field E	<u>nvironme</u> nt	al Coordinato	<u>r</u>		,	Approval Dat	e:	E	xpiration l	Date:		
						G 11.1						
E-mail Addre	ss: peace.je	ttrey@bp.con	<u>n</u>	<u> </u>		Conditions of	Approval:			Attached		
Date: March	10, 2015		Phone: 5	05-326-9479								

<sup>\*</sup> Attach Additional Sheets If Necessary

ВР	API#: 3004510711					
CLIEN I:		ა 	TANK ID (if applicble):	Α		
FIELD REPORT:	(circle one): BGT CONFIRMATION / RE	ELEASE INVESTIGATION / OTHER:		PAGE #:	<b>1</b> of	_1
SITE INFORMATION	I: SITE NAME: STATE GO	C K #1		DATE STARTED:	08/0	1/11
QUAD/UNIT: L SEC: 16 TWP:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER:    Confirmation   Site name   State GC   K #1					
1/4-1/4/FOOTAGE: 1,650'S/790'\	STEIN   P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199 (Fi applicable):   TANK ID (Fi applicable):					
LEASE#:	PROD. FORMATION: MV CONT	TRACTOR: ELKHORN			JC	B
REFERENCE POINT	-: WELL HEAD (W.H.) GPS CC	OORD.: 36 89603 X 108	00217	GLELI	EV.: <b>5</b> .	.960
· · · · · ·			STANCE/BE/	ARING FROM W.H.:		
4)	GPS COORD.:	DI:	STANCE/BE/	ARING FROM W.H.:		
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR L	AB USED: HALL				OVM READING
	5' SAMPLE DATE: 08/01/11		418.1/8	3015B/8021B/30	00.0 (CI)	(ppm) <b>0.0</b>
. •			-	-		
4) SAMPLEID:	SAMPLE DATE:	SAMPLE TIME: LAB ANALYSIS:				
SOIL DESCRIPTION	SOIL TYPE: SAND / SILTY SA	ND SILT / SILTY CLAY / CLAY / GRA	VEL / OTI	HER		
SOIL COLOR:			·• ·			
· · · · · · · · · · · · · · · · · · ·		` '				
<del></del> -		· ·	•			
		HC ODOR DETECTED: YES [N	OI FXPD	ANATION		
NAME OF THE OWNER	7				-	
·		ATOP BGT POSITION.				
ADDITIONAL COMMENTE.		Allei seri serier.				
OOU INADAOT DINAENCIONI ESTIMATIONI	NA A Y NA A	V NA A EVCAVAT	TONEST	** * ATION! (Oubio Vo	· J_ \ ,	NIA .
				·		ppm
SITE SKETCH		DLOT DLAN sirele: attach		ANNO DEAD		<del></del>
OFFE CINETON		PLOTPLAN CITCLE. ALLACIN				111 - 0.02
	PBGTL					
$(x \hat{x} x) \leftarrow$	- T.B. ~ 5'	17				
P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199  FIELD REPORT:  (dirde one): BGT CONFRMATION] / RELEASE INVESTIGATION / OTHER  SITE INFORMATION: SITE NAME STATE GC K #1  QUADUNIT L SEC: 16 run: 31N ring: 11W pm. NM only: SJ st. NM  1/4-1/4/FOOTAGE: 1,650'S/790'W NW/SW LEASE TYPE: FEDERAL STATE FEE / INDIAN LEASE # PROD. FORMATION: MV CONTRACTOR ELKHORN  SFECALIST(S): JCB  REFERENCE POINT: WELL HEAD (WH.) GPS COORD: 36.89603 X 108.002427 DISTANCEBEARING FROM WH.  2) GPS COORD: 36.896228 X 108.002427 DISTANCEBEARING FROM WH.  2) GPS COORD: DISTANCEBEARING FROM WH.  3) GPS COORD: DISTANCEBEARING FROM WH.  4) GPS COORD: DISTANCEBEARING FROM WH.  4) GPS COORD: DISTANCEBEARING FROM WH.  4) GPS COORD: SWAFE THE LIBRANGES  SAMPLING DATA: CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL  1) SAMPLEID: SWAFE WE SWAFE THE LIBRANGES  SAMPLEID: SWAFE WE SWAFE WE LIBRANGES  SWAFE THE LIBRANGES  SWAFE WE LIBRANGES  MOSTINEE DISTANCEBEARING FROM WH.  2) SAMPLEID: SWAFE WE SWAFE WE LIBRANGES  SWAFE WE LIBRANGE						
					<u> </u>	
					I DCT	
			'-	) #. <u> </u>	<u>)-U</u>	
		$\oplus$	-	Permit date(s):	06/14/1	0
						-
		X - S.P.	D A			
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATIV	ON DEPRESSION; B.G. = BELOW GRADE; B = BELOW	t, T.H. = TEST HOLE; ~ = APPROX.; W.H. = WELL HE	AD;			
	OW-GRADE TANK LOCATION; SPD = SAMPLE POINT E WALL; DW - DOUBLE WALL; SB - SINGLE BOTTOM;		<sup>Г</sup>   <u>М</u>	agnetic declinat	ion: 10	<u>E</u>
TRAVEL NOTES: CALLOUT:	08/01/11	ONSITE: 08/01/11				

## Hall Environmental Analysis Laboratory, Inc.

Date: 10-Aug-11 Analytical Report

CLIENT:

Blagg Engineering

Lab Order:

1108123

Client Sample ID: 95 BGT 5-pt @ -5'

Collection Date: 8/1/2011 2:58:00 PM

Project: Lab ID: STATE GCK #1

1108123-01

Date Received: 8/2/2011

Matrix: SO1L

Analyses	Result	PQL Q	ual Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	E ORGANICS				Analyst: JB
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	8/5/2011 3:48:16 PM
Surr: DNOP	95.9	73.4-123	%REC	1	8/5/2011 3:48:16 PM
EPA METHOD 8015B: GASOLINE RA	NGE				Analyst: RAA
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	8/5/2011 5:14:27 PM
Surr: BFB	96.4	75.2-136	%REC	1	8/5/2011 5:14:27 PM
EPA METHOD 8021B: VOLATILES					Analyst: RAA
Benzene	ND	0.047	mg/Kg	1	8/5/2011 5:14:27 PM
Toluene	ND	0.047	mg/ <b>Kg</b>	1	8/5/2011 5:14:27 PM
Ethylbenzene	ND	0.047	mg/Kg	1	8/5/2011 5:14:27 PM
Xylenes, Total	ND	0.094	mg/Kg	1	8/5/2011 5:14:27 PM
Surr: 4-Bromofluorobenzene	105	90.3-115	%REC	1	8/5/2011 5:14:27 PM
EPA METHOD 300.0: ANIONS					Analyst: SRM
Chloride	7.5	1.5	mg/Kg	1	8/6/2011 12:01:17 AM
EPA METHOD 418.1: TPH					Analyst: JB
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	8/9/2011

#### Qualifiers:

- Value exceeds Maximum Contaminant Level
- Е Estimated value
- Analyte detected below quantitation limits
- Non-Chlorinated
- PQL Practical Quantitation Limit

- В Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded Н
- MCL Maximum Contaminant Level
- Not Detected at the Reporting Limit
- Spike recovery outside accepted recovery limits

Date: 10-Aug-11

# **QA/QC SUMMARY REPORT**

Client:

Blagg Engineering

**Project:** STATE GCK #1

Work Order:

1108123

											1100123
Analyte	Result	Units	PQL	SPK Va S	SPK ref	%Rec L	owLimit Hi	ghLimit	%RPD	RPDLimit	Qual
Method: EPA Method 300.0: A	nions										
Sample ID: MB-27922		MBLK				Batch ID:	27922	Analys	sis Date:	8/5/2011 1	0:34:14 PN
Chloride	ND	mg/Kg	1.5								
Sample ID: LCS-27922		LCS				Batch ID:	27922	•	sis Date:	8/5/2011 1	0:51:38 PN
Chloride	14.04	mg/Kg	1.5	15	0	93.6 —-	90	110			
Method: EPA Method 418.1: T	PH										
Sample ID: MB-27933		MBLK				Batch ID:	27933	Analys	is Date:		8/9/201
Petroleum Hydrocarbons, TR	ND	mg/Kg	20								
Sample ID: LCS-27933		LCS				Batch ID:	27933	Analys	is Date:		8/9/201
Petroleum Hydrocarbons, TR	95.06	mg/Kg	20	100	0	95.1	87.8	115			
Sample ID: LCSD-27933		LCSD				Batch ID:	27933	Analys	is Date:		8/9/201
Petroleum Hydrocarbons, TR	101.6	mg/Kg	20	100	0	102	87.8	115	6.61	8.04	
Method: EPA Method 8015B: I	Diesel Range	Organics									
Sample ID: 1108123-01AMSD	·	MSD				Batch ID:	27907	Analys	is Date:	8/5/2011	4:5 <b>7</b> :37 PN
Diesel Range Organics (DRO)	47.81	mg/Kg	10	49.8	0	96.0	61.9	125	6.03	22.3	
Sample ID: MB-27907		MBLK				Batch ID:	27907	Analys	is Date:	8/5/2011	7:56:31 AN
Diesel Range Organics (DRO)	ND	mg/Kg	10								
Sample ID: LCS-27907		LCS				Batch ID:	27907	Analys	is Date:	8/5/2011 8	3:30:54 AN
Diesel Range Organics (DRO)	39.99	mg/Kg	10	50	0	80.0	66.7	119			
Sample ID: LCSD-27907		LCSD				Batch ID:	27907	Analys	is Date:	8/5/2011 9	9:05:15 AM
Diesel Range Organics (DRO)	43.90	mg/Kg	10	50	0	87.8	66.7	119	9.31	18.9	
Sample ID: 1108123-01AMS		MS				Batch ID:	<b>27</b> 9 <b>07</b>	Analys	is Date:	8/5/2011 4	1:22:58 PN
Diesel Range Organics (DRO)	45.01	mg/Kg	9.8	48.88	0	92.1	61.9	125			
Method: EPA Method 8015B: 0	Gasoline Rar	nge									
Sample ID: MB-27886		MBLK				Batch ID:	27886	Analys	is Date:	8/5/2011 10	:09:14 AN
Gasoline Range Organics (GRO)	ND	mg/Kg	5.0								
Sample ID: LCS-27886		LCS				Batch ID:	27886	Analys	is Date:	8/5/2011 12	2:03:29 PM
Gasoline Range Organics (GRO)	30.64	mg/Kg	5.0	25	0	123	86.4	132			

### Qualifiers:

E Estimated value

J Analyte detected below quantitation limits

NC Non-Chlorinated

R RPD outside accepted recovery limits

Date: 10-Aug-11

# QA/QC SUMMARY REPORT

Client:

Blagg Engineering

Project:

STATE GCK #1

Work Order:

1108123

Analyte	Result	Units	PQL	SPK Va	SPK ref	%Rec L	owLimit Hi	ghLimit	%RPD	RPDLimit	Qual
Method: EPA Method 8021B:	Volatiles										
Sample ID: 1108123-01A MSD		MSD				Batch ID:	27886	Analysi	is Date:	8/5/2011 11	1:58:15 PM
Benzene	1.169	mg/Kg	0.047	0.941	0	124	67.2	113	6.48	14.3	S
Toluene	1.220	mg/Kg	0.047	0.941	0	130	62.1	116	8.04	15.9	S
Ethylbenzene	1.252	mg/Kg	0.047	0.941	0	133	67.9	127	5.69	14.4	S
Xylenes, Total	3.795	mg/Kg	0.094	2.822	0	134	60.6	134	6.26	12.6	S
Sample ID: MB-27886		MBLK				Batch ID:	27886	Analysi	is Date:	8/5/2011 10	0:09:14 AM
Benzene	ND	mg/Kg	0.050								
Toluene	ND	mg/Kg	0.050								
Ethylbenzene	ND	mg/Kg	0.050				•				
Xylenes, Total	ND	mg/Kg	0.10								
Sample ID: LCS-27866		LCS				Batch ID:	27886	Analysi	is Date:	8/5/2011 12	:32:12 PM
Benzene	0.9503	mg/Kg	0.050	1	0	95.0	83.3	107			
Toluene	0.9900	mg/Kg	0.050	1	0	99.0	74.3	115			
Ethylbenzene	1.011	mg/Kg	0.050	1	0	101	80.9	122			
Xylenes, Total	3.050	mg/Kg	0.10	3	0	102	85.2	123			
Sample ID: 1108123-01A MS		MS				Batch ID:	27886	Analysi	s Date:	8/5/2011 11	:29:23 PM
Benzene	1.247	mg/Kg	0.049	0.984	0	127	67.2	113			s
Toluene	1.322	mg/Kg	0.049	0.984	0	134	62.1	116			s
Ethylbenzene	1.325	mg/Kg	0.049	0.984	0	135	67.9	127			s
Xylenes, Total	4.040	mg/Kg	0.098	2.953	0	137	60.6	134			S

E Estimated value

J Analyte detected below quantitation limits

NC Non-Chlorinated

R RPD outside accepted recovery limits

# Hall Environmental Analysis Laboratory, Inc.

## Sample Receipt Checklist

Client Name BLAGG	Date Re	ceived:	8/2/2011							
Work Order Number 1108123	Receive	ed by: LNM								
Checklist completed by: Signature	· · · · · · · · · · · · · · · · · · ·	Sample Spale	ID labels checked I	by: Diffiels						
Matrix:	Carrier name: Greyho	ound								
Shipping container/cooler in good condition?	Yes 🕨	Ø No □	Not Present							
Custody seals intact on shipping container/cooler?	Yes 🖢	<b>Ø</b> No □	Not Present	☐ Not Shipped ☐						
Custody seals intact on sample bottles?	Yes [	□ No □	N/A	<b>✓</b>						
Chain of custody present?	Yes 🛂	No 🗆								
Chain of custody signed when relinquished and received	ved? Yes 🗹	Ø No□								
Chain of custody agrees with sample labels?	Yes 🛂	Ø No □								
Samples in proper container/bottle?	Yes 🔽	No 🗆								
Sample containers intact?	Yes 🖳	No 🗌								
Sufficient sample volume for indicated test?	Yes 🖳	No 🗆								
All samples received within holding time?	Yes 🖳	Ø No □		Number of preserved						
Water - VOA vials have zero headspace?	VOA vials submitted 🖳	Yes 🗌	No 🗌	bottles checked for pH:						
Water - Preservation labels on bottle and cap match?	Yes 🗆	] No □	N/A 🗹							
Water - pH acceptable upon receipt?	Yes 🗆	] No □	N/A	<2 >12 unless noted						
Container/Temp Blank temperature?	2.9°		-	below.						
COMMENTS:		If given suff	iclent time to cool.							
	======									
Client contacted Date	contacted:		Person contacted							
Contacted by: Rega	arding:									
Comments:										
Corrective Action		the statement and a statement		-						

C	hain	of-Cu	stody Record	Turn-Around	Time:	<del></del>					_											
Client: BLAGG ENGINEERING INC. BP AMERICA			Standard □ Rush				HALL ENVIRONMENTAL															
			Project Name:						ANALYSIS LABORATORY  www.hallenvironmental.com													
Mailing	Address	P n 1	Sox: 87	STATE G	c K #1				400	04.11									400			
		13/ day 1	Deal of Alm	Project #:	·	·		1		01 H												
Phone		505-1	Aireld, NM 632-1199	1				13		el. 50								410 。				a are
email o		203	2)0 - 11 [1	Project Mana	nger:	-									_			.a)``^	india.	<u> </u>		35 0
QA/QC	Package:		☐ Level 4 (Full Validation)	J.H E	Ū			-EMB's (8021)	Gas on	as/Dies					PO4,SO	PCB's						
Accred	itation	□ Othe		Sampler:	Teff Bleg	9 451 No.2			F TPH (	15B (G	418.1)	504.1)	AH)		3,NO <sub>2</sub> ,	/ 8082		(a				Ş
	(Type)				perature	29			出	80	d 41	)d 5(	or P	tals	N,	ides	7	0	ايها			ځ
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	162 162	LNO.	BTEX + WATBE-	BTEX + MTBE + TPH (Gas only)	TPH Method 8015B (Gas/Diesel)	TPH (Method	EDB (Method	8310 (PNA or PAH)	RCRA 8 Metals	Anions (F,CI,NO3,NO2,PO4,SO4)	8081 Pesticides / 8082	8260B (VOA)	8270 (Semi-VOA)	CHOLINE			Air Bubbles (Y or N)
e//11	1453	SOIL	95 BGT 5-Pte-5	402×1	COUL		- 1	×		X	X			_					X	$\neg$	$\top$	
				-																十		
																				_	$\top$	$\top$
									-					_						7	$\top$	$\top$
						-		ļ											$\exists$	_	$\top$	$\dagger$
				-				1											$\exists$	$\top$	十	-
																			$\neg$	_	$\top$	$\uparrow$
							- <del></del>	<b>†</b>												_	$\top$	7
							***************************************												$\Box$	$\neg$	$\top$	1
														-						$\top$		$\top$
																				$\top$	$\top$	$\top$
Date:	Time:	Relinquish	ed by: Slag	Received by: Date Time  Whyste   bets 8//11 1541		Remarks: GRO + DRO ON BOISB WORKORDER: N 1389466																
Date:	Time:	Relinquish	ed by:	Received by:		Date	Time			<b>∤∶</b> ₹									٠			
<u> 1411                                 </u>	I II O If necessary,	samples sub	mitted to Hall Environmental may be sub-	Department of the contract of	ogredited laboratoric	es. This serve	s as notice of this	1s possi	bility.	Any su	b-conf	tracted	d data	will be	dear	ty nata	ited or	the a	nalytic	al repor	t.	



