District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr.

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

Form C-144

Revised June 6, 2013

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Below-Grade Tank, or

Santa Fe, NM 87505

12 795 Proposed Alternative Method Permit or Closure Plan Application
Type of action:
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID #:778_
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Riddle F LS 11 MAR 1 6 2015
API Number:3004521145OCD Permit Number:
U/L or Qtr/QtrESection20Township28NRange8WCounty:San JuanNMOCD
Center of Proposed Design: Latitude36.65015 Longitude107.71075 NAD: ☐ 1927 ☑ 1983 Surface
Owner: Nederal State Private Tribal Trust or Indian Allotment
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Below-grade tank: Subsection I of 19.15.17.11 NMAC Tank A
Volume:45.0bbl Type of fluid:Produced water
Tank Construction material:Steel
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other _Double walled/double bottomed; side walls not visible
Liner type: Thicknessmil
4. Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Form C-144

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify Alternate.										
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)										
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC										
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.										
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source									
General siting										
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	☐ Yes ☐ No ☐ NA									
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No									
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No									
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No									
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No									
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	☐ Yes ☐ No									
Below Grade Tanks										
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	2:									
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No									

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No										
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 											
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site											
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site											
Temporary Pit Non-low chloride drilling fluid											
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No										
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image											
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site											
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No										
Permanent Pit or Multi-Well Fluid Management Pit											
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No										
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No										
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No										
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No										
Emporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are trached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC											
Previously Approved Design (attach copy of design) API Number: or Permit Number:											
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC											
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC											
Previously Approved Design (attach copy of design) API Number: or Permit Number:											

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Clip Held Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well For Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
14. Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a	attached to the
closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. F 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland.	
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality											
	☐ Yes ☐ No										
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No										
Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological											
Society; Topographic map											
Within a 100-year floodplain FEMA map											
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC											
17. Operator Application Certification:											
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.										
Name (Print):											
Signature: Date:											
e-mail address: Telephone:											
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: 4/14/2015											
Title: Comprime Office OCD Permit Number:											
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:2/2/2015	the closure report.										
Title: OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	the closure report. complete this										

22.									
Operator Closure Certification:									
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.									
Name (Print):Jeff Peace	Title: Field Environmental Coordinator								
Signature: Jeff Pexel	Date:March 13, 2015								
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479								

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Riddle F LS 11 API No. 3004521145 Unit Letter E, Section 20, T28N, R8W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Notice is attached.

- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- i. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	45 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned as part of final reclamation.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505

* Attach Additional Sheets If Necessary

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-141

Revised August 8, 2011

Release Notification and Corrective Action														
					OPERATOR Initial Report I									
Name of Co					Contact: Jeff Peace									
		Court, Farm	ington, N	M 87401			No.: 505-326-94							
Facility Nar	ne: Riddle	e F LS II				Facility Typ	e: Natural gas v	vell						
Surface Ow	ner: Feder	al		Mineral C	wner:]	Federal		1	API No	. 30045211	145			
				LOCA	TION	OF REI	LEASE							
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	East/Wes	t Line	County: Sa	an Juar	1		
E	20	28N	8W	1,460	North		800	West						
,		Lat	itude_3	6.65015		Longitud	e107.71075							
				NAT	URE	OF RELI	EASE							
Type of Relea							Release: N/A	V	olume F	Recovered: N	J/A			
Source of Re	lease: belov	w grade tank –	- 45 bbl			Date and H N/A	lour of Occurrenc	e: D	ate and	Hour of Dis	covery	: N/A		
Was Immedia	ate Notice (Given?				If YES, To	Whom?							
			Yes	No Not Re	equired									
By Whom?		1 10				Date and H								
Was a Watercourse Reached? ☐ Yes ☒ No						If YES, Volume Impacting the Watercourse.								
If a Watercou	irse was Im	pacted, Descr	ibe Fully.	4										
				n Taken.* Sampli					emoval	to ensure no	soil in	npacts from		
the BGT. So	il analysis i	resulted in TP.	H, BTEX	and chlorides belo	w stand	ards. Analys	is results are attac	ched.						
Describe Are	a Affected	and Cleanup	Action Tal	ten.* BGT was re	moved o	and the area u	ndarnaath the DC	Т мас сат	nled T	he area unde	r the D	GT was		
				active well area.	moved a	iliu ilie area u	ilderifeatif the BO	i was saiii	picu. 1	ne area unde	i uic D	our was		
	•													
I hereby certi	fy that the	information gi	iven above	is true and comp	lete to th	ne best of my	knowledge and u	nderstand t	hat purs	suant to NM	OCD ri	ules and		
				nd/or file certain r										
				ce of a C-141 report investigate and re										
or the environ	nment. In a	addition, NMC	OCD accep	tance of a C-141	report de	oes not reliev	e the operator of i	responsibili	ty for c	ompliance wa	ith any	other		
		ws and/or regu												
٨		0					OIL CONS	SERVA'	<u> </u>	DIVISIO	N			
Signature:	off 1	Posee												
Printed Name					a	Approved by	Environmental S ₁	pecialist:						
Tillica Ivallic	. Jen reac													
Title: Field E	nvironmen	tal Coordinate	or			Approval Dat	e:	Exp	iration	Date:				
E-mail Addre	ess: peace.j	effrey@bp.co	m			Conditions of Approval:			Attached					
Date: March	13, 2015		Phone:	505-326-9479										

CLIENT: BP	P.O. BOX 87,	ENGINEERING, BLOOMFIELD, 505) 632-1199		API #: 3004521 TANK ID (if applicble): A	
FIELD REPORT:	/ OTHER:	PAGE#: 1 o	f 1		
SITE INFORMATION	: SITE NAME: RIDDL	E F LS #11		DATE STARTED: 01/2	29/15
QUAD/UNIT: E SEC: 20 TWP:	28N RNG: 8W P	M: NM CNTY: S	SJ ST: NM	DATE FINISHED:	
1/4 -1/4/FOOTAGE: 1,460'N / 80)'W SW/NW LEAS	E TYPE: FEDERAL STA	ATE / FEE / INDIAN	ENVIRONMENTAL	
LEASE #: SF080112	PROD. FORMATION: PC	CROSS CONTRACTOR: MBF -	SFIRE C. KENNETH	SPECIALIST(S):	JV
REFERENCE POINT	WELL HEAD (W.H.) G	PS COORD.: 36.6	5010 X 107.71070	GL ELEV.: 5	.739'
	GPS COORD.:				
2)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
3)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
4)	GPS COORD.:		DISTANCE/BEA	RING FROM W.H.:	
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S)	# OR LAB USED:	ALL		OVM READING
1) SAMPLE ID: 5PC-TB@6'	45) SAMPLE DATE: 01/2	9/15 SAMPLE TIME: 073	BO LAB ANALYSIS: 418	3.1/8021B/300.0 (CI)	(ppm)
2) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
3) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
4) SAMPLE ID:	SAMPLE DATE:	SAMPLE TIME:	LAB ANALYSIS:		
SOIL DESCRIPTION	SOIL TYPE: SAND SILTY SAND	SILT / SILTY CLAY / CLAY / G	RAVEL / OTHER		
SOIL COLOR: DARK YELLOW				OHESIVE / MEDIUM PLASTIC / HIGH	ILY PLASTIC
COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY		E DENSITY (COHESIVE CLAY		STIFF / VERY STIFF / HARD	
CONSISTENCY (NON COHESIVE SOILS): LC			NO EXPLANATION -		
MOISTURE: DRY/SLIGHTLYMOIST/MOIST/W SAMPLE TYPE: GRAB/COMPOSITE.#			ETNESS: YES NO EXPLA	NATION -	
DISCOLORATION/STAINING OBSERVED: YES IN		ANT AREAG DIGI EATING WE	THEOD. TEO THO EXPEN	WHON-	
SITE OBSERVATION	S: LOST INTEGRITY OF EQUIPME	NT: YES NO EXPLANATION -			
APPARENT EVIDENCE OF A RELEASE OBSERVE		PLANATION:		,	
EQUIPMENT SET OVER RECLAIMED AREA: OTHER:	res NO Explanation -				
SOIL IMPACT DIMENSION ESTIMATION:	NA ft. X NA			FIMATION (Cubic Yards) :	NA
	EAREST WATER SOURCE: >1,00			CD TPH CLOSURE STD: 10	D ppm
SITE SKETCH	BGT Located: off on	PLOT PLAN	circle: attached 0VM	CALIB. READ. = NA pp	111 -0.02
				CALIB. GAS = NA pp	
		METER	N TIME		NA
		RUN		MISCELL. NO	ΓES
	BERM			vo: N15529608	
	Y			0#:	
PBGTL T.B. ~ 6'				K:	
TO B.G.	$(x \ddot{x} \dot{x})$	BULLET	1 -	J #: ermit date(s): 06/14	/10
EPHEMERAL WASH FENCE		SEPARATOR		CD Appr. date(s): 11/16	
	W.H.			nk OVM = Organic Vapor Me	ter
			Ä		N
			X - S.P.D.	BGT Sidewalls Visible: Y /	N
NOTES: BGT = BELOW-GRADE TANK; E.D. = EXCAVATION			ROX.; W.H. = WELL HEAD;	BGT Sidewalls Visible: Y /	
T.B. = TANK BOTTOM; PBGTL = PREVIOUS BEL APPLICABLE OR NOT AVAILABLE; SW - SINGLI	WALL; DW - DOUBLE WALL; SB - SINGLE E	SOTTOM; DB - DOUBLE BOTTOM.		Magnetic declination: 10) E
NOTES: GOOGLE EARTH IMAG	RY DATE: 05/02/2013.	ONSITE: 01	/29/15		

Analytical Report

Lab Order 1501A55

Date Reported: 2/2/2015

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Client Sample ID: 5PC-TB @ 6' (45)

Project: RIDDLE F LS #11

Collection Date: 1/29/2015 7:30:00 AM

Lab ID: 1501A55-001

Matrix: SOIL

Received Date: 1/30/2015 7:35:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8021B: VOLATILES					Analys	t: NSB
Benzene	ND	0.035	mg/Kg	1	1/30/2015 10:26:06 AM	A 17463
Toluene	ND	0.035	mg/Kg	1	1/30/2015 10:26:06 AM	A 17463
Ethylbenzene	ND	0.035	mg/Kg	1	1/30/2015 10:26:06 AM	A 17463
Xylenes, Total	ND	0.070	mg/Kg	1	1/30/2015 10:26:06 AM	A 17463
Surr: 4-Bromofluorobenzene	106	80-120	%REC	1	1/30/2015 10:26:06 AM	17463
EPA METHOD 300.0: ANIONS					Analys	t: Igp
Chloride	ND	30	mg/Kg	20	1/30/2015 11:11:03 AM	A 17475
EPA METHOD 418.1: TPH					Analys	t: BCN
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	1/30/2015 1:00:00 PM	17460

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 4

- P Sample pH greater than 2.
- RL Reporting Detection Limit

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1501A55 02-Feb-15

Client:

Blagg Engineering

Project:

RIDDLE F LS #11

Sample ID MB-17475

SampType: MBLK

TestCode: EPA Method 300.0: Anions

LowLimit

Client ID:

Batch ID: 17475

PQL

RunNo: 24018

SPK value SPK Ref Val

Prep Date:

1/30/2015

Analysis Date: 1/30/2015

SeqNo: 708259

%REC

Units: mg/Kg HighLimit

Analyte

Result

RPDLimit

Qual

Chloride

ND 1.5

Sample ID LCS-17475

SampType: LCS

TestCode: EPA Method 300.0: Anions RunNo: 24018

LCSS Prep Date: 1/30/2015 Batch ID: 17475

Client ID:

Analysis Date: 1/30/2015

SeqNo: 708260

Units: mg/Kg

Analyte

RPDLimit

Qual

Result

%REC

14

110

SPK value SPK Ref Val

%RPD

Chloride

93.4

PQL 1.5

0

15.00

LowLimit 90 HighLimit

%RPD

Qualifiers:

E

Value exceeds Maximum Contaminant Level. Value above quantitation range

Analyte detected below quantitation limits RSD is greater than RSDlimit 0

RPD outside accepted recovery limits R Spike Recovery outside accepted recovery limits Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit ND

Sample pH greater than 2

Reporting Detection Limit

RL

Page 2 of 4

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#:

1501A55

02-Feb-15

Client:

Blagg Engineering

Project:

RIDDLE F LS #11

Sample ID MB-17460

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID: PBS

Batch ID: 17460

RunNo: 24008

Analysis Date: 1/30/2015

SeqNo: 707833

Prep Date:

1/29/2015

PQL SPK value SPK Ref Val

20

Units: mg/Kg

Analyte

Result ND %REC LowLimit HighLimit

RPDLimit

Qual

Petroleum Hydrocarbons, TR Sample ID LCS-17460

SampType: LCS

RunNo: 24008

TestCode: EPA Method 418.1: TPH

%RPD

%RPD

Client ID:

LCSS

Batch ID: 17460

Prep Date:

1/29/2015

Analysis Date: 1/30/2015

100.0

SeqNo: 707834

Units: mg/Kg

RPDLimit

Analyte Petroleum Hydrocarbons, TR

Result PQL

100

SPK value SPK Ref Val

%REC 103

86.7

LowLimit

HighLimit 126 Qual

Qual

Sample ID LCSD-17460

SampType: LCSD

20

TestCode: EPA Method 418.1: TPH

Client ID:

LCSS02

Batch ID: 17460

RunNo: 24008

126

Prep Date:

1/29/2015

Analysis Date: 1/30/2015

100

SegNo: 707835

Units: mg/Kg HighLimit

%RPD **RPDLimit**

Analyte Petroleum Hydrocarbons, TR PQL SPK value SPK Ref Val %REC 20

100.0

LowLimit

86.7

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits

RSD is greater than RSDlimit 0

R RPD outside accepted recovery limits

Spike Recovery outside accepted recovery limits

P Sample pH greater than 2

J

RL Reporting Detection Limit

Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded Not Detected at the Reporting Limit ND

Page 3 of 4

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

3.1

1.1

0.10

3.000

1.000

WO#:

1501A55 02-Feb-15

Client:

Blagg Engineering

Project:

Xylenes, Total

Surr: 4-Bromofluorobenzene

RIDDLE F LS #11

Sample ID MB-17463	SampType: MBLK TestCode: EPA Method 8021B: Volatiles									
Client ID: PBS	Batch ID:	17463	F							
Prep Date: 1/29/2015	Analysis Date:	1/30/2015	5	SeqNo: 70	08415	Units: mg/K	g			
Analyte	Result P	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	ND 0.	050								
Toluene	ND 0.	050								
Ethylbenzene	ND 0.	050								
Kylenes, Total	ND 0	0.10								
Surr: 4-Bromofluorobenzene	1.1	1.000		107	80	120				
Sample ID LCS-17463	SampType	: LCS	Tes	tCode: EF	PA Method	8021B: Volat	iles			
Client ID: LCSS	Batch ID:	17463	F	RunNo: 24	1020					
Prep Date: 1/29/2015	Analysis Date:	1/30/2015	5	SeqNo: 70	08416	Units: mg/K	g			
Analyte	Result P	QL SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
Benzene	1.1 0.0	050 1.000	0	106	80	120				
Toluene	1.0 0.0	050 1.000	0	99.7	80	120				
Ethylbenzene	1.0 0.0	050 1.000	0	103	80	120				

0

104

115

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded

120

120

80

80

- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2.
- RL Reporting Detection Limit

Page 4 of 4



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107

Website: www.hallenvironmental.com

Sample Log-In Check List

BLAGG Client Name: Work Order Number: 1501A55 RcptNo: 1 -01/30/15 Received by/date: anne Stram Logged By: **Anne Thorne** 1/30/2015 7:35:00 AM anne Mr. Completed By: Anne Thorne 1/30/2015 30/15 Reviewed By: Chain of Custod 1. Custody seals intact on sample bottles? Not Present 🗸 Yes Yes 🗸 No 🗌 Not Present 2. Is Chain of Custody complete? 3 How was the sample delivered? Courier Log In 4. Was an attempt made to cool the samples? Yes 🗸 No NA . 5. Were all samples received at a temperature of >0° C to 6.0°C No 🗌 NA 🗌 Yes V No 🗌 6. Sample(s) in proper container(s)? No 7. Sufficient sample volume for indicated test(s)? **V** No 8. Are samples (except VOA and ONG) properly preserved? Yes [No V NA 🗌 9. Was preservative added to bottles? No VOA Vials 10. VOA vials have zero headspace? Yes No 🗌 Yes No V 11. Were any sample containers received broken? # of preserved bottles checked Yes 🗸 No 🗌 for pH: 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) Adjusted? V No 13 Are matrices correctly identified on Chain of Custody? Yes V No 🗌 14. Is it clear what analyses were requested? No 🗌 15. Were all holding times able to be met? Checked by: Yes 🗸 (If no, notify customer for authorization.) Special Handling (if applicable) Yes NA V 16. Was client notified of all discrepancies with this order? No 🗌 Person Notified: Date By Whom: Via: Phone Fax eMail Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Cooler No Temp °C Condition Seal Intact | Seal No | Seal Date | Signed By 1.0 Good

Chain-of-Custody Record			Turn-Around	liffe.	SAME			150	н	AL	LE	N	/TF	30	NI	ME	NT	A	L	
Client:	Client: BLAGG ENGR. / BP AMERICA			Standard	Rush _	DAY)				-							RA			
					· · · · · · · · · · · · · · · · · · ·	NACONAL PROPERTY OF THE PARTY O										l.com				_
Mailing A	Mailing Address: P.O. BOX 87		RIDOLE	F LS	7 11		490	01 Ha								37109	9			
	BLOOMFIELD, NM 87413			Project #:						5-345			-			-410				
Phone #:	Phone #: (505) 632-1199			1			Analysis Request													
	email or Fax#:			Project Manag	ger:				ny	-	HIS STATE OF THE STATE OF		-				1)			
QA/QC Package: Standard Level 4 (Full Validation)			NELSON VE	LEZ	(8021B)		(ONW)		10)		PO4,SO,	PCB's			ter - 300.1)			9		
Accreditat	tion:			Sampler:	NELSON VE	LEZ AV	-8	(Gas	/ DRO /	7	304.1)		102,	8082			/ water			dwi
□ NELAF	□ NELAP □ Other		On Ice:	A Constitution of the Cons	□ No	TATE	TPH	0/0	418	204	S	03,7	es /		OA)	300.0 /			te sa	
□ EDD (Гуре)	T		Sample Temp	erature: // Ø		I.	BE+	(GR	pou	or C	8 Metals	C,N	icide	(AC)V-ic	1 1		ple	oosi
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO.	BTEX +-toff	BTEX + MTBE + TPH (Gas only)	TPH 8015B (GRO	TPH (Method 418.1)	EDB (INIELFIOR 304.1)			8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (soil		Grab sample	5 pt. composite sample
1/29/15	0730	SOIL	5PC-TB&6' (45)	4021	COOL	-001	1			1							/		1	$\sqrt{}$
																		\top		
												1								\top
										\top		1						\top	\top	\neg
			F TFH 418-1>100						1		+	\top						\top	\top	\top
			mg Kg, THER RUN															\top	\top	\top
		1	TPH 8015B																\top	\top
																		_		
										\top	-	1						\top	1	1
												1						\top	\top	
Date:	Time:	Relinquish	led by:	Received by:		Date Time	Ren	narks	5:				1							
1/29/15	1714	70	lul	Musto	Walten	129/15 17/4				Y TO		`aust	Farm	oinat	- A	ILA O	7401			
Date:	Time: 1728	Relinquish	ed by:	Received by: Date Time Ol/30/IC Work Order: N155 29608 Paykey:						7401										
- 13	If necess	any, samples	submitted to Hall Environmental may be s	subcontracted to other	accredited laboratorie		f this p	ossibili	ty. An	y sub-c	ontracte	d data	will be	clearly	y notal	ted on	the and	alytical	report	L



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

January 6, 2015

Bureau of Land Management Mark Kelly 6251 College Blvd Suite A Farmington, NM 87402

VIA CERTIFIED MAIL -- RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: RIDDLE F LS 011

API#: 3004521145

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about January 12, 2015. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

9DVa Rin

Surface Land Negotiator

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: CORY.SMITH@STATE.NM.US

January 6, 2014

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

RIDDLE F LS 011 API 30-045-21145 (E) Section 20 – T28N – R08W San Juan County, New Mexico

Dear Mr. Cory Smith:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 45 bbl BGT that will no longer be operational at this well site. We anticipate this work to start on or around January 12, 2015.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Jeff Peace

BP Field Environmental Advisor

(505) 326-9479



