District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources** Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Dit Dalam Guada Taula au
Pit, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application
Type of action: Below grade tank registration OIL CONS. DIV DIST. 3
45 20327 Permit of a pit or proposed alternative method
☐ Modification to an existing permit/or registration
Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: BP America Production Company OGRID#:778
Address:200 Energy Court, Farmington, NM 87401
Facility or well name:Federal Gas Com L 1
API Number:3004520327OCD Permit Number:4589
U/L or Qtr/QtrF Section14 Township30N Range11W County:San Juan
Center of Proposed Design: Latitude36.81502 Longitude107.96481 NAD: □1927 ⋈ 983
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
2. Pit: Subsection F, G or J of 19.15.17.11 NMAC
Temporary: Drilling Workover
Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management Low Chloride Drilling Fluid ☐ yes ☐ no
☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
\Mathrm{Below-grade tank:} Subsection I of 19.15.17.11 NMAC Tank A
Volume: 95.0 bbl Type of fluid: Produced water
Tank Construction material:Steel
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other _Double walled/double bottomed; side walls not visible
Liner type: Thicknessmil

Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

 Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, 	hognital			
institution or church)	nospital,			
Four foot height, four strands of barbed wire evenly spaced between one and four feet				
Alternate. Please specify				
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)				
☐ Screen ☐ Netting ☐ Other				
Monthly inspections (If netting or screening is not physically feasible)				
7. Signs: Subsection C of 19.15.17.11 NMAC				
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers				
☐ Signed in compliance with 19.15.16.8 NMAC				
· ·				
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.				
Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.				
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.				
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source			
General siting				
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No			
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes☐ No☐ NA			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No			
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No			
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map				
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No			
Below Grade Tanks				
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site				
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	·			
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No			
application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image				
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Temporary Pit Non-low chloride drilling fluid				
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,				
or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No			
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Permanent Pit or Multi-Well Fluid Management Pit				
1000				
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No			
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of				
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N	MAC			
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	cuments are			
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9	NMAC			
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC				
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC	15.17.9 NMAC			
Previously Approved Design (attach copy of design) API Number: or Permit Number:				
n. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC				
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc	ruments are			
 □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC 				
and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC				
☐ Previously Approved Design (attach copy of design) API Number: or Permit Number:				

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method	luid Management Pit
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes No

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No					
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No					
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 						
Within a 100-year floodplain FEMA map	☐ Yes ☐ No☐ Yes ☐ No					
16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC						
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beling the complete to the best of my knowledge and beli						
Name (Print):						
Signature: Date:						
e-mail address: Telephone:						
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 4/22/6	See C-141 2015					
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:3/26/2010_						
20. Closure Method: Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-logical of the different from approved plan, please explain.	op systems only)					
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please in mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique	dicate, by a check					

Operator Closure Certification:	
	ith this closure report is true, accurate and complete to the best of my knowledge and closure requirements and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Name (Print):Jeff Peace	Date:March 17, 2015
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Federal Gas Com L 1 API No. 3004520327 Unit Letter F, Section 14, T30N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - No notice was made due to misunderstanding of the BGT notice requirements at that time.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)

- d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
- e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	95 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	550
Chlorides	US EPA Method 300.0 or 4500B	250 or background	50

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. TPH was 550 ppm by Method 418.1 but was non-detect (ND) by Method 8015B. Sampling data is attached.

- 7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**
- 8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active well area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area as part of final reclamation when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Revised August 8, 2011

Form C-141

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action

						OPERA	ΓOR	4	hitia	ıl Report	\boxtimes	Final Rep	ort
Name of Company: BP			(Contact: Jeff Peace									
Address: 200 Energy Court, Farmington, NM 87401				Telephone 1	No.: 505-326-94	79							
Facility Name: Federal Gas Com L 1]	Facility Typ	e: Natural gas v	vell							
Surface Owner: Federal Mineral Owner			wner: I	Federal			API No	. 30045203	27				
				LOCA	TION	OF REI	LEASE						
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	East/\	Vest Line	County: Sa	n Juan		
F	14	30N	11W	1,550	North		1,500	West					ļ
		Lati	tude3	6.81502		Longitud	e107.96481						
		•		· NAT	URE	OF REL	EASE						
Type of Rele	ase: none	··	····				Release: N/A		Volume R	ecovered: N	I/A		
		v grade tank –	95 bbl			Date and I-	lour of Occurrenc	e:	Date and	Hour of Dis	covery:	N/A	-
Was Immedia	ate Notice (v	L. 57.11.10		If YES, To	Whom?						
			Yes	No 🛛 Not Re	quirea								
By Whom?		1 10				Date and I-							
Was a Water	course Reac		Yes 🗵	No		If YES, Vo	olume Impacting t	he Wate	ercourse.				
If a Watercou	ırse was Im	pacted, Descri	be Fully.*			<u> </u>							\dashv
the BGT. So Analysis resu	il analysis r ilts are attac	resulted in TPI ched.	H, BTEX :	n Taken.* Samplin and chlorides belo buter Spansen.* BGT was ref	w stand	ards. TPH w	as 550 ppm by M	ethod 4	18.1 but wa	s non-detec	by Me	thod 8015E	3.
Describe Are backfilled and	a Affected a	and Cleanuß A d and is still w	tion Tak ithin the a	en.* BGT was rel active well area.	noved a	nd the area u	nderneath the BG	T was s	ampled. Ti	ne area unde	r the B	GT was	
I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations.													
OIL CONSERVATION DIVISION				-									
Signature:	OHI I	Pases											
Printed Name	: Jeff Peace	Approved by Environmental Specialist:											
		tal Coordinato	r		/	Approval Dat	te:		Expiration 1	Date:			
E-mail Addre	ess: peace.je	effrey@bp.cor	m	·.	(Conditions of	Approval:			Attached			
Date: March	17, 2015		Phone:	505-326-9479									

^{*} Attach Additional Sheets If Necessary

CLIENT: BP	BLAGG ENGIN P.O. BOX 87, BLOOF (505) 632	MFIELD, NM 87413		API#: 300	04520327
FIELD REPORT:	BGT CONFIRMATION TEMP. PIT CLO	OSURE / RELEASE INVESTIGATION		PAGE No:	of 1
SITE INFORMATION QUAD/UNIT: F SEC: 14 TW	I: SITE NAME: FEDERAL P: 30N RNG: 11W PM: NM			DATE STARTED:	03/23/10
	,500'W SE/NW LEASE TYPE: PROD. FORMATION: DK	FEDERAL STATE / FEE / II ELKHORN CONTRACTOR: BP - M. TRUE		ENVIRONMENTAL SPECIALIST:	NJV
REFERENCE POINT 1) 95 BGT #1 (DW/DB) 2)	WELL HEAD (W.H.) GPS COGPS COORD.: GPS COORD.: GPS COORD.: GPS COORD.:	OORD.: 36.81488 X	DISTANCE/BE DISTANCE/BE DISTANCE/BE DISTANCE/BE	ARING FROM WH.: CARING FROM WH.:	√: <u>5,897'</u> 135', N59W
LAB INFORMATION: 1) SAMPLE ID: 2) SAMPLE ID: 3) SAMPLE ID: 4) SAMPLE ID:	CHAIN OF CUSTODY RECC 5' SAMPLE DATE: 03/23/10 SAMPLE DATE: SAMPLE DATE:	SAMPLE TIME: 1135 LAB ANALY SAMPLE TIME: LAB ANALY SAMPLE TIME: LAB ANALY SAMPLE TIME: LAB ANALY	/sis: 418.1 /sis: /sis:	//8015/8021/4500	B (CI) NA
SOIL DESCRIPTION SOIL COLOR: PALE YELI COHESION (ALL OTHERS): NON COHESIVE SCILS): I PLASTICITY (CLAYS): NON PLASTIC (SLIGHTLY PLASTIC DENSITY (COHESIVE CLAYS & SILTS): SOF MOISTURE: DRY (SLIGHTLY MOIST) MOIST (ADDITIONAL COMMENTS: BEDROC	LOWISH BROWN TLY COHESIVE / COHESIVE / HIGHLY COHESIVE LOOSE FIRM DENSE VERY DENSE COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC FT / FIRM STIFF VERY STIFF / HARD	DISCOLORATION/STAINING HC ODOR DETECTED: YES SAMPLE TYPE: GRAB COMP	OBSERVE	D: YES NO EXP	
EXCAVATION DIMENSIONS (if applicable): NA ft. X NA	ft. X NA ft.	cubic yard	ds excavated (if applicable	<u> </u>
SITE SKETCH	PROD. TANK	OVM CAVIB. READ. =ppm OVM CALIB. GAS =ppm . JAME:am/pmJATE:	<u>RF = 9.52</u>		T PLAN Attached NOTES
BERM>		•	N		
(BGT1) PBGTL T.B. ~ 5' B.G.	< SEPARATOR		-		
		⊕ WELL HEAD X - S	PD -		
	AVATION DEPRESSION; B.G. = BELOW GRADE; I S BELOW-GRADE TANK LOCATION; SPD = SAMI 03/22/10 - Afternoon	B = BELOW; T.H. = TEST HOLE; ~ = APPRO	X.; NG WALL	MAGNETIC DECLIF	NATION @ 10°E



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Glient:	Blagg/BP	Project #:	94034-0010
Sample ID:	BGT 1 (DW)	Datë Reported:	03-26-10
Laboratory Number:	53467	Date Sampled:	03-23-10
Chain of Custody No:	5964	Date Received:	03-25-10
Sample Matrix:	Soil	Dale Extracted:	03-26-10
Préservative:	Çool	Date Analyzed:	03-26-10
Condition:	Intact	Analysis Needed:	TPH-418-1

	<u> </u>	Det.
	Concentration	Limiţ
Parameter	(mg/kg)	(mg/kg),

Total Petroleum Hydrocarbons

550

21.5

.ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

Federal GC L#1, 5PT. Composite Sample

:Analvšt

7.



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

√Ĉlient:	Blagg/BP	Project_#:	94034-0010
Sample ID:	BGT 1 (DW)	Date Reported:	03-26-10
Laboratory Number:	53467	Date Sampled:	03-23-10
Chain of Custody No.	5964	Date Received:	03-25-10
Sample Matrix:	Soil	Date Extracted:	03-25-10
Preservative:	Cool	Date Analyzed:	03-26-10
Condition:	Intact	Analysis Requested:	8015 TPH

Parameter Gasoline Range (C5 - C10) Diesel Range (C10 - C28)	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ŅĎ.	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND:	0,2

ND- Parameter not detected at the stated detection limit.

References:

Method 8015B; Nonhálogenátéd Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Federal GC L#1, 5PT. Composite Sample

Ph (505) 632-0615 Fr (800) 362-1879 Fx (505) 632-1865 | ab@envirotech-inc.com



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Blagg/BP	Project#:	94034-0010
BGT 1 (DW)	Date Reported:	03126-10
53467	Date Sampled:	03-23-10
5964	Date Received:	03-25-10
Soil	Date Analyzed:	03 <u>÷</u> 26-10
Cool	Date Extracted:	03-25-10
Intact	Analysis Requested:	BTEX
	BGT 1 (DW) 53467 5964 Soil Cool	BGT 1 (DW) Date Reported: 53467 Date Sampled: 5964 Date Received: Soil Date Analyzed: Cool Date Extracted:

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)					
<u> </u>							
Benzene	ND	0.9					
Toluene	ЙĎ	1.0					
Ethylbenzene	ND	1 ₌ 0.					
p _i m-Xylene	ND	1.2					
o-Xylene	ND	0.9.					
Total BTEX	ND						

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	91.0 %
	1,4-difluorobenzene	99.0 %.
	Bromochlorobenzene	94.0 %

References:

Method 5030B, Purge-and Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile, Organics, Test Methods for Evaluating Solid Waste, SW:846,

USEPA, December 1996.

Comments:

Federal GC/L#1, 5PT. Composite Sample

Analyst

Miotine of Western



Chloride

Client:	Blagg/BP	Project #:	94034-0010
Sample ID:	BGT 1 (DW)	Date Reported:	03-26-10
Lab ID#:	53467	Date Sampled:	03-23-10
Sample Matrix:	Soil	Date Received:	03-25-10
Preservative:	Cool	Date Analyzed:	03-26-10
Condition:	Untact	Chain₁of Custody:	5964
Condition:	IIntact	Chain of Custody:	5964

Parameter

Concentration (mg/Kg)

Total Chloride

50

Reference:

U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes"; 1983. Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments:

Federal GC L#1, 5PT. Composite Sample

Analyst

Mintime of Weaters)--



EPA METHOD 418.1 TOTAL PETROLEUM **HYROCARBONS** QUALITY ASSURANCE REPORT

CI.	ė	nt	٠

QA/QC

Project #:

ÑΑ

Sample ID:

QA/QC

Date Reported:

03-26-10

Laboratory Number:

03-26TPH.QA/QC 53466

Date Sampled:

N/A

TPH

Sample Matrix:

Freon-113

Date Analyzed:

03-26-10

Preservative: Condition:

N/A N/A Date Extracted: Analysis Needed: 03-26-10

Calibration 1-Calibate Calibrate 1-Calibration C-Calibration Accept Range

03-04-10

03-26-10

1,680

1,630

3.0%

+/- 10%

Blank Conc. (mg/Kg)

TPH

ND.

Concentration Detection Limit 21.5

Duplicate Conc. (mg/Kg)

TPH

Sample: Duplicate %Difference Accept Range 102

106

3.9%

+/- 30%

Sample Spike Added Spike Result % Recovery Accept Range Spike Conc. (mg/Kg)

TPH

102

2.000

1,740

82.8%

80 - 120%

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

QA/QC for Samples 53466 - 53467;

5796(US Highway) 64, Farmington, NM-87401 Ph (505) 632-0615 Fr (800) 362-1879 Fx (505) 632-1865 lab@envirotech-inc.com envirotech-inc.com



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Sample ID	· · ·		<u> </u>				
Sample S	Client:	•					
Sample Martin: Sall Date Received: N/A Preservative: N/A Date Analyzed: 03.26-10 STEX							
Presentative: NA Date Analyzed: 03-26-10 Condition NA Condit							
Sample			* *				
CaDK			·ΙΔΑ ΝΙΑ				BTEX
Depte 1,0171E+006 1,0191E+008 0,2% ND				and the second s			The property of the same of th
Toluene 8.3825E-005 9.4013E-005 0.2% ND 0.1 Ethylbenzene 8.485(E-005 8)61512E+005 0.2% ND 0.1 D. Apylene 2.0886E-006 2.0905E-005 0.2% ND 0.1 D. Apylene 7.9846E+005 7.9906E+005 0.2% ND 0.1 D. Aylene ND ND 0.0% 0.30% 0.9 D. Aylene ND ND 0.0% 0.30% 1.0 D. Aylene ND ND 0.0% 0.30% 0.9 D. Aylene ND 50.0 41.8 83.6% 39150 D. Aylene ND 50.0 47.6 95.2% 46148 D. Aylene ND 50.0 47.6 95.2% 46148 D. Aylene ND 50.0 47.8 95.8% 32180 D. Aylene ND 50.0 47.8 95.8% 32180 D. Aylene ND 100 95.8 95.8% 46148 D. Aylene ND 100 95.8 95.8% 46148 D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit. D. Parameter not detected at the stated detection limit.	A STATE OF THE PARTY OF THE PAR	s (üg/L)	LCal RF	· · · · · · · · · · · · · · · · · · ·	The state of the s	一种的现在分类的	
Teluene 9.3825E-005 9.4018E-005 0.2% ND 0.1 Ethylbenzene 8.485TE-005 8.5122E-005 0.2% ND 0.1 Ethylbenzene 2.0884E-006 2.9905E-005 0.2% ND 0.1 Ethylbenzene 7.9846E+005 7.9906E-005 0.2% ND 0.1 Ethylbenzene 7.9846E+005 7.9906E-005 0.2% ND 0.1 Ethylbenzene ND ND 0.0% 0.30% 0.9 Ethylbenzene ND ND 0.0% 0.30% 1.0 Ethylbenzene ND ND 0.0% 0.30% 1.2 Ethylbenzene ND ND 0.0% 0.30% 0.9 Ethylbenzene ND 0.00 47.6 95.2% 46-148 Ethylbenzene ND 50.0 47.6 95.2% 46-148 Ethylbenzene ND 50.0 47.8 95.8% 32-160 Ethylbenzene ND 50.0 47.8 95.8% 32-160 Ethylbenzene ND 50.0 47.8 95.8% 46-148 Ethylbenzene ND 50.0 47.8 95.8% 46-148 Ethylbenzene ND 50.0 47.8 95.8% 46-148 Ethylbenzene ND 50.0 47.8 95.8% 46-148 Ethylbenzene ND 50.0 47.8 95.8% 46-148 Ethylbenzene ND 50.0 47.8 95.8% 46-148 Ethylbenzene ND 50.0 47.8 95.8% 46-148 Ethylbenzene ND 50.0 47.8 95.8% 46-148 Ethylbenzene ND 50.0 47.8 95.8% 46-148 Ethylbenzene ND 50.0 47.8 95.8% 46-148 Ethylbenzene ND 50.0 47.8 95.8%	Benzene		1,017,1E+006	1,0191E+006	0:2%	ŅĎ	.0.1
2,093E-1006 2,093E-1009 0,2% ND 10,1	Toluene				0.2%	ND	0:1
2,093E-1006 2,093E-1009 0,2% ND 10,1	Ethylbenzene		8:4951E+005	8:5122E+005	0.2%	ND	• 1
Page			• •		0.2%	ΝĎ	(0.1
ND	o-Xylene		7:9646E+005	7,9806E+005.	.0.2%	ŅĎ	<u>:0:</u> 1
ND ND ND ND ND ND ND ND	Duplicate Conc.	ug(Kg)	Sample: 1	E Duplicate F	on configuration of the config	Accept Range	Detect Limit
ND ND ND ND ND ND ND ND	Benzene		מאי.	NΘ	:Ò.Ő%	0 - 30%	0.9
Etrylbenzene				-			
ND ND 0.0% 0 - 30% 1.2				* ** *			
Spike (Sonc. (ug/Kg) Sample Amount Spike) Spiked Semple Recovery Accept Range Benzene							
Sample Amount Spikes Sample W. Becovery Accept Range							
Toluenia ND 50.0 47.6 95.2% 46-148 Ethylbenzene ND 50.0 47.9 95.8% 32-160 m-Xylerie ND 100 95.8 95.8% 46-148 Xylerie ND 50.0 47.8 95.6% 46-148 Xylerie ND Parameter not detected at the stated detection limit. **Elerences** Method, 5030B, Purgo-ond-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996. Method, 8021B, Aromatic, and Halogenaled Volatiles by Gas Chromatography Using Photolohization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996. **Comments:** QA/QC for Samples 53454 + 53457 and 53466 - 53469	Spike Conc. (ug/	(8)	Sample	Amount,Spiked	Spiked Sample:	% Recovery	Accept Range
Toluenia ND 50.0 47.6 95.2% 46-148 Ethylbenzene ND 50.0 47.9 95.8% 32-160 m-Xylerie ND 100 95.8 95.8% 46-148 Xylerie ND 50.0 47.8 95.6% 46-148 Xylerie ND Parameter not detected at the stated detection limit. **Elerences** Method, 5030B, Purgo-ond-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996. Method, 8021B, Aromatic, and Halogenaled Volatiles by Gas Chromatography Using Photolohization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996. **Comments:** QA/QC for Samples 53454 + 53457 and 53466 - 53469	Beńzene	•	ND	.50.0	41.8	83.6%	39 - 150
ND 50.0 47.9 95.8% 32160 m. Xylene ND 100 95.8 95.8% 46-148 Xylene ND 50.0 47.8 95.6% 46-148 Xylene ND 50.0 47.8 95.6% 46-148 Xylene ND Parameter not detected at the stated detection limit. Peterences. Method, 5030B. Purgo-ond-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA December 1996. Method 5021B. Aromatic and Halogenated Volatiles by Gas Chromatography Using Photolopization and/or Electrolytic Conductivity Detectors. SW-846, USEPA December 1996. Comments: QA/QC for Samples 53454 ÷ 53457 and 53466 ÷ 53469			*			• • •	
ND 100 95.8 95.8% 46 - 148 Xylene ND 50.0 47.8 95.6% 46 - 148 D - Parameter not detected at the stated detection limit. References. Method 5030B, Purgo-ond Trop, Test Methods for Evaluating Solid Waste, SW.846, USEPA. December 1996. Method 8021B, Aromatic and Halogenaged Volatiles by Gas Chromatography Using Photolopization and/or Electrolytic Conductivity Detectors. SW-846, USEPA December 1996. Comments: QA/QC for Samples 53454 - 53457 and 53466 - 53469	(s · s ·						•
ND 50.0 47.8 95.6% 46 - 148 ND Parameter not detected at the stated detection limit. Neterences. Method 5030B, Purge and Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996. Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photolohization and/or Electrolytic Conductivity Delectors. SW-846, USEPA December 1996. Comments: QA/QC for Samples 53454 - 53457 and 53466 - 53469	1						
Parameter not detected at the stated detection limit. Alterences. Method 5030B, Purge and Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996. Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photolopitzation and/or Electrolytic Conductivity Detectors. SW-846, USEPA December 1996. Comments: QA/QC for Samples 53454 - 53457 and 53466 - 53469						* * * * * * * * * * * * * * * * * * * *	
Method, 5030B. Rurge-end. Trap, Test Methods for Evaluating Solld Waste, SW. 846, USEPA, December 1996. Method, 8021B., Aromatic, and Halogenated Volatiles by Gas Chromatography Using Photolopization and/or Electrolytic Conductivity Delectors. SW-846, USEPA December 1996 OMMENTS: QA/QC for Samples 53454 - 53457 and 53466 - 53469	2-Vileus		сīм	بزِپوه،	·470	.93;6%	<u>140</u> - 140
December 1996: Method 80218. Aromatic and Halogenated Volatiles by Gas Chromatography Using Photolopitzation and Halogenated Volatiles by Gas Chromatography Using Photolopitzation and/or Electrolytic Conductivity Defectors. SW-846, USEPA December 1996 Comments: QA/QC for Samples 53454 ÷ 53457 and 53466 ÷ 53469 Amature of User Samples 53454.	ND = Parameter not/s	detected at the stated	detection limit.				
Photolopizátion and/or Electrolylic Conductivity Delectors. SW-846, USEPA December 1996 Comments: QA/QC for Samples 53454 + 53457 and 53466 - 53469 And Ive or Welling Conductivity Delectors. SW-846, USEPA December 1996 Comments: QA/QC for Samples 53454 + 53457 and 53466 - 53469	Řeferences,		ng-ơng Trạp, Test Meth	nođặ fór Eváligating S	Solid Waste, SW-846	, USEPA,	
Ametine midaeleis	!	Method 8021B. Aron Photolopization and	natic and Halogenated or Electrolylic Conduct	Volatilės by Gas Ch ivily Delectors, SW	romatography Uşing 846, USEPA Decemt	per 199 <u>6</u>	
	Comments:	QA/QC for S	amples 53454	53457 and 5	3466 - 53469		
	1 /	1	- May 1		Mistine	mile	eleis
en e	Añalysi			()	Ŗeview.	· /*-	



EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Quality Assurance Report

				•	
Client:	QA/QC		Project#:	N/A	
Sample ID:	03-26-10 QA/0	ðÇ	Date Reported:	03-26-10	
Laboratory Number:	53454		Date Sampled:		N/A·
Sample Matrix:	Methylene Chlor	ide	Date Réceived:		,N/A
Preservative:	N/A		Date Analyzed:		03-26-10
Condition:	N/A		Analysis Reques	TPH	
	i Calidaté	Pegire:	e carren	% Difference	Accept Range
Gasoline Range C5 - C10	.05-07₌07	9.4355E+002	9.4393É+002	0.04%	0 - 15%
Diesel Range C10 : C28	05-07-07	8:3973E+002	8:4 <u>007E</u> +0 <u>0</u> 2	0.04%	0 = 15%
Blank Conc. (me/les/mg/kg)		Concentration		Délédion Limit	15
Gasoline Range 'C5 - C10		NĎ	·	0.2	
Diesel Range C10 - C28		ŅĎ		0:1	
Total Petroleum Hydrocarbons		ND		0:2	
Duplicate Conc (ing/Kg)	Sample	Duplicate!!	?/o.Difference	Accept Range	
Gasoline Range C5 - C10	ND	ŅD	0.0%	0 - 30%	
Diesel Range C10 - C28	:ND	ND	0.0%	0 - 30%	
Spike Conc (mg/kg) 2.	Sample"	Spike Added	Spike Result	% Recovery	Accept Range
Gasoline Range C5 - C10	ND	250	252	101%	75 - 125%
Diesel Range C10 - C28	(ND	250	265	106%	75 - 125%

ND:- Parameter not detected at the stated detection limit.

References

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

ŚW-846, USEPA, December 1996.

Comments:

QA/QC for Samples 53454 - 53457 and 53466 - 53470

Analyst

CHAIN OF CUSTODY RECORD

5964

			, U 0 0	A-BREA	1 6		9	U 🐸	المحطا		11 11	- ~	9	n mr									
Client: BASG / B	E:		Project Name /				,							ANAL	YSIS	/PAR	AME	TERS					
2010016	<i>'</i>		FEDERAL GC L #1																				
Client Address:			Sampler Name:	1/					(2)	BTEX (Method 8021)	(Og										ig)		
			Sampler Name: NELSON VELEZ				8	8	8	<u>0</u>	نہ ا	ľ	0	1					'n				
Client Phone No.:			Client No.:		~				TPH (Method 8015)	ğ.	VOC:(Method:8260)	RCRA 8.Métals	Cation / Anion.		TCLP with H/P	1	E	ழ்			5. pr. Lamper S. 1.7.	0	Sample Intact
	***		يخ (14039	1-0010 ample				Met	S.	Met	86	Ϋ́		with		418	문			Trynghie	e C	ie ir
Sample No./	Sample	Samp	l lan No			No./Volum	e Pre	servativ	의 포	Ä	ပြွ	8	ig.	20	片	PAH	TPH (418.1)	CHLORIDE	-{		\$ 8	Sample Cool	amp
Identification	Date	Time	9		Vatrix	of Container	s HoCl	, HCI	<u> </u>	<u>6</u>	≽_	Ĕ	ပြီ	Ĭĸ.	F	12	E	ō	ļ		LA	ιχ	ဟိ
-3-5	3/23/10	<u>پيور</u> (93466	Solid	Sludge Aqueous	1-40-2	1	\bot	1/	/	ļ	ļ	_	ļ	<u> </u>		1	1/2			/	- T X	-,1
	77-1.	-	7766	Soil	Sludge		┤.	-	+	\ <u> </u>	 	-	 	-	-	 -	-	-			· -	-4)	U.
				Solid	Aqueous																	ر 	
BETI (pw)	7/23/15	113	53467	Soil- Solid	'Sludge Aqueous	1- 40z			V	1							1	1			1	u	u
				Soll Solid	Sludge Aqueous																	J	1
				Soil Solid	Sludge Aqueous						_		-										
				Soil Solid	Sludge Aqueous																		
	-			Solid	Studge Aqueous																-		
				Soil Solid	Sludge Aqueous											l							
				Soil Solid	Sludge Aqueous																		
				Sòil Solid	Sludge Âqueous																		
Relinguished by: (Sign	nature) VX				Date 3/25/10	Time	1	Recei	red by:	(Sigr	nature 	(آ خز.	V,	1	2				-	1 /	ate	1	ime 2/
Relinquished by: (Sign		·			1,7,0		7	Recei	ed by:	(Sigr	nature	1	Jun 1	7.~	c					11.00	/(1.0	<u>. i</u>
Relinquished by: (Sign	nature)						-	Recei	ed by:	(Sigr	náture)				 ,						-	- 1 -
	:		·		ENV	IRO	TE	<u>C</u>		n	C.		<u>.</u>										,
			5796 U	.S. Hig	nway 64	• Farmir	gtor	n, NN	1 874	01 •	Tel	505	-632	-061	5								

ACCENT Printing • Form 28-0807



