District I 1625 N. French Dr., Hobbs, NM 88240 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

Tank Construction material: Steel

Form C-144

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Form C-144

Revised June 6, 2013

1220 South St. Francis Dr. Santa Fe, NM 87505

Pit, Below-Grade Tank, or 12863 Proposed Alternative Method Permit or Closure Plan Application OIL CONS. DIV DIST. 3 Type of action: Below grade tank registration Permit of a pit or proposed alternative method 45-22821 Closure of a pit, below-grade tank, or proposed alternative method APR 1 4 2015 Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances, Operator: BP America Production Company______ OGRID #:__778____ Address: __200 Energy Court, Farmington, NM 87401_____ Facility or well name: ___Barnes LS 16 _____ API Number: ____3004522821_______OCD Permit Number: ____ U/L or Qtr/Qtr ____M____ Section ____23 ___ Township ___32N ___ Range __11W ____ County: ___ San Juan _____ Center of Proposed Design: Latitude ____36.965926 _____ Longitude __-107.965138 _____ NAD: ☐1927 ☒ 1983 Surface Owner: ☑ Federal ☑ State ☑ Private ☑ Tribal Trust or Indian Allotment Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid \(\square\) yes \(\square\) no Lined Unlined Liner type: Thickness _____ mil LLDPE HDPE PVC Other _____ ☐ String-Reinforced Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D Below-grade tank: Subsection 1 of 19.15.17.11 NMAC 21.0 bbl Type of fluid: Produced water

☐ Visible sidewalls and liner ☐ Visible sidewalls only ☒ Other Single walled/double bottomed; side walls not visible Liner type: Thickness _____ mil HDPE PVC Other Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off

Page 1 of 6

5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school,	hospital,
institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet	·
Alternate. Please specify	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Variance(s): Requests must be submitted to the appropriate division district for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptance are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	ptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes No					
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 						
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Temporary Pit Non-low chloride drilling fluid						
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	∏ Yes∏ No					
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.						
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No					
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Permanent Pit or Multi-Well Fluid Management Pit						
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image						
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of						
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No					
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9	cuments are					
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC						
Previously Approved Design (attach copy of design) API Number: or Permit Number:						
11. Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.	cuments are					
 □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ A List of wells with approved application for permit to drill associated with the pit. □ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC □ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC 	15.17.9 NMAC					
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:						
Treviously Approved Design (attach copy of design) Art Number: of Pennit Number:						

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are
attached. ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan ☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC ☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial	luid Management Pit
Alternative Closure Method	\
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
15.	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland.	
US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

Page 4 of 6

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	
Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure pl by a check mark in the box, that the documents are attached.	an. Please indicate,
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	15.17.11 NMAC
17. Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 4/23/ Title: OCD Permit Number:	2015
Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:2/20/2012	
20. Closure Method: Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-lo☐ If different from approved plan, please explain.	op systems only)
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please in mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division)	dicate, by a check
Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude36.965926Longitude107.965138NAD: □19	02 7 ⊠ 1983

Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure rebelief. I also certify that the closure complies with all applicable closure requirements.	
ocher. Talso certify that the closure compiles with an apprecable closure requireme	ones and conditions specified in the approved closure plan.
Name (Print):Jeff Peace	Title: Field Environmental Coordinator
Signature: Jeff Peace	Date:April 14, 2015
e-mail address:peace.jeffrey@bp.com	Telephone:(505) 326-9479

Form C-144

BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

BELOW-GRADE TANK CLOSURE PLAN

Barnes LS 16 API No. 3004522821 Unit Letter M, Section 23, T32N, R11W

This plan will address the standard protocols and procedures for closure of below-grade tanks (BGTs) on BP America Production Company (BP) well sites. As stipulated in Paragraph A of 19.15.17.13 NMAC, BP shall close a BGT within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the New Mexico Oil Conservation Division (NMOCD) requires because of imminent danger to fresh water, public health, safety or the environment. If deviations from this plan are necessary, any specific changes will be included on form C-144 and approved by the NMOCD. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofit with a BGT that complies with the BP NMOCD approved BGT design attached to the BP Design and Construction Plan. BP shall close an existing BGT that does not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, if not previously retrofitted to comply with the BP NMOCD approve BGT Design attached to the BP Design and Construction Plan, prior to any sale or change in operator pursuant to 19.15.9.9 NMAC. BP shall close the permitted BGT within 60 days of cessation of the BGTs operation or as required by the transitional provisions of Subsection B, D, or E of 19.15.17.17 NMAC.

General Closure Plan

- 1. BP shall notify the surface owner by certified mail that it plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.
 - Notice is attached.
- 2. BP shall notify the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice shall include the operator's name, and the location to be closed by unit letter, section, township and range. If the BGT closure is associated with a particular well, then the notice shall also include the well's name, number and API number.
 - Notice is attached.
- 3. BP shall remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. The facilities to be used are:
 - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
 - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
 - c. Basin Disposal, Permit NM-01-0005 (Liquids)
 - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
 - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)

- f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
- g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
- h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
- i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
- j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
- k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

All liquids and sludge in the BGT were removed and sent to one of the above NMOCD approved facilities for disposal.

4. BP shall remove the BGT and dispose of it in a NMOCD approved facility or recycle, reuse, or reclaim it in a manner that the NMOCD approves. If a liner is present and must be disposed of it will be cleaned by scraping any soils or other attached materials on the liner to a de minimus amount and disposed at a permitted solid waste facility, pursuant to Subparagraph (m) of Paragraph (1) of Subsection C of 19.15.35.8 NMAC. Documentation as to the final disposition of the removed BGT will be provided in the final closure report.

The BGT was transported to a storage area for sale and re-use.

5. BP shall remove any on-site equipment associated with a BGT unless the equipment is required for well production.

All equipment associated with the BGT has been removed.

6. BP shall test the soils beneath the BGT to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample and individual grab samples from any area that is wet, discolored or showing other evidence of a release and analyze for BTEX, TPH and chlorides. The testing methods for those constituents are as follows;

Constituents	Testing Method	Release Verification	Sample
	21 bbl BGT	(mg/Kg)	results
Benzene	US EPA Method SW-846 8021B or 8260B	0.2	ND
Total BTEX	US EPA Method SW-846 8021B or 8260B	50	ND
TPH	US EPA Method SW-846 418.1	100	ND
Chlorides	US EPA Method 300.0 or 4500B	250 or background	ND

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. Chloride closure standards will be determined by which ever concentration level is greatest.

Soil under the BGT was sampled and TPH, BTEX and chloride levels were below the stated limits. Sampling data is attached.

7. BP shall notify the division District III office of its results on form C-141. **C-141 is attached.**

8. If it is determined that a release has occurred, then BP will comply with 19.15.30 NMAC and 19.15.29 NMAC, as appropriate.

Sampling results indicate no release occurred.

9. If the sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then BP shall backfill the excavation, with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover, re-contour and re-vegetate the location. The location will be reclaimed if it is not with in the active process area

The area under the BGT was backfilled with clean soil and is still within the active area.

10. BP shall reclaim the BGT location and all areas associated with the BGT including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC, re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Subsection I of 19.15.17.13 NMAC.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

11. The soil cover for closures where the BGT has been removed or remediated to the NMOCD's satisfaction shall consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

12. BP shall seed the disturbed area the first growing season after closure of the BGT. Seeding will be accomplished by drilling on the contour whenever practical or by other division-approved methods. Vegetative cover will be, at a minimum, 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire or other intrusion damaging to native vegetation), consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintenance of that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

The area over the BGT is still within the active well area. This area will be reclaimed when the well is plugged and abandoned as part of final reclamation.

13. BP shall seed, plant and re-seed pursuant to Paragraph (3) of Subsection I of 19.15.17.13 NMAC, until the location successfully achieves the required vegetative cover.

BP will seed the area when the well is plugged and abandoned.

14. Pursuant to Paragraph (5) of Subsection I of 19.15.17.13 NMAC, BP shall notify the NMOCD when it has seeded or planted and when it successfully achieves revegetation.

BP will notify NMOCD when re-vegetation is successful.

- 15. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
 - a. proof of closure notification (surface owner and NMOCD)
 - b. sampling analytical reports; information required by 19.15.17 NMAC;
 - c. disposal facility name and permit number
 - d. details on back-filling, capping, covering, and where applicable re-vegetation application rates and seeding techniques and
 - e. site reclamation, photo documentation.

 Closure report on C-144 form is included.
- 16. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

Certification section of C-144 has been completed.

<u>District 1</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 District III

1000 Rio Brazos Road, Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Release Notification and Corrective Action

Form C-141

Revised August 8, 2011

	OPERATOR	☐ Initial Report ☐ Final Report						
Name of Company: BP	Contact: Jeff Peace							
Address: 200 Energy Court, Farmington, NM 87401	Telephone No.: 505-326-9479							
Facility Name: Barnes LS 16	Facility Type: Natural gas well							
Surface Owner: Federal Mineral Ov	ner: Federal API No. 3004522821							
		111110. 300 1022021						
	ΓΙΟΝ OF RELEASE							
	1 1	Cast/West Line County: San Juan Vest						
Latitude 36.965926	Longitude107.965138	<u>.</u>						
NATU	JRE OF RELEASE							
Type of Release: none	Volume of Release: N/A	Volume Recovered: N/A						
Source of Release: below grade tank – 21 bbl	Date and Hour of Occurrence:	Date and Hour of Discovery:						
Was Immediate Notice Given? ☐ Yes ☐ No ☒ Not Req	uired If YES, To Whom?							
By Whom?	Date and Hour							
Was a Watercourse Reached? ☐ Yes ☒ No		If YES, Volume Impacting the Watercourse.						
If a Watercourse was Impacted, Describe Fully.*								
if a watercourse was impacted, Describe runy.								
Describe Cause of Problem and Remedial Action Taken.* Sampling	of the sail beneath the DCT was done	during removal to angure no call imports from						
the BGT. Soil analysis resulted in TPH, BTEX and chloride below								
Describe Area Affected and Cleanup Action Taken.* BGT was rem	oved and the area underneath the BGT v	was sampled. The area under the BGT was						
backfilled and compacted and is still within the active well area.								
I hereby certify that the information given above is true and complete								
regulations all operators are required to report and/or file certain rele								
public health or the environment. The acceptance of a C-141 report should their operations have failed to adequately investigate and ren								
or the environment. In addition, NMOCD acceptance of a C-141 re								
federal, state, or local laws and/or regulations.	port does not remove and operator or resp	Johnson Gomphanics with any coner						
A 0	· OIL CONSE	OIL CONSERVATION DIVISION						
Signature: Off Peace								
Signature:								
Printed Name: Jeff Peace	Approved by Environmental Spec	ialist:						
Title: Field Environmental Coordinator	Approval Date:	Expiration Date:						
E-mail Address: peace.jeffrey@bp.com	Conditions of Approval:							
E-man Address, peace.jemey(w,op.com	Conditions of Approvar:	Attached						
Date: April 14, 2015 Phone: 505-326-9479								

^{*} Attach Additional Sheets If Necessary

ממ	BLAGG ENGINEERING, INC.	2004522024
CLIENT: BP	P.O. BOX 87, BLOOMFIELD, NM 87413	API#: 3004522821
	(505) 632-1199	TANK ID (if applicble):
FIELD REPORT:	(circle one): BGT CONFIRMATION / RELEASE INVESTIGATION / OTHER: 95 SW/DB TO BE REPLACED WITH 95 DW/DB	PAGE#:1 of1_
	: SITE NAME: BARNES LS #16	DATE STARTED: 02/10/12
QUAD/UNIT: M SEC: 23 TWP:	32N RNG: 11W PM: NM CNTY: SJ ST: NM	DATE FINISHED:
1/4-1/4/FOOTAGE: 1,060'S / 810' LEASE#: SF078039	W SW/SW LEASE TYPE: FEDERAL STATE / FEE / INDIAN ELKHORN PROD. FORMATION: PC CONTRACTOR: MBF - J. YEAGER	ENVIRONMENTAL SPECIALIST(S): NJV
REFERENCE POINT		GLELEV.: 6.363'
1)21 BGT (SW/DB) - A	20 00E720 V 407 00E420	EARING FROM W.H.: 78.5', \$35.5W
₂₎ 95 BGT (3W/DB) - B	GPS COORD.: 36.965909 X 107.964940 DISTANCE/BI	EARING FROM W.H.: 78, SOE
3)	GPS COORD.: DISTANCE/BI	EARING FROM W.H.:
4)	GPS COORD.: DISTANCE/BE	EARING FROM W.H.:
SAMPLING DATA:	CHAIN OF CUSTODY RECORD(S) # OR LAB USED: HALL	OVM READING (ppm)
• .	BGT) SAMPLE DATE: 02/10/12 SAMPLE TIME: 1410 LAB ANALYSIS: 418.1/3	8015B/8021/B/300.0 (CI) NA
	BGT) SAMPLE DATE: 02/21/12 SAMPLE TIME: 1520 LAB ANALYSIS:	· · · · · · · · · · · · · · · · · · ·
	SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS:	
	SAMPLE DATE: SAMPLE TIME: LAB ANALYSIS:	
SOIL DESCRIPTION		THER
SOIL COLOR: DARK YELL COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY	LOWISH BROWN COHESIVE / COHESIVE / HIGHLY COHESIVE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC /	COLICOR (MEDIUM DI ACTIC MICHINADI ACTIC
CONSISTENCY (NON COHESIVE SOILS): LO		
MOISTURE: DRY (SLIGHTLY MOIST / WI	TT/SATURATED/SUPER SATURATED HC ODOR DETECTED: YES NO EXPL	
SAMPLE TYPE: GRAB (COMPOSITE) # OF PTS. DISCOLORATION/STAINING OBSERVED:		
	TEO (NO EXILENTE CONTROL CONTR	
ANY AREAS DISPLAYING WETNESS: YES NO		
ADDITIONAL COMMENTS: NO APPARE	NT EVIDENCE OF A RELEASE OBSERVED FROM EITHER BGT.	
SOIL IMPACT DIMENSION ESTIMATION: DEPTH TO GROUNDWATER: <u>>100'</u> N		TIMATION (Cubic Yards): NA CD TPH CLOSURE STD: 1,000 ppm
SITE SKETCH	TO PLOT PLAN circle: attached OM	M CALIB. READ. = 52.5 ppm RF = 0.52
	/ HEAD	M CALIB. GAS = 100 ppm
	N I IIM	E: <u>3:30</u> am(pm) DATE: <u>02/21/12</u>
SEPARATOR	(95)	MISCELL. NOTES
DEHYDRATOR		WO - N1410228
22113101131	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	PO - 57922
	FENCE -	PK - ZSCHWLLBGT
(21) PBGTL		PJ - Z2-00690-C
T.B. $\sim 6.5'$ B.G.	Pe	ermit Date: 06/13/10 (A), 05/09/11 (B)
	BERM &	CD Appr. Date: 11/29/10 (A), 08/09/11 (B)
	PROD.	
X - S.P.D.	TANK TANK	BGT Sidewalls Visible: Y /(N)/ NA
	ATION DEPRESSION; B.G. = BELOW GRADE; B = BELOW; T.H. = TEST HOLE; ~ = APPROX.; BELOW-GRADE TANK LOCATION; SPD = SAMPLE POINT DESIGNATION; R.W. = RETAINING WALL;	
NA - NOT APPLICABLE OR NOT AVAILABLE	SW-SINGLE WALL; DW-DOUBLE WALL; SB-SINGLE BOTTOM; DB-DOUBLE BOTTOM.	Magnetic declination: 10 E
TRAVEL NOTES: CALLOUT:	ONSITE: 02/10/12, 02/21/12	

Analytical Report

Lab Order 1202466

Date Reported: 2/20/2012

Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering

Project:

Lab ID:

Barnes LS #16 1202466-001

Matrix: SOIL

Client Sample ID: 5PC-TB @ 7' (21 BGT) Collection Date: 2/10/2012 2:10:00 PM

Received Date: 2/14/2012 12:45:00 PM

Analyses	Result	RL (Qual Units	DF	Date Analyzed
EPA METHOD 8015B: DIESEL RANG	GE ORGANICS				Analyst: JMP
Diesel Range Organics (DRO)	ND	9.8	mg/Kg	1	2/16/2012 9:16:18 AM
Surr: DNOP	94.6	77.4-131	%REC	1	2/16/2012 9:16:18 AM
EPA METHOD 8015B: GASOLINE R.	ANGE				Analyst: RAA
Gasoline Range Organics (GRO)	. ND	4.8	mg/Kg	1	2/16/2012 4:41:01 PM
Surr: BFB	107	69.7-121	%REC	1	2/16/2012 4:41:01 PM
EPA METHOD 8021B: VOLATILES					Analyst: RAA
Benzene	ND	0.048	mg/Kg	1	2/16/2012 2:12:48 AM
Toluene	, ND	0.048	mg/Kg	1	2/16/2012 2:12:48 AM
Ethylbenzene	ND	0.048	mg/Kg	1	2/16/2012 2:12:48 AM
Xylenes, Total	ND	0.097	mg/Kg	1	2/16/2012 2:12:48 AM
Surr: 4-Bromofluorobenzene	103	85.3-139	%REC	1	2/16/2012 2:12:48 AM
EPA METHOD 300.0: ANIONS					Analyst: BRM
Chloride	ND	1.5	mg/Kg	1	2/16/2012 9:22:54 PM
EPA METHOD 418.1: TPH					Analyst: JMP
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	2/15/2012

Qualifiers:

- */X Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- RL Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202466 20-Feb-12

Client:

Blagg Engineering

Project:

Barnes LS #16

Sample ID MB-735

SampType: MBLK

TestCode: EPA Method 300.0; Anions

TestCode: EPA Method 300.0: Anions

LowLimit

Client ID: PBS

LCSS

Batch ID: 735

RunNo: 995

Prep Date:

2/16/2012

Analysis Date: 2/16/2012

SeqNo: 28846

Units: mg/Kg

HighLimit

RPDLimit

Qual

Analyte Chloride

Result PQL ND 1.5

Sample ID LCS-735

SampType: LCS

Batch ID: 735

RunNo: 995

Prep Date: 2/16/2012

Analysis Date: 2/16/2012

SeqNo: 28847

Units: mg/Kg HighLimit

%RPD

RPDLimit

Qual

Analyte

Result PQL

90

SPK value SPK Ref Val %REC LowLimit

%REC

SPK value SPK Ref Val

Chloride

Client ID:

14

1.5

15.00

90.9

110

%RPD

Qualifiers:

Value exceeds Maximum Contaminant Level. */X

Value above quantitation range Е

Analyte detected below quantitation limits

Analyte detected in the associated Method Blank

Holding times for preparation or analysis exceeded Н

ND Not Detected at the Reporting Limit Page 2 of 6

R

RPD outside accepted recovery limits

Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202466 20-Feb-12

Client:

Blagg Engineering

Project:

Barnes LS #16

Sample ID MB-708

Prep Date:

Analyte

SampType: MBLK

Analysis Date: 2/15/2012

PQL

20

TestCode: EPA Method 418.1: TPH

Client ID:

PBS

Batch ID: 708

RunNo: 955

SeqNo: 27726

Units: mg/Kg

HighLimit

RPDLimit %RPD

Qual

Petroleum Hydrocarbons, TR

ND

Result

SampType: LCS

TestCode: EPA Method 418.1: TPH

Sample ID LCS-708 Client ID:

LCSS

Batch ID: 708

RunNo: 955

Prep Date: 2/14/2012 Analysis Date: 2/15/2012

SeqNo: 27727

104

SeqNo: 27728

Units: mg/Kg

Analyte Petroleum Hydrocarbons, TR

Client ID:

Prep Date:

2/14/2012

PQL 20

100.0

SPK value SPK Ref Val %REC

SPK value SPK Ref Val %REC LowLimit

LowLimit

87.8

HighLimit

115

RPDLimit Qual

Qual

Sample ID LCSD-708

SampType: LCSD Batch ID: 708

TestCode: EPA Method 418.1: TPH RunNo: 955

Units: mg/Kg

%RPD

Analyte Petroleum Hydrocarbons, TR

2/14/2012

LCSS02

Analysis Date: 2/15/2012

110

Result

100

PQL

20

SPK value SPK Ref Val 100.0

%REC 0 105 LowLimit 87.8 HighLimit 115 %RPD **RPDLimit** 1.01

8.04

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

Value above quantitation range Analyte detected below quantitation limits

Analyte detected in the associated Method Blank В

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit Page 3 of 6

RPD outside accepted recovery limits R

Reporting Detection Limit

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202466

20-Feb-12

Client:

Blagg Engineering

Project:

Barnes LS #16

Sample ID MB-725	Samp	SampType: MBLK -			TestCode: EPA Method 8015B: Diesel Range Organics					
Client ID: PBS	Batc	h ID: 72	5	F	RunNo: 9	66				
Prep Date: 2/15/2012	Analysis [Date: 2 /	16/2012	5	SeqNo: 2	8071	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	ND	10								
Surr: DNOP	9.4		10.00		93.5	77.4	131			
Sample ID LCS-725	Samp	Гуре: LC	s	Tes	tCode: El	PA Method	8015B: Dies	el Range (Organics	
Client ID: LCSS	Batc	h ID: 72	5	F	RunNo: 9	66				
Prep Date: 2/15/2012	Analysis [Date: 2/	16/2012	S	SeqNo: 2	8077	Units: mg/K	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Diesel Range Organics (DRO)	40	10	50.00	0	79.6	62.7	139			
Surr: DNOP	4.7		5.000		93.5	77.4	131			

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

R RPD outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

RL Reporting Detection Limit

Page 4 of 6

Hall Environmental Analysis Laboratory, Inc.

WO#:

1202466 20-Feb-12

Client:

Blagg Engineering

Project:

Barnes LS #16

Sample ID MB-711	Samp ⁻	ype: ME	BLK	Test	TestCode: EPA Method 8015B: Gasoline Range					
Client ID: PBS	Batch ID: 711				unNo: 9	72				
Prep Date: 2/14/2012	Analysis [Date: 2/	15/2012	S	eqNo: 2	8357	Units: mg/k	(g		
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Gasoline Range Organics (GRO)	ND	5.0								
Surr: BFB	910		1,000		90.9	69.7	121			
Sample ID LCS-711	Samp ⁻	ype: LC	s	TestCode: EPA Method 8015B: Gasoline Range				e		
Client ID: LCSS	Batc	1D: 71	1	R	unNo: 9	72				

Sample ID LOG-711	Gampi	урс. с	.5	163	icode. Li	A Melilou	OUTUD. Gasc	mile Kang	e			
Client ID: LCSS	Batch ID: 711			Client ID: LCSS Batch ID: 711 RunNo: 972								
Prep Date: 2/14/2012	Analysis D	ate: 2/	15/2012	5	SeqNo: 2	8361	Units: mg/K	(g				
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual		
Gasoline Range Organics (GRO)	27	5.0	25.00	0	109	98.5	133					
Surr: BFB	860		1,000		86.0	69.7	121					

_

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

R RPD outside accepted recovery limits

B Analyte detected in the associated Method Blank

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting LimitRL Reporting Detection Limit

Page 5 of 6

Hall Environmental Analysis Laboratory, Inc.

0.10

3.0

0.88

3.000

1.000

WO#:

1202466

20-Feb-12

Client:

Blagg Engineering

Project:

Xylenes, Total

Surr: 4-Bromofluorobenzene

Barnes LS #16

Sample ID MB-711 SampType: MBLK				Tes	TestCode: EPA Method 8021B: Volatiles								
Client ID: PBS	Batc	1	F										
Prep Date: 2/14/2012	Analysis [Date: 2/	15/2012	SeqNo: 28392			Units: mg/k	ίg					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	ND	0.050											
Toluene	ND	0.050											
Ethylbenzene	ND	0.050											
Xylenes, Total	ND	0.10											
Surr: 4-Bromofluorobenzene	0.92		1.000		92.2	85.3	139						
Sample ID LCS-711 SampType: LCS				TestCode: EPA Method 8021B: Volatiles									
Client ID: LCSS	Batc	Batch ID: 711 RunNo: 972											
Prep Date: 2/14/2012	Analysis Date: 2/15/2012			SeqNo: 28393			Units: mg/k	(g					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual			
Benzene	0.96	0.050	1.000	0	96.2	83.3	107						
Foluene	0.90	0.050	1.000	0	90.0	74.3	· 115						
Ethylbenzene	0.96	0.050	1.000	0	96.1	80.9	122						

Qualifiers:

*/X Value exceeds Maximum Contaminant Level.

E Value above quantitation range

J Analyte detected below quantitation limits

R RPD outside accepted recovery limits

B Analyte detected in the associated Method Blank

85.2

85.3

99.3

123

139

H Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Page 6 of 6

Reporting Detection Limit Page 6



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

Sample Log-In Check List

Client Name: **BLAGG** Work Order Number: 1202466 02/14/12 Received by/date: Logged By: Anne Thorne 2/14/2012 12:45:00 PM an Ihan Completed By: 2/14/2012 Anne Thorne Reviewed By: Chain of Custody Yes No 🗆 . Not Present 🗹 1. Were seals intact? Yes 🗸 No 🗌 Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Courier Log In Yes V No NA 🗀 4. Coolers are present? (see 19. for cooler specific information) Yes 🗸 No 🗌 NA 🗌 5. Was an attempt made to cool the samples? Yes 🗸 No 🗌 NA 🗍 6 Were all samples received at a temperature of >0° C to 6.0°C Yes 🗹 No 🗌 7. Sample(s) in proper container(s)? Yes 🗸 No 🗌 8. Sufficient sample volume for indicated test(s)? Yes 🗸 No 🛄 9. Are samples (except VOA and ONG) properly preserved? NA 🗌 Yes No 🗹 10. Was preservative added to bottles? Yes No No VOA Vials 11 VOA vials have zero headspace? Yes No 🗹 12. Were any sample containers received broken? # of preserved Yes 🗹 No 🗌 13. Does paperwork match bottle labels? bottles checked (Note discrepancies on chain of custody) for pH: 14. Are matrices correctly identified on Chain of Custody? Yes 🗹 No 🗌 (<2 or >12 unless noted) Adjusted? Yes 🔽 No 🗌 15. Is it clear what analyses were requested? Yes 🗹 No 🗌 16 Were all holding times able to be met? (If no, notify customer for authorization.) Checked by: Special Handling (if applicable) Yes 🗌 No 🗌 . NA 🗹 17. Was client notified of all discrepancies with this order? Person Notified: Date By Whom: Via: eMail Phone Fax In Person Regarding: Client Instructions: 18. Additional remarks: 19 Cooler Information Cooler No Seal Intact | Seal No Temp ºC Condition Seal Date Signed By Good

Chain-of-Custody Record			rum-Around Time:				HALL ENVIRONMENTAL														
Client: BLAGG ENGR. / BP AMERICA			☑ Standard	-											RA						
				Project Name:											nme				A 18 40	*** II 7	. .
Mailing Address: P.O. BOX 87 BLOOMFIELD, NM 87413 Phone #: (505) 632-1199 email or Fax#:			BARNES LS # 16				40	∩1 L									37109	ב			
			Project #:)5-34					505-				,			
										10-0									i sa Majak		
			Project Manager:				Analysis Request														
QA/QC Package: Standard Level 4 (Full Validation)			NELSON VELEZ				(Aluo	(Diesel)					PO4, SO4)	.B's							
Accreditation:			Sampler: NELSON VELEZ				Gas	Gas/					02, 1	32 PCB						sample	
□ NELAP □ Other			Ønice: □XYes □ No				F	15B (418.1)	504.1)	РАН))3, N	/ 8082						e sa	
□ EDD (Type)			Sample Temperature: 3.9				+ #	08 p	d 41)d 50	r P	als	I, NC	ides		Ϋ́	0.0		<u>ē</u>	osit	
Date	Time	Matrix	Sample Request ID	Container Type and #	Preservative Type	HEAL NO.	BTEX +- MATE	BTEX + MTBE + TPH (Gas only)	TPH Method 8015B (Gas/Diesel)	TPH (Method	EDB (Method	8310 (PNA or	RCRA 8 Metals	Anions (F, Cl, NO3, NO2,	8081 Pesticides	8260B (VOA)	8270 (Semi-VOA)	Chloride (300.0)		Grab sample	5 pt. composite
2/10/12	1410	SOIL	5PC-TB @ 7' (21 BGT)	4 oz 2	Cool	_ [٧		V	٧					30			٧			V
											-									7	
																П					—
			,				·													7	十
*						***************************************														7	十
		<u> </u>				7 141 144 144 144 144 144 144 144 144 14													_	\dashv	\top
***************************************					· · · · · · · · · · · · · · · · · · ·		 												\dashv		-
		 					 												_	\dashv	+
·	ļ <u>-</u>						1		<u> </u>									\vdash	十	\dashv	+
	\			<u> </u>				<u> </u>								\vdash		\vdash	+	-	+
		<u> </u>					-	 										\vdash	+	┪	-
		 					 	-										\vdash	-	\dashv	\dashv
Date:	Time:	Relinquish	ed by:	Received by:		Date Time	Rer	l nark	s:	TPH	1 (8)	015	3) -	GRO) & (DRC	10 (JLY.			
1/5/12	1135	70	My Uf	Mother whoten 2/3/2 1/35																	
Date:			Received by:	<i>^</i>	Date Time	· · · · · · · · · · · · · · · · · · ·															
2/13/12 14/12 Christia la hoten =		MI. h. 181	ተ ‴	אונעל	ושטור	Work Order: N1410228 Paykey: ZSCHWLLBGT															



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

January 30, 2012

Bureau of Land Management Mark Kelly 1235 La Plata Hwy Farmington, NM 87401

VIA CERTIFIED MAIL - RETURN RECEIPT REUESTED

Re: Notification of plans to close/remove a below grade tank Well Name: BARNES LS 016

Dear Mark Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove a below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about January 30, 2012. If there aren't any unforeseen problems, the work should be completed within 10 working days.

As a point of clarification, BP will be closing the below grade tank and either operating without one or replacing it with an above ground tank, the well site will continue to operate.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

JD Vel (Re

Surface Coordinator/Business Security Representative

BP America Production Company

BP America Production Company

200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

SENT VIA E-MAIL TO: BRANDON.POWELL@STATE.NM.US

January 30, 2011

New Mexico Oil Conservation Division 1000 Rio Brazos Road Aztec, New Mexico 87410

RE: Notice of Proposed Below-Grade Tank (BGT) Closure

BARNES LS 016 API 30-045-22821 (M) Section 23 – T32N – R11W San Juan County, New Mexico

Dear Mr. Brandon Powell:

In regards to the captioned subject and requirements of the NMOCD pit rule, this letter is notification that BP is planning to close a 21 bbl. BGT that will no longer be operational at this well site.

Should you have any questions, please feel free to contact BP at our Farmington office.

Sincerely,

Buddy Shaw BP Environmental Advisor

(505) 320-0401



