This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico.

NEW MEXICO OIL CONSERVATION DIVISION

Page 1 Revised June 10, 2003

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

i Southeast New	Mexico	OKIHWESIN	CEW MEXICO P	ACKER L	LAKAGE IE	101	,
Operator Chadron mideations				ne Rinco	14	Well No. <u>88</u>	
ocation Of W	ell: Unit Letter	Sec/	3 Twp 27	<u> </u> Rge	7 API#	30-0 <u>3</u> 9	7-07665
	Name of Rese	rvoir or Pool	Type of Prod. (Oil or Gas)		Method of Prod. (Flow or Art. Lift)		Prod. Medium (Tbg. Or Csg.)
Upper Completion	Pictue cliff	0	gas		Flow		7B3
LOWCI	mest verde	-	395		Flow Plonge		TBS
		Pre	e-Flow Shut-In P	ressure Dat	Ŭ		•
Completion	Hour, Date, Shut-	In	Length of Time	SI Press. Psig		Stabilized? (Yes or No)	
Lower Completion	Hour, Date, Shut-	In	Length of Time	SI Press. Psig		Stabilized? (Yes or No)	
			Flow Test N	No. 1			
Commenced	at (hour, date)* 2	20 0			g (Upper or Lo	ower):	Lower
Time (Hour, Date)	Lapsed Time Since*	<u>Pre</u> Upper Compl.	<u>ssure</u> Lower Compl.	Prod. Zo Temp	1	CS	
235 919	15m12	55	34		noc	chan	e in Oppor
			•			••	RCVD SEP 19'14
							OIL CONS. DIV.
							DIST. 3
		•					
Production rat	e during test	<u> </u>					
Oil:	BOPD based o	nBb	ls. In	Hrs	Grav		GOR
Gas: 23	MCFP MCFP	D; Test thru (Orit	fice or Meter):1	nete			
	·	M	id-Test Shut-In I	Pressure Da	ta		
Upper Completion	Hour, Date, Shut-In		Length of Time Shut-In		SI Press. Psig		Stabilized? (Yes or No)
Lower	Hour, Date, Shut-In		Length of Time	SI Press. Psig		Stabilized? (Yes or No)	

(Continue on reverse side)

Flow Test No. 2

Commenced a	t (hour, date)**			Zone producing (Upper or Lower):							
Time	Lapsed Time	<u>Pre</u>	essure	Prod. Z	Cone	Remarks					
(Hour, Date)	Since**	Upper Compl.	Lower Comp	l. Tem	p						
						,					
											
			}								
		3		1							
:											
Production rate during test											
Oil: BOPD based on Bbls. In Hrs. Grav. GOR Gas: MCFPD; Test thru (Orifice or Meter):											
Gas: MCFPD; Test thru (Orifice or Meter): Remarks:											
icinairs.	•			a							
I hereby certify	that the informa	tion herein contai	ined is true and	l complete to th	ie best	of my knowledge.	,				
Annewad		J.L.	20 16	0		House					
New Mexico C	Oil Conservation	Division	<u> </u>	Opera	Operator Cricovore						
Trew Michieo C	on conscivation i	1		By	By Randy Calcote						
. //											
By	A Ky	// (Title	Operator Ctleuron By Randy Calcote Title Calder Service						
Title <u>np</u>	IITY NI L g	GAS INSPES	<u> </u>	E-ma	E-mail Address Randy . Cocaldorsen						
_ • •	DISTRI		A C 1	Date	Date 9-9-14						
*			st New Mexico Pac	ker Leakage Test I							

- Northwest New Mexico Packer Leakage Test Instructions
- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shal remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests immediately prior to the beginning of each flow-period, at fifteen-minut intervals during the first hour thereof, and at hourly intervals thereafter including one pressure measurement immediately prior to the beginnin of each flow period, at least one time during each flow period (a approximately the midway point) and immediately prior to the conclusio of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).